



Public REST API Developer's Guide

Revision dated 04.09.2024

Table of Contents

1.	Overview	5
2.	Common REST API	6
2.1.	Authentication/Authorization	6
2.2.	Departments	9
2.2.1.	Get list of Departments	10
2.2.2.	Get Department by ID	12
2.2.3.	Add new Department	13
2.2.4.	Edit Department	14
2.2.5.	Delete Department	15
2.2.6.	Create multiple departments at a time	16
2.2.7.	Edit multiple departments at a time	18
2.2.8.	Delete multiple departments at a time	20
2.2.9.	Count departments	21
2.3.	Positions	22
2.3.1.	Get list of Positions	23
2.3.2.	Get Position by ID	25
2.3.3.	Add new Position	26
2.3.4.	Edit Position	27
2.3.5.	Delete Position	28
2.3.6.	Create multiple positions at a time	29
2.3.7.	Update multiple positions at a time	31
2.3.8.	Delete multiple positions at a time	33
2.4.	Cards	34
2.4.1.	Overview	35
2.4.2.	Get list of Cards	36
2.4.3.	Get Card by ID	38
2.4.4.	Add new Card	39
2.4.5.	Edit Card	41
2.4.6.	Delete Card	42
2.4.7.	Create multiple cards at a time	43
2.4.8.	Update multiple cards at a time	45
2.4.9.	Delete multiple cards at a time	47
2.5.	Employees	48
2.5.1.	Get list of Employees	49
2.5.2.	Get Employee by ID	53
2.5.3.	Add new Employee	55
2.5.4.	Edit Employee	57
2.5.5.	Delete Employee	60
2.5.6.	Block employee	62
2.5.7.	Unblock employee	63
2.5.8.	Bulk operations	64
2.5.9.	Count Employees	73
2.5.10.	Deprecated: Employees Vehicles	75
2.6.	Official Vehicles	78
2.6.1.	Get list of Official vehicles	79
2.6.2.	Get Official vehicle by ID	81

2.6.3.	Add new Official vehicle	82
2.6.4.	Edit Official vehicle	83
2.6.5.	Delete Official vehicle	84
2.6.6.	Create multiple official vehicles at a time	85
2.6.7.	Update multiple official vehicles at a time	87
2.6.8.	Delete multiple official vehicles at a time	89
2.7.	Bindings	90
2.7.1.	Employees-Cards	91
2.7.2.	Employees-Access Rules	97
2.7.3.	Employees-Access Points	101
2.7.4.	Official Vehicles-Cards	104
2.7.5.	Official Vehicles-Access Rules	109
2.7.6.	Official Vehicles-Access Points	113
2.7.7.	Access Rules-Access Points	116
2.8.	Access Rules	120
2.8.1.	Get list of Access Rules	121
2.8.2.	Get Access Rule by ID	124
2.8.3.	Create Access Rule	125
2.8.4.	Update Access Rule	127
2.8.5.	Delete Access Rule	129
2.8.6.	Count Access Rules	130
2.8.7.	Get all folders of Access Rules	132
2.9.	Access Points	134
2.9.1.	Get list of Access Points	135
2.9.2.	Get Access Point by ID	137
2.9.3.	Get all folders of Access Points	138
2.9.4.	Count Access Points	140
2.10.	Users	141
2.10.1.	Get all users	142
2.10.2.	Get user by ID	144
2.10.3.	Create user from an existing employee	145
2.10.4.	Update user	146
2.10.5.	Delete user	148
2.11.	Zones	149
2.11.1.	Get list of Zones	150
2.11.2.	Get Zone by ID	152
2.12.	Custom Fields	153
2.12.1.	Overview	154
2.12.2.	Get list of Custom Fields	155
2.12.3.	Add new Custom Field	157
2.12.4.	Edit Custom Field	159
2.12.5.	Delete Custom Field	160
2.13.	Events	161
2.13.1.	Get list of event types	162
2.13.2.	Get list of Events	164
2.13.3.	Get all parsed events	166
3.	Response Error Codes	179
3.1.	400 Invalid Request	179
3.2.	401 Unauthorized	179

- 3.3. 403 Forbidden 179
- 3.4. 404 Not Found 179
- 3.5. 422 Unprocessable Entity 179
- 3.6. 500 Internal Server Error 180

1. Overview

This guide describes the public REST API of SIGUR ACS with request/response descriptions and examples.

REST APIs are available at *HTTP://<SIGUR Server IP address>:9500/api/v1/<endpoint>*.

Swagger's specifications ([OAS¹](#)) are available at *HTTP://<SIGUR Server IP address>:9500/swagger*.

Any entry "<custom field>:<Field type>" implies the use of custom fields.

This guide contains information accorded with the software version 1.6.3.14.

2. Common REST API

2.1. Authentication/Authorization

Session key (JWT token) is required for accessing Public REST API. It must be present in authorization header. The key is valid for one hour. Once it expires, the new key must be generated. There is a limit of how many session keys can be active at a time. If this limit is reached, the oldest session key is revoked and cannot be used anymore.

URL Endpoint	/api/v1/users/auth
Method	POST
Header Parameters	Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "username": "string", "password": "string" }</pre> Required fields: - username - system user's login - password - system user's password
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "token": "string", "refreshToken": "string", "expiresAt": "2023-12-03T13:29:50.590Z", "refreshExpiresAt": "2023-12-03T13:29:50.590Z" }</pre>
Error Response	401 (Unauthorized) 403 (Forbidden) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/users/auth -H 'Content-Type: application/json' -d '{"username": "username", "password": "password"}</pre> <u>Response:</u> <pre>{ "token": "eyJhbGciOiJSUz...", "refreshToken": "eyJhbGciOiJSUz...", "expiresAt": "2023-12-03T17:38:59.931748+03:00", "refreshExpiresAt": "2023-12-04T16:39:00.1471714+03:00" }</pre>

Refresh JWT Access Token

URL Endpoint	/api/v1/jwt/refresh
Method	POST
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	
Body	"string"
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "token": "string", "refreshToken": "string", "expiresAt": "2023-12-03T18:08:10.737Z", "refreshExpiresAt": "2023-12-03T18:08:10.737Z" }</pre>
Error Response	<u>400 (Invalid Request)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://localhost:9500/api/v1/jwt/refresh -H 'Authorization: Bearer eyJhbGciOiJSUzI...'' -d 'eyJhbGciOiJSUzI...' <u>Response:</u> <pre>{ "token": "eyJhbGciOiJSUzI...", "refreshToken": "eyJhbGciOiJSUzI...", "expiresAt": "2023-12-03T17:38:59.931748+03:00", "refreshExpiresAt": "2023-12-04T16:39:00.1471714+03:00" }</pre>

This endpoint is deprecated. Use `api/v1/users/auth` instead.

URL Endpoint	api/v1/application-keys/auth
Method	POST
Header Parameters	Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "system": <String>, "password": <String> }</pre> Required fields: - system - system user's login - password - system user's password
Success Response	Status code: 200 Content-type: application/json Body: <Session key>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/application-keys/auth -H "Content-Type: application/json" -d 'ahe5aNJ...'</pre> <u>Response:</u> <pre>eyJraWQiOiJh...</pre>

2.2. Departments

- [Get list of Departments](#)
- [Get Department by ID](#)
- [Add new Department](#)
- [Edit Department](#)
- [Delete Department](#)
- [Create multiple departments at a time](#)
- [Edit multiple departments at a time](#)
- [Delete multiple departments at a time](#)
- [Count departments](#)

2.2.1. Get list of Departments

URL Endpoint	api/v1/departments
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Department(s) - returns only records with specified identifiers (e.g. api/v1/departments?id=1,2 or api/v1/departments? id=1&id=2) parentId - identifier of a parent department. If you want to get only root departments then use parentId=0 (e.g. api/v1/departments?parentId=1) name - filter by department name (e.g. api/v1/departments?name=Warehouse) limit - specifies how many entities the response should contain (e.g. api/v1/departments?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/departments?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 <any custom field> - e.g. custom field externalId has been created (e.g. api/v1/departments?externalId=135) includeFields - specifies what fields the response should contain (e.g. api/v1/departments?includeFields=name,parentId - only fields name and parentId are returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/departments?excludeFields=name - all fields besides name are returned in the response) sortBy - specifies sort field (e.g. api/v1/departments?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/departments?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "parentId": <Number>, "name": <String>, "hasChildren": <boolean>, "description": <String>, "<custom field>": <Field type>, ... }, ...]</pre>

Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Access denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/departments -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "id":1, "parentId": 0, "name":"Head Department", "hasChildren": true, "description": "Main", "externalId": 135 }, { "id":2, "parentId":1, "name":"R&D", "hasChidren": false, "externalId": 136 }]</pre>

2.2.3. Add new Department

URL Endpoint	api/v1/departments
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }</pre> Required fields: name If "parentId" is not specified then high level department is assigned (root department).
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "parentId": <Number>, "name": <String>, "Description": <String>, "<custom field>": <Field type> ... }</pre>
Error Response	400 (Invalid Request) 401 (Unauthorized) 403 (Access denied) 404 (Parent department is not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/departments -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm" -d {'name':"Test department ","parentId":1,"externalId":135}'</pre> <u>Response:</u> <pre>{ "id":3, "parentId":1, "name":"Test department", "externalId":135 }</pre>

2.2.4. Edit Department

URL Endpoint	api/v1/departments/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of Department to be edited
Query Parameters	
Body	<pre>{ "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }</pre> Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "parentId": <Number>, "name": <String>, "hasChildren": <Boolean>, "description": <String>, "<custom field>": <Field type> ... }</pre>
Error Response	400 (Invalid Request) 401 (Unauthorized) 403 (Permission denied) 404 (Department with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/departments/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm" -d '{"name":"Test updated department ","parentId":1}'</pre> <u>Response:</u> <pre>{ "id":3, "parentId":1, "name":"Test updated department", "hasChildren": false }</pre>

2.2.5. Delete Department

Deletes department with specified identifier and returns deleted entity.

Department can't be deleted if contains assigned employees or vehicles (recursively). So all assigned entities should be unassigned first.

URL Endpoint	api/v1/departments/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of Department to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "parentId": <Number>, "name": <String>, "hasChildren": <Boolean>, "description": <String>, "<custom field>": <Field type> ... }</pre> Department won't be deleted if it contains child departments.
Error Response	400 (Invalid Request) 401 (Unauthorized) 403 (Permission denied) 404 (Department with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/departments/3 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm"</pre> <u>Response:</u> <pre>{ "id":3, "parentId":1, "name":"Test updated department" }</pre>

2.2.6. Create multiple departments at a time

URL Endpoint	api/v1/departments/create
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }, { "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }, ...]</pre> Required fields: name If "parentId" is not specified then high level department is assigned (root department).
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "parentId": <Number>, "description": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "name": <String>, "parentId": <Number>, "description": <String>, "<custom field>": <Field type>, ... }, ...]</pre>

Error Response	<u>400 (Invalid Request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/departments/create -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '[{ "name": "Test department ", "parentId": 1, "externalId ":135}, { "name": "Test department 1 ", "parentId": 2, "externalId ":136}]'</pre> <u>Response:</u> <pre>[{ "id": 3, "parentId": 1, "name": "Test department", "externalId": 135 }, { "id": 4, "parentId": 2, "name": "Test department 1", "externalId ": 136 }]</pre>

2.2.7. Edit multiple departments at a time

URL Endpoint	api/v1/departments/update
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "id": <Number>, "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }, { "id": <Number>, "parentId": <Number>, "name": <String>, "description": <String>, "<custom field>": <Field type> ... }, ...]</pre> Required fields: id Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "parentId": <Number>, "name": <String>, "hasChildren": <boolean>, "description": <String>, "<custom field>": <Field type> ... }, { "id": <Number>, "parentId": <Number>, "name": <String>, "hasChildren": <boolean>, "description": <String>, "<custom field>": <Field type> ... }, ...]</pre>

Error Response	<u>400 (Invalid Request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/departments/update -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"id":3,"name":"Test department updated"},"id":4, "name":"Test department 1 updated"}]'</pre> <u>Response:</u> <pre>[{ "id": 3, "parentId": 1, "name": "Test department updated", "hasChildren": false, "description": "desc1" }, { "id": 4, "parentId": 2, "name": "Test department 1 updated", "hasChildren": false, "description": "desc2" }]</pre>

2.2.9. Count departments

URL Endpoint	api/v1/departments/count
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Department(s) - returns only records with specified identifiers (e.g. api/v1/departments/count?id=1,2 or api/v1/departments/count? id=1 &id=2) parentId - identifier of parent department. If you want to get only root departments then use parentId=0 (e.g. api/v1/departments/count?parentId=1) name - filter by department name (e.g. api/v1/departments/count?name=Warehouse) isRecursive - whether to count departments recursively or not (e.g. api/v1/departments/count?isRecursive=true)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[<Number>]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Access denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/departments/count -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y1lljoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[8]</pre>

2.3. Positions

- [Get list of Positions](#)
- [Get Position by ID](#)
- [Add new Position](#)
- [Edit Position](#)
- [Delete Position](#)
- [Create multiple positions at a time](#)
- [Update multiple positions at a time](#)
- [Delete multiple positions at a time](#)

2.3.1. Get list of Positions

URL Endpoint	api/v1/positions
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Position(s) - returns only records with specified identifiers (e.g. api/v1/positions?id=1,2 or api/v1/positions?id=1&id=2) name - filter by position name (e.g. api/v1/positions?name=Developer) limit - specifies how many entities the response should contain (e.g. api/v1/positions?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/positions?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 <any custom field> - e.g. custom field externalId has been created (e.g. api/v1/positions?externalId=135) includeFields - specifies what fields the response should contain (e.g. api/v1/positions?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/positions?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/positions?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/positions?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/positions -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "id":1, "name":"Head of Department" }, { "id":2, "name":"Designer" }]</pre>
----------------	---

2.3.2. Get Position by ID

URL Endpoint	api/v1/positions/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Position
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/positions/1?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/positions/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Position with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/positions/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitlcm" <u>Response:</u></pre> <pre>{ "id":2, "name":"Designer" }</pre>

2.3.3. Add new Position

URL Endpoint	api/v1/positions
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "<custom field>": <Field type>, ... }</pre> Required fields: name
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/positions -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d {"name":"Developer"}</pre> <u>Response:</u> <pre>{ "id":3, "name":"Developer" }</pre>

2.3.4. Edit Position

URL Endpoint	api/v1/positions/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of Position to be edited
Query Parameters	
Body	<pre>{ "name": <String>, "<custom field>": <Field type>, ... }</pre> Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Position with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/positions/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"name":"Team Lead"}'</pre> <u>Response:</u> <pre>{ "id":3, "name":"Team Lead" }</pre>

2.3.5. Delete Position

Position can be deleted only if it is not assigned to any employee. So a deleted position should be unassigned first.

URL Endpoint	api/v1/positions/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Position to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Position with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/positions/3 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm"</pre> <u>Response:</u> <pre>{ "id":3, "name":"Team Lead" }</pre>

2.3.6. Create multiple positions at a time

URL Endpoint	api/v1/positions/create
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "name": <String>, "<custom field>": <Field type>, ... }, { "name": <String>, "<custom field>": <Field type>, ... } ...]</pre> Required fields: name
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... } ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/positions/create -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{ "name": "HR"}, { "name": "DevOps"}]'</pre> <u>Response:</u> <pre>[{ "id": 4, "name": "HR" }, { "id": 5, "name": "DevOps" }]</pre>
---------	---

2.3.7. Update multiple positions at a time

URL Endpoint	api/v1/positions/update
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... } ...]</pre> Required fields: id Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "name": <String>, "<custom field>": <Field type>, ... } ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (not found) 422 (Validation Error) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/positions/update -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{ "id": 4, "name": "Head of HR"}, { "id": 5, "name": "System Administrator"}]'</pre> <u>Response:</u> <pre>[{ "id": 4, "name": "Head of HR" }, { "id": 5, "name": "System Administrator" }]</pre>
---------	---

2.3.8. Delete multiple positions at a time

URL Endpoint	api/v1/positions/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number>] Body contains ids of positions that should be deleted.
Success Response	Status code: 200 Content-type: application/json Body: [<Number>, <Number>] Body contains ids of deleted positions.
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://localhost:9500/api/v1/positions/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[4, 5]' <u>Response:</u> [4, 5]

2.4. Cards

- [Overview](#)
- [Get list of Cards](#)
- [Get Card by ID](#)
- [Add new Card](#)
- [Delete Card](#)
- [Edit Card](#)
- [Create multiple cards at a time](#)
- [Update multiple cards at a time](#)
- [Delete multiple cards at a time](#)

2.4.1. Overview

Public REST API for dealing with cards provides an ability to have a cards dictionary with the following formats:

- **UID** - allows to specify UID as card value in raw format. It allows to assign this card in different hardware (wiegand) formats using a specific algorithm. The algorithm is - take the needed number of bytes from the beginning (if there are not enough bytes provided, then fill with zeros before provided bytes) and reverse it.
Example:

- value - AABBCCDDEE
format - **W26** => value to assign - CCBBA
format - **W34** => value to assign - DDCCBBAA
- value - AABBB
format - **W26** => value to assign - BBAA00
format - **W34** => value to assign - BBAA0000

- **MEMORY** - allows to provide a memory block that can be used for assigning this card in different formats. The algorithm is - take the needed number of bytes from the beginning
Example:

- value - AABBCCDDEE
format - **W26** => value to assign - AABBC
format - **W34** => value to assign - AABBCDD

- Specific wiegand format (**W26, W34, W36, W37, W42, W58DEC, W58**) - just perceives the value as ready to assign.



"Cards" endpoints are not designed to work with visitor QR-codes.

2.4.2. Get list of Cards

URL Endpoint	api/v1/cards
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Card(s) - returns only records with specified identifiers (e.g. api/v1/cards?id=1,2 or api/v1/cards?id=1&id=2) issued - if true returns only those cards that have holder, otherwise - free cards (e.g. api/v1/cards?issued=true) name - filter by card's name with condition 'starts with' (e.g. api/v1/cards?name=Card1) value - filter by card's value with condition 'starts with' (e.g. api/v1/cards?value=AABBCC) search - filter by card's name or value or wiegand codekey (e.g. api/v1/cards?search=18AABBCC - search by codekey) guestApplicable - specifies what kind of cards should be returned. "True" means guest cards. By default, all cards are returned (e.g. api/v1/cards?guestApplicable=true - only guest applicable cards would be returned) <any custom field> e.g. custom field "holderName" has been created (e.g. api/v1/cards?holderName=135) excludeLegacyGuests - If true, cards issued to legacy guests are not taken into account (e.g. api/v1/cards?excludeLegacyGuests=true) limit - specifies how many entities the response should contain (e.g. api/v1/cards?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/cards?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/cards?includeFields=value - only field value is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/cards?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/cards?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/cards?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order)
Body	

Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "holder": <{Holder object}>, "guestApplicable": <Boolean>, "<custom field>": <Field type> }, ...]</pre> Field "value" contains HEX string of card's identifier where every 2 characters represent a hexadecimal number of 1 byte of a card identifier.
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/cards -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiYm9keWVlcnRlcilsm"</pre> <u>Response:</u> <pre>[{ "id": 1, "name": "Card 1", "value": "AABBCCDD", "formattedValue": "170,48076", "format": "W26", "holder": { "holderId": 10, "type": "EMP" }, "guestApplicable": false }]</pre>

2.4.3. Get Card by ID

URL Endpoint	api/v1/cards/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - unique ID of Card
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/cards/1?includeFields=value - only field value is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/cards/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String> "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "holder": <{Holder object}>, "guestApplicable": <Boolean>, "<custom field>": <Field type> }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Card with specified id not found) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/cards/1 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm"</pre> <u>Response:</u> <pre>{ "id":1, "name":"Card 1", "value":"AABBCDD", "formattedValue": "170,48076", "format": "W26", "holder":{ "holderId":10, "type":"EMP" }, "guestApplicable": false }</pre>

2.4.4. Add new Card

URL Endpoint	api/v1/cards
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "value": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> }</pre> Required fields: • value • format Field "value" contains HEX string of card's identifier where every 2 characters represent a hexadecimal number of 1 byte of a card identifier.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> }</pre>
Error Response	400 (Invalid Request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '{"name": "Card 1", "value": "ABCCDDEE", "format": "W26"}'</pre> <u>Response:</u> <pre>{ "id": 2, "name": "Card 1", "value": "ABCCDDEE", "formattedValue": "170,48076", "format": "W26", "guestApplicable": false }</pre>
-----------------------	---

2.4.5. Edit Card

URL Endpoint	api/v1/cards/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - unique ID of Card
Query Parameters	
Body	<pre>{ "id": 0, "name": "string", "value": "string", "formattedValue": "string", "format": "UID", "holder": { "holderId": 0, "type": "EMP" }, "guestApplicable": true, "mfUid": "string" }</pre> Body contains fields that should be modified. It is possible to update card's name and custom fields.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "name": <String>, "<custom field>": <Field type> }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Card with specified id not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/cards/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d {'name': "Card 2"}</pre> <u>Response:</u> <pre>{ "id": 2, "name": "Card 2", "value": "ABCCDDEE", "formattedValue": "170,48076", "format": "W26", "guestApplicable": false }</pre>

2.4.6. Delete Card

URL Endpoint	api/v1/cards/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - unique ID of Card
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "value": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "formattedValue": <String>, "guestApplicable": <Boolean>, "custom field>": <Field type> }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Card with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/cards/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm"</pre> <u>Response:</u> <pre>{ "id":2, "name":"Card 1", "value ":"ABCCDDEE", "formattedValue": "170,48076", "format": "W26", "guestApplicable": false }</pre>

2.4.7. Create multiple cards at a time

URL Endpoint	api/v1/cards/create
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "name": <String>, "value": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... }, { "name": <String>, "value": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... } ...]</pre> Required fields: • valueformat Field "value" contains HEX string of card's identifier where every 2 characters represent a hexadecimal number of 1 byte of a card identifier.

Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... }, { "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... } ...]</pre>
Error Response	400 (Invalid Request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/cards/create -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzlm" -d '[{ "name": "Card 1", "value": "ABCCDDEE", "format": "W26"}, { "name": "Card 2", "value": "ABCCDDFF", "format": "W26"}]'</pre> <u>Response:</u> <pre>[{ "id": 1, "name": "Card 1", "value": "ABCCDDEE", "formattedValue": "170,48076", "format": "W26", "guestApplicable": false }, { "id": 2, "name": "Card 2", "value": "ABCCDDFF", "formattedValue": "171,52445", "format": "W26", "guestApplicable": false }]</pre>

2.4.8. Update multiple cards at a time

URL Endpoint	api/v1/cards/update
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "id": <Number>, "name": <String>, "<custom field>": <Field type> ... }, { "id": <Number>, "name": <String>, "<custom field>": <Field type> ... } ...]</pre> Required fields: id Body contains fields that should be changed. It is possible to update a card name and custom fields. If you send "name":"" in the body of the request, the card name will be deleted (it will become an empty string). If you send "name": null, the card name will not be changed.
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... }, { "id": <Number>, "name": <String>, "value": <String>, "formattedValue": <String>, "format": <Enum: [UID, MEMORY, W26, W34, W36, W37, W42, W58, W58DEC]>, "guestApplicable": <Boolean>, "<custom field>": <Field type> ... } ...]</pre>

Error Response	<u>400 (Invalid Request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/cards/update -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '[{ "id":1,"name":"Card 1 updated"},{ "id":2,"name":"Card 2 updated"}]'</pre> <u>Response:</u> <pre>[{ "id": 1, "name": "Card 1 updated", "value ": "ABCCDDDEE", "formattedValue": "170,48076", "format": "W26", "guestApplicable": false }, { "id": 2, "name": "Card 2 updated", "value ": "ABCCDDFF", "formattedValue": "171,52445", "format": "W26", "guestApplicable": false }]</pre>

2.4.9. Delete multiple cards at a time

URL Endpoint	api/v1/cards/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number>] Body contains ids of cards that should be deleted.
Success Response	Status code: 200 Content-type: application/json Body: [<Number>, <Number>] Body contains ids of deleted cards.
Error Response	<u>400 (Invalid Request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://localhost:9500/api/v1/cards/delete -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[1, 2]' <u>Response:</u> [1, 2]

2.5. Employees

- [Get list of Employees](#)
- [Get Employee by ID](#)
- [Add new Employee](#)
- [Edit Employee](#)
- [Delete Employee](#)
- [Block employee](#)
- [Unblock employee](#)
- [Bulk operations](#)
 - Create multiple employees at a time
 - Update multiple employees at a time
 - Delete multiple employees at a time
 - Block multiple employees at a time
 - Unblock multiple employees at a time
- [Employees Vehicles](#)
 - Add new Employee Vehicle
 - Edit Employee vehicle
 - Delete Employee vehicle
- [Count employees](#)

2.5.1. Get list of Employees

Returns list of employees according to user's permissions.

URL Endpoint	api/v1/employees
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	

Query Parameters	id - identifier(s) of Employee(s) - returns only records with specified identifiers (e.g. api/v1/employees?id=1,2 or api/v1/employees?id=1&id=2) departmentId - filter by department identifiers. If you want to get employees that don't have assignment with departments then use departmentId=0. You can specify multiple ids. positionId - filter by position identifiers. You can specify multiple ids (e.g. api/v1/employees?positionId=2, api/v1/employees?positionId=0,1,2) name - filter by employee's name with condition «starts with» for firstName, lastName, middleName at the same time (e.g. api/v1/employees?name=Jack) blocked - specifies whether to return only blocked/unblocked employees (e.g. api/v1/employees?blocked=true) tabId[operation] - Filter by tab id. Possible values for "operation" are: EQ - exact match, STARTS_WITH - starts with. EQ is used if none specified (e.g. api/v1/employees?tabId%5BSTARTS_WITH%5D=4533454) limit - specifies how many entities the response should contain (e.g. api/v1/employees?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/employees?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 sortBy - specifies sort field (e.g. api/v1/employees?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/employees?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order) <any custom field> - e.g. custom field externalId has been created (e.g. api/v1/employees?externalId=135) includeFields - specifies what fields the response should contain (e.g. api/v1/employees?includeFields=firstName,lastName - only fields firstName, lastName are returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/employees?excludeFields=id - all fields besides id are returned in the response) For example, api/v1/employees?includeFields=name means that the response will be the following: <pre>[{ "name": <String> }]</pre>
Body	

Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "vehicles": [{ "id": <Number>, "lpNumber": <String>, "<custom field>": <Field type>, ... }, ...], "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId":<String>, "location": { "zoneId": <Number>, "zoneName": <String>, "entranceTime": <DateTime> } }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/employees -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id": 1, "name": "Jack Noname", "departmentId": 2, "departmentName": "R&D", "positionId": 8, "positionName": "Developer", "vehicles": [{ "id": 1, "lpNumber": "d849kp" }], "photo": "/9j/4AAQSkZJRgABA...", "birthDate": "2000-03-15", "contactDetails": [{ "type": "TELEGRAM", "value": "@telegramUsername", "preferable": true }], "isBlocked": false }]</pre>
-----------------------	---

2.5.2. Get Employee by ID

Returns employee with a specified ID according to user's permissions.

URL Endpoint	api/v1/employees/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Employee
Query Parameters	withFullPhoto - specifies whether response should contain full employee's photo includeFields - specifies what fields the response should contain (e.g. api/v1/employees/1?includeFields=firstName,lastName - only fields firstName, lastName are returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/employees/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "vehicles": [{ "id": <Number>, "lpNumber": <String>, "<custom field>": <Field type>, ... }, ...], "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean> }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Employee with specified id not found)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/employees/1 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm</pre> <u>Response:</u> <pre>{ "id": 1, "name": "Jack Noname", "departmentId": 2, "departmentName": "R&D", "positionId": 8, "positionName": "Developer", "vehicles": [{ "id": 1, "lpNumber": "d849kp" }], "photo": "/9j/4AAQSkZJRgABA...", "birthDate": "2000-03-15", "contactDetails": [{ "type": "TELEGRAM", "value": "@telegramUsername", "preferable": true }], "isBlocked": false }</pre>
---------	---

2.5.3. Add new Employee

URL Endpoint	api/v1/employees
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "description": <String>, "tabId": <String> }</pre> Required fields: ▪ name ▪ departmentId
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId": <String> }</pre>

Error Response	401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	Request: curl -X POST http://192.168.0.108:9500/api/v1/employees -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm" -d '{"name":"Tom Taylor","departmentId":3,"positionId":9,"birthDate":"1998-03-12"}' Response: { "id": 2, "name": "Tom Taylor", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 9, "positionName": "QA", "photo": "/9j/4AAQSkZJRgABA...", "isBlocked": false, "birthDate": "1998-03-12" }

2.5.4. Edit Employee

URL Endpoint	api/v1/employees/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of an employee to be edited
Query Parameters	
Body	<pre>{ "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "description": <String>, "tabId": <String> }</pre> Body contains fields that should be modified.

Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "vehicles": [{ "id": <Number>, "lpNumber": <String>, "<custom field>": <Field type>, ... }, ...], "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId": <String>, "location": { "zoneId": <Number>, "zoneName": <String>, "entranceTime": <String> } }</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Employee with specified id not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/employees/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d {"name":"Tomas Taylor"}</pre> <u>Response:</u> <pre>{ "id": 2, "name": "Tomas Taylor", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 9, "positionName": "QA", "photo": "/9j/4AAQSkZJRgABA...", "isBlocked": false, "birthDate": "1998-03-12" }</pre>
---------	---

2.5.5. Delete Employee

URL Endpoint	api/v1/employees/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of an employee to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "vehicles": [{ "id": <Number>, "lpNumber": <String>, "<custom field>": <Field type>, ... }, ...], "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId": <String>, "location": { "zoneId": <Number>, "zoneName": <String>, "entranceTime": <String> } }</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Employee with specified id not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/employees/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm"</pre> <u>Response:</u> <pre>{ "id": 2, "name": "Tomas Taylor", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 9, "positionName": "QA", "photo": "/9j/4AAQSkZJRgABA...", "isBlocked": false, "birthDate": "1998-03-12" }</pre>
----------------	---

2.5.6. Block employee

URL Endpoint	api/v1/employees/{id}/block
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of an employee to be blocked
Query Parameters	
Body	
Success Response	Status code: 204 No content
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Employee with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X PUT http://192.168.0.108:9500/api/v1/employees/2/block -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitlcm" <u>Response:</u> 204 No content

2.5.7. Unblock employee

URL Endpoint	api/v1/employees/{id}/unlock
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of an employee to be unblocked
Query Parameters	
Body	
Success Response	Status code: 204 No content
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Employee with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X PUT http://192.168.0.108:9500/api/v1/employees/2/unlock -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitlcm"
	<u>Response:</u> 204 No content

2.5.8. Bulk operations

Create multiple employees at a time

URL Endpoint	api/v1/employees/create
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "description": <String>, "tabId":<String> } ...]</pre> Required fields: ▪ name ▪ departmentId

Success Response	Status code: 200 Content-type: application/json Body: [{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ... "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId":<String> }]
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/employees/create -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '{"name":"Tom Taylor","departmentId":3,"positionId":9,"birthDate":"1998-03-12 "},"name":"David Lynch","departmentId":3,"positionId":10,"birthDate":"1946-01-20 "}'</pre> <u>Response:</u> <pre>[{ "id": 99, "name": "Tom Taylor", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 9, "positionName": "QA", "isBlocked": false, "birthDate": "1998-03-12" }, { "id": 100, "name": "David Lynch", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 10, "positionName": "HW Developer", "isBlocked": false, "birthDate": "1946-01-20" }]</pre>
-----------------------	---

Update multiple employees at a time

URL Endpoint	api/v1/employees/update
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "description": <String>, "tabId":<String> }, ...]</pre> Required fields: • id Body contains only those fields that should be modified.

Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "departmentId": <Number>, "departmentName": <String>, "positionId": <Number>, "positionName": <String>, "photo": <String>, "<custom field>": <Field type>, ..., "vehicles": [{ "id": <Number>, "lpNumber": <String>, "<custom field>": <Field type>, ... }, ...], "contactDetails": [{ "type": <Enum: [SMS, VIBER, TELEGRAM, EMAIL]>, "value": <String>, "preferable": <Boolean> }, ...], "isBlocked": <Boolean>, "description": <String>, "tabId": <String>, "location": { "zoneId": <Number>, "zoneName": <String>, "entranceTime": <String> } }]</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/employees/update -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"id":99,"name":"Tomas Taylor"},{"id":100,"name":"David Bowie"}'</pre> <u>Response:</u> <pre>[{ "id": 99, "name": "Tomas Taylor", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 9, "positionName": "QA", "isBlocked": false, "birthDate": "1998-03-12" }, { "id": 100, "name": "David Bowie", "departmentId": 3, "departmentName": "Hardware R&D", "positionId": 10, "positionName": "HW Developer", "isBlocked": false, "birthDate": "1946-01-20" }]</pre>
---------	---

Delete multiple employees at a time

URL Endpoint	api/v1/employees/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number> ...] Body contains ids of employees to be deleted.
Success Response	Status code: 200 Content-type: application/json Body: [<Number>, <Number> ...]
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://192.168.0.108:9500/api/v1/employees/delete -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[99, 100]' <u>Response:</u> [<Number>, <Number> ...]

Block multiple employees at a time

URL Endpoint	api/v1/employees/block
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number> ...] Body contains ids of employees to be blocked.
Success Response	Status code: 204 No content
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://192.168.0.108:9500/api/v1/employees/block -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm" -d '[1, 2]' <u>Response:</u> 204 No content

Unblock multiple employees at a time

URL Endpoint	api/v1/employees/unblock
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number> ...] Body contains ids of employees to be unblocked.
Success Response	Status code: 204 No content
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://192.168.0.108:9500/api/v1/employees/unblock -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[1, 2]' <u>Response:</u> 204 No content

2.5.9. Count Employees

URL Endpoint	api/v1/employees/count
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of employees(s) - returns only records with specified identifiers (e.g. api/v1/employees/count?id=1,2 or api/v1/employees/count?id=1&id=2) departmentId - identifier(s) of department. If you want to get only root departments then use departmentId=0 (e.g. api/v1/employees/count?departmentId=1) positionId - filter by position ids (e.g. api/v1/employees/count?positionId=1) name - filter by employees name (e.g. api/v1/employees/count?name=IvanIvanov) blocked - specifies whether to return only blocked/unblocked employees (e.g. api/v1/employees/count?blocked=true) <custom_field_name> - Filter by custom field with condition 'equals' (e.g. api/v1/employees/count?%3Ccustom_field_name%3E=dr) groupBy - specifies which field to use for grouping. Available values: departmentId, departmentName, positionId, positionName, name (e.g. api/v1/employees/count?groupBy=departmentName) isRecursive - whether to count employees recursively or not (e.g. api/v1/employees/count?isRecursive=true)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "groupByField": <String>, "employeeCount": <Number> }]</pre>
Error Response	401 (Unauthorized) 403 (Access denied) 422 (Validation Error) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/employees/count -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "groupByField": null, "employeeCount": 5 }]</pre>
----------------	---

Edit Employee Vehicle

URL Endpoint	api/v1/employees/{id}/vehicles/{vehicleId}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of an employee vehicleId - identifier of Vehicle to be edited
Query Parameters	
Body	<pre>{ "id": <Number>, "lpNumber ": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... }</pre> Body contains only modified fields.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber ": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 404 (Employee with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/employees/1/vehicles/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '{"lpNumber": "r586po"}'</pre> <u>Response:</u> <pre>{ "id": 3, "lpNumber ": "r586po" }</pre>

Delete Employee Vehicle

URL Endpoint	api/v1/employees/{id}/vehicles/{vehicleId}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of an employee vehicleId - identifier of an employee vehicle to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber ": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 404 (Employee with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/employees/1/vehicles/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm"</pre> <u>Response:</u> <pre>{ "id":3, "lpNumber ":"r586po" }</pre>

2.6. Official Vehicles

- [Get list of Official vehicles](#)
- [Get Official vehicle by ID](#)
- [Add new Official vehicle](#)
- [Edit Official vehicle](#)
- [Delete Official vehicle](#)
- [Create multiple official vehicles at a time](#)
- [Update multiple official vehicles at a time](#)
- [Delete multiple official vehicles at a time](#)

2.6.1. Get list of Official vehicles

URL Endpoint	api/v1/vehicles/official
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Official Vehicles(s). Returns only records with specified identifiers (e.g. api/v1/vehicles/official?id=1,2 or api/v1/vehicles/official?id=1&id=2) departmentId - filter by department identifiers. If you want to get vehicles that don't have assignment with departments then use departmentId=0. You can specify multiple identifiers (e.g. api/v1/vehicles/official?departmentId=2, api/v1/vehicles/official?departmentId=0,1,2) lpNumber - filter by vehicles's license plate number with condition «starts with» (e.g. api/v1/vehicles/official?lpNumber=s123) limit - specifies how many entities the response should contain (e.g. api/v1/vehicles/official?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/vehicles/official?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 <any custom field> - e.g. custom field externalId has been created (e.g. api/v1/vehicles/official?externalId=135) includeFields - specifies what fields the response should contain (e.g. api/v1/vehicles/official?includeFields=lpNumber - only field lpNumber is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/vehicles/official?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/vehicles/official?sortBy=lpNumber - means that entities would be sorted by lpNumber field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/vehicles/official?sortBy=lpNumber&sortOrder=DESC - means that entities would be sorted by lpNumber field in descending order)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }, ...]</pre>

Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/vehicles/official -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm</pre> <u>Response:</u> <pre>[{ "id":1, "departmentId":2, "departmentName": "R&D", "lpNumber":"d156dd" }, { "id":2, "lpNumber":"r884we" }]</pre>

2.6.2. Get Official vehicle by ID

URL Endpoint	api/v1/vehicles/official/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of official vehicle
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/vehicles/official/1?includeFields=lpNumber - only field lpNumber is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/official/vehicles/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Department with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/vehicles/official/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm"</pre> <u>Response:</u> <pre>{ "id":2, "lpNumber":"r884we" }</pre>

2.6.3. Add new Official vehicle

URL Endpoint	api/v1/vehicles/official
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... }</pre> Required fields: lpNumber
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Department with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/vehicles/official -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"lpNumber":"r586po"}'</pre> <u>Response:</u> <pre>{ "id":3, "lpNumber ":"r586po", "departmentId": 0 }</pre>

2.6.4. Edit Official vehicle

URL Endpoint	api/v1/vehicles/official/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of Official vehicle to be edited
Query Parameters	
Body	<pre>{ "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... }</pre> Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Department with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/vehicles/official/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"lpNumber": "r586so"}'</pre> <u>Response:</u> <pre>{ "id": 3, "lpNumber": "r586so", "departmentId": 4, "departmentName": "Служебный транспорт" }</pre>

2.6.5. Delete Official vehicle

URL Endpoint	api/v1/vehicles/official/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Official vehicle to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Department with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/vehicles/official/3 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm"</pre> <u>Response:</u> <pre>{ "id": 3, "lpNumber": "r586so", "departmentId": 4, "departmentName": "Служебный транспорт" }</pre>

2.6.6. Create multiple official vehicles at a time

URL Endpoint	api/v1/vehicles/official/create
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... }, { "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... } ...]</pre> Required fields: lpNumber
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... } ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (not found) 422 (Validation Error) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/vehicles/official/ create -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{ "lpNumber": "a111aa"}, {"lpNumber": "b222bb"}]'</pre> <u>Response:</u> <pre>[{ "id": 4, "lpNumber": "a111aa", "departmentId": 0 }, { "id": 5, "lpNumber": "b222bb", "departmentId": 0 }]</pre>
-----------------------	---

2.6.7. Update multiple official vehicles at a time

URL Endpoint	api/v1/vehicles/official/update
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... }, { "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "<custom field>": <Field type>, ... } ...]</pre> Required fields: • id Body contains fields that should be modified.
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... }, { "id": <Number>, "lpNumber": <String>, "departmentId": <Number>, "departmentName": <String>, "<custom field>": <Field type>, ... } ...]</pre>

Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://localhost:9500/api/v1/vehicles/official/ update -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{ "IpNumber": "a888aa"}, {"IpNumber": "b999bb"}]'</pre> <u>Response:</u> <pre>[{ "id": 4, "IpNumber": "a888aa", "departmentId": 0 }, { "id": 5, "IpNumber": "b999bb", "departmentId": 0 }]</pre>

2.6.8. Delete multiple official vehicles at a time

URL Endpoint	api/v1/vehicles/official/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	[<Number>, <Number>] Body contains ids of official vehicles that should be deleted.
Success Response	Status code: 200 Content-type: application/json Body: [<Number>, <Number>] Body contains ids of deleted official vehicles.
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X POST http://localhost:9500/api/v1/vehicles/official/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitlcm" -d '[4, 5]' <u>Response:</u> [4, 5]

2.7. Bindings

- Employees-Cards
 - Get Employee - Card bindings
 - Assign Cards to Employees
 - Update expiration time for the specified cards assigned to employees
 - Update start and expired time for the specified cards assigned to employees
 - Remove Cards from Employees
- Employees-Access Rules
 - Get Employees Access Rules
 - Assign Access Rules to Employees
 - Remove Access Rules from Employees
- Employees-Access Points
 - Get Employees Access Points
 - Create bindings between employees and access points
 - Delete bindings between employees and access points
- Official Vehicles-Cards
 - Get Official Vehicles Cards
 - Assign Cards to Official Vehicles
 - Remove Cards from Official Vehicles
 - Updates expiration time for the specified cards assigned to official vehicles
- Official Vehicles-Access Rules
 - Get Official Vehicles Access Rules
 - Assign Access Rules to Official Vehicle
 - Remove Access Rules from Official Vehicles
- Official Vehicles-Access Points
 - Get bindings between vehicles and access points
 - Create bindings between vehicles and access points
 - Delete bindings between vehicles and access points
- Access Rules-Access Points
 - Get bindings between Access Rules and Access Points
 - Assign Access Points to Access Rules
 - Unassign Access Points from Access Rules



You cannot assign visitor QR codes to employees or vehicles.

2.7.1. Employees-Cards

Get Employee - Card bindings

URL Endpoint	api/v1/bindings/employees-cards
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	employeeId - identifier(s) of Employee(s) - returns only records with specified identifiers (e.g. api/v1/bindings/employees-cards?employeeId=1,2 or api/v1/bindings/employees-cards?employeeId=1&employeeId=2) cardId - IDs of Card(s) - returns only records with specified identifiers (e.g. api/v1/bindings/employees-cards?cardId=1,2 or api/v1/bindings/employees-cards?cardId=1&cardId=2) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/employees-cards?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/employees-cards?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "employeeId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/employees-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "employeeId": 1, "cardId": 1, "startDate": "2023-12-03T17:57:09.104Z", "expirationDate": "2023-12-03T17:57:09.104Z", "format": "W26" }]</pre>
----------------	---

Assign Cards to Employees

URL Endpoint	api/v1/bindings/employees-cards
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: • employeeId • cardId • format
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{"employeeId":1,"cardId": 2,"format": "W26", "startDate":"2021-03-01 18:00:00","expirationDate":"2021-03-31 18:00:00"}]'</pre> <u>Response:</u> 204 No Content

Update expiration time for the specified cards assigned to employees

URL Endpoint	api/v1/bindings/employees-cards
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId":<Number>, "cardId": <Number>, "startDate":<Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: • employeeId • cardId • expirationDate If "expirationDate" was specified earlier, and now you do not send its value (or send {"expirationDate":null}), then the values of both "startDate" and "expirationDate" become null.
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/bindings/employees-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm" -d '{"employeeId":1, "cardId": 2, "format": "W26", "startDate":"2021-03-01 18:00:00", "expirationDate":"2021-03-31 18:00:00"}'</pre> <u>Response:</u> 204 No Content

Update start and expiration time for the specified cards assigned to employees

URL Endpoint	api/v1/bindings/employees-cards
Method	PATCH
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId":<Number>, "cardId": <Number>, "startDate":<Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: ▪ employeeId ▪ cardId ▪ startDate ▪ expirationDate If you send an empty value of "startDate" or/and "expirationDate", then the value of a parameter becomes null.
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PATCH http://192.168.0.108:9500/api/v1/bindings/employees-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d [{"employeeId":1,"cardId": 2,"format": "W26", "startDate":"2021-03-01 18:00:00","expirationDate":"2021-03-31 18:00:00"}]</pre> <u>Response:</u> 204 No Content

Remove Cards from Employees

URL Endpoint	api/v1/bindings/employees-cards/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: - employeeId - cardId - format
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-cards/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y2lkIjoiaXNlcilzIm" -d '{"employeeId": 1, "cardId": 2, "startDate": "2023-12-03T19:03:22.155Z", "expirationDate": "2023-12-03T19:03:22.155Z", "format": "W26"}'</pre> <u>Response:</u> 204 No Content

2.7.2. Employees-Access Rules

Get Employees Access Rules

URL Endpoint	api/v1/bindings/employees-accessrules
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	employeeId - identifier(s) of Employee(s) - returns only records with specified identifiers (e.g. api/v1/bindings/employees-accessrules?employeeId=1,2 or api/v1/bindings/employees-accessrules?employeeId=1&employeeId=2) accessruleId - IDs of Acces Rule (s) - returns only records with specified identifiers (e.g. api/v1/binding/employees-accessrules?accessrulesId=1,2 or api/v1/bindings/employees-accessrules?accessruleId=1&accessrulesId=2) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/employees-accessrules?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/employees-accessrules?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "employeeId": <Number>, "accessruleId ": <Number> }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/employees-accessrules -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0Y1lljoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "employeeId": 1, "accessRuleId": 1 }, { "employeeId": 1, "accessRuleId": 2 }, { "employeeId": 2, "accessRuleId": 1 }]</pre>
----------------	---

Assign Access Rules to Employees

URL Endpoint	api/v1/bindings/employees-accessrules
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId": <Number>, "accessRuleId ": <Number> }, ...]</pre> Required fields: ▪ employeeId ▪ accessRuleId
Success Response	Status code: 204 No Content
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-accessrules -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '[{ "employeeId":1, "accessRuleId":1}, {"employeeId":2, "accessRuleId":2}]'</pre> <u>Response:</u> 204 No Content

Remove Access Rules from Employees

URL Endpoint	api/v1/bindings/employees-accessrules/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeId": <Number>, "accessruleId": <Number> }, ...]</pre> Required fields: - employeeId - accessruleId
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-accessrules/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d [{"employeeId":1, "accessruleId":1}, {"employeeId":2, "accessruleId":2}]</pre> <u>Response:</u> 204 No Content

2.7.3. Employees-Access Points

Get bindings between employees and access points

URL Endpoint	api/v1/bindings/employees-accesspoints
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	employeeId - identifier(s) of Employee(s) - returns only records with specified identifiers (e.g. api/v1/bindings/employees-accesspoints?employeeId=1,2 or api/v1/bindings/employees-accesspoints?employeeId=1&employeeId=2) accessPointId - identifier(s) of access point(s) - returns only records with specified identifiers (e.g. api/v1/bindings/employees-accesspoints?accessPointId=1) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/employees-accesspoints?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/employees-accesspoints?offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "employeeId": <Number>, "accessPointId": <Number> }, ...]</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/employees-accesspoints -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ"</pre> <u>Response:</u> <pre>[{ "employeeId": 7, "accessPointId": 1 }, { "employeeId": 8, "accessPointId": 2 }]</pre>

Create bindings between employees and access points

URL Endpoint	api/v1/bindings/employees-accesspoints
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeIds": [<Number>], "accessPointIds": [<Number>] }]</pre> Required fields: - employeeIds - accessPointIds
Success Response	Status code: 204 No Content
Error Response	401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-accesspoints -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ" -d '{"employeeIds":[7,8],"accessPointIds":[3]}'</pre> <u>Response:</u> 204 No Content

Delete bindings between employees and access points

URL Endpoint	api/v1/bindings/employees-accesspoints/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "employeeIds": [<Number>], "accessPointIds": [<Number>] }]</pre> Required fields: - employeeIds - accessPointIds
Success Response	Status code: 204 No Content
Error Response	401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/employees-accesspoints/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ" -d '{"employeeIds":[7,8],"accessPointIds":[2,3]}'</pre> <u>Response:</u> 204 No Content

2.7.4. Official Vehicles-Cards

Get Official Vehicles Cards

URL Endpoint	api/v1/bindings/vehicles-cards
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	vehicleId - identifier(s) of Official Vehicle(s) - returns only records with specified identifiers (e.g. api/v1/bindings/vehicles-cards?vehicleId=1,2 or api/v1/bindings/vehicles-cards?vehicleId=1&vehicleId=2) cardId - IDs of Card(s) - returns only records with specified identifiers (e.g. api/v1/bindings/vehicles-cards?cardId=1,2 or api/v1/bindings/vehicles-cards?cardId=1&cardId=2) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/vehicles-cards?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/vehicles-cards?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "vehicleId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/vehicles-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0eXAiOiJKV1QiLCiImlm"</pre> <u>Response:</u> <pre>[{ "vehicleId": 1, "cardId": 1, "startDate": "2023-12-03T21:41:45.384Z", "expirationDate": "2023-12-03T21:41:45.384Z", "format": "W26" }]</pre>
----------------	---

Update expiration time for Cards of Official Vehicles

URL Endpoint	api/v1/bindings/vehicles-cards
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleId":<Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: - vehicleId - cardId - expirationDate
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/bindings/vehicles-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '[{ "vehicleId":1, "cardId": 2, "format": "W26", "startDate": "2023-12-01T21:45:01.520Z", "expirationDate": "2023-12-03T21:45:01.520Z"}]'</pre> <u>Response:</u> 204 No Content

Assign Cards to Official Vehicles

URL Endpoint	api/v1/bindings/vehicles-cards
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: • vehicleId • cardId • format
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-cards -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d '{"vehicleId":1, "cardId": 2, "format": "W26", "startDate": "2023-12-01T21:48:38.836Z", "expirationDate": "2023-12-03T21:48:38.836Z"}'</pre> <u>Response:</u> 204 No Content

Remove Cards from Official Vehicles

URL Endpoint	api/v1/bindings/vehicles-cards/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleId": <Number>, "cardId": <Number>, "startDate": <Date>, "expirationDate": <Date>, "format": <Enum: [W26, W34, W36, W37, W42, W58, W58DEC]> }, ...]</pre> Required fields: - vehicleId - cardId - format
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-cards/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm" -d '[{"vehicleId":1, "cardId": 2, "format": "W26", "startDate": "2023-12-01T21:57:58.357Z", "expirationDate": "2023-12-03T21:57:58.357Z"}]'</pre> <u>Response:</u> 204 No Content

2.7.5. Official Vehicles-Access Rules

Get Official Vehicles Access Rules

URL Endpoint	api/v1/bindings/vehicles-accessrules
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	vehicleId - identifier(s) of Official Vehicle(s) - returns only records with specified identifiers (e.g. api/v1/bindings/vehicles-accessrules?vehicleId=1,2 or api/v1/bindings/vehicles-accessrules?vehicleId=1&vehicleId=2) accessruleId - IDs of Acces Rule (s) - returns only records with specified identifiers (e.g. api/v1/binding/vehicles-accessrules?accessrulesId=1,2 or api/v1/bindings/vehicles-accessrules?accessruleId=1&accessrulesId=2) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/vehicles-accessrules?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/vehicles-accessrules?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "vehicleId": <Number>, "accessruleId ": <Number> }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/vehicles-accessrules -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm"</pre> <u>Response:</u> <pre>[{ "vehicleId": 1, "accessruleId": 1 }, { "vehicleId": 1, "accessruleId": 2 }, { "vehicleId": 2, "accessruleId": 1 }]</pre>
---------	--

Assign Access Rules to Official Vehicle

URL Endpoint	api/v1/bindings/vehicles-accessrules
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleId": <Number>, "accessruleId ": <Number> }, ...]</pre> Required fields: ▪ vehicleId ▪ accessruleId
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-accessrules -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm" -d '{"vehicleId":1, "accessruleId":1}, {"vehicleId":2, "accessruleId":2}]'</pre> <u>Response:</u> 204 No Content

Remove Access Rules from Official Vehicles

URL Endpoint	api/v1/bindings/vehicles-accessrules/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleId": <Number>, "accessruleId ": <Number> }, ...]</pre> Required fields: - vehicleId - accessruleId
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-accessrules/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm"-d '[{ "vehicleId":1, "accessruleId":1}, {"vehicleId":2, "accessruleId":2}]'</pre> <u>Response:</u> 204 No Content

2.7.6. Official Vehicles-Access Points

Get bindings between official vehicles and access points

URL Endpoint	api/v1/bindings/vehicles-accesspoints
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	vehicleIds - identifier(s) of Official Vehicle(s) - returns only records with specified identifiers (e.g. api/v1/bindings/vehicles-accesspoints?vehicleIds=1,2 or api/v1/bindings/vehicles-accesspoints?vehicleIds=1&vehicleIds=2) accessPointId - identifier(s) of access point(s) - returns only records with specified identifiers (e.g. api/v1/bindings/vehicles-accesspoints?accessPointId=1) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/vehicles-accesspoints?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/vehicles-accesspoints?offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "vehicleId": <Number>, "accessPointId": <Number> }, ...]</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/vehicles-accesspoints -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ"</pre> <u>Response:</u> <pre>[{ "vehicleId": 10, "accessPointId": 1 }, { "vehicleId": 10, "accessPointId": 2 }]</pre>

Create bindings between vehicles and access points

URL Endpoint	api/v1/bindings/vehicles-accesspoints
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleIds": [<Number>], "accessPointIds": [<Number>] }]</pre> Required fields: • vehicleIds • accessPointIds
Success Response	Status code: 204 No Content
Error Response	401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-accesspoints -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ" -d '{"vehicleIds":[10],"accessPointIds":[2,3]}'</pre> <u>Response:</u> 204 No Content

Delete bindings between vehicles and access points

URL Endpoint	api/v1/bindings/vehicles-accesspoints/delete
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "vehicleIds": [<Number>], "accessPointIds": [<Number>] }]</pre> Required fields: - vehicleIds - accessPointIds
Success Response	Status code: 204 No Content
Error Response	401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/vehicles-accesspoints/delete -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJ" -d '{"vehicleIds":[10],"accessPointIds":[1]}'</pre> <u>Response:</u> 204 No Content

2.7.7. Access Rules-Access Points

Get bindings between access rules and access points

URL Endpoint	api/v1/bindings/accessrules-accesspoints
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	accessRuleId - identifier(s) of access rule(s) - returns only records with specified identifiers (e.g. api/v1/bindings/accessrules-accesspoints?accessRuleId=6) accessPointId - identifier(s) of access point(s) - returns only records with specified identifiers (e.g. api/v1/bindings/accessrules-accesspoints?accessPointId=1) limit - specifies how many entities the response should contain (e.g. api/v1/bindings/accessrules-accesspoints?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/bindings/accessrules-accesspoints?offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "accessRuleId": <Number>, "accessPointId ": <Number> }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/bindings/accessrules-accesspoints -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "accessRuleId": 6, "accessPointId": 1 }, { "accessRuleId": 4, "accessPointId": 7 },]</pre>
---------	--

Assign access points to access rules

URL Endpoint	api/v1/bindings/accessrules-accesspoints
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>[{ "accessruleId": <Number>, "accesspointId": <Number>, }, ...]</pre> Required fields: - accessruleId - accesspointId
Success Response	Status code: 204 No Content
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/bindings/accessrules-accesspoints -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d [{"accessruleId":6,"accesspointId":2}]</pre> <u>Response:</u> 204 No Content

2.8. Access Rules

- [Get list of Access Rules](#)
- [Get Access Rule by ID](#)
- [Create Access Rule](#)
- [Update Access Rule](#)
- [Delete Access Rule](#)
- [Get all folders of Access Rules](#)
- [Count Access Rules](#)

2.8.1. Get list of Access Rules

URL Endpoint	api/v1/accessrules
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Access Rule(s) - returns only records with specified identifiers (e.g. api/v1/accessrules?id=1,2 or api/v1/accessrules?id=1&id=2) level - filter by rule's level name - filter by access rule name with condition «starts with» (e.g. api/v1/accessrules?name=Rule1) limit - specifies how many entities the response should contain (e.g. api/v1/accessrules?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/accessrules?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/accessrules?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/accessrules?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/accessrules?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/accessrules?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order) deployments - filter by deployment ids (e.g. api/v1/accessrules?deployments=1) folderId - filter by folder id (e.g. api/v1/accessrules?folderId=2) type - filter by rule type. Possible values of are: NORMAL, DOOR (e.g. api/v1/accessrules?type=NORMAL) startDate[operation] - filter by start date of access rule (e.g. api/v1/accessrules?startDate%5Bgte%5D=2023-05-10) endDate[operation] - filter by end date of access rule (e.g. api/v1/accessrules?endDate%5Bgte%5D=2023-05-10) Possible values of "operation" are: • EQ - equal • GT - greater than • LT - less than • GTE - greater than or equal • LTE - less than or equal
Body	

Success Response	Status code: 200 Content-type: application/json Body: [{ "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId":<Number> }, { "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId":<Number> }, ...]
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accessrules -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm</pre> <u>Response:</u> <pre>[{ "id":1, "name":"Default", "description":"Working days since 9:00am till 6:00pm", "startDate": "2021-01-01", "endDate": "2022-01-01", "level": 1, "folderId": 1 }, { "id":2, "name":"Holidays", "description":"Access on Holidays", "startDate": "2021-01-01", "endDate": "2022-01-01", "level": 2, "folderId":2 }, { "id":3, "name":"Special", "description":"Special rule", "startDate": "2021-01-01", "endDate": "2022-01-01", "level": 3, "folderId": 3 }]</pre>
-----------------------	--

2.8.2. Get Access Rule by ID

URL Endpoint	api/v1/accessrules/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Access Rule
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/accessrules/1?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/accessrules/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId": <Number> }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Access rule with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accessrules/3 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>{ "id":3, "name":"Special", "description":"Special rule", "startDate": "2021-01-01", "endDate": "2022-01-01", "level": 3, "folderId": 4 }</pre>

2.8.3. Create Access Rule

URL Endpoint	api/v1/accessrules
Method	POST
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId":<Number> }</pre> Required fields: name
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId":<Number> }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/accessrules -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm" -d {"name":"access rule","description":"description", "startDate":"2022-02-14","endDate":"2022-02-14", "level":3,"folderId":4}</pre> <u>Response:</u> <pre>{ "id": 21, "name": "access rule", "description": "description", "startDate": "2022-02-14", "endDate": "2022-02-14", "level": 3, "folderId": 4 }</pre>
----------------	--

2.8.4. Update Access Rule

URL Endpoint	api/v1/accessrules/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId": <Number> }</pre>
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId": <Number> }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Access rule with specified id not found)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/accessrules/21 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm" -d '{"id": 0, "name": "updated access rule", "description": "updated description", "startDate": "2023-05-05", "endDate": "2023-05-05", "level": 3, "folderId": 2}'</pre> <u>Response:</u> <pre>{ "id": 0, "name": "updated access rule", "description": "updated description", "startDate": "2023-05-05", "endDate": "2023-05-05", "level": 3, "folderId": 2 }</pre>
----------------	--

2.8.5. Delete Access Rule

URL Endpoint	api/v1/accessrules/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Access Rule
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "startDate": <Date>, "endDate": <Date>, "level": <Number>, "folderId": <Number> }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Access rule with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/accessrules/21 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm"</pre> <u>Response:</u> <pre>{ "id": 21, "name": "updated access rule", "description": "updated description", "startDate": "2022-02-14", "endDate": "2022-02-14", "level": 3, "folderId": 2 }</pre>

2.8.6. Count Access Rules

URL Endpoint	api/v1/accessrules/count
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Access Rule(s) - returns count of records with specified identifiers (e.g. api/v1/accessrules/count?id=6&id=1) level - filter by rule's level (e.g. api/v1/accessrules/count?level=1) name - filter by access rule name with condition «starts with» (e.g. api/v1/accessrules/count?name=free) deployments - filter by deployment ids (e.g. api/v1/accessrules/count?deployments=1) folderId - filter by folder id (e.g. api/v1/accessrules/count?folderId=2) type - filter by rule type. Possible values of are: NORMAL, DOOR (e.g. api/v1/accessrules/count?type=NORMAL) startDate[operation] - filter by start date of access rule (e.g. api/v1/accessrules/count?startDate%5Bgte%5D=2023-05-10) endDate[operation] - filter by end date of access rule of access rule (e.g. api/v1/accessrules/count?endDate%5Bgte%5D=2023-05-10) Possible values of "operation" are: • EQ - equal • GT - greater than • LT - less than • GTE - greater than or equal • LTE - less than or equal groupBy - specifies which field to use for grouping. Permitted values are: name, level, folderId (e.g. api/v1/accessrules/count?groupBy=folderid) isRecursive - specifies whether to count access rules recursively or not (e.g. api/v1/accessrules/count?isRecursive=true)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "count": <Number> }]</pre>

Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Access denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accessrules/count -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "count": 3 }]</pre>

2.8.7. Get all folders of Access Rules

URL Endpoint	api/v1/accessrules/hierarchy
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	name - filter by name with condition «starts with» (e.g. api/v1/accessrules/hierarchy?name=access) parentID - filter by parent id (e.g. api/v1/accessrules/hierarchy?parentId=2) limit - specifies how many entities the response should contain (e.g. api/v1/accessrules/hierarchy?limit=10). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/accessrules/hierarchy?offset=10). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "parentId": <Number>, "level": <Number> }, { "id": <Number>, "name": <String>, "parentId": <Number>, "level": <Number> } ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Access denied)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accessrules/hierarchy -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1YyIjoiVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id": 5, "name": "access", "parentId": 2, "level": 2 }, { "id": 6, "name": "stop", "parentId": 2, "level": 2 }]</pre>
---------	--

2.9. Access Points

- [Get list of Access Points](#)
- [Get Access Point by ID](#)
- [Get all folders of Access Points](#)
- [Count Access Points](#)

2.9.1. Get list of Access Points

URL Endpoint	api/v1/accesspoints
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Access Point(s) - returns only records with specified identifiers (e.g. api/v1/accesspoints?id=1,2 or api/v1/accesspoints?id=1&id=2) name - filter by access point name with condition «starts with» (e.g. api/v1/accesspoints?name=Door1) folderId - filter by folder id (e.g. api/v1/accesspoints?folderId=4) limit - specifies how many entities the response should contain (e.g. api/v1/accesspoints?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/accesspoints?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/accesspoints?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/accesspoints?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/accesspoints?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/accesspoints?sortBy=name&sortOrder=DESC - means that entities would be sorted by name field in descending order)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "folderId": <Number> }, { "id": <Number>, "name": <String>, "folderId": <Number> }, ...]</pre>

Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accesspoints -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id":1, "name":"AccessPoint 1", "folderId": 1 }, { "id":2, "name":"AccessPoint 2", "folderId": 2 }]</pre>

2.9.2. Get Access Point by ID

URL Endpoint	api/v1/accesspoints/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Access Point
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/accesspoints/1?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/accesspoints/1?excludeFields=id - all fields besides id are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "folderId": <Number> }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Access Point with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accesspoints/2 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y2llbjojVXNlciIsIm"</pre> <u>Response:</u> <pre>{ "id":2, "name":"AccessPoint 2", "folderId": 1 }</pre>

2.9.3. Get all folders of Access Points

URL Endpoint	api/v1/accesspoints/hierarchy
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	name - filter by name with condition «starts with» (e.g. api/v1/accesspoints/hierarchy?name=door) parentID - filter by parent id (e.g. api/v1/accesspoints/hierarchy?parentId=4) limit - specifies how many entities the response should contain (e.g. api/v1/accesspoints/hierarchy?limit=10). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/accesspoints/hierarchy?offset=10). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "parentId": <Number>, }, { "id": <Number>, "name": <String>, "parentId": <Number>, } ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Access denied)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/accesspoints/hierarchy -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcitsIm"</pre> <u>Response:</u> <pre>[{ "id": 5, "name": "1 здание", "parentId": 0, }, { "id": 2, "name": "2 здание", "parentId": 0, }]</pre>
---------	--

2.9.4. Count Access Points

URL Endpoint	api/v1/accesspoints/count
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Access Points(s) - returns count of records with specified identifiers (e.g. api/v1/accesspoints/count?id=1) name - filter by access rule name with condition «starts with» (e.g. api/v1/accesspoints/count?name=%D1%81) folderId - filter by folder id (e.g. api/v1/accesspoints/count?folderId=4) groupBy - specifies which field to use for grouping. Permitted values are: name, folderId (e.g. api/v1/accesspoints/count?groupBy=folderid) isRecursive - specifies whether to count access points recursively or not (e.g. api/v1/accesspoints/count?isRecursive=true)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "count": <Number> }]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Access denied) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1//accesspoints/count -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y1lljoiVXNlciIsIm"</pre> <u>Response:</u> <pre>[{ "count": 3 }]</pre>

2.10. Users

- [Get user by ID](#)
- [Update user](#)
- [Delete user](#)
- [Get all users](#)
- [Create user from an existing employee](#)

2.10.1. Get all users

URL Endpoint	/api/v1/users/
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - Identifier(s) of a user(employee) (e.g. /api/v1/users?id=5&id=6&id=7) username - Filter by username with condition "starts with" (e.g. /api/v1/users?username=user) limit - Specifies how many entities the response should contain (e.g. /api/v1/users?limit=10). The value of this parameter must be between 0 and 3000 offset - Specifies how many entities should be skipped from the top (e.g. /api/v1/users?offset=2). The value of this parameter must be greater than or equal to 0 sortBy - Sort field (Default value: id) (e.g. /api/v1/users?sortBy=id) sortOrder - Sort order. Can be either ASC or DESC (Default value: ASC) (e.g. /api/v1/users?sortOrder=ASC)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": 0, "username": "string", "depRestriction": true, "depAccessList": [0] }]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 Unprocessable Entity</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/users -H 'accept: application/json' -H 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm'</pre> <u>Response:</u> <pre>[{ "id": 6, "username": "Administrator", "depRestriction": false, "depAccessList": [] }, { "id": 10, "username": "User", "depRestriction": false, "depAccessList": [] }]</pre>
---------	---

2.10.2. Get user by ID

URL Endpoint	/api/v1/users/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of a user (employee)
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": 0, "username": "string", "depRestriction": true, "depAccessList": [0] }</pre> ▪ "id" - identifier of a user (employee) ▪ "username" - username of a user ▪ "depRestriction" - shows whether access to departments is restricted for this user ▪ "depAccessList" - allowed departments' identifiers list
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 Not Found 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/users/7 -H 'accept: application/json' -H 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y1lljoiVXNlciIsIm'</pre> <u>Response:</u> <pre>{ "id": 7, "username": "User", "depRestriction": true, "depAccessList": [2] }</pre>

2.10.3. Create user from an existing employee

URL Endpoint	/api/v1/users/
Method	POST
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	
Body	<pre>{ "employeeId": 0, "username": "string", "password": "string", "depRestriction": true, "depAccessList": [0] }</pre> You should take into account the restrictions to users' passwords mentioned in File - Settings - Operator rights.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": 0, "username": "string", "depRestriction": true, "depAccessList": [0] }</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 422 Unprocessable Entity 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X POST http://127.0.0.1:9500/api/v1/users -H 'accept: application/json' -H 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm' -H 'Content-Type: application/json' -d '{"employeeId":11,"username": "user", "password": "user","depRestriction": true, "depAccessList": [2]}'</pre> <u>Response:</u> <pre>{ "id": 11, "username": "user", "depRestriction": true, "depAccessList": [2] }</pre>

2.10.4. Update user

URL Endpoint	/api/v1/users/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of a user (employee)
Query Parameters	
Body	<pre>{ "username": "string", "password": "string", "depRestriction": true, "depAccessList": [0] }</pre> Body contains fields that should be modified. It is possible to update the following fields: • username • password • depRestriction • depAccessList The user making this request cannot change their own settings except password (the checkbox "Change his own password" must be enabled in Cardholders - User). You should take into account the restrictions to users' passwords mentioned in File - Settings - Operator rights.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": 0, "username": "string", "depRestriction": true, "depAccessList": [0] }</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 404 Not Found 422 Unprocessable Entity 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/users/8 -H 'accept: application/json' -H 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm' -H 'Content-Type: application/json' -d '{"username": "Office Administrator", "password": "123456", "depRestriction": false, "depAccessList": []}'</pre> <u>Response:</u> <pre>{ "id": 8, "username": "Office Administrator", "depRestriction": false, "depAccessList": [] }</pre>
---------	--

2.10.5. Delete user

This request revokes the right to be a system user. An employee won't be deleted.

URL Endpoint	/api/v1/users/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of a user (employee). The user making this request cannot revoke their own right to be a system user.
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": 0, "depRestriction": true, "depAccessList": [0] }</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 Not Found</u> <u>422 Unprocessable Entity</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> curl -X DELETE http://192.168.0.108:9500/api/v1/users/7 -H 'accept: application/json' -H 'Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0eXB1IjoiVXNlcilmlm' <u>Response:</u> { "id": 7, "depRestriction": false, "depAccessList": [] }

2.11. Zones

- [Get list of Zones](#)
- [Get Zone by ID](#)

2.11.1. Get list of Zones

URL Endpoint	api/v1/zones
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	id - identifier(s) of Zone(s) - returns only records with specified identifiers (e.g. api/v1/zones?id=1,2 or api/v1/zones?id=1&id=2) accessPointId - filter by Access Point, returns only zones linked with specified Access Point (e.g. api/v1/zones?accessPointId=10) name - filter by zone name with condition "starts with" (e.g. api/v1/zones?name=ZoneA) accessPointId - identifier of access point (e.g. api/v1/zones?accessPointId=1) limit - specifies how many entities the response should contain (e.g. api/v1/zones?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 type - specifies what type of zones the response should contain (e.g. api/v1/zones?type=WORK) offset - specifies how many entities should be skipped from the top (e.g. api/v1/zones?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/zones?includeFields=name - only field "name" is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/zones?excludeFields=id - all fields besides "id" are returned in the response) sortBy - specifies sort field (e.g. api/v1/zones?sortBy=name - means that entities would be sorted by "name" field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/zones?sortBy=type&sortOrder=ASC - means that entities would be sorted by "type" field in ascending order (WORK -> EVACUATION -> UNDEFINED))
Body	

Success Response	The maximum number of returned objects is 50. Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "type": <String>, "accessPoints": [{"id":<Number>, "direction":<Enum: IN OUT>}, {"id":<Number>, "direction":<Enum: IN OUT>}, ...], { "id": <Number>, "name": <String>, "type": <String>, "accessPoints": [{"id":<Number>, "direction":<Enum: IN OUT>}, {"id":<Number>, "direction":<Enum: IN OUT>}, ...], ...] }</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/zones -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilslm"</pre> <u>Response:</u> <pre>{ "id":1, "name":"Zone 1", "type": "WORK", "accessPoints":[{"id":1, "direction":"IN"}, {"id":2, "direction":"OUT"}], { "id":2, "name":"Zone 2", "type": "EVACUATION", "accessPoints":[{"id":3, "direction":"IN"}, {"id":4, "direction":"OUT"}] } }</pre>

2.11.2. Get Zone by ID

URL Endpoint	api/v1/zones/{id}
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of zone
Query Parameters	includeFields - specifies what fields the response should contain (e.g. api/v1/zones/1?includeFields=name - only field "name" is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/zones/1?excludeFields=id - all fields besides "id" are returned in the response)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "type": <String>, "accessPoints": [{"id":<Number>, "direction":<Enum: IN OUT>}, {"id":<Number>, "direction":<Enum: IN OUT>}, ...] }</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 404 (Zone with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/zones/3 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlcilzIm"</pre> <u>Response:</u> <pre>{ "id":3, "name":"Zone 3", "type":"WORK", "accessPoints":[{"id":5, "direction":"IN"}, {"id":6, "direction":"OUT"}] }</pre>

2.12. Custom Fields

- [Overview](#)
- [Get list of Custom Fields](#)
- [Add new Custom Field](#)
- [Edit Custom Field](#)
- [Delete Custom Field](#)

2.12.1. Overview

Custom fields are additional fields that can be added to some entity and can be used for filtering. At the moment the following types of entities (field entity) are available:

- EMPLOYEES - applies to Employees;
- VEHICLES - applies to vehicles (Employees' and Officials);
- DEPARTMENTS - applies to Departments;
- POSITIONS - applies to Positions;
- CARDS - applies to Cards;
- VISITORS - applies to Visitors;
- VISITOR_VEHICLES - applies to visitor vehicles.

The following data types (field type) are supported:

- STRING
- DATE (e.g 2021-03-21)
- DATETIME (e.g. 2021-03-21T18:00:57) (with timezone in ISO8601 format)
- TIME (e.g. 12:36)
- LONG
- DOUBLE
- BOOLEAN
- LIST



Field name can contain only English letters and numbers ([a-zA-Z0-9]).

2.12.2. Get list of Custom Fields

URL Endpoint	api/v1/custom/fields
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	entity - filter by entity (e.g. api/v1/custom/fields?entity=EMPLOYEE) name - filter by custom field name with condition «starts with» (e.g. api/v1/custom/fields?name=dateBirth) limit - specifies how many entities the response should contain (e.g. api/v1/custom/fields?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/custom/fields?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/custom/fields?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/custom/fields?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/custom/fields?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/custom/fields?sortBy=name&sortOrder=ASC - means that entities would be sorted by name field in descending order)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id": <Number>, "name": <String>, "description": <String>, "type": <Enum (see above)>, "entity": "<Enum (see above)>", "values": [<String>, <String>, ...], "required": <Boolean> }, ...]</pre> If type is LIST then field values contain list of possible values.
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>

	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/custom/fields -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJyYyIljojoiVFNlcilslm"</pre> <u>Response:</u> <pre>[{ "id":1, "name":"birthDate", "description":"Employee birth date", "type":"STRING", "entity":"EMPLOYEES", "required": false }, { "id":2, "name":"Model", "description":"Vehicle model", "type":"STRING", "entity":"VEHICLES", "required": false }, { "id":3, "name":"Color", "description":"Color of some attribute", "type":"LIST", "entity":"EMPLOYEES", "values":["Red", "Green", "Blue"], "required": false }]</pre>
Example	

2.12.3. Add new Custom Field

URL Endpoint	api/v1/custom/fields
Method	POST
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	
Query Parameters	
Body	<pre>{ "name": <String>, "description": <String>, "type": <Enum (see above)>, "entity": "<Enum (see above)>", "values": [<String>, ...], "required": <Boolean> }</pre> Required fields: - name - description - type - entity - values (only if type is LIST) Attribute "required" is false by default.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "type": <Enum (see above)>, "entity": "<Enum (see above)>", "values": [<String>, <String>, ...], "required": <Boolean> }</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>422 (Validation Error)</u> <u>500 (Internal Server Error)</u>

Example	<u>Request:</u> <pre>curl -X POST http://192.168.0.108:9500/api/v1/custom/fields -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNiciIsIm" -d '{"name": "birthDate", "description": "Employee's date birth", "type": "STRING", "entity": "EMPLOYEES"}'</pre> <u>Response:</u> <pre>{ "id": 1, "name": "birthDate", "description": "Employee birth date", "type": "STRING", "entity": "EMPLOYEES", "required": false }</pre>
-----------------------	--

2.12.4. Edit Custom Field

URL Endpoint	api/v1/custom/fields/{id}
Method	PUT
Header Parameters	Authorization: Bearer <JWT access token> Content-Type: application/json
Path Parameters	id - identifier of Custom Field to be edited
Query Parameters	
Body	<pre>{ "name": <String>, "description": <String>, "values": [<String>, <String>, ...], "required": <Boolean> }</pre> Body contains fields that should be modified. Only new values can be added for type LIST.
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "type": <Enum (see above)>, "entity": "<Enum (see above)>", "values": [<String>, <String>, ...], "required": <Boolean> }</pre>
Error Response	401 (Unauthorized) 403 (Permission denied) 404 (Custom Field with specified id not found) 422 (Validation Error) 500 (Internal Server Error)
Example	<u>Request:</u> <pre>curl -X PUT http://192.168.0.108:9500/api/v1/custom/fields/1 -H "Content-Type: application/json" -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm" -d '{"description": "Birth Date"}'</pre> <u>Response:</u> <pre>{ "id": 1, "name": "birthDate", "description": "Birth date", "type": "STRING", "entity": "EMPLOYEES", "required": false }</pre>

2.12.5. Delete Custom Field

URL Endpoint	api/v1/custom/fields/{id}
Method	DELETE
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	id - identifier of Custom Field to be deleted
Query Parameters	
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "name": <String>, "description": <String>, "type": <Enum (see above)>, "entity": "Enum (see above)", "values": [<String>, <String>, ...], "required": <Boolean> }</pre>
Error Response	<u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>404 (Custom Field with specified id not found)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X DELETE http://192.168.0.108:9500/api/v1/custom/fields/1 -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1IjoiVXNlciIsIm"</pre> <u>Response:</u> <pre>{ "id": 1, "name": "birthDate", "description": "Birth date", "type": "STRING", "entity": "EMPLOYEES", "required": false }</pre>

2.13. Events

- [Get list of event types](#)
- [Get list of Events](#)
- [Get all parsed events](#)

2.13.1. Get list of event types

URL Endpoint	api/v1/events/types
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	name - filter by type name with condition 'starts with' limit - specifies how many entities the response should contain (e.g. api/v1/events/types?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/events/types?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/events/types?includeFields=name - only field name is returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/events/types?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/events/types?sortBy=name - means that entities would be sorted by name field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/events/types?sortBy=name&sortOrder=DESC)
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id":<Number>, "name":<String>, "description":<String> }, ...]</pre>
Error Response	400 (Invalid request) 401 (Unauthorized) 403 (Permission denied) 500 (Internal Server Error)

Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/events/types -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9 eyJuYyIljoiVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id":6, "name":"AccessPassed", "description":"Generated by controller when passed is registered" }, { "id":7, "name":"AccessDenied", "description":"Generated by controller when access denied is registered" }]</pre>
----------------	---

2.13.2. Get list of Events

URL Endpoint	api/v1/events
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	eventTypeId - filter events by type - only events with specified type are returned (e.g. api/v1/events?eventTypeId=6,12) lastId - only events with identifiers greater than specified are returned (e.g. api/v1/events?lastId=122345) startTime - only events starting from specified time are returned (e.g. api/v1/events?startTime=2021-04-01T08:00:00Z or e.g. api/v1/events?startTime=2021-04-01T08:00:00%2b03:00) endTime - only events till specified time are returned (e.g. api/v1/events?endTime=2021-04-30T23:59:59Z or e.g. api/v1/events?endTime=2021-04-30T23:59:59%2b03:00) accessObjectId - only events for specified access object are returned (access object identifier) (e.g. api/v1/events?accessObjectId=1456) accessPointId - only events for specified Access Point are returned (e.g. api/v1/events?accessPointId =6543) limit - specifies how many entities the response should contain (e.g. api/v1/events?limit=10 - means that only 10 entities returned in a response). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/events?limit=10&offset=10 - means that 10 records are skipped and next 10 entities returned in a response). The value of this parameter must be greater than or equal to 0 includeFields - specifies what fields the response should contain (e.g. api/v1/events?includeFields=type,timestamp - only fields type, timestamp are returned in the response) excludeFields - specifies what fields the response should not contain (e.g. api/v1/events?excludeFields=id - all fields besides id are returned in the response) sortBy - specifies sort field (e.g. api/v1/events?sortBy=timestamp - means that entities would be sorted by timestamp field) sortOrder - specifies sort order. Can be either ASC or DESC (e.g. api/v1/events?sortBy=timestamp&sortOrder=DESC) <u>Character + must be encoded as %2b in URL endpoint.</u>
Body	

Success Response	Status code: 200 Content-type: application/json Body: <pre>[{ "id":<Number>, "type":<Number>, "timestamp":<String>, "accessPointId":<Number>, "accessObjectId":<Number>, "direction":<String> }, ...]</pre>
Error Response	<u>400 (Invalid request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://192.168.0.108:9500/api/v1/events -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ1Y29kIjojVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id":1, "type":6, "timestamp":"2021-03-31T13:46:14+03:00", "accessPointId":6543, "accessObjectId":3456, "direction":"IN" }]</pre>

2.13.3. Get all parsed events

- Format of field "alcValue" - promille;
- Format of field "value" - volt;
- Format of field "temperature" & "TemperatureThreshold" - celsius.

URL Endpoint	api/v1/events/parsed
Method	GET
Header Parameters	Authorization: Bearer <JWT access token>
Path Parameters	
Query Parameters	startTime - filter by timestamp with condition 'greater than' (e.g. api/v1/events/parsed?startTime=2011-12-03T10:15:30%2B03:00) endTime - filter by timestamp with condition 'less than' (e.g. api/v1/events/parsed?endTime=2011-12-03T10:15:30%2B03:00) eventType - filter by event type (e.g. api/v1/events/parsed?eventType=PASS_DETECTED) accessPointId - filter by access point id (e.g. api/v1/events/parsed?accessPointId=1) accessObjectId - filter by access object id (e.g. api/v1/events/parsed?accessObjectId=1) cardKey - filter by card key (e.g. api/v1/events/parsed?cardKey=1800000100000000) lastId - only events with identifiers greater than specified are returned (e.g. api/v1/events/parsed?lastId=12345) lastLogId - only events with identifiers greater than specified are returned (e.g. api/v1/events/parsed?lastLogId=12345) includeFields - specifies what fields the response should contain (e.g. api/v1/events/parsed?includeFields=eventTimestamp) excludeFields - specifies what fields the response should not contain (e.g. api/v1/events/parsed?excludeFields=id) limit - specifies how many entities the response should contain (e.g. api/v1/events/parsed?limit=10). The value of this parameter must be between 0 and 3000 offset - specifies how many entities should be skipped from the top (e.g. api/v1/events/parsed?offset=10). The value of this parameter must be greater than or equal to 0
Body	
Success Response	Status code: 200 Content-type: application/json Body: <pre>{ "id": <Number>, "logId": <Number>, "data": <Object>, "additionalData": <Object>, "eventType": <Enum>, "timestamp": <Date and time>, "receivedTime": <Date and time> } ...]</pre>

Error Response	<u>400 (Invalid Request)</u> <u>401 (Unauthorized)</u> <u>403 (Permission denied)</u> <u>500 (Internal Server Error)</u>
Example	<u>Request:</u> <pre>curl -X GET http://localhost:9500/api/v1/events/parsed -H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJ0Y1lljoiVXNlcilsm"</pre> <u>Response:</u> <pre>[{ "id": 1, "logId": 100, "data": { "accessPointId": 1, "direction": "IN", "passReasonCode": 5, "passReason": "Pass though open door", "employeeId": 45, "cardKey": "180000001000000000", "alcValue": 655.35, "zoneId": 1 }, "additionalData": { "accessObject": { "type": "EMPLOYEE", "data": { "id": 45, "name": "Ivanov Ivan Ivanovich", "position": "Software Developer" } }, "zone": { "id": 1, "name": "Zone A" }, "accessPoint": { "id": 1, "name": "AP1", "linkType": "ETHACTIVE" } }, "eventType": "PASS_DETECTED", "timestamp": "2021-11-30T18:00:00+03:00", "receivedTime": "2021-11-30T18:00:01+03:00" }]</pre>

Possible content of "data"

Type event or group of events	Description	Content of "data"
ACCESS_ABORTED	Pass aborted by timeout	Success Response <pre>... "data": { "zoneId": <NUMBER>, "accessPointId": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "cardKey": <STRING> } ...</pre> Example <pre>... "data": { "zoneId": 1, "accessPointId": 1, "direction": "IN", "employeeId": 5, "cardKey": "20E1282CC6000000" } ...</pre>
PASS_DETECTED	Pass	Success Response <pre>... "data": { "zoneId": <NUMBER>, "accessPointId": <NUMBER>, "direction": <STRING>, "passReasonCode": <NUMBER>, "passReason": <STRING>, "employeeId": <NUMBER>, "cardKey": <STRING>, "alcValue": <NUMBER> } ...</pre> Example <pre>... "data": { "zoneId": 1, "accessPointId": 1, "direction": "IN", "passReasonCode": 3, "passReason": "Pass (by rules)", "employeeId": 5, "cardKey": "20E1282CC6000000", "alcValue": 0 } ...</pre>

PASS_DENY	Access denied	Success Response <pre> ... "data":{ "zoneId": <NUMBER>, "accessPointId": <NUMBER>, "direction": <STRING>, "denyReasonCode":<NUMBER>, "denyReason":<STRING>, "employeeId": <NUMBER>, "cardKey":<STRING>, "alcValue":<NUMBER> } ... </pre> Example <pre> ... "data":{ "zoneId":1, "accessPointId": 1, "direction": "IN", "denyReasonCode":3, "denyReason":"Pass (by rules)", "employeeId": 5, "cardKey":"20E1282CC6000000", "alcValue":0 } ... </pre>
FIRE_UNLOCK_BEGIN	Fire alarm! Emergency unlock activated	Success Response <pre> ... "data":{ "accessPointId": <NUMBER> } ... </pre>
FIRE_UNLOCK_END	Fire alarm end	Example
DOOR_HOLD_BEGIN	Door hold	<pre> ... "data":{ "accessPointId": 1 } ... </pre>
DOOR_HOLD_END	Door hold ended	<pre> ... </pre>
BOX_CLOSED	Controller case closed	Success Response <pre> ... "data":{ "accessPointId": <NUMBER>, "numberOfAccessPointsOnTheController": <NUMBER> } ... </pre> Example <pre> ... "data":{ "accessPointId": 4, "numberOfAccessPointsOnTheController": 1 } ... </pre>

BOX_OPENED	Controller case opened	Success Response ... <pre>"data":{ "accessPointId": <NUMBER>, "numberOfAccessPointsOnTheController": <NUMBER> }</pre> ... Example ... <pre>"data":{ "accessPointId": 4, "numberOfAccessPointsOnTheController": 1 }</pre> ...
AP_ONLINE_STATUS	Connection lost or Connection restored	Success Response ... <pre>"data":{ "accessPointId": <NUMBER>, "onlineStatus": <NUMBER> }</pre> ... Example ... <pre>"data":{ "accessPointId": 4, "onlineStatus":1 }</pre> ...
DEV_ACTION	Escort card read or Gate state change	Success Response ... <pre>"data":{ "accessPointId": <NUMBER>, "direction": <STRING>, "action":<STRING>, "zoneId":<NUMBER>, "employeeId": <NUMBER>, "cardKey":<STRING> }</pre> ... Example ... <pre>"data":{ "accessPointId": 1, "direction": "IN", "action": "Escort card read", "zoneId":1, "employeeId": 5, "cardKey": "20E1282CC6000000" }</pre> ...

VOLTAGE_STATUS	Battery or power supply's status change	Success Response <pre>... "data": { "accessPointId": <NUMBER>, "voltageStatus": <STRING>, "numberOfAccessPointsOnTheController": <NUMBER> } ...</pre> Example <pre>... "data": { "accessPointId": 4, "voltageStatus": "MAIN SUPPLY", "numberOfAccessPointsOnTheController": 1 } ...</pre>
LPR_NUMBER_EVENT	Number detected	Success Response <pre>... "data": { "zoneId": <NUMBER>, "direction": <STRING>, "accessPointId": <NUMBER>, "verticalDirection": <STRING>, "licencePlateNumber": <STRING> } ...</pre> Example <pre>... "data": { "zoneId": 0, "direction": "IN", "accessPointId": 4, "verticalDirection": "NO DATA", "licencePlateNumber": "A123AA12" } ...</pre>
MNG_STATE_CHANGED	Switching the door mode	Success Response <pre>... "data": { "cardKey": <NUMBER>, "newMode": <STRING>, "oldMode": „<STRING>, "changeReason": <STRING>, "accessPointId": <NUMBER> } ...</pre> Example <pre>... "data": { "cardKey": "0", "newMode": "UNLOCKED", "oldMode": "NORMAL", "changeReason": "SERVER COMMAND", "accessPointId": 1 } ...</pre>

TEXT	Text message	Success Response ... <pre>"data":{ "accessPointId": <Number>, "Text":<STRING> }</pre> ... Example ... <pre>"data":{ "accessPointId": 1, "Text":"message" }</pre> ...
TEXT2	Alarm text message	Success Response ... <pre>"data":{ "accessPointId": <Number>, "alarmingEvent":<BOOLEAN>, "Text":<STRING> }</pre> ... Example ... <pre>"data":{ "accessPointId": 1, "alarmingEvent": TRUE, "Text":"message" }</pre> ...
ALKO_DINGO_RAW_REPORT	Dingo breathalyzer's raw report	Success Response <pre>"data":{ "accessPointId": <NUMBER>, "direction":<STRING>, "reportData":<NUMBER> }</pre> Example ... <pre>"data":{ "accessPointId": 1, "direction":"IN", "reportData":<6> }</pre> ...

WAITING_FOR_RULE_STAGE	Waiting for escort, PIN, alko events or another event	Success Response <pre>... "data": { "zoneId": <NUMBER>, "cardKey": <STRING>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER>, "waitingReason": <STRING> } ...</pre> Example <pre>... "data": { "zoneId": 1, "cardKey": "208F1C0855000000", "direction": "IN", "employeeId": 5, "accessPointId": 4, "waitingReason": "Waiting for escort" } ...</pre>
LOCK_FAIL	Hall sensor alarm event	Success Response <pre>... "data": { "alarmType": <STRING>, "accessPointId": <NUMBER> } ...</pre> Example <pre>... "data": { "alarmType": "Hall sensor in active (should be inactive since lock is inactive)", "accessPointId": 4 } ...</pre>
FACE_RECOGNIZED	Face is identified (in identification mode)	Success Response <pre>... "data": { "zoneId": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER> } ...</pre> Example <pre>... "data": { "zoneId": 0, "direction": "IN", "employeeId": 6, "accessPointId": 4 } ...</pre>

FACE_VERIFICATION_FAILED	Face not recognized (in soft verification mode)	Success Response ... <pre>"data": { "zoneId": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER> }</pre> ... Example ... <pre>"data": { "zoneId": 0, "direction": "IN", "employeeId": 6, "accessPointId": 4 }</pre> ...
VOLTAGE_VALUE	Voltage value change	Success Response ... <pre>"data": { "accessPointId": <NUMBER>, "status": <STRING>, "value": <NUMBER>, "numberOfAccessPointsOnTheController": <NUMBER> }</pre> ... Example ... <pre>"data": { "accessPointId": 1, "status": "NORMAL", "value": 11.7, "numberOfAccessPointsOnTheController": 1 }</pre> ...

TEMPERATURE_ALERT	Temperature alert threshold exceeded	Success Response ... "data": { "zoneId": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER>, "temperature": <NUMBER>, "temperatureThreshold": <NUMBER> } ... Example ... "data": { "zoneId": 1, "direction": "IN", "employeeId": 5, "accessPointId": <NUMBER>, "temperature": 36.6, "temperatureThreshold": 37.0 } ...
TEMPERATURE_FINE	Normal temperature	
TEMPERATURE_WARNING	Temperature warning threshold exceeded	
FACE_MASK_VERIFICATION_FAILED	Face mask is absent (in soft verification mode)	Success Response ... "data": { "zoneId": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER> } ... Example ... "data": { "zoneId": 1, "direction": "IN", "employeeId": 5, "accessPointId": 1 } ...

FACE_MASK_VERIFICATION_SUCCESS	Face mask is on	Success Response ... <pre>"data": { "zoneld": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER> }</pre> ... Example ... <pre>"data": { "zoneld": 1, "direction": "IN", "employeeId": 5, "accessPointId": 1 }</pre> ...
TEMPERATURE_VERIFICATION_FAILED	Temperature check failed (in soft verification mode)	Success Response ... <pre>"data": { "zoneld": <NUMBER>, "direction": <STRING>, "employeeId": <NUMBER>, "accessPointId": <NUMBER> }</pre> ... Example ... <pre>"data": { "zoneld": 1, "direction": "IN", "employeeId": 5, "accessPointId": 1 }</pre> ...

Possible values of fields.**Possible values of field «direction»:**

- IN;
- OUT;
- NOT DEFINED;
- UNKNOWN.

Possible values of fields «passReasonCode»-«passReason»:

- 0 - Break-in;
- 1 - Pass in unlocked mode;
- 2 - Pass allowed by button;
- 3 - Pass (by rules);
- 4 - Pass (authorized by an external entity);
- 5 - Pass through open door;
- 6 - Pass (registered at work time terminal without access check);
- 7 - Pass, card was used (anviz);
- 8 - Pass, password was used (anviz);
- 9 - Pass, card + password were used (anviz);
- 128 - Waybill pass;
- default - Unknown reason;

Possible values of fields «denyReasonCode»-«denyReason»

- 0 - Wrong PIN;
- 1 - Key has expired;
- 2 - System error (code2);
- 3 - Unknown key;
- 4 - According to time zones;
- 5 - No access to this door;
- 6 - No access at this time;
- 7 - Passback;
- 8 - Main reader is used (while extra is expected);
- 9 - Extra reader is used (while main is expected);
- 10 - Time zones intersection error;
- 11 - Door is locked;
- 12 - Block button is active;
- 13 - Another airlock door is open;
- 14 - Zone capacity limit reached;
- 15 - Guard has denied the access;
- 16 - Alcohol overdose;
- 17 - Authorization timed out;
- 18 - Breathalyzer timed out;
- 19 - Escort card timed out;
- 20 - Guard decision timed out;
- 21 - Second card timed out;
- 22 - Previous transaction is in progress (code 22);
- 23 - Previous transaction is in progress;
- 24 - Unable to withdraw item cost";
- 25 - No licence plate recognition event;
- 26 - Special restrictions apply;
- 27 - There are assigned items;
- 28 - Face is not identified;
- 29 - Key brute force;
- 30 - Waiting for the escort;
- 31 - Access by LP is denied by the time zone;
- 32 - Got no decision from the external system;
- 33 - Forbidden Bby the external system;
- 34 - No connection with the server;
- 35 - Temperature check failed;
- 36 - Verification failed;
- 37 - Face mask is absent;
- Default - Unknown reason.

Possible values of field «action»:

- Escort cart read;
- Gate closed;
- Gate opened;
- Gate moved;
- Unknown action. Code N.

Possible values of field «voltageStatus»:

- Main supply;
- Battery.

Possible values of field «verticalDirection»:

- No data;
- Down;
- Up;
- Unknown.

Possible values of fields «newMode» and «oldMode»:

- Normal;
- Locked;
- Unlocked;
- Unknown.

Possible values of fields «changeReason»:

- Unknown;
- Fire unlock;
- Button;
- Double card read;
- Server command;
- Unknown.

Possible values of fields «waitingReason»:

- Waiting for escort;
- Waiting for PIN;
- Waiting for breathalyzer;
- Waiting for operator (access is allowed);
- Waiting for operator (access is denied);
- Checking for face mask;
- Waiting for temperature measurement;
- Waiting for face;
- Unknown reason.

Possible values of fields «alarmType»:

- Hall sensor is inactive (should be active since lock is active, door closed);
- Hall sensor is active (should be inactive since lock is inactive);
- Unknown.

Possible values of fields «status»:

- Normal;
- Below normal;
- Above normal;
- Unknown.

Possible values of fields «onlinestatus»:

- 1 (connection success);
- 0 (connection failed).

3. Response Error Codes

3.1. 400 Invalid Request

Status code: 400
Content-type: application/json
Body:

```
{
  "status": 400,
  "errors": [
    <Error description>
  ]
}
```

3.2. 401 Unauthorized

Status code: 401
Content-type: application/json
Body:

```
{
  "status": 401,
  "errors": [
    <Error description>
  ]
}
```

3.3. 403 Forbidden

Status code: 403
Content-type: application/json
Body:

```
{
  "status": 403,
  "errors": [
    <Error description>
  ]
}
```

3.4. 404 Not Found

Status code: 404
Content-type: application/json
Body:

```
{
  "status": 404,
  "errors": [
    <Error description>
  ]
}
```

3.5. 422 Unprocessable Entity

Status code: 422
Content-type: application/json
Body:

```
{
  "status": 422,
  "errors": [
    <Error description>
  ]
}
```

3.6. 500 Internal Server Error

Status code: 500

Content-type: application/json

Body:

```
{
  "status": 500,
  "errors": [
    <Error description>
  ]
}
```