

FCC REPORT

(WIFI)

Applicant: Balena Ltd.

Address of Applicant: 6th Floor, One London Wall London, London, EC2Y 5EB United Kingdom

Equipment Under Test (EUT)

Product Name: balenaFin

Model No.: v1.1

Trade mark: balenaFin

FCC ID: 2APW6-FIN0110-CM2

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 23 Aug., 2019

Date of Test: 24 Aug., to 26 Dec., 2019

Date of report issued: 27 Dec., 2019

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	27 Dec., 2019	Original

Tested by:
Test Engineer**Date:** 27 Dec., 2019**Reviewed by:**
Project Engineer**Date:** 27 Dec., 2019

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND TEST MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY	6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	6
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	7
5.9 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 ANTENNA REQUIREMENT	8
6.2 CONDUCTED EMISSION	9
6.3 CONDUCTED OUTPUT POWER	12
6.4 OCCUPY BANDWIDTH	15
6.5 POWER SPECTRAL DENSITY	20
6.6 BAND EDGE	23
6.6.1 Conducted Emission Method.....	23
6.6.2 Radiated Emission Method.....	26
6.7 SPURIOUS EMISSION	59
6.7.1 Conducted Emission Method.....	59
6.7.2 Radiated Emission Method.....	62
7 TEST SETUP PHOTO	74
8 EUT CONSTRUCTIONAL DETAILS	76

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (b)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247 (d)	Pass
Spurious Emission	15.205 & 15.209	Pass

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: Not Applicable.
3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).

Test Method:	ANSI C63.4-2014 ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02
---------------------	---

5 General Information

5.1 Client Information

Applicant:	Balena Ltd.
Address:	6th Floor, One London Wall London, London, EC2Y 5EB United Kingdom
Manufacturer:	Balena Ltd.
Address:	6th Floor, One London Wall London, London, EC2Y 5EB United Kingdom
Factory:	Fae Technology S.p.a.
Address:	Via C. Battisti, 136 Gazzaniga (BG) 24025 - Italia

5.2 General Description of E.U.T.

Product Name:	balenaFin
Model No.:	v1.1
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)) 2422MHz~2452MHz (802.11n(H40))
Channel numbers:	11 for 802.11b/802.11g/802.11(H20) 7 for 802.11n(H40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal Antenna External Antenna
Antenna gain:	Internal Antenna: 1dBi External Antenna: 2dBi
Power supply:	DC6V-24V
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel for 802.11b/g/n(H20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

- For 802.11n-HT40 mode, the channel number is from 3 to 9;
- Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel. Channel 3, 6 & 9 selected for 802.11n-HT40 as Lowest, Middle and Highest channel, Channel.

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
<p>The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p> <p>We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:</p>	
Per-scan all kind of data rate, the follow list were the worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
GSP	Adapter	GSCV0600S019V12E	N/A	DoC
Raspberry Pi	Compute Module	Compute Module 3+	N/A	N/A

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282, Fax: +86-755-23116366
 Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instruments list

Radiated Emission:						
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)	
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020	
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-18-2019	03-17-2020	
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020	
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020	
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020	
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019	
				11-20-2019	11-19-2020	
EMI Test Software	AUDIX	E3	Version: 6.110919b			
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020	
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020	
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020	
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019	
				11-20-2019	11-19-2020	
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020	
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020	
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020	
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020	
RF Switch Unit	MWRFTEST	MW200	N/A	N/A	N/A	
Test Software	MWRFTEST	MTS8200	Version: 2.0.0.0			

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-18-2019	03-17-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-18-2019	03-17-2020
LISN	CHASE	MN2050D	1447	03-18-2019	03-17-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2021
Cable	HP	10503A	N/A	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement


Standard requirement:	FCC Part 15 C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	The BLE antenna is an Internal antenna and External antenna which cannot replace by end-user, the best-case gain of the antenna is Internal antenna: 1 dBi and External antenna: 2 dBi
Internal antenna	External antenna
	

6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
	0.15-0.5	Quasi-peak	Average
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement. 		
Test setup:	<p style="text-align: center;">Reference Plane</p> <p>Diagram illustrating the test setup for conducted emission testing. The setup consists of a 'Reference Plane' at the top, followed by a 'Test table/Insulation plane'. On the table, there are two LISNs (Line Impedance Stabilization Networks). One LISN is connected to the 'E.U.T' (Equipment Under Test), and the other is connected to an 'EMI Receiver'. The 'E.U.T' is also connected to an 'AUX Equipment'. The distance between the LISNs is 40cm. The distance from the LISN connected to the E.U.T to the LISN connected to the EMI Receiver is 80cm. The 'EMI Receiver' is connected to an 'AC power' source via a 'Filter'. A note below the diagram specifies: 'Remark: E.U.T: Equipment Under Test; LISN: Line Impedance Stabilization Network; Test table height=0.8m'.</p>		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Product name:	balenaFin	Product Model:	v1.1
Test by:	Carey	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




	Freq MHz	Read Level dBuV	LISN Factor dB	Aux Factor dB	Cable Loss dB	Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.174	31.08	-0.43	-0.11	10.77	41.31	64.77	-23.46	QP
2	0.194	30.76	-0.41	-0.15	10.76	40.96	63.84	-22.88	QP
3	0.502	20.59	-0.39	-0.35	10.76	30.61	46.00	-15.39	Average
4	0.541	30.04	-0.39	-0.36	10.76	40.05	56.00	-15.95	QP
5	0.561	20.56	-0.39	-0.37	10.76	30.56	46.00	-15.44	Average
6	0.614	17.11	-0.38	-0.38	10.77	27.12	46.00	-18.88	Average
7	1.016	13.75	-0.38	0.44	10.87	24.68	46.00	-21.32	Average
8	1.054	24.73	-0.38	0.40	10.88	35.63	56.00	-20.37	QP
9	1.636	22.17	-0.40	-0.09	10.93	32.61	56.00	-23.39	QP
10	1.680	14.24	-0.40	-0.13	10.94	24.65	46.00	-21.35	Average
11	2.678	22.93	-0.43	-0.24	10.93	33.19	56.00	-22.81	QP
12	2.779	15.22	-0.43	-0.23	10.93	25.49	46.00	-20.51	Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	balenaFin	Product Model:	v1.1
Test by:	Carey	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor dB	Aux Factor dB	Cable Loss dB	Line Level dBuV	Limit Line dBuV	Over Limit dB	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.502	21.25	-0.65	0.00	10.76	31.36	46.00	-14.64 Average
2	0.535	22.99	-0.65	0.00	10.76	33.10	46.00	-12.90 Average
3	0.541	30.97	-0.65	0.00	10.76	41.08	56.00	-14.92 QP
4	0.561	29.00	-0.65	0.00	10.76	39.11	56.00	-16.89 QP
5	0.561	21.29	-0.65	0.00	10.76	31.40	46.00	-14.60 Average
6	1.010	27.24	-0.63	0.00	10.87	37.48	56.00	-18.52 QP
7	1.016	17.79	-0.63	0.00	10.87	28.03	46.00	-17.97 Average
8	1.054	26.96	-0.63	0.00	10.88	37.21	56.00	-18.79 QP
9	1.645	16.53	-0.66	0.00	10.93	26.80	46.00	-19.20 Average
10	1.654	24.75	-0.66	0.00	10.94	35.03	56.00	-20.97 QP
11	2.608	26.21	-0.67	0.00	10.93	36.47	56.00	-19.53 QP
12	2.608	17.05	-0.67	0.00	10.93	27.31	46.00	-18.69 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.


6.3 Conducted Output Power


Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	 <p>The diagram illustrates the test setup for conducted output power. A Spectrum Analyzer is connected to the Equipment Under Test (E.U.T) via a cable. The E.U.T is positioned on a Non-Conducted Table. The entire setup rests on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Test CH	Maximum Conducted Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	13.12	12.37	12.32	10.34	30.00	Pass
Middle	12.33	12.17	11.99	9.87		
Highest	12.18	11.86	11.85	9.85		

Test plot as follows:






6.4 Occupy Bandwidth


Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	 <p>The diagram shows a 'Spectrum Analyzer' with a graph displaying a signal. A red line connects it to a 'E.U.T' (Equipment Under Test) box. This assembly rests on a 'Non-Conducted Table'. Below the table is a horizontal grey bar labeled 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:


Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	11.12	16.56	17.76	36.32	>500	Pass
Middle	10.24	16.48	17.76	36.32		
Highest	10.24	16.56	17.76	36.48		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	13.28	16.88	17.76	36.48	N/A	N/A
Middle	13.28	16.80	17.76	36.64		
Highest	13.28	16.80	17.76	36.64		

Test plot as follows:










6.5 Power Spectral Density


Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a coaxial cable. The E.U.T is placed on a Non-Conducted Table. The entire assembly sits on a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Test CH	Power Spectral Density (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	-11.34	-14.74	-14.35	-19.58	8.00	Pass
Middle	-12.09	-15.96	-16.17	-19.34		
Highest	-12.60	-17.07	-14.86	-20.21		

Test plot as follows:

Test mode: 802.11b




Test mode: 802.11g




Date: 20.DEC.2019 11:28:50

Lowest channel




Date: 20.DEC.2019 10:57:21

Lowest channel




Date: 20.DEC.2019 11:29:25

Middle channel



Date: 20.DEC.2019 10:57:58

Middle channel




Date: 20.DEC.2019 11:29:52

Highest channel


Date: 20.DEC.2019 10:58:26

Highest channel




6.6 Band Edge

6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Test plot as follows:

802.11b



Date: 20.DEC.2019 11:50:50


Lowest channel



Date: 20.DEC.2019 11:36:11


Highest channel

802.11g




Date: 20.DEC.2019 11:49:17

Lowest channel



Date: 20.DEC.2019 11:38:18

Highest channel




6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205										
Test Frequency Range:	2.3GHz to 2.5GHz										
Test Distance:	3m										
Receiver setup:	Frequency	Detector	RBW	VBW	Remark						
	Above 1GHz	Peak	1MHz	3MHz	Peak Value						
Limit:	Frequency	Limit (dBuV/m @3m)		Remark							
	Above 1GHz	54.00		Average Value							
Test Procedure:		<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 									
Test setup:											
Test Instruments:	Refer to section 5.9 for details										
Test mode:	Refer to section 5.3 for details										
Test results:	Passed										

Internal Antenna

802.11b mode:

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




ReadAntenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Level	Line	Limit	Remark

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	20.01	27.07	4.69	0.00	51.77	74.00	-22.23 Peak
2	2390.000	8.55	27.07	4.69	0.00	40.31	54.00	-13.69 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read	Antenna Level Factor	Cable Loss Factor	Preamplifier Level dB	Limit dBuV/m	Over Line dBuV/m	Over Line dB	Over Line Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 2390.000	20.68	27.08	4.69	0.00	52.45	74.00	-21.55	Peak
2 2390.000	8.64	27.08	4.69	0.00	40.41	54.00	-13.59	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	
1	2483.500	20.74	27.36	4.81	0.00	52.91	74.00	-21.09	Peak
2	2483.500	9.04	27.36	4.81	0.00	41.21	54.00	-12.79	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	21.58	27.35	4.81	0.00	53.74	74.00 -20.26 Peak
2	2483.500	9.07	27.35	4.81	0.00	41.23	54.00 -12.77 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g mode:

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 2390.000	20.96	27.07	4.69	0.00	52.72	74.00	-21.28	Peak
2 2390.000	8.89	27.07	4.69	0.00	40.65	54.00	-13.35	Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss Factor	Preamp Factor	Limit Level	Line Limit	Over Remark
------	-------------------	-------------------	---------------	-------------	------------	-------------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.48	27.08	4.69	0.00	53.25	74.00	-20.75 Peak
2	2390.000	9.67	27.08	4.69	0.00	41.44	54.00	-12.56 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	ReadAntenna Freq	Cable Level	Preamp Factor	Limit Loss	Line Factor	Over Level	Line Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	19.90	27.36	4.81	0.00	52.07	74.00	-21.93 Peak
2	2483.500	9.01	27.36	4.81	0.00	41.18	54.00	-12.82 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.64	27.35	4.81	0.00	53.80	74.00	-20.20 Peak
2	2483.500	9.38	27.35	4.81	0.00	41.54	54.00	-12.46 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT20):

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Line	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.30	27.07	4.69	0.00	53.06	74.00	-20.94 Peak
2	2390.000	8.59	27.07	4.69	0.00	40.35	54.00	-13.65 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Freq	Level	Factor	Loss	Factor	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2390.000	22.88	27.08	4.69	0.00	54.65	74.00	-19.35 Peak
2 2390.000	10.37	27.08	4.69	0.00	42.14	54.00	-11.86 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Over Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	20.86	27.36	4.81	0.00	53.03	74.00 -20.97 Peak
2	2483.500	9.13	27.36	4.81	0.00	41.30	54.00 -12.70 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.19	27.35	4.81	0.00	53.35	74.00	-20.65 Peak
2	2483.500	9.53	27.35	4.81	0.00	41.69	54.00	-12.31 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT40):

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Factor	Preamp Loss	Avg	Limit Level	Line Limit	Over Line Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	21.58	27.07	4.69	0.00	53.34	74.00	-20.66 Peak
2	2390.000	8.60	27.07	4.69	0.00	40.36	54.00	-13.64 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	Freq	Level	Factor	Loss			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	20.69	27.08	4.69	0.00	52.46	74.00 -21.54 Peak
2	2390.000	9.35	27.08	4.69	0.00	41.12	54.00 -12.88 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read	Antenna Level dBuV	Cable Loss dB	Preamp Factor dB	Limit Line dBuV/m	Over Line dB	Over Limit Remark
	Freq MHz	Antenna Level dBuV/m	Cable Loss dB	Preamp Factor dB	Limit Line dBuV/m	Over Line dB	Over Limit Remark
1 2483.500	21.63	27.36	4.81	0.00	53.80	74.00	-20.20 Peak
2 2483.500	9.12	27.36	4.81	0.00	41.29	54.00	-12.71 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq	Read	Antenna	Cable	Preamp	Limit	Over
MHz	Level	Factor	Loss	Level	Line	Line

1	2483.500	22.17	27.35	4.81	0.00	54.33	74.00	-19.67	Peak
2	2483.500	9.44	27.35	4.81	0.00	41.60	54.00	-12.40	Average


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

External Antenna

802.11b mode:

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna	Cable	Preamp	Limit	Over	Remark		
	Freq	Level	Factor	Loss	Factor	Line	Limit	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	19.64	27.07	4.69	0.00	51.40	74.00	-22.60 Peak
2	2390.000	8.57	27.07	4.69	0.00	40.33	54.00	-13.67 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	19.97	27.08	4.69	0.00	51.74	74.00	-22.26 Peak
2	2390.000	8.50	27.08	4.69	0.00	40.27	54.00	-13.73 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Over Line Limit	Over Remark
------	-------------------	------------	---------------	-------------	-----------------	-------------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	20.32	27.36	4.81	0.00	52.49	74.00	-21.51 Peak
2	2483.500	9.07	27.36	4.81	0.00	41.24	54.00	-12.76 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2483.500	21.01	27.35	4.81	0.00	53.17	74.00	-20.83 Peak
2	2483.500	9.10	27.35	4.81	0.00	41.26	54.00	-12.74 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g mode:

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss Factor	Preamp Factor	Limit Level	Over Line	Over Limit	Remark
------	-------------------	-------------------	---------------	-------------	-----------	------------	--------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.60	27.07	4.69	0.00	53.36	74.00	-20.64 Peak
2	2390.000	9.13	27.07	4.69	0.00	40.89	54.00	-13.11 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	ReadAntenna Freq	Level MHz	Antenna Factor	Cable Loss Factor	Preamp Level dB	Limit dBuV/m	Over Line dBuV/m	Over Limit dB	Remark
1	2390.000	20.79	27.08	4.69	0.00	52.56	74.00	-21.44	Peak
2	2390.000	8.69	27.08	4.69	0.00	40.46	54.00	-13.54	Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Line	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	24.05	27.36	4.81	0.00	56.22	74.00	-17.78 Peak
2	2483.500	10.47	27.36	4.81	0.00	42.64	54.00	-11.36 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	20.99	27.35	4.81	0.00	53.15	74.00	-20.85 Peak
2	2483.500	9.22	27.35	4.81	0.00	41.38	54.00	-12.62 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT20):

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Over Line	Over Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 2390.000	21.87	27.07	4.69	0.00	53.63	74.00	-20.37 Peak
2 2390.000	9.19	27.07	4.69	0.00	40.95	54.00	-13.05 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Cable Loss	Preamp Factor	Limit Level	Over Line Limit	Over Remark
------	-------------------	------------	---------------	-------------	-----------------	-------------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.29	27.08	4.69	0.00	53.06	74.00	-20.94 Peak
2	2390.000	8.79	27.08	4.69	0.00	40.56	54.00	-13.44 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




	ReadAntenna Freq	Level MHz	Antenna Factor	Cable Loss Factor	Preamp Level dB	Limit dBuV/m	Over Line dBuV/m	Over Line dB	Over Line Remark
1	2483.500	22.83	27.36	4.81	0.00	55.00	74.00	-19.00	Peak
2	2483.500	10.38	27.36	4.81	0.00	42.55	54.00	-11.45	Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Level		
MHz	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	22.13	27.35	4.81	0.00	54.29	74.00	-19.71 Peak
2	2483.500	9.25	27.35	4.81	0.00	41.41	54.00	-12.59 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT40):

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Line Limit	Over Limit	Remark
------	-------------------	----------------	------------	---------------	-------------	------------	------------	--------

	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2390.000	21.88	27.07	4.69	0.00	53.64	74.00	-20.36 Peak
2	2390.000	9.30	27.07	4.69	0.00	41.06	54.00	-12.94 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Line	Limit	Remark
MHz	Level	Factor	Loss	Factor	Level	dBuV/m	dBuV/m	dB	
1 2390.000	19.81	27.08	4.69	0.00	51.58	74.00	-22.42	Peak	
2 2390.000	8.81	27.08	4.69	0.00	40.58	54.00	-13.42	Average	

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
 4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Line		
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2483.500	24.44	27.36	4.81	0.00	56.61	74.00	-17.39 Peak
2	2483.500	10.38	27.36	4.81	0.00	42.55	54.00	-11.45 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna		Cable Preamp		Limit Line	Over Limit	Remark
	Freq	Level Factor	Loss Factor	Level			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	
1	2483.500	21.76	27.35	4.81	0.00	53.92	74.00 -20.08 Peak
2	2483.500	9.17	27.35	4.81	0.00	41.33	54.00 -12.67 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.7 Spurious Emission


6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

Test mode: 802.11b


Lowest channel



Date: 20.DEC.2019 11:53:39


Test mode: 802.11g

Lowest channel




Date: 20.DEC.2019 11:58:29

Middle channel




Date: 20.DEC.2019 11:55:22

Middle channel




Date: 20.DEC.2019 11:59:28

Highest channel




Date: 20.DEC.2019 11:56:12

Highest channel




Date: 20.DEC.2019 12:00:53



6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205								
Test Frequency Range:	9kHz to 25GHz								
Test Distance:	3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit:	RMS	1MHz	3MHz	3MHz	Average Value				
	Frequency	Limit (dBuV/m @3m)		Remark					
	30MHz-88MHz	40.0		Quasi-peak Value					
	88MHz-216MHz	43.5		Quasi-peak Value					
	216MHz-960MHz	46.0		Quasi-peak Value					
	960MHz-1GHz	54.0		Quasi-peak Value					
	Above 1GHz	54.0		Average Value					
		74.0		Peak Value					
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 								
Test setup:	<p>Below 1GHz</p> <p>Above 1GHz</p>								




Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	<ol style="list-style-type: none">1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.2. 9 kHz to 30MHz is too low, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):**Below 1GHz: (External antenna worst case)**

Product Name:	balenaFin		Product Model:	v1.1																																																																									
Test By:	Carey		Test mode:	Wi-Fi Tx mode																																																																									
Test Frequency:	30 MHz ~ 1 GHz		Polarization:	Vertical																																																																									
Test Voltage:	AC 120/60Hz		Environment:	Temp: 24°C	Huni: 57%																																																																								
<table border="1"> <thead> <tr> <th>Freq</th> <th>ReadAntenna Level</th> <th>Antenna Factor</th> <th>Cable Loss</th> <th>Preamp Factor</th> <th>Limit Level</th> <th>Over Line</th> <th>Over Limit</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td></td> </tr> <tr> <td>1</td> <td>52.575</td> <td>38.13</td> <td>11.83</td> <td>1.29</td> <td>29.81</td> <td>21.44</td> <td>40.00</td> <td>-18.56 QP</td> </tr> <tr> <td>2</td> <td>69.845</td> <td>36.09</td> <td>8.56</td> <td>1.52</td> <td>29.72</td> <td>16.45</td> <td>40.00</td> <td>-23.55 QP</td> </tr> <tr> <td>3</td> <td>117.773</td> <td>37.96</td> <td>11.04</td> <td>2.14</td> <td>29.40</td> <td>21.74</td> <td>43.50</td> <td>-21.76 QP</td> </tr> <tr> <td>4</td> <td>325.596</td> <td>36.14</td> <td>14.14</td> <td>3.02</td> <td>28.51</td> <td>24.79</td> <td>46.00</td> <td>-21.21 QP</td> </tr> <tr> <td>5</td> <td>435.590</td> <td>39.16</td> <td>16.16</td> <td>3.16</td> <td>28.85</td> <td>29.63</td> <td>46.00</td> <td>-16.37 QP</td> </tr> <tr> <td>6</td> <td>480.528</td> <td>40.19</td> <td>17.52</td> <td>3.46</td> <td>28.92</td> <td>32.25</td> <td>46.00</td> <td>-13.75 QP</td> </tr> </tbody> </table>						Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Line	Over Limit	Remark	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		1	52.575	38.13	11.83	1.29	29.81	21.44	40.00	-18.56 QP	2	69.845	36.09	8.56	1.52	29.72	16.45	40.00	-23.55 QP	3	117.773	37.96	11.04	2.14	29.40	21.74	43.50	-21.76 QP	4	325.596	36.14	14.14	3.02	28.51	24.79	46.00	-21.21 QP	5	435.590	39.16	16.16	3.16	28.85	29.63	46.00	-16.37 QP	6	480.528	40.19	17.52	3.46	28.92	32.25	46.00	-13.75 QP
Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Line	Over Limit	Remark																																																																					
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB																																																																						
1	52.575	38.13	11.83	1.29	29.81	21.44	40.00	-18.56 QP																																																																					
2	69.845	36.09	8.56	1.52	29.72	16.45	40.00	-23.55 QP																																																																					
3	117.773	37.96	11.04	2.14	29.40	21.74	43.50	-21.76 QP																																																																					
4	325.596	36.14	14.14	3.02	28.51	24.79	46.00	-21.21 QP																																																																					
5	435.590	39.16	16.16	3.16	28.85	29.63	46.00	-16.37 QP																																																																					
6	480.528	40.19	17.52	3.46	28.92	32.25	46.00	-13.75 QP																																																																					
<p>Remark:</p> <ol style="list-style-type: none"> Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor. The emission levels of other frequencies are very lower than the limit and not show in test report. 																																																																													

Product Name:	balenaFin	Product Model:	v1.1
Test By:	Carey	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Level dBuV/m	Line Limit dBuV/m	Over Line Limit dB	Over Limit Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1 317.701	41.35	13.98	3.00	28.49	29.84	46.00	-16.16 QP
2 383.932	48.34	15.08	3.09	28.71	37.80	46.00	-8.20 QP
3 428.019	43.23	15.99	3.15	28.83	33.54	46.00	-12.46 QP
4 495.934	41.14	18.06	3.59	28.94	33.85	46.00	-12.15 QP
5 625.078	37.89	19.61	3.90	28.86	32.54	46.00	-13.46 QP
6 875.247	33.35	22.55	3.95	27.94	31.91	46.00	-14.09 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Internal Antenna**Above 1GHz**

802.11b								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.79	31.06	6.81	41.82	43.84	74.00	-30.16	Vertical
4824.00	47.48	31.06	6.81	41.82	43.53	74.00	-30.47	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	37.92	31.06	6.81	41.82	33.97	54.00	-20.03	Vertical
4824.00	38.14	31.06	6.81	41.82	34.19	54.00	-19.81	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.68	31.16	6.85	41.84	43.85	74.00	-30.15	Vertical
4874.00	47.28	31.16	6.85	41.84	43.45	74.00	-30.55	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	37.52	31.16	6.85	41.84	33.69	54.00	-20.31	Vertical
4874.00	38.12	31.16	6.85	41.84	34.29	54.00	-19.71	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.24	31.25	6.89	41.86	43.52	74.00	-30.48	Vertical
4924.00	47.67	31.25	6.89	41.86	43.95	74.00	-30.05	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	37.26	31.25	6.89	41.86	33.54	54.00	-20.46	Vertical
4924.00	38.06	31.25	6.89	41.86	34.34	54.00	-19.66	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.72	31.06	6.81	41.82	43.77	74.00	-30.23	Vertical
4824.00	48.15	31.06	6.81	41.82	44.20	74.00	-29.80	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	36.77	31.06	6.81	41.82	32.82	54.00	-21.18	Vertical
4824.00	38.31	31.06	6.81	41.82	34.36	54.00	-19.64	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.39	31.16	6.85	41.84	43.56	74.00	-30.44	Vertical
4874.00	48.27	31.16	6.85	41.84	44.44	74.00	-29.56	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	37.13	31.16	6.85	41.84	33.30	54.00	-20.70	Vertical
4874.00	37.96	31.16	6.85	41.84	34.13	54.00	-19.87	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	48.01	31.25	6.89	41.86	44.29	74.00	-29.71	Vertical
4924.00	47.78	31.25	6.89	41.86	44.06	74.00	-29.94	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	36.95	31.25	6.89	41.86	33.23	54.00	-20.77	Vertical
4924.00	38.57	31.25	6.89	41.86	34.85	54.00	-19.15	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT20)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.38	31.06	6.81	41.82	43.43	74.00	-30.57	Vertical
4824.00	48.60	31.06	6.81	41.82	44.65	74.00	-29.35	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	37.16	31.06	6.81	41.82	33.21	54.00	-20.79	Vertical
4824.00	38.80	31.06	6.81	41.82	34.85	54.00	-19.15	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.48	31.16	6.85	41.84	43.65	74.00	-30.35	Vertical
4874.00	49.51	31.16	6.85	41.84	45.68	74.00	-28.32	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	36.62	31.16	6.85	41.84	32.79	54.00	-21.21	Vertical
4874.00	38.62	31.16	6.85	41.84	34.79	54.00	-19.21	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.91	31.25	6.89	41.86	44.19	74.00	-29.81	Vertical
4924.00	49.52	31.25	6.89	41.86	45.80	74.00	-28.20	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	36.61	31.25	6.89	41.86	32.89	54.00	-21.11	Vertical
4924.00	38.71	31.25	6.89	41.86	34.99	54.00	-19.01	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT40)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	47.84	31.10	6.83	41.83	43.94	74.00	-30.06	Vertical
4844.00	49.77	31.10	6.83	41.83	45.87	74.00	-28.13	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	37.26	31.10	6.83	41.83	33.36	54.00	-20.64	Vertical
4844.00	38.51	31.10	6.83	41.83	34.61	54.00	-19.39	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.72	31.16	6.85	41.84	43.89	74.00	-30.11	Vertical
4874.00	49.77	31.16	6.85	41.84	45.94	74.00	-28.06	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	36.84	31.16	6.85	41.84	33.01	54.00	-20.99	Vertical
4874.00	38.99	31.16	6.85	41.84	35.16	54.00	-18.84	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	47.86	31.22	6.87	41.85	44.10	74.00	-29.90	Vertical
4904.00	49.98	31.22	6.87	41.85	46.22	74.00	-27.78	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	36.81	31.22	6.87	41.85	33.05	54.00	-20.95	Vertical
4904.00	38.67	31.22	6.87	41.85	34.91	54.00	-19.09	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

External Antenna

Above 1GHz

802.11b								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.95	31.06	6.81	41.82	44.00	74.00	-30.00	Vertical
4824.00	47.89	31.06	6.81	41.82	43.94	74.00	-30.06	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	37.98	31.06	6.81	41.82	34.03	54.00	-19.97	Vertical
4824.00	37.62	31.06	6.81	41.82	33.67	54.00	-20.33	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.49	31.16	6.85	41.84	43.66	74.00	-30.34	Vertical
4874.00	48.35	31.16	6.85	41.84	44.52	74.00	-29.48	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	38.23	31.16	6.85	41.84	34.40	54.00	-19.60	Vertical
4874.00	37.59	31.16	6.85	41.84	33.76	54.00	-20.24	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.64	31.25	6.89	41.86	43.92	74.00	-30.08	Vertical
4924.00	48.42	31.25	6.89	41.86	44.70	74.00	-29.30	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	38.09	31.25	6.89	41.86	34.37	54.00	-19.63	Vertical
4924.00	37.84	31.25	6.89	41.86	34.12	54.00	-19.88	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11g								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.54	31.06	6.81	41.82	43.59	74.00	-30.41	Vertical
4824.00	48.77	31.06	6.81	41.82	44.82	74.00	-29.18	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	37.22	31.06	6.81	41.82	33.27	54.00	-20.73	Vertical
4824.00	37.99	31.06	6.81	41.82	34.04	54.00	-19.96	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.61	31.16	6.85	41.84	43.78	74.00	-30.22	Vertical
4874.00	48.51	31.16	6.85	41.84	44.68	74.00	-29.32	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	37.19	31.16	6.85	41.84	33.36	54.00	-20.64	Vertical
4874.00	38.25	31.16	6.85	41.84	34.42	54.00	-19.58	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.68	31.25	6.89	41.86	43.96	74.00	-30.04	Vertical
4924.00	48.17	31.25	6.89	41.86	44.45	74.00	-29.55	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	37.56	31.25	6.89	41.86	33.84	54.00	-20.16	Vertical
4924.00	38.73	31.25	6.89	41.86	35.01	54.00	-18.99	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11n(HT20)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	47.64	31.06	6.81	41.82	43.69	74.00	-30.31	Vertical
4824.00	48.42	31.06	6.81	41.82	44.47	74.00	-29.53	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4824.00	38.09	31.06	6.81	41.82	34.14	54.00	-19.86	Vertical
4824.00	37.84	31.06	6.81	41.82	33.89	54.00	-20.11	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	47.17	31.16	6.85	41.84	43.34	74.00	-30.66	Vertical
4874.00	48.62	31.16	6.85	41.84	44.79	74.00	-29.21	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	38.07	31.16	6.85	41.84	34.24	54.00	-19.76	Vertical
4874.00	38.23	31.16	6.85	41.84	34.40	54.00	-19.60	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	47.60	31.25	6.89	41.86	43.88	74.00	-30.12	Vertical
4924.00	48.16	31.25	6.89	41.86	44.44	74.00	-29.56	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4924.00	37.80	31.25	6.89	41.86	34.08	54.00	-19.92	Vertical
4924.00	39.20	31.25	6.89	41.86	35.48	54.00	-18.52	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.


802.11n(HT40)								
Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	47.10	31.10	6.83	41.83	43.20	74.00	-30.80	Vertical
4844.00	48.47	31.10	6.83	41.83	44.57	74.00	-29.43	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4844.00	37.71	31.10	6.83	41.83	33.81	54.00	-20.19	Vertical
4844.00	38.27	31.10	6.83	41.83	34.37	54.00	-19.63	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	46.73	31.16	6.85	41.84	42.90	74.00	-31.10	Vertical
4874.00	48.47	31.16	6.85	41.84	44.64	74.00	-29.36	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4874.00	38.04	31.16	6.85	41.84	34.21	54.00	-19.79	Vertical
4874.00	38.49	31.16	6.85	41.84	34.66	54.00	-19.34	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	47.20	31.22	6.87	41.85	43.44	74.00	-30.56	Vertical
4904.00	48.27	31.22	6.87	41.85	44.51	74.00	-29.49	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4904.00	37.60	31.22	6.87	41.85	33.84	54.00	-20.16	Vertical
4904.00	38.76	31.22	6.87	41.85	35.00	54.00	-19.00	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

7 Test Setup Photo

Radiated Spurious Emission
Below 1GHz
External antenna



Above 1GHz
Internal antenna



External antenna**Conducted Emission**

8 EUT Constructional Details

Reference to the test report No.: CCISE190808001

-----End of report-----