

GitHub Actions — Reusable Workflow Layout

A reusable workflow is useful when you want to standardize the complete deployment pipeline across DEV and QA.

1. Recommended Layout

```
.github/  
├── workflows/  
│   ├── deploy.yml  
│   └── reusable-deploy.yml
```

2. deploy.yml — Select DEV or QA

```
name: Deploy Application  
  
on:  
  workflow_dispatch:  
    inputs:  
      environment:  
        description: Select environment  
        required: true  
        type: choice  
        options:  
          - DEV  
          - QA  
  
jobs:  
  deploy:  
    uses: ../github/workflows/reusable-deploy.yml  
    with:  
      environment: ${ inputs.environment }  
    secrets: inherit
```

3. reusable-deploy.yml — Complete Pipeline

```
name: Reusable Deploy  
  
on:  
  workflow_call:  
    inputs:  
      environment:  
        required: true  
        type: string  
  
jobs:  
  build:  
    runs-on: ubuntu-latest  
    steps:  
      - uses: actions/checkout@v4  
      - uses: actions/setup-dotnet@v4  
      - run: dotnet restore  
      - run: dotnet build --configuration Release --no-restore  
      - run: dotnet test --configuration Release --no-build  
  
  deploy:  
    needs: build  
    runs-on: ubuntu-latest  
    steps:  
      - uses: actions/checkout@v4  
      - run: echo "Deploying to ${ inputs.environment }"  
      - uses: azure/login@v2  
        with:  
          client-id: ${ secrets.AZURE_CLIENT_ID }  
          tenant-id: ${ secrets.AZURE_TENANT_ID }  
          subscription-id: ${ secrets.AZURE_SUBSCRIPTION_ID }  
      - uses: Azure/functions-action@v1  
        with:  
          app-name: ${ vars.AZURE_FUNCTION_APP_NAME }  
          package: .
```

4. Pipeline Flow

Stage	Purpose
deploy.yml	User selects DEV or QA
reusable-deploy.yml	Receives the selected environment
Build	Restore → Build → Test
Deploy	Azure Login → Azure Function deployment

Key idea: Reusable workflow = reusable job(s) / pipeline. Custom action = reusable steps.