

VIJAYA WATERPROOFING

H.No 7-1-75 Sree Sree Towers D.K Road Ameerpet Hyderabad 500016

Contact: 7675042117,

Date: 18-04-2025

To,
Mr Sai Raj,
Suchitra,
Hyderabad.

Dear Sir,

Sub: Quotation for the – Balcony, Bathroom Waterproofing Treatment.

Here by we are providing the Quotation for the above subject of work with most competitive price and suitable waterproofing system.

| S.NO | Description of the work | Units SFT | Price per SFT | Total Rs. |
|------|---|--------------------|---------------------|-----------------|
| 1. | <p>Balcony waterproofing tile joints waterproofing with Epoxy Grout (Pidilite Roff Epoxy)</p> <p>Product Description:</p> <p>Pidilite (Roff) Epoxy three component Epoxy Grout</p> <p>It is a three component epoxy resin based silica component used for joints.</p> <ul style="list-style-type: none">▪ Resistant to mild chemicals and acids▪ Non staining & easily cleaned▪ Resists bacterial growth <p>Application Methodology</p> <ul style="list-style-type: none">• SURFACE PREPARATION: Clean the surfaces thoroughly, it should be free from oil, grease, dust, dirt, fungus and moss.• Cut the Floor Tile/Granite joints 3mmx3mm and by using mechanical cutting machine.• Cleaning the joints with wire brush air blower to make the joints dust free.• Covering the joint edges with masking tape to avoid the spread of epoxy material apart from Floor Joints. | 610 SFT | 70/- | 42,700/- |

| | | | | |
|----|--|--------|--------|----------|
| | Mixing the Part-A , Part-B, Part-C resins as per manufacturers defined ratio Filling the above mixed Epoxy material in all the joints properly. | | | |
| 2. | Bathroom tile joints waterproofing with Epoxy Grout (Pidilite Roff Epoxy/ FOSROC EPW GROUT) Product Description: <p>Fosroc EPW Grout/Pidilite (Roff) Epoxy three component Epoxy Grout</p> <p>It is a three component epoxy resin based silica component used for joints.</p> <ul style="list-style-type: none"> ▪ Resistant to mild chemicals and acids ▪ Non staining & easily cleaned ▪ Resists bacterial growth Application Methodology <ul style="list-style-type: none"> • Cut the Floor Tile/Granite joints 3mmx3mm and by using mechanical cutting machine. • SURFACE PREPARATION: Clean the surfaces thoroughly, it should be free from oil, grease, dust, dirt, fungus and moss. • Cleaning the joints with wire brush air blower to make the joints dust free. • Covering the joint edges with masking tape to avoid the spread of epoxy material apart from Floor Joints. <p>Mixing the Part-A , Part-B, Part-C resins as per manufacturers defined ratio Filling the above mixed Epoxy material in all the joints properly.</p> | 06 NOS | 5000/- | 30,000/- |

Total : 72,700/-

(Seventy two thousand seven hundred rupees only)

1. The above quotation is including all materials and application.
2. Mode of Payment
3. 50% advance, 40% during work in progress, 10% payment after completion of work.

TEAM Vijaya.

Contractors & Engineer's- (Waterproofing & Structural Repairs).

Contact: 7675042117