Activities Terminal

v23be1

File Edit View Search Terminal Help

```
//command line arguements using atoi(CLIENT)................//

#include header.h
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./client server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in server_id;
        int sfd,len;
        ///////////*******SOCKET*********//
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
        ////////////*********CONNECT**********////
        server_id.sin_family=AF_INET;
        server_id.sin_port=htons(atoi(argv[1]));
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(connect(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("CONNECT");
                return 0;
        }
        perror("CONNECT");
        char s[20];
        while(1){
                int num;
        printf("enter the string\n");
        scanf("%s",s);
        write(sfd,s,strlen(s)+1);

        read(sfd,&num,sizeof(num));
        printf("%s\n",s);
        }
        close(sfd);
}
~
-- INSERT --
```

ties Terminal v2

File Edit View Search Terminal Help

```
//command line arguements using atoi program.(SERVER).....//

#include header.h"
void client_info(struct sockaddr_in client_info)
{
        printf("client port address:%d\n",client_info.sin_port);
        printf("client ip address:%s\n",inet_ntoa(client_info.sin_addr));
}
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./server server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in client_id,server_id;
        int sfd,len,nsfd;
        ///////SOCKET**********////////////////
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
        ///BIND**************////////////
        server_id.sin_family=AF_INET;
        server_id.sin_port=htons(atoi(argv[1]));
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(bind(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("BIND");
                return 0;
        }
        perror("BIND");
        /////////********listen********///
        if(listen(sfd,5)<0)
        {
                perror("LISTEN");
                return 0;
        }
        perror("LISTEN");
        //////////******ACCEPT**********//////
-- INSERT --
```

Terminal

File Edit View Search Terminal Help

```
        {
                perror("BIND");
                return 0;

        }
        perror("BIND");
        /////////********listen********///
        if(listen(sfd,5)<0)
        {
                perror("LISTEN");
                return 0;

        }
        perror("LISTEN");
        ///////////******ACCEPT***********//////
        printf("before accepting client request..........\n");
        nsfd=accept(sfd,(struct sockaddr*)&client_id,&len);
        if(nsfd<0)
        {
                perror("ACCEPT");
                return 0;

        }
        printf("after accepting request.......\n");
        client_info(client_id);
        char s[20];
        // int num=0,i=0;
        while(1){
            int num=0,i=0;
        read(nsfd,s,sizeof(s));
        if(s[0]=='-')
        i=1;
        for( ;s[i];i++)
        {
                if(s[i]>='0' && s[i]<='9')
                num=num*10+s[i]-48;
                else
                    break;
        }
        if(s[0]=='-')
                num=-num;
    printf("%d\n",num);
        write(nsfd,&num,sizeof(num));
        }
        close(sfd);
        close(nsfd);
}
-- INSERT --
```

Activities Terminal

Firefox Web Browser

File Edit View Search Terminal Help

```
//command line arguements using atof program(SERVER).........//

#include"header.h"
void client_info(struct sockaddr_in client_info)
{
        printf("client port address:%d\n",client_info.sin_port);
        printf("client ip address:%s\n",inet_ntoa(client_info.sin_addr));
}
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./server server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in client_id,server_id;
        int sfd,len,nsfd;
        ///////SOCKET**********////////////////
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
        ///BIND***************////////////
        server_id.sin_family=AF_INET;
        server_id.sin_port=htons(atoi(argv[1]));
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(bind(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("BIND");
                return 0;
        }
        perror("BIND");
        /////////********listen********///
        if(listen(sfd,5)<0)
        {
                perror("LISTEN");
                return 0;
        }
        perror("LISTEN");
        ///////////******ACCEPT**********//////
-- INSERT --
```

Activities Terminal

File Edit View Search Terminal Help

```
        ///////////********listen********///
        if(listen(sfd,5)<0)
        {
                perror("LISTEN");
                return 0;
        }
        perror("LISTEN");
        ///////////******ACCEPT***********//////
        printf("before accepting client request..........\n");
        nsfd=accept(sfd,(struct sockaddr*)&client_id,&len);
        if(nsfd<0)
        {
                perror("ACCEPT");
                return 0;
        }
        printf("after accepting request.......\n");
        client_info(client_id);
        char s[20];
        // int num=0,i=0;
        while(1){
            int num=0,i=0,c=0,d,num1=0;
            double f;
        read(nsfd,s,sizeof(s));
        if(s[0]=='-')
        i=1;
        for( ;s[i]!='.';i++)
        {
                if(s[i]>='0' && s[i]<='9')
                num=num*10+s[i]-48;
                else
                    break;
        }
        for(i++;s[i];i++)
        {
                if(s[i]>='0' &&s[i]<='9')
                {
                        num1=num1*10+s[i]-48;
                        c++;
                }
                else
                        break;
        }
        for(d=1;c;c--)
        d=d*10;
        f=(float)num1/(float)d;
//      printf("%f",f);
        f=num+f;

        if(s[0]=='-')
                f=-f;
    printf("%f\n",f);
        write(nsfd,&f,sizeof(f));
        }
        close(sfd);
        close(nsfd);
}
-- INSERT --
```

Activities Terminal

File Edit View Search Terminal Help

```c
//command line arguements using atof(CLIENT)................//

#include"header.h"
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./client server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in server_id;
        int sfd,len;
        ///////////*******SOCKET*********//
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
        ////////////*********CONNECT**********////
        server_id.sin_family=AF_INET;
        server_id.sin_port=htons(atoi(argv[1]));
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(connect(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("CONNECT");
                return 0;
        }
        perror("CONNECT");
        char s[20];
        while(1){
                int num;
                double f;
        printf("enter the string\n");
        scanf("%s",s);
        write(sfd,s,strlen(s)+1);
        //read(sfd,s,strlen(s));
        read(sfd,&f,sizeof(f));
    //    printf("%f\n",f);
        }
        close(sfd);
}
-- INSERT --
```

Activities Terminal

File Edit View Search Terminal Help

```c
//.............CLIENT CONVERT OPPOSITE CASE.............//

#include"header.h"
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./client server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in server_id;
        int sfd,len;
        ///////******SOCKET***********//
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
       ////**********BIND****************//
       server_id.sin_family=AF_INET;
       server_id.sin_port=htons(atoi(argv[1]));
       server_id.sin_addr.s_addr=inet_addr(argv[2]);
       len=sizeof(server_id);
       if(connect(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("CONNECT");
                return 0;
        }
        perror("CONNECT");
//      printf("after accepting request......\n");
        char s[20];
        while(1){
        printf("enter the msg\n");
        scanf("%s",s);
        // gets(s);
        write(sfd,s,strlen(s)+1);
        read(sfd,s,sizeof(s));
        printf("updated data:%s\n",s);
        }
        close(sfd);
}

-- INSERT --
```

Activities Terminal v23be1s1

File Edit View Search Terminal Help

```
//......using command line arguements to convert upper to lower(SERVER).............

#include"header.h"
void client_info(struct sockaddr_in client_info)
{
        printf("client port address:%d\n",client_info.sin_port);
        printf("client ip address:%s\n",inet_ntoa(client_info.sin_addr));
}
int main(int argc,char **argv)
{
        if(argc!=3)
        {
                printf("usage:./server server_port server_ip_addr\n");
                return 0;
        }
        struct sockaddr_in client_id,server_id;
        int sfd,len,nsfd;
        ///////******SOCKET************//
        sfd=socket(AF_INET,SOCK_STREAM,0);
        if(sfd<0)
        {
                perror("SOCKET");
                return 0;
        }
        perror("SOCKET");
        ////*********BIND*****************//
        server_id.sin_family=AF_INET;
        server_id.sin_port=htons(atoi(argv[1]));
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(bind(sfd,(struct sockaddr*)&server_id,len)<0)
        {
                perror("BIND");
                return 0;
        }
        perror("BIND");
        ///////////***LISTEN******.////////////////
        if(listen(sfd,5)<0)
        {
                perror("LISTEN");
                return 0;
        }
        perror("LISTEN");
        //////****ACCEPT***********//////////
-- INSERT --
```

Activities Terminal

File Edit View Search Terminal Help

```
        server_id.sin_addr.s_addr=inet_addr(argv[2]);
        len=sizeof(server_id);
        if(bind(sfd,(struct sockaddr*)&server_id,len)<0)
         {
                perror("BIND");
                return 0;
         }
         perror("BIND");
         ///////////***LISTEN******./////////////////
         if(listen(sfd,5)<0)
         {
                perror("LISTEN");
                return 0;
         }
         perror("LISTEN");
         //////****ACCEPT***********//////////
         printf("befor accepting request.....\n");
         nsfd=accept(sfd,(struct sockaddr*)&client_id,&len);
         if(nsfd<0)
         {
                perror("ACCEPT");
                return 0;
         }
         printf("after accepting request......\n");
         client_info(client_id);
         char s[20];
         int i;
//       client_info(client_id);
         while(1){
         read(nsfd,s,sizeof(s));
         printf("client data:%s\n",s);
         for(i=0;s[i];i++)
         {
                if(s[i]>='a' && s[i]<='z')
                s[i]=s[i]-32;
                else if(s[i]>='A' && s[i]<='Z')
                s[i]=s[i]+32;
         }
         write(nsfd,s,strlen(s)+1);
         }
         close(sfd);
         close(nsfd);
}
```

-- INSERT --