02/02/24 TCP/IP Imp

1. Difference b/w MAC & IP ?

2. Which protocol converts the IP @ to physical @

(a) RARP (b) DNS
(c) ICMP (d) ARP

3.
```
main()
{
    int a[5] = {1,3,6,7,0};
    int *b = &a[2];
    Pf("%d\n", b[-1]);
}
```

4. size of a port number ____

(i) 4 (ii) 2
(iii) 8 (iv) None

5.
```
#define Str(x) #x
#define Xstr(x) Str(x)
#define OP plus
main()
{
    char *opname = Xstr(OP);
    Pf("%s\n", opname);
}
```

6. What is the max. size of a datagram of IPv4 ____

7. What is the range of class D is ____

8. How classless IP @ represents.

9.
```
func(int i)
{
    if (i%2)
        return 0;
    else
        return 1;
}
main(){
    int i=3;
    i=func(i);
    i=func(i);
    Pf("%d\n", i); }
```

10. Which layer is responsible to encrypt & decrypt the user layer data in OSI reference model

(a) Application layer
(b) Session layer
(c) Presentation layer
(d) N/w layer.

11. Prototype of bind(), listen(), connect().

12. Port number of DNS ? ____

13. PDU of physical layer in TCP/IP

(a) data (b) bit
(c) frame (d) packet

14. Socket is using

(a) port no (b) interrupt no
(c) m/r @ (d) all

15. Difference b/w TCP & UDP

16. RFC of TCP

(a) 768 (b) 532
(c) 793 (d) 256

17.
```
static int a[] = {0,1,2,3,4};
static int *p[] = {a, a+1, a+2, a+3, a+4};
int **ptr = p;
**ptr++;
Pf("%d %d %d\n", ptr-p, *ptr-a, **ptr);

*++*ptr;
Pf("%d %d %d\n", ptr-p, *ptr-a, **ptr);
++**ptr;
Pf("%d %d %d\n", ptr-p, *ptr-a, **ptr);
```

Scanned with OKEN Scanner

18. What dest. @ can be used to send a packet from a host with IP @ 188.1.1.1 to all hosts and the n/w?

(a) 188.0.0.0

(b) 0.0.0.0

(c) 255.255.255.255.

(d) 188.1.255.255.

19. What is first octet range of class A IP @?

(a) 1-126 (b) 1-128

(c) 1-198 (d) None.

20. Hub operates in which layer of OSI _____

(a) Physical (b) Session

(c) Transport (d) Application.

21. OSI layer responsible for mail & file transfer?

(a) Transport (b) Data link

(c) Application (d) Physical

22. What is the use of NTP?

23. Port no. of HTTP _____

(a) 80 (b) 20

(c) 21 (d) 110

24. OSI layer packages bits into frames?

(a) Physical (b) DLL

(c) Network (d) Application.

25. Max. hop count _____

26. Class C contains _____

27. Private n/w range of class A _____

28. A Gateway works in which layer _____

(a) DLL (b) n/w

(c) Application (d) Physical.

29. IPV6 has ___ bit @'s

(a) 32 (b) 64

(c) 128. (d) Variable

30. Which protocol is used to send the mail _____.

Scanned with OKEN Scanner