

---

# **Amazon Simple Storage Service**

## **API Reference**

**API Version 2006-03-01**



# Amazon Web Services, LLC

## Amazon Simple Storage Service: API Reference

Amazon Web Services, LLC

Copyright © 2012 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

The following are trademarks or registered trademarks of Amazon: Amazon, Amazon.com, Amazon.com Design, Amazon DevPay, Amazon EC2, Amazon Web Services Design, AWS, CloudFront, EC2, Elastic Compute Cloud, Kindle, and Mechanical Turk. In addition, Amazon.com graphics, logos, page headers, button icons, scripts, and service names are trademarks, or trade dress of Amazon in the U.S. and/or other countries. Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon.

All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Welcome to Amazon S3 .....	1
Amazon S3 API Reference Introduction .....	2
Error Responses .....	3
REST API .....	11
Common Request Headers .....	12
Common Response Headers .....	14
Operations on the Service .....	15
GET Service .....	15
Operations on Buckets .....	18
DELETE Bucket .....	19
DELETE Bucket cors .....	21
DELETE Bucket lifecycle .....	23
DELETE Bucket policy .....	25
DELETE Bucket tagging .....	27
DELETE Bucket website .....	29
GET Bucket (List Objects) .....	31
GET Bucket acl .....	38
GET Bucket cors .....	41
GET Bucket lifecycle .....	44
GET Bucket policy .....	47
GET Bucket location .....	49
GET Bucket logging .....	51
GET Bucket notification .....	54
GET Bucket tagging .....	57
GET Bucket Object versions .....	60
GET Bucket requestPayment .....	72
GET Bucket versioning .....	74
GET Bucket website .....	77
HEAD Bucket .....	79
List Multipart Uploads .....	81
PUT Bucket .....	89
PUT Bucket acl .....	94
PUT Bucket cors .....	101
PUT Bucket lifecycle .....	106
PUT Bucket policy .....	112
PUT Bucket logging .....	114
PUT Bucket notification .....	119
PUT Bucket tagging .....	123
PUT Bucket requestPayment .....	126
PUT Bucket versioning .....	128
PUT Bucket website .....	132
Operations on Objects .....	139
DELETE Object .....	141
Delete Multiple Objects .....	144
GET Object .....	153
GET Object ACL .....	161
Versioning .....	161
GET Object torrent .....	165
HEAD Object .....	167
Versioning .....	167
OPTIONS object .....	172
POST Object .....	175
Versioning .....	175
POST Object restore .....	182
PUT Object .....	185
Versioning .....	185
PUT Object acl .....	194
PUT Object - Copy .....	201

Versioning .....	201
Initiate Multipart Upload .....	210
Upload Part .....	216
Upload Part - Copy .....	219
Complete Multipart Upload .....	224
Abort Multipart Upload .....	229
List Parts .....	231
SOAP API .....	236
Operations on the Service .....	236
ListAllMyBuckets .....	236
Operations on Buckets .....	238
CreateBucket .....	238
DeleteBucket .....	239
ListBucket .....	239
GetBucketAccessControlPolicy .....	242
SetBucketAccessControlPolicy .....	243
GetBucketLoggingStatus .....	244
SetBucketLoggingStatus .....	245
Operations on Objects .....	246
PutObjectInline .....	247
PutObject .....	249
CopyObject .....	252
GetObject .....	256
GetObjectExtended .....	261
DeleteObject .....	261
GetObjectAccessControlPolicy .....	262
SetObjectAccessControlPolicy .....	263
Amazon S3 Resources .....	265
Document History .....	267
Glossary .....	272
Index .....	274

# Welcome to Amazon S3

---

This is the *Amazon Simple Storage Service (Amazon S3) API Reference*. It explains the Amazon S3 API interface. It describes various API operations, related request and response structures, and error codes.

Amazon Simple Storage Service (Amazon S3) is a web service that enables you to store data in the cloud. You can then download the data or use the data with other AWS services, such as Amazon Elastic Cloud Computer (see [Amazon Elastic Compute Cloud \(Amazon EC2\)](#) ).

## How Do I...?

Information	Relevant Sections
General product overview and pricing	<a href="#">Amazon Simple Storage Service (Amazon S3)</a>
List of REST Operations	<a href="#">REST API (p. 11)</a>
List of SOAP Operations	<a href="#">SOAP API (p. 236)</a>
Amazon S3 Error codes and descriptions	<a href="#">List of Error Codes (p. 3)</a>

# Amazon S3 API Reference

## Introduction

---

This application programming interface reference explains Amazon S3 operations, their parameters, responses, and errors. There are separate sections for the REST and SOAP APIs, which include example requests and responses.

The location of the latest Amazon S3 WSDL is <http://doc.s3.amazonaws.com/2006-03-01/AmazonS3.wsdl>.

# Error Responses

---

This section provides reference information about Amazon S3 errors.

## List of Error Codes

The following table lists Amazon S3 error codes.

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
AccessDenied	Access Denied	403 Forbidden	Client
AccountProblem	There is a problem with your AWS account that prevents the operation from completing successfully. Please use <a href="#">Contact Us</a> .	403 Forbidden	Client
AmbiguousGrantByEmailAddress	The e-mail address you provided is associated with more than one account.	400 Bad Request	Client
BadDigest	The Content-MD5 you specified did not match what we received.	400 Bad Request	Client
BucketAlreadyExists	The requested bucket name is not available. The bucket namespace is shared by all users of the system. Please select a different name and try again.	409 Conflict	Client
BucketAlreadyOwnedByYou	Your previous request to create the named bucket succeeded and you already own it.	409 Conflict	Client
BucketNotEmpty	The bucket you tried to delete is not empty.	409 Conflict	Client



**Amazon Simple Storage Service API Reference**  
**List of Error Codes**

---

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
CredentialsNotSupported	This request does not support credentials.	400 Bad Request	Client
CrossLocationLoggingProhibited	Cross location logging not allowed. Buckets in one geographic location cannot log information to a bucket in another location.	403 Forbidden	Client
EntityTooSmall	Your proposed upload is smaller than the minimum allowed object size.	400 Bad Request	Client
EntityTooLarge	Your proposed upload exceeds the maximum allowed object size.	400 Bad Request	Client
ExpiredToken	The provided token has expired.	400 Bad Request	Client
IllegalVersioningConfigurationException	Indicates that the Versioning configuration specified in the request is invalid.	400 Bad Request	Client
IncompleteBody	You did not provide the number of bytes specified by the Content-Length HTTP header	400 Bad Request	Client
IncorrectNumberOfFilesInPostRequest	POST requires exactly one file upload per request.	400 Bad Request	Client
InlineDataTooLarge	Inline data exceeds the maximum allowed size.	400 Bad Request	Client
InternalServerError	We encountered an internal error. Please try again.	500 Internal Server Error	Server
InvalidAccessKeyId	The AWS Access Key Id you provided does not exist in our records.	403 Forbidden	Client
InvalidAddressingHeader	You must specify the Anonymous role.	N/A	Client
InvalidArgument	Invalid Argument	400 Bad Request	Client
InvalidBucketName	The specified bucket is not valid.	400 Bad Request	Client
InvalidBucketState	The request is not valid with the current state of the bucket.	409 Conflict	Client
InvalidDigest	The Content-MD5 you specified was an invalid.	400 Bad Request	Client

**Amazon Simple Storage Service API Reference**  
**List of Error Codes**

---

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
InvalidLocationConstraint	The specified location constraint is not valid. For more information about Regions, see <a href="#">How to Select a Region for Your Buckets</a> .	400 Bad Request	Client
InvalidObjectState	The operation is not valid for the current state of the object.	403 Forbidden	Client
InvalidPart	One or more of the specified parts could not be found. The part might not have been uploaded, or the specified entity tag might not have matched the part's entity tag.	400 Bad Request	Client
InvalidPartOrder	The list of parts was not in ascending order. Parts list must specified in order by part number.	400 Bad Request	Client
InvalidPayer	All access to this object has been disabled.	403 Forbidden	Client
InvalidPolicyDocument	The content of the form does not meet the conditions specified in the policy document.	400 Bad Request	Client
InvalidRange	The requested range cannot be satisfied.	416 Requested Range Not Satisfiable	Client
InvalidRequest	SOAP requests must be made over an HTTPS connection.	400 Bad Request	Client
InvalidSecurity	The provided security credentials are not valid.	403 Forbidden	Client
InvalidSOAPRequest	The SOAP request body is invalid.	400 Bad Request	Client
InvalidStorageClass	The storage class you specified is not valid.	400 Bad Request	Client
InvalidTargetBucketForLogging	The target bucket for logging does not exist, is not owned by you, or does not have the appropriate grants for the log-delivery group.	400 Bad Request	Client
InvalidToken	The provided token is malformed or otherwise invalid.	400 Bad Request	Client
InvalidURI	Couldn't parse the specified URI.	400 Bad Request	Client
KeyTooLong	Your key is too long.	400 Bad Request	Client

**Amazon Simple Storage Service API Reference**  
**List of Error Codes**

---

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
MalformedACLError	The XML you provided was not well-formed or did not validate against our published schema.	400 Bad Request	Client
MalformedPOSTRequest	The body of your POST request is not well-formed multipart/form-data.	400 Bad Request	Client
MalformedXML	This happens when the user sends a malformed xml (xml that doesn't conform to the published xsd) for the configuration. The error message is, "The XML you provided was not well-formed or did not validate against our published schema."	400 Bad Request	Client
MaxMessageLengthExceeded	Your request was too big.	400 Bad Request	Client
MaxPostPreDataLengthExceededError	Your POST request fields preceding the upload file were too large.	400 Bad Request	Client
MetadataTooLarge	Your metadata headers exceed the maximum allowed metadata size.	400 Bad Request	Client
MethodNotAllowed	The specified method is not allowed against this resource.	405 Method Not Allowed	Client
MissingAttachment	A SOAP attachment was expected, but none were found.	N/A	Client
MissingContentLength	You must provide the Content-Length HTTP header.	411 Length Required	Client
MissingRequestBodyError	This happens when the user sends an empty xml document as a request. The error message is, "Request body is empty."	400 Bad Request	Client
MissingSecurityElement	The SOAP 1.1 request is missing a security element.	400 Bad Request	Client
MissingSecurityHeader	Your request was missing a required header.	400 Bad Request	Client
NoLoggingStatusForKey	There is no such thing as a logging status sub-resource for a key.	400 Bad Request	Client
NoSuchBucket	The specified bucket does not exist.	404 Not Found	Client
NoSuchKey	The specified key does not exist.	404 Not Found	Client

**Amazon Simple Storage Service API Reference**  
**List of Error Codes**

---

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
NoSuchLifecycleConfiguration	The lifecycle configuration does not exist.	404 Not Found	Client
NoSuchUpload	The specified multipart upload does not exist. The upload ID might be invalid, or the multipart upload might have been aborted or completed.	404 Not Found	Client
NoSuchVersion	Indicates that the version ID specified in the request does not match an existing version.	404 Not Found	Client
NotImplemented	A header you provided implies functionality that is not implemented.	501 Not Implemented	Server
NotSignedUp	Your account is not signed up for the Amazon S3 service. You must sign up before you can use Amazon S3. You can sign up at the following URL: <a href="http://aws.amazon.com/s3">http://aws.amazon.com/s3</a>	403 Forbidden	Client
NotSuchBucketPolicy	The specified bucket does not have a bucket policy.	404 Not Found	Client
OperationAborted	A conflicting conditional operation is currently in progress against this resource. Please try again.	409 Conflict	Client
PermanentRedirect	The bucket you are attempting to access must be addressed using the specified endpoint. Please send all future requests to this endpoint.	301 Moved Permanently	Client
PreconditionFailed	At least one of the preconditions you specified did not hold.	412 Precondition Failed	Client
Redirect	Temporary redirect.	307 Moved Temporarily	Client
RestoreAlreadyInProgress	Object restore is already in progress.	409 Conflict	Client
RequestIsNotMultiPartContent	Bucket POST must be of the enclosure-type multipart/form-data.	400 Bad Request	Client
RequestTimeout	Your socket connection to the server was not read from or written to within the timeout period.	400 Bad Request	Client
RequestTimeTooSkewed	The difference between the request time and the server's time is too large.	403 Forbidden	Client
RequestTorrentOfBucketError	Requesting the torrent file of a bucket is not permitted.	400 Bad Request	Client

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
SignatureDoesNotMatch	The request signature we calculated does not match the signature you provided. Check your AWS Secret Access Key and signing method. For more information, see <a href="#">REST Authentication</a> and <a href="#">SOAP Authentication</a> for details.	403 Forbidden	Client
ServiceUnavailable	Please reduce your request rate.	503 Service Unavailable	Server
SlowDown	Please reduce your request rate.	503 Slow Down	Server
TemporaryRedirect	You are being redirected to the bucket while DNS updates.	307 Moved Temporarily	Client
TokenRefreshRequired	The provided token must be refreshed.	400 Bad Request	Client
TooManyBuckets	You have attempted to create more buckets than allowed.	400 Bad Request	Client
UnexpectedContent	This request does not support content.	400 Bad Request	Client
UnresolvableGrantByEmailAddress	The e-mail address you provided does not match any account on record.	400 Bad Request	Client
UserKeyMustBeSpecified	The bucket POST must contain the specified field name. If it is specified, please check the order of the fields.	400 Bad Request	Client

## REST Error Responses

When there is an error, the header information contains:

- Content-Type: application/xml
- An appropriate 3xx, 4xx, or 5xx HTTP status code

The body or the response also contains information about the error. The following sample error response shows the structure of response elements common to all REST error responses.

```
<?xml version="1.0" encoding="UTF-8"?>
<Error>
  <Code>NoSuchKey</Code>
  <Message>The resource you requested does not exist</Message>
  <Resource>/mybucket/myfoto.jpg</Resource>
```

```
<RequestId>4442587FB7D0A2F9</RequestId>  
</Error>
```

The following table explains the REST error response elements

Name	Description
<i>Code</i>	The error code is a string that uniquely identifies an error condition. It is meant to be read and understood by programs that detect and handle errors by type. For more information, see <a href="#">List of Error Codes (p. 3)</a> . Type: String Ancestor: Error
<i>Error</i>	Container for all error elements. Type: Container Ancestor: None
<i>Message</i>	The error message contains a generic description of the error condition in English. It is intended for a human audience. Simple programs display the message directly to the end user if they encounter an error condition they don't know how or don't care to handle. Sophisticated programs with more exhaustive error handling and proper internationalization are more likely to ignore the error message. Type: String Ancestor: Error
<i>RequestId</i>	ID of the request associated with the error. Type: String Ancestor: Error
<i>Resource</i>	The bucket or object that is involved in the error. Type: String Ancestor: Error

Many error responses contain additional structured data meant to be read and understood by a developer diagnosing programming errors. For example, if you send a Content-MD5 header with a REST PUT request that doesn't match the digest calculated on the server, you receive a BadDigest error. The error response also includes as detail elements the digest we calculated, and the digest you told us to expect. During development, you can use this information to diagnose the error. In production, a well-behaved program might include this information in its error log.

For information about general response elements, go to [Error Responses](#).

## SOAP Error Responses

In SOAP, an error result is returned to the client as a SOAP fault, with the HTTP response code 500. If you do not receive a SOAP fault, then your request was successful. The Amazon S3 SOAP fault code is comprised of a standard SOAP 1.1 fault code (either "Server" or "Client") concatenated with the Amazon S3-specific error code. For example: "Server.InternalError" or "Client.NoSuchBucket". The SOAP fault string element contains a generic, human readable error message in English. Finally, the SOAP fault detail element contains miscellaneous information relevant to the error.

For example, if you attempt to delete the object "Fred", which does not exist, the body of the SOAP response contains a "NoSuchKey" SOAP fault.

The following example shows a sample SOAP error response.

```
<soapenv:Body>
  <soapenv:Fault>
    <Faultcode>soapenv:Client.NoSuchKey</Faultcode>
    <Faultstring>The specified key does not exist.</Faultstring>
    <Detail>
      <Key>Fred</Key>
    </Detail>
  </soapenv:Fault>
</soapenv:Body>
```

The following table explains the SOAP error response elements

Name	Description
<i>Detail</i>	Container for the key involved in the error Type: Container Ancestor: Body.Fault
<i>Fault</i>	Container for error information. Type: Container Ancestor: Body
<i>Faultcode</i>	The fault code is a string that uniquely identifies an error condition. It is meant to be read and understood by programs that detect and handle errors by type. For more information, see <a href="#">List of Error Codes (p. 3)</a> . Type: String Ancestor: Body.Fault
<i>Faultstring</i>	The fault string contains a generic description of the error condition in English. It is intended for a human audience. Simple programs display the message directly to the end user if they encounter an error condition they don't know how or don't care to handle. Sophisticated programs with more exhaustive error handling and proper internationalization are more likely to ignore the fault string. Type: String Ancestor: Body.Fault
<i>Key</i>	Identifies the key involved in the error Type: String Ancestor: Body.Fault

# REST API

---

## Topics

- [Common Request Headers \(p. 12\)](#)
- [Common Response Headers \(p. 14\)](#)
- [Operations on the Service \(p. 15\)](#)
- [Operations on Buckets \(p. 18\)](#)
- [Operations on Objects \(p. 139\)](#)

This section contains information specific to the Amazon S3 REST API.

The examples in this guide use the newer virtual hosted-style method for accessing buckets instead of the path-style. Although the path-style is still supported for legacy applications, we recommend using the virtual-hosted style where applicable. For more information, see [Working with Amazon S3 Buckets](#)

The following example is a virtual hosted-style request that deletes the `puppy.jpg` file from the `mybucket` bucket.

```
DELETE /puppy.jpg HTTP/1.1
User-Agent: dotnet
Host: mybucket.s3.amazonaws.com
Date: Tue, 15 Jan 2008 21:20:27 +0000
x-amz-date: Tue, 15 Jan 2008 21:20:27 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:k3nL7gH3+PadhTEVn5EXAMPLE
```

The following example is a path-style version of the same request.

```
DELETE /mybucket/puppy.jpg HTTP/1.1
User-Agent: dotnet
Host: s3.amazonaws.com
Date: Tue, 15 Jan 2008 21:20:27 +0000
x-amz-date: Tue, 15 Jan 2008 21:20:27 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:k3nL7gH3+PadhTEVn5EXAMPLE
```



## Common Request Headers

The following table describes headers that can be used by various types of Amazon S3 REST requests.

Header Name	Description
Authorization	The information required for request authentication. For more information, go to <a href="#">The Authentication Header</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . For anonymous requests this header is not required.
Content-Length	Length of the message (without the headers) according to RFC 2616. This header is required for PUTs and operations that load XML, such as logging and ACLs.
Content-Type	The content type of the resource in case the request content in the body. Example: <code>text/plain</code>
Content-MD5	The base64 encoded 128-bit MD5 digest of the message (without the headers) according to RFC 1864. This header can be used as a message integrity check to verify that the data is the same data that was originally sent. Although it is optional, we recommend using the Content-MD5 mechanism as an end-to-end integrity check. For more information about REST request authentication, go to <a href="#">REST Authentication</a> in the <i>Amazon Simple Storage Service Developer Guide</i> .
Date	The current date and time according to the requester. Example: <code>Wed, 01 Mar 2009 12:00:00 GMT</code> . When you specify the <code>Authorization</code> header, you must specify either the <code>x-amz-date</code> or the <code>Date</code> header
Expect	When your application uses 100-continue, it does not send the request body until it receives an acknowledgment. If the message is rejected based on the headers, the body of the message is not sent. This header can be used only if you are sending a body. Valid Values: 100-continue
Host	For path-style requests, the value is <code>s3.amazonaws.com</code> . For virtual-style requests, the value is <code>BucketName.s3.amazonaws.com</code> . For more information, go to <a href="#">Virtual Hosting</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . This header is required for HTTP 1.1 (most toolkits add this header automatically); optional for HTTP/1.0 requests.
x-amz-date	The current date and time according to the requester. Example: <code>Wed, 01 Mar 2009 12:00:00 GMT</code> . When you specify the <code>Authorization</code> header, you must specify either the <code>x-amz-date</code> or the <code>Date</code> header. If you specify both, the value specified for the <code>x-amz-date</code> header takes precedence.

Header Name	Description
x-amz-security-token	<p>This header can be used in the following scenarios:</p> <ul style="list-style-type: none"><li>• <b>Provide security tokens for Amazon DevPay operations</b>—Each request that uses Amazon DevPay requires two <code>x-amz-security-token</code> headers: one for the product token and one for the user token. When Amazon S3 receives an authenticated request, it compares the computed signature with the provided signature. Improperly formatted multi-value headers used to calculate a signature can cause authentication issues</li><li>• <b>Provide security token when using temporary security credentials</b>—When making requests using temporary security credentials you obtained from IAM you must provide a security token using this header. To learn more about temporary security credentials, go to <a href="#">Making Requests</a>.</li></ul> <p>This header is required for requests that use Amazon DevPay and requests that are signed using temporary security credentials.</p>

## Common Response Headers

The following table describes response headers that are common to most AWS S3 responses.

Name	Description
Content-Length	The length in bytes of the body in the response. Type: String Default: None
Connection	specifies whether the connection to the server is open or closed. Type: Enum Valid Values: open   close Default: None
Date	The date and time Amazon S3 responded, for example, Wed, 01 Mar 2009 12:00:00 GMT. Type: String Default: None
ETag	The entity tag is a hash of the object. The ETag only reflects changes to the contents of an object, not its metadata. The ETag is determined when an object is created. For objects created by the PUT Object operation and the POST Object operation, the ETag is a quoted, 32-digit hexadecimal string representing the MD5 digest of the object data. For other objects, the ETag may or may not be an MD5 digest of the object data. If the ETag is not an MD5 digest of the object data, it will contain one or more non-hexadecimal characters and/or will consist of less than 32 or more than 32 hexadecimal digits. Type: String
Server	The name of the server that created the response. Type: String Default: AmazonS3
x-amz-delete-marker	Specifies whether the object returned was (true) or was not (false) a Delete Marker. Type: Boolean Valid Values: true   false Default: false
x-amz-id-2	A special token that helps AWS troubleshoot problems. Type: String Default: None
x-amz-request-id	A value created by Amazon S3 that uniquely identifies the request. In the unlikely event that you have problems with Amazon S3, AWS can use this value to troubleshoot the problem. Type: String Default: None

Name	Description
x-amz-version-id	<p>The version of the object. When you enable versioning, Amazon S3 generates a random number for objects added to a bucket. The value is UTF-8 encoded and URL ready. When you PUT an object in a bucket where versioning has been suspended, the version ID is always <code>null</code>.</p> <p>Type: String</p> <p>Valid Values: <code>null</code>   any URL-ready, UTF-8 encoded string</p> <p>Default: <code>null</code></p>

## Operations on the Service

### Topics

- [GET Service \(p. 15\)](#)

This section describes operations you can perform on the Amazon S3 service.

## GET Service

### Description

This implementation of the `GET` operation returns a list of all buckets owned by the authenticated sender of the request.

To authenticate a request, you must use a valid AWS Access Key ID that is registered with Amazon S3. Anonymous requests cannot list buckets, and you cannot list buckets that you did not create.

### Requests

#### Syntax

```
GET / HTTP/1.1
Host: s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Elements

Name	Description
<i>Bucket</i>	Container for bucket information. Type: Container Children: Name, CreationDate Ancestor: ListAllMyBucketsResult.Buckets
<i>Buckets</i>	Container for one or more buckets. Type: Container Children: Bucket Ancestor: ListAllMyBucketsResult
<i>CreationDate</i>	Date the bucket was created. Type: date ( of the form yyyy-mm-ddThh:mm:ss.timezone, e.g., 2009-02-03T16:45:09.000Z) Ancestor: ListAllMyBucketsResult.Buckets.Bucket
<i>DisplayName</i>	Bucket owner's display name. Type: String Ancestor: ListAllMyBucketsResult.Owner
<i>ID</i>	Bucket owner's user ID. Type: String Ancestor: ListAllMyBucketsResult.Owner
<i>ListAllMyBucketsResult</i>	Container for response. Type: Container Children: Owner, Buckets Ancestor: None
<i>Name</i>	Bucket's name. Type: String Ancestor: ListAllMyBucketsResult.Buckets.Bucket
<i>Owner</i>	Container for bucket owner information. Type: Container Ancestor: ListAllMyBucketsResult

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The GET operation on the Service endpoint (s3.amazonaws.com) returns a list of all of the buckets owned by the authenticated sender of the request.

```
GET / HTTP/1.1
Host: s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<ListAllMyBucketsResult xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Owner>
    <ID>bcaf1ffd86f461ca5fb16fd081034f</ID>
    <DisplayName>webfile</DisplayName>
  </Owner>
  <Buckets>
    <Bucket>
      <Name>quotes</Name>
      <CreationDate>2006-02-03T16:45:09.000Z</CreationDate>
    </Bucket>
    <Bucket>
      <Name>samples</Name>
      <CreationDate>2006-02-03T16:41:58.000Z</CreationDate>
    </Bucket>
  </Buckets>
</ListAllMyBucketsResult>
```

## Related Resources

- [GET Bucket \(List Objects\) \(p. 31\)](#)
- [GET Object \(p. 153\)](#)

# Operations on Buckets

## Topics

- [DELETE Bucket](#) (p. 19)
- [DELETE Bucket cors](#) (p. 21)
- [DELETE Bucket lifecycle](#) (p. 23)
- [DELETE Bucket policy](#) (p. 25)
- [DELETE Bucket tagging](#) (p. 27)
- [DELETE Bucket website](#) (p. 29)
- [GET Bucket \(List Objects\)](#) (p. 31)
- [GET Bucket acl](#) (p. 38)
- [GET Bucket cors](#) (p. 41)
- [GET Bucket lifecycle](#) (p. 44)
- [GET Bucket policy](#) (p. 47)
- [GET Bucket location](#) (p. 49)
- [GET Bucket logging](#) (p. 51)
- [GET Bucket notification](#) (p. 54)
- [GET Bucket tagging](#) (p. 57)
- [GET Bucket Object versions](#) (p. 60)
- [GET Bucket requestPayment](#) (p. 72)
- [GET Bucket versioning](#) (p. 74)
- [GET Bucket website](#) (p. 77)
- [HEAD Bucket](#) (p. 79)
- [List Multipart Uploads](#) (p. 81)
- [PUT Bucket](#) (p. 89)
- [PUT Bucket acl](#) (p. 94)
- [PUT Bucket cors](#) (p. 101)
- [PUT Bucket lifecycle](#) (p. 106)
- [PUT Bucket policy](#) (p. 112)
- [PUT Bucket logging](#) (p. 114)
- [PUT Bucket notification](#) (p. 119)
- [PUT Bucket tagging](#) (p. 123)
- [PUT Bucket requestPayment](#) (p. 126)
- [PUT Bucket versioning](#) (p. 128)
- [PUT Bucket website](#) (p. 132)

This section describes operations you can perform on Amazon S3 buckets.

### Note

For information about access policies, see [REST Access Policy](#) .

# DELETE Bucket

## Description

This implementation of the `DELETE` operation deletes the bucket named in the URI. All objects (including all object versions and Delete Markers) in the bucket must be deleted before the bucket itself can be deleted.

## Requests

### Syntax

```
DELETE / HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request deletes the bucket named "quotes".



```
DELETE / HTTP/1.1
Host: quotes.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

## Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: JuKZqmXuiwFeDQxhD7M8KtsKobSzWA1QEjLbTMTagkKdBX2z7I1/jGhDeJ3j6s80
x-amz-request-id: 32FE2CEB32F5EE25
Date: Wed, 01 Mar 2009 12:00:00 GMT
Connection: close
Server: AmazonS3
```

## Related Resources

- [PUT Bucket \(p. 89\)](#)
- [DELETE Object \(p. 141\)](#)

# DELETE Bucket cors

## Description

Deletes the `cors` configuration information set for the bucket.

To use this operation, you must have permission to perform the `s3:PutCORSCONfiguration` action. The bucket owner has this permission by default and can grant this permission to others.

For information more about `cors`, go to [Enabling Cross-Origin Resource Sharing](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
DELETE /?cors HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

## Examples

### Example 1: Retrieve cors subresource

The following DELETE request deletes the `cors` subresource from the specified bucket. This action removes `cors` configuration that is stored in the subresource.

#### Sample Request

```
DELETE /?cors HTTP/1.1
Host: examplebucket.s3.amazonaws.com
```

```
Date: Tue, 13 Dec 2011 19:14:42 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAAAAA=
```

### Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: 0FmFIWsh/PpBuzZ0JFRC55ZGVmQW4SHJ7xVDqKwhEdJmf3q63RtrvH8ZuxW1Bo15
x-amz-request-id: 0CF038E9BCF63097
Date: Tue, 13 Dec 2011 19:14:42 GMT
Server: AmazonS3
Content-Length: 0
```

### Related Resources

- [PUT Bucket cors](#) (p. 101)
- [DELETE Bucket cors](#) (p. 21)
- [OPTIONS object](#) (p. 172)

# DELETE Bucket lifecycle

## Description

Deletes the lifecycle configuration from the specified bucket. Amazon S3 removes all the lifecycle configuration rules in the lifecycle subresource associated with the bucket. Your objects never expire, and Amazon S3 no longer automatically deletes any objects on the basis of rules contained in the deleted lifecycle configuration.

To use this operation, you must have permission to perform the `s3:PutLifecycleConfiguration` action. By default, the bucket owner has this permission and the bucket owner can grant this permission to others.

There is usually some time lag before lifecycle configuration deletion is fully propagated to all the Amazon S3 systems.

For more information about the object expiration, go to [Object Expiration](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
DELETE /?lifecycle HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

## Examples

### Sample Request

The following DELETE request deletes the `lifecycle` subresource from the specified bucket. This removes lifecycle configuration stored in the subresource.

```
DELETE /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Date: Wed, 14 Dec 2011 05:37:16 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:k3nL7gH3+PadhTEVn5EXAMPLE
```

## Sample Response

The following successful response shows Amazon S3 returning a 204 No Content response. Objects in your bucket no longer expire.

```
HTTP/1.1 204 No Content
x-amz-id-2: Uuag1LuByRx9e6j5OnimrSAMPLEtRPfTaOAa==
x-amz-request-id: 656c76696e672SAMPLE5657374
Date: Wed, 14 Dec 2011 05:37:16 GMT
Connection: keep-alive
Server: AmazonS3
```

## Related Resources

- [PUT Bucket lifecycle \(p. 106\)](#)
- [GET Bucket lifecycle \(p. 44\)](#)

## DELETE Bucket policy

### Description

This implementation of the `DELETE` operation uses the *policy* subresource to delete the policy on a specified bucket. To use the operation, you must have *DeletePolicy* permissions on the specified bucket and be the bucket owner.

If you do not have *DeletePolicy* permissions, Amazon S3 returns a 403 `Access Denied` error. If you have the correct permissions, but are not the bucket owner, Amazon S3 returns a 405 `Method Not Allowed` error. If the bucket doesn't have a policy, Amazon S3 returns a 204 `No Content` error. There are restrictions about who can create bucket policies and which objects in a bucket they can apply to. For more information, go to [Using Bucket Policies](#).

### Requests

#### Syntax

```
DELETE /?policy HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

#### Request Parameters

This implementation of the operation does not use request parameters.

#### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

#### Request Elements

This implementation of the operation does not use request elements.

### Responses

#### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

#### Response Elements

The response elements contain the status of the `DELETE` operation including the error code if the request failed.

#### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request deletes the bucket named `BucketName`.

```
DELETE /?policy HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Tue, 04 Apr 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:k3nL7gH3+PadhTEVn5EXAMPLE
```

### Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: Uuag1LuByRx9e6j5OnimrSAMPLEtRPfTaOFg==
x-amz-request-id: 656c76696e672SAMPLE5657374
Date: Tue, 04 Apr 2010 20:34:56 GMT
Connection: keep-alive
Server: AmazonS3
```

## Related Resources

- [PUT Bucket](#) (p. 89)
- [DELETE Object](#) (p. 141)

# DELETE Bucket tagging

## Description

This implementation of the `DELETE` operation uses the *tagging* subresource to remove a tag set from the specified bucket.

To use this operation, you must have permission to perform the `s3:PutBucketTagging` action. By default, the bucket owner has this permission and can grant this permission to others.

## Requests

### Syntax

```
DELETE /?tagging HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

## Examples

### Sample Request

The following `DELETE` request deletes the tag set from the specified bucket.

```
DELETE /?tagging HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Date: Wed, 14 Dec 2011 05:37:16 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:k3nL7gH3+PadhTEVn5EXAMPLE
```



## Sample Response

The following successful response shows Amazon S3 returning a 204 No Content response. The tag set for the bucket has been removed.

```
HTTP/1.1 204 No Content
Date: Wed, 25 Nov 2009 12:00:00 GMT
Connection: close
Server: AmazonS3
```

## Related Resources

- [GET Bucket tagging \(p. 57\)](#)
- [PUT Bucket tagging \(p. 123\)](#)

# DELETE Bucket website

## Description

This operation removes the website configuration for a bucket. Amazon S3 returns a 200 OK response upon successfully deleting a website configuration on the specified bucket. You will get a 200 OK response if the website configuration you are trying to delete does not exist on the bucket. Amazon S3 returns a 404 response if the bucket specified in the request does not exist.

This DELETE operation requires the `S3:DeleteBucketWebsite` permission. By default, only the bucket owner can delete the *website* configuration attached to a bucket. However, bucket owners can grant other users permission to delete the *website* configuration by writing a bucket policy granting them the `S3:DeleteBucketWebsite` permission.

For more information about hosting websites, go to [Hosting Websites on Amazon S3](#) in the *Amazon S3 Developer Guide*.

## Requests

### Syntax

```
DELETE /?website HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

## Examples

### Sample Request

This request deletes the website configuration on the specified bucket.

```
DELETE ?website HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Thu, 27 Jan 2011 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sW0+ugzxhf2AtcqRLgy70B=
```

### Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: aws-s3integ-s3ws-31008.sea31.amazon.com
x-amz-request-id: AF1DD829D3B49707
Date: Thu, 03 Feb 2011 22:10:26 GMT
Server: AmazonS3
```

## Related Resources

- [GET Bucket website \(p. 77\)](#)
- [PUT Bucket website \(p. 132\)](#)

# GET Bucket (List Objects)

## Description

This implementation of the `GET` operation returns some or all (up to 1000) of the objects in a bucket. You can use the request parameters as selection criteria to return a subset of the objects in a bucket.

To use this implementation of the operation, you must have `READ` access to the bucket.

### Note

To get a list of your buckets, see [GET Service \(p. 15\)](#).

## Requests

### Syntax

```
GET / HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of `GET` uses the parameters in the following table to return a subset of the objects in a bucket.

Parameter	Description	Required
<i>delimiter</i>	A delimiter is a character you use to group keys. All keys that contain the same string between the <i>prefix</i> , if specified, and the first occurrence of the delimiter after the prefix are grouped under a single result element, <i>CommonPrefixes</i> . If you don't specify the <i>prefix</i> parameter, then the substring starts at the beginning of the key. The keys that are grouped under <i>CommonPrefixes</i> result element are not returned elsewhere in the response. Type: String Default: None	No
<i>marker</i>	Specifies the key to start with when listing objects in a bucket. Amazon S3 lists objects in alphabetical order. Type: String Default: None	No
<i>max-keys</i>	Sets the maximum number of keys returned in the response body. The response might contain fewer keys but will never contain more. If there are additional keys that satisfy the search criteria but were not returned because <i>max-keys</i> was exceeded, the response contains <code>&lt;IsTruncated&gt;true&lt;/IsTruncated&gt;</code> . To return the additional keys, see <i>marker</i> . Type: String Default: 1000	No

Parameter	Description	Required
<i>prefix</i>	Limits the response to keys that begin with the specified prefix. You can use prefixes to separate a bucket into different groupings of keys. (You can think of using <i>prefix</i> to make groups in the same way you'd use a folder in a file system.) Type: String Default: None	No

## Request Elements

This implementation of the operation does not use request elements.

## Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
Contents	Metadata about each object returned. Type: XML metadata Ancestor: ListBucketResult
CommonPrefixes	A response can contain <i>CommonPrefixes</i> only if you specify a <i>delimiter</i> . When you do, <i>CommonPrefixes</i> contains all (if there are any) keys between <i>Prefix</i> and the next occurrence of the string specified by <i>delimiter</i> . In effect, <i>CommonPrefixes</i> lists keys that act like subdirectories in the directory specified by <i>Prefix</i> . For example, if <i>prefix</i> is <i>notes/</i> and <i>delimiter</i> is a slash (/), in <i>notes/summer/july</i> , the common prefix is <i>notes/summer/</i> . All of the keys rolled up in a common prefix count as a single return when calculating the number of returns. See <i>MaxKeys</i> . Type: String Ancestor: ListBucketResult
Delimiter	Causes keys that contain the same string between the prefix and the first occurrence of the delimiter to be rolled up into a single result element in the <i>CommonPrefixes</i> collection. These rolled-up keys are not returned elsewhere in the response. Each rolled up result counts as only one return against the <i>MaxKeys</i> value. Type: String Ancestor: ListBucketResult

**Amazon Simple Storage Service API Reference**  
**GET Bucket (List Objects)**

---

Name	Description
DisplayName	Object owner's name. Type: String Ancestor: ListBucketResult.Contents.Owner
ETag	The entity tag is an MD5 hash of the object. The ETag only reflects changes to the contents of an object, not its metadata. Type: String Ancestor: ListBucketResult.Contents
ID	Object owner's ID. Type: String Ancestor: ListBucketResult.Contents.Owner
IsTruncated	Specifies whether ( <i>true</i> ) or not ( <i>false</i> ) all of the results were returned. All of the results may not be returned if the number of results exceeds that specified by <i>MaxKeys</i> . Type: String Ancestor: boolean
Key	The object's key. Type: String Ancestor: ListBucketResult.Contents
LastModified	Date and time the object was last modified. Type: Date Ancestor: ListBucketResult.Contents
Marker	Indicates where in the bucket to begin listing. Type: String Ancestor: ListBucketResult
MaxKeys	The maximum number of keys returned in the response body. Type: String Ancestor: ListBucketResult
Name	Name of the bucket. Type: String Ancestor: ListBucketResult
Owner	Bucket owner. Type: String Children: DisplayName, ID Ancestor: ListBucketResult.Contents   CommonPrefixes
Prefix	Keys that begin with the indicated prefix. Type: String Ancestor: ListBucketResult

Name	Description
Size	Size in bytes of the object. Type: String Ancestor: ListBucketResult.Contents
StorageClass	STANDARD   REDUCED_REDUNDANCY   GLACIER Type: String Ancestor: ListBucketResult.Contents

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request returns the objects in *BucketName*.

```
GET / HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
```

### Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>bucket</Name>
  <Prefix/>
  <Marker/>
  <MaxKeys>1000</MaxKeys>
  <IsTruncated>>false</IsTruncated>
  <Contents>
    <Key>my-image.jpg</Key>
    <LastModified>2009-10-12T17:50:30.000Z</LastModified>
    <ETag>"fba9dede5f27731c9771645a39863328"</ETag>
    <Size>434234</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
      <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
      <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
  </Contents>
  <Contents>
    <Key>my-third-image.jpg</Key>
    <LastModified>2009-10-12T17:50:30.000Z</LastModified>
    <ETag>"1b2cf535f27731c974343645a3985328"</ETag>
    <Size>64994</Size>
```

```
<StorageClass>STANDARD</StorageClass>
<Owner>
  <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
  <DisplayName>mtd@amazon.com</DisplayName>
</Owner>
</Contents>
</ListBucketResult>
```

## Sample Request Using Request Parameters

This example lists up to 40 keys in the "quotes" bucket that start with "N" and occur lexicographically after "Ned".

```
GET /?prefix=N&marker=Ned&max-keys=40 HTTP/1.1
Host: quotes.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: gyB+3jRPnrkN98ZajxHXr3u7EFM67bNgSaxexeEHndCX/7GRnfTXxReKUQF28IfP
x-amz-request-id: 3B3C7C725673C630
Date: Wed, 01 Mar 2009 12:00:00 GMT
Content-Type: application/xml
Content-Length: 302
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>quotes</Name>
  <Prefix>N</Prefix>
  <Marker>Ned</Marker>
  <MaxKeys>40</MaxKeys>
  <IsTruncated>>false</IsTruncated>
  <Contents>
    <Key>Nelson</Key>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>&quot;828ef3fdfa96f00ad9f27c383fc9ac7f&quot;</ETag>
    <Size>5</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
      <ID>bcaf161ca5fb16fd081034f</ID>
      <DisplayName>webfile</DisplayName>
    </Owner>
  </Contents>
  <Contents>
    <Key>Neo</Key>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>&quot;828ef3fdfa96f00ad9f27c383fc9ac7f&quot;</ETag>
    <Size>4</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
```



```
<ID>bcaflffd86a5fbl6fd081034f</ID>
<DisplayName>webfile</DisplayName>
</Owner>
</Contents>
</ListBucketResult>
```

## Sample Request Using Prefix and Delimiter

Assume you have the following keys in your bucket.

sample.jpg

photos/2006/January/sample.jpg

photos/2006/February/sample2.jpg

photos/2006/February/sample3.jpg

photos/2006/February/sample4.jpg

The following GET request specifies the delimiter parameter with value "/".

```
GET /?delimiter=/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

The key *sample.html* does not contain the delimiter character, and Amazon S3 returns it in the *Contents* element in the response. However, all other keys contain the delimiter character. Amazon S3 groups these keys and return a single *CommonPrefixes* element with prefix value *photos/* that is a substring from the beginning of these keys to the first occurrence of the specified delimiter.

```
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>example-bucket</Name>
  <Prefix></Prefix>
  <Marker></Marker>
  <MaxKeys>1000</MaxKeys>
  <Delimiter></Delimiter>
  <IsTruncated>>false</IsTruncated>
  <Contents>
    <Key>sample.html</Key>
    <LastModified>2011-02-26T01:56:20.000Z</LastModified>
    <ETag>"bfl d737a4d46a19f3bcd6905cc8b902"</ETag>
    <Size>142863</Size>
    <Owner>
      <ID>canonical-user-id</ID>
      <DisplayName>display-name</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
  </Contents>
  <CommonPrefixes>
    <Prefix>photos/</Prefix>
  </CommonPrefixes>
</ListBucketResult>
```

The following GET request specifies the `delimiter` parameter with value `/`, and the `prefix` parameter with value `photos/2006/`.

```
GET /?prefix=photos/2006/&delimiter=/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

In response, Amazon S3 returns only the keys that start with the specified prefix. Further, it uses the *delimiter* character to group keys that contain the same substring until the first occurrence of the *delimiter* character after the specified prefix. For each such key group Amazon S3 returns one `<CommonPrefixes>` element in the response. The keys grouped under this *CommonPrefixes* element are not returned elsewhere in the response. The value returned in the *CommonPrefixes* element is a substring from the beginning of the key to the first occurrence of the specified delimiter after the prefix.

```
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>example-bucket</Name>
  <Prefix>photos/2006/</Prefix>
  <Marker></Marker>
  <MaxKeys>1000</MaxKeys>
  <Delimiter>/</Delimiter>
  <IsTruncated>>false</IsTruncated>

  <CommonPrefixes>
    <Prefix>photos/2006/feb/</Prefix>
  </CommonPrefixes>
  <CommonPrefixes>
    <Prefix>photos/2006/jan/</Prefix>
  </CommonPrefixes>
</ListBucketResult>
```

## Related Resources

- [GET Object \(p. 153\)](#)
- [PUT Object \(p. 185\)](#)
- [PUT Bucket \(p. 89\)](#)

# GET Bucket acl

## Description

This implementation of the `GET` operation uses the `acl` subresource to return the access control list (ACL) of a bucket. To use `GET` to return the ACL of the bucket, you must have `READ_ACP` access to the bucket. If `READ_ACP` permission is granted to the anonymous user, you can return the ACL of the bucket without using an authorization header.

## Requests

### Syntax

```
GET /?acl HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
<code>AccessControlList</code>	Container for ACL information. Type: Container Ancestry: <code>AccessControlPolicy</code>
<code>AccessControlPolicy</code>	Container for the response. Type: Container Ancestry: None

Name	Description
DisplayName	Bucket owner's display name. This is returned only if the owner's e-mail address (or the forum name, if configured) can be determined from the <i>ID</i> . Type: String Ancestry: AccessControlPolicy.Owner
Grant	Container for <i>Grantee</i> and <i>Permission</i> . Type: Container Ancestry: AccessControlPolicy.AccessControlList
Grantee	Container for <i>DisplayName</i> and <i>ID</i> of the person being granted permissions. Type: Container Ancestry: AccessControlPolicy.AccessControlList.Grant
ID	Bucket owner's ID. Type: String Ancestry: AccessControlPolicy.Owner
Owner	Container for bucket owner information. Type: Container Ancestry: AccessControlPolicy
Permission	Permission given to the <i>Grantee</i> for bucket. Type: String Valid Values: FULL_CONTROL   WRITE   WRITE_ACP   READ   READ_ACP Ancestry: AccessControlPolicy.AccessControlList.Grant

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the ACL of the specified bucket.

```
GET ?acl HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
```

```
x-amz-request-id: 318BC8BC148832E5
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
Content-Length: 124
Content-Type: text/plain
Connection: close
Server: AmazonS3

<AccessControlPolicy>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>CustomersName@amazon.com</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

        <DisplayName>CustomersName@amazon.com</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Related Resources

- [GET Bucket Objects \(p. 31\)](#)

# GET Bucket cors

## Description

Returns the *cors* configuration information set for the bucket.

To use this operation, you must have permission to perform the `s3:GetCORSCONFIGURATION` action. By default, the bucket owner has this permission and can grant it to others.

To learn more *cors*, go to [Enabling Cross-Origin Resource Sharing](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
GET /?cors HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

This implementation of `GET` returns the following response elements.

Name	Description
<i>CORSCONFIGURATION</i>	Container for up to 100 <i>CORSRules</i> elements. Type: Container Children: <i>CORSRules</i> Ancestor: None

Name	Description
<i>CORSRule</i>	<p>A set of origins and methods (cross-origin access that you want to allow).. You can add up to 100 rules to the configuration.</p> <p>Type: Container</p> <p>Children: AllowedOrigin, AllowedMethod, MaxAgeSeconds, ExposeHeader, ID.</p> <p>Ancestor: CORSConfiguration</p>
<i>AllowedHeader</i>	<p>Specifies which headers are allowed in a pre-flight OPTIONS request through the Access-Control-Request-Headers header. Each header name specified in the Access-Control-Request-Headers must have a corresponding entry in the rule. Only the headers that were requested will be sent back. This element can contain at most one * wildcard character.</p> <p>A CORSRule can have at most one <i>MaxAgeSeconds</i> element.</p> <p>Type: Integer (seconds)</p> <p>Ancestor: CORSRule</p>
<i>AllowedMethod</i>	<p>Identifies an HTTP method that the domain/origin specified in the rule is allowed to execute.</p> <p>Each <i>CORSRule</i> must contain at least one <i>AllowedMethod</i> and one <i>AllowedOrigin</i> element.</p> <p>Type: Enum (GET, PUT, HEAD, POST, DELETE)</p> <p>Ancestor: CORSRule</p>
<i>AllowedOrigin</i>	<p>One or more response headers that you want customers to be able to access from their applications (for example, from a JavaScript XMLHttpRequest object).</p> <p>Each <i>CORSRule</i> must have at least one <i>AllowedOrigin</i> element. The string value can include at most one '*' wildcard character, for example, http://*.example.com". You can also specify only "*" to allow cross-origin access for all domains/origins.</p> <p>Type: String</p> <p>Ancestor: CORSRule</p>
<i>ExposeHeader</i>	<p>One or more headers in the response that you want customers to be able to access from their applications (for example, from a JavaScript XMLHttpRequest object).</p> <p>You add one <i>ExposeHeader</i> in the rule for each header.</p> <p>Type: String</p> <p>Ancestor: CORSRule</p>
<i>ID</i>	<p>An optional unique identifier for the rule. The ID value can be up to 255 characters long. The IDs help you find a rule in the configuration.</p> <p>Type: String</p> <p>Ancestor: CORSRule</p>
<i>MaxAgeSeconds</i>	<p>The time in seconds that your browser is to cache the preflight response for the specified resource.</p> <p>A CORSRule can have at most one <i>MaxAgeSeconds</i> element.</p> <p>Type: Integer (seconds)</p> <p>Ancestor: CORSRule</p>

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Example 1: Retrieve cors subresource

The following example gets the `cors` subresource of a bucket.

#### Sample Request

```
GET /?cors HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Date: Tue, 13 Dec 2011 19:14:42 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAAAAA=
```

#### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: 0FmFIWsh/PpBuzZ0JFRC55ZGVmQW4SHJ7xVDqKwhEdJmf3q63RtrvH8ZuxW1Bo15
x-amz-request-id: 0CF038E9BCF63097
Date: Tue, 13 Dec 2011 19:14:42 GMT
Server: AmazonS3
Content-Length: 280

<CORSConfiguration>
  <CORSRule>
    <AllowedOrigin>http://www.example.com</AllowedOrigin>
    <AllowedMethod>GET</AllowedMethod>
    <MaxAgeSeconds>3000</MaxAgeSec>
    <ExposeHeader>x-amz-server-side-encryption</ExposeHeader>
  </CORSRule>
</CORSConfiguration>
```

## Related Resources

- [PUT Bucket cors \(p. 101\)](#)
- [DELETE Bucket cors \(p. 21\)](#)
- [OPTIONS object \(p. 172\)](#)



# GET Bucket lifecycle

## Description

Returns the *lifecycle* configuration information set on the bucket.

To use this operation, you must have permission to perform the `s3:GetLifecycleConfiguration` action. The bucket owner has this permission, by default. The bucket owner can grant this permission to others.

To learn more about object expiration, go to [Object Lifecycle Management](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
GET /?lifecycle HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

This implementation of `GET` returns the following response elements.

Name	Description
<i>Date</i>	Indicates when the specific rule take effect.  The date value must conform to the ISO 8601 format. The time is always midnight UTC. Type: String Ancestor: Expiration or Transition

Name	Description
<i>Days</i>	Indicates the number of days after creation when the specific rule take effect. Type: non-negative integer Ancestor: Expiration or Transition
<i>Expiration</i>	Container for the object expiration rule. Type: Container Children: Days or Date Ancestor: Rule
<i>ID</i>	Unique identifier for the rule. The value cannot be longer than 255 characters. Type: String Ancestor: Rule
<i>LifecycleConfiguration</i>	Container for lifecycle rules. You can add as many as 1000 rules. Type: Container Children: Rule Ancestor: None
<i>Prefix</i>	Object key prefix identifying one or more objects to which the rule applies. Type: String Ancestor: Rule
<i>Rule</i>	Container for a lifecycle rule. Type: Container Ancestor: LifecycleConfiguration
<i>Status</i>	If Enabled, Amazon S3 executes the rule as scheduled. If Disabled, Amazon S3 ignores the rule. Type: String Ancestor: Rule
<i>Transition</i>	Container for the transition rule that describes when objects transition to the Glacier storage class. Type: Container Ancestor: Rule
<i>StorageClass</i>	Indicates the Amazon S3 storage class to which you want the object to transition to. Type: String Ancestor: Transition

## Special Errors

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
NoSuchLifecycleConfiguration	The lifecycle configuration does not exist.	404 Not Found	Client

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Example 1: Retrieve lifecycle subresource

The following GET request retrieves the `lifecycle` subresource from the specified bucket. Amazon S3 returns the lifecycle configuration in the response body.

#### Sample Request

```
GET /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Thu, 15 Nov 2012 00:17:21 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAAAAA=
```

#### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: ITnGTly4RyTmXa3rPi4hklTXouTf0hccUjo0iCPjz6FnfIutBj3M7fPglWO2SEWp
x-amz-request-id: 51991C342C575321
Date: Thu, 15 Nov 2012 00:17:23 GMT
Server: AmazonS3
Content-Length: 358

<?xml version="1.0" encoding="UTF-8"?>
<LifecycleConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Rule>
    <ID>Archive and then delete rule</ID>
    <Prefix>projectdocs</Prefix>
    <Status>Enabled</Status>
    <Transition>
      <Days>365</Days>
      <StorageClass>GLACIER</StorageClass>
    </Transition>
    <Expiration>
      <Days>3650</Days>
    </Expiration>
  </Rule>
</LifecycleConfiguration>
```

## Related Resources

- [PUT Bucket lifecycle \(p. 106\)](#)
- [DELETE Bucket lifecycle \(p. 23\)](#)

# GET Bucket policy

## Description

This implementation of the `GET` operation uses the *policy* subresource to return the policy of a specified bucket. To use this operation, you must have `GetPolicy` permissions on the specified bucket, and you must be the bucket owner.

If you don't have `GetPolicy` permissions, Amazon S3 returns a 403 `Access Denied` error. If you have the correct permissions, but you're not the bucket owner, Amazon S3 returns a 405 `Method Not Allowed` error. If the bucket does not have a policy, Amazon S3 returns a 404 `Policy Not found` error. There are restrictions about who can create bucket policies and which objects in a bucket they can apply to. For more information, go to [Using Bucket Policies](#).

## Requests

### Syntax

```
GET /?policy HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

The response contains the (JSON) policy of the specified bucket.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the policy of the specified bucket.

```
GET ?policy HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByru9pO4SAMPLEAtRPfTaOFg==
x-amz-request-id: 656c76696e67SAMPLE57374
Date: Tue, 04 Apr 2010 20:34:56 GMT
Connection: keep-alive
Server: AmazonS3

{
  "Version": "2008-10-17",
  "Id": "aaaa-bbbb-cccc-dddd",
  "Statement" : [
    {
      "Effect": "Deny",
      "Sid": "1",
      "Principal" : {
        "AWS": [ "111122223333", "444455556666" ]
      },
      "Action": [ "s3:*" ],
      "Resource": "arn:aws:s3:::bucket/*"
    }
  ]
}
```

## Related Resources

- [GET Bucket Objects \(p. 31\)](#)

# GET Bucket location

## Description

This implementation of the `GET` operation uses the *location* subresource to return a bucket's Region. You set the bucket's Region using the *LocationConstraint* request parameter in a *PUT Bucket* request. For more information, see [PUT Bucket \(p. 89\)](#).

To use this implementation of the operation, you must be the bucket owner.

## Requests

### Syntax

```
GET /?location HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
<i>LocationConstraint</i>	<p>Specifies the Region where the bucket resides. For more information about region endpoints and location constraints, go to <a href="#">Regions and Endpoints</a> in the <i>Amazon Web Services Glossary</i>.</p> <p>Type: String</p> <p>Valid Values: EU   eu-west-1   us-west-1   us-west-2   ap-southeast-1   ap-southeast-2   ap-northeast-1   sa-east-1   empty string (for the US Classic Region)</p> <p>Ancestry: None</p>

When the bucket's Region is US Classic, Amazon S3 returns an empty string for the bucket's Region:

```
<LocationConstraint xmlns="http://s3.amazonaws.com/doc/2006-03-01/" />
```

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

### Examples

#### Sample Request

The following request returns the Region of the specified bucket.

```
GET /?location HTTP/1.1
Host: myBucket.s3.amazonaws.com
Date: Tue, 09 Oct 2007 20:26:04 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:JUtd9kkJFjbKbkP9f6T/tAxozYY=
```

#### Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<LocationConstraint xmlns="http://s3.amazonaws.com/doc/2006-03-01/">EU</LocationConstraint>
```

### Related Resources

- [GET Bucket Objects \(p. 31\)](#)
- [PUT Bucket \(p. 89\)](#)

# GET Bucket logging

## Note

Logging functionality is currently in beta.

## Description

This implementation of the `GET` operation uses the *logging* subresource to return the logging status of a bucket and the permissions users have to view and modify that status. To use `GET`, you must be the bucket owner.

## Requests

### Syntax

```
GET /?logging HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signature
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
BucketLoggingStatus	Container for the response. Type: Container Ancestry: None
EmailAddress	E-mail address of the person whose logging permissions are displayed. Type: String Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant.Grantee



Name	Description
Grant	Container for <i>Grantee</i> and <i>Permission</i> . Type: Container Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants
Grantee	Container for <i>EmailAddress</i> of the person whose logging permissions are displayed. Type: Container Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant
LoggingEnabled	Container for logging information. This element and its children are present when logging is enabled, otherwise, this element and its children are absent. Type: Container Ancestry: BucketLoggingStatus
Permission	Logging permissions assigned to the <i>Grantee</i> for the bucket. Type: String Valid Values: FULL_CONTROL   READ   WRITE Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant
TargetBucket	Specifies the bucket whose logging status is being returned. This element specifies the bucket where server access logs will be delivered. Type: String Ancestry: BucketLoggingStatus.LoggingEnabled
TargetGrants	Container for granting information. Type: Container Ancestry: BucketLoggingStatus.LoggingEnabled
TargetPrefix	Specifies the prefix for the keys that the log files are being stored under. Type: String Ancestry: BucketLoggingStatus.LoggingEnabled

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the logging status for *mybucket*.

```
GET ?logging HTTP/1.1
Host: mybucket.s3.amazonaws.com
Date: Wed, 25 Nov 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response Showing an Enabled Logging Status

```
HTTP/1.1 200 OK
Date: Wed, 25 Nov 2009 12:00:00 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<BucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <LoggingEnabled>
    <TargetBucket>mybucketlogs</TargetBucket>
    <TargetPrefix>mybucket-access_log-</TargetPrefix>
    <TargetGrants>
      <Grant>
        <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
          xsi:type="AmazonCustomerByEmail">
          <EmailAddress>user@company.com</EmailAddress>
        </Grantee>
        <Permission>READ</Permission>
      </Grant>
    </TargetGrants>
  </LoggingEnabled>
</BucketLoggingStatus>
```

## Sample Response Showing a Disabled Logging Status

```
HTTP/1.1 200 OK
Date: Wed, 25 Nov 2009 12:00:00 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<BucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01" />
```

## Related Resources

- [PUT Bucket \(p. 89\)](#)
- [PUT Bucket logging \(p. 114\)](#)

# GET Bucket notification

## Description

This implementation of the `GET` operation uses the *notification* subresource to return the notification configuration of a bucket. Currently, the *s3:ReducedRedundancyLostObject* event is the only event supported for notifications. The *s3:ReducedRedundancyLostObject* event is triggered when Amazon S3 detects that it has lost all replicas of a Reduced Redundancy Storage object and can no longer service requests for that object.

If notifications are not enabled on the bucket, the operation returns an empty `NotificationConfiguration` element.

By default, you must be the bucket owner to read the notification configuration of a bucket. However, the bucket owner can use a bucket policy to grant permission to other users to read this configuration with the *s3:GetBucketNotification* permission.

For more information about setting and reading the notification configuration on a bucket, see [Setting Up Notification of Bucket Events](#). For more information about bucket policies, see [Using Bucket Policies](#).

## Requests

### Syntax

```
GET /?notification HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

## Response Elements

Name	Description
<i>NotificationConfiguration</i>	Container for specifying the notification configuration of the bucket. If this element is empty, the bucket's notifications are turned off. Type: Container Children: <i>TopicConfiguration</i> Ancestry: None
<i>TopicConfiguration</i>	Container for specifying the topic configuration for the notification. Currently, only one topic can be configured for notifications. Type: Container Children: <i>Topic</i> , <i>Event</i> Ancestry: <i>NotificationConfiguration</i>
<i>Topic</i>	Amazon SNS topic to which Amazon S3 will publish a message to report the specified events for the bucket. Type: String Ancestry: <i>TopicConfiguration</i>
<i>Event</i>	Bucket event to send notifications for. Currently, <i>s3:ReducedRedundancyLostObject</i> is the only event supported for notifications. Type: String Valid Values: <i>s3:ReducedRedundancyLostObject</i> Ancestry: <i>TopicConfiguration</i>

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request returns the notification configuration on bucket quotes.s3.amazonaws.com.

```
GET ?notification HTTP/1.1
Host: quotes.s3.amazonaws.com
Date: Wed, 09 June 2010 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

This response returns that the notification configuration for the specified bucket.

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMgUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A02
Date: Wed, 02 Jun 2010 12:00:00 GMT
Connection: close
Server: AmazonS3
<NotificationConfiguration>
  <TopicConfiguration>
    <Topic>arn:aws:sns:us-east-1:123456789012:myTopic</Topic>
    <Event>s3:ReducedRedundancyLostObject</Event>
  </TopicConfiguration>
</NotificationConfiguration>
```

## Related Resources

- [PUT Bucket notification \(p. 119\)](#)

# GET Bucket tagging

## Description

This implementation of the GET operation uses the *tagging* subresource to return the tag set associated with the bucket.

To use this operation, you must have permission to perform the `s3:GetBucketTagging` action. By default, the bucket owner has this permission and can grant this permission to others.

## Requests

### Syntax

```
GET /?tagging HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
Tagging	Contains the TagSet and Tag elements. Type: Container Ancestry: None
TagSet	Contains the tag set. Type: Container Ancestry: Tagging

Name	Description
Tag	Contains the tag information. Type: Container Ancestry: TagSet
Key	Name of the tag Type: String Ancestry: Tag
Value	Value of the tag Type: String Ancestry: Tag

## Special Errors

- NoSuchTagSetError - There is no tag set associated with the bucket.

## Examples

### Sample Request

The following request returns the tag set of the specified bucket.

```
GET ?tagging HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 25 Nov 2009 12:00:00 GMT
Connection: close
Server: AmazonS3

<Tagging>
  <TagSet>
    <Tag>
      <Key>Project</Key>
      <Value>Project One</Value>
    </Tag>
    <Tag>
      <Key>User</Key>
      <Value>jsmith</Value>
    </Tag>
  </TagSet>
</Tagging>
```

## Related Resources

- [PUT Bucket tagging \(p. 123\)](#)

- [DELETE Bucket tagging \(p. 27\)](#)



# GET Bucket Object versions

## Description

You can use the *versions* subresource to list metadata about all of the versions of objects in a bucket. You can also use request parameters as selection criteria to return metadata about a subset of all the object versions. For more information, see [Request Parameters](#) (p. 60).

To use this operation, you must have `READ` access to the bucket.

## Requests

### Syntax

```
GET /?versions HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of `GET` uses the parameters in the following table to return a subset of the objects in a bucket.

Parameter	Description	Required
<i>delimiter</i>	A delimiter is a character that you specify to group keys. All keys that contain the same string between the <i>prefix</i> and the first occurrence of the delimiter are grouped under a single result element in <i>CommonPrefixes</i> . These groups are counted as one result against the <i>max-keys</i> limitation. These keys are not returned elsewhere in the response. Also, see <i>prefix</i> . Type: String Default: None	No
<i>key-marker</i>	Specifies the key in the bucket that you want to start listing from. Also, see <i>version-id-marker</i> . Type: String Default: None	No
<i>max-keys</i>	Sets the maximum number of keys returned in the response body. The response might contain fewer keys, but will never contain more. If additional keys satisfy the search criteria, but were not returned because <i>max-keys</i> was exceeded, the response contains <code>&lt;isTruncated&gt;true&lt;/isTruncated&gt;</code> . To return the additional keys, see <i>key-marker</i> and <i>version-id-marker</i> . Type: String Default: 1000	No

Parameter	Description	Required
<i>prefix</i>	Use this parameter to select only those keys that begin with the specified prefix. You can use prefixes to separate a bucket into different groupings of keys. (You can think of using <i>prefix</i> to make groups in the same way you'd use a folder in a file system.) You can use <i>prefix</i> with <i>delimiter</i> to roll up numerous objects into a single result under <i>CommonPrefixes</i> . Also, see <i>delimiter</i> . Type: String Default: None	No
<i>version-id-marker</i>	Specifies the object version you want to start listing from. Also, see <i>key-marker</i> . Type: String Default: None Valid Values: Valid version ID   Default Constraint: May not be an empty string	No

## Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
DeleteMarker	Container for an object that is a Delete Marker. Type: Container Children: Key, VersionId, IsLatest, LastModified, Owner Ancestor: ListVersionsResult
DisplayName	Object owner's name. Type: String Ancestor: ListVersionsResult.Version.Owner   ListVersionsResult.DeleteMarker.Owner
ETag	The entity tag is an MD5 hash of the object. The ETag only reflects changes to the contents of an object, not its metadata. Type: String Ancestor: ListVersionsResult.Version

**Amazon Simple Storage Service API Reference**  
**GET Bucket Object versions**

---

Name	Description
ID	Object owner's ID. Type: String Ancestor: ListVersionsResult.Version.Owner   ListVersionsResult.DeleteMarker.Owner
IsLatest	Specifies whether the object is ( <code>true</code> ) or is not ( <code>false</code> ) the latest version of an object. Type: Boolean Valid Values: <code>true</code>   <code>false</code> Ancestor: ListVersionsResult.Version   ListVersionsResult.DeleteMarker
IsTruncated	A flag that indicates whether ( <code>true</code> ) or not ( <code>false</code> ) Amazon S3 returned all of the results that satisfied the search criteria. If your results were truncated, you can make a follow-up paginated request using the <i>NextKeyMarker</i> and <i>NextVersionIdMarker</i> response parameters as a starting place in another request to return the rest of the results. Type: Boolean Valid Values: <code>true</code>   <code>false</code> Ancestor: ListVersionsResult
Key	The object's key. Type: String Ancestor: ListVersionsResult.Version   ListVersionsResult.DeleteMarker
KeyMarker	Marks the last <i>Key</i> returned in a truncated response. Type: String Ancestor: ListVersionsResult
LastModified	Date and time the object was last modified. Type: Date Ancestor: ListVersionsResult.Version   ListVersionsResult.DeleteMarker
ListVersionsResult	Container for the result. Type: Container Children: All elements in the response Ancestor: ListVersionsResult
MaxKeys	Specifies the maximum number of objects to return. Type: String Default: 1000 Valid Values: Integers from 1 to 1000, inclusive Ancestor: ListVersionsResult
Name	Bucket owner's name. Type: String Ancestor: ListVersionsResult

Name	Description
NextKeyMarker	When the number of responses exceeds the value of <i>MaxKeys</i> , <i>NextKeyMarker</i> specifies the first key not returned that satisfies the search criteria. Use this value for the <i>key-marker</i> request parameter in a subsequent request. Type: String Ancestor: ListVersionsResult
NextVersionIdMarker	When the number of responses exceeds the value of <i>MaxKeys</i> , <i>NextVersionIdMarker</i> specifies the first object version not returned that satisfies the search criteria. Use this value for the <i>version-id-marker</i> request parameter in a subsequent request. Type: String Ancestor: ListVersionsResult
Owner	Bucket owner. Type: String Children: DisplayName, ID Ancestor: ListVersionsResult.Version   ListVersionsResult.DeleteMarker
Prefix	Selects objects that start with the value supplied by this parameter. Type: String Ancestor: ListVersionsResult
Size	Size in bytes of the object. Type: String Ancestor: ListVersionsResult.Version
StorageClass	Always STANDARD. Type: String Ancestor: ListVersionsResult.Version
Version	Container for version information. Type: Container Ancestor: ListVersionsResult
VersionId	Version ID of an object Type: String Ancestor: ListVersionsResult.Version   ListVersionsResult.DeleteMarker
VersionIdMarker	Marks the last version of the <i>Key</i> returned in a truncated response. Type: String Ancestor: ListVersionsResult

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns all of the versions of all of the objects in the specified bucket.

```
GET /?versions HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response to GET Versions

```
<?xml version="1.0" encoding="UTF-8"?>

<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <Name>bucket</Name>
  <Prefix>my</Prefix>
  <KeyMarker/>
  <VersionIdMarker/>
  <MaxKeys>5</MaxKeys>
  <IsTruncated>false</IsTruncated>
  <Version>
    <Key>my-image.jpg</Key>
    <VersionId>3/L4kgtJl40Nr8X8gdRQBpUMLUo</VersionId>
    <IsLatest>true</IsLatest>
    <LastModified>2009-10-12T17:50:30.000Z</LastModified>
    <ETag>"fba9dede5f27731c9771645a39863328"</ETag>
    <Size>434234</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
      <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
      <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
  </Version>
  <DeleteMarker>
    <Key>my-second-image.jpg</Key>
    <VersionId>03jpff543dhffds434rfdSFDN943fdsFkdmqnh892</VersionId>
    <IsLatest>true</IsLatest>
    <LastModified>2009-11-12T17:50:30.000Z</LastModified>
    <Owner>
      <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
      <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
  </DeleteMarker>
  <Version>
    <Key>my-second-image.jpg</Key>
    <VersionId>QUpfndndhfd8438MNFdN93jdnJFkdmqnh893</VersionId>
    <IsLatest>false</IsLatest>
    <LastModified>2009-10-10T17:50:30.000Z</LastModified>
    <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
    <Size>166434</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
```

```

        <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
        <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
</Version>
<DeleteMarker>
    <Key>my-third-image.jpg</Key>
    <VersionId>03jpff543dhffds434rfdSFdN943fdfsFkdmqnh892</VersionId>
    <IsLatest>true</IsLatest>
    <LastModified>2009-10-15T17:50:30.000Z</LastModified>
    <Owner>
        <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
        <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
</DeleteMarker>
<Version>
    <Key>my-third-image.jpg</Key>
    <VersionId>UIORUnfndfhnw89493jJFJ</VersionId>
    <IsLatest>false</IsLatest>
    <LastModified>2009-10-11T12:50:30.000Z</LastModified>
    <ETag>"772cf535f27731c974343645a3985328"</ETag>
    <Size>64</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
        <ID>75aa57f09aa0c8cae
ab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
        <DisplayName>mtd@amazon.com</DisplayName>
    </Owner>
</Version>
</ListVersionsResult>

```

## Sample Request

The following request returns objects in the order they were stored, returning the most recently stored object first starting with the value for *key-marker*.

```

GET /?versions&key-marker=key2 HTTP/1.1
User-Agent: curl/7.10.6 (i386-redhat-linux-gnu) libcurl/7.10.6 OpenSSL/0.9.7a
ipv6 zlib/1.1.4
Host: s3.amazonaws.com
Pragma: no-cache
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, */*
Date: Thu, 10 Dec 2009 22:46:32 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:U1j5vNnJfzmiv3c1GnlG6MLVeZU=

```

## Sample Response

```

<?xml version="1.0" encoding="UTF-8"?>
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
    <Name>mtp-versioning-fresh</Name>
    <Prefix/>
    <KeyMarker>key2</KeyMarker>
    <VersionIdMarker/>
    <MaxKeys>1000</MaxKeys>

```

```
<IsTruncated>false</IsTruncated>
<Version>
  <Key>key3</Key>
  <VersionId>I5VhmK6CDDdQ5PwfelgcHZWmHDpcv7gfmfc29UBxsKU.</VersionId>
  <IsLatest>true</IsLatest>
  <LastModified>2009-12-09T00:19:04.000Z</LastModified>
  <ETag>&quot;396fefef536d5ce46c7537ecf978a360&quot;</ETag>
  <Size>217</Size>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
  <StorageClass>STANDARD</StorageClass>
</Version>
<DeleteMarker>
  <Key>sourcekey</Key>
  <VersionId>qDhprLU80sAlCFLu2DWgXAEDgKzWarn-HS_JU0TvYqs.</VersionId>
  <IsLatest>true</IsLatest>
  <LastModified>2009-12-10T16:38:11.000Z</LastModified>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
</DeleteMarker>
<Version>
  <Key>sourcekey</Key>
  <VersionId>wxXQ7ezLaL5JN2Sislq66Syxxo0k7uHTUpb9qiiMxNg.</VersionId>
  <IsLatest>false</IsLatest>
  <LastModified>2009-12-10T16:37:44.000Z</LastModified>
  <ETag>&quot;396fefef536d5ce46c7537ecf978a360&quot;</ETag>
  <Size>217</Size>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
  <StorageClass>STANDARD</StorageClass>
</Version>
</ListVersionsResult>
```

## Sample Request Using prefix

This example returns objects whose keys begin with `source`.

```
GET /?versions&prefix=source HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>mtp-versioning-fresh</Name>
  <Prefix>source</Prefix>
  <KeyMarker/>
```

```
<VersionIdMarker/>
<MaxKeys>1000</MaxKeys>
<IsTruncated>>false</IsTruncated>
<DeleteMarker>
  <Key>sourcekey</Key>
  <VersionId>qDhprLU80sAlCFLu2DWgXAEDgKzWarn-HS_JU0TvYqs.</VersionId>
  <IsLatest>>true</IsLatest>
  <LastModified>2009-12-10T16:38:11.000Z</LastModified>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
</DeleteMarker>
<Version>
  <Key>sourcekey</Key>
  <VersionId>wxQ7ezLaL5JN2Sislq66Syxxo0k7uHTUpb9qiiMxNg.</VersionId>
  <IsLatest>>false</IsLatest>
  <LastModified>2009-12-10T16:37:44.000Z</LastModified>
  <ETag>&quot;396fefef536d5ce46c7537ecf978a360&quot;</ETag>
  <Size>217</Size>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
  <StorageClass>STANDARD</StorageClass>
</Version>
</ListVersionsResult>
```

## Sample Request Using key-marker and version-id-marker Parameters

The following example returns objects starting at the specified key (*key-marker*) and version ID (*version-id-marker*).

```
GET /?versions&key-marker=key3&version-id-marker=t46ZenlYtZBnj HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>mtp-versioning-fresh</Name>
  <Prefix/>
  <KeyMarker>key3</KeyMarker>
  <VersionIdMarker>t46ZenlYtZBnj</VersionIdMarker>
  <MaxKeys>1000</MaxKeys>
  <IsTruncated>>false</IsTruncated>
  <DeleteMarker>
    <Key>sourcekey</Key>
    <VersionId>qDhprLU80sAlCFLu2DWgXAEDgKzWarn-HS_JU0TvYqs.</VersionId>
    <IsLatest>>true</IsLatest>
    <LastModified>2009-12-10T16:38:11.000Z</LastModified>
    <Owner>
      <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
```



```
</Owner>
</DeleteMarker>
<Version>
  <Key>sourcekey</Key>
  <VersionId>wxXQ7ezLaL5JN2Sislq66Syxxo0k7uHTUpb9qiiMxNg.</VersionId>
  <IsLatest>false</IsLatest>
  <LastModified>2009-12-10T16:37:44.000Z</LastModified>
  <ETag>"396fefef536d5ce46c7537ecf978a360"</ETag>
  <Size>217</Size>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

  </Owner>
  <StorageClass>STANDARD</StorageClass>
</Version>
</ListVersionsResult>
```

## Sample Request Using key-marker, version-id-marker and max-keys

The following request returns up to three (the value of *max-keys*) objects starting with the key specified by *key-marker* and the version ID specified by *version-id-marker*.

```
GET /?versions&key-marker=key3&version-id-marker=t46Z0menlYtZBnj HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 +0000
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
<?xml version="1.0" encoding="UTF-8"?>
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>mtp-versioning-fresh</Name>
  <Prefix/>
  <KeyMarker>key3</KeyMarker>
  <VersionIdMarker>null</VersionIdMarker>
  <NextKeyMarker>key3</NextKeyMarker>
  <NextVersionIdMarker>d-d309mfjFrUmoQ0DBsVqmcMV15OI.</NextVersionIdMarker>
  <MaxKeys>2</MaxKeys>
  <IsTruncated>true</IsTruncated>
  <Version>
    <Key>key3</Key>
    <VersionId>8XECiENpj8pydEDJdd-_VRrvaGKAHOaGMNW7tg6UViI.</VersionId>
    <IsLatest>false</IsLatest>
    <LastModified>2009-12-09T00:18:23.000Z</LastModified>
    <ETag>"396fefef536d5ce46c7537ecf978a360"</ETag>
    <Size>217</Size>
    <Owner>
      <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

    </Owner>
    <StorageClass>STANDARD</StorageClass>
  </Version>
  <Version>
    <Key>key3</Key>
```

```
<VersionId>d-d309mfjFri40QYukDozqBt3UmoQ0DBsVqmcMV15OI.</VersionId>
<IsLatest>>false</IsLatest>
<LastModified>2009-12-09T00:18:08.000Z</LastModified>
<ETag>&quot;396fefef536d5ce46c7537ecf978a360&quot;</ETag>
<Size>217</Size>
<Owner>
  <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

</Owner>
<StorageClass>STANDARD</StorageClass>
</Version>
</ListVersionsResult>
```

## Sample Request Using the Delimiter and the Prefix Parameters

Assume you have the following keys in your bucket, `example-bucket`.

`photos/2006/January/sample.jpg`

`photos/2006/February/sample.jpg`

`photos/2006/March/sample.jpg`

`videos/2006/March/sample.wmv`

`sample.jpg`

The following GET versions request specifies the delimiter parameter with value `"/`.

```
GET /?versions&delimiter=/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Wed, 02 Feb 2011 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

The list of keys from the specified bucket are shown in the following response.

The response returns the `sample.jpg` key in a `<Version>` element. However, because all the other keys contain the specified delimiter, a distinct substring, from the beginning of the key to the first occurrence of the delimiter, from each of these keys is returned in a `<CommonPrefixes>` element. The key substrings, `photos/` and `videos/`, in the `<CommonPrefixes>` element indicate that there are one or more keys with these key prefixes.

This is a useful scenario if you use key prefixes for your objects to create a logical folder like structure. In this case you can interpret the result as the folders `photos/` and `videos/` have one or more objects.

```
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>mvbucketwithversionon1</Name>
  <Prefix></Prefix>
  <KeyMarker></KeyMarker>
  <VersionIdMarker></VersionIdMarker>
  <MaxKeys>1000</MaxKeys>
  <Delimiter>/</Delimiter>
  <IsTruncated>>false</IsTruncated>

  <Version>
    <Key>Sample.jpg</Key>
```

```
<VersionId>toxMzQlBsGyGCz1YuMWMp90cdXLzqOCH</VersionId>
<IsLatest>true</IsLatest>
<LastModified>2011-02-02T18:46:20.000Z</LastModified>
<ETag>&quot;3305f2cfc46c0f04559748bb039d69ae&quot;</ETag>
<Size>3191</Size>
<Owner>
  <ID>852b113e7a2f25102679df27bb0ae12b3f85be6f290b936c4393484be31bebcc</ID>

  <DisplayName>display-name</DisplayName>
</Owner>
<StorageClass>STANDARD</StorageClass>
</Version>

<CommonPrefixes>
  <Prefix>photos/</Prefix>
</CommonPrefixes>
<CommonPrefixes>
  <Prefix>videos/</Prefix>
</CommonPrefixes>
</ListVersionsResult>
```

In addition to the delimiter parameter you can filter results by adding a `prefix` parameter as shown in the following request.

```
GET /?versions&prefix=photos/2006/&delimiter=/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Wed, 02 Feb 2011 19:34:02 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

In this case the response will include only objects keys that start with the specified prefix. The value returned in the `<CommonPrefixes>` element is a substring from the beginning of the key to the first occurrence of the specified delimiter after the prefix.

```
<?xml version="1.0" encoding="UTF-8"?>
<ListVersionsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>example-bucket</Name>
  <Prefix>photos/2006/</Prefix>
  <KeyMarker></KeyMarker>
  <VersionIdMarker></VersionIdMarker>
  <MaxKeys>1000</MaxKeys>
  <Delimiter></Delimiter>
  <IsTruncated>>false</IsTruncated>
  <Version>
    <Key>photos/2006/</Key>
    <VersionId>3U275dAA4gz8ZOqOPHtJCU0i60krpCdy</VersionId>
    <IsLatest>true</IsLatest>
    <LastModified>2011-02-02T18:47:27.000Z</LastModified>
    <ETag>&quot;d41d8cd98f00b204e9800998ecf8427e&quot;</ETag>
    <Size>0</Size>
    <Owner>
      <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

      <DisplayName>display-name</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
  </Version>
```

```
<CommonPrefixes>
  <Prefix>photos/2006/February/</Prefix>
</CommonPrefixes>
<CommonPrefixes>
  <Prefix>photos/2006/January/</Prefix>
</CommonPrefixes>
<CommonPrefixes>
  <Prefix>photos/2006/March/</Prefix>
</CommonPrefixes>
</ListVersionsResult>
```

## Related Resources

- [GET Bucket Objects \(p. 31\)](#)
- [GET Object \(p. 153\)](#)
- [PUT Object \(p. 185\)](#)
- [DELETE Object \(p. 141\)](#)

# GET Bucket requestPayment

## Description

This implementation of the `GET` operation uses the `requestPayment` subresource to return the request payment configuration of a bucket. To use this version of the operation, you must be the bucket owner. For more information, see [Requester Pays Buckets](#).

## Requests

### Syntax

```
GET ?requestPayment HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Date
Authorization: Signature
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
<i>Payer</i>	Specifies who pays for the download and request fees. Type: Enum Valid Values: Requester   BucketOwner Ancestor: RequestPaymentConfiguration
<i>RequestPaymentConfiguration</i>	Container for <i>Payer</i> . Type: Container

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the payer for the bucket, colorpictures.

```
GET ?requestPayment HTTP/1.1
Host: colorpictures.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
Content-Type: [type]
Content-Length: 0
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<RequestPaymentConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Payer>Requester</Payer>
</RequestPaymentConfiguration>
```

This response shows that the bucket is a Requester Pays bucket, meaning the person requesting a download from this bucket pays the transfer fees.

## Related Resources

- [GET Bucket \(List Objects\) \(p. 31\)](#)

# GET Bucket versioning

## Description

This implementation of the `GET` operation uses the *versioning* subresource to return the versioning state of a bucket. To retrieve the versioning state of a bucket, you must be the bucket owner.

This implementation also returns the MFA Delete status of the versioning state, i.e., if the MFA Delete status is `enabled`, the bucket owner must use an authentication device to change the versioning state of the bucket.

There are three versioning states:

- If you enabled versioning on a bucket, the response is:

```
<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Enabled</Status>
</VersioningConfiguration>
```

- If you suspended versioning on a bucket, the response is:

```
<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Suspended</Status>
</VersioningConfiguration>
```

- If you never enabled (or suspended) versioning on a bucket, the response is:

```
<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/" />
```

## Requests

### Syntax

```
GET /?versioning HTTP/1.1
Host: BucketName.s3.amazonaws.com
Content-Length: length
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of GET returns the following response elements.

Name	Description
<i>MfaDelete</i>	Specifies whether MFA delete is enabled in the bucket versioning configuration. This element is only returned if the bucket has been configured with MfaDelete. If the bucket has never been so configured, this element is not returned. Type: Enum Valid Values: Disabled   Enabled Ancestor: VersioningConfiguration
<i>Status</i>	The versioning state of the bucket. Type: Enum Valid Values: Suspended   Enabled Ancestor: VersioningConfiguration
<i>VersioningConfiguration</i>	Container for the <i>Status</i> response element. Type: Container Ancestor: None

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This example returns the versioning state of myBucket.

```
GET /?versioning HTTP/1.1
Host: myBucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
```

### Sample Response

The following is a sample of the response body (only) that shows bucket versioning is enabled.



```
<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Enabled</Status>
</VersioningConfiguration>
```

## Related Resources

- [GET Object \(p. 153\)](#)
- [PUT Object \(p. 185\)](#)
- [DELETE Object \(p. 141\)](#)

# GET Bucket website

## Description

This implementation of the `GET` operation returns the website configuration associated with a bucket. To host website on Amazon S3, you can configure a bucket as website by adding a website configuration. For more information about hosting websites, go to [Hosting Websites on Amazon S3](#) in the *Amazon S3 Developer Guide*.

This `GET` operation requires the `S3:GetBucketWebsite` permission. By default, only the bucket owner can read the bucket *website* configuration. However, bucket owners can allow other users to read the *website* configuration by writing a bucket policy granting them the `S3:GetBucketWebsite` permission.

## Requests

### Syntax

```
GET /?website HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

The response XML includes same elements that were uploaded when you configured the bucket as website. For more information, see [PUT Bucket website \(p. 132\)](#).

## Examples

### Sample Request

This request retrieves website configuration on the specified bucket.

```
GET ?website HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Thu, 27 Jan 2011 00:49:20 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:n0Nhek72Ufg/u7Sm5C1dqRLs8XX=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMgUAdQkf3ShJTOOpXUueF6QKo
x-amz-request-id: 3848CD259D811111
Date: Thu, 27 Jan 2011 00:49:26 GMT
Content-Length: 240
Content-Type: application/xml
Transfer-Encoding: chunked
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<WebsiteConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <IndexDocument>
    <Suffix>index.html</Suffix>
  </IndexDocument>
  <ErrorDocument>
    <Key>404.html</Key>
  </ErrorDocument>
</WebsiteConfiguration>
```

## Related Resources

- [DELETE Bucket website \(p. 29\)](#)
- [PUT Bucket website \(p. 132\)](#)

# HEAD Bucket

## Description

This operation is useful to determine if a bucket exists and you have permission to access it. The operation returns a 200 OK if the bucket exists and you have permission to access it. Otherwise, the operation might return responses such as 404 Not Found and 403 Forbidden.

## Requests

### Syntax

```
HEAD / HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Elements

This implementation of the operation does not use request elements.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This requests returns the objects in *BucketName*.

```
HEAD / HTTP/1.1
Date: Fri, 10 Feb 2012 21:34:55 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Host: myawsbucket.s3.amazonaws.com
Connection: Keep-Alive
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: JuKZqmXuiwFeDQxhD7M8KtsKobSzWA1QEjLbTMTagkKdBX2z7I1/jGhDeJ3j6s80
x-amz-request-id: 32FE2CEB32F5EE25
Date: Fri, 10 2012 21:34:56 GMT
Server: AmazonS3
```

# List Multipart Uploads

## Description

This operation lists in-progress multipart uploads. An in-progress multipart upload is a multipart upload that has been initiated, using the Initiate Multipart Upload request, but has not yet been completed or aborted.

This operation returns at most 1,000 multipart uploads in the response. 1,000 multipart uploads is the maximum number of uploads a response can include, which is also the default value. You can further limit the number of uploads in a response by specifying the *max-uploads* parameter in the response. If additional multipart uploads satisfy the list criteria, the response will contain an *IsTruncated* element with the value *true*. To list the additional multipart uploads, use the *key-marker* and *upload-id-marker* request parameters.

In the response, the uploads are sorted by key. If your application has initiated more than one multipart upload using the same object key, then uploads in the response are first sorted by key. Additionally, uploads are sorted in ascending order within each key by the upload initiation time.

For more information on multipart uploads, go to [Uploading Objects Using Multipart Upload](#) in the *Amazon S3 Developer Guide*.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer Guide*.

## Requests

### Syntax

```
GET /?uploads HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Date
Authorization: Signature
```

### Request Parameters

Parameter	Description	Required
<i>delimiter</i>	Character you use to group keys.  All keys that contain the same string between the <i>prefix</i> , if specified, and the first occurrence of the delimiter after the prefix are grouped under a single result element, <i>CommonPrefixes</i> . If you don't specify the <i>prefix</i> parameter, then the substring starts at the beginning of the key. The keys that are grouped under <i>CommonPrefixes</i> result element are not returned elsewhere in the response. Type: String	No
<i>max-uploads</i>	Sets the maximum number of multipart uploads, from 1 to 1,000, to return in the response body. 1,000 is the maximum number of uploads that can be returned in a response. Type: Integer Default: 1,000	No

Parameter	Description	Required
<i>key-marker</i>	<p>Together with <code>upload-id-marker</code>, this parameter specifies the multipart upload after which listing should begin.</p> <p>If <code>upload-id-marker</code> is not specified, only the keys lexicographically greater than the specified <i>key-marker</i> will be included in the list.</p> <p>If <code>upload-id-marker</code> is specified, any multipart uploads for a key equal to the <i>key-marker</i> might also be included, provided those multipart uploads have upload IDs lexicographically greater than the specified <i>upload-id-marker</i>.</p> <p>Type: String</p>	No
<i>prefix</i>	<p>Lists in-progress uploads only for those keys that begin with the specified prefix. You can use prefixes to separate a bucket into different grouping of keys. (You can think of using prefix to make groups in the same way you'd use a folder in a file system.)</p> <p>Type: String</p>	No
<i>upload-id-marker</i>	<p>Together with <code>key-marker</code>, specifies the multipart upload after which listing should begin. If <code>key-marker</code> is not specified, the <code>upload-id-marker</code> parameter is ignored. Otherwise, any multipart uploads for a key equal to the <i>key-marker</i> might be included in the list only if they have an upload ID lexicographically greater than the specified <i>upload-id-marker</i>.</p> <p>Type: String</p>	No

## Request Headers

This operation uses only Request Headers common to most requests. For more information, see [Common Request Headers \(p. 12\)](#).

## Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
ListMultipartUploadsResult	<p>Container for the response.</p> <p>Children: <i>Bucket</i>, <i>KeyMarker</i>, <i>UploadIdMarker</i>, <i>NextKeyMarker</i>, <i>NextUploadIdMarker</i>, <i>MaxUploads</i>, <i>Delimiter</i>, <i>Prefix</i>, <i>CommonPrefixes</i>, <i>IsTruncated</i></p> <p>Type: Container</p> <p>Ancestor: None</p>

**Amazon Simple Storage Service API Reference**  
**List Multipart Uploads**

---

Name	Description
Bucket	Name of the bucket to which the multipart upload was initiated. Type: String Ancestor: <i>ListMultipartUploadsResult</i>
KeyMarker	The key at or after which the listing began. Type: String Ancestor: <i>ListMultipartUploadsResult</i>
UploadIdMarker	Upload ID after which listing began. Type: String Ancestor: <i>ListMultipartUploadsResult</i>
NextKeyMarker	When a list is truncated, this element specifies the value that should be used for the <i>key-marker</i> request parameter in a subsequent request. Type: String Ancestor: <i>ListMultipartUploadsResult</i>
NextUploadIdMarker	When a list is truncated, this element specifies the value that should be used for the <i>upload-id-marker</i> request parameter in a subsequent request. Type: String Ancestor: <i>ListMultipartUploadsResult</i>
MaxUploads	Maximum number of multipart uploads that could have been included in the response. Type: Integer Ancestor: <i>ListMultipartUploadsResult</i>
IsTruncated	Indicates whether the returned list of multipart uploads is truncated. A value of <i>true</i> indicates that the list was truncated. The list can be truncated if the number of multipart uploads exceeds the limit allowed or specified by <i>MaxUploads</i> . Type: Boolean Ancestor: <i>ListMultipartUploadsResult</i>
Upload	Container for elements related to a particular multipart upload. A response can contain zero or more <i>Upload</i> elements. Type: Container Children: <i>Key</i> , <i>UploadId</i> , <i>InitiatorOwner</i> , <i>StorageClass</i> , <i>Initiated</i> Ancestor: <i>ListMultipartUploadsResult</i>
Key	Key of the object for which the multipart upload was initiated. Type: Integer Ancestor: <i>Upload</i>
UploadId	Upload ID that identifies the multipart upload. Type: Integer Ancestor: <i>Upload</i>



**Amazon Simple Storage Service API Reference**  
**List Multipart Uploads**

---

Name	Description
Initiator	Container element that identifies who initiated the multipart upload. If the initiator is an AWS account, this element provides the same information as the <i>Owner</i> element. If the initiator is an IAM User, then this element provides the user ARN and display name. Children: <i>ID, DisplayName</i> Type: Container Ancestor: <i>Upload</i>
ID	If the principal is an AWS account, it provides the Canonical User ID. If the principal is an IAM User, it provides a user ARN value. Type: String Ancestor: <i>Initiator, Owner</i>
DisplayName	Principal's name. Type: String Ancestor: <i>Initiator, Owner</i>
Owner	Container element that identifies the object owner, after the object is created. If multipart upload is initiated by an IAM user, this element provides a the parent account ID and display name. Type: Container Children: <i>ID, DisplayName</i> Ancestor: <i>Upload</i>
StorageClass	The class of storage ( <i>STANDARD</i> or <i>REDUCED_REDUDANCY</i> ) that will be used to store the object when the multipart upload is complete. Type: String Ancestor: <i>Upload</i>
Initiated	Date and time at which the multipart upload was initiated. Type: <i>Date</i> Ancestor: <i>Upload</i>
ListMultipartUploadsResult.Prefix	When a prefix is provided in the request, this field contains the specified prefix. The result contains only keys starting with the specified prefix. Type: <i>String</i> Ancestor: <i>ListMultipartUploadsResult</i>
Delimiter	Contains the delimiter you specified in the request. If you don't specify a delimiter in your request, this element is absent from the response. Type: <i>String</i> Ancestor: <i>ListMultipartUploadsResult</i>

Name	Description
<code>CommonPrefixes</code>	If you specify a delimiter in the request, then the result returns each distinct key prefix containing the delimiter in a <code>CommonPrefixes</code> element. The distinct key prefixes are returned in the <code>Prefix</code> child element.  Type: <i>Container</i> Ancestor: <i>ListMultipartUploadsResult</i>
<code>CommonPrefixes.Prefix</code>	If the request does not include the <code>Prefix</code> parameter, then this element shows only the substring of the key that precedes the first occurrence of the delimiter character. These keys are not returned anywhere else in the response.  If the request includes the <code>Prefix</code> parameter, then this element shows the substring of the key from the beginning to the first occurrence of the delimiter after the prefix.  Type: <i>String</i> Ancestor: <i>CommonPrefixes</i>

## Examples

### Sample Request

The following request lists three multipart uploads. The request specifies the `max-uploads` request parameter to set the maximum number of multipart uploads to return in the response body.

```
GET /?uploads&max-uploads=3 HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

The following sample response indicates that the multipart upload list was truncated and provides the `NextKeyMarker` and the `NextUploadIdMarker` elements. You specify these values in your subsequent requests to read the next set of multipart uploads. That is, send a subsequent request specifying `key-marker=my-movie2.m2ts` (value of the `NextKeyMarker` element) and `upload-id-marker=YW55IGlkZWVsdmluZydzIHVwbG9hZCBmYWlsZWQ` (value of the `NextUploadIdMarker`).

The sample response also shows a case of two multipart uploads in progress with the same key (`my-movie.m2ts`). That is, the response shows two uploads with the same key. This response shows the uploads sorted by key, and within each key the uploads are sorted in ascending order by the time the multipart upload was initiated.

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 1330
Connection: keep-alive
Server: AmazonS3
```

```
<?xml version="1.0" encoding="UTF-8"?>
<ListMultipartUploadsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Bucket>bucket</Bucket>
  <KeyMarker></KeyMarker>
  <UploadIdMarker></UploadIdMarker>
  <NextKeyMarker>my-movie.m2ts</NextKeyMarker>
  <NextUploadIdMarker>YW55IGlkZWEd2h5IGVsdmluZydzIHVwbG9hZCBmYWlsZWQ</NextUp
loadIdMarker>
  <MaxUploads>3</MaxUploads>
  <IsTruncated>true</IsTruncated>
  <Upload>
    <Key>my-divisor</Key>
    <UploadId>XMgbGlrZSB1bHZpbmcncyBub3QgaGF2aW5nIG11Y2ggbHVjaw</UploadId>
    <Initiator>
      <ID>arn:aws:iam::111122223333:user/user1-11111a31-17b5-4fb7-9df5-
b11111f13de</ID>
      <DisplayName>user1-11111a31-17b5-4fb7-9df5-b11111f13de</DisplayName>
    </Initiator>
    <Owner>
      <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

      <DisplayName>OwnerDisplayName</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
    <Initiated>2010-11-10T20:48:33.000Z</Initiated>
  </Upload>
  <Upload>
    <Key>my-movie.m2ts</Key>
    <UploadId>VXBsb2FkIEFlEIGZvcilBbHZpbmcncyBteS1tb3ZpZS5tMnRzIHVwbG9hZA</Up
loadId>
    <Initiator>
      <ID>b1d16700c70b0b05597d7acd6a3f92be</ID>
      <DisplayName>InitiatorDisplayName</DisplayName>
    </Initiator>
    <Owner>
      <ID>b1d16700c70b0b05597d7acd6a3f92be</ID>
      <DisplayName>OwnerDisplayName</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
    <Initiated>2010-11-10T20:48:33.000Z</Initiated>
  </Upload>
  <Upload>
    <Key>my-movie.m2ts</Key>
    <UploadId>YW55IGlkZWEd2h5IGVsdmluZydzIHVwbG9hZCBmYWlsZWQ</UploadId>
    <Initiator>
      <ID>arn:aws:iam::444455556666:user/user1-22222a31-17b5-4fb7-9df5-
b22222f13de</ID>
      <DisplayName>user1-22222a31-17b5-4fb7-9df5-b22222f13de</DisplayName>
    </Initiator>
    <Owner>
      <ID>b1d16700c70b0b05597d7acd6a3f92be</ID>
      <DisplayName>OwnerDisplayName</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
    <Initiated>2010-11-10T20:49:33.000Z</Initiated>
  </Upload>
</ListMultipartUploadsResult>
```

## Sample Request Using the Delimiter and the Prefix Parameters

Assume you have a multipart upload in progress for the following keys in your bucket, `example-bucket`.

`photos/2006/January/sample.jpg`

`photos/2006/February/sample.jpg`

`photos/2006/March/sample.jpg`

`videos/2006/March/sample.wmv`

`sample.jpg`

The following list multipart upload request specifies the delimiter parameter with value `"/"`.

```
GET /?uploads&delimiter=/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

The following sample response lists multipart uploads on the specified bucket, `example-bucket`.

The response returns multipart upload for the `sample.jpg` key in an `<Upload>` element.

However, because all the other keys contain the specified delimiter, a distinct substring, from the beginning of the key to the first occurrence of the delimiter, from each of these keys is returned in a `<CommonPrefixes>` element. The key substrings, `photos/` and `videos/`, in the `<CommonPrefixes>` element indicate that there are one or more in-progress multipart uploads with these key prefixes.

This is a useful scenario if you use key prefixes for your objects to create a logical folder like structure. In this case you can interpret the result as the folders `photos/` and `videos/` have one or more multipart uploads in progress.

```
<ListMultipartUploadsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Bucket>example-bucket</Bucket>
  <KeyMarker/>
  <UploadIdMarker/>
  <NextKeyMarker>sample.jpg</NextKeyMarker>
  <NextUploadIdMarker>Xgw4MJT6ZPAVx
pY0SAuGN7q4uWJm22ZYg1W99trdp4tpO88.PT6.Mh00w2E17eutfAvQfQWojgE_W2gpcxQw--
</NextUploadIdMarker>
  <Delimiter></Delimiter>
  <Prefix/>
  <MaxUploads>1000</MaxUploads>
  <IsTruncated>>false</IsTruncated>
  <Upload>
    <Key>sample.jpg</Key>
    <UploadId>Agw4MJT6ZPAVxpY0SAuGN7q4uWJm22ZYg1W99trdp4tpO88.PT6.Mh00w2E17eut
fAvQfQWojgE_W2gpcxQw--</UploadId>
    <Initiator>
      <ID>314133b66967d86f031c7249d1d9a80249109428335cd0ef1cdc487b4566cb1b</ID>

      <DisplayName>s3-nickname</DisplayName>
    </Initiator>
    <Owner>
      <ID>314133b66967d86f031c7249d1d9a80249109428335cd0ef1cdc487b4566cb1b</ID>
```

```
<DisplayName>s3-nickname</DisplayName>
</Owner>
<StorageClass>STANDARD</StorageClass>
<Initiated>2010-11-26T19:24:17.000Z</Initiated>
</Upload>
<CommonPrefixes>
  <Prefix>photos/</Prefix>
</CommonPrefixes>
<CommonPrefixes>
  <Prefix>videos/</Prefix>
</CommonPrefixes>
</ListMultipartUploadsResult>
```

In addition to the delimiter parameter you can filter results by adding a `prefix` parameter as shown in the following request.

```
GET /?uploads&delimiter=/&prefix=photos/2006/ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

In this case the response will include only multipart uploads for keys that start with the specified prefix. The value returned in the `<CommonPrefixes>` element is a substring from the beginning of the key to the first occurrence of the specified delimiter after the prefix.

```
<?xml version="1.0" encoding="UTF-8"?>
<ListMultipartUploadsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Bucket>example-bucket</Bucket>
  <KeyMarker/>
  <UploadIdMarker/>
  <NextKeyMarker/>
  <NextUploadIdMarker/>
  <Delimiter>/</Delimiter>
  <Prefix>photos/2006/</Prefix>
  <MaxUploads>1000</MaxUploads>
  <IsTruncated>false</IsTruncated>
  <CommonPrefixes>
    <Prefix>photos/2006/February/</Prefix>
  </CommonPrefixes>
  <CommonPrefixes>
    <Prefix>photos/2006/January/</Prefix>
  </CommonPrefixes>
  <CommonPrefixes>
    <Prefix>photos/2006/March/</Prefix>
  </CommonPrefixes>
</ListMultipartUploadsResult>
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)

# PUT Bucket

## Description

This implementation of the `PUT` operation creates a new bucket. To create a bucket, you must register with Amazon S3 and have a valid AWS Access Key ID to authenticate requests. Anonymous requests are never allowed to create buckets. By creating the bucket, you become the bucket owner.

Not every string is an acceptable bucket name. For information on bucket naming restrictions, see [Working with Amazon S3 Buckets](#).

By default, the bucket is created in the US Standard region. You can optionally specify a region in the request body. You might choose a Region to optimize latency, minimize costs, or address regulatory requirements. For example, if you reside in Europe, you will probably find it advantageous to create buckets in the EU (Ireland) Region. For more information, see [How to Select a Region for Your Buckets](#).

### Note

If you create a bucket in a region other than US Standard, your application must be able to handle 307 redirect. For more information, go to [Virtual Hosting of Buckets](#) in *Amazon Simple Storage Service Developer Guide*.

When creating a bucket using this operation, you can optionally specify the accounts or groups that should be granted specific permissions on the bucket. There are two ways to grant the appropriate permissions using the request headers.

- Specify a canned ACL using the `x-amz-acl` request header. For more information, see [Canned ACL](#) in the *Amazon Simple Storage Service Developer Guide*.
- Specify access permissions explicitly using the `x-amz-grant-read`, `x-amz-grant-write`, `x-amz-grant-read-acp`, `x-amz-grant-write-acp`, `x-amz-grant-full-control` headers. These headers map to the set of permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#) in the *Amazon Simple Storage Service Developer Guide*.

### Note

You can use either a canned ACL or specify access permissions explicitly. You cannot do both.

## Requests

### Syntax

```
PUT / HTTP/1.1
Host: BucketName.s3.amazonaws.com
Content-Length: length
Date: date
Authorization: signatureValue

<CreateBucketConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <LocationConstraint>BucketRegion</LocationConstraint>
</CreateBucketConfiguration>
```

### Note

The syntax shows some of the request headers. For a complete list, see the Request Headers section.

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

When creating a bucket, you can grant permissions to individual AWS accounts or predefined groups defined by Amazon S3. This results in creation of the Access Control List (ACL) on the bucket. For more information, see [Using ACLs](#). You have the following two ways to grant these permissions:

- **Specify a canned ACL** — Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, go to [Canned ACL](#).

Name	Description	Required
<i>x-amz-acl</i>	The canned ACL to apply to the bucket you are creating. For more information, go to <a href="#">Canned ACL</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Valid Values: private   public-read   public-read-write   authenticated-read   bucket-owner-read   bucket-owner-full-control	No

- **Specify access permissions explicitly** — If you want to explicitly grant access permissions to specific AWS accounts or groups, you use the following headers. Each of these headers maps to specific permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#). In the header value, you specify a list of grantees who get the specific permission

Name	Description	Required
<i>x-amz-grant-read</i>	Allows grantee to list the objects in the bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write</i>	Allows grantee to create, overwrite, and delete any object in the bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-read-acl</i>	Allows grantee to read the bucket ACL. Type: String Default: None Constraints: None	No

Name	Description	Required
<i>x-amz-grant-write-ap</i>	Allows grantee to write the ACL for the applicable bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-full-control</i>	Allows grantee the READ, WRITE, READ_ACP, and WRITE_ACP permissions on the bucket. Type: String Default: None Constraints: None	No

You specify each grantee as a `type=value` pair, where the type can be one of the following::

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical user ID of an AWS account
- **uri** — if granting permission to a predefined group.

For example, the following `x-amz-grant-read` header grants list objects permission to the AWS accounts identified by their email addresses.

```
x-amz-grant-read: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

For more information see, [ACL Overview](#).

## Request Elements

Name	Description	Required
<i>CreateBucketConfiguration</i>	Container for bucket configuration settings. Type: Container Ancestor: None	No
<i>LocationConstraint</i>	Specifies the region where the bucket will be created. For more information about region endpoints and location constraints, go to <a href="#">Regions and Endpoints</a> in the <i>Amazon Web Services Glossary</i> . Type: Enum Valid Values: EU   eu-west-1   us-west-1   us-west-2   ap-southeast-1   ap-southeast-2   ap-northeast-1   sa-east-1   empty string (for the US Classic Region) Default: US Standard Ancestor: CreateBucketConfiguration	No

## Response Elements

This implementation of the operation does not return response elements.



## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request creates a bucket named `colorpictures`.

```
PUT / HTTP/1.1
Host: colorpictures.s3.amazonaws.com
Content-Length: 0
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT

Location: /colorpictures
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Request: Setting the region of a bucket

The following request sets the region the bucket to `EU`.

```
PUT / HTTP/1.1
Host: bucketName.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 124

<CreateBucketConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <LocationConstraint>EU</LocationConstraint>
</CreateBucketConfiguration >
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT

Location: /colorpictures
```

```
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Request: Creating a bucket and configuring access permission using a canned ACL

This request creates a bucket named "colorpictures" and sets the ACL to `private`.

```
PUT / HTTP/1.1
Host: colorpictures.s3.amazonaws.com
Content-Length: 0
x-amz-acl: private
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT

Location: /colorpictures
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Request: Creating a bucket and configuring access permissions explicitly

This request creates a bucket named `colorpictures` and grants `WRITE` permission to the AWS account identified by an email address.

```
PUT HTTP/1.1
Host: colorpictures.s3.amazonaws.com
x-amz-date: Sat, 07 Apr 2012 00:54:40 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
x-amz-grant-write: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

### Sample Response

```
HTTP/1.1 200 OK
```

## Related Resources

- [PUT Object \(p. 185\)](#)
- [DELETE Bucket \(p. 19\)](#)

# PUT Bucket acl

## Description

This implementation of the `PUT` operation uses the `acl` subresource to set the permissions on an existing bucket using access control lists (ACL). For more information, go to [Using ACLs](#). To set the ACL of a bucket, you must have `WRITE_ACP` permission.

You can use one of the following two ways to set a bucket's permissions:

- Specify the ACL in the request body
- Specify permissions using request headers

### Note

You cannot specify access permission using both the body and the request headers.

Depending on your application needs, you may choose to set the ACL on a bucket using either the request body or the headers. For example, if you have an existing application that updates a bucket ACL using the request body, then you can continue to use that approach.

## Requests

### Syntax

The following request shows the syntax for sending the ACL in the request body. If you want to use headers to specify the permissions for the bucket, you cannot send the ACL in the request body. Instead, see Request Headers section for a list of headers you can use.

```
PUT /?acl HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue

<AccessControlPolicy>
  <Owner>
    <ID>ID</ID>
    <DisplayName>EmailAddress</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>ID</ID>
        <DisplayName>EmailAddress</DisplayName>
      </Grantee>
      <Permission>Permission</Permission>
    </Grant>
    ...
  </AccessControlList>
</AccessControlPolicy>
```

### Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

You can use the following request headers in addition to the [Common Request Headers \(p. 12\)](#).

These headers enable you to set access permissions using one of the following methods:

- Specify a canned ACL, or
- Specify the permission for each grantee explicitly

Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, see [Canned ACL](#). To grant access permissions by specifying canned ACLs, you use the following header and specify the canned ACL name as its value. If you use this header, you cannot use other access control specific headers in your request.

Name	Description	Required
<i>x-amz-acl</i>	Sets the ACL of the bucket using the specified canned ACL. Type: String Valid Values: private   public-read   public-read-write   authenticated-read Default: private	No

If you need to grant individualized access permissions on a bucket, you can use the following "x-amz-grant-permission" headers. When using these headers you specify explicit access permissions and grantees (AWS accounts or a Amazon S3 groups) who will receive the permission. If you use these ACL specific headers, you cannot use *x-amz-acl* header to set a canned ACL.

### Note

Each of the following request headers maps to specific permissions Amazon S3 supports in an ACL. For more information go to [Access Control List \(ACL\) Overview](#).

Name	Description	Required
<i>x-amz-grant-read</i>	Allows the specified grantee(s) to list the objects in the bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write</i>	Allows the specified grantee(s) to create, overwrite, and delete any object in the bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-read-acl</i>	Allows the specified grantee(s) to read the bucket ACL. Type: String Default: None Constraints: None	No

Name	Description	Required
<i>x-amz-grant-write-acp</i>	Allows the specified grantee(s) to write the ACL for the applicable bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-full-control</i>	Allows the specified grantee(s) the READ, WRITE, READ_ACP, and WRITE_ACP permissions on the bucket. Type: String Default: None Constraints: None	No

For each of these headers, the value is a comma-separated list of one or more grantees. You specify each grantee as a `type=value` pair, where the `type` can be one of the following:

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical User ID of an AWS account
- **uri** — if granting permission to a predefined Amazon S3 group.

For example, the following `x-amz-grant-write` header grants create, overwrite, and delete objects permission to `LogDelivery` group predefined by Amazon S3 and two AWS accounts identified by their email addresses.

```
x-amz-grant-write: uri="http://acs.amazonaws.com/groups/s3/LogDelivery",
emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

For more information, go to [Access Control List \(ACL\) Overview](#). For more information about bucket logging, go to [Server Access Logging](#).

## Request Elements

If you decide to use the request body to specify an ACL, you must use the following elements.

### Note

If you request the request body, you cannot use the request headers to set an ACL.

Name	Description	Required
<i>AccessControlList</i>	Container for Grant, Grantee, and Permission Type: Container Ancestors: <i>AccessControlPolicy</i>	No
<i>AccessControlPolicy</i>	Contains the elements that set the ACL permissions for an object per grantee. Type: String Ancestors: None	No
<i>DisplayName</i>	Screen name of the bucket owner. Type: String Ancestors: <i>AccessControlPolicy.Owner</i>	No

Name	Description	Required
<i>Grant</i>	Container for the grantee and his or her permissions. Type: Container Ancestors: <code>AccessControlPolicy.AccessControlList</code>	No
<i>Grantee</i>	The subject whose permissions are being set. For more information, see <a href="#">Grantee Values (p. 97)</a> . Type: String Ancestors: <code>AccessControlPolicy.AccessControlList.Grant</code>	No
<i>ID</i>	ID of the bucket owner, or the ID of the grantee. Type: String Ancestors: <code>AccessControlPolicy.Owner   AccessControlPolicy.AccessControlList.Grant</code>	No
<i>Owner</i>	Container for the bucket owner's display name and ID. Type: Container Ancestors: <code>AccessControlPolicy</code>	No
<i>Permission</i>	Specifies the permission given to the grantee. Type: String Valid Values: <code>FULL_CONTROL   WRITE   WRITE_ACP   READ   READ_ACP</code> Ancestors: <code>AccessControlPolicy.AccessControlList.Grant</code>	No

### Grantee Values

You can specify the person (grantee) to whom you're assigning access rights (using request elements) in the following ways:

- By the person's ID:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:type="CanonicalUser">
  <ID>ID</ID>
  <DisplayName>GranteesEmail</DisplayName>
</Grantee>
```

*DisplayName* is optional and ignored in the request.

- By Email address:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="AmazonCustomerByEmail">
  <EmailAddress>Grantees@email.com</EmailAddress>
</Grantee>
```

The grantee is resolved to the *CanonicalUser* and, in a response to a `GET Object acl` request, appears as the *CanonicalUser*.

- By URI:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="Group">
  <URI>http://acs.amazonaws.com/groups/global/AuthenticatedUsers<URI>
</Grantee>
```

## Responses

### Response Headers

The operation returns response header that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This operation does not return response elements.

### Special Errors

This operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request: Access permissions specified in the body

The following request grants access permission to the existing `examplebucket` bucket. The request specifies the ACL in the body. In addition to granting full control to the bucket owner, the XML specifies the following grants.

- Grant `AllUsers` group `READ` permission on the bucket.
- Grant the `LogDelivery` group `WRITE` permission on the bucket.
- Grant an AWS account, identified by email address, `WRITE_ACP` permission.
- Grant an AWS account, identified by canonical user ID, `READ_ACP` permission.

```
PUT ?acl HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Content-Length: 1660
x-amz-date: Thu, 12 Apr 2012 20:04:21 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=

<AccessControlPolicy xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Owner>
    <ID>852b113e7a2f25102679df27bb0ae12b3f85be6BucketOwnerCanonicalUserID</ID>

    <DisplayName>OwnerDisplayName</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>852b113e7a2f25102679df27bb0ae12b3f85be6BucketOwnerCanonic
alUserID</ID>
```

```
        <DisplayName>OwnerDisplayName</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="Group">
        <URI xmlns="">http://acs.amazonaws.com/groups/global/AllUsers</URI>
      </Grantee>
      <Permission xmlns="">READ</Permission>
    </Grant>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="Group">
        <URI xmlns="">http://acs.amazonaws.com/groups/s3/LogDelivery</URI>
      </Grantee>
      <Permission xmlns="">WRITE</Permission>
    </Grant>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="AmazonCustomerByEmail">
        <EmailAddress xmlns="">xyz@amazon.com</EmailAddress>
      </Grantee>
      <Permission xmlns="">WRITE_ACP</Permission>
    </Grant>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID xmlns="">f30716ab7115dcb44a5ef76e9d74b8e20567f63TestAccountCanonic
alUserID</ID>
      </Grantee>
      <Permission xmlns="">READ_ACP</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: NxqO3PNiMHXXGwjgv15LLgUoAmPVmG0xtZw2sxePXLhpIvcyouXDrcQUaWWXcOK0
x-amz-request-id: C651BC9B4E1BD401
Date: Thu, 12 Apr 2012 20:04:28 GMT
Content-Length: 0
Server: AmazonS3
```

## Sample Request: Access permissions specified using headers

The following request uses ACL-specific request headers to grant the following permissions:

- Write permission to the Amazon S3 LogDelivery group and an AWS account identified by the email xyz@amazon.com.
- Read permission to the Amazon S3 AllUsers group



```
PUT ?acl HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Sun, 29 Apr 2012 22:00:57 GMT
x-amz-grant-write: uri="http://acs.amazonaws.com/groups/s3/LogDelivery",
emailAddress="xyz@amazon.com"
x-amz-grant-read: uri="http://acs.amazonaws.com/groups/global/AllUsers"
Accept: */*
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: 0w9iImt23VF9s6QofOTDzelF7mrryz7d04Mw23FQCi40205Zw28Zn+d340/RytoQ
x-amz-request-id: A6A8F01A38EC7138
Date: Sun, 29 Apr 2012 22:01:10 GMT
Content-Length: 0
Server: AmazonS3
```

## Related Resources

- [PUT Bucket \(p. 89\)](#)
- [DELETE Bucket \(p. 19\)](#)
- [GET Object ACL \(p. 161\)](#)

# PUT Bucket cors

## Description

Sets the `cors` configuration for your bucket. If the configuration exists, Amazon S3 replaces it.

To use this operation, you must be allowed to perform the `s3:PutCORSCONfiguration` action. By default, the bucket owner has this permission and can grant it to others.

You set this configuration on a bucket so that the bucket can service cross-origin requests. For example, you might want to enable a request whose origin is `http://www.example.com` to access your Amazon S3 bucket at `my.example.bucket.com` by using the browser's `XMLHttpRequest` capability.

To enable cross-origin resource sharing (CORS) on a bucket, you add the `cors` subresource to the bucket. The `cors` subresource is an XML document in which you configure rules that identify origins and the HTTP methods that can be executed on your bucket. For example, the following cors configuration on a bucket has two rules:

- The first `CORSRule` allows cross-origin PUT, POST and DELETE requests whose origin is `https://www.example.com` origins. The rule also allows all headers in a pre-flight OPTIONS request through the `Access-Control-Request-Headers` header. Therefore, in response to any pre-flight OPTIONS request, Amazon S3 will return any requested headers.
- The second rule allows cross-origin GET requests from all the origins. The `*` wildcard character refers to all origins.

```
<CORSConfiguration>
  <CORSRule>
    <AllowedOrigin>http://www.example.com</AllowedOrigin>

    <AllowedMethod>PUT</AllowedMethod>
    <AllowedMethod>POST</AllowedMethod>
    <AllowedMethod>DELETE</AllowedMethod>

    <AllowedHeader>*</AllowedHeader>
  </CORSRule>
  <CORSRule>
    <AllowedOrigin>*</AllowedOrigin>
    <AllowedMethod>GET</AllowedMethod>
  </CORSRule>
</CORSConfiguration>
```

The `cors` configuration also allows additional optional configuration parameters as shown in the following cors configuration on a bucket. For example, this `cors` configuration allows cross-origin PUT and POST requests from `http://www.example.com`.

```
<CORSConfiguration>
  <CORSRule>
    <AllowedOrigin>http://www.example.com</AllowedOrigin>
    <AllowedMethod>PUT</AllowedMethod>
    <AllowedMethod>POST</AllowedMethod>
    <AllowedMethod>DELETE</AllowedMethod>
    <AllowedHeader>*</AllowedHeader>
    <MaxAgeSeconds>3000</MaxAgeSeconds>
    <ExposeHeader>x-amz-server-side-encryption</ExposeHeader>
```

```
</CORSRule>  
</CORSConfiguration>
```

In the preceding configuration, `CORSRule` includes the following additional optional parameters:

- `MaxAgeSeconds`—Specifies the time in seconds that the browser will cache an Amazon S3 response to a pre-flight `OPTIONS` request for the specified resource. In this example, this parameter is 3000 seconds. Caching enables the browsers to avoid sending pre-flight `OPTIONS` request to Amazon S3 for repeated requests.
- `ExposeHeader`—Identifies the response header (in this case `x-amz-server-side-encryption`) that you want customers to be able to access from their applications (for example, from a JavaScript `XMLHttpRequest` object).

When Amazon S3 receives a cross-origin request (or a pre-flight `OPTIONS` request) against a bucket, it evaluates the `cors` configuration on the bucket and uses the first `CORSRule` rule that matches the incoming browser request to enable a cross-origin request. For a rule to match, the following conditions must be met:

- The request's `Origin` header must match `AllowedOrigin` elements.
- The request method (for example, `GET`, `PUT`, `HEAD` and so on) or the `Access-Control-Request-Method` header in case of a pre-flight `OPTIONS` request must be one of the `AllowedMethod` elements.
- Every header specified in the `Access-Control-Request-Headers` request header of a pre-flight request must match an `AllowedHeader` element.

For more information about CORS, go to [Enabling Cross-Origin Resource Sharing](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
PUT /?cors HTTP/1.1  
Host: bucketname.s3.amazonaws.com  
Content-Length: length  
Date: date  
Authorization: signatureValue  
Content-MD5: MD5  
  
<CORSConfiguration>  
  <CORSRule>  
    <AllowedOrigin>Origin you want to allow cross-domain requests from</AllowedOrigin>  
    <AllowedOrigin>...</AllowedOrigin>  
    ...  
    <AllowedMethod>HTTP method</AllowedMethod>  
    <AllowedMethod>...</AllowedMethod>  
    ...  
    <MaxAgeSeconds>Time in seconds your browser to cache the pre-flight OPTIONS response for a resource</MaxAgeSeconds>  
    <AllowedHeader>Headers that you want the browser to be allowed to send</AllowedHeader>  
    <AllowedHeader>...</AllowedHeader>  
    ...
```

```
<ExposeHeader>Headers in the response that you want accessible from client
application</ExposeHeader>
<ExposeHeader>...</ExposeHeader>
...
</CORSRule>
<CORSRule>
...
</CORSRule>
...
</CORSConfiguration>
```

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

Name	Description	Required
<i>Content-MD5</i>	The base64-encoded 128-bit MD5 digest of the data. This header must be used as a message integrity check to verify that the request body was not corrupted in transit. For more information, go to <a href="#">RFC 1864</a> .  Type: String  Default: None	Yes

## Request Elements

Name	Description	Required
<i>CORSConfiguration</i>	Container for up to 100 <code>CORSRules</code> elements. Type: Container Children: <code>CORSRules</code> Ancestor: None	Yes
<i>CORSRule</i>	A set of origins and methods (cross-origin access that you want to allow). You can add up to 100 rules to the configuration. Type: Container Children: <code>AllowedOrigin</code> , <code>AllowedMethod</code> , <code>MaxAgeSeconds</code> , <code>ExposeHeader</code> , <code>ID</code> . Ancestor: <code>CORSConfiguration</code>	Yes
<i>ID</i>	A unique identifier for the rule. The ID value can be up to 255 characters long. The IDs help you find a rule in the configuration. Type: String Ancestor: <code>CORSRule</code>	No

Name	Description	Required
<i>AllowedMethod</i>	An HTTP method that you want to allow the origin to execute. Each <i>CORSRule</i> must identify at least one origin and one method. Type: Enum (GET, PUT, HEAD, POST, DELETE) Ancestor: <i>CORSRule</i>	Yes
<i>AllowedOrigin</i>	An origin that you want to allow cross-domain requests from. This can contain at most one * wild character. Each <i>CORSRule</i> must identify at least one origin and one method. The origin value can include at most one '*' wild character. For example, "http://*.example.com". You can also specify only * as the origin value allowing all origins cross-domain access. Type: String Ancestor: <i>CORSRule</i>	Yes
<i>AllowedHeader</i>	Specifies which headers are allowed in a pre-flight OPTIONS request via the <i>Access-Control-Request-Headers</i> header. Each header name specified in the <i>Access-Control-Request-Headers</i> header must have a corresponding entry in the rule. Amazon S3 will send only the allowed headers in a response that were requested. This can contain at most one * wild character. Type: String Ancestor: <i>CORSRule</i>	No
<i>MaxAgeSeconds</i>	The time in seconds that your browser is to cache the preflight response for the specified resource. A <i>CORSRule</i> can have at most one <i>MaxAgeSeconds</i> element. Type: Integer (seconds) Ancestor: <i>CORSRule</i>	No
<i>ExposeHeader</i>	One or more headers in the response that you want customers to be able to access from their applications (for example, from a JavaScript XMLHttpRequest object). You add one <i>ExposeHeader</i> element in the rule for each header. Type: String Ancestor: <i>CORSRule</i>	No

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

The following examples add the `cors` subresource to a bucket.

### Example : Configure cors

#### Sample Request

The following PUT request adds the `cors` subresource to a bucket (`examplebucket`).

```
PUT /?cors HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Tue, 21 Aug 2012 17:54:50 GMT
Content-MD5: 8dYiLewFWZyGgV2Q5FNI4W==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:z6mvnXscCWad60vdmB9xZVVZn46=
Content-Length: 216

<CORSConfiguration>
  <CORSRule>
    <AllowedOrigin>http://www.example.com</AllowedOrigin>
    <AllowedMethod>PUT</AllowedMethod>
    <AllowedMethod>POST</AllowedMethod>
    <AllowedMethod>DELETE</AllowedMethod>
    <AllowedHeader>*</AllowedHeader>
    <MaxAgeSeconds>3000</MaxAgeSec>
    <ExposeHeader>x-amz-server-side-encryption</ExposeHeader>
  </CORSRule>
  <CORSRule>
    <AllowedOrigin>*</AllowedOrigin>
    <AllowedMethod>GET</AllowedMethod>
    <AllowedHeader>*</AllowedHeader>
    <MaxAgeSeconds>3000</MaxAgeSeconds>
  </CORSRule>
</CORSConfiguration>
```

#### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: CCshOvbOPfxzhwOADyC4qHj/Ck3F9Q0viXKw3rivZ+GcBoZSO0ahvEJfPisZB7B
x-amz-request-id: BDC4B83DF5096BBE
Date: Tue, 21 Aug 2012 17:54:50 GMT
Server: AmazonS3
```

## Related Resources

- [GET Bucket cors \(p. 41\)](#)
- [DELETE Bucket cors \(p. 21\)](#)
- [OPTIONS object \(p. 172\)](#)

# PUT Bucket lifecycle

## Description

Creates a new lifecycle configuration for the bucket or replaces an existing lifecycle configuration. For information about lifecycle configuration, go to [Object Lifecycle Management](#) in the *Amazon Simple Storage Service Developer Guide*.

To use this operation, you must be allowed to perform the `s3:PutLifecycleConfiguration` action. By default, the bucket owner has this permission and can grant this permission to others.

### Note

If your bucket is version-enabled or versioning is suspended, you cannot add a lifecycle configuration.

If you want to block users or accounts from removing or deleting objects from your bucket, you must deny them permissions for the following actions:

`s3:DeleteObject`

`s3:DeleteObjectVersion` and

`s3:PutLifecycleConfiguration`

For more information, go to [Access Control](#) section in the *Amazon S3 Developer Guide*.

If you want to block users or accounts from managing lifecycle configurations, you must deny permission for the `s3:PutLifecycleConfiguration` action.

## Requests

### Syntax

```
PUT /?lifecycle HTTP/1.1
Host: bucketname.s3.amazonaws.com
Content-Length: length
Date: date
Authorization: signatureValue
Content-MD5: MD5
```

*Lifecycle configuration in the request body*

### Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

Name	Description	Required
<i>Content-MD5</i>	<p>The base64-encoded 128-bit MD5 digest of the data. This header must be used as a message integrity check to verify that the request body was not corrupted in transit. For more information, go to <a href="#">RFC 1864</a>.</p> <p>Type: String</p> <p>Default: None</p>	Yes

## Request Body

In the request, you specify lifecycle configuration in the request body. The lifecycle configuration is specified as XML with the following elements.

Name	Description	Required
<i>Date</i>	<p>Indicates when the specific rule take effect.</p> <p>The date value must conform to the ISO 8601 format. The time is always midnight UTC.</p> <p>Type: String</p> <p>Ancestor: <i>Expiration</i> or <i>Transition</i></p>	Yes, if <i>Days</i> is absent
<i>Days</i>	<p>Indicates the number of days after creation when the specific rule take effect.</p> <p>Type: non-negative integer</p> <p>Ancestor: <i>Expiration</i> or <i>Transition</i></p>	Yes, if <i>Date</i> is absent
<i>Expiration</i>	<p>Container for the object expiration rule.</p> <p>Type: Container</p> <p>Children: <i>Days</i> or <i>Date</i></p> <p>Ancestor: <i>Rule</i></p>	Yes, if <i>Transition</i> is absent in a <i>Rule</i>
<i>ID</i>	<p>Unique identifier for the rule. The value cannot be longer than 255 characters.</p> <p>Type: String</p> <p>Ancestor: <i>Rule</i></p>	No
<i>LifecycleConfiguration</i>	<p>Container for lifecycle rules. You can add as many as 1000 rules.</p> <p>Type: Container</p> <p>Children: <i>Rule</i></p> <p>Ancestor: None</p>	Yes
<i>Prefix</i>	<p>Object key prefix identifying one or more objects to which the rule applies.</p> <p>Type: String</p> <p>Ancestor: <i>Rule</i></p>	Yes



Name	Description	Required
<i>Rule</i>	Container for a lifecycle rule. Type: Container Ancestor: LifecycleConfiguration	Yes
<i>Status</i>	If Enabled, Amazon S3 executes the rule as scheduled. If Disabled, Amazon S3 ignores the rule. Type: String Ancestor: Rule Valid values: Enabled, Disabled.	Yes
<i>Transition</i>	Container for the transition rule that describes when objects transition to the Glacier storage class. Type: Container Ancestor: Rule	Yes, if Expiration is absent in the Rule
<i>StorageClass</i>	Indicates the Amazon S3 storage class to which you want the object to transition to. Type: String Ancestor: Transition Valid values: GLACIER.	Yes

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Example 1: Configure lifecycle - Archive objects immediately

The following lifecycle configuration rule sets objects with key prefix "glacierobjects/" to transition to storage class "GLACIER" immediately upon creation. Note the transition days value is zero.

```
<LifecycleConfiguration>
  <Rule>
    <ID>delete-all-glacierobjects-in-30-days</ID>
    <Prefix>glacierobjects/</Prefix>
    <Status>Enabled</Status>
    <Transition>
```

```
<Days>0</Days>
<StorageClass>GLACIER</StorageClass>
</Transition>
</Rule>
</LifecycleConfiguration>
```

When you upload an object with "glacierobjects/" key prefix, Amazon S3 archives the object by the next day midnight UTC and sets its storage class to Glacier.

The following is a sample PUT `/?lifecycle` request that adds the preceding lifecycle configuration to the `examplebucket` bucket.

```
PUT /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Tue, 16 Oct 2012 04:20:50 GMT
Content-MD5: 8dYiLewFWZyGgV2Q5FNI4W==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:z6mvnXscCWad60vdmB9xZVVZn46=
Content-Length: 294

<LifecycleConfiguration>
  <Rule>
    <ID>Transition-Immediately-Rule</ID>
    <Prefix>glacierobjects/</Prefix>
    <Status>Enabled</Status>
    <Transition>
      <Days>0</Days>
      <StorageClass>GLACIER</StorageClass>
    </Transition>
  </Rule>
</LifecycleConfiguration>
```

The following is a sample response.

```
HTTP/1.1 200 OK
x-amz-id-2: cIC06kjlCeh41RP7SVdOtPOBYRJdvCqFGf/GYCL4nXgpMqZaFlmrugH6/CFX2Zf4fCe
CURXls0=
x-amz-request-id: D92FE35006B77B4A
Date: Tue, 16 Oct 2012 04:20:37 GMT
Content-Length: 0
Server: AmazonS3
```

## Example 2: Configure lifecycle - First archive and later expire objects

The following PUT `/?lifecycle` request adds a lifecycle configuration to the `examplebucket` bucket. The lifecycle configuration requests Amazon S3 to transition the objects with prefix `glacierobjects/` to the storage class Glacier on December 31, 2012, and subsequently expire them 10 years later.

```
PUT /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Wed, 17 Oct 2012 04:11:08 GMT
Content-MD5: 8dYiLewFWZyGgV2Q5FNI4W==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:z6mvnXscCWad60vdmB9xZVVZn46=
Content-Length: 399

<LifecycleConfiguration>
```

```
<Rule>
  <ID>delete-all-glacierobjects-in-30-days</ID>
  <Prefix>glacierobjects/</Prefix>
  <Status>Enabled</Status>
  <Transition>
    <Date>2012-12-31T00:00:00.000Z</Date>
    <StorageClass>GLACIER</StorageClass>
  </Transition>
  <Expiration>
    <Date>2022-10-12T00:00:00.000Z</Date>
  </Expiration>
</Rule>
</LifecycleConfiguration>
```

The preceding configuration uses date in the setting rules. You can optionally specify number of days since the creation of the objects when these rules take effect as shown in the following example. The lifecycle configuration requests Amazon S3 transition objects with key prefix "glacierobjects/" to Glacier storage class (archive them) 30 days after creation and delete them 365 days after creation date.

```
PUT /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Wed, 17 Oct 2012 04:11:08 GMT
Content-MD5: 8dYiLewFWZyGgV2Q5FNI4W==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:z6mvnXscCWad60vdmB9xZVVZn46=
Content-Length: 399

<LifecycleConfiguration>
  <Rule>
    <ID>delete-all-glacierobjects-in-30-days</ID>
    <Prefix>glacierobjects/</Prefix>
    <Status>Enabled</Status>
    <Transition>
      <Days>30</Days>
      <StorageClass>GLACIER</StorageClass>
    </Transition>
    <Expiration>
      <Days>365</Days>
    </Expiration>
  </Rule>
</LifecycleConfiguration>
```

### Example 3: Configure lifecycle - Specify rule that applies to all objects in the bucket

When you specify an empty prefix, the rule applies to all objects in the bucket. The following PUT /?lifecycle request adds a lifecycle configuration to expire all objects in the bucket 10 years after creation. Note the empty Prefix in the configuration.

```
PUT /?lifecycle HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-date: Tue, 13 Dec 2011 17:54:50 GMT
Content-MD5: 8dYiLewFWZyGgV2Q5FNI4W==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:z6mvnXscCWad60vdmB9xZVVZn46=
Content-Length: 226
```

```
<LifecycleConfiguration>
  <Rule>
    <ID>delete-all-in-30-days-rule</ID>
    <Prefix></Prefix>
    <Status>Enabled</Status>
    <Expiration>
      <Days>3650</Days>
    </Expiration>
  </Rule>
</LifecycleConfiguration>
```

## Related Resources

- [GET Bucket lifecycle \(p. 44\)](#)
- [POST Object restore \(p. 182\)](#)

# PUT Bucket policy

## Description

This implementation of the `PUT` operation uses the *policy* subresource to add to or replace a policy on a bucket. If the bucket already has a policy, the one in this request completely replaces it. To perform this operation, you must be the bucket owner.

If you are not the bucket owner but have *PutBucketPolicy* permissions on the bucket, Amazon S3 returns a *405 Method Not Allowed*. In all other cases for a PUT bucket policy request that is not from the bucket owner, Amazon S3 returns *403 Access Denied*. There are restrictions about who can create bucket policies and which objects in a bucket they can apply to. For more information, go to [Using Bucket Policies](#).

## Requests

### Syntax

```
PUT /?policy HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

*Policy written in JSON*

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

The body is a JSON string containing the policy contents containing the policy statements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

`PUT` response elements return whether the operation succeeded or not.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request shows the `PUT` individual policy request for the bucket.

```
PUT /?policy HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Tue, 04 Apr 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=

{
  "Version": "2008-10-17",
  "Id": "aaaa-bbbb-cccc-dddd",
  "Statement" : [
    {
      "Effect": "Allow",
      "Sid": "1",
      "Principal" : {
        "AWS": [ "111122223333", "444455556666" ]
      },
      "Action": [ "s3:*" ],
      "Resource": "arn:aws:s3:::bucket/*"
    }
  ]
}
```

### Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: Uuag1LuByR5Onimru9SAMPLEAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732SAMPLE7374
Date: Tue, 04 Apr 2010 20:34:56 GMT
Connection: keep-alive
Server: AmazonS3
```

## Related Resources

- [PUT Bucket \(p. 89\)](#)
- [DELETE Bucket \(p. 19\)](#)

# PUT Bucket logging

## Description

### Note

The logging implementation of PUT Bucket is a beta feature.

This implementation of the `PUT` operation uses the `logging` subresource to set the logging parameters for a bucket and to specify permissions for who can view and modify the logging parameters. To set the logging status of a bucket, you must be the bucket owner.

The bucket owner is automatically granted `FULL_CONTROL` to all logs. You use the `Grantee` request element to grant access to other people. The `Permissions` request element specifies the kind of access the grantee has to the logs.

To enable logging, you use `LoggingEnabled` and its children request elements.

To disable logging, you use an empty `BucketLoggingStatus` request element:

```
<BucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01" />
```

For more information about creating a bucket, see [PUT Bucket \(p. 89\)](#). For more information about returning the logging status of a bucket, see [GET Bucket logging \(p. 51\)](#).

## Requests

### Syntax

```
PUT /?logging HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

*Request elements vary depending on what you're setting.*

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

Name	Description	Required
<i>BucketLoggingStatus</i>	Container for logging status information. Type: Container Children: <code>LoggingEnabled</code> Ancestry: None	Yes

**Amazon Simple Storage Service API Reference**  
**PUT Bucket logging**

---

Name	Description	Required
<i>EmailAddress</i>	E-mail address of the person being granted logging permissions. Type: String Children: None Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant.Grantee	No
<i>Grant</i>	Container for the grantee and his/her logging permissions. Type: Container Children: Grantee, Permission Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants	No
<i>Grantee</i>	Container for <i>EmailAddress</i> of the person being granted logging permissions. For more information, see <a href="#">Grantee Values (p. 116)</a> . Type: Container Children: EmailAddress Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant	No
<i>LoggingEnabled</i>	Container for logging information. This element is present when you are enabling logging (and not present when you are disabling logging). Type: Container Children: Grant, TargetBucket, TargetPrefix Ancestry: BucketLoggingStatus	No
<i>Permission</i>	Logging permissions given to the <i>Grantee</i> for the bucket. The bucket owner is automatically granted FULL_CONTROL to all logs delivered to the bucket. This optional element enables you grant access to others. Type: String Valid Values: FULL_CONTROL   READ   WRITE Children: None Ancestry: BucketLoggingStatus.LoggingEnabled.TargetGrants.Grant	No
<i>TargetBucket</i>	Specifies the bucket where you want Amazon S3 to store server access logs. You can have your logs delivered to any bucket that you own, including the same bucket that is being logged. You can also configure multiple buckets to deliver their logs to the same target bucket. In this case you should choose a different TargetPrefix for each source bucket so that the delivered log files can be distinguished by key. Type: String Children: None Ancestry: BucketLoggingStatus.LoggingEnabled	No



Name	Description	Required
<i>TargetGrants</i>	Container for granting information. Type: Container Children: Grant, Permission Ancestry: BucketLoggingStatus.LoggingEnabled	No
<i>TargetPrefix</i>	This element lets you specify a prefix for the keys that the log files will be stored under. Type: String Children: None Ancestry: BucketLoggingStatus.LoggingEnabled	No

## Grantee Values

You can specify the person (grantee) to whom you're assigning access rights (using request elements) in the following ways:

- By the person's ID:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:type="CanonicalUser">
  <ID>ID</ID>
  <DisplayName>GranteesEmail</DisplayName>
</Grantee>
```

*DisplayName* is optional and ignored in the request.

- By Email address:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="AmazonCustomerByEmail">
  <EmailAddress>Grantees@email.com</EmailAddress>
</Grantee>
```

The grantee is resolved to the *CanonicalUser* and, in a response to a GET Object acl request, appears as the *CanonicalUser*.

- By URI:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="Group">
  <URI>http://acs.amazonaws.com/groups/global/AuthenticatedUsers</URI>
</Grantee>
```

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

## Response Elements

This implementation of the operation does not return response elements.

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request enables logging and gives the grantee of the bucket READ access to the logs.

```
PUT ?logging HTTP/1.1
Host: quotes.s3.amazonaws.com
Content-Length: 214
Date: Wed, 25 Nov 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=

<?xml version="1.0" encoding="UTF-8"?>
<BucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <LoggingEnabled>
    <TargetBucket>mybucketlogs</TargetBucket>
    <TargetPrefix>mybucket-access_log-</TargetPrefix>
    <TargetGrants>
      <Grant>
        <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
          xsi:type="AmazonCustomerByEmail">
          <EmailAddress>user@company.com</EmailAddress>
        </Grantee>
        <Permission>READ</Permission>
      </Grant>
    </TargetGrants>
  </LoggingEnabled>
</BucketLoggingStatus>
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
```

### Sample Request Disabling Logging

This request disables logging on the bucket, quotes.

```
PUT ?logging HTTP/1.1
Host: quotes.s3.amazonaws.com
Content-Length: 214
Date: Wed, 25 Nov 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

```
<?xml version="1.0" encoding="UTF-8"?>
<BucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01" />
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFBiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
```

## Related Resources

- [PUT Object \(p. 185\)](#)
- [DELETE Bucket \(p. 19\)](#)
- [PUT Bucket \(p. 89\)](#)
- [GET Bucket logging \(p. 51\)](#)

# PUT Bucket notification

## Description

This implementation of the `PUT` operation uses the *notification* subresource to enable notifications of specified events for a bucket. Currently, the *s3:ReducedRedundancyLostObject* event is the only event supported for notifications. The *s3:ReducedRedundancyLostObject* event is triggered when Amazon S3 detects that it has lost all replicas of an object and can no longer service requests for that object.

If the bucket owner and Amazon SNS topic owner are the same, the bucket owner has permission to publish notifications to the topic by default. Otherwise, the owner of the topic must create a policy to enable the bucket owner to publish to the topic. For more information about creating this policy, go to [Example Cases for Amazon SNS Access Control](#).

By default, only the bucket owner can configure notifications on a bucket. However, bucket owners can use a bucket policy to grant permission to other users to set this configuration with *s3:PutBucketNotification* permission.

After you call the `PUT` operation to configure notifications on a bucket, Amazon S3 publishes a test notification to ensure that the topic exists and that the bucket owner has permission to publish to the specified topic. If the notification is successfully published to the SNS topic, the `PUT` operation updates the bucket configuration and returns the 200 OK response with a *x-amz-sns-test-message-id* header containing the message ID of the test notification sent to topic.

To turn off notifications on a bucket, you specify an empty *NotificationConfiguration* element in your request: `<NotificationConfiguration />`

For more information about setting and reading the notification configuration on a bucket, see [Setting Up Notification of Bucket Events](#). For more information about bucket policies, see [Using Bucket Policies](#).

## Requests

### Syntax

```
PUT /?notification HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
<NotificationConfiguration>
  <TopicConfiguration>
    <Topic>TopicARN</Topic>
    <Event>Event</Event>
  </TopicConfiguration>
</NotificationConfiguration>
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

## Request Elements

Name	Description	Required
<i>NotificationConfiguration</i>	Container for specifying the notification configuration of the bucket. If this element is empty, notifications are turned off on the bucket. Type: Container Children: <i>TopicConfiguration</i> Ancestry: None	Yes
<i>TopicConfiguration</i>	Container for specifying the topic configuration for the notification. Currently, only one topic can be configured for notifications. Type: Container Children: <i>Topic</i> , <i>Event</i> Ancestry: <i>NotificationConfiguration</i>	No
<i>Topic</i>	Amazon SNS topic to which Amazon S3 will publish a message to report the specified events for the bucket. Type: String Ancestry: <i>TopicConfiguration</i>	No
<i>Event</i>	Bucket event for which to send notifications. Currently, <i>s3:ReducedRedundancyLostObject</i> is the only event supported for notifications. Type: String Valid Values: <i>s3:ReducedRedundancyLostObject</i> Ancestry: <i>TopicConfiguration</i>	No

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

Amazon S3 checks the validity of the proposed *NotificationConfiguration* element and verifies whether the proposed configuration is valid when you call the `PUT` operation. The following table lists the errors and possible causes.

HTTP Error	Code	Cause
HTTP 400 Bad Request	InvalidArgument	<p>The following conditions can cause this error:</p> <ul style="list-style-type: none"> <li>• The specified event is not supported for notifications.</li> <li>• The specified topic ARN does not exist or is not well-formed. Verify the topic ARN.</li> <li>• The specified topic is in a different region than the bucket. You must use a topic that resides in the same Region as the bucket.</li> <li>• The bucket owner does not have <i>Publish</i> permission on the specified topic.</li> </ul>
HTTP 403 Forbidden	AccessDenied	<p>You are not the owner of the specified bucket or you do not have the <i>s3:PutBucketNotification</i> bucket permission to set the notification configuration on the bucket.</p>

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Requests

This request enables notification on bucket `quotes.s3.amazonaws.com` for the event *s3:ReducedRedundancyLostObject* with notifications published to the topic `arn:aws:sns:us-east-1:123456789012:myTopic`.

```
PUT ?notification HTTP/1.1
Host: quotes.s3.amazonaws.com
Date: Wed, 02 June 2010 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
<NotificationConfiguration>
  <TopicConfiguration>
    <Topic>arn:aws:sns:us-east-1:123456789012:myTopic</Topic>
    <Event>s3:ReducedRedundancyLostObject</Event>
  </TopicConfiguration>
</NotificationConfiguration>
```

This request turns off notification on the `quotes.s3.amazonaws.com` bucket.

```
PUT ?notification HTTP/1.1
Host: quotes.s3.amazonaws.com
Date: Wed, 02 June 2010 12:01:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
<NotificationConfiguration />
```

### Sample Responses

In this response, you are notified that the notification configuration was successful. It also returns the ID of the test message Amazon S3 sent to the topic.

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbIKa2bj0KMgUAdQkf3ShJTOOpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
x-amz-sns-test-message-id: feebldff-cc96-449d-964c-f8a1890fd007
Date: Wed, 02 Jun 2010 12:00:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

This response returns that the notification was turned off successfully. Note that Amazon S3 doesn't send a test notification when notifications are turned off.

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbIKa2bj0KMgUAdQkf3ShJTOOpXUueF6QKo
x-amz-request-id: 236A890524860101
Date: Wed, 02 Jun 2010 12:01:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Related Resources

- [GET Bucket notification \(p. 54\)](#)

# PUT Bucket tagging

## Description

This implementation of the `PUT` operation uses the *tagging* subresource to add a set of tags to an existing bucket.

Use tags to organize your AWS bill to reflect your own cost structure. To do this, sign up to get your AWS account bill with tag key values included. Then, to see the cost of combined resources, organize your billing information according to resources with the same tag key values. For example, you can tag several resources with a specific application name, and then organize your billing information to see the total cost of that application across several services. For more information, see [Cost Allocation and Tagging in About AWS Account Billing](#).

To use this operation, you must have permission to perform the `s3:PutBucketTagging` action. By default, the bucket owner has this permission and can grant this permission to others.

## Requests

### Syntax

The following request shows the syntax for sending tagging information in the request body.

```
PUT /?tagging HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue

<Tagging>
  <TagSet>
    <Tag>
      <Key>Tag Name</Key>
      <Value>Tag Value</Value>
    </Tag>
  </TagSet>
</Tagging>
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

Content-MD5 will be a required header for this operation.

### Request Elements

Name	Description	Required
<i>Tagging</i>	Container for the <code>TagSet</code> and <code>Tag</code> elements. Type: String Ancestors: None	Yes



Name	Description	Required
<i>TagSet</i>	Container for a set of tags Type: Container Ancestors: Tagging	Yes
<i>Tag</i>	Container for tag information. Type: Container Ancestors: TagSet	Yes
<i>Key</i>	Name of the tag. Type: String Ancestors: Tag	Yes
<i>Value</i>	Value of the tag. Type: String Ancestors: Tag	Yes

## Responses

### Response Headers

The operation returns response header that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This operation does not return response elements.

### Special Errors

- **InvalidTagError** - The tag provided was not a valid tag. This error can occur if the tag did not pass input validation. See the [CostAllocation](#) docs for a description of valid tags.
- **MalformedXMLError** - The XML provided does not match the schema.
- **OperationAbortedError** - A conflicting conditional operation is currently in progress against this resource. Please try again.
- **InternalError** - The service was unable to apply the provided tag to the bucket.

## Examples

### Sample Request: Add tag set to a bucket

The following request adds a tag set to the existing `examplebucket` bucket.

```
PUT ?tagging HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Content-Length: 1660
x-amz-date: Thu, 12 Apr 2012 20:04:21 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=

<Tagging>
```

```
<TagSet>
  <Tag>
    <Key>Project</Key>
    <Value>Project One</Value>
  </Tag>
  <Tag>
    <Key>User</Key>
    <Value>jsmith</Value>
  </Tag>
</TagSet>
</Tagging>
```

## Sample Response

```
HTTP/1.1 204 No Content
x-amz-id-2: YgIPiFBiKa2bj0KMgUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Oct 2012 12:00:00 GMT
```

## Related Resources

- [GET Bucket tagging \(p. 57\)](#)
- [DELETE Bucket tagging \(p. 27\)](#)

# PUT Bucket requestPayment

## Description

This implementation of the `PUT` operation uses the `requestPayment` subresource to set the request payment configuration of a bucket. By default, the bucket owner pays for downloads from the bucket. This configuration parameter enables the bucket owner (only) to specify that the person requesting the download will be charged for the download. For more information, see [Requester Pays Buckets](#).

## Requests

### Syntax

```
PUT ?requestPayment HTTP/1.1
Host: BucketName.s3.amazonaws.com
Content-Length: length
Date: date
Authorization: signatureValue

<RequestPaymentConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Payer>payer</Payer>
</RequestPaymentConfiguration>
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

Name	Description
<i>Payer</i>	Specifies who pays for the download and request fees. Type: Enum Valid Values: Requester   BucketOwner Ancestor: RequestPaymentConfiguration
<i>RequestPaymentConfiguration</i>	Container for <i>Payer</i> . Type: Container

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

## Response Elements

This implementation of the operation does not return response elements.

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This request creates a Requester Pays bucket named "colorpictures."

```
PUT ?requestPayment HTTP/1.1
Host: colorpictures.s3.amazonaws.com
Content-Length: 173
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=

<RequestPaymentConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Payer>Requester</Payer>
</RequestPaymentConfiguration>
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPIfBiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJTOOpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
Location: /colorpictures
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Related Resources

- [PUT Bucket \(p. 89\)](#)
- [GET Bucket requestPayment \(p. 72\)](#)

# PUT Bucket versioning

## Description

This implementation of the `PUT` operation uses the `versioning` subresource to set the versioning state of an existing bucket. To set the versioning state, you must be the bucket owner.

You can set the versioning state with one of the following values:

- **Enabled**—Enables versioning for the objects in the bucket  
All objects added to the bucket receive a unique version ID.
- **Suspended**—Disables versioning for the objects in the bucket  
All objects added to the bucket receive the version ID `null`.

If the versioning state has never been set on a bucket, it has no versioning state; a `GET versioning` request does not return a versioning state value.

If the bucket owner enables MFA Delete in the bucket versioning configuration, the bucket owner must include the `x-amz-mfa` request header and the `Status` and the `MfaDelete` request elements in a request to set the versioning state of the bucket.

For more information about creating a bucket, see [PUT Bucket \(p. 89\)](#). For more information about returning the versioning state of a bucket, see [GET Bucket Versioning Status \(p. 74\)](#).

## Requests

### Syntax

```
PUT /?versioning HTTP/1.1
Host: BucketName.s3.amazonaws.com
Content-Length: length
Date: date
Authorization: signatureValue
x-amz-mfa: [SerialNumber] [TokenCode]

<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>VersioningState</Status>
  <MfaDelete>MfaDeleteState</MfaDelete>
</VersioningConfiguration>
```

Note the space between [*SerialNumber*] and [*TokenCode*].

### Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

Name	Description	Required
<i>x-amz-mfa</i>	The value is the concatenation of the authentication device's serial number, a space, and the value displayed on your authentication device. Type: String Default: None Condition: Required to configure the versioning state if versioning is configured with MFA Delete enabled.	Conditional

## Request Elements

Name	Description	Required
<i>Status</i>	Sets the versioning state of the bucket. Type: Enum Valid Values: Suspended   Enabled Ancestor: VersioningConfiguration	No
<i>MfaDelete</i>	Specifies whether MFA Delete is enabled in the bucket versioning configuration. When enabled, the bucket owner must include the <i>x-amz-mfa</i> request header in requests to change the versioning state of a bucket and to permanently delete a versioned object. Type: Enum Valid Values: Disabled   Enabled Ancestor: VersioningConfiguration Constraint: Can only be used when you use <i>Status</i> .	No
<i>VersioningConfiguration</i>	Container for setting the versioning state. Type: Container Children: Status Ancestor: None	Yes

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

This implementation of the operation does not return response elements.

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request enables versioning for the specified bucket.

```
PUT /?versioning HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 124

<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Enabled</Status>
</VersioningConfiguration>
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
```

### Sample Request

The following request suspends versioning for the specified bucket.

```
PUT /?versioning HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 124

<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Suspended</Status>
</VersioningConfiguration>
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT
```

## Sample Request Enabling Versioning and MFA Delete on a Bucket

The following request enables versioning and MFA Delete on a bucket.

```
PUT /?versioning HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
x-amz-mfa:[SerialNumber] [TokenCode]
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 124

<VersioningConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Status>Enabled</Status>
  <MfaDelete>Enabled</MfaDelete>
</VersioningConfiguration>
```

Note the space between [*SerialNumber*] and [*TokenCode*] and that you must include *Status* whenever you use *MfaDelete*.

## Sample Response

```
HTTPS/1.1 200 OK
x-amz-id-2: YgIPiFbiKa2bj0KMg95r/0zo3emzU4dzsD4rcKCHQUAdQkf3ShJT0OpXUueF6QKo
x-amz-request-id: 236A8905248E5A01
Date: Wed, 01 Mar 2009 12:00:00 GMT

Location: /colourpictures
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Related Resources

- [DELETE Bucket \(p. 19\)](#)
- [PUT Bucket \(p. 89\)](#)



# PUT Bucket website

## Description

Sets the configuration of the website that is specified in the *website* subresource. To configure a bucket as a website, you can add this subresource on the bucket with website configuration information such as the file name of the index document and any redirect rules. For more information, go to [Hosting Websites on Amazon S3](#) in the *Amazon S3 Developer Guide*.

This PUT operation requires the `S3:PutBucketWebsite` permission. By default, only the bucket owner can configure the *website* attached to a bucket; however, bucket owners can allow other users to set the *website* configuration by writing a bucket policy that grants them the `S3:PutBucketWebsite` permission.

## Requests

### Syntax

```
PUT /?website HTTP/1.1
Host: bucketname.s3.amazonaws.com
Date: date
Content-Length: ContentLength
Authorization: signatureValue

<WebsiteConfiguration xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <!-- website configuration information. -->
</WebsiteConfiguration>
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

You can use a website configuration to redirect all requests to the website endpoint of a bucket, or you can add routing rules that redirect only specific requests.

- To redirect all website requests sent to the bucket's website endpoint, you add a website configuration with the following elements. Because all requests are sent to another website, you don't need to provide index document name for the bucket.

Name	Description	Required
<i>WebsiteConfiguration</i>	The root element for the website configuration Type: Container Ancestors: None	Yes

Name	Description	Required
<i>RedirectAllRequestsTo</i>	Describes the redirect behavior for every request to this bucket's website endpoint. If this element is present, no other siblings are allowed. Type: Container Ancestors: WebsiteConfiguration	Yes
<i>HostName</i>	Name of the host where requests will be redirected. Type: String Ancestors: RedirectAllRequestsTo	Yes
<i>Protocol</i>	Protocol to use (http, https) when redirecting requests. The default is the protocol that is used in the original request. Type: String Ancestors: RedirectAllRequestsTo	No

- If you want granular control over redirects, you can use the following elements to add routing rules that describe conditions for redirecting requests and information about the redirect destination. In this case, the website configuration must provide an index document for the bucket, because some requests might not be redirected.

Name	Description	Required
<i>WebsiteConfiguration</i>	Container for the request Type: Container Ancestors: None	Yes
<i>IndexDocument</i>	Container for the <i>Suffix</i> element. Type: Container Ancestors: WebsiteConfiguration	Yes
<i>Suffix</i>	A suffix that is appended to a request that is for a <i>directory</i> on the website endpoint (e.g., if the suffix is <i>index.html</i> and you make a request to <i>samplebucket/images/</i> , the data that is returned will be for the object with the key name <i>images/index.html</i> ) The suffix must not be empty and must not include a slash character. Type: String Ancestors: WebsiteConfiguration.IndexDocument	Yes
<i>ErrorDocument</i>	Container for the <i>Key</i> element Type: Container Ancestors: WebsiteConfiguration	No

Name	Description	Required
<i>Key</i>	The object key name to use when a 4XX class error occurs. This key identifies the page that is returned when such an error occurs. Type: String Ancestors: WebsiteConfiguration.ErrorDocument Condition: Required when <i>ErrorDocument</i> is specified.	Conditional
<i>RoutingRules</i>	Container for a collection of RoutingRule elements. Type: Container Ancestors: WebsiteConfiguration	No
<i>RoutingRule</i>	Container for one routing rule that identifies a condition and a redirect that applies when the condition is met. Type: String Ancestors: WebsiteConfiguration.RoutingRules Condition: In a <i>RoutingRules</i> container, there must be at least one of <i>RoutingRule</i> element.	Yes
<i>Condition</i>	A container for describing a condition that must be met for the specified redirect to apply. For example: <ul style="list-style-type: none"> <li>• If request is for pages in the <code>/docs</code> folder, redirect to the <code>/documents</code> folder.</li> <li>• If request results in HTTP error 4xx, redirect request to another host where you might process the error.</li> </ul> Type: Container Ancestors: WebsiteConfiguration.RoutingRules.RoutingRule	No
<i>KeyPrefixEquals</i>	The object key name prefix when the redirect is applied. For example, to redirect requests for <code>ExamplePage.html</code> , the key prefix will be <code>ExamplePage.html</code> . To redirect request for all pages with the prefix <code>docs/</code> , the key prefix will be <code>/docs</code> , which identifies all objects in the <code>docs/</code> folder. Type: String Ancestors: WebsiteConfiguration.RoutingRules.RoutingRule.Condition Condition: Required when the parent element <i>Condition</i> is specified and sibling <i>HttpErrorCodeReturnedEquals</i> is not specified. If both conditions are specified, both must be true for the redirect to be applied.	Conditional

Name	Description	Required
<i><del>HttpErrorCodeReturnedEquals</del></i>	<p>The HTTP error code when the redirect is applied. In the event of an error, if the error code equals this value, then the specified redirect is applied.</p> <p>Type: String</p> <p>Ancestors:  WebsiteConfiguration.RoutingRules.RoutingRule.Condition</p> <p>Condition: Required when parent element <i>Condition</i> is specified and sibling <i>KeyPrefixEquals</i> is not specified. If both are specified, then both must be true for the redirect to be applied.</p>	Conditional
<i>Redirect</i>	<p>Container for redirect information. You can redirect requests to another host, to another page, or with another protocol. In the event of an error, you can specify a different error code to return.</p> <p>Type: String</p> <p>Ancestors:  WebsiteConfiguration.RoutingRules.RoutingRule</p>	Yes
<i>Protocol</i>	<p>The protocol to use in the redirect request.</p> <p>Type: String</p> <p>Ancestors:  WebsiteConfiguration.RoutingRules.RoutingRule.Redirect</p> <p>Valid Values: http, https</p> <p>Condition: Not required if one of the siblings is present</p>	No
<i>HostName</i>	<p>The host name to use in the redirect request.</p> <p>Type: String</p> <p>Ancestors:  WebsiteConfiguration.RoutingRules.RoutingRule.Redirect</p> <p>Condition: Not required if one of the siblings is present</p>	No
<i>ReplaceKeyPrefixWith</i>	<p>The object key prefix to use in the redirect request. For example, to redirect requests for all pages with prefix docs/ (objects in the docs/ folder) to documents/, you can set a condition block with <i>KeyPrefixEquals</i> set to docs/ and in the <i>Redirect</i> set <i>ReplaceKeyPrefixWith</i> to /documents.</p> <p>Type: String</p> <p>Ancestors:  WebsiteConfiguration.RoutingRules.RoutingRule.Redirect</p> <p>Condition: Not required if one of the siblings is present. Can be present only if <i>ReplaceKeyWith</i> is not provided.</p>	No

Name	Description	Required
<i>ReplaceKeyWith</i>	The specific object key to use in the redirect request. For example, redirect request to <code>error.html</code> . Type: String Ancestors: WebsiteConfiguration.RoutingRules.RoutingRule.Redirect Condition: Not required if one of the sibling is present. Can be present only if <i>ReplaceKeyPrefixWith</i> is not provided.	No
<i>HttpRedirectCode</i>	The HTTP redirect code to use on the response. Type: String Ancestors: WebsiteConfiguration.RoutingRules.RoutingRule.Redirect Condition: Not required if one of the siblings is present.	No

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

## Examples

### Example 1: Configure bucket as a website (add website configuration)

The following request configures a bucket `example.com` as a website. The configuration in the request specifies `index.html` as the index document. It also specifies the optional error document, `SomeErrorDocument.html`.

```
PUT ?website HTTP/1.1
Host: example.com.s3.amazonaws.com
Content-Length: 256
Date: Thu, 27 Jan 2011 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sWO+ugzxhf2AtcqRLGy70B=

<WebsiteConfiguration xmlns='http://s3.amazonaws.com/doc/2006-03-01/'>
  <IndexDocument>
    <Suffix>index.html</Suffix>
  </IndexDocument>
  <ErrorDocument>
    <Key>SomeErrorDocument.html</Key>
  </ErrorDocument>
</WebsiteConfiguration>
```

Amazon S3 returns the following sample response.

```
HTTP/1.1 200 OK
x-amz-id-2: YgIPfBiKa2bj0KMgUAdQkf3ShJTOOpXUueF6QKo
x-amz-request-id: 80CD4368BD211111
Date: Thu, 27 Jan 2011 00:00:00 GMT
Content-Length: 0
Server: AmazonS3
```

## Example 2: Configure bucket as a website but redirect all requests

The following request configures a bucket `www.example.com` as a website; however, the configuration specifies that all GET requests for the `www.example.com` bucket's website endpoint will be redirected to host `example.com`.

```
PUT ?website HTTP/1.1
Host: www.example.com.s3.amazonaws.com
Content-Length: length-value
Date: Thu, 27 Jan 2011 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sW0+ugzxhf2AtcqRLgy70B=

<WebsiteConfiguration xmlns='http://s3.amazonaws.com/doc/2006-03-01/'>
  <RedirectAllRequestsTo>
    <HostName>example.com</HostName>
  </RedirectAllRequestsTo>
</WebsiteConfiguration>
```

This redirect can be useful when you want to serve requests for both `http://www.example.com` and `http://example.com`, but you want to maintain the website content in only one bucket, in this case `example.com`. For more information, go to [Hosting Websites on Amazon S3](#) in the *Amazon Simple Storage Service Developer Guide*.

## Example 3: Configure bucket as a website and also specify optional redirection rules

Example 1 is the simplest website configuration. It configures a bucket as a website by providing only an index document and an error document. You can further customize the website configuration by adding routing rules that redirect requests for one or more objects. For example, suppose your bucket contained the following objects:

`index.html`

`docs/article1.html`

`docs/article2.html`

If you decided to rename the folder from `docs/` to `documents/`, you would need to redirect requests for prefix `/docs` to `documents/`. For example, a request for `docs/article1.html` will need to be redirected to `documents/article1.html`.

In this case, you update the website configuration and add a routing rule as shown in the following request:

```
PUT ?website HTTP/1.1
Host: www.example.com.s3.amazonaws.com
Content-Length: length-value
Date: Thu, 27 Jan 2011 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sW0+ugzxhf2AtcqRLgy70B=
```

```
<WebsiteConfiguration xmlns='http://s3.amazonaws.com/doc/2006-03-01/'>
  <IndexDocument>
    <Suffix>index.html</Suffix>
  </IndexDocument>
  <ErrorDocument>
    <Key>Error.html</Key>
  </ErrorDocument>

  <RoutingRules>
    <RoutingRule>
      <Condition>
        <KeyPrefixEquals>docs/</KeyPrefixEquals>
      </Condition>
      <Redirect>
        <ReplaceKeyPrefixWith>documents/</ReplaceKeyPrefixWith>
      </Redirect>
    </RoutingRule>
  </RoutingRules>
</WebsiteConfiguration>
```

#### Example 4: Configure bucket as a website and redirect errors

You can use a routing rule to specify a condition that checks for a specific HTTP error code. When a page request results in this error, you can optionally reroute requests. For example, you might route requests to another host and optionally process the error. The routing rule in the following requests redirects requests to an EC2 instance in the event of an HTTP error 404. For illustration, the redirect also inserts a object key prefix `report-404/` in the redirect. For example, if you request a page `ExamplePage.html` and it results in a HTTP 404 error, the request is routed to a page `report-404/testPage.html` on the specified EC2 instance. If there is no routing rule and the HTTP error 404 occurred, then `Error.html` would be returned.

```
PUT ?website HTTP/1.1
Host: www.example.com.s3.amazonaws.com
Content-Length: 580
Date: Thu, 27 Jan 2011 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sW0+ugzxhf2AtcqRLgy70B=

<WebsiteConfiguration xmlns='http://s3.amazonaws.com/doc/2006-03-01/'>
  <IndexDocument>
    <Suffix>index.html</Suffix>
  </IndexDocument>
  <ErrorDocument>
    <Key>Error.html</Key>
  </ErrorDocument>

  <RoutingRules>
    <RoutingRule>
      <Condition>
        <HttpErrorCodeReturnedEquals>404</HttpErrorCodeReturnedEquals >
      </Condition>
      <Redirect>
        <HostName>ec2-11-22-333-44.compute-1.amazonaws.com</HostName>
        <ReplaceKeyPrefixWith>report-404/</ReplaceKeyPrefixWith>
      </Redirect>
    </RoutingRule>
```

```
</RoutingRules>  
</WebsiteConfiguration>
```

### Example 5: Configure a bucket as a website and redirect folder requests to a page

Suppose you have the following pages in your bucket:

images/photo1.jpg

images/photo2.jpg

images/photo3.jpg

Now you want to route requests for all pages with the `images/` prefix to go to a single page, `errorpage.html`. You can add a website configuration to your bucket with the routing rule shown in the following request:

```
PUT ?website HTTP/1.1  
Host: www.example.com.s3.amazonaws.com  
Content-Length: 481  
Date: Thu, 27 Jan 2011 12:00:00 GMT  
Authorization: AWS AKIAIOSFODNN7EXAMPLE:acxI7sWO+ugzxhf2AtcqRLgy70B=  
  
<WebsiteConfiguration xmlns='http://s3.amazonaws.com/doc/2006-03-01/'>  
  <IndexDocument>  
    <Suffix>index.html</Suffix>  
  </IndexDocument>  
  <ErrorDocument>  
    <Key>Error.html</Key>  
  </ErrorDocument>  
  
  <RoutingRules>  
    <RoutingRule>  
      <Condition>  
        <KeyPrefixEquals>images/</KeyPrefixEquals>  
      </Condition>  
      <Redirect>  
        <ReplaceKeyWith>errorpage.html</ReplaceKeyWith>  
      </Redirect>  
    </RoutingRule>  
  </RoutingRules>  
</WebsiteConfiguration>
```

## Operations on Objects

### Topics

- [DELETE Object \(p. 141\)](#)
- [Delete Multiple Objects \(p. 144\)](#)
- [GET Object \(p. 153\)](#)
- [GET Object ACL \(p. 161\)](#)
- [GET Object torrent \(p. 165\)](#)
- [HEAD Object \(p. 167\)](#)



- [OPTIONS object](#) (p. 172)
- [POST Object](#) (p. 175)
- [POST Object restore](#) (p. 182)
- [PUT Object](#) (p. 185)
- [PUT Object acl](#) (p. 194)
- [PUT Object - Copy](#) (p. 201)
- [Initiate Multipart Upload](#) (p. 210)
- [Upload Part](#) (p. 216)
- [Upload Part - Copy](#) (p. 219)
- [Complete Multipart Upload](#) (p. 224)
- [Abort Multipart Upload](#) (p. 229)
- [List Parts](#) (p. 231)

This section describes operations you can perform on Amazon S3 objects.

**Note**

For information about access policies, see [REST Access Policy](#) .

# DELETE Object

## Description

The `DELETE` operation removes the null version (if there is one) of an object and inserts a delete marker, which becomes the latest version of the object. If there isn't a null version, Amazon S3 does not remove any objects.

## Versioning

To remove a specific version, you must be the bucket owner and you must use the `versionId` subresource. Using this subresource permanently deletes the version. If the object deleted is a Delete Marker, Amazon S3 sets the response header, `x-amz-delete-marker`, to `true`.

If the object you want to delete is in a bucket where the bucket versioning configuration is MFA Delete enabled, you must include the `x-amz-mfa` request header in the `DELETE versionId` request. Requests that include `x-amz-mfa` must use HTTPS.

For more information about MFA Delete, go to [Using MFA Delete](#). To see sample requests that use versioning, see [Sample Request \(p. 143\)](#).

You can delete objects by explicitly calling the `DELETE Object` API or configure its lifecycle (see [PUT Bucket lifecycle \(p. 106\)](#)) to enable Amazon S3 to remove them for you. If you want to block users or accounts from removing or deleting objects from your bucket you must deny them `s3:DeleteObject`, `s3:DeleteObjectVersion` and `s3:PutLifecycleConfiguration` actions.

## Requests

### Syntax

```
DELETE /ObjectName HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Content-Length: length
Authorization: signatureValue
```

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

Name	Description	Required
<code>x-amz-mfa</code>	The value is the concatenation of the authentication device's serial number, a space, and the value displayed on your authentication device. Type: String Default: None Condition: Required to permanently delete a versioned object if versioning is configured with MFA Delete enabled.	Conditional

## Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

Header	Description
x-amz-delete-marker	Specifies whether the versioned object that was permanently deleted was ( <code>true</code> ) or was not ( <code>false</code> ) a delete marker. In a simple DELETE, this header indicates whether ( <code>true</code> ) or not ( <code>false</code> ) a delete marker was created. Type: Boolean Valid Values: <code>true</code>   <code>false</code> Default: <code>false</code>
x-amz-version-id	Returns the version ID of the delete marker created as a result of the DELETE operation. If you delete a specific object version, the value returned by this header is the version ID of the object version deleted. Type: String Default: None

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request deletes the object, `my-second-image.jpg`.

```
DELETE /my-second-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
```

### Sample Response

```
HTTP/1.1 204 NoContent
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEb1a0wiIOIx1+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
Date: Wed, 12 Oct 2009 17:50:00 GMT
Content-Length: 0
```

```
Connection: close
Server: AmazonS3
```

## Sample Request Deleting a Specified Version of an Object

The following request deletes the specified version of the object, `my-third-image.jpg`.

```
DELETE /my-third-image.jpg?versionId=UIORUnfndfiufdisojhr398493jfdkjFJjkndnqUif
hnw89493jJFJ HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 0
```

## Sample Response

```
HTTP/1.1 204 NoContent
x-amz-id-2: LriYPLdmOdAiIfgSm/FlYsViT1LW94/xUQxMsF7xiEbla0wiIOIx1+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: UIORUnfndfiufdisojhr398493jfdkjFJjkndnqUifhnw89493jJFJ
Date: Wed, 12 Oct 2009 17:50:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Sample Response if the Object Deleted is a Delete Marker

```
HTTP/1.1 204 NoContent
x-amz-id-2: LriYPLdmOdAiIfgSm/FlYsViT1LW94/xUQxMsF7xiEbla0wiIOIx1+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: 3/L4kqtJlcpXroDTdMJ+rmSpXd3dIbrHY+MTRCxf3vjVBH40Nr8X8gdRQBpUM
LUo
x-amz-delete-marker: true
Date: Wed, 12 Oct 2009 17:50:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Sample Request Deleting a Specified Version of an Object in an MFA-Enabled Bucket

The following request deletes the specified version of the object, `my-third-image.jpg`, which is stored in an MFA-enabled bucket.

```
DELETE /my-third-image.jpg?versionId=UIORUnfndfiuf HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
x-amz-mfa: [SerialNumber] [AuthenticationCode]
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 0
```

## Sample Response

```
HTTPS/1.1 204 NoContent
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEbla0wiIOIx1+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: UIORUnfndfiuf
Date: Wed, 12 Oct 2009 17:50:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Related Resources

- [PUT Object \(p. 185\)](#)
- [DELETE Object \(p. 141\)](#)

# Delete Multiple Objects

## Description

The Multi-Object Delete operation enables you to delete multiple objects from a bucket using a single HTTP request. If you know the object keys that you want to delete, then this operation provides a suitable alternative to sending individual delete requests (see [DELETE Object \(p. 141\)](#)), reducing per-request overhead.

The Multi-Object Delete request contains a list of up to 1000 keys that you want to delete. In the XML, you provide the object key names, and optionally, version IDs if you want to delete a specific version of the object from a versioning-enabled bucket. For each key, Amazon S3 performs a delete operation and returns the result of that delete, success, or failure, in the response. Note that, if the object specified in the request is not found, Amazon S3 returns the result as deleted.

The Multi-Object Delete operation supports two modes for the response; verbose and quiet. By default, the operation uses verbose mode in which the response includes the result of deletion of each key in your request. In quiet mode the response includes only keys where the delete operation encountered an error. For a successful deletion, the operation does not return any information about the delete in the response body.

When performing a Multi-Object Delete operation on an MFA Delete enabled bucket, that attempts to delete any versioned objects, you must include an MFA token. If you do not provide one, the entire request will fail, even if there are non versioned objects you are attempting to delete. If you provide an invalid token, whether there are versioned keys in the request or not, the entire Multi-Object Delete request will fail. For information about MFA Delete, see [MFA Delete](#).

Finally, the Content-MD5 header is required for all Multi-Object Delete requests. Amazon S3 uses the header value to ensure that your request body has not be altered in transit.

## Requests

### Syntax

```
POST /?delete HTTP/1.1
Host: bucketname.s3.amazonaws.com
Authorization: Signature
```

```
Content-Length: Size
Content-MD5: MD5

<?xml version="1.0" encoding="UTF-8"?>
<Delete>
  <Quiet>true</Quiet>
  <Object>
    <Key>Key</Key>
    <VersionId>VersionId</VersionId>
  </Object>
  <Object>
    <Key>Key</Key>
  </Object>
  ...
</Delete>
```

## Request Parameters

The Multi-Object Delete operation requires a single query string parameter called "delete" to distinguish it from other bucket POST operations.

## Request Headers

This operation uses the following Request Headers in addition to the request headers common to most requests. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>Content-MD5</i>	The base64-encoded 128-bit MD5 digest of the data. This header must be used as a message integrity check to verify that the request body was not corrupted in transit. For more information, go to <a href="#">RFC 1864</a> .  Type: String  Default: None	Yes
<i>Content-Length</i>	Length of the body according to RFC 2616.  Type: String  Default: None	Yes
<i>x-amz-mfa</i>	The value is the concatenation of the authentication device's serial number, a space, and the value that is displayed on your authentication device.  Type: String  Default: None Condition: Required to permanently delete a versioned object if versioning is configured with MFA Delete enabled.	Conditional

## Request Elements

Name	Description	Required
<i>Delete</i>	Container for the request.  Ancestor: None Type: Container Children: One or more <i>Object</i> elements and an optional <i>Quiet</i> element.	Yes
<i>Quiet</i>	Element to enable quiet mode for the request. When you add this element, you must set its value to true.  Ancestor: <i>Delete</i> Type: Boolean Default: false	No
<i>Object</i>	Container element that describes the delete request for an object.  Ancestor: <i>Delete</i> Type: Container Children: <i>Key</i> element and an optional <i>VersionId</i> element.	Yes
<i>Key</i>	Key name of the object to delete.  Ancestor: <i>Object</i> Type: String	Yes
<i>VersionId</i>	VersionId for the specific version of the object to delete.  Ancestor: <i>Object</i> Type: String	No

## Responses

### Response Headers

This operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

Name	Description
<i>DeleteResult</i>	Container for the response. Children: <i>Deleted</i> , <i>Error</i> Type: Container Ancestor: None

Name	Description
Deleted	<p>Container element for a successful delete. It identifies the object that was successfully deleted.</p> <p>Children: <i>Key</i>, <i>VersionId</i></p> <p>Type: <i>Container</i></p> <p>Ancestor: <i>DeleteResult</i></p>
Key	<p>Key name for the object that Amazon S3 attempted to delete.</p> <p>Type: <i>String</i></p> <p>Ancestor: <i>Deleted</i>, or <i>Error</i></p>
VersionId	<p>VersionId for the versioned object in the case of a versioned delete.</p> <p>Type: <i>String</i></p> <p>Ancestor: <i>Deleted</i></p>
DeleteMarker	<p>DeleteMarker element with a true value indicates that the request accessed a delete marker.</p> <p>If a specific delete request either creates or deletes a delete marker, Amazon S3 returns this element in the response with a value of true. This is only the case when your Multi-Object Delete request is on a bucket that has versioning enabled or suspended. For more information about delete markers, go to <a href="#">Object Versioning</a>.</p> <p>Type: <i>Boolean</i></p> <p>Ancestor: <i>Deleted</i></p>
DeleteMarkerVersionId	<p>Version ID of the delete marker accessed (deleted or created) by the request.</p> <p>If the specific delete request in the Multi-Object Delete either creates or deletes a delete marker, Amazon S3 returns this element in response with the version ID of the delete marker. When deleting an object in a bucket with versioning enabled, this value is present for the following two reasons:</p> <ul style="list-style-type: none"> <li>• You send a non-versioned delete request, that is, you specify only object key and not the version ID. In this case, Amazon S3 creates a delete marker and returns its version ID in the response.</li> <li>• You send a versioned delete request, that is, you specify an object key and a version ID in your request; however, the version ID identifies a delete marker. In this case, Amazon S3 deletes the delete marker and returns the specific version ID in response. For information about versioning, go to <a href="#">Object Versioning</a>.</li> </ul> <p>Type: <i>String</i></p> <p>Ancestor: <i>Deleted</i></p>



Name	Description
Error	Container for a failed delete operation that describes the object that Amazon S3 attempted to delete and the error it encountered. Children: <i>Key</i> , <i>VersionId</i> , <i>Code</i> , <i>Message</i> . Type: <i>String</i> Ancestor: <i>DeleteResult</i>
Key	Key for the object Amazon S3 attempted to delete. Type: <i>String</i> Ancestor: <i>Error</i>
VersionId	Version ID of the versioned object Amazon S3 attempted to delete. Amazon S3 includes this element only in case of a versioned-delete request. Type: <i>String</i> Ancestor: <i>Deleted</i> , <i>Error</i>
Code	Status code for the result of the failed delete. . Type: <i>String</i> Values: <i>AccessDenied</i> , <i>InternalError</i> Ancestor: <i>Error</i>
Message	Error description. Type: <i>String</i> Ancestor: <i>Error</i>

## Examples

### Example 1: Multi-Object Delete resulting in mixed success/error response

This example illustrates a Multi-Object Delete request to delete objects that result in mixed success and errors response.

#### Sample Request

The following Multi-Object Delete request deletes two objects from a bucket (bucketname). In this example, the requester does not have permission to delete the sample2.txt object.

```
POST /?delete HTTP/1.1
Host: bucketname.S3.amazonaws.com
Accept: */*
x-amz-date: Wed, 30 Nov 2011 03:39:05 GMT
Content-MD5: p5/WA/oEr30qrEE121PAqw==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:W0qPYCLe6JwkZAD1ei6hp9XZIee=
Content-Length: 125
Connection: Keep-Alive

<Delete>
  <Object>
    <Key>sample1.txt</Key>
  </Object>
```

```
<Object>
  <Key>sample2.txt</Key>
</Object>
</Delete>
```

### Sample Response

The response includes a `DeleteResult` element that includes a `Deleted` element for the item that Amazon S3 successfully deleted and an `Error` element that Amazon S3 did not delete because you didn't have permission to delete the object.

```
HTTP/1.1 200 OK
x-amz-id-2: 5h4FxsNCUS7wP5z92eGCWDshNpMnRuXvETa4HH3Lvvh6VAIr0jU7tH9kM7X+njXx
x-amz-request-id: A437B3B641629AEE
Date: Fri, 02 Dec 2011 01:53:42 GMT
Content-Type: application/xml
Server: AmazonS3
Content-Length: 251

<?xml version="1.0" encoding="UTF-8"?>
<DeleteResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Deleted>
    <Key>sample1.txt</Key>
  </Deleted>
  <Error>
    <Key>sample2.txt</Key>
    <Code>AccessDenied</Code>
    <Message>Access Denied</Message>
  </Error>
</DeleteResult>
```

### Example 2: Deleting Object from a Versioned Bucket

If you delete an item from a versioning enabled bucket, all versions of that object remain in the bucket; however, Amazon S3 inserts a delete marker. For more information, go to [Object Versioning](#).

The following scenarios describe the behavior of a Multi-Object Delete request when versioning is enabled for your bucket.

#### Case 1 - Simple Delete

The following sample the Multi-Object Delete request specifies only one key.

```
POST /?delete HTTP/1.1
Host: bucketname.S3.amazonaws.com
Accept: */*
x-amz-date: Wed, 30 Nov 2011 03:39:05 GMT
Content-MD5: p5/WA/oEr30qrEE121PAqw==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:W0qPYCLe6JwkZAD1ei6hp9XZIee=
Content-Length: 79
Connection: Keep-Alive

<Delete>
  <Object>
    <Key>SampleDocument.txt</Key>
```

```
</Object>
</Delete>
```

Because versioning is enabled on the bucket, Amazon S3 does not delete the object. Instead, it adds a delete marker for this object. The response indicates that a delete marker was added (the `DeleteMarker` element in the response as a value of `true`) and the version number of the delete marker it added.

```
HTTP/1.1 200 OK
x-amz-id-2: P3xqrhuhYxlrefdw3rEzmJh8z5KDtGzb+/FB7oiQaScI9Yaxd8olYXc7d1111ab+
x-amz-request-id: 264A17BF16E9E80A
Date: Wed, 30 Nov 2011 03:39:32 GMT
Content-Type: application/xml
Server: AmazonS3
Content-Length: 276

<?xml version="1.0" encoding="UTF-8"?>
<DeleteResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Deleted>
    <Key>SampleDocument.txt</Key>
    <DeleteMarker>true</DeleteMarker>
    <DeleteMarkerVersionId>NeQt5xeFTfgPJD8B4CGWnkSLtluMr1ls</DeleteMarkerVer
sionId>
  </Deleted>
</DeleteResult>
```

### Case 2 - Versioned Delete

The following Multi-Object Delete attempts to delete a specific version of an object

```
POST /?delete HTTP/1.1
Host: bucketname.S3.amazonaws.com
Accept: */*
x-amz-date: Wed, 30 Nov 2011 03:39:05 GMT
Content-MD5: p5/WA/oEr30qrEE121PAqw==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:W0qPYCLe6JwkZAD1ei6hp9XZIx=
Content-Length: 140
Connection: Keep-Alive

<Delete>
  <Object>
    <Key>SampleDocument.txt</Key>
    <VersionId>OYcLXagmS.WaD..oyH4KRguB95_YhLs7</VersionId>
  </Object>
</Delete>
```

In this case, Amazon S3 deletes the specific object version from the bucket and returns the following response. In the response, Amazon S3 returns the key and version ID of the object deleted.

```
HTTP/1.1 200 OK
x-amz-id-2: P3xqrhuhYxlrefdw3rEzmJh8z5KDtGzb+/FB7oiQaScI9Yaxd8olYXc7d1111xx+
x-amz-request-id: 264A17BF16E9E80A
Date: Wed, 30 Nov 2011 03:39:32 GMT
Content-Type: application/xml
Server: AmazonS3
Content-Length: 219
```

```
<?xml version="1.0" encoding="UTF-8"?>
<DeleteResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Deleted>
    <Key>SampleDocument.txt</Key>
    <VersionId>OYcLXagmS.WaD..oyH4KRguB95_YhLs7</VersionId>
  </Deleted>
</DeleteResult>
```

### Case 3 - Versioned Delete of a Delete Marker

In the preceding example, the request refers to a delete marker (instead of an object), then Amazon S3 deletes the delete marker. The effect of this operation is to make your object reappear in your bucket. Amazon S3 returns a response that indicates the delete marker it deleted (`DeleteMarker` element with value `true`) and the version ID of the delete marker.

```
HTTP/1.1 200 OK
x-amz-id-2: IIPUZrtolxDEmWsKOae9JlSZe6yWfTye3HQ3T2iAe0ZE4XH6NKvAJcPp51zZaBr
x-amz-request-id: D6B284CEC9B05E4E
Date: Wed, 30 Nov 2011 03:43:25 GMT
Content-Type: application/xml
Server: AmazonS3
Content-Length: 331

<?xml version="1.0" encoding="UTF-8"?>
<DeleteResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Deleted>
    <Key>SampleDocument.txt</Key>
    <VersionId>NeQt5xeFTfgPJD8B4CGWnkSLtluMr1ls</VersionId>
    <DeleteMarker>true</DeleteMarker>
    <DeleteMarkerVersionId>NeQt5xeFTfgPJD8B4CGWnkSLtluMr1ls</DeleteMarkerVer
sionId>
  </Deleted>
</DeleteResult>
```

In general, when a Multi-Object Delete request results in Amazon S3 either adding a delete marker or removing a delete marker, the response returns the following elements.

```
<DeleteMarker>true</DeleteMarker>
<DeleteMarkerVersionId>NeQt5xeFTfgPJD8B4CGWnkSLtluMr1ls</DeleteMarkerVersionId>
```

### Example 3: Malformed XML in the Request

This example shows how Amazon S3 responds to a request that includes a malformed XML document.

#### Sample Request

The following requests sends a malformed XML document (missing the `Delete` end element).

```
POST /?delete HTTP/1.1
Host: bucketname.S3.amazonaws.com
Accept: */*
x-amz-date: Wed, 30 Nov 2011 03:39:05 GMT
Content-MD5: p5/WA/oEr30qrEE121PAqw==
```

```
Authorization: AWS AKIAIOSFODNN7EXAMPLE:W0qPYCL6JwkZAD1ei6hp9XZIee=  
Content-Length: 104  
Connection: Keep-Alive
```

```
<Delete>  
  <Object>  
    <Key>404.txt</Key>  
  </Object>  
  <Object>  
    <Key>a.txt</Key>  
  </Object>
```

### Sample Response

The response returns the Error messages that describe the error.

```
HTTP/1.1 200 OK  
x-amz-id-2: P3xqrhuhYxlrefdw3rEzmJh8z5KDtGzb+/FB7oiQaScI9Yaxd8olYXc7d1111ab+  
x-amz-request-id: 264A17BF16E9E80A  
Date: Wed, 30 Nov 2011 03:39:32 GMT  
Content-Type: application/xml  
Server: AmazonS3  
Content-Length: 207  
  
<?xml version="1.0" encoding="UTF-8"?>  
<Error>  
  <Code>MalformedXML</Code>  
  <Message>The XML you provided was not well-formed or did not  
    validate against our published schema</Message>  
  <RequestId>91F27FB5811111F</RequestId>  
  <HostId>LCiQK7KbXyJ1t+tncmjRwmNoeerNW1/ktJ61IC8kN32SFXJx7UBhOzseJCixAbcD</Host  
Id>  
</Error>
```

### Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)

# GET Object

## Description

This implementation of the `GET` operation retrieves objects from Amazon S3. To use `GET`, you must have `READ` access to the object. If you grant `READ` access to the anonymous user, you can return the object without using an authorization header.

An Amazon S3 bucket has no directory hierarchy such as you would find in a typical computer file system. You can, however, create a logical hierarchy by using object key names that imply a folder structure. For example, instead of naming an object `sample.jpg`, you can name it `photos/2006/February/sample.jpg`.

To get an object from such a logical hierarchy, specify the full key name for the object in the `GET` operation. For a virtual hosted-style request example, if you have the object `photos/2006/February/sample.jpg`, specify the resource as `/photos/2006/February/sample.jpg`. For a path-style request example, if you have the object `photos/2006/February/sample.jpg` in the bucket named `examplebucket`, specify the resource as `/examplebucket/photos/2006/February/sample.jpg`. For more information about request types, see [HTTP Host Header Bucket Specification](#) in the *Amazon Simple Storage Service Developer Guide*.

To distribute large files to many people, you can save bandwidth costs using BitTorrent. For more information, see [Amazon S3 Torrent](#) in the *Amazon Simple Storage Service Developer Guide*. For more information about returning the ACL of an object, see [GET Object acl](#) (p. 161).

If the object you are retrieving is a GLACIER storage class object, the object is archived in Amazon Glacier. You must first restore a copy using the [POST Object restore](#) (p. 182) API before you can retrieve the object. Otherwise, this operation returns `InvalidObjectStateError` error. For information about archiving objects in Amazon Glacier, go to [Object Lifecycle Management](#) in the *Amazon Simple Storage Service Developer Guide*.

## Versioning

By default, the `GET` operation returns the latest version of an object. To return a different version, use the `versionId` subresource.

### Note

If the latest version of the object is a Delete Marker, Amazon S3 behaves as if the object was deleted and includes `x-amz-delete-marker: true` in the response.

For more information about versioning, see [PUT Bucket versioning](#) (p. 128). To see sample requests that use versioning, see [Sample Request Getting a Specified Version of an Object](#) (p. 158).

## Requests

### Syntax

```
GET /ObjectName HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
Range: bytes=byte_range
```

## Request Parameters

There are times when you want to override certain response header values in a GET response. For example, you might override the `Content-Disposition` response header value in your GET request.

You can override values for a set of response headers using the query parameters listed in the following table. These response header values are only sent on a successful request, that is, when status code 200 OK is returned. The set of headers you can override using these parameters is a subset of the headers that Amazon S3 accepts when you create an object. The response headers that you can override for the GET response are `Content-Type`, `Content-Language`, `Expires`, `Cache-Control`, `Content-Disposition`, and `Content-Encoding`. To override these header values in the GET response, you use the request parameters described in the following table.

### Note

You must sign the request, either using an `Authorization` header or a Pre-signed URL, when using these parameters. They can not be used with an unsigned (anonymous) request.

Parameter	Description	Required
<i>response-content-type</i>	Sets the <code>Content-Type</code> header of the response. Type: String Default: None	No
<i>response-content-language</i>	Sets the <code>Content-Language</code> header of the response. Type: String Default: None	No
<i>response-expires</i>	Sets the <code>Expires</code> header of the response. Type: String Default: None	No
<i>response-cache-control</i>	Sets the <code>Cache-Control</code> header of the response. Type: String Default: None	No
<i>response-content-disposition</i>	Sets the <code>Content-Disposition</code> header of the response. Type: String Default: None	No
<i>response-content-encoding</i>	Sets the <code>Content-Encoding</code> header of the response. Type: String Default: None	No

## Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>Range</i>	Downloads the specified range bytes of an object. For more information about the HTTP Range header, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.35">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.35</a> . Type: String Default: None Constraints: None	No
<i>If-Modified-Since</i>	Return the object only if it has been modified since the specified time, otherwise return a 304 (not modified). Type: String Default: None Constraints: None	No
<i>If-Unmodified-Since</i>	Return the object only if it has not been modified since the specified time, otherwise return a 412 (precondition failed). Type: String Default: None Constraints: None	No
<i>If-Match</i>	Return the object only if its entity tag ( <i>ETag</i> ) is the same as the one specified, otherwise return a 412 (precondition failed). Type: String Default: None Constraints: None	No
<i>If-None-Match</i>	Return the object only if its entity tag ( <i>ETag</i> ) is different from the one specified, otherwise return a 304 (not modified). Type: String Default: None Constraints: None	No

## Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

Header	Description
<i>x-amz-delete-marker</i>	Specifies whether the object retrieved was ( <i>true</i> ) or was not ( <i>false</i> ) a Delete Marker. If <i>false</i> , this response header does not appear in the response. Type: Boolean Valid Values: <i>true</i>   <i>false</i> Default: <i>false</i>



Header	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <code>expiry-date</code> and <code>rule-id</code> key value pairs providing object expiration information. The value of the <code>rule-id</code> is URL encoded. Type: String
<i>x-amz-server-side-encryption</i>	If the object is stored using server-side encryption, response includes this header with value of the encryption algorithm used. Type: String Valid Values: AES256
<i>x-amz-restore</i>	Provides information about object restoration operation and expiration time of the restored object copy.  For more information about archiving objects and restoring them, go to <a href="#">Object Lifecycle Management</a> in <i>Amazon Simple Storage Service Developer Guide</i> Type: String Default: None
<i>x-amz-version-id</i>	Returns the version ID of the retrieved object if it has a unique version ID. Type: String Default: None
<del><i>x-amz-website-redirect-location</i></del>	When a bucket is configured as a website, you can set this metadata on the object so the website endpoint will evaluate the request for the object as a 301 redirect to another object in the same bucket or an external URL. Type: String Default: None

## Response Elements

This implementation of the operation does not return response elements.

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the object, `my-image.jpg`.

```
GET /my-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Wed, 12 Oct 2009 17:50:00 GMT
ETag: "fba9dede5f27731c9771645a39863328"
Content-Length: 434234
Content-Type: text/plain
Connection: close
Server: AmazonS3
[434234 bytes of object data]
```

If the object had expiration set using lifecycle configuration, you get the following response with the `x-amz-expiration` header.

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Wed, 12 Oct 2009 17:50:00 GMT
x-amz-expiration: expiry-date="Fri, 23 Dec 2012 00:00:00 GMT", rule-id="picture-
deletion-rule"
ETag: "fba9dede5f27731c9771645a39863328"
Content-Length: 434234
Content-Type: text/plain
Connection: close
Server: AmazonS3
[434234 bytes of object data]
```

## Sample response if object is archived in Amazon Glacier

An object archived in Amazon Glacier must first be restored before you can access it. If you attempt to access a Glacier object without restoring it, Amazon S3 returns the following error.

```
HTTP/1.1 403 Forbidden
x-amz-request-id: CD4BD8A1310A11B3
x-amz-id-2: m9RDbQU0+RRBTjOUN1ChQ1eqMUNr9dv8b+KP6I2gHfRJZSTSrMCoRP8RtPRzX9mb
Content-Type: application/xml
Date: Mon, 12 Nov 2012 23:53:21 GMT
Server: AmazonS3
Content-Length: 231

<Error>
  <Code>InvalidObjectState</Code>
  <Message>The operation is not valid for the object's storage class</Message>

  <RequestId>9FEFFF118E15B86F</RequestId>
  <HostId>WVQ5kzhiT+oiUfDCoiOYv8W4Tk9eNcxWi/MK+hTS/av34Xy4rBU3zsavf0aaaaa</Host
Id>
</Error>
```

## Sample Response if Latest Object is a Delete Marker

```
HTTP/1.1 404 Not Found
x-amz-request-id: 318BC8BC148832E5
x-amz-id-2: eftixk72aD6Ap51Tnqzj7UDNEHGran
x-amz-version-id: 3GL4kqtJlcpXroDTDm3vjVBH40Nr8X8g
x-amz-delete-marker: true
Date: Wed, 28 Oct 2009 22:32:00 GMT
Content-Type: text/plain
Connection: close
Server: AmazonS3
```

Notice that the delete marker returns a 404 Not Found error.

## Sample Request Getting a Specified Version of an Object

The following request returns the specified version of an object.

```
GET /myObject?versionId=3/L4kqtJlcpXroDTDmpUMLUo HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response to a Versioned Object GET Request

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap54OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
x-amz-version-id: 3/L4kqtJlcpXroDTDmJ+rmSpXd3QBpUMLUo
ETag: "fba9dede5f27731c9771645a39863328"
Content-Length: 434234
Content-Type: text/plain
Connection: close
Server: AmazonS3
[434234 bytes of object data]
```

## Sample Request with Parameters Altering Response Header Values

The following request specifies all the query string parameters in a GET request overriding the response header values.

```
GET /Junk3.txt?response-cache-control=No-cache&response-content-disposition=attachment%3B%20filename%3Dtesting.txt&response-content-encoding=x-gzip&response-content-language=mi%2C%20en&response-expires=Thu%2C%2001%20Dec%201994%2016:00:00%20GMT HTTP/1.1
x-amz-date: Sun, 19 Dec 2010 01:53:44 GMT
Accept: */*
Authorization: AWS AKIAIOSFODNN7EXAMPLE:aaStE6nKnw8ihhiIdReoXYlMamW=
```

## Sample Response with Overridden Response Header Values

In the following sample response note the header values are set to the values specified in the `true` request.

```
HTTP/1.1 200 OK
x-amz-id-2: SIidWAK3hK+Il3/QqiulZKEuegzLAAspwsqwnwygb9GgFseeFHL5CII8NXSrfWW2
x-amz-request-id: 881B1CBD9DF17WA1
Date: Sun, 19 Dec 2010 01:54:01 GMT
x-amz-meta-param1: value 1
x-amz-meta-param2: value 2
Cache-Control: No-cache
Content-Language: mi, en
Expires: Thu, 01 Dec 1994 16:00:00 GMT
Content-Disposition: attachment; filename=testing.txt
Content-Encoding: x-gzip
Last-Modified: Fri, 17 Dec 2010 18:10:41 GMT
ETag: "0332beela7bf845f176c5c0d1ae7cf07"
Accept-Ranges: bytes
Content-Type: text/plain
Content-Length: 22
Server: AmazonS3

[object data not shown]
```

## Sample Request with the Range Header

The following request specifies the HTTP Range header to retrieve first 10 bytes of an object. For more information about the HTTP Range header, go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html>.

```
GET /example-object HTTP/1.1
Host: example-bucket.s3.amazonaws.com
x-amz-date: Fri, 28 Jan 2011 21:32:02 GMT
Range: bytes=0-9
Authorization: AWS AKIAIOSFODNN7EXAMPLE:Yxg83MzaEgh3OZ3l0rLo5RTX1lo=
Sample Response with Specified Range of the Object Bytes
```

## Sample Response

In the following sample response note the header values are set to the values specified in the `true` request.

```
HTTP/1.1 206 Partial Content
x-amz-id-2: MzRISOWyjmupCzjI1WC06l5TTAzm7/JypPGXLh0OVFGcJaaO3KW/hRAqKOpIEEp
x-amz-request-id: 47622117804B3E11
Date: Fri, 28 Jan 2011 21:32:09 GMT
x-amz-meta-title: the title
Last-Modified: Fri, 28 Jan 2011 20:10:32 GMT
ETag: "b2419ble3fd45d596ee22bdf62aaaa2f"
Accept-Ranges: bytes
Content-Range: bytes 0-9/443
Content-Type: text/plain
Content-Length: 10
Server: AmazonS3
```

[10 bytes of object data]

## Related Resources

- [GET Service \(p. 15\)](#)
- [GET Object acl \(p. 161\)](#)

# GET Object ACL

## Description

This implementation of the `GET` operation uses the `acl` subresource to return the access control list (ACL) of an object. To use this operation, you must have `READ_ACP` access to the object.

## Versioning

By default, `GET` returns ACL information about the latest version of an object. To return ACL information about a different version, use the `versionId` subresource.

To see sample requests that use Versioning, see [Sample Request Getting the ACL of the Specific Version of an Object](#) (p. 163).

## Requests

### Syntax

```
GET /ObjectName?acl HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
Range:bytes=byte_range
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

Name	Description
<code>AccessControlList</code>	Container for Grant, Grantee, and Permission Type: Container Ancestors: <code>AccessControlPolicy</code>

Name	Description
AccessControlPolicy	Contains the elements that set the ACL permissions for an object per Grantee. Type: Container Ancestors: None
DisplayName	Screen name of the bucket owner Type: String Ancestors: AccessControlPolicy.Owner
Grant	Container for the grantee and his or her permissions. Type: Container Ancestors: AccessControlPolicy.AccessControlList
Grantee	The subject whose permissions are being set. Type: String Ancestors: AccessControlPolicy.AccessControlList.Grant
ID	ID of the bucket owner, or the ID of the grantee Type: String Ancestors: AccessControlPolicy.Owner or AccessControlPolicy.AccessControlList.Grant
Owner	Container for the bucket owner's display name and ID. Type: Container Ancestors: AccessControlPolicy
Permission	Specifies the permission (FULL_CONTROL, WRITE, READ_ACP) given to the grantee. Type: String Ancestors: AccessControlPolicy.AccessControlList.Grant

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns information, including the ACL, of the object, my-image.jpg.

```
GET /my-image.jpg?acl HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-version-id: 4HL4kqtJlcpXroDTmJ+rmSpXd3dIbrHY+MTRCxf3vjVBH40NrjfkD
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
Content-Length: 124
Content-Type: text/plain
Connection: close
Server: AmazonS3

<AccessControlPolicy>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>mtd@amazon.com</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

        <DisplayName>mtd@amazon.com</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Sample Request Getting the ACL of the Specific Version of an Object

The following request returns information, including the ACL, of the specified version of the object, my-image.jpg.

```
GET /my-image.jpg?versionId=3/L4kqtJlcpXroDVbH40Nr8X8gdRQBpUMLUo&acl HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response Showing the ACL of the Specific Version

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
x-amz-version-id: 3/L4kqtJlcpXroDTmJ+rmSpXd3dIbrHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
Content-Length: 124
Content-Type: text/plain
Connection: close
Server: AmazonS3
```



```
<AccessControlPolicy>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>mdtd@amazon.com</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

        <DisplayName>mdtd@amazon.com</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Related Resources

- [GET Object \(p. 153\)](#)
- [PUT Object \(p. 185\)](#)
- [DELETE Object \(p. 141\)](#)

# GET Object torrent

## Description

This implementation of the `GET` operation uses the *torrent* subresource to return torrent files from a bucket. BitTorrent can save you bandwidth when you're distributing large files. For more information about BitTorrent, see [Amazon S3 Torrent](#).

### Note

You can get torrent only for objects that are less than 5 GB in size.

To use `GET`, you must have `READ` access to the object.

## Requests

### Syntax

```
GET /ObjectName?torrent HTTP/1.1  
Host: BucketName.s3.amazonaws.com  
Date: date  
Authorization: signatureValue
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation uses only request headers that are common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

### Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers \(p. 14\)](#).

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Getting Torrent Files in a Bucket

This example retrieves the Torrent file for the "Nelson" object in the "quotes" bucket.

```
GET /quotes/Nelson?torrent HTTP/1.0
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-request-id: 7CD745EBB7AB5ED9
Date: Wed, 25 Nov 2009 12:00:00 GMT
Content-Disposition: attachment; filename=Nelson.torrent;
Content-Type: application/x-bittorrent
Content-Length: 537
Server: AmazonS3

<body: a Bencoded dictionary as defined by the BitTorrent specification>
```

## Related Resources

- [GET Object \(p. 153\)](#)

# HEAD Object

## Description

The `HEAD` operation retrieves metadata from an object without returning the object itself. This operation is useful if you are interested only in an object's metadata. To use `HEAD`, you must have `READ` access to the object.

A `HEAD` request has the same options as a `GET` operation on an object. The response is identical to the `GET` response except that there is no response body.

## Versioning

By default, the `HEAD` operation retrieves metadata from the latest version of an object. If the latest version is a delete marker, Amazon S3 behaves as if the object was deleted. To retrieve metadata from a different version, use the `versionId` subresource. For more information, see [Versions](#) in the *Amazon Simple Storage Service Developer Guide*.

To see sample requests that use versioning, see [Sample Request Getting Metadata From a Specified Version of an Object \(p. 170\)](#).

## Requests

### Syntax

```
HEAD /ObjectName HTTP/1.1
Host: BucketName.s3.amazonaws.com
Authorization: signatureValue
Date: date
```

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>Range</i>	Downloads the specified range bytes of an object. For more information about the HTTP Range header, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.35">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.35</a> . Type: String Default: None Constraints: None	No
<i>If-Modified-Since</i>	Return the object only if it has been modified since the specified time, otherwise return a 304 (not modified). Type: String Default: None Constraints: None	No

Name	Description	Required
<i>If-Unmodified-Since</i>	Return the object only if it has not been modified since the specified time, otherwise return a 412 (precondition failed). Type: String Default: None Constraints: None	No
<i>If-Match</i>	Return the object only if its entity tag ( <i>ETag</i> ) is the same as the one specified, otherwise return a 412 (precondition failed). Type: String Default: None Constraints: None	No
<i>If-None-Match</i>	Return the object only if its entity tag ( <i>ETag</i> ) is different from the one specified, otherwise return a 304 (not modified). Type: String Default: None Constraints: None	No

## Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <i>expiry-date</i> and <i>rule-id</i> key value pairs providing object expiration information. The value of the <i>rule-id</i> is URL encoded. Type: String
<i>x-amz-meta-*</i>	If you supplied user metadata in a <b>PUT</b> object operation, that metadata is returned in one or more response headers prefixed with <i>x-amz-meta-</i> and with the suffix name that you provided on storage. For example, for family, the response header would be <i>x-amz-meta-family</i> . Amazon S3 returns this metadata verbatim; Amazon S3 does not interpret it. Type: String
<i>x-amz-missing-meta</i>	This header is set to the number of metadata entries that were not returned in <i>x-amz-meta</i> headers. This can happen if you create metadata using an API like SOAP that supports more flexible metadata than the REST API. For example, with SOAP, you can create metadata with values that are not valid HTTP headers. Type: String

Name	Description
<code>x-amz-restore</code>	<p>If the object is an archived object (an object whose storage class is Glacier), the response includes this header if either the archive restoration is in progress (see <a href="#">POST Object restore (p. 182)</a>) or an archive copy is already restored.</p> <p>If an archive copy is already restored, the header value indicates when Amazon S3 is scheduled to delete the object copy. For example,</p> <pre>x-amz-restore: ongoing-request="false", expiry-date="Fri, 23 Dec 2012 00:00:00 GMT"</pre> <p>If the object restoration is in progress, the header will return value <code>ongoing-request="true"</code>.</p> <p>For more information about archiving objects, go to <a href="#">Object Lifecycle Management</a> in <i>Amazon Simple Storage Service Developer Guide</i></p> <p>Type: String</p> <p>Default: None</p>
<code>x-amz-server-side-encryption</code>	<p>If the object is stored by using server-side encryption, the response includes this header with a value of the encryption algorithm that was used.</p> <p>Type: String</p> <p>Valid Values: AES256</p>
<code>x-amz-version-id</code>	<p>The version ID of the object returned.</p> <p>Type: String</p>

## Response Elements

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request returns the metadata of an object.

```
HEAD /my-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:02236Q3V0RonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: ef8yU9ASled4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC143432E5
x-amz-version-id: 3HL4kqtJlcpXroDTDmjVBH40NrjfkD
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
ETag: "fba9dede5f27731c9771645a39863328"
Content-Length: 434234
Content-Type: text/plain
Connection: close
Server: AmazonS3
```

If the object is scheduled to expire according to lifecycle configuration set on the bucket, the response returns `x-amz-expiration` tag with information when Amazon S3 will delete the object. For more information, go to [Object Expiration](#) in the *Amazon Simple Storage Service Developer Guide*.

```
HTTP/1.1 200 OK
x-amz-id-2: azQRZtQJ2mlP8R+TIsG9h0VuC/DmISJmjXUMq7snk+LKSJeurtmfzSlGhR46GzSJ
x-amz-request-id: 0EFF61CCE3F24A26
Date: Mon, 17 Dec 2012 02:26:39 GMT
Last-Modified: Mon, 17 Dec 2012 02:14:10 GMT
x-amz-expiration: expiry-date="Fri, 21 Dec 2012 00:00:00 GMT", rule-id="Rule
for testfile.txt"
ETag: "54b0c58c7ce9f2a8b551351102ee0938"
Accept-Ranges: bytes
Content-Type: text/plain
Content-Length: 14
Server: AmazonS3
```

## Sample Request Getting Metadata From a Specified Version of an Object

The following request returns the metadata of the specified version of an object.

```
HEAD /my-image.jpg?versionId=3HL4kqCxf3vjVBH40NrjfkD HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:02236Q3V0WpaBX5sCYVf1bNRuU=
```

## Sample Response to a Versioned HEAD Request

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap5lTnqcoF8epIszj7UDNEHGran
x-amz-request-id: 318BC8BC143432E5
x-amz-version-id: 3HL4kqtJlcpXrof3vjVBH40NrjfkD
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
ETag: "fba9dede5f27731c9771645a39863328"
Content-Length: 434234
Content-Type: text/plain
Connection: close
Server: AmazonS3
```

## Sample Request for a Glacier Object

If you request metadata for an object that is archived in Amazon Glacier you must first restore a copy of the object. The HEAD request return the x-amz-restore header providing the status of the restoration.

```
HEAD /my-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: 13 Nov 2012 00:28:38 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:02236Q3V0RonhpaBX5sCYVflbNRuU=
```

## Sample Response-Glacier Object

If the object is already restored, the x-amz-restore header provides the date when the restored copy will expire as shown in the following response.

```
HTTP/1.1 200 OK
x-amz-id-2: FSVaTMjrmBp3IzslNnwBZeu7M19iI8UbxMbi0A8AirHANJBo+hEftBuiESACOMJp
x-amz-request-id: E5CEFCB143EB505A
Date: Tue, 13 Nov 2012 00:28:38 GMT
Last-Modified: Mon, 15 Oct 2012 21:58:07 GMT
x-amz-restore: ongoing-request="false", expiry-date="Wed, 07 Nov 2012 00:00:00 GMT"
ETag: "1accb31fcf202eba0c0f41fa2f09b4d7"
Accept-Ranges: bytes
Content-Type: binary/octet-stream
Content-Length: 300
Server: AmazonS3
```

If the restoration is in progress, then the x-amz-restore header return message accordingly.

```
HTTP/1.1 200 OK
x-amz-id-2: b+V2mDiMHTdylmyoUBpctvmJl95H9U/OSUm/jRtHxjh0+pCk5SvByL4xu2TDv4GM
x-amz-request-id: E2E7B6AEE4E9BD2B
Date: Tue, 13 Nov 2012 00:43:32 GMT
Last-Modified: Sat, 20 Oct 2012 21:28:27 GMT
x-amz-restore: ongoing-request="true"
ETag: "1accb31fcf202eba0c0f41fa2f09b4d7"
Accept-Ranges: bytes
Content-Type: binary/octet-stream
Content-Length: 300
Server: AmazonS3
```

## Related Resources

- [GET Object \(p. 153\)](#)



# OPTIONS object

## Description

A browser can send this preflight request to Amazon S3 to determine if it can send an actual request with the specific origin, HTTP method, and headers.

Amazon S3 supports cross-origin resource sharing (CORS) by enabling you to add a `cors` subresource on a bucket. When a browser sends this preflight request, Amazon S3 responds by evaluating the rules that are defined in the `cors` configuration.

If `cors` is not enabled on the bucket, then Amazon S3 returns a 403 `Forbidden` response.

For more information about CORS, go to [Enabling Cross-Origin Resource Sharing](#) in the *Amazon Simple Storage Service Developer Guide*.

## Requests

### Syntax

```
OPTIONS /ObjectName HTTP/1.1
Host: BucketName.s3.amazonaws.com
Origin: Origin
Access-Control-Request-Method: HTTPMethod
Access-Control-Request-Headers: RequestHeader
```

### Request Parameters

This operation does not introduce any specific request parameters, but it may contain any request parameters that are required by the actual request.

### Request Headers

Name	Description	Required
<i>Origin</i>	Identifies the origin of the cross-origin request to Amazon S3. For example, <code>http://www.example.com</code> .  Type: String  Default: None	Yes
<del><i>Access-Control-Request-Method</i></del>	Identifies what HTTP method will be used in the actual request.  Type: String  Default: None	Yes

Name	Description	Required
<del>Access-Control-Request-Headers</del>	<p>A comma-delimited list of HTTP headers that will be sent in the actual request.</p> <p>For example, to put an object with server-side encryption, this preflight request will determine if it can include the <code>x-amz-server-side-encryption</code> header with the request.</p> <p>Type: String</p> <p>Default: None</p>	No

## Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

Header	Description
<del>Access-Control-Allow-Origin</del>	<p>The origin you sent in your request. If the origin in your request is not allowed, Amazon S3 will not include this header in the response.</p> <p>Type: String</p>
<del>Access-Control-Max-Age</del>	<p>How long, in seconds, the results of the preflight request can be cached.</p> <p>Type: String</p>
<del>Access-Control-Allow-Methods</del>	<p>The HTTP method that was sent in the original request. If the method in the request is not allowed, Amazon S3 will not include this header in the response.</p> <p>Type: String</p>
<del>Access-Control-Allow-Headers</del>	<p>A comma-delimited list of HTTP headers that the browser can send in the actual request. If any of the requested headers is not allowed, Amazon S3 will not include that header in the response, nor will the response contain any of the headers with the <code>Access-Control</code> prefix.</p> <p>Type: String</p>
<del>Access-Control-Expose-Headers</del>	<p>A comma-delimited list of HTTP headers. This header provides the JavaScript client with access to these headers in the response to the actual request.</p> <p>Type: String</p>

## Response Elements

This implementation of the operation does not return response elements.

## Examples

### Example : Send a preflight OPTIONS request to a `cors` enabled bucket

A browser can send this preflight request to Amazon S3 to determine if it can send the actual PUT request from `http://www.example.com` origin to the Amazon S3 bucket named `examplebucket`.

#### Sample Request

```
OPTIONS /exampleobject HTTP/1.1
Host: examplebucket.s3.amazonaws.com
Origin: http://www.example.com
Access-Control-Request-Method: PUT
```

#### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: aws-s3integ-s3ws-31008.sea31@1332371394
x-amz-request-id: BDC4B83DF5096BBE
Date: Wed, 21 Aug 2012 23:09:55 GMT
Etag: "1f1a1af1f111111111111111c11aed1da1"
Access-Control-Allow-Origin: http://www.example.com
Access-Control-Allow-Methods: PUT
Access-Control-Expose-Headers: x-amz-request-id
Content-Length: 0
Server: AmazonS3
```

## Related Resources

- [GET Bucket cors \(p. 41\)](#)
- [DELETE Bucket cors \(p. 21\)](#)
- [PUT Bucket cors \(p. 101\)](#)

# POST Object

## Description

The `POST` operation adds an object to a specified bucket using HTML forms. `POST` is an alternate form of `PUT` that enables browser-based uploads as a way of putting objects in buckets. Parameters that are passed to `PUT` via HTTP Headers are instead passed as form fields to `POST` in the multipart/form-data encoded message body. You must have `WRITE` access on a bucket to add an object to it. Amazon S3 never stores partial objects: if you receive a successful response, you can be confident the entire object was stored.

Amazon S3 is a distributed system. If Amazon S3 receives multiple write requests for the same object simultaneously, all but the last object written will be overwritten.

To ensure that data is not corrupted traversing the network, use the Content-MD5 form field. When you use the Content-MD5 form field, Amazon S3 checks the object against the provided MD5 value. If they do not match, Amazon S3 returns an error. Additionally, you can calculate the MD5 while posting an object to Amazon S3 and compare the returned *ETag* to the calculated MD5 value. The ETag only reflects changes to the contents of an object, not its metadata.

### Note

To configure your application to send the Request Headers prior to sending the request body, use the 100-continue HTTP status code. For `POST` operations, this helps you avoid sending the message body if the message is rejected based on the headers (e.g., authentication failure or redirect). For more information on the 100-continue HTTP status code, go to Section 8.2.3 of <http://www.ietf.org/rfc/rfc2616.txt>.

## Versioning

If you enable versioning for a bucket, `POST` automatically generates a unique version ID for the object being added. Amazon S3 returns this ID in the response using the *x-amz-version-id* response header.

If you suspend versioning for a bucket, Amazon S3 always uses `null` as the version ID of the object stored in a bucket.

For more information about returning the versioning state of a bucket, see [GET Bucket \(Versioning Status\)](#) (p. 74).

Amazon S3 is a distributed system. If you enable versioning on a bucket and Amazon S3 receives multiple write requests for the same object simultaneously, all of the objects will be stored.

To see sample requests that use versioning, see [Sample Request](#) (p. 181).

## Requests

### Syntax

```
POST / HTTP/1.1
Host: destinationBucket.s3.amazonaws.com
User-Agent: browser_data
Accept: file_types
Accept-Language: Regions
Accept-Encoding: encoding
Accept-Charset: character_set
Keep-Alive: 300
Connection: keep-alive
```

```
Content-Type: multipart/form-data; boundary=9431149156168
Content-Length: length

--9431149156168
Content-Disposition: form-data; name="key"


acl
--9431149156168
Content-Disposition: form-data; name="success_action_redirect"


success_redirect
--9431149156168
Content-Disposition: form-data; name="Content-Type"


content_type
--9431149156168
Content-Disposition: form-data; name="x-amz-meta-uuid"


uuid
--9431149156168
Content-Disposition: form-data; name="x-amz-meta-tag"


metadata
--9431149156168
Content-Disposition: form-data; name="AWSAccessKeyId"


access-key-id
--9431149156168
Content-Disposition: form-data; name="Policy"


encoded_policy
--9431149156168
Content-Disposition: form-data; name="Signature"


signature=
--9431149156168
Content-Disposition: form-data; name="file"; filename="MyFilename.jpg"
Content-Type: image/jpeg


file_content
--9431149156168
Content-Disposition: form-data; name="submit"


Upload to Amazon S3
--9431149156168--
```

## Request Parameters

This implementation of the operation does not use request parameters.

## Form Fields

This operation can use the following form fields.

**Amazon Simple Storage Service API Reference**  
**POST Object**

---

Name	Description	Required
<i>AWSSecretKeyId</i>	The AWS Access Key ID of the owner of the bucket who grants an Anonymous user access for a request that satisfies the set of constraints in the Policy. Type: String Default: None Constraints: Required if a policy document is included with the request.	Conditional
<i>Cache-Control, Content-Type, Content-Disposition, Content-Encoding</i>	REST-specific headers. For more information, see <a href="#">PUT Object (p. 185)</a> . Type: String Default: None	No
<i>expires</i>	Number of milliseconds before expiration Type: Int Default: None	No
<i>file</i>	File or text content. The file or text content must be the last field in the form. You cannot upload more than one file at a time. Type: File or text content Default: None	Yes
<i>key</i>	The name of the uploaded key. To use the filename provided by the user, use the <code>\${filename}</code> variable. For example, if the user Betty uploads the file lolcatz.jpg and you specify <code>/user/betty/\${filename}</code> , the key name will be <code>/user/betty/lolcatz.jpg</code> . For more information, go to <a href="#">Object Key and Metadata</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Default: None	Yes
<i>policy</i>	Security Policy describing what is permitted in the request. Requests without a security policy are considered anonymous and only work on publicly writable buckets. For more information, go to <a href="#">HTML Forms</a> and <a href="#">Upload Examples</a> . Type: String Default: None	No

Name	Description	Required
<i>success_action_redirect, redirect</i>	<p>The URL to which the client is redirected upon successful upload.</p> <p>If <i>success_action_redirect</i> is not specified, Amazon S3 returns the empty document type specified in the <i>success_action_status</i> field.</p> <p>If Amazon S3 cannot interpret the URL, it acts as if the field is not present.</p> <p>If the upload fails, Amazon S3 displays an error and does not redirect the user to a URL.</p> <p>Type: String</p> <p>Default: None</p> <p><b>Note</b></p> <p>The <i>redirect</i> field name is deprecated and support for the <i>redirect</i> field name will be removed in the future.</p>	No
<i>success_action_status</i>	<p>The status code returned to the client upon successful upload if <i>success_action_redirect</i> is not specified.</p> <p>Accepts the values 200, 201, or 204 (default).</p> <p>If the value is set to 200 or 204, Amazon S3 returns an empty document with a 200 or 204 status code.</p> <p>If the value is set to 201, Amazon S3 returns an XML document with a 201 status code.</p> <p>If the value is not set or if it is set to an invalid value, Amazon S3 returns an empty document with a 204 status code.</p> <p>Type: String</p> <p>Default: None</p> <p><b>Note</b></p> <p>Some versions of the Adobe Flash player do not properly handle HTTP responses with an empty body. To support uploads through Adobe Flash, we recommend setting <i>success_action_status</i> to 201.</p>	No
<i>x-amz-storage-class</i>	<p>Storage class to use for storing the object.</p> <p>Type: String</p> <p>Default: STANDARD</p> <p>Valid Values: STANDARD   REDUCED_REDUNDANCY</p> <p>Constraints: You cannot specify <i>GLACIER</i> as the storage class. To transition objects to the <i>GLACIER</i> storage class you can use lifecycle configuration.</p>	No
<i>x-amz-meta-*</i>	<p>Field names prefixed with <i>x-amz-meta-</i> contain user-specified metadata.</p> <p>Amazon S3 does not validate or use this data.</p> <p>For more information, see <a href="#">PUT Object (p. 185)</a>.</p> <p>Type: String</p> <p>Default: None</p>	No

Name	Description	Required
<code>x-amz-security-token</code>	Amazon DevPay security token. Each request that uses Amazon DevPay requires two <code>x-amz-security-token</code> form fields: one for the product token and one for the user token. For more information, go to <a href="#">Using DevPay</a> . Type: String Default: None	No
<code>x-amz-server-side-encryption</code>	Specifies server-side encryption algorithm to use when Amazon S3 creates an object. Type: String Valid Value: AES256	No
<code>x-amz-website-redirect-location</code>	If the bucket is configured as a website, redirects requests for this object to another object in the same bucket or to an external URL. Amazon S3 stores the value of this header in the object metadata. For information about object metadata, go to <a href="#">Object Key and Metadata</a> .  In the following example, the request header sets the redirect to an object ( <code>anotherPage.html</code> ) in the same bucket: <pre>x-amz-website-redirect-location: /anotherPage.html</pre> In the following example, the request header sets the object redirect to another website: <pre>x-amz-website-redirect-location: http://www.example.com/</pre> For more information about website hosting in Amazon S3, go to sections <a href="#">Hosting Websites on Amazon S3</a> and <a href="#">How to Configure Website Page Redirects</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Default: None Constraints: The value must be prefixed by, <code>"/</code> , <code>"http://"</code> or <code>"https://"</code> . The length of the value is limited to 2 K.	No

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers](#) (p. 14).



Name	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <code>expiry-date</code> and <code>rule-id</code> key value pairs providing object expiration information. The value of the <code>rule-id</code> is URL encoded. Type: String
<i>success_action_redirect, redirect</i>	The URL to which the client is redirected on successful upload. Type: String Ancestor: PostResponse
<i>x-amz-server-side-encryption</i>	If you request server-side encryption when adding an object, the response includes this header confirming the encryption algorithm used. Type: String
<i>x-amz-version-id</i>	Version of the object. Type: String

### Response Elements

Name	Description
<i>Bucket</i>	Name of the bucket the object was stored in. Type: String Ancestor: PostResponse
<i>ETag</i>	The entity tag is an MD5 hash of the object that you can use to do conditional <code>GET</code> operations using the <code>If-Modified</code> request tag with the <code>GET</code> request operation. The <code>ETag</code> only reflects changes to the contents of an object, not its metadata. Type: String Ancestor: PostResponse
<i>Key</i>	The object key name. Type: String Ancestor: PostResponse
<i>Location</i>	URI of the object. Type: String Ancestor: PostResponse

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

```
POST /Neo HTTP/1.1
Content-Length: 4
Host: quotes.s3.amazonaws.com
Date: Wed, 01 Mar 2009 12:00:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Expect: the 100-continue HTTP status code
```

*ObjectContent*

### Sample Response With Versioning Suspended

The following shows a sample response when bucket versioning is suspended.

```
HTTP/1.1 100 Continue
HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/FlySViT1LW94/xUQxMsF7xiEb1a0wiIOIxl+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: default
Date: Wed, 12 Oct 2009 17:50:00 GMT
ETag: "1b2cf535f27731c974343645a3985328"
Content-Length: 0
Connection: close
Server: AmazonS3
```

Notice in this response the version ID is null.

### Sample Response With Versioning Enabled

The following shows a sample response when bucket versioning is enabled.

```
HTTP/1.1 100 Continue
HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/FlySViT1LW94/xUQxMsF7xiEb1a0wiIOIxl+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: 43jfkodU8493jnFJD9fjj3HHNVfdsQUIFDNsidf038jfdsjGFDSIRp
Date: Wed, 01 Mar 2009 12:00:00 GMT
ETag: "828ef3fdfa96f00ad9f27c383fc9ac7f"
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Related Resources

- [PUT Object - Copy \(p. 201\)](#)
- [POST Object \(p. 175\)](#)
- [GET Object \(p. 153\)](#)

# POST Object restore

## Description

Restores a temporary copy of an archived object. In the request, you specify the number of days that you want the restored copy to exist. After the specified period, Amazon S3 deletes the temporary copy. Note that the object remains archived; Amazon S3 deletes only the restored copy.

An object in the Glacier storage class is an archived object. To access the object, you must first initiate a restore request, which restores a copy of the archived object. Restore jobs typically complete in three to five hours.

For more information about archiving objects, go to [Object Lifecycle Management](#) in *Amazon Simple Storage Service Developer Guide*.

You can obtain restoration status by sending a HEAD request. In the response, these operations return the `x-amz-restore` header with restoration status information.

After restoring an object copy, you can update the restoration period by reissuing this request with the new period. Amazon S3 updates the restoration period relative to the current time.

You cannot issue another restore request when Amazon S3 is actively processing your first restore request; however, after Amazon S3 restores a copy of the object, you can send restore requests to update the expiration period of the restored object copy.

If your bucket has a lifecycle configuration with a rule that includes an expiration action, the object expiration overrides the life span that you specify in a restore request. For example, if you restore an object copy for 10 days but the object is scheduled to expire in 3 days, Amazon S3 deletes the object in 3 days. For more information about lifecycle configuration, see [PUT Bucket lifecycle \(p. 106\)](#).

To use this action, you must have `s3:RestoreObject` permissions on the specified object. For more information, go to [Access Control](#) section in the *Amazon S3 Developer Guide*.

## Requests

### Syntax

```
POST /ObjectName?restore HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
Content-MD5: MD5

<RestoreRequest xmlns="http://s3.amazonaws.com/doc/2006-3-01">
  <Days>NumberOfDays</Days>
</RestoreRequest>
```

#### Note

The syntax shows some of the request headers. For a complete list, see the Request Headers section.

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

Name	Description	Required
<i>Content-MD5</i>	The base64-encoded 128-bit MD5 digest of the data. This header must be used as a message integrity check to verify that the request body was not corrupted in transit. For more information, go to <a href="#">RFC 1864</a> .  Type: String  Default: None	Yes

## Request Elements

Name	Description
<i>RestoreRequest</i>	Container for restore information Type: Container Ancestors: <i>AccessControlPolicy</i>
<i>Days</i>	Lifetime of the restored (active) copy. The minimum number of days that you can restore an object from Amazon Glacier is 1. After the object copy reaches the specified lifetime, Amazon S3 removes the copy from the bucket. Type: Positive integer Ancestors: <i>RestoreRequest</i>

## Responses

A successful operation returns either 200 *OK* or 202 *Accepted* status code.

- If the object copy is not previously restored, then Amazon S3 returns 202 *Accepted* in the response.
- If the object copy is previously restored, Amazon S3 returns 200 *OK* in the response.

## Response Headers

This implementation of the operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

## Response Elements

This operation does not return response elements.

## Special Errors

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
<i>RestoreAlreadyInProgress</i>	Object restore is already in progress.	409 Conflict	Client

## Examples

### Restore an object for 2 days

The following restore request restores a copy of the `photo1.jpg` object from Amazon Glacier for a period of 2 days.

```
POST /photo1.jpg?restore HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Mon, 22 Oct 2012 01:49:52 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Length: 53

<RestoreRequest>
  <Days>2</Days>
</RestoreRequest>
```

If the `examplebucket` does not have a restored copy of the object, Amazon S3 returns the following 202 Accepted response.

```
HTTP/1.1 202 Accepted
x-amz-id-2: GFihv3y6+kE7KG1lGEkQhU7/2/cHR3Yb2fCb2S04nxI423Dqwg2XiQ0B/UZlzyQvPiBlZNRcovw=
x-amz-request-id: 9F341CD3C4BA79E0
Date: Sat, 20 Oct 2012 23:54:05 GMT
Content-Length: 0
Server: AmazonS3
```

If a copy of the object is already restored, Amazon S3 returns a 200 OK response, only updating the restored copy's expiry time.

## Related Resources

- [GET Bucket lifecycle \(p. 44\)](#)
- [PUT Bucket lifecycle \(p. 106\)](#)

# PUT Object

## Description

This implementation of the `PUT` operation adds an object to a bucket. You must have `WRITE` permissions on a bucket to add an object to it.

Amazon S3 never adds partial objects; if you receive a success response, Amazon S3 added the entire object to the bucket.

Amazon S3 is a distributed system. If it receives multiple write requests for the same object simultaneously, it overwrites all but the last object written. Amazon S3 does not provide object locking; if you need this, make sure to build it into your application layer or use versioning instead.

To ensure that data is not corrupted traversing the network, use the Content-MD5 header. When you use this header, Amazon S3 checks the object against the provided MD5 value and, if they do not match, returns an error. Additionally, you can calculate the MD5 while putting an object to Amazon S3 and compare the returned `ETag` to the calculated MD5 value.

### Note

To configure your application to send the Request Headers prior to sending the request body, use the `100-continue` HTTP status code. For `PUT` operations, this helps you avoid sending the message body if the message is rejected based on the headers (e.g., because of authentication failure or redirect). For more information on the `100-continue` HTTP status code, go to Section 8.2.3 of <http://www.ietf.org/rfc/rfc2616.txt>.

## Versioning

If you enable versioning for a bucket, Amazon S3 automatically generates a unique version ID for the object being stored. Amazon S3 returns this ID in the response using the `x-amz-version-id` response header. If versioning is suspended, Amazon S3 always uses `null` as the version ID for the object stored. For more information about returning the versioning state of a bucket, see [GET Bucket versioning \(p. 74\)](#).

If you enable versioning on a bucket, when Amazon S3 receives multiple write requests for the same object simultaneously, it stores all of the objects.

To see sample requests that use versioning, see [Sample Request \(p. 192\)](#).

## Reduced Redundancy Storage

Reduced redundancy storage (RRS) enables customers to reduce their costs by storing non-critical, reproducible data at lower levels of redundancy than Amazon S3's standard storage. RRS provides a cost-effective, highly available solution for distributing or sharing content that is durably stored elsewhere, or for storing thumbnails, transcoded media, or other processed data that can be easily reproduced. The RRS option stores objects on multiple devices across multiple facilities, providing 400 times the durability of a typical disk drive, but does not replicate objects as many times as standard Amazon S3 storage. Thus, using RRS is even more cost effective.

To store an object using reduced redundancy, set the `x-amz-storage-class` request header to `REDUCED_REDUNDANCY`. The default value is `STANDARD`.

## Access Permissions

When uploading an object, you can optionally specify the accounts or groups that should be granted specific permissions on your object. There are two ways to grant the appropriate permissions using the request headers:

- Specify a canned (predefined) ACL using the `x-amz-acl` request header. For more information, see [Canned ACL](#) in the *Amazon Simple Storage Service Developer Guide*.
- Specify access permissions explicitly using the `x-amz-grant-read`, `x-amz-grant-read-acp`, and `x-amz-grant-write-acp`, `x-amz-grant-full-control` headers. These headers map to the set of permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#) in the *Amazon Simple Storage Service Developer Guide*.

**Note**

You can either use a canned ACL or specify access permissions explicitly. You cannot do both.

## Requests

### Syntax

```
PUT /ObjectName HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

**Note**

The syntax shows some of the request headers. For a complete list, see the Request Headers section.

### Request Parameters

This implementation of the operation does not use request parameters.

### Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>Cache-Control</i>	Can be used to specify caching behavior along the request/reply chain. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9</a> . Type: String Default: None Constraints: None	No
<i>Content-Disposition</i>	Specifies presentational information for the object. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1">http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1</a> . Type: String Default: None Constraints: None	No

Name	Description	Required
<i>Content-Encoding</i>	Specifies what content encodings have been applied to the object and thus what decoding mechanisms must be applied to obtain the media-type referenced by the <i>Content-Type</i> header field. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.11">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.11</a> . Type: String Default: None Constraints: None	No
<i>Content-Length</i>	The size of the object, in bytes. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.13">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.13</a> . Type: String Default: None Constraints: None	Yes
<i>Content-MD5</i>	The base64-encoded 128-bit MD5 digest of the message (without the headers) according to RFC 1864. This header can be used as a message integrity check to verify that the data is the same data that was originally sent. Although it is optional, we recommend using the Content-MD5 mechanism as an end-to-end integrity check. For more information about REST request authentication, go to <a href="#">REST Authentication</a> in the <a href="#">Amazon Simple Storage Service Developer Guide</a> . Type: String Default: None Constraints: None	No
<i>Content-Type</i>	A standard MIME type describing the format of the contents. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.17">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.17</a> . Type: String Default: binary/octet-stream Valid Values: MIME types Constraints: None	No
<i>Expect</i>	When your application uses <code>100-continue</code> , it does not send the request body until it receives an acknowledgment. If the message is rejected based on the headers, the body of the message is not sent. Type: String Default: None Valid Values: <code>100-continue</code> Constraints: None	No
<i>Expires</i>	Number of milliseconds before expiration Type: Int Default: None Constraints: None	No



Name	Description	Required
<code>x-amz-meta-</code>	Any header starting with this prefix is considered user metadata. It will be stored with the object and returned when you retrieve the object. The PUT request header is limited to 8 KB in size. Within the PUT request header, the user-defined metadata is limited to 2 KB in size. User-defined metadata is a set of key-value pairs. The size of user-defined metadata is measured by taking the sum of the number of bytes in the UTF-8 encoding of each key and value. Type: String Default: None Constraints: None	No
<code>x-amz-server-side-encryption</code>	Specifies a server-side encryption algorithm to use when Amazon S3 creates an object. Type: String Valid Value: AES256	No
<code>x-amz-storage-class</code>	RRS enables customers to reduce their costs by storing non-critical, reproducible data at lower levels of redundancy than Amazon S3's standard storage. Type: Enum Default: STANDARD Valid Values: STANDARD   REDUCED_REDUNDANCY Constraints: You cannot specify GLACIER as the storage class. To transition objects to the GLACIER storage class you can use lifecycle configuration.	No
<code>x-amz-website-redirect-location</code>	If the bucket is configured as a website, redirects requests for this object to another object in the same bucket or to an external URL. Amazon S3 stores the value of this header in the object metadata. For information about object metadata, go to <a href="#">Object Key and Metadata</a> .  In the following example, the request header sets the redirect to an object (anotherPage.html) in the same bucket: x-amz-website-redirect-location: /anotherPage.html  In the following example, the request header sets the object redirect to another website:  x-amz-website-redirect-location: http://www.example.com/  For more information about website hosting in Amazon S3, go to sections <a href="#">Hosting Websites on Amazon S3</a> and <a href="#">How to Configure Website Page Redirects</a> in the <i>Amazon Simple Storage Service Developer Guide</i> . Type: String Default: None Constraints: The value must be prefixed by "/", "http://" or "https://". The length of the value is limited to 2 K.	No

Additionally, you can use the following access control related headers with this operation. By default, all objects are private: only the owner has full control. When adding a new object, you can grant permissions to individual AWS accounts or predefined Amazon S3 groups. These permissions are then used to create the Access Control List (ACL) on the object. For more information, go to [Using ACLs](#).

You can use one of the following two ways to grant these permissions:

- **Specify a canned ACL** — Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, go to [Canned ACL](#).

Name	Description	Required
<code>x-amz-acl</code>	<p>The canned ACL to apply to the object. For more information, see <a href="#">Canned ACL</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p> <p>Type: String</p> <p>Default: private</p> <p>Valid Values: private   public-read   public-read-write   authenticated-read   bucket-owner-read   bucket-owner-full-control</p> <p>Constraints: None</p>	No

- **Specify access permissions explicitly** — If you want to explicitly grant access permissions to specific AWS accounts or a group, you use the following headers. Each of the following headers maps to specific permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#). In the header value, you specify a list of grantees who get the specific permission.

Name	Description	Required
<code>x-amz-grant-read</code>	<p>Allows grantee to read the object data and its metadata.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-write</code>	<p>Not applicable. This applies only when granting permission on a bucket.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-read-ap</code>	<p>Allows grantee to read the object ACL.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grat-write-ap</code>	<p>Allows grantee to write the ACL for the applicable object.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No

Name	Description	Required
<i>x-amz-grant-full-control</i>	Allows grantee the READ, READ_ACP, and WRITE_ACP permissions on the object. Type: String Default: None Constraints: None	No

You specify each grantee as a `type=value` pair, where the type can be one of the following:

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical user ID of an AWS account
- **uri** — if granting permission to a predefined group.

For example, the following `x-amz-grant-read` header grants read object data and its metadata permission to the AWS accounts identified by their email addresses.

```
x-amz-grant-read: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <code>expiry-date</code> and <code>rule-id</code> key-value pairs providing object expiration information. The value of the <code>rule-id</code> is URL encoded. Type: String
<i>x-amz-server-side-encryption</i>	If you request server-side encryption when adding an object, the response includes this header confirming the encryption algorithm used. Type: String
<i>x-amz-version-id</i>	Version of the object. Type: String

### Response Elements

This implementation of the operation does not return response elements.

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request stores the image `my-image.jpg` in the bucket `myBucket`.

```
PUT /my-image.jpg HTTP/1.1
Host: myBucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: text/plain
Content-Length: 11434
Expect: 100-continue
[11434 bytes of object data]
```

### Sample Response With Versioning Suspended

```
HTTP/1.1 100 Continue

HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEb1a0wiIOIxl+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
Date: Wed, 12 Oct 2009 17:50:00 GMT
ETag: "1b2cf535f27731c974343645a3985328"
Content-Length: 0
Connection: close
Server: AmazonS3
```

If an expiration rule created on the bucket using lifecycle configuration applies to the object, you get a response with an `x-amz-expiration` header as shown in the following response. For more information, go to [Object Expiration](#).

```
HTTP/1.1 100 Continue

HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEb1a0wiIOIxl+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
Date: Wed, 12 Oct 2009 17:50:00 GMT
x-amz-expiration: expiry-date="Fri, 23 Dec 2012 00:00:00 GMT", rule-id="1"
ETag: "1b2cf535f27731c974343645a3985328"
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Response with Versioning Enabled

If the bucket has versioning enabled, the response includes the `x-amz-version-id` header.

```
HTTP/1.1 100 Continue

HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEb1a0wiIOIxl+zbwZ163pt7
x-amz-request-id: 0A49CE4060975EAC
x-amz-version-id: 43jfkodU8493jnFJD9fjj3HHNVfdsQUIFDNsidf038jfdsjGFDSIRp
```

```
Date: Wed, 12 Oct 2009 17:50:00 GMT
ETag: "fbacf535f27731c9771645a39863328"
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Request: Specifying reduced redundancy storage class

The following request stores the image, `my-image.jpg`, in the bucket, `myBucket`. The request specifies `x-amz-storage-class` header to request object be stored using the `REDUCED_REDUNDANCY` storage class.

```
PUT /my-image.jpg HTTP/1.1
Host: myBucket.s3.amazonaws.com
Date: Wed, 12 Oct 2009 17:50:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Type: image/jpeg
Content-Length: 11434
Expect: 100-continue
x-amz-storage-class: REDUCED_REDUNDANCY
```

### Sample Response

```
HTTP/1.1 100 Continue

HTTP/1.1 200 OK
x-amz-id-2: LriYPLdmOdAiIfgSm/F1YsViT1LW94/xUQxMsF7xiEbla0wiIOIxl+zbwZl63pt7
x-amz-request-id: 0A49CE4060975EAC
Date: Wed, 12 Oct 2009 17:50:00 GMT
ETag: "1b2cf535f27731c974343645a3985328"
Content-Length: 0
Connection: close
Server: AmazonS3
```

### Sample Request: Uploading an object and specifying access permissions explicitly

The following request stores the file `TestObject.txt` in the bucket `myBucket`. The request specifies various ACL headers to grant permission to AWS accounts specified using canonical user ID and email address.

```
PUT TestObject.txt HTTP/1.1
Host: myBucket.s3.amazonaws.com
x-amz-date: Fri, 13 Apr 2012 05:40:14 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
x-amz-grant-write-acp: id=8a6925ce4adf588a4532142d3f74dd8c71fa124ExampleCanonicalUserID
x-amz-grant-full-control: emailAddress="ExampleUser@amazon.com"
x-amz-grant-write: emailAddress="ExampleUser1@amazon.com", emailAddress="ExampleUser2@amazon.com"
Content-Length: 300
Expect: 100-continue
Connection: Keep-Alive
```

...Object data in the body...

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: RUxG2sZJUfs+ezeAS2i0Xj6w/ST6xqF/8pFNHjTjTrECW56SCAUWGg+7QLVoj1GH
x-amz-request-id: 8D017A90827290BA
Date: Fri, 13 Apr 2012 05:40:25 GMT
ETag: "dd038b344cf9553547f8b395a814b274"
Content-Length: 0
Server: AmazonS3
```

## Sample Request: Using canned ACL to set access permissions

The following request stores the file `TestObject.txt` in the bucket `myBucket`. The request uses an `x-amz-acl` header to specify a canned ACL to grant READ permission to the public.

```
...Object data in the body...
PUT TestObject.txt HTTP/1.1
Host: myBucket.s3.amazonaws.com
x-amz-date: Fri, 13 Apr 2012 05:54:57 GMT
x-amz-acl: public-read
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Length: 300
Expect: 100-continue
Connection: Keep-Alive

...Object data in the body...
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: Yd6PSJxJFQeTYJ/3dDO7miqJfVMXXW0S2Hijo3Wfs4bz6oe2QCVXasxXLZdMfASd
x-amz-request-id: 80DF413BB3D28A25
Date: Fri, 13 Apr 2012 05:54:59 GMT
ETag: "dd038b344cf9553547f8b395a814b274"
Content-Length: 0
Server: AmazonS3
```

## Related Resources

- [PUT Object - Copy \(p. 201\)](#)
- [POST Object \(p. 175\)](#)
- [GET Object \(p. 153\)](#)

# PUT Object acl

## Description

This implementation of the `PUT` operation uses the `acl` subresource to set the access control list (ACL) permissions for an object that already exists in a bucket. You must have `WRITE_ACP` permission to set the ACL of an object.

You can use one of the following two ways to set an object's permissions:

- Specify the ACL in the request body, or
- Specify permissions using request headers

Depending on your application needs, you may choose to set the ACL on an object using either the request body or the headers. For example, if you have an existing application that updates an object ACL using the request body, then you can continue to use that approach.

## Versioning

The ACL of an object is set at the object version level. By default, `PUT` sets the ACL of the latest version of an object. To set the ACL of a different version, use the `versionId` subresource.

To see sample requests that use versioning, see [Sample Request: Setting the ACL of a specified object version](#) (p. 199).

## Requests

### Syntax

The following request shows the syntax for sending the ACL in the request body. If you want to use headers to specify the permissions for the object, you cannot send the ACL in the request body. Instead, see the Request Headers section for a list of headers you can use.

```
PUT /ObjectName?acl HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue

<AccessControlPolicy>
  <Owner>
    <ID>ID</ID>
    <DisplayName>EmailAddress</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>ID</ID>
        <DisplayName>EmailAddress</DisplayName>
      </Grantee>
      <Permission>Permission</Permission>
    </Grant>
    ...
  </AccessControlList>
</AccessControlPolicy>
```

**Note**

The syntax shows some of the request headers. For a complete list see the Request Headers section.

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

You can use the following request headers in addition to the [Common Request Headers \(p. 12\)](#).

These headers enable you to set access permissions using one of the following methods:

- Specify canned ACL, or
- Specify the permission for each grantee explicitly

Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, see [Canned ACL](#). To grant access permissions by specifying canned ACLs, you use the following header and specify the canned ACL name as its value. If you use this header, you cannot use other access control-specific headers in your request.

Name	Description	Required
<i>x-amz-acl</i>	The canned ACL to apply to the object. For more information, go to <a href="#">Canned ACL</a> in the Amazon Simple . Type: String Valid Values: private   public-read   public-read-write   authenticated-read   bucket-owner-read   bucket-owner-full-control Default: private	No

If you need to grant individualized access permissions on an object, you can use the following *x-amz-grant-permission* headers. When using these headers you specify explicit access permissions and grantees (AWS accounts or Amazon S3 groups) who will receive the permission. If you use these ACL specific headers, you cannot use *x-amz-acl* header to set a canned ACL.

**Note**

Each of the following request headers maps to specific permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#).

Name	Description	Required
<i>x-amz-grant-read</i>	Allows the specified grantee to list the objects in the bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write</i>	Not applicable when granting access permissions on objects. You can use this when granting access permissions on buckets. Type: String Default: None Constraints: None	No



Name	Description	Required
<i>x-amz-grant-read-acl</i>	Allows the specified grantee to read the bucket ACL. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write-acl</i>	Allows the specified grantee to write the ACL for the applicable bucket. Type: String Default: None Constraints: None	No
<i>x-amz-grant-full-control</i>	Allows the specified grantee the READ, WRITE, READ_ACP, and WRITE_ACP permissions on the bucket. Type: String Default: None Constraints: None	No

For each of these headers, the value is a comma-separated list of one or more grantees. You specify each grantee as a `type=value` pair, where the type can be one of the following:

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical user ID of an AWS account
- **uri** — if granting permission to a predefined group.

For example, the following `x-amz-grant-read` header grants list objects permission to the two AWS accounts identified by their email addresses.

```
x-amz-grant-read: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

For more information, go to [Access Control List \(ACL\) Overview](#).

## Request Elements

If you decide to use the request body to specify an ACL, you must use the following elements.

### Note

If you use the request body, you cannot use the request headers to set an ACL.

Name	Description
<i>AccessControlList</i>	Container for ACL information Type: Container Ancestors: <i>AccessControlPolicy</i>
<i>AccessControlPolicy</i>	Contains the elements that set the ACL permissions for an object per grantee Type: Container Ancestors: None

Name	Description
<i>DisplayName</i>	Screen name of the bucket owner Type: String Ancestors: <code>AccessControlPolicy.Owner</code>
<i>Grant</i>	Container for the grantee and his or her permissions Type: Container Ancestors: <code>AccessControlPolicy.AccessControlList</code>
<i>Grantee</i>	The subject whose permissions are being set. Type: String Valid Values: <code>DisplayName</code>   <code>EmailAddress</code>   <code>AuthenticatedUser</code> . For more information, see <a href="#">Grantee Values (p. 197)</a> . Ancestors: <code>AccessControlPolicy.AccessControlList.Grant</code>
<i>ID</i>	ID of the bucket owner, or the ID of the grantee Type: String Ancestors: <code>AccessControlPolicy.Owner</code> or <code>AccessControlPolicy.AccessControlList.Grant</code>
<i>Owner</i>	Container for the bucket owner's display name and ID Type: Container Ancestors: <code>AccessControlPolicy</code>
<i>Permission</i>	Specifies the permission given to the grantee Type: String Valid Values: <code>FULL_CONTROL</code>   <code>WRITE</code>   <code>WRITE_ACP</code>   <code>READ</code>   <code>READ_ACP</code> Ancestors: <code>AccessControlPolicy.AccessControlList.Grant</code>

## Grantee Values

You can specify the person (grantee) to whom you're assigning access rights (using request elements) in the following ways:

- By the person's ID:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:type="CanonicalUser">
  <ID>ID</ID>
  <DisplayName>GranteesEmail</DisplayName>
</Grantee>
```

*DisplayName* is optional and ignored in the request.

- By Email address:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="AmazonCustomerByEmail">
  <EmailAddress>Grantees@email.com</EmailAddress>
</Grantee>
```

The grantee is resolved to the *CanonicalUser* and, in a response to a GET Object acl request, appears as the *CanonicalUser*.

- By URI:

```
<Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="Group">
  <URI>http://acs.amazonaws.com/groups/global/AuthenticatedUsers</URI>
</Grantee>
```

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
x-amz-version-id	Version of the object whose ACL is being set. Type: String Default: None

### Response Elements

This operation does not return response elements.

### Special Errors

This operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request grants access permission to an existing object. The request specifies the ACL in the body. In addition to granting full control to the object owner, the XML specifies full control to an AWS account identified by its canonical user ID.

```
PUT /my-image.jpg?acl HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Length: 124

<AccessControlPolicy>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>CustomersName@amazon.com</DisplayName>
  </Owner>
  <AccessControlList>
```

```
<Grant>
  <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeeExampleCanonicalUserID</ID>

    <DisplayName>CustomerName@amazon.com</DisplayName>
  </Grantee>
  <Permission>FULL_CONTROL</Permission>
</Grant>
</AccessControlList>
</AccessControlPolicy>
```

## Sample Response

The following shows a sample response when versioning on the bucket is enabled.

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51T9ASled4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-version-id: 3/L4kqtJlcpXrof3vjVBH40Nr8X8gdRQBpUMLUo
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Sample Request: Setting the ACL of a specified object version

The following request sets the ACL on the specified version of the object.

```
PUT /my-image.jpg?acl&versionId=3HL4kqtJlcpXroDTDmJ+rmSpXd3dIb
rHY+MTRCxf3vjVBH40NrjfkD HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Content-Length: 124

<AccessControlPolicy>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>mtd@amazon.com</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:type="CanonicalUser">
        <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

        <DisplayName>mtd@amazon.com</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51u8yU9ASled4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-version-id: 3/L4kqtJlcpXro3vjVBH40Nr8X8gdRQBpUMLUo
Date: Wed, 28 Oct 2009 22:32:00 GMT
Last-Modified: Sun, 1 Jan 2006 12:00:00 GMT
Content-Length: 0
Connection: close
Server: AmazonS3
```

## Sample Request: Access permissions specified using headers

The following request uses ACL-specific request headers, `x-amz-acl`, and specifies a canned ACL (`public_read`) to grant object read access to everyone.

```
PUT ExampleObject.txt?acl HTTP/1.1
Host: examplebucket.s3.amazonaws.com
x-amz-acl: public-read
Accept: */*
Authorization: AWS AKIAIOSFODNN7EXAMPLE:xQE0diMbLRepdf3YB+FIEXAMPLE=
Host: s3.amazonaws.com
Connection: Keep-Alive
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: w5YegkbG6ZDsje4WK56RWPxNQHIQ0CjrjyRVFZhEJI9E3kbabXnBO9w5G7Dmxsgk
x-amz-request-id: C13B2827BD8455B1
Date: Sun, 29 Apr 2012 23:24:12 GMT
Content-Length: 0
Server: AmazonS3
```

## Related Resources

- [PUT Object - Copy \(p. 201\)](#)
- [POST Object \(p. 175\)](#)
- [GET Object \(p. 153\)](#)

# PUT Object - Copy

## Description

This implementation of the `PUT` operation creates a copy of an object that is already stored in Amazon S3. A `PUT` copy operation is the same as performing a `GET` and then a `PUT`. Adding the request header, `x-amz-copy-source`, makes the `PUT` operation copy the source object into the destination bucket.

### Note

You can store individual objects of up to 5 TB in Amazon S3. You create a copy of your object up to 5 GB in size in a single atomic operation using this API. However, for copying an object greater than 5 GB, you must use the multipart upload API. For conceptual information on multipart upload, go to [Uploading Objects Using Multipart Upload](#) in the *Amazon Simple Storage Service Developer Guide*.

When copying an object, you can preserve most of the metadata (default) or specify new metadata. However, the ACL is not preserved and is set to `private` for the user making the request.

All copy requests must be authenticated and cannot contain a message body. Additionally, you must have `READ` access to the source object and `WRITE` access to the destination bucket. For more information, see [REST Authentication](#).

To copy an object only under certain conditions, such as whether the `ETag` matches or whether the object was modified before or after a specified date, use the request headers `x-amz-copy-source-if-match`, `x-amz-copy-source-if-none-match`, `x-amz-copy-source-if-unmodified-since`, or `x-amz-copy-source-if-modified-since`.

### Note

All headers prefixed with `x-amz-` must be signed, including `x-amz-copy-source`.

There are two opportunities for a copy request to return an error. One can occur when Amazon S3 receives the copy request and the other can occur while Amazon S3 is copying the files. If the error occurs before the `copy` operation starts, you receive a standard Amazon S3 error. If the error occurs during the `copy` operation, the error response is embedded in the `200 OK` response. This means that a `200 OK` response can contain either a success or an error. Make sure to design your application to parse the contents of the response and handle it appropriately.

If the copy is successful, you receive a response that contains the information about the copied object.

### Note

If the request is an HTTP 1.1 request, the response is chunk encoded. Otherwise, it will not contain the content-length and you will need to read the entire body.

## Versioning

By default, `x-amz-copy-source` identifies the latest version of an object to copy. (If the latest version is a Delete Marker, Amazon S3 behaves as if the object was deleted.) To copy a different version, use the `versionId` subresource.

If you enable Versioning on the target bucket, Amazon S3 generates a unique version ID for the object being copied. This version ID is different from the version ID of the source object. Amazon S3 returns the version ID of the copied object in the `x-amz-version-id` response header in the response.

If you do not enable versioning or suspend it on the target bucket, the version ID Amazon S3 generates is always `null`.

If the source object's storage class is `Glacier`, then you must first restore a copy of this object before you can use it as a source object for the copy operation. For more information, see [POST Object restore](#) (p. 182).

To see sample requests that use versioning, see [Sample Request: Copying a specified version of an object](#) (p. 208).

## Access Permissions

When copying an object, you can optionally specify the accounts or groups that should be granted specific permissions on the new object. There are two ways to grant the permissions using the request headers:

- Specify a canned ACL using the `x-amz-acl` request header. For more information, see [Canned ACL](#) in the *Amazon Simple Storage Service Developer Guide*.
- Specify access permissions explicitly using the `x-amz-grant-read`, `x-amz-grant-read-acp`, `x-amz-grant-write-acp`, and `x-amz-grant-full-control` headers. These headers map to the set of permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#) in the *Amazon Simple Storage Service Developer Guide*.

### Note

You can use either a canned ACL or specify access permissions explicitly. You cannot do both.

## Requests

### Syntax

```
PUT /destinationObject HTTP/1.1
Host: destinationBucket.s3.amazonaws.com
x-amz-copy-source: /source_bucket/sourceObject
x-amz-metadata-directive: metadata_directive
x-amz-copy-source-if-match: etag
x-amz-copy-source-if-none-match: etag
x-amz-copy-source-if-unmodified-since: time_stamp
x-amz-copy-source-if-modified-since: time_stamp
<request metadata>
Authorization: signatureValue
Date: date
```

### Note

The syntax shows only some of the request headers. For a complete list, see the Request Headers section.

## Request Parameters

This implementation of the operation does not use request parameters.

## Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers](#) (p. 12).

Name	Description	Required
<i>x-amz-copy-source</i>	<p>The name of the source bucket and key name of the source object, separated by a slash (/).</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints:</p> <p>This string must be URL-encoded. Additionally, the source bucket must be valid and you must have READ access to the valid source object.</p> <p>If the source object is archived in Amazon Glacier (storage class of the object is GLACIER), you must first restore a temporary copy using the <a href="#">POST Object restore (p. 182)</a>. Otherwise, Amazon S3 returns the 403 <code>ObjectNotInActiveTierError</code> error response.</p>	Yes
<i>x-amz-metadata-directive</i>	<p>Specifies whether the metadata is copied from the source object or replaced with metadata provided in the request.</p> <ul style="list-style-type: none"><li>• If copied, the metadata, except for the version ID, remains unchanged. In addition, the <code>server-side-encryption</code>, <code>storage-class</code>, and <code>website-redirect-location</code> metadata from the source is not copied. If you specify this metadata explicitly in the copy request, Amazon S3 adds this metadata to the resulting object. If you specify headers in the request specifying any user-defined metadata, Amazon S3 ignores these headers.</li><li>• If replaced, all original metadata is replaced by the metadata you specify.</li></ul> <p>Type: String</p> <p>Default: <code>COPY</code></p> <p>Valid values: <code>COPY</code>   <code>REPLACE</code></p> <p>Constraints: Values other than <code>COPY</code> or <code>REPLACE</code> result in an immediate 400-based error response. You cannot copy an object to itself unless the <code>MetadataDirective</code> header is specified and its value set to <code>REPLACE</code>.</p> <p>For information on supported metadata, see <a href="#">Common Request Headers (p. 12)</a></p>	No



Name	Description	Required
<i>x-amz-copy-source-if-match</i>	Copies the object if its entity tag (ETag) matches the specified tag; otherwise, the request returns a 412 HTTP status code error (failed precondition). Type: String Default: None Constraints: This header can be used with <i>x-amz-copy-source-if-unmodified-since</i> , but cannot be used with other conditional copy headers.	No
<i>x-amz-copy-source-if-none-match</i>	Copies the object if its entity tag (ETag) is different than the specified ETag; otherwise, the request returns a 412 HTTP status code error (failed precondition). Type: String Default: None Constraints: This header can be used with <i>x-amz-copy-source-if-modified-since</i> , but cannot be used with other conditional copy headers.	No
<i>x-amz-copy-source-if-unmodified-since</i>	Copies the object if it hasn't been modified since the specified time; otherwise, the request returns a 412 HTTP status code error (failed precondition). Type: String Default: None Constraints: This must be a valid HTTP date. For more information, go to <a href="http://www.ietf.org/rfc/rfc2616.txt">http://www.ietf.org/rfc/rfc2616.txt</a> . This header can be used with <i>x-amz-copy-source-if-match</i> , but cannot be used with other conditional copy headers.	No
<i>x-amz-copy-source-if-modified-since</i>	Copies the object if it has been modified since the specified time; otherwise, the request returns a 412 HTTP status code error (failed condition). Type: String Default: None Constraints: This must be a valid HTTP date. This header can be used with <i>x-amz-copy-source-if-none-match</i> , but cannot be used with other conditional copy headers.	No
<i>x-amz-server-side-encryption</i>	Specifies the server-side encryption algorithm to use when Amazon S3 creates the target object. Type: String Valid Value: AES256	No

Name	Description	Required
<code>x-amz-storage-class</code>	<p>RRS enables customers to reduce their costs by storing noncritical, reproducible data at lower levels of redundancy than Amazon S3's standard storage.</p> <p>Type: Enum</p> <p>Default: STANDARD</p> <p>Valid Values: STANDARD   REDUCED_REDUNDANCY</p> <p>Constraints: You cannot specify GLACIER as the storage class. To transition objects to the GLACIER storage class you can use lifecycle configuration.</p>	No
<code>x-amz-website-redirect-location</code>	<p>If the bucket is configured as a website, redirects requests for this object to another object in the same bucket or to an external URL. Amazon S3 stores the value of this header in the object metadata. For information about object metadata, go to <a href="#">Object Key and Metadata</a>.</p> <p>In the following example, the request header sets the redirect to an object (anotherPage.html) in the same bucket:</p> <pre>x-amz-website-redirect-location: /anotherPage.html</pre> <p>In the following example, the request header sets the object redirect to another website:</p> <pre>x-amz-website-redirect-location: http://www.example.com/</pre> <p>For more information about website hosting in Amazon S3, go to sections <a href="#">Hosting Websites on Amazon S3</a> and <a href="#">How to Configure Website Page Redirects</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: The value must be prefixed by, "/", "http://" or "https://". The length of the value is limited to 2 K.</p>	No

Additionally, you can use the following access control related headers with this operation. By default, all objects are private, only the owner has full access control. When adding a new object, you can grant permissions to individual AWS accounts or predefined groups defined by Amazon S3. These permissions are then added to the Access Control List (ACL) on the object. For more information, go to [Using ACLs](#). This operation enables you grant access permissions using one of the following two methods:

- **Specify a canned ACL** — Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, go to [Canned ACL](#).

Name	Description	Required
<code>x-amz-acl</code>	<p>The canned ACL to apply to the object. For more information, go to <a href="#">REST Access Policy</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p> <p>Type: String</p> <p>Default: private</p> <p>Valid Values: <code>private</code>   <code>public-read</code>   <code>public-read-write</code>   <code>authenticated-read</code>   <code>bucket-owner-read</code>   <code>bucket-owner-full-control</code></p> <p>Constraints: None</p>	No

- **Specify access permissions explicitly** — If you want to explicitly grant access permissions to specific AWS accounts or groups, you can use the following headers. Each of these headers maps to specific permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#). In the header, you specify a list of grantees who get the specific permission.

Name	Description	Required
<code>x-amz-grant-read</code>	<p>Allows grantee to read the object data and its metadata.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-write</code>	<p>Not applicable. This applies only when granting access permissions on a bucket.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-read-acl</code>	<p>Allows grantee to read the object ACL.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-write-acl</code>	<p>Allows grantee to write the ACL for the applicable object.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No
<code>x-amz-grant-full-control</code>	<p>Allows grantee the READ, READ_ACP, and WRITE_ACP permissions on the object.</p> <p>Type: String</p> <p>Default: None</p> <p>Constraints: None</p>	No

You specify each grantee as a `type=value` pair, where the type can be one of the following:

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical user ID of an AWS account
- **uri** — if granting permission to a predefined group.

For example, the following `x-amz-grant-read` header grants read object data and its metadata permission to the AWS accounts identified by their email addresses.

```
x-amz-grant-read: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

## Request Elements

This implementation of the operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <code>expiry-date</code> and <code>rule-id</code> key-value pairs providing object expiration information. The value of the <code>rule-id</code> is URL encoded. Type: String
<i>x-amz-copy-source-version-id</i>	Version of the source object that was copied. Type: String
<i>x-amz-server-side-encryption</i>	If you request server-side encryption, the response includes this header confirming the encryption algorithm used for the target object. Type: String
<i>x-amz-version-id</i>	Version of the copied object in the destination bucket. Type: String

### Response Elements

Name	Description
<i>CopyObjectResult</i>	Container for all response elements. Type: Container Ancestor: None
<i>ETag</i>	Returns the <code>ETag</code> of the new object. The <code>ETag</code> only reflects changes to the contents of an object, not its metadata. Type: String Ancestor: <code>CopyObjectResult</code>

Name	Description
<i>LastModified</i>	Returns the date the object was last modified. Type: String Ancestor: CopyObjectResult

## Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses](#) (p. 3).

## Examples

### Sample Request

This example copies `my-image.jpg` into the bucket, `bucket`, with the key name `my-second-image.jpg`.

```
PUT /my-second-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
x-amz-copy-source: /bucket/my-image.jpg
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-copy-source-version-id: 3/L4kqtJlcpXroDTDmJ+rmSpXd3dIb
rHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
x-amz-version-id: QUpfdndhfd8438MNFNDN93jdnJFkdmqnh893
Date: Wed, 28 Oct 2009 22:32:00 GMT
Connection: close
Server: AmazonS3

<CopyObjectResult>
  <LastModified>2009-10-28T22:32:00</LastModified>
  <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
</CopyObjectResult>
```

*x-amz-version-id* returns the version ID of the object in the destination bucket, and *x-amz-copy-source-version-id* returns the version ID of the source object.

### Sample Request: Copying a specified version of an object

The following request copies the key `my-image.jpg` with the specified version ID and copies it into the bucket `bucket` and gives it the key `my-second-image.jpg`.

```
PUT /my-second-image.jpg HTTP/1.1
Host: bucket.s3.amazonaws.com
Date: Wed, 28 Oct 2009 22:32:00 GMT
x-amz-copy-source: /bucket/my-image.jpg?versionId=3/L4kqtJlcpXroDTDmJ+rmSpXd3dIb
```

```
rHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Success Response: Copying a versioned object into a version enabled bucket

The following response shows that an object was copied into a target bucket where Versioning is enabled.

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-version-id: QUpfdndhfd8438MNFDN93jdnJFkdmqnh893
  x-amz-copy-source-version-id: 09df8234529fjs0dfi0w52935029wefdj
Date: Wed, 28 Oct 2009 22:32:00 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<CopyObjectResult>
  <LastModified>2009-10-28T22:32:00</LastModified>
  <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
</CopyObjectResult>
```

## Success Response: Copying a versioned object into a version suspended bucket

The following response shows that an object was copied into a target bucket where versioning is suspended. Note that the parameter `<VersionId>` does not appear.

```
HTTP/1.1 200 OK
x-amz-id-2: eftixk72aD6Ap51TnqcoF8eFidJG9Z/2mkiDFu8yU9AS1ed4OpIszj7UDNEHGran
x-amz-request-id: 318BC8BC148832E5
x-amz-copy-source-version-id: 3/L4kqtJlcpXroDTDmJ+rmSpXd3dIb
rHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
Date: Wed, 28 Oct 2009 22:32:00 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<CopyObjectResult>
  <LastModified>2009-10-28T22:32:00</LastModified>
  <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
</CopyObjectResult>
```

## Related Resources

- [Copying Objects](#)
- [PUT Object \(p. 185\)](#)
- [GET Object \(p. 153\)](#)

# Initiate Multipart Upload

## Description

This operation initiates a multipart upload and returns an upload ID. This upload ID is used to associate all the parts in the specific multipart upload. You specify this upload ID in each of your subsequent upload part requests (see [Upload Part \(p. 216\)](#)). You also include this upload ID in the final request to either complete or abort the multipart upload request.

For more information on multipart uploads, go to [Multipart Upload Overview](#) in the *Amazon Simple Storage Service Developer Guide*.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon Simple Storage Service Developer Guide*.

### Note

If you create an object using the multipart upload APIs, currently you cannot copy the object between regions.

## Requests

### Syntax

```
POST /ObjectName?uploads HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Authorization: signatureValue
```

### Request Parameters

This operation does not use request parameters.

### Request Headers

Name	Description	Required
<i>Cache-Control</i>	Can be used to specify caching behavior along the request/reply chain. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9</a> . Type: String Default: None	No
<i>Content-Disposition</i>	Specifies presentational information for the object. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1">http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1</a> . Type: String Default: None	No

Name	Description	Required
<i>Content-Encoding</i>	Specifies what content encodings have been applied to the object and thus what decoding mechanisms must be applied to obtain the media-type referenced by the <i>Content-Type</i> header field. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.11">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.11</a> . Type: String Default: None	No
<i>Content-Type</i>	A standard MIME type describing the format of the object data. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.17">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.17</a> . Type: String Default: binary/octet-stream Constraints: MIME types only	No
<i>Expires</i>	The date and time at which the object is no longer cacheable. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.21">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.21</a> . Type: String Default: None	No
<i>x-amz-meta-</i>	Any header starting with this prefix is considered user metadata. It will be stored with the object and returned when you retrieve the object. Type: String Default: None	No
<i>x-amz-server-side-encryption</i>	Specifies the server-side encryption algorithm to use. As you uploads individual object parts, Amazon S3 applies server-side encryption to each part you upload. Type: String Valid Value: AES256	No
<i>x-amz-storage-class</i>	The type of storage to use for the object that is created after successful multipart upload. Type: String Valid Values: STANDARD   REDUCED_REDUNDANCY Default: STANDARD Constraints: You cannot specify GLACIER as the storage class. To transition objects to the GLACIER storage class you can use lifecycle configuration.	No



Name	Description	Required
<code>x-amz-website-redirect-location</code>	<p>If the bucket is configured as a website, redirects requests for this object to another object in the same bucket or to an external URL. Amazon S3 stores the value of this header in the object metadata. For information about object metadata, go to <a href="#">Object Key and Metadata</a>.</p> <p>In the following example, the request header sets the redirect to an object (anotherPage.html) in the same bucket:  <code>x-amz-website-redirect-location: /anotherPage.html</code></p> <p>In the following example, the request header sets the object redirect to another website:  <code>x-amz-website-redirect-location: http://www.example.com/</code></p> <p>For more information about website hosting in Amazon S3, go to sections <a href="#">Hosting Websites on Amazon S3</a> and <a href="#">How to Configure Website Page Redirects</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p> <p>Type: String  Default: None  Constraints: The value must be prefixed by "/", "http://" or "https://". The length of the value is limited to 2 K.</p>	No

Additionally, you can use the following access control-related headers with this operation. By default, all objects are private, only the owner has full access control. When adding a new object, you can grant permissions to individual AWS accounts or predefined groups defined by Amazon S3. These permissions are then added to the Access Control List (ACL) on the object. For more information, go to [Access Control List \(ACL\) Overview](#) in the *Amazon Simple Storage Service Developer Guide*. This operation enables you grant access permissions using one of the following two ways:

- **Specify canned ACL** — Amazon S3 supports a set of predefined ACLs, known as canned ACLs. Each canned ACL has a predefined set of grantees and permissions. For more information, go to [Canned ACL](#).

Name	Description	Required
<code>x-amz-acl</code>	<p>The canned ACL to apply to the object. For more information, go to <a href="#">REST Access Policy</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p> <p>Type: String  Default: private  Valid Values: <code>private   public-read   public-read-write   authenticated-read   bucket-owner-read   bucket-owner-full-control</code>  Constraints: None</p>	No

- **Specify access permissions explicitly** — If you want to explicitly grant access permissions to specific AWS accounts or groups, you can use the following headers. Each of these headers maps to specific

permissions Amazon S3 supports in an ACL. For more information, go to [Access Control List \(ACL\) Overview](#). In the header, you specify a list of grantees who get the specific permission.

Name	Description	Required
<i>x-amz-grant-read</i>	Allows grantee to read the object data and its metadata. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write</i>	Not applicable. Type: String Default: None Constraints: None	No
<i>x-amz-grant-read-acp</i>	Allows grantee to read the object ACL. Type: String Default: None Constraints: None	No
<i>x-amz-grant-write-acp</i>	Allows grantee to write the ACL for the applicable object. Type: String Default: None Constraints: None	No
<i>x-amz-grant-full-control</i>	Allows grantee the READ, READ_ACP, and WRITE_ACP permissions on the object. Type: String Default: None Constraints: None	No

You specify each grantee as a `type=value` pair, where the type can be one of the following::

- **emailAddress** — if value specified is the email address of an AWS account
- **id** — if value specified is the canonical user ID of an AWS account
- **uri** — if granting permission to a predefined group.

For example, the following `x-amz-grant-read` header grants read object data and its metadata permission to the AWS accounts identified by their email addresses.

```
x-amz-grant-read: emailAddress="xyz@amazon.com", emailAddress="abc@amazon.com"
```

## Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
<i>x-amz-server-side-encryption</i>	If you specify server-side encryption in your request, the response includes this header. It confirms the encryption algorithm that will be used for the object that is created after successful multipart upload. Type: String

### Response Elements

Name	Description
InitiateMultipartUploadResult	Container for response. Type: Container Children: Bucket, Key, UploadId Ancestors: None
Bucket	Name of the bucket to which the multipart upload was initiated. Type: string Ancestors: InitiateMultipartUploadResult
Key	Object key for which the multipart upload was initiated. Type: String Ancestors: InitiateMultipartUploadResult
UploadId	ID for the initiated multipart upload. Type: String Ancestors: InitiateMultipartUploadResult

### Special Errors

This implementation of the operation does not return special errors. For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

This operation initiates a multipart upload for the `example-object` object.

```
POST /example-object?uploads HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

## Sample Response

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOFg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 197
Connection: keep-alive
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<InitiateMultipartUploadResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">

  <Bucket>example-bucket</Bucket>
  <Key>example-object</Key>
  <UploadId>VXBsb2FkIElEIGZvcia2aWWpbmcncyBteS1tb3ZpZS5tMnRzIHVwbG9hZA</UploadId>
</InitiateMultipartUploadResult>
```

## Related Actions

- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)
- [List Multipart Uploads \(p. 81\)](#)

# Upload Part

## Description

This operation uploads a part in a multipart upload.

### Note

In this operation you provide part data in your request. However, you have an option to specify your existing Amazon S3 object as data source for the part you are uploading. To upload a part from an existing object you use the Upload Part (Copy) operation. For more information, see [Upload Part - Copy \(p. 219\)](#).

You must initiate a multipart upload (see [Initiate Multipart Upload \(p. 210\)](#)) before you can upload any part. In response to your initiate request, Amazon S3 returns an upload ID, a unique identifier, that you must include in your upload part request.

Part numbers can be any number from 1 to 10,000, inclusive. A part number uniquely identifies a part and also defines its position within the object being created. If you upload a new part using the same part number that was used with a previous part, the previously uploaded part is overwritten. Each part must be at least 5 MB in size, except the last part. There is no size limit on the last part of your multipart upload.

To ensure that data is not corrupted when traversing the network, specify the `Content-MD5` header in the upload part request. Amazon S3 checks the part data against the provided MD5 value. If they do not match, Amazon S3 returns an error.

For more information on multipart uploads, go to [Multipart Upload Overview](#) in the *Amazon S3 Developer guide*.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer guide*.

## Requests

### Syntax

```
PUT /ObjectName?partNumber=PartNumber&uploadId=UploadId HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: date
Content-Length: Size
Authorization: Signature
```

### Request Parameters

This operation does not use request parameters.

### Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>Content-Length</i>	The size of the part, in bytes. For more information, go to <a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.13">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.13</a> . Type: Integer Default: None	Yes
<i>Content-MD5</i>	The base64-encoded 128-bit MD5 digest of the part data. This header can be used as a message integrity check to verify that the part data is the same data that was originally sent. Although it is optional, we recommend using the Content-MD5 mechanism as an end-to-end integrity check. For more information, see <a href="#">RFC 1864</a> . Type: String Default: None	No
<i>Expect</i>	When your application uses 100-continue, it does not send the request body until it receives an acknowledgment. If the message is rejected based on the headers, the body of the message is not sent. For more information, go to <a href="#">RFC 2616</a> . Type: String Default: None Valid Values: 100-continue	No

## Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This implementation of the operation can include the following response headers in addition to the response headers common to all responses. For more information, see [Common Response Headers \(p. 14\)](#).

Name	Description
<i>x-amz-server-side-encryption</i>	If you specified server-side encryption in your initiate multipart upload request, the response includes this header. It confirms the encryption algorithm that Amazon S3 used to encrypt the part you uploaded. Type: String

### Response Elements

This operation does not use response elements.

## Special Errors

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
NoSuchUpload	The specified multipart upload does not exist. The upload ID might be invalid, or the multipart upload might have been aborted or completed.	404 Not Found	Client

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following PUT request uploads a part (part number 1) in a multipart upload. The request includes the upload ID that you get in response to your Initiate Multipart Upload request.

```
PUT /my-movie.m2ts?partNumber=1&uploadId=VCVsb2FkIElEIGZvciblbZzpbm
cncyBteS1tb3ZpZS5tMnRzIHVwbG9hZR HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 10485760
Content-MD5: pUNXr/BjKK5G2UKvaRRrOA==
Authorization: AWS AKIAIOSFODNN7EXAMPLE:VGhpcyBtZXNzYWdlIHNPZ25lZGgieSRlbHZpbmc=

***part data omitted***
```

### Sample Response

The response includes the ETag header. You need to retain this value for use when you send the Complete Multipart Upload request.

```
HTTP/1.1 200 OK
x-amz-id-2: Vvag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
ETag: "b54357faf0632cce46e942fa68356b38"
Content-Length: 0
Connection: keep-alive
Server: AmazonS3
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)
- [List Multipart Uploads \(p. 81\)](#)

# Upload Part - Copy

## Description

Uploads a part by copying data from an existing object as data source. You specify the data source by adding the request header `x-amz-copy-source` in your request and a byte range by adding the request header `x-amz-copy-source-range` in your request.

### Note

Instead of using an existing object as part data, you might use the `Upload Part` operation and provide data in your request. For more information, see [Upload Part \(p. 216\)](#).

You must initiate a multipart upload before you can upload any part. In response to your initiate request, Amazon S3 returns a unique identifier, the upload ID, that you must include in your upload part request.

For conceptual information on multipart uploads, go to [Uploading Objects Using Multipart Upload](#) in the *Amazon S3 Developer guide*. For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer guide*. To more information about copying objects using a single atomic operation vs. the multipart upload, go to [Operations On Objects](#) in the *Amazon S3 Developer guide*.

## Requests

### Syntax

```
PUT /ObjectName?partNumber=PartNumber&uploadId=UploadId HTTP/1.1
Host: BucketName.s3.amazonaws.com
x-amz-copy-source: /source_bucket/sourceObject
x-amz-copy-source-range: bytes=first-last
x-amz-copy-source-if-match: etag
x-amz-copy-source-if-none-match: etag
x-amz-copy-source-if-unmodified-since: time_stamp
x-amz-copy-source-if-modified-since: time_stamp
Date: date
Authorization: Signature
```

### Request Parameters

This operation does not use request parameters.

### Request Headers

This implementation of the operation can use the following request headers in addition to the request headers common to all operations. For more information, see [Common Request Headers \(p. 12\)](#).

Name	Description	Required
<i>x-amz-copy-source</i>	The name of the source bucket and the source object key name separated by a slash (/). Type: String Default: None	Yes



Name	Description	Required
<i>x-amz-copy-source-range</i>	<p>The range of bytes to copy from the source object. The range value must use the form <code>bytes=first-last</code>, where the first and last are the zero-based byte offsets to copy. For example, <code>bytes=0-9</code> indicates that you want to copy the first ten bytes of the source.</p> <p>You can copy a range only if the source object is greater than 5 GB.</p> <p>This request header is not required when copying an entire source object.</p> <p>Type: Integer Default: None</p>	No

The following conditional headers are based on the object that the *x-amz-copy-source* header specifies.

Name	Description	Required
<i>x-amz-copy-source-if-match</i>	<p>Perform a copy if the source object entity tag (ETag) matches the specified value. If the value does not match, Amazon S3 returns an HTTP status code 412 <i>precondition failed</i> error.</p> <p>Type: String Default: None</p>	No
<i>x-amz-copy-source-if-none-match</i>	<p>Perform a copy if the source object entity tag (ETag) is different than the value specified using this header. If the values match, Amazon S3 returns an HTTP status code 412 <i>precondition failed</i> error.</p> <p>Type: String Default: None</p>	No
<i>x-amz-copy-source-if-unmodified-since</i>	<p>Perform a copy if the source object is not modified after the time specified using this header. If the source object is modified, Amazon S3 returns an HTTP status code 412 <i>precondition failed</i> error.</p> <p>Type: String Default: None</p>	No
<i>x-amz-copy-source-if-modified-since</i>	<p>Perform a copy if the source object is modified after the time specified using this header. If the source object is not modified, Amazon S3 returns an HTTP status code 412 <i>precondition failed</i> error.</p> <p>Type: String Default: None</p>	No

## Request Elements

This operation does not use request elements.

## Versioning

If your bucket has versioning enabled, you could have multiple versions of the same object. By default, *x-amz-copy-source* identifies the latest version of the object to copy. If the latest version is a delete marker and you don't specify a versionId in the *x-amz-copy-source*, Amazon S3 returns a 404 error, because the object does not exist. If you specify versionId in the *x-amz-copy-source* and the versionId is a delete marker, Amazon S3 returns an HTTP 400 error, because you are not allowed to specify a delete marker as a version for the *x-amz-copy-source*.

You can optionally specify a specific version of the source object to copy by adding the `versionId` subresource as shown in the following example:

```
x-amz-copy-source: /bucket/object?versionId=version id
```

## Responses

### Response Headers

This implementation of the operation can include the following headers in addition to the response headers common to all response. For more information, see [Common Response Headers](#) (p. 14).

Name	Description
<i>x-amz-copy-source-version-id</i>	The version of the source object that was copied, if you have enabled versioning on the source bucket. Type: String
<i>x-amz-server-side-encryption</i>	If you specified server-side encryption in your initiate multipart upload request, the response includes this header. It confirms the encryption algorithm that Amazon S3 used to encrypt the part that you uploaded. Type: String

### Response Elements

Name	Description
<i>CopyPartResult</i>	Container for all response elements. Type: Container Ancestor: None
<i>ETag</i>	Returns the ETag of the new part. Type: String Ancestor: <i>CopyPartResult</i>
<i>LastModified</i>	Returns the date the part was last modified. Type: String Ancestor: <i>CopyPartResult</i>

## Special Errors

Error Code	Description	HTTP Status Code
NoSuchUpload	The specified multipart upload does not exist. The upload ID might be invalid, or the multipart upload might have been aborted or completed.	404 Not Found
InvalidRequest	The specified copy source is not supported as a byte-range copy source.	400 Bad Request

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

As the following examples illustrate, when a request succeeds, Amazon S3 returns `<CopyPartResult>` in the body. If you included `versionId` in the request, Amazon S3 returns the version ID in the `x-amz-copy-source-version-id` response header.

### Sample Request

The following `PUT` request uploads a part (part number 2) in a multipart upload. The request specifies a byte range from an existing object as the source of this upload. The request includes the upload ID that you get in response to your `Initiate Multipart Upload` request.

```
PUT /newobject?partNumber=2&uploadId=VCVsb2FkIElEIGZvciBlbZZpbm
cncyBteS1tb3ZpZS5tMnRzIHVwbG9hZR HTTP/1.1
Host: target-bucket.s3.amazonaws.com
Date: Mon, 11 Apr 2011 20:34:56 GMT
x-amz-copy-source: /source-bucket/sourceobject
x-amz-copy-source-range: bytes=500-6291456
Authorization: AWS AKIAIOSFODNN7EXAMPLE:VGhpcyBtZXNzYWdlIHdpZ251ZGgieSRlbHZZpbmc=
```

### Sample Response

The response includes the `ETag` value. You need to retain this value to use when you send the `Complete Multipart Upload` request.

```
HTTP/1.1 200 OK
x-amz-id-2: Vvag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtrPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 11 Apr 2011 20:34:56 GMT
Server: AmazonS3

<CopyPartResult>
  <LastModified>2009-10-28T22:32:00</LastModified>
  <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
</CopyPartResult>
```

### Sample Request

The following `PUT` request uploads a part (part number 2) in a multipart upload. The request does not specify the optional byte range header, but requests the entire source object copy as part 2. The request includes the upload ID that you got in response to your `Initiate Multipart Upload` request.

```
PUT /newobject?partNumber=2&uploadId=VCVsb2FkIElEIGZvciBlbZZpbm
cncyBteS1tb3ZpZS5tMnRzIHVwbG9hZR HTTP/1.1
Host: target-bucket.s3.amazonaws.com
Date: Mon, 11 Apr 2011 20:34:56 GMT
x-amz-copy-source: /source-bucket/sourceobject
Authorization: AWS AKIAIOSFODNN7EXAMPLE:VGhpcyBtZXNzYWdlIHNPZ25lZGgieSRlbHZpbmc=
Sample Response
```

The response structure is similar to the one specified in the preceding example.

## Sample Request

The following PUT request uploads a part (part number 2) in a multipart upload. The request specifies a specific version of the source object to copy by adding the `versionId` subresource. The byte range requests 6 MB of data, starting with byte 500, as the part to be uploaded.

```
PUT /newobject?partNumber=2&uploadId=VCVsb2FkIElEIGZvciBlbZZpbm
cncyBteS1tb3ZpZS5tMnRzIHVwbG9hZR HTTP/1.1
Host: target-bucket.s3.amazonaws.com
Date: Mon, 11 Apr 2011 20:34:56 GMT
x-amz-copy-source: /source-bucket/sourceobject?versionId=3/L4kqtJlcpXroDTDmJ+rm
SpXd3dIbrHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
x-amz-copy-source-range:bytes=500-6291456
Authorization: AWS AKIAIOSFODNN7EXAMPLE:VGhpcyBtZXNzYWdlIHNPZ25lZGgieSRlbHZpbmc=
```

## Sample Response

The response includes the ETag value. You need to retain this value to use when you send the Complete Multipart Upload request.

```
HTTP/1.1 200 OK
x-amz-id-2: Vvag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
x-amz-copy-source-version-id: 3/L4kqtJlcpXroDTDmJ+rmSpXd3dIb
rHY+MTRCxf3vjVBH40Nr8X8gdRQBpUMLUo
Date: Mon, 11 Apr 2011 20:34:56 GMT
Server: AmazonS3

<CopyPartResult>
  <LastModified>2009-10-28T22:32:00</LastModified>
  <ETag>"9b2cf535f27731c974343645a3985328"</ETag>
</CopyPartResult>
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)
- [List Multipart Uploads \(p. 81\)](#)

# Complete Multipart Upload

## Description

This operation completes a multipart upload by assembling previously uploaded parts.

You first initiate the multipart upload and then upload all parts using the Upload Parts operation (see [Upload Part \(p. 216\)](#)). After successfully uploading all relevant parts of an upload, you call this operation to complete the upload. Upon receiving this request, Amazon S3 concatenates all the parts in ascending order by part number to create a new object. In the Complete Multipart Upload request, you must provide the parts list. You must ensure the parts list is complete, this operation concatenates the parts you provide in the list. For each part in the list, you must provide the part number and the *ETag* header value, returned after that part was uploaded.

Processing of a Complete Multipart Upload request could take several minutes to complete. After Amazon S3 begins processing the request, it sends an HTTP response header that specifies a 200 OK response. While processing is in progress, Amazon S3 periodically sends whitespace characters to keep the connection from timing out. Because a request could fail after the initial 200 OK response has been sent, it is important that you check the response body to determine whether the request succeeded.

Note that if Complete Multipart Upload fails, applications should be prepared to retry the failed requests. For more information, go to [Amazon S3 Error Best Practices](#) section of the *Amazon S3 Developer guide*.

For more information on multipart uploads, go to [Uploading Objects Using Multipart Upload](#) in the *Amazon S3 Developer guide*.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer guide*.

## Requests

### Syntax

```
POST /ObjectName?uploadId=UploadId HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Date
Content-Length: Size
Authorization: Signature

<CompleteMultipartUpload>
  <Part>
    <PartNumber>PartNumber</PartNumber>
    <ETag>ETag</ETag>
  </Part>
  ...
</CompleteMultipartUpload>
```

### Request Parameters

This operation does not use request parameters.

### Request Headers

This operation uses only Request Headers common to most requests. For more information, see [Common Request Headers \(p. 12\)](#)

## Request Elements

Name	Description	Required
<i>CompleteMultipartUpload</i>	Container for the request.  Ancestor: None Type: Container Children: One or more <i>Part</i> elements	Yes
<i>Part</i>	Container for elements related to a particular previously uploaded part.  Ancestor: <i>CompleteMultipartUpload</i> Type: Container Children: <i>PartNumber</i> , <i>ETag</i>	Yes
<i>PartNumber</i>	Part number that identifies the part.  Ancestor: <i>Part</i> Type: Integer	Yes
<i>ETag</i>	Entity tag returned when the part was uploaded.  Ancestor: <i>Part</i> Type: String	Yes

## Responses

### Response Headers

The operation uses the following response header, in addition to the response headers common to most requests. For more information, see [Common Response Headers \(p. 14\)](#).

Header	Description
<i>x-amz-expiration</i>	If the object expiration is configured (see <a href="#">PUT Bucket lifecycle (p. 106)</a> ), the response includes this header. It includes the <code>expiry-date</code> and <code>rule-id</code> key value pairs providing object expiration information. The value of the <code>rule-id</code> is URL encoded.  Type: String
<i>x-amz-server-side-encryption</i>	If you specified server-side encryption in your initiate multipart upload request, the response includes this header confirming the encryption algorithm Amazon S3 used to save your object data to disks in its data centers.  Type: String
<i>x-amz-version-id</i>	Version ID of the newly created object, in case the bucket has versioning turned on.  Type: String

## Response Elements

Name	Description
<code>CompleteMultipartUploadResult</code>	Container for the response Type: Container Children: <i>Location</i> , <i>Bucket</i> , <i>Key</i> , <i>ETag</i> Ancestors: None
<code>Location</code>	The URI that identifies the newly created object. Type: URI Ancestors: <i>CompleteMultipartUploadResult</i>
<code>Bucket</code>	The name of the bucket that contains the newly created object. Type: String Ancestors: <i>CompleteMultipartUploadResult</i>
<code>Key</code>	The object key of the newly created object. Type: String Ancestors: <i>CompleteMultipartUploadResult</i>
<code>ETag</code>	Entity tag that identifies the newly created object's data. Objects with different object data will have different entity tags. The entity tag is an opaque string. The entity tag may or may not be an MD5 digest of the object data. If the entity tag is not an MD5 digest of the object data, it will contain one or more non-hexadecimal characters and/or will consist of less than 32 or more than 32 hexadecimal digits. Type: String Ancestors: <i>CompleteMultipartUploadResult</i>

## Special Errors

Error Code	Description	HTTP Status Code
<code>EntityTooSmall</code>	Your proposed upload is smaller than the minimum allowed object size. Each part must be at least 5 MB in size, except the last part.	400 Bad Request
<code>InvalidPart</code>	One or more of the specified parts could not be found. The part might not have been uploaded, or the specified entity tag might not have matched the part's entity tag.	400 Bad Request
<code>InvalidPartOrder</code>	The list of parts was not in ascending order. Parts list must be specified in order by part number.	400 Bad Request
<code>NoSuchUpload</code>	The specified multipart upload does not exist. The upload ID might be invalid, or the multipart upload might have been aborted or completed.	404 Not Found

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following Complete Multipart Upload request specifies three parts in the *CompleteMultipartUpload* element.

```
POST /example-object?uploadId=AAAsb2FkIElEIGZvciBlbHZpbmcncyWeeSltb3ZpZS5tMnRzIR
RwbG9hZA HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 391
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=

<CompleteMultipartUpload>
  <Part>
    <PartNumber>1</PartNumber>
    <ETag>"a54357aff0632cce46d942af68356b38"</ETag>
  </Part>
  <Part>
    <PartNumber>2</PartNumber>
    <ETag>"0c78aef83f66abc1fale8477f296d394"</ETag>
  </Part>
  <Part>
    <PartNumber>3</PartNumber>
    <ETag>"acbd18db4cc2f85cedef654fccc4a4d8"</ETag>
  </Part>
</CompleteMultipartUpload>
```

### Sample Response

The following response indicates that an object was successfully assembled.

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<CompleteMultipartUploadResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">

  <Location>http://Example-Bucket.s3.amazonaws.com/Example-Object</Location>
  <Bucket>Example-Bucket</Bucket>
  <Key>Example-Object</Key>
  <ETag>"3858f62230ac3c915f300c664312c11f-9"</ETag>
</CompleteMultipartUploadResult>
```

### Sample Response with Error Specified in Header

The following response indicates that an error occurred before the HTTP response header was sent.

```
HTTP/1.1 403 Forbidden
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
```



```
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 237
Connection: keep-alive
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<Error>
  <Code>AccessDenied</Code>
  <Message>Access Denied</Message>
  <RequestId>656c76696e6727732072657175657374</RequestId>
  <HostId>Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOFg==</HostId>
</Error>
```

### Sample Response with Error Specified in Body

The following response indicates that an error occurred after the HTTP response header was sent. Note that while the HTTP status code is 200 OK, the request actually failed as described in the *Error* element.

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOFg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Connection: close
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<Error>
  <Code>InternalError</Code>
  <Message>We encountered an internal error. Please try again.</Message>
  <RequestId>656c76696e6727732072657175657374</RequestId>
  <HostId>Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOFg==</HostId>
</Error>
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Parts \(p. 231\)](#)
- [List Multipart Uploads \(p. 81\)](#)

# Abort Multipart Upload

## Description

This operation aborts a multipart upload. After a multipart upload is aborted, no additional parts can be uploaded using that upload ID. The storage consumed by any previously uploaded parts will be freed. However, if any part uploads are currently in progress, those part uploads might or might not succeed. As a result, it might be necessary to abort a given multipart upload multiple times in order to completely free all storage consumed by all parts.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer Guide*.

## Requests

### Syntax

```
DELETE /ObjectName?uploadId=UploadId HTTP/1.1  
Host: BucketName.s3.amazonaws.com  
Date: Date  
Authorization: Signature
```

### Request Parameters

This operation does not use request parameters.

### Request Headers

This operation uses only Request Headers common to most requests. For more information, see [Common Request Headers](#) (p. 12).

### Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

This operation does not use response elements.

## Special Errors

Error Code	Description	HTTP Status Code	SOAP Fault Code Prefix
NoSuchUpload	The specified multipart upload does not exist. The upload ID might be invalid, or the multipart upload might have been aborted or completed.	404 Not Found	Client

For general information about Amazon S3 errors and a list of error codes, see [Error Responses \(p. 3\)](#).

## Examples

### Sample Request

The following request aborts a multipart upload identified by its upload ID.

```
DELETE /example-object?uploadId=VXBsb2FkIElEIGZvcjBlbHZpbmcncyBteS1tb3ZpZS5tMnRzIHVwbG9hZ HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf3/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

```
HTTP/1.1 204 OK
x-amz-id-2: Weag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 996c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 0
Connection: keep-alive
Server: AmazonS3
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [List Parts \(p. 231\)](#)
- [List Multipart Uploads \(p. 81\)](#)

# List Parts

## Description

This operation lists the parts that have been uploaded for a specific multipart upload.

This operation must include the upload ID, which you obtain by sending the initiate multipart upload request (see [Initiate Multipart Upload \(p. 210\)](#)). This request returns a maximum of 1,000 uploaded parts. The default number of parts returned is 1,000 parts. You can restrict the number of parts returned by specifying the `max-parts` request parameter. If your multipart upload consists of more than 1,000 parts, the response returns an `IsTruncated` field with the value of `true`, and a `NextPartNumberMarker` element. In subsequent List Parts requests you can include the `part-number-marker` query string parameter and set its value to the `NextPartNumberMarker` field value from the previous response.

For more information on multipart uploads, go to [Uploading Objects Using Multipart Upload](#) in the *Amazon S3 Developer Guide*.

For information on permissions required to use the multipart upload API, go to [Multipart Upload API and Permissions](#) in the *Amazon S3 Developer Guide*.

## Requests

### Syntax

```
GET /ObjectName?uploadId=UploadId HTTP/1.1
Host: BucketName.s3.amazonaws.com
Date: Date
Authorization: Signature
```

### Request Parameters

This implementation of GET uses the parameters in the following table to return a subset of the objects in a bucket.

Parameter	Description	Required
<i>uploadId</i>	Upload ID identifying the multipart upload whose parts are being listed. Type: String Default: None	Yes
<i>max-parts</i>	Sets the maximum number of parts to return in the response body. Type: String Default: 1,000	No
<i>part-number-marker</i>	Specifies the part after which listing should begin. Only parts with higher part numbers will be listed. Type: String Default: None	No

### Request Headers

This operation uses only Request Headers common to most requests. For more information, see [Common Request Headers \(p. 12\)](#).

## Request Elements

This operation does not use request elements.

## Responses

### Response Headers

This operation uses only response headers that are common to most responses. For more information, see [Common Response Headers](#) (p. 14).

### Response Elements

Name	Description
ListPartsResult	Container for the response. Children: <i>Bucket, Key, UploadId, Initiator, Owner, StorageClass, PartNumberMarker, NextPartNumberMarker, MaxParts, IsTruncated, Part</i> Type: Container
Bucket	Name of the bucket to which the multipart upload was initiated. Type: String Ancestor: <i>ListPartsResult</i>
Key	Object key for which the multipart upload was initiated. Type: String Ancestor: <i>ListPartsResult</i>
UploadId	Upload ID identifying the multipart upload whose parts are being listed. Type: String Ancestor: <i>ListPartsResult</i>
Initiator	Container element that identifies who initiated the multipart upload. If the initiator is an AWS account, this element provides the same information as the <i>Owner</i> element. If the initiator is an IAM User, then this element provides the user ARN and display name. Children: <i>ID, DisplayName</i> Type: Container Ancestor: <i>ListPartsResult</i>
ID	If the principal is an AWS account, it provides the Canonical User ID. If the principal is an IAM User, it provides a user ARN value. Type: String Ancestor: <i>Initiator</i>
DisplayName	Principal's name. Type: String Ancestor: <i>Initiator</i>

Name	Description
Owner	Container element that identifies the object owner, after the object is created. If multipart upload is initiated by an IAM user, this element provides the parent account ID and display name. Children: <i>ID</i> , <i>DisplayName</i> Type: Container Ancestor: <i>ListPartsResult</i>
StorageClass	Class of storage (STANDARD or REDUCED_REDUNDANCY) used to store the uploaded object. Type: String Ancestor: <i>ListPartsResult</i>
PartNumberMarker	Part number after which listing begins. Type: Integer Ancestor: <i>ListPartsResult</i>
NextPartNumberMarker	When a list is truncated, this element specifies the last part in the list, as well as the value to use for the <i>part-number-marker</i> request parameter in a subsequent request. Type: Integer Ancestor: <i>ListPartsResult</i>
MaxParts	Maximum number of parts that were allowed in the response. Type: Integer Ancestor: <i>ListPartsResult</i>
IsTruncated	Indicates whether the returned list of parts is truncated. A <i>true</i> value indicates that the list was truncated. A list can be truncated if the number of parts exceeds the limit returned in the <i>MaxParts</i> element. Type: Boolean Ancestor: <i>ListPartsResult</i>
Part	Container for elements related to a particular part. A response can contain zero or more <i>Part</i> elements. Children: <i>PartNumber</i> , <i>LastModified</i> , <i>ETag</i> , <i>Size</i> Type: String Ancestor: <i>ListPartsResult</i>
PartNumber	Part number identifying the part. Type: Integer Ancestor: <i>Part</i>
LastModified	Date and time at which the part was uploaded. Type: Date Ancestor: <i>Part</i>
ETag	Entity tag returned when the part was uploaded. Type: String Ancestor: <i>Part</i>

Name	Description
Size	Size of the uploaded part data. Type: Integer Ancestor: <i>Part</i>

## Examples

### Sample Request

Assume you have uploaded parts with sequential part numbers starting with 1. The following List Parts request specifies *max-parts* and *part-number-marker* query parameters. The request lists the first two parts that follow part number 1, that is, you will get parts 2 and 3 in the response. If more parts exist, the result is a truncated result and therefore the response will return an *IsTruncated* element with the value *true*. The response will also return the *NextPartNumberMarker* element with the value 3, which should be used for the value of the *part-number-marker* request query string parameter in the next List Parts request.

```
GET /example-object?uploadId=XXBsb2FkIElEIGZvciblbHZpbmcncyVcdS1tb3ZpZS5tMnRzEEEwbG9hZA&max-parts=2&part-number-marker=1 HTTP/1.1
Host: example-bucket.s3.amazonaws.com
Date: Mon, 1 Nov 2010 20:34:56 GMT
Authorization: AWS AKIAIOSFODNN7EXAMPLE:0RQf4/cRonhpaBX5sCYVf1bNRuU=
```

### Sample Response

The following is a sample response.

```
HTTP/1.1 200 OK
x-amz-id-2: Uuag1LuByRx9e6j5Onimru9pO4ZVKnJ2Qz7/C1NPcfTWAtRPfTaOfg==
x-amz-request-id: 656c76696e6727732072657175657374
Date: Mon, 1 Nov 2010 20:34:56 GMT
Content-Length: 985
Connection: keep-alive
Server: AmazonS3

<?xml version="1.0" encoding="UTF-8"?>
<ListPartsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Bucket>example-bucket</Bucket>
  <Key>example-object</Key>
  <UploadId>XXBsb2FkIElEIGZvciblbHZpbmcncyVcdS1tb3ZpZS5tMnRzEEEwbG9hZA</UploadId>

  <Initiator>
    <ID>arn:aws:iam::111122223333:user/some-user-11116a31-17b5-4fb7-9df5-b288870f11xx</ID>
    <DisplayName>umat-user-11116a31-17b5-4fb7-9df5-b288870f11xx</DisplayName>
  </Initiator>
  <Owner>
    <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>
    <DisplayName>someName</DisplayName>
  </Owner>
  <StorageClass>STANDARD</StorageClass>
  <PartNumberMarker>1</PartNumberMarker>
```

```
<NextPartNumberMarker>3</NextPartNumberMarker>
<MaxParts>2</MaxParts>
<IsTruncated>true</IsTruncated>
<Part>
  <PartNumber>2</PartNumber>
  <LastModified>2010-11-10T20:48:34.000Z</LastModified>
  <ETag>"7778aef83f66abc1fale8477f296d394"</ETag>
  <Size>10485760</Size>
</Part>
<Part>
  <PartNumber>3</PartNumber>
  <LastModified>2010-11-10T20:48:33.000Z</LastModified>
  <ETag>"aaaa18db4cc2f85cedef654fccc4a4x8"</ETag>
  <Size>10485760</Size>
</Part>
</ListPartsResult>
```

## Related Actions

- [Initiate Multipart Upload \(p. 210\)](#)
- [Upload Part \(p. 216\)](#)
- [Complete Multipart Upload \(p. 224\)](#)
- [Abort Multipart Upload \(p. 229\)](#)
- [List Multipart Uploads \(p. 81\)](#)



# SOAP API

---

## Topics

- [Operations on the Service \(p. 236\)](#)
- [Operations on Buckets \(p. 238\)](#)
- [Operations on Objects \(p. 246\)](#)

This section describes the SOAP API with respect to service, bucket, and object operations.

### Note

SOAP requests, both authenticated and anonymous, must be sent to Amazon S3 using SSL. Amazon S3 returns an error when you send a SOAP request over HTTP.

## Operations on the Service

### Topics

- [ListAllMyBuckets \(p. 236\)](#)

This section describes operations you can perform on the Amazon S3 service.

## ListAllMyBuckets

The `ListAllMyBuckets` operation returns a list of all buckets owned by the sender of the request.

## Example

### *Sample Request*

```
<ListAllMyBuckets xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</ListAllMyBuckets>
```

### *Sample Response*

```
<ListAllMyBucketsResult xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <Owner>
    <ID>bcaf1ffd86f41161ca5fb16fd081034f</ID>
    <DisplayName>webfile</DisplayName>
  </Owner>
  <Buckets>
    <Bucket>
      <Name>quotes</Name>
      <CreationDate>2006-02-03T16:45:09.000Z</CreationDate>
    </Bucket>
    <Bucket>
      <Name>samples</Name>
      <CreationDate>2006-02-03T16:41:58.000Z</CreationDate>
    </Bucket>
  </Buckets>
</ListAllMyBucketsResult>
```

## Response Body

- *Owner*:

This provides information that Amazon S3 uses to represent your identity for purposes of authentication and access control. ID is a unique and permanent identifier for the developer who made the request. DisplayName is a human-readable name representing the developer who made the request. It is not unique, and might change over time. We recommend that you match your DisplayName to your Forum name.

- *Name*:

The name of a bucket. Note that if one of your buckets was recently deleted, the name of the deleted bucket might still be present in this list for a period of time.

- *CreationDate*:

The time that the bucket was created.

## Access Control

You must authenticate with a valid AWS Access Key ID. Anonymous requests are never allowed to list buckets, and you can only list buckets for which you are the owner.

# Operations on Buckets

## Topics

- [CreateBucket](#) (p. 238)
- [DeleteBucket](#) (p. 239)
- [ListBucket](#) (p. 239)
- [GetBucketAccessControlPolicy](#) (p. 242)
- [SetBucketAccessControlPolicy](#) (p. 243)
- [GetBucketLoggingStatus](#) (p. 244)
- [SetBucketLoggingStatus](#) (p. 245)

This section describes operations you can perform on Amazon S3 buckets.

## CreateBucket

The `CreateBucket` operation creates a bucket. Not every string is an acceptable bucket name. For information on bucket naming restrictions, see [Working with Amazon S3 Buckets](#).

### Note

To determine whether a bucket name exists, use `ListBucket` and set `MaxKeys` to 0. A `NoSuchBucket` response indicates that the bucket is available, an `AccessDenied` response indicates that someone else owns the bucket, and a `Success` response indicates that you own the bucket or have permission to access it.

### Example Create a bucket named "quotes".

*Sample Request*

```
<CreateBucket xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</CreateBucket>
```

*Sample Response*

```
<CreateBucketResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <CreateBucketResponse>
    <Bucket>quotes</Bucket>
  </CreateBucketResponse>
</CreateBucketResponse>
```

## Elements

- *Bucket*: The name of the bucket you are trying to create.
- *AccessControlList*: The access control list for the new bucket. This element is optional. If not provided, the bucket is created with an access policy that give the requester `FULL_CONTROL` access.

## Access Control

You must authenticate with a valid AWS Access Key ID. Anonymous requests are never allowed to create buckets.

## Related Resources

- [ListBucket](#) (p. 239)

## DeleteBucket

The `DeleteBucket` operation deletes a bucket. All objects in the bucket must be deleted before the bucket itself can be deleted.

### Example

This example deletes the "quotes" bucket.

*Sample Request*

```
<DeleteBucket xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <AWSAccessKeyId> AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</DeleteBucket>
```

*Sample Response*

```
<DeleteBucketResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <DeleteBucketResponse>
    <Code>204</Code>
    <Description>No Content</Description>
  </DeleteBucketResponse>
</DeleteBucketResponse>
```

## Elements

- *Bucket*: The name of the bucket you want to delete.

## Access Control

Only the owner of a bucket is allowed to delete it, regardless the access control policy on the bucket.

## ListBucket

The `ListBucket` operation returns information about some of the items in the bucket.

For a general introduction to the list operation, see the [Listing Object Keys](#).

## Requests

This example lists up to 1000 keys in the "quotes" bucket that have the prefix "notes."

### Syntax

```
<ListBucket xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Prefix>notes</Prefix>
  <Delimiter></Delimiter>
  <MaxKeys>1000</MaxKeys>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</ListBucket>
```

### Parameters

Name	Description	Required
<i>prefix</i>	Limits the response to keys which begin with the indicated prefix. You can use prefixes to separate a bucket into different sets of keys in a way similar to how a file system uses folders. Type: String Default: None	No
<i>marker</i>	Indicates where in the bucket to begin listing. The list will only include keys that occur lexicographically after marker. This is convenient for pagination: To get the next page of results use the last key of the current page as the marker. Type: String Default: None	No
<i>max-keys</i>	The maximum number of keys you'd like to see in the response body. The server might return fewer than this many keys, but will not return more. Type: String Default: None	No
<i>delimiter</i>	Causes keys that contain the same string between the prefix and the first occurrence of the delimiter to be rolled up into a single result element in the CommonPrefixes collection. These rolled-up keys are not returned elsewhere in the response. Type: String Default: None	No

## Success Response

This response assumes the bucket contains the following keys:

```
notes/todos.txt
notes/2005-05-23/customer_mtg_notes.txt
notes/2005-05-23/phone_notes.txt
notes/2005-05-28/sales_notes.txt
```

## Syntax

```
<?xml version="1.0" encoding="UTF-8"?>
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01/">
  <Name>backups</Name>
  <Prefix>notes/</Prefix>
  <MaxKeys>1000</MaxKeys>
  <Delimiter>/</Delimiter>
  <IsTruncated>>false</IsTruncated>
  <Contents>
    <Key>notes/todos.txt</Key>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
    <Size>5126</Size>
    <StorageClass>STANDARD</StorageClass>
    <Owner>
      <ID>75aa57f09aa0c8caeab4f8c24e99d10f8e7faeebf76c078efc7c6caea54ba06a</ID>

      <DisplayName>webfile</DisplayName>
    </Owner>
    <StorageClass>STANDARD</StorageClass>
  </Contents>
  <CommonPrefixes>
    <Prefix>notes/2005-05-23/</Prefix>
  </CommonPrefixes>
  <CommonPrefixes>
    <Prefix>notes/2005-05-28/</Prefix>
  </CommonPrefixes>
</ListBucketResult>
```

As you can see, many of the fields in the response echo the request parameters. *IsTruncated*, *Contents*, and *CommonPrefixes* are the only response elements that can contain new information.

## Response Elements

Name	Description
<i>Contents</i>	Metadata about each object returned. Type: XML metadata Ancestor: ListBucketResult
<i>CommonPrefixes</i>	A response can contain <i>CommonPrefixes</i> only if you specify a <i>delimiter</i> . When you do, <i>CommonPrefixes</i> contains all (if there are any) keys between <i>Prefix</i> and the next occurrence of the string specified by <i>delimiter</i> . In effect, <i>CommonPrefixes</i> lists keys that act like subdirectories in the directory specified by <i>Prefix</i> . For example, if <i>prefix</i> is <i>notes/</i> and <i>delimiter</i> is a slash (/), in <i>notes/summer/july</i> , the common prefix is <i>notes/summer/</i> . Type: String Ancestor: ListBucketResult

Name	Description
<i>Delimiter</i>	Causes keys that contain the same string between the prefix and the first occurrence of the delimiter to be rolled up into a single result element in the CommonPrefixes collection. These rolled-up keys are not returned elsewhere in the response. Type: String Ancestor: ListBucketResult
<i>IsTruncated</i>	Specifies whether (true) or not (false) all of the results were returned. All of the results may not be returned if the number of results exceeds that specified by <i>MaxKeys</i> . Type: String Ancestor: boolean
<i>Marker</i>	Indicates where in the bucket to begin listing. Type: String Ancestor: ListBucketResult
<i>MaxKeys</i>	The maximum number of keys returned in the response body. Type: String Ancestor: ListBucketResult
<i>Name</i>	Name of the bucket. Type: String Ancestor: ListBucketResult
<i>Prefix</i>	Keys that begin with the indicated prefix. Type: String Ancestor: ListBucketResult

## Response Body

For information about the list response, see [Listing Keys Response](#).

## Access Control

To list the keys of a bucket you need to have been granted `READ` access on the bucket.

## GetBucketAccessControlPolicy

The `GetBucketAccessControlPolicy` operation fetches the access control policy for a bucket.

## Example

This example retrieves the access control policy for the "quotes" bucket.

*Sample Request*

```
<GetBucketAccessControlPolicy xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetBucketAccessControlPolicy>
```

*Sample Response*

```
<AccessControlPolicy>
  <Owner>
    <ID>a9a7b886d6fd2441bf9b1c61be666e9</ID>
    <DisplayName>chriscustomer</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b886d6fd2441bf9b1c61be666e9</ID>
        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
    <Grant>
      <Grantee xsi:type="Group">
        <URI>http://acs.amazonaws.com/groups/global/AllUsers</URI>
      </Grantee>
      <Permission>READ</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Response Body

The response contains the access control policy for the bucket. For an explanation of this response, see [SOAP Access Policy](#).

## Access Control

You must have `READ_ACP` rights to the bucket in order to retrieve the access control policy for a bucket.

## SetBucketAccessControlPolicy

The `SetBucketAccessControlPolicy` operation sets the Access Control Policy for an existing bucket. If successful, the previous Access Control Policy for the bucket is entirely replaced with the specified Access Control Policy.



## Example

Give the specified user (usually the owner) `FULL_CONTROL` access to the "quotes" bucket.

*Sample Request*

```
<SetBucketAccessControlPolicy xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b8863000e241bf9b1c61be666e9</ID>
        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</SetBucketAccessControlPolicy >
```

*Sample Response*

```
<GetBucketAccessControlPolicyResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <GetBucketAccessControlPolicyResponse>
    <Code>200</Code>
    <Description>OK</Description>
  </GetBucketAccessControlPolicyResponse>
</GetBucketAccessControlPolicyResponse>
```

## Access Control

You must have `WRITE_ACP` rights to the bucket in order to set the access control policy for a bucket.

## GetBucketLoggingStatus

### Important

This document describes Beta functionality that is subject to change in future releases.

The `GetBucketLoggingStatus` retrieves the logging status for an existing bucket.

For a general introduction to this feature, see [Server Logs](#) . For information about the response document, see [Logging API](#) .

## Example

### Sample Request

```
<?xml version="1.0" encoding="utf-8"?>
  <soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
      <GetBucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01">

        <Bucket>mybucket</Bucket>
        <AWSAccessKeyId>YOUR_AWS_ACCESS_KEY_ID</AWSAccessKeyId>
        <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
        <Signature>YOUR_SIGNATURE_HERE</Signature>
      </GetBucketLoggingStatus>
    </soap:Body>
  </soap:Envelope>
```

### Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
  <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" >
    <soapenv:Header>
    </soapenv:Header>
    <soapenv:Body>
      <GetBucketLoggingStatusResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
        <GetBucketLoggingStatusResponse>
          <LoggingEnabled>
            <TargetBucket>mylogs</TargetBucket>
            <TargetPrefix>mybucket-access_log</TargetPrefix>
          </LoggingEnabled>
        </GetBucketLoggingStatusResponse>
      </GetBucketLoggingStatusResponse>
    </soapenv:Body>
  </soapenv:Envelope>
```

## Access Control

Only the owner of a bucket is permitted to invoke this operation.

## SetBucketLoggingStatus

### Important

This document describes Beta functionality that is subject to change in future releases.

The `SetBucketLoggingStatus` operation updates the logging status for an existing bucket.

For a general introduction to this feature, see [Server Logs](#) . For information about the response document, see [Logging API](#) .

## Example

This sample request enables server access logging for the 'mybucket' bucket, and configures the logs to be delivered to 'mylogs' under prefix 'access\_log-'

*Sample Request*

```
<?xml version="1.0" encoding="utf-8"?>
  <soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <soap:Body>
      <SetBucketLoggingStatus xmlns="http://doc.s3.amazonaws.com/2006-03-01">
        <Bucket>myBucket</Bucket>
        <AWSAccessKeyId>YOUR_AWS_ACCESS_KEY_ID</AWSAccessKeyId>
        <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
        <Signature>YOUR_SIGNATURE_HERE</Signature>
        <BucketLoggingStatus>
          <LoggingEnabled>
            <TargetBucket>mylogs</TargetBucket>
            <TargetPrefix>mybucket-access_log-</TargetPrefix>
          </LoggingEnabled>
        </BucketLoggingStatus>
      </SetBucketLoggingStatus>
    </soap:Body>
  </soap:Envelope>
```

*Sample Response*

```
<?xml version="1.0" encoding="utf-8"?>
  <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <soapenv:Header>
    </soapenv:Header>
    <soapenv:Body>
      <SetBucketLoggingStatusResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01"/>
    </soapenv:Body>
  </soapenv:Envelope>
```

## Access Control

Only the owner of a bucket is permitted to invoke this operation.

# Operations on Objects

### Topics

- [PutObjectInline \(p. 247\)](#)
- [PutObject \(p. 249\)](#)
- [CopyObject \(p. 252\)](#)

- [GetObject](#) (p. 256)
- [GetObjectExtended](#) (p. 261)
- [DeleteObject](#) (p. 261)
- [GetObjectAccessControlPolicy](#) (p. 262)
- [SetObjectAccessControlPolicy](#) (p. 263)

This section describes operations you can perform on Amazon S3 objects.

## PutObjectInline

The `PutObjectInline` operation adds an object to a bucket. The data for the object is provided in the body of the SOAP message.

If an object already exists in a bucket, the new object will overwrite it because Amazon S3 stores the last write request. However, Amazon S3 is a distributed system. If Amazon S3 receives multiple write requests for the same object nearly simultaneously, all of the objects might be stored, even though only one wins in the end. Amazon S3 does not provide object locking; if you need this, make sure to build it into your application layer.

To ensure an object is not corrupted over the network, you can calculate the MD5 of an object, PUT it to Amazon S3, and compare the returned Etag to the calculated MD5 value.

`PutObjectInline` is not suitable for use with large objects. The system limits this operation to working with objects 1MB or smaller. `PutObjectInline` will fail with the *InlineDataTooLargeError* status code if the `Data` parameter encodes an object larger than 1MB. To upload large objects, consider using the non-inline `PutObject` API, or the REST API instead.

## Example

This example writes some text and metadata into the "Nelson" object in the "quotes" bucket, give a user (usually the owner) `FULL_CONTROL` access to the object, and make the object readable by anonymous parties.

*Sample Request*

```
<PutObjectInline xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <Metadata>
    <Name>Content-Type</Name>
    <Value>text/plain</Value>
  </Metadata>
  <Metadata>
    <Name>family</Name>
    <Value>Muntz</Value>
  </Metadata>
  <Data>aGEtaGE=</Data>
  <ContentLength>5</ContentLength>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b886d6fde241bf9b1c61be666e9</ID>
        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
    <Grant>
      <Grantee xsi:type="Group">
        <URI>http://acs.amazonaws.com/groups/global/AllUsers</URI>
      </Grantee>
      <Permission>READ</Permission>
    </Grant>
  </AccessControlList>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</PutObjectInline>
```

*Sample Response*

```
<PutObjectInlineResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <PutObjectInlineResponse>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
    <LastModified>2006-01-01T12:00:00.000Z</lastModified>
  </PutObjectInlineResponse>
</PutObjectInlineResponse>
```

## Elements

- *Bucket*: The bucket in which to add the object.
- *Key*: The key to assign to the object.

- *Metadata*: You can provide name-value metadata pairs in the metadata element. These will be stored with the object.
- *Data*: The base 64 encoded form of the data.
- *ContentLength*: The length of the data in bytes.
- *AccessControlList*: An Access Control List for the resource. This element is optional. If omitted, the requester is given `FULL_CONTROL` access to the object. If the object already exists, the preexisting access control policy is replaced.

## Responses

<listitem>*ETag*: The entity tag is an MD5 hash of the object that you can use to do conditional fetches of the object using `GetObjectExtended`. The ETag only reflects changes to the contents of an object, not its metadata.</listitem>

- *LastModified*: The Amazon S3 timestamp for the saved object.

## Access Control

You must have `WRITE` access to the bucket in order to put objects into the bucket.

## Related Resources

- [PutObject](#) (p. 249)
- [CopyObject](#) (p. 252)

## PutObject

The `PutObject` operation adds an object to a bucket. The data for the object is attached as a DIME attachment.

To ensure an object is not corrupted over the network, you can calculate the MD5 of an object, PUT it to Amazon S3, and compare the returned Etag to the calculated MD5 value.

If an object already exists in a bucket, the new object will overwrite it because Amazon S3 stores the last write request. However, Amazon S3 is a distributed system. If Amazon S3 receives multiple write requests for the same object nearly simultaneously, all of the objects might be stored, even though only one wins in the end. Amazon S3 does not provide object locking; if you need this, make sure to build it into your application layer.

## Example

This example puts some data and metadata in the "Nelson" object of the "quotes" bucket, give a user (usually the owner) `FULL_CONTROL` access to the object, and make the object readable by anonymous parties. In this sample, the actual attachment is not shown.

*Sample Request*

```
<PutObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <Metadata>
    <Name>Content-Type</Name>
    <Value>text/plain</Value>
  </Metadata>
  <Metadata>
    <Name>family</Name>
    <Value>Muntz</Value>
  </Metadata>
  <ContentLength>5</ContentLength>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b886d6241bf9b1c61be666e9</ID>
        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
    <Grant>
      <Grantee xsi:type="Group">
        <URI>http://acs.amazonaws.com/groups/global/AllUsers<URI>
      </Grantee>
      <Permission>READ</Permission>
    </Grant>
  </AccessControlList>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2007-05-11T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</PutObject>
```

*Sample Response*

```
<PutObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <PutObjectResponse>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
    <LastModified>2006-03-01T12:00:00.183Z</LastModified>
  </PutObjectResponse>
</PutObjectResponse>
```

## Elements

- *Bucket*: The bucket in which to add the object.
- *Key*: The key to assign to the object.

- *Metadata*: You can provide name-value metadata pairs in the metadata element. These will be stored with the object.
- *ContentLength*: The length of the data in bytes.
- *AccessControlList*: An Access Control List for the resource. This element is optional. If omitted, the requester is given `FULL_CONTROL` access to the object. If the object already exists, the preexisting Access Control Policy is replaced.

## Responses

- *ETag*: The entity tag is an MD5 hash of the object that you can use to do conditional fetches of the object using `GetObjectExtended`. The ETag only reflects changes to the contents of an object, not its metadata.
- *LastModified*: The Amazon S3 timestamp for the saved object.

## Access Control

To put objects into a bucket, you must have `WRITE` access to the bucket.

## Related Resources

- [CopyObject](#) (p. 252)



# CopyObject

## Description

The `CopyObject` operation creates a copy of an object when you specify the key and bucket of a source object and the key and bucket of a target destination.

When copying an object, you can preserve all metadata (default) or specify new metadata. However, the ACL is not preserved and is set to `private` for the user making the request. To override the default ACL setting, specify a new ACL when generating a copy request. For more information, see [Amazon S3 ACLs](#).

All copy requests must be authenticated. Additionally, you must have `read` access to the source object and `write` access to the destination bucket. For more information, see [Using Auth Access](#).

To only copy an object under certain conditions, such as whether the Etag matches or whether the object was modified before or after a specified date, use the request parameters

`CopySourceIfUnmodifiedSince`, `CopyIfUnmodifiedSince`, `CopySourceIfMatch`, or `CopySourceIfNoneMatch`.

### Note

You might need to configure the SOAP stack socket timeout for copying large objects.

## Request Syntax

```
<CopyObject xmlns="http://bucket_name.s3.amazonaws.com/2006-03-01">
  <SourceBucket>source_bucket</SourceBucket>
  <SourceObject>source_object</SourceObject>
  <DestinationBucket>destination_bucket</DestinationBucket>
  <DestinationObject>destination_object</DestinationObject>
  <MetadataDirective>{REPLACE | COPY}</MetadataDirective>
  <Metadata>
    <Name>metadata_name</Name>
    <Value>metadata_value</Value>
  </Metadata>
  ...
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="user_type">
        <ID>user_id</ID>
        <DisplayName>display_name</DisplayName>
      </Grantee>
      <Permission>permission</Permission>
    </Grant>
    ...
  </AccessControlList>
  <CopySourceIfMatch>etag</CopySourceIfMatch>
  <CopySourceIfNoneMatch>etag</CopySourceIfNoneMatch>
  <CopySourceIfModifiedSince>date_time</CopySourceIfModifiedSince>
  <CopySourceIfUnmodifiedSince>date_time</CopySourceIfUnmodifiedSince>
  <AWSAccessKeyId>AWSAccessKeyId</AWSAccessKeyId>
  <Timestamp>TimeStamp</Timestamp>
  <Signature>Signature</Signature>
</CopyObject>
```

## Request Parameters

Name	Description	Required
<i>SourceBucket</i>	The name of the source bucket. Type: String Default: None Constraints: A valid source bucket.	Yes
<i>SourceKey</i>	The key name of the source object. Type: String Default: None Constraints: The key for a valid source object to which you have READ access.	Yes
<i>DestinationBucket</i>	The name of the destination bucket. Type: String Default: None Constraints: You must have WRITE access to the destination bucket.	Yes
<i>DestinationKey</i>	The key of the destination object. Type: String Default: None Constraints: You must have WRITE access to the destination bucket.	Yes
<i>MetadataDirective</i>	Specifies whether the metadata is copied from the source object or replaced with metadata provided in the request. Type: String Default: COPY Valid values: COPY   REPLACE Constraints: Values other than COPY or REPLACE will result in an immediate error. You cannot copy an object to itself unless the MetadataDirective header is specified and its value set to REPLACE.	No
<i>Metadata</i>	Specifies metadata name-value pairs to set for the object.If MetadataDirective is set to COPY, all metadata is ignored. Type: String Default: None Constraints: None.	No
<i>AccessControlList</i>	Grants access to users by e-mail addresses or canonical user ID. Type: String Default: None Constraints: None	No

Name	Description	Required
<i>CopySourceIfMatch</i>	Copies the object if its entity tag (ETag) matches the specified tag; otherwise return a PreconditionFailed. Type: String Default: None Constraints: None. If the Etag does not match, the object is not copied.	No
<i>CopySourceIfNoneMatch</i>	Copies the object if its entity tag (ETag) is different than the specified Etag; otherwise returns an error. Type: String Default: None Constraints: None.	No
<i>CopySourceIfUnmodifiedSince</i>	Copies the object if it hasn't been modified since the specified time; otherwise returns a PreconditionFailed. Type: dateTime Default: None	No
<i>CopySourceIfModifiedSince</i>	Copies the object if it has been modified since the specified time; otherwise returns an error. Type: dateTime Default: None	No

## Response Syntax

```
<CopyObjectResponse xmlns="http://bucket_name.s3.amazonaws.com/2006-03-01">
  <CopyObjectResponse>
    <ETag>"etag"</ETag>
    <LastModified>timestamp</LastModified>
  </CopyObjectResponse>
</CopyObjectResponse>
```

## Response Elements

Name	Description
<i>Etag</i>	Returns the etag of the new object. The ETag only reflects changes to the contents of an object, not its metadata. Type: String Ancestor: CopyObjectResult
<i>LastModified</i>	Returns the date the object was last modified. Type: String Ancestor: CopyObjectResult

For information about general response elements, see [Using REST Error Response Headers](#) .

## Special Errors

There are no special errors for this operation. For information about general Amazon S3 errors, see [List of Error Codes](#) (p. 3).

## Examples

This example copies the `flotsam` object from the `pacific` bucket to the `jetsam` object of the `atlantic` bucket, preserving its metadata.

### Sample Request

```
<CopyObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <SourceBucket>pacific</SourceBucket>
  <SourceObject>flotsam</SourceObject>
  <DestinationBucket>atlantic</DestinationBucket>
  <DestinationObject>jetsam</DestinationObject>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2008-02-18T13:54:10.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbq7RrtSFmw=</Signature>
</CopyObject>
```

### Sample Response

```
<CopyObjectResponse xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <CopyObjectResponse>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
    <LastModified>2008-02-18T13:54:10.183Z</LastModified>
  </CopyObjectResponse>
</CopyObjectResponse>
```

This example copies the "tweedledee" object from the `wonderland` bucket to the "tweedledum" object of the `wonderland` bucket, replacing its metadata.

### Sample Request

```
<CopyObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <SourceBucket>wonderland</SourceBucket>
  <SourceObject>tweedledee</SourceObject>
  <DestinationBucket>wonderland</DestinationBucket>
  <DestinationObject>tweedledum</DestinationObject>
  <MetadataDirective>REPLACE</MetadataDirective>
  <Metadata>
    <Name>Content-Type</Name>
    <Value>text/plain</Value>
  </Metadata>
  <Metadata>
    <Name>relationship</Name>
    <Value>twins</Value>
  </Metadata>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2008-02-18T13:54:10.183Z</Timestamp>
```

```
<Signature>Iuyz3d3P0aTou39dz bq7RrtSFmw=</Signature>
</CopyObject>
```

## Sample Response

```
<CopyObjectResponse xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <CopyObjectResponse>
    <ETag>"828ef3fd fa96f00ad9f27c383fc9ac7f"</ETag>
    <LastModified>2008-02-18T13:54:10.183Z</LastModified>
  </CopyObjectResponse>
</CopyObjectResponse>
```

## Related Resources

- [PutObject](#) (p. 249)
- [PutObjectInline](#) (p. 247)

## GetObject

The `GetObject` operation returns the latest version of an object. If you try to `GetObject` an object that has a Delete Marker as its latest version, S3 returns a 404 error. You cannot use the SOAP API to retrieve a specified version of an object. To do that, use the REST API. For more information, see [Versioning](#). For more options, use the [GetObjectExtended](#) (p. 261) operation.

## Example

This example gets the "Nelson" object from the "quotes" bucket.

*Sample Request*

```
<GetObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <GetMetadata>true</GetMetadata>
  <GetData>true</GetData>
  <InlineData>true</InlineData>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetObject>
```

*Sample Response*

```
<GetObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <GetObjectResponse>
    <Status>
      <Code>200</Code>
      <Description>OK</Description>
    </Status>
    <Metadata>
      <Name>Content-Type</Name>
      <Value>text/plain</Value>
    </Metadata>
    <Metadata>
      <Name>family</Name>
      <Value>Muntz</Value>
    </Metadata>
    <Data>aGEtaGE=</Data>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
  </GetObjectResponse>
</GetObjectResponse>
```

## Elements

- *Bucket*: The bucket from which to retrieve the object.
- *Key*: The key that identifies the object.
- *GetMetadata*: The metadata is returned with the object if this is true.
- *GetData*: The object data is returned if this is true.
- *InlineData*: If this is true, then the data is returned, base 64-encoded, as part of the SOAP body of the response. If false, then the data is returned as a SOAP attachment. The InlineData option is not suitable for use with large objects. The system limits this operation to working with 1MB of data or less. A GetObject request with the InlineData flag set will fail with the *InlineDataTooLargeError* status code if the resulting Data parameter would have encoded more than 1MB. To download large objects, consider calling GetObject without setting the InlineData flag, or use the REST API instead.

## Returned Elements

- *Metadata*: The name-value paired metadata stored with the object.
- *Data*: If *InlineData* was true in the request, this contains the base 64 encoded object data.
- *LastModified*: The time that the object was stored in Amazon S3.
- *ETag*: The object's entity tag. This is a hash of the object that can be used to do conditional gets. The ETag only reflects changes to the contents of an object, not its metadata.

## Access Control

You can read an object only if you have been granted `READ` access to the object.

## SOAP Chunked and Resumable Downloads

To provide `GET` flexibility, Amazon S3 supports chunked and resumable downloads.

Select from the following:

- For large object downloads, you might want to break them into smaller chunks. For more information, see [Range GETs \(p. 258\)](#)
- For `GET` operations that fail, you can design your application to download the remainder instead of the entire file. For more information, see [REST GET Error Recovery \(p. 261\)](#)

## Range GETs

For some clients, you might want to break large downloads into smaller downloads. To break a `GET` into smaller units, use `Range`.

Before you can break a `GET` into smaller units, you must determine its size. For example, the following request gets the size of the `bigfile` object.

```
<ListBucket xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>bigbucket</Bucket>
  <Prefix>bigfile</Prefix>
  <MaxKeys>1</MaxKeys>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</ListBucket>
```

Amazon S3 returns the following response.

```
<ListBucketResult xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <Name>quotes</Name>
  <Prefix>N</Prefix>
  <MaxKeys>1</MaxKeys>
  <IsTruncated>>false</IsTruncated>
  <Contents>
    <Key>bigfile</Key>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>"828ef3fd96f00ad9f27c383fc9ac7f"</ETag>
    <Size>2023276</Size>
    <StorageClass>STANDARD</StorageClass>
```

```
<Owner>
  <ID>bca1fffd86f41161ca5fb16fd081034f</ID>
  <DisplayName>bigfile</DisplayName>
</Owner>
</Contents>
</ListBucketResult>
```

Following is a request that downloads the first megabyte from the bigfile object.

```
<GetObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>bigbucket</Bucket>
  <Key>bigfile</Key>
  <GetMetadata>true</GetMetadata>
  <GetData>true</GetData>
  <InlineData>true</InlineData>
  <ByteRangeStart>0</ByteRangeStart>
  <ByteRangeEnd>1048576</ByteRangeEnd>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetObject>
```

Amazon S3 returns the first megabyte of the file and the Etag of the file.

```
<GetObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <GetObjectResponse>
    <Status>
      <Code>200</Code>
      <Description>OK</Description>
    </Status>
    <Metadata>
      <Name>Content-Type</Name>
      <Value>text/plain</Value>
    </Metadata>
    <Metadata>
      <Name>family</Name>
      <Value>Muntz</Value>
    </Metadata>
    <Data>--first megabyte of bigfile--</Data>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
  </GetObjectResponse>
</GetObjectResponse>
```

To ensure the file did not change since the previous portion was downloaded, specify the `IfMatch` element. Although the `IfMatch` element is not required, it is recommended for content that is likely to change.

The following is a request that gets the remainder of the file, using the `IfMatch` request header.

```
<GetObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>bigbucket</Bucket>
  <Key>bigfile</Key>
  <GetMetadata>true</GetMetadata>
  <GetData>true</GetData>
  <InlineData>true</InlineData>
```



```
<ByteRangeStart>10485761</ByteRangeStart>
<ByteRangeEnd>2023276</ByteRangeEnd>
<IfMatch>"828ef3fd9a96f00ad9f27c383fc9ac7f"</IfMatch>
<AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
<Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
<Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetObject>
```

Amazon S3 returns the following response and the remainder of the file.

```
<GetObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <GetObjectResponse>
    <Status>
      <Code>200</Code>
      <Description>OK</Description>
    </Status>
    <Metadata>
      <Name>Content-Type</Name>
      <Value>text/plain</Value>
    </Metadata>
    <Metadata>
      <Name>family</Name>
      <Value>>Muntz</Value>
    </Metadata>
    <Data>--remainder of bigfile--</Data>
    <LastModified>2006-01-01T12:00:00.000Z</LastModified>
    <ETag>"828ef3fd9a96f00ad9f27c383fc9ac7f"</ETag>
  </GetObjectResponse>
</GetObjectResponse>
```

## Versioned GetObject

The following request returns the specified version of the object in the bucket.

```
<GetObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <GetMetadata>true</GetMetadata>
  <GetData>true</GetData>
  <InlineData>true</InlineData>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetObject>
```

## Sample Response

```
<GetObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <GetObjectResponse>
    <Status>
      <Code>200</Code>
      <Description>OK</Description>
    </Status>
    <Metadata>
      <Name>Content-Type</Name>
```

```
<Value>text/plain</Value>
</Metadata>
<Metadata>
<Name>family</Name>
<Value>Muntz</Value>
</Metadata>
<Data>aGETaGE=</Data>
<LastModified>2006-01-01T12:00:00.000Z</LastModified>
<ETag>"828ef3fdfa96f00ad9f27c383fc9ac7f"</ETag>
</GetObjectResponse>
</GetObjectResponse>
```

## REST GET Error Recovery

If an object GET fails, you can get the rest of the file by specifying the range to download. To do so, you must get the size of the object using `ListBucket` and perform a range GET on the remainder of the file. For more information, see [GetObjectExtended](#) (p. 261).

## Related Resources

[Operations on Objects](#) (p. 246)

# GetObjectExtended

`GetObjectExtended` is exactly like [GetObject](#) (p. 256), except that it supports the following additional elements that can be used to accomplish much of the same functionality provided by HTTP GET headers (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html>).

`GetObjectExtended` supports the following elements in addition to those supported by `GetObject`:

- *ByteRangeStart*, *ByteRangeEnd*: These elements specify that only a portion of the object data should be retrieved. They follow the behavior of the HTTP byte ranges (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.35>).
- *IfModifiedSince*: Return the object only if the object's timestamp is later than the specified timestamp. (<http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.25>)
- *IfUnmodifiedSince*: Return the object only if the object's timestamp is earlier than or equal to the specified timestamp. (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.28>)
- *IfMatch*: Return the object only if its ETag matches the supplied tag(s). (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.24>)
- *IfNoneMatch*: Return the object only if its ETag does not match the supplied tag(s). (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.26>)
- *ReturnCompleteObjectOnConditionFailure*: `ReturnCompleteObjectOnConditionFailure`: If true, then if the request includes a range element and one or both of `IfUnmodifiedSince`/`IfMatch` elements, and the condition fails, return the entire object rather than a fault. This enables the If-Range functionality (go to <http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.27>).

## DeleteObject

The `DeleteObject` operation removes the specified object from Amazon S3. Once deleted, there is no method to restore or undelete an object.

### Note

If you delete an object that does not exist, Amazon S3 will return a success (not an error message).

## Example

This example deletes the "Nelson" object from the "quotes" bucket.

*Sample Request*

```
<DeleteObject xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <AWSAccessKeyId> AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</DeleteObject>
```

*Sample Response*

```
<DeleteObjectResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <DeleteObjectResponse>
    <Code>200</Code>
    <Description>OK</Description>
  </DeleteObjectResponse>
</DeleteObjectResponse>
```

## Elements

- *Bucket*: The bucket that holds the object.
- *Key*: The key that identifies the object.

## Access Control

You can delete an object only if you have `WRITE` access to the bucket, regardless of who owns the object or what rights are granted to it.

## GetObjectAccessControlPolicy

The `GetObjectAccessControlPolicy` operation fetches the access control policy for an object.

## Example

This example retrieves the access control policy for the "Nelson" object from the "quotes" bucket.

*Sample Request*

```
<GetObjectAccessControlPolicy xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</GetObjectAccessControlPolicy>
```

*Sample Response*

```
<AccessControlPolicy>
  <Owner>
    <ID>a9a7b886d6fd24a541bf9b1c61be666e9</ID>
    <DisplayName>chriscustomer</DisplayName>
  </Owner>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b841bf9b1c61be666e9</ID>
        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
    <Grant>
      <Grantee xsi:type="Group">
        <URI>http://acs.amazonaws.com/groups/global/AllUsers<URI>
      </Grantee>
      <Permission>READ</Permission>
    </Grant>
  </AccessControlList>
</AccessControlPolicy>
```

## Response Body

The response contains the access control policy for the bucket. For an explanation of this response, see [SOAP Access Policy](#).

## Access Control

You must have `READ_ACP` rights to the object in order to retrieve the access control policy for an object.

## SetObjectAccessControlPolicy

The `SetObjectAccessControlPolicy` operation sets the access control policy for an existing object. If successful, the previous access control policy for the object is entirely replaced with the specified access control policy.

## Example

This example gives the specified user (usually the owner) `FULL_CONTROL` access to the "Nelson" object from the "quotes" bucket.

*Sample Request*

```
<SetObjectAccessControlPolicy xmlns="http://doc.s3.amazonaws.com/2006-03-01">
  <Bucket>quotes</Bucket>
  <Key>Nelson</Key>
  <AccessControlList>
    <Grant>
      <Grantee xsi:type="CanonicalUser">
        <ID>a9a7b886d6fd24a52fe8ca5bef65f89a64e0193f23000e241bf9b1c61be666e9</ID>

        <DisplayName>chriscustomer</DisplayName>
      </Grantee>
      <Permission>FULL_CONTROL</Permission>
    </Grant>
  </AccessControlList>
  <AWSAccessKeyId>AKIAIOSFODNN7EXAMPLE</AWSAccessKeyId>
  <Timestamp>2006-03-01T12:00:00.183Z</Timestamp>
  <Signature>Iuyz3d3P0aTou39dzbqaEXAMPLE=</Signature>
</SetObjectAccessControlPolicy>
```

*Sample Response*

```
<SetObjectAccessControlPolicyResponse xmlns="http://s3.amazonaws.com/doc/2006-03-01">
  <SetObjectAccessControlPolicyResponse>
    <Code>200</Code>
    <Description>OK</Description>
  </SetObjectAccessControlPolicyResponse>
</SetObjectAccessControlPolicyResponse>
```

## Access Control

You must have `WRITE_ACP` rights to the object in order to set the access control policy for a bucket.

# Amazon S3 Resources

---

Following is a table that lists related resources that you'll find useful as you work with this service.

Resource	Description
<a href="#">Amazon S3 Getting Started Guide</a>	The Getting Started Guide provides a quick tutorial of the service based on a simple use case. Examples and instructions for Java, Perl, PHP, C#, Python, and Ruby are included.
<a href="#">Amazon S3 Developer Guide</a>	The developer guide describes how to accomplish tasks using Amazon S3 operations.
<a href="#">Amazon S3 Technical FAQ</a>	The FAQ covers the top 20 questions developers have asked about this product.
<a href="#">Amazon S3 Release Notes</a>	The Release Notes give a high-level overview of the current release. They specifically note any new features, corrections, and known issues.
<a href="#">AWS Developer Resource Center</a>	A central starting point to find documentation, code samples, release notes, and other information to help you build innovative applications with AWS.
<a href="#">AWS Management Console</a>	The console allows you to perform most of the functions of Amazon S3 without programming.
<a href="#">Discussion Forums</a>	A community-based forum for developers to discuss technical questions related to Amazon Web Services.
<a href="#">AWS Support Center</a>	The home page for AWS Technical Support, including access to our Developer Forums, Technical FAQs, Service Status page, and Premium Support.
<a href="#">AWS Premium Support</a>	The primary web page for information about AWS Premium Support, a one-on-one, fast-response support channel to help you build and run applications on AWS Infrastructure Services.
<a href="#">Amazon S3 product information</a>	The primary web page for information about Amazon S3.

Resource	Description
<a href="#">Contact Us</a>	A central contact point for inquiries concerning AWS billing, account, events, abuse etc.
<a href="#">Conditions of Use</a>	Detailed information about the copyright and trademark usage at Amazon.com and other topics.

# Document History

---

This document history is associated with the 2006-03-01 release of Amazon S3. This guide was last updated on December 27, 2012.

The following table describes the important changes since the last release of the *Amazon S3 API Reference*.

Change	Description	Release Date
Root domain support for website hosting	<p>Amazon S3 now supports hosting static websites at the root domain. Visitors to your website can access your site from their browser without specifying "www" in the web address (e.g., "example.com"). Many customers already host static websites on Amazon S3 that are accessible from a "www" subdomain (e.g., "www.example.com"). Previously, to support root domain access, you needed to run your own web server to proxy root domain requests from browsers to your website on Amazon S3. Running a web server to proxy requests introduces additional costs, operational burden, and another potential point of failure. Now, you can take advantage of the high availability and durability of Amazon S3 for both "www" and root domain addresses.</p> <p>For an example walkthrough, go to go to <a href="#">Example: Setting Up a Static Website Using a Custom Domain</a>. For conceptual information, go to <a href="#">Hosting Static Websites on Amazon S3</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	In this release.



Change	Description	Release Date
Support for Archiving Data to Amazon Glacier	<p>Amazon S3 now support a storage option that enables you to utilize Amazon Glacier's low-cost storage service for data archival. To archive objects, you define archival rules identifying objects and a timeline when you want Amazon S3 to archive these objects to Amazon Glacier. You can easily set the rules on a bucket using the Amazon S3 console or programmatically using the Amazon S3 API or AWS SDKs.</p> <p>To support data archival rules, Amazon S3 lifecycle management API has been updated. For more information, see <a href="#">PUT Bucket lifecycle (p. 106)</a>.</p> <p>After you archive objects, you must first restore a copy before you can access the data. Amazon S3 offers an new API for you to initiate a restore. For more information, see <a href="#">POST Object restore (p. 182)</a>.</p> <p>For conceptual information, go to <a href="#">Object Lifecycle Management</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	In this release.
Support for Website Page Redirects	<p>For a bucket that is configured as a website, Amazon S3 now supports redirecting a request for an object to another object in the same bucket or to an external URL. You can configure redirect by adding the <code>x-amz-website-redirect-location</code> metadata to the object.</p> <p>The object upload APIs <a href="#">PUT Object (p. 185)</a>, <a href="#">Initiate Multipart Upload (p. 210)</a>, and <a href="#">POST Object (p. 175)</a> allow you to configure the <code>x-amz-website-redirect-location</code> object metadata.</p> <p>For conceptual information, go to <a href="#">How to Configure Website Page Redirects</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	04 October 2012
Cross-Origin Resource Sharing (CORS) support	<p>Amazon S3 now supports Cross-Origin Resource Sharing (CORS). CORS defines a way in which client web applications that are loaded in one domain can interact with or access resources in a different domain. With CORS support in Amazon S3, you can build rich client-side web applications on top of Amazon S3 and selectively allow cross-domain access to your Amazon S3 resources. For more information, see <a href="#">Enabling Cross-Origin Resource Sharing</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	31 August 2012
Cost Allocation Tagging support	<p>Amazon S3 now supports cost allocation tagging, which allows you to label S3 buckets so you can more easily track their cost against projects or other criteria. For more information, see <a href="#">Cost Allocation Tagging</a> in the <i>Amazon S3 Developer Guide</i>.</p>	21 August 2012
Object Expiration support	<p>You can use Object Expiration to schedule automatic removal of data after a configured time period. You set object expiration by adding lifecycle configuration to a bucket. For more information, see <a href="#">Object Expiration</a>.</p>	27 December 2011
New Region supported	<p>Amazon S3 now supports the South America (Sao Paulo) Region. For more information, see <a href="#">Buckets and Regions</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	14 December 2011

Change	Description	Release Date
Multi-Object Delete	<p>Amazon S3 now supports Multi-Object Delete API that enables you to delete multiple objects in a single request. With this feature, you can remove large numbers of objects from Amazon S3 more quickly than using multiple individual DELETE requests.</p> <p>For more information about the API see, see <a href="#">Delete Multiple Objects (p. 144)</a>.</p> <p>For conceptual information about the delete operation, see <a href="#">Deleting Objects</a>.</p>	07 December 2011
New Region supported	Amazon S3 now supports the US West (Oregon) Region. For more information, see <a href="#">Buckets and Regions</a> in the <i>Amazon Simple Storage Service Developer Guide</i> .	08 November 2011
Server-side encryption support	Amazon S3 now supports server-side encryption. It enables you to request Amazon S3 to encrypt your data at rest, that is, encrypt your object data when Amazon S3 writes your data to disks in its data centers. To request server-side encryption, you must add the <code>x-amz-server-side-encryption</code> header to your request. To learn more about data encryption, go to <a href="#">Using Data Encryption</a> .	17 October 2011
Multipart Upload API extended to enable copying objects up to 5 TB	Prior to this release, Amazon S3 API supported copying objects (see <a href="#">PUT Object - Copy (p. 201)</a> ) of up to 5 GB in size. To enable copying objects larger than 5 GB, Amazon S3 extends the multipart upload API with a new operation, <code>Upload Part (Copy)</code> . You can use this multipart upload operation to copy objects up to 5 TB in size. For conceptual information about multipart upload, go to <a href="#">Uploading Objects Using Multipart Upload</a> . To learn more about the new API, see <a href="#">Upload Part - Copy (p. 219)</a> .	21 June 2011
SOAP API calls over HTTP disabled	To increase security, SOAP API calls over HTTP are disabled. Authenticated and anonymous SOAP requests must be sent to Amazon S3 using SSL.	6 June 2011
Support for hosting static websites in Amazon S3	<p>Amazon S3 introduces enhanced support for hosting static websites. This includes support for index documents and custom error documents. When using these features, requests to the root of your bucket or a subfolder (e.g., <code>http://mywebsite.com/subfolder</code>) returns your index document instead of the list of objects in your bucket. If an error is encountered, Amazon S3 returns your custom error message instead of an Amazon S3 error message. For API information to configure your bucket as a website, see the following sections:</p> <ul style="list-style-type: none"> <li>• <a href="#">PUT Bucket website (p. 132)</a></li> <li>• <a href="#">GET Bucket website (p. 77)</a></li> <li>• <a href="#">DELETE Bucket website (p. 29)</a></li> </ul> <p>For conceptual overview, go to <a href="#">Hosting Websites on Amazon S3</a> in the <i>Amazon Simple Storage Service Developer Guide</i>.</p>	17 February 2011

Change	Description	Release Date
Response Header API Support	The GET Object REST API now allows you to change the response headers of the REST GET Object request for each request. That is, you can alter object metadata in the response, without altering the object itself. For more information, see <a href="#">GET Object (p. 153)</a> .	14 January 2011
Large Object Support	Amazon S3 has increased the maximum size of an object you can store in an S3 bucket from 5 GB to 5 TB. If you are using the REST API you can upload objects of up to 5 GB size in a single PUT operation. For larger objects, you must use the Multipart Upload REST API to upload objects in parts. For conceptual information, go to <a href="#">Uploading Objects Using Multipart Upload</a> . For multipart upload API information, see <a href="#">Initiate Multipart Upload (p. 210)</a> , <a href="#">Upload Part (p. 216)</a> , <a href="#">Complete Multipart Upload (p. 224)</a> , <a href="#">List Parts (p. 231)</a> , and <a href="#">List Multipart Uploads (p. 81)</a>	9 December 2010
Multipart upload	Multipart upload enables faster, more flexible uploads into Amazon S3. It allows you to upload a single object as a set of parts. For conceptual information, go to <a href="#">Uploading Objects Using Multipart Upload</a> . For multipart upload API information, see <a href="#">Initiate Multipart Upload (p. 210)</a> , <a href="#">Upload Part (p. 216)</a> , <a href="#">Complete Multipart Upload (p. 224)</a> , <a href="#">List Parts (p. 231)</a> , and <a href="#">List Multipart Uploads (p. 81)</a>	10 November 2010
Notifications	The Amazon S3 notifications feature enables you to configure a bucket so that Amazon S3 publishes a message to an Amazon Simple Notification Service (SNS) topic when Amazon S3 detects a key event on a bucket. For more information, see <a href="#">GET Bucket notification (p. 54)</a> and <a href="#">PUT Bucket notification (p. 54)</a> .	14 July 2010
Bucket policies	Bucket policies is an access management system you use to set access permissions on buckets, objects, and sets of objects. This functionality supplements and in many cases replaces access control lists.	6 July 2010
Reduced Redundancy	Amazon S3 now enables you to reduce your storage costs by storing objects in Amazon S3 with reduced redundancy. For more information, see <a href="#">PUT Object (p. 185)</a> .	12 May 2010
New Region supported	Amazon S3 now supports the Asia Pacific (Singapore) Region and therefore new location constraints. For more information, see <a href="#">GET Bucket location (p. 49)</a> and <a href="#">PUT Bucket (p. 89)</a> .	28 April 2010
Object Versioning	This release introduces object Versioning. All objects now have a key and a version. If you enable versioning for a bucket, Amazon S3 gives all objects added to a bucket a unique version ID. This feature enables you to recover from unintended overwrites and deletions. For more information, see <a href="#">GET Object (p. 153)</a> , <a href="#">DELETE Object (p. 141)</a> , <a href="#">PUT Object (p. 185)</a> , <a href="#">PUT Object Copy (p. 201)</a> , or <a href="#">POST Object (p. 175)</a> . The SOAP API does not support versioned objects.	8 February 2010

Change	Description	Release Date
New Region supported	Amazon S3 now supports the US-West (Northern California) Region. The new endpoint is <code>s3-us-west-1.amazonaws.com</code> . For more information, see <a href="#">How to Select a Region for Your Buckets</a> .	2 December 2009
C# Library Support	AWS now provides Amazon S3 C# libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of REST or SOAP. These libraries provide basic functions (not included in the REST or SOAP APIs), such as request authentication, request retries, and error handling so that it's easier to get started.	11 November 2009
Technical documents reorganized	The API reference has been split out of the <i>Amazon S3 Developer Guide</i> . Now, on the documentation landing page, <a href="http://developer.amazonwebservices.com/connect/entry.jspa?externalID=123&amp;categoryID=48">http://developer.amazonwebservices.com/connect/entry.jspa?externalID=123&amp;categoryID=48</a> you can select the document you want to view. When viewing the documents online, the links in one document will take you, when appropriate, to one of the other guides.	16 September 2009

## Glossary

---

100-continue	A method that enables a client to see if a server can accept a request before actually sending it. For large <code>PUTs</code> , this can save both time and bandwidth charges.
account	AWS account associated with a particular developer.
authentication	The process of proving your identity to the system.
bucket	A container for objects stored in Amazon S3. Every object is contained within a bucket. For example, if the object named <code>photos/puppy.jpg</code> is stored in the <code>johnsmith</code> bucket, then it is addressable using the URL <code>http://johnsmith.s3.amazonaws.com/photos/puppy.jpg</code>
canned access policy	A standard access control policy that you can apply to a bucket or object. Valid Values: <code>private</code>   <code>public-read</code>   <code>public-read-write</code>   <code>authenticated-read</code>   <code>bucket-owner-read</code>   <code>bucket-owner-full-control</code>
canonicalization	The process of converting data into a standard format that will be recognized by a service such as Amazon S3.
consistency model	The method through which Amazon S3 achieves high availability, which involves replicating data across multiple servers within Amazon's data centers. After a "success" is returned, your data is safely stored. However, information about the changes might not immediately replicate across Amazon S3.
key	The unique identifier for an object within a bucket. Every object in a bucket has exactly one key. Since a bucket and key together uniquely identify each object, Amazon S3 can be thought of as a basic data map between "bucket + key" and the object itself. Every object in Amazon S3 can be uniquely addressed through the combination of the web service endpoint, bucket name, and key, as in <code>http://doc.s3.amazonaws.com/2006-03-01/AmazonS3.wsdl</code> , where "doc" is the name of the bucket, and "2006-03-01/AmazonS3.wsdl" is the key.
metadata	The metadata is a set of name-value pairs that describe the object. These include default metadata such as the date last modified and standard HTTP metadata such as <code>Content-Type</code> . The developer can also specify custom metadata at the time the Object is stored.
object	The fundamental entities stored in Amazon S3. Objects consist of object data and metadata. The data portion is opaque to Amazon S3.
part	The fundamental entities stored in Amazon S3. Objects consist of object data and metadata. The data portion is opaque to Amazon S3.

service endpoint	The host and port with which you are trying to communicate within the destination URL. For virtual hosted-style requests, this is <code>mybucket.s3.amazonaws.com</code> . For path-style requests, this is <code>s3.amazonaws.com</code>
------------------	---

# Index

## A

abort upload, 229  
API  
    REST, 11

## B

buckets  
    creating, 238  
    putting, 29, 77, 89, 94, 112, 114, 128, 132  
    REST operations, 18  
    SOAP operations, 238  
    tagging, 123

## C

changes, 267  
common response headers, 14  
complete upload, 224  
content-MD5, 175, 182, 185, 194, 249  
Content-MD5, 247  
COPY, REST, 201  
copying objects  
    REST, 201  
    SOAP, 252  
CopyObject  
    errors, 255  
CopyObject, SOAP, 252  
cors, 21, 41, 101, 172  
cors configuration, 21  
cors subresource, 21, 41, 101, 172  
CreateBucket  
    SOAP, 238  
creating buckets  
    SOAP, 238

## D

data corruption  
    preventing, 175, 182, 185, 194, 247, 249  
DELETE  
    REST, 19, 25, 27, 141  
DeleteBucket, 239  
deleting objects  
    SOAP, 261  
duplicating objects, 252

## E

errors  
    CopyObject, 255  
    list, 3

## G

GET

    policy, REST, 15  
    REST, 31, 54, 60, 72, 74, 161  
GET, REST, 38, 47, 49, 51, 57, 153, 165  
GetBucketAccessControlPolicy  
    SOAP, 242  
GetBucketLoggingStatus  
    SOAP, 244  
GetObject  
    SOAP, 256  
GetObjectAccessControlPolicy  
    SOAP, 262  
GetObjectExtended  
    SOAP, 261  
guide organization, 1

## H

HEAD  
    REST, 79  
HEAD object  
    REST, 167  
headers, request  
    REST, 12

## I

initiate, 210

## L

large object upload  
    abort, 229  
    complete, 224  
    initiate, 210  
    list, 81, 144  
    list parts, 231  
    upload part, 216, 219  
lifecycle subresource, 23, 44, 106  
list multipart uploads, 81, 144  
list parts, 231  
ListAllMyBuckets  
    SOAP, 236  
ListBucket  
    SOAP, 239

## N

notification, 54, 119

## O

object expiration, 23, 44, 106  
objects  
    copying, 201, 252  
    REST operations, 139  
    SOAP operations, 246  
organization of guide, 1

## P

POST, REST, 175

PUT  
  REST, 29, 77, 89, 94, 112, 114, 119, 123, 126, 128, 132  
PUT, REST, 182, 185, 194  
PutObject  
  SOAP, 249  
PutObjectInline  
  SOAP, 247  
putting buckets  
  REST, 29, 77, 89, 94, 112, 114, 128, 132  
putting Request Payments  
  REST, 126  
putting tagging  
  REST, 123

## R

Request Headers, 12  
requestPayments  
  putting, 126  
resources, related, 265  
response headers, common, 14  
REST  
  API, 11  
  bucket operations, 18  
  COPY, 201  
  DELETE, 19, 25, 27, 141  
  GET, 15, 31, 54, 60, 72, 74, 161  
  GET object, 38, 47, 49, 51, 153, 165, 216, 219  
  GET tagging, 57  
  HEAD, 79  
  HEAD object, 167  
  object operations, 139  
  POST object, 175  
  PUT, 29, 77, 89, 94, 112, 114, 119, 123, 126, 128, 132  
  PUT object, 182, 185, 194  
  service operations, 15

## S

S3 cors, 41, 101, 172  
S3 object lifecycle management, 23, 44, 106  
service  
  REST operations, 15  
  SOAP operations, 236  
SetBucketAccessControlPolicy  
  SOAP, 243  
SetBucketLoggingStatus  
  SOAP, 245  
SetObjectAccessControlPolicy  
  SOAP, 263  
SOAP  
  bucket operations, 238  
  CopyObject, 252  
  CreateBucket, 238  
  DeleteBucket, 239  
  DeleteObject, 261  
  GetBucketAccessControlPolicy, 242  
  GetBucketLoggingStatus, 244  
  GetObject, 256

GetObjectAccessControlPolicy, 262  
GetObjectExtended, 261  
ListAllMyBuckets, 236  
ListBucket, 239  
object operations, 246  
PutObject, 249  
PutObjectInline, 247  
service operations, 236  
SetBucketAccessControlPolicy, 243  
SetBucketLoggingStatus, 245  
SetObjectAccessControlPolicy, 263

## T

tag, 27, 57, 123  
tag set, 27, 57, 123  
tagging subresource, 27, 57, 123

## U

upload part, 216, 219

## W

WSDL, 2