OdimH5 User's Guide

Version 0.9
11 czerwca 2010

This document is a user's guide on how to use OdimH5.
It's still under development.

OdimH5 is a console utility designed to work on radar data files and it provides XML descriptor handler, HDF5 converter, Baltrad feeder mode.

1 Introduction

1.1 Overview

The OdimH5 is a Java-based tool working on meteorological radar data. It allows users to create an XML descriptor which contains all major information require to create a HDF5 file. The application also allows users to convert specific radar data to HDF5 format based on the descriptor. For `Baltrad` users it provides automatic online mode which feeds `BaltradDex` with actual data.

The application was implemented using the Java$^{\text{TM}}$ 2 Platform, which is machine-independent.

HDF libraries

This release was built and tested with HDF5-1.8.4 Patch 1 with HDF5 1.6 compatibility flag. For information on new features in HDF5 Release 1.8.0 and format compatibility considerations, please visit.

Platforms

This release was built and tested for the following platforms:

- Linux

- Linux x86_64

- Windows

Major Improvements

Major Bug Fixes

1.2 Current Features

This version can work with limited radar systems and products listed below.

Platforms

- Gematronik RAINBOW

Type of product

- Polar Volume Scan

  - dBZ - Reflectivity
  - uPhiDP - Differential Phase Shift
  - KDP - Specific Differential Phase Shift
  - RhoHV - Correlation Coefficient

- Cartesian image and composite

  - PPI - Plan Position Indicator
  - CAPPI - Constant Altitude PPI
  - MAX - Maximum Display
  - EHT - Echo Height
  - SRI - Surface Rainfall Intensity
  - PAC - Precipitation Accumulation
  - VIL - Vertical Integrated Liquid
  - HSHEAR - Horizontal Shear

- Vertical profile (Not implemented)

- Range-height indicator

  - RHI - Range Height Indicator

2 Getting Started

2.1 Installation

Program requires no special installation. It consists of only one runnable `.jar` file which has to be copy on local machine.

> Program uses HDF5 libraries, which are mostly included to the `.jar` file. For Linux platforms the JNI interfaces files need separate installation. The `libjhdf.so` and `libjhdf5.so` files which are provided with main program must be included to the `LD_LIBRARY_PATH` for running. Linking will be done automatically when final version of application is realised.

2.2 Convertion mode

`OdimH5` provides two convertion modes. First one creates XML descriptor, that can be used later to create HDF file. Second mode converts raw data directely to HDF5.

2.2.1 Prepare descriptor

Descriptor is an XML file, which structure corresponds to HDF5 file. To prepare descriptor use the following parameters:

`-i`   Input file's path.
Program can work with only one file simultaneously.

`-o`   Output file's path.
It is suggested to use `.xml` filename extension.

`-p`   Radar platform's name.
At the moment only Gematronik's RAINBOW software is supported.

`-f`   Product format.
Use one of the formats listed above according to input data type.

`-v`   Verbose mode.
It is optional and displays status of progress of program work.

Example of use:

```
java -jar OdimH5.jar -i input.ppi -o ppi.xml -p RAINBOW -f IMAGE -v
```

2.2.2 Prepare HDF5 file from descriptor

It requires XML descriptor as an input file. To prepare HDF5 use the following parameters:

`-i`   Input file's path.
Program can work with only one file simultaneously.

`-o`   Output file's path.
It is suggested to use `.h5` filename extension.

`-v`   Verbose mode.
It is optional and displays status of progress of program work.

Example of use:

```
java -jar OdimH5.jar -i ppi.xml -o output.h5 -v
```

2.2.3   Prepare HDF5 file directly from raw file

It has the same parameters as descriptor preparation mode, but output file name
has to end with `.h5`.

Example of use:

```
java -jar OdimH5.jar -i input.ppi -o ppi.h5 -p RAINBOW -f PVOL -v
```

2.3   Baltrad Feeder

`OdimH5` allows users to send HDF5 files into `BaltradDex` system. To send a file
use following command:

```
java -jar OdimH5.jar -i input.h5 -r Brzuchania -s IMGW.pl
-a http://172.30.9.34:8084/BaltradDex/transmitter.htm
```

It sends a single HDF5 file to server but it can work as a continuous `Baltrad`
feeder aswell with online convertion to HDF5 format. It works automatical-
ly with specific options provided by user. The program reads options from
`options.xml` file stored in the main folder. The following options are required
for proper work:

- Radar name. Every radar is represented by `radar` element in XML.

- IP address of FTP server where actual data are stored.

- Login to FTP server.

- Password to FTP server.

- Remote directory on FTP server.

- Repetition time in minutes. Program wakes up every this repetition time
  and downloads all files that match criterium. E.g. if repetition time equals
  10 minutes, program will download files that were created during last 10-
  minute period and will start again in 10 minutes.

- Address of HTTP server.

- Sender name.

Example `options.xml` file:

```
<?xml version=\"1.0\" ?>
<!-- FTP options -->
<options>
<radar name="Brzuchania">
<address>172.30.9.23</address>
<login>rainbow</login>
<password>****</password>
<remote_dir>/usr/local/Rainbow5/rainbow/rawdata/BRZ/BRZ_250_Z.vol
</remote_dir>
</radar>
<repetition_time>10</repetition_time>
<server>http://172.30.9.34:8084/BaltradDex/transmitter.htm</server>
<sender>Baltrad.IMGW.pl</sender>
</options>
```

To run feeder use `-c` option with one of following parameters:

- `RVOL` for RAINBOW volume files.

- `H5` for HDF5 files.

Example of use:

```
java -jar OdimH5.jar -c RVOL -v
```

2.4   Help

To display help menu in program use following parameter:

```
java -jar OdimH5.jar -h
```

2.5   Troubleshooting

Application is in its developing state and have not been tested thoroughly. To report a bug please send information to lukasz.wojtas@imgw.pl