Cyclus As a Synthetic Testbed of Systems-Level Diversion Signatures

Meghan B. McGarry¹, Paul P.H. Wilson¹, Tom Atwood²

¹Department of Nuclear Engineering and Engineering Physics, University of Wisconsin-Madison

Abstract

Already the dominant source of clean energy, nuclear power is growing at a rapid pace. While beneficial to a world confronting climate change, the nuclear security and non-proliferation impacts of expanding nuclear power will become more consequential. As a result, it is imperative to develop credible methods to verify compliance with treaties that control fissile material production, such as the Non-Proliferation Treaty or a potential Fissile Material Cutoff Treaty. As part of the Consortium for Verification Technology, the Cyclus fuel cycle simulator is being used as a testbed for the development of new technologies and analysis approaches to treaty verification. Cyclus is an agent-based, systems-level simulator that tracks discrete material flow through the entire fuel cycle, from mining through burnup in reactors to a repository, or alternatively through one or more iterations of reprocessing. A systems-level view facilitates the study of correlated signals from different facilities that combine to form identifiable signatures of clandestine activity. Cyclus also includes a region/institution/facility hierarchy that can incorporate the effects of tariffs and sanctions in regional or global contexts. Cyclus enables social-behavioral modeling of the interactions between individual facilities or regions. This paper presents the first use of Cyclus to simulate nuclear material diversion from the fuel cycle using a variety of contemporaneous signals: material flow, facility power consumption, effluent emissions (including geospatial distribution), event-logs. Multiple signal modalities can be analyzed in concert using anomaly detection techniques to identify signatures of material diversion or other signatures of clandestine nuclear weapons development. The Cyclus testbed can then be used to examine treaty verification techniques and inspection regimens to to inform their sensitivity and limitations.

1 Introduction

Nuclear expertise is rapidly expanding around the world as demand for energy increases steadily[1]. As climate change becomes increasingly important with respect to national security, the perception of the risk inherent to nuclear energy is decreasing and states are embracing nuclear energy as a reliable large-scale source of carbon-neutral energy. However, the expansion of nuclear power amplifies nuclear security concerns with increased production of civilian fissile materials and as the knowledge and technology required to make nuclear weapons proliferates around the globe [2].

While it has not proven possible to prevent the spread of nuclear knowledge entirely, international treaties have been used in an attempt to minimize it. The Nuclear Nonproliferation Treaty (NPT), which has been signed by 190 states including the original five nuclear weapons states, has codified a set of rules and norms for allowing the peaceful pursuit of nuclear energy [3]. The NPT created the International Atomic Energy Agency (IAEA), whose role is to verify compliance with the treaty by periodically inspecting

²Sandia National Laboratories




Fig. 1: The CYCLUS nuclear fuel cycle simulator provides a testbed to integrate innovations in treaty verification across many disciplines.

facilities related to nuclear technology. Other relevant treaties include Comprehensive Nuclear-Test-Ban Treaty (CTBT), which placed a moratorium on testing nuclear weapons, and the Strategic Arms Reduction Treaties (START) in which the United States (US) and Russia agreed to nuclear arms reductions [4, 5]. A potential Fissile Material Cutoff Treaty (FMCT) would place limits on the amount of weapons-grade fissile material that each signatory state could stockpile, possibly including current stockpiles in the case of weapons states.

An effective treaty verification regime must synthesize knowledge from the realms of political science, international relations, nuclear physics and engineering, and even behavioral psychology. Figure 1 illustrates the role of a fuel cycle simulator such as CYCLUS in bringing together these disparate fields to provide insights into proposed verification technologies. A fuel cycle simulator tracks the flow of nuclear material through the facilities in a fuel cycle[6]. Uranium enrichment and spent fuel reprocessing are two particularly sensitive parts of the fuel cycle, but correlated signatures of illicit activity are likely to be present across the fuel cycle. A fuel cycle simulator creates synthetic data, such as what would be available to an inspector, for many different facilities simultaneously while incorporating a system-level perspective of proliferation scenarios. This synthetic data can then be used as a testbed to investigate the efficacy of new detection and analysis techniques and illucidate the strengths and weaknesses of various verification strategies.

2 The Cyclus Fuel Cycle Simulator

The Computational Nuclear Engineering Research Group (CNERG)¹ group at the University of Wisconsin has developed the CYCLUS² nuclear fuel cycle simulator to model all aspects of the nuclear fuel cycle in a flexible way [7]. CYCLUS tracks material flow over time for every agent in a fuel cycle (such as a mine, a nuclear reactor, or even a governing body. Each agent in the simulation is self-contained and may include physics, economics, or behavioral components [8, 9, 10]. The agents interact with one another through the dynamic resource exchange (DRE), which facilitates the trading of resources and commodities [11]. At each

¹ http://cnerg.github.io/

² http://fuelcycle.org/

timestep, agents can choose to request resources, defined using both a quantity and quality (e.g. 1 metric ton of natural uranium with a composition of 99.7% ^{238}U and 0.3% ^{235}U). The DRE then solicits bids from any facilities that are interested in offering those resources. After the bids are received, the requestor is able to state a preference for one bid over another. Finally, the DRE calculates all potential trades across all agents, executes an optimization algorithm to find the solution that most closely fulfills a maximum of requests, and the material is transfered across the facilities. The output of a CYCLUS simulation is a database with information on facility flow and inventories, material composition, transactions between facilities, and facility build and decommissioning histories.

CYCLUS has three key features: it is *agent-based*, it tracks *discrete materials*, and it incorporates *social* and behavioral interaction models. Agent-based design allows for modular simulations where individual facilities can be swapped compared in otherwise identical simulations[12, 13]. CYCLUS tracks discrete material flow through the simulation, and uses data from PyNE,³ to track decay and transumutation data at all timesteps [14, 15]. Finally, behavioral modeling allows facilities and institutions to engage in dynamic decision-making based on their preferences, needs, or political constraints. A specific agent might have preferences based on material composition, physical proximity between facilities, or allowed and disallowed trading partners, which are implemented in a region-institution-facility hierarchy that enables economic modeling [16].

Although the primary use case for CYCLUS is to assess the transition from once-through fuel cycles to alternative next-generation scenarios including technologies such as spent fuel recycling, it is was also designed for examining proliferation issues, due to its ability to capture agent behavior. For example, an enrichment facility receiving illicit requests for highly enriched uranium (HEU) may define its own criteria for whether or not to fulfill this order. It may disallow production of enrichments above a certain level, choose to trade only with specific facilities, or choose to preferentially fulfill requests at one enrichment level over an other. Likewise, a requestor of HEU can make requests at regular or random intervals, and may request randomly or gaussian distributions of material quantity. At the insitution level, CYCLUS allows trading decisions between facilities to be controlled by the owner of those facilities, which may be a commercial entity or a nation-state. This facilitiates modeling of the interactions between multiple states within a region.

3 Signatures and Observables

Figure 2 characterizes potential signatures and observables of illicit activity at all major facilities in the nuclear fuel cycle. Each potential signature is color coded to represent the accessibility of the data: measureable through open, independent sources such as satellite imagery (green), available through official inspections (blue), or potentially unreliable due to physical or political constraints such as state declarations (yellow). Not all of these signatures are currently collected, and it would be prohibitively resource intensive to maintain comprehensive monitoring. Therefore, correlations in these individual signatures must be leveraged to overcome sparse datasets or resource constraints.

CYCLUS is being used to produce a variety of synthetic signals spanning a range of modalities that would be available either publicly or via official inspections (green or blue). As detailed in Section 4, all facilities in CYCLUS inherently produce time-series data such as material flow, inventory, and separative work unit (SWU) consumption (for enrichment facilities). As seen in Figure 3, CYCLUS can combine atmospheric transport models with facility effluent concentration (*I*) to track geographic dispersion. In this

³ http://pyne.io/

Signatures	Mining/Milling	Conversion	Enrichment (centrifuge)	Fuel Fabrication (U)	Reactors (Gen)	Separations	Waste Disposal
Nuc Matl In (estimate)	Jg	# 55 gall drums		#tanks	# assemblies	# casks or assemblies	# casks or barrels
Nuc Matl In (qty, precise)		Mass	Mass, PSI	Mass, PSI	mass	mass	barrels, tanker trucks, casks, trupack2 concrete barrels
Nuc Matl In (quality)		assays	IAEA assays	assays	IAEA assays	assays, radiometry	radiometry
read mate in (quanty)		usbuys	In the readoury of	ussays		UF6 tanks	radiometry
Nuc Matl Out (estimate)	Trucks	# tanks	# tanks	# assemblies	pools, dry cask storage	(UF6), Pu or Pu+FP	
						total mass can be tracked, but stream fraction depends on	
Nuc Matl Out (qty, precise)		mass, psi	mass, psi	mass	mass	burnup	
Nuc Matl Out (quality)	radiometry	assays	assays	assays	assays	assays	
Supplemental Material In	Sulfuric acid (20kg/tonne), magnesium chlorite, lime, magnanese, ammonia, or caustic soda	nitric acid, HF, tributyl phosphate		zircaloy(tin, niobium,iron,chromiu m,nickel), NSF cladding (zircaloy+iron), H2, ammonia or ammonium carbonate, argon, erbium, organic binding agent (polyvinal alcohol), He, HNO3-HF	(heavy water, gas cooling, etc) ?	nitric acid, kerosene or dodecane, Na2CO3, NaOH, HNO3	entombment matls (concrete, filler matl), vitrifcation material (borosilicate glass)
Supplemental Material Out		Chem waste, silicon flouride (commercial) from DU		florine, hafnium (natural Zr byproduct)	(sodium? other chemicals)	Chem waste, Alternative isotope streams (Ti, I, Tc, Pt, Np,Am), fuel casing metals	
Power		Trans line/substation	Trans line/substation	Trans line/substation	produce vs consumed	Trans line/substation	(vitrification)
Nuc Waste Quantity	Tailings pond (satellite)		Trucks	"lost fuel": grinding, scraps (diff. to measure)	low-level (trucks)	Containers (borosilicate glass, high level waste)	
Nuc Waste Quality	radiometry		Tails Enrichment	assay	radiometry	radiometry	
	tailpipe emissions,	Ammonia gas				Kr85, Xenon,	
Effluent	radon	leaks	uranyl, HF		fuel leak (Kr, Xe)	tritium, I, CO2	
					soil contam, fuel leak in coolant		
Environmental Signatures	dynamite blast s			soil contamination	water (I,Cs)	soil contam	soil contam (barren
Declarations to IAEA	Out Qty/Quality	Satellite (#	Satellite (#	In/Out Qty/Quality Satellite (# trucks),	In/Out Qty/Quality Satellite (# trucks,	-	Satellite (# trucks),
Shipping In	0-4-11:4- (#	trucks), freq	trucks), freq	freq	rail), freq`	trucks), freq	freq
Shipping Out	Satellite (# trucks), freq	Satellite (# trucks), freq	Satellite (# trucks), freq	Satellite (# trucks), freq	Satellite (# trucks, rail), freq	Satellite (# trucks), freq	
Specialized Equipment	bulldozers, dynamite	centrifuge	Forklift rigs	Forklift rigs	radioactive handling	acid storage/handling , radioactive handling	radioactive handling
Heat Processes/Signatures		furnace (800C), fuel/ash signature		furnace (1750C), fuel/ash signature	cooling towers/ponds (temp, vol, fan speed)	furnace (1200C - pyroprocessing) , fuel/ash signature	vitrification (1100C), fuel/ash signature
Connections outside facility	where do trucks go	where do trucks	where do trucks go	where do trucks go	trans lines to correct location	where do trucks	where do trucks come from
Special Handling Protocols/Rates	acoustic signatures of dynamite	florine handling, heavy tanks	florine handling, heavy tanks, building below	flouride handling, heaving shipping (0.5tons/assembly), high temp vaccum oven	refueling frequency, transition to offsite waste storage	refresh acid supply, toxic waste, venting (operated at negative pressure), radioactive handling	
Configuration Change (staging materials etc)	addition of mill to mine site	combined w/ enrichment	piping			special construction matls (ceramic vats, piping)	

Fig. 2: Table of potential signatures across the fuel cycle: measureable through open, independent sources such as satellite imagery (green), available through official inspections (blue), or potentially unreliable due to physical or political constraints (yellow).




Fig. 3: Effluent transport with wind from left, hides a clandestine reprocessing facility x,y=(11,9) in close proximity to two declared facilities x,y=(1,3), (1,17)

example, a simple atmospheric diffusion model of wind (from the left) is used to illustrate how a small clandestine reprocessing facility could be hidden in close proximity to two larger declared facilities[17].

CYCLUS also models sparse, discrete-event data such as declared truck shipments or IAEA inspections that test for the presence of HEU. Figure 4 pairs inspections with undeclared truck shipments of HEU. IAEA inspections typically involve multiple swipe samples per location, with some likelihood of false-positive or false-negative results[18]. In this example, it is assumed that the likelihood of detecting HEU in the enrichment facility increases with each shipment, because contamination is possible when HEU is removed from cascades and bottled for shipping. The undeclared HEU shipments are shown as black bars, where amplitude incorporates the cumulative amount of HEU that has been produced at the facility. The colored dots scale from yellow to red, indicating the fraction of positive swipes at an IAEA inspector visit, assuming a total of 10 swipes are taken per inspection and a 30% chance that an individual swipe may produce a false reading.

Figure 5 shows the breakdown of true positive, false positive, and false negative results for each inspection. Before month 30, no HEU has been produced in the facility, so any "positive" swipes are false-positives (tan). Once the facility begins producing HEU, likelihood of contamination increases until it is detected near month 80. If the swipe tests were perfect, there would be a 100% detection rate for all inspections after that time. However, the possibility of false-negatives (pink), make the measured inspection data appear to be the tan signal before month 80 and the red signal after month 80. In this scenario, it would be difficult for an inspector to conclude that HEU was being produced with this dataset alone.

4 A Diversion Scenario: Highly Enriched Uranium

As a part of the Consortium for Verification Technology (CVT)⁴, CYCLUS is being used to generate multi-modal datasets with signatures of diversion with the goal of improving anomaly and change detection techniques. Figure 6 illustrates a toy scenario in which HEU is clandestinely produced and then diverted from a declared enrichment facility. A mine supplies natural uranium (0.7% ²³⁵U) to an enrichment facility, which in turn receives requests for low enriched uranium (LEU) one of five enrichment levels (3-5%) from

⁴ http://cvt.engin.umich.edu/




Fig. 4: Black bars indicate clandestine shipments of HEU, amplitudes show gross HEU production at the enrichment facility. Colored circles are fraction of swipes (out of 10) testing positive for HEU during an inspection. Both false positives and false negatives may be present, introducing uncertainty into the data.




Fig. 5: The scenario in Figure 4 had a 30% rate for both false-positives and false-negatives. Before month 30, no HEU has been produced so all detections are false positives (tan). Once HEU contamination is present (near month 80), true detections (red) combine with false-negatives (pink), resulting in a effective 70% detection rate.




Fig. 6: Diversion scenario: Enrichment facility produced LEU for 5 different customers, plus occasional clandestine HEU. Both LEU quantity and tails assays have some non-deterministic time variation.

several declared light-water reactors (ignoring the fuel fabrication facility for simplicity). The enrichment facility also receives requests for 90% enriched HEU from an undeclared actor seeking to build a nuclear weapon. Each month, the enrichment facility fulfills an order for one LEU enrichment level, and sometimes produces small quantities of HEU request.

Figure 7 shows the time series data for declared production of LEU (top) and the total SWU consumed by the enrichment plant (middle) available to the inspector (SWU can be used as a rough proxy for power consumption). Months where HEU is produced are denoted with green on the LEU plot. The HEU signature is hidden in the material flow because there is a gaussian variation in both the tails assay and the quantity of LEU produced, so it is not possible to detect diversion from the individual time-series data alone. However, the two signals can be combined to highlight the correlated signature of diverion. The bottom plot in Figure 7 shows time-series data for the ratio of SWU consumption to declared LEU production. When the variation due to changes in tails assay is sufficiently small, the deviations may be seen by eye. In practice, as the variations increase or the HEU quantity reduces in amplitude, this signature requires sophisticated change detection techniques to catch.

While this example is clearly a toy model, it illustrates the power of combining multiple signals from a scenario to improve detection capabilities. CYCLUS is being used provide more complex synthetic datasets to groups that specialize in developing advanced anomaly detection techniques. An ongoing collaboration with researchers at the Michigan Institute for Data Science⁵ seeks to apply innovative anomaly and change detection techniques to these simulations to investigate detection limits for scenarios with sparse data sets or low signal-to-noise ratios.

⁵ http://midas.umich.edu/




Fig. 7: Time-series data for declared LEU production (top) and facility SWU consumption (middle). Green dots illustrate times at which HEU is also produced. Theratio of power to LEU quantity (bottom) shows deviations from the mean when HEU is produced.

5 Discussion 9

Modality	Physical Signal		
Time-series	Material Flow		
	Power Usage		
Discrete Event	Shipments		
Sparse Data	Inspections		
Geospatially Distributed	Effluent Dispersion		
Energy-series	Neutron Spectra		
Surveillance Images	Resource tracking		
(under development)	Thermal Maps		
	Infrastructure Modifications		

Tab. 1: Data modalities available in CYCLUS and their fuel cycle applications

5 Discussion

CYCLUS models signatures of diversion from a diverse set of facilities in the nuclear fuel cycle and with a variety of data modalities listed in Table 1. One modality with diverse set of potential applications is satellite imagery. We are now developing the software infrastructure to create synthetic satellite images with signatures of diversion. Satellite imagery has a variety of applications: tracking personnel or truck movement patterns, thermal or visible signatures of effluent or heat, or major facility changes such as new or removed buildings.

These diverse datasets can be combined to highlight signatures of diversion that are small enough to be hidden in the noise of individual signals. We have illustrated this technique by combining time-series data for power consumption and declared LEU production for a simple scenario of HEU production in an enrichment facility. More realistic scenarios require advanced anomaly detection techniques such as those being developed at University of Michigan (UM). A collaboration with UM and Sandia National Laboratories (Sandia) is planned to investigate ways to optimize subsets of diverse signal modalities to ensure reliable detection while minimizing resource usage. Additionally, CYCLUS has the capability to produce synthetic signals of inherent physical processes such as neutron spectra of various materials. In this way, CYCLUS simulations can provide theoretical signals to researchers developing experimental detectors in order to test sensitivity and detector response. The CYCLUS fuel cycle simulator is being used as a framework for combining techniques and knowledge from a variety of disciplines to support a cohesive approach to treaty verification.

This work was funded by the Consortium for Verification Technology under Department of Energy National Nuclear Security Administration award number DE-NA0002534

References

- [1] C. MOONEY, "Why climate change is forcing some environmentalists to back nuclear power," *The Washington Post* (2014). http://www.washingtonpost.com/news/wonkblog/wp/2014/12/16/why-climate-change-is-forcing-some-environmentalists-to-back-nuclear-power/ (accessed 2015-09-17).
- [2] H. A. FEIVESON, A. GLASER, Z. MIAN, and F. N. V. V. HIPPEL, *Unmaking the Bomb: A Fissile Material Approach to Nuclear Disarmament and Nonproliferation*, The MIT Press, Cambridge, Massachusetts (2014).
- [3] "Treaty on the Non-Proliferation of Nuclear Weapons (NPT),". http://www.un.org/disarmament/WMD/Nuclear/NPT.shtml (accessed 2015-09-18).

5 Discussion 10

- [4] "The Treaty: CTBTO Preparatory Commission,". https://www.ctbto.org/the-treaty/ (accessed 2015-10-12).
- [5] D. OF STATE, "New START," 2010. http://www.state.gov/t/avc/newstart/index.htm (accessed 2015-10-12).
- [6] K. D. HUFF et al., "Fundamental concepts in the Cyclus nuclear fuel cycle simulation framework," Advances in Engineering Software, 94, 46 (2016). http://www.sciencedirect.com/science/article/pii/S0965997816300229 (accessed 2016-05-16).
- [7] R. CARLSEN et al., "Cyclus v1.3.0," (2015). http://dx.doi.org/10.6084/m9.figshare.1427429.
- [8] K. D. HUFF, P. P. WILSON, and M. J. GIDDEN, "Open Architecture and Modular Paradigm of Cyclus, a Fuel Cycle Simulation Code," *Proc. Transactions of the American Nuclear Society*, volume 104, page 183, 2011.
- [9] M. GIDDEN and P. WILSON, "An Agent-Based Framework for Fuel Cycle Simulation with Recycling," *Proc. Proceedings of GLOBAL*, Salt Lake City, UT, United States, 2013.
- [10] M. J. GIDDEN, An Agent-Based Modeling Framework and Application for the Generic Nuclear Fuel Cycle, PhD thesis, University of Wisconsin, Madison, WI, United States, 2015.
- [11] M. GIDDEN et al., "Agent-Based Dynamic Resource Exchange in Cyclus," *Proc. Proceedings of PHYSOR*, Kyoto, Japan, 2014.
- [12] N. R. JENNINGS, "On agent-based software engineering," *Artificial Intelligence*, **117**, 277 (2000). http://www.sciencedirect.com/science/article/pii/S0004370299001071 (accessed 2015-09-23).
- [13] S. TAYLOR, Agent-based Modeling and Simulation, Palgrave Macmillan (2014).
- [14] A. SCOPATZ, P. K. ROMANO, P. P. WILSON, and K. D. HUFF, "PyNE: Python for Nuclear Engineering," *Proc. Am. Nuc. Soc. Winter Meeting 2012*, volume 107, San Diego, CA, USA, 2012.
- [15] K. D. HUFF, An Integrated Used Fuel Disposition and Generic Repository Model for Fuel Cycle Analysis, PhD thesis, University of Wisconsin Madison, 2013.
- [16] K. M. OLIVER, GENIUSV2: SOFTWARE DESIGN AND MATHEMATICAL FORMULATIONS FOR MULTI-REGION DISCRETE NUCLEAR FUEL CYCLE SIMULATION AND ANALYSIS, Master of Science, Nuclear Engineering, University of Wisconsin, Madison, 2009.
- [17] S. HANNA, G. BRIGGS, and R. HOSKER, JR., "Handbook on Atmospheric Diffusion," DE82002045 (DOE/TIC-11223), National Oceanic and Atmospheric Administration (NOAA) (1982). http://www.wmo.int/pages/prog/www/DPFSERA/documents/workbook.pdf.
- [18] M. RYJINSKI and D. DONOHUE, "IDMS Analysis of Blank Swipe Samples For Uranium Quantity and Isotopic Composition," 2003. http://www.iaea.org/inis/collection/NCLCollectionStore/_Public/33/006/33006984.pdf (accessed 2016-05-16).