Vehicle Dynamics and Simulation

Engine Modelling

Dr B Mason

Loughborough University

Mean value model creation

- System representation (naturally aspirated/gasoline)



$\dot{m} \propto torque$

Note: Boosted engines will also have wastegate position / duty cycle

Mean value engine model

- Origin of air flow is induction into cylinder.
- Airflow is throttled.
- Volumetric flow is given;

$$\dot{V} = V_{disp}\frac{N_{eng}}{120}$$

- Mass flow (speed density equation);

$$\dot{m} = \frac{P_{man}}{RT_{man}}\frac{V_{disp}}{120}N_{eng}$$



Easy so far? Things get worse from here!

Loughborough University

Mean value engine model – volumetric efficiency

- Volumetric efficiency, η

$$\dot{m} = \eta \frac{P_{man}}{RT_{man}} \frac{V_{disp}}{120} N_{eng}$$

$0.5 < \eta < 1.2$

Max is ≈ 1 for Naturally aspirated

- Modifies the speed density equation
- Depends on;
  - Intake and exhaust geometry
  - Intake and exhaust manifold pressure
  - Engine speed
  - Valve timing
  - Acoustic and inertial air effects
  - etc
- Perhaps the most important parameter in all of the mean value models!

Loughborough University

Throttle

- Can be modelled as Laval nozzle of variable throat area (projected cross sectional area).
- For $\frac{P_{man}}{P_{atm}} > 0.528$ mass flow depends on P_{atm} and P_{man};

$$\dot{m} = \frac{C_d A_{th} P_{atm}}{\sqrt{RT_{atm}}} \left(\frac{P_{man}}{P_{atm}}\right)^{\frac{1}{\gamma}} \left\{\frac{2\gamma}{\gamma - 1}\left[1 - \left(\frac{P_{man}}{P_{atm}}\right)^{\frac{\gamma-1}{\gamma}}\right]\right\}^{\frac{1}{2}}$$

- For $\frac{P_{man}}{P_{atm}} \leq 0.528$ flow depends on P_{in} alone (sonic/choked flow);

$$\dot{m} = \frac{C_d A_{th} P_{atm}}{\sqrt{RT_{atm}}} \sqrt{\gamma} \left(\frac{2}{\gamma + 1}\right)^{\frac{\gamma+1}{2(\gamma-1)}}$$



- At max throat flow velocity;

$$\frac{P_{man}}{P_{atm}} = \left(\frac{2}{\gamma + 1}\right)^{\frac{\gamma}{\gamma-1}}$$

Loughborough University

Throttle



- Throttle effective area

$$A_{th} = \frac{\pi D^2}{4}\left\{\left(1 - \frac{\cos\psi}{\cos\psi_0}\right) + \frac{2}{\pi}\left[\frac{a}{\cos\psi}\left(\cos^2\psi - a^2\cos^2\psi_0\right)^{\frac{1}{2}} - \frac{\cos\psi}{\cos\psi_0}\sin^{-1}\left(\frac{a\cos\psi_0}{\cos\psi}\right) - a\left(1-a^2\right)^{\frac{1}{2}} + \sin^{-1}a\right]\right\}$$

- Where

$$a = \frac{d}{D}$$



- Throttle max occurs when

$$\psi = \cos^{-1}(a\cos\psi_0)$$

- So that at ψ_{max}

$$A_{th} \approx \frac{\pi D^2}{4} - dD$$

Loughborough University

Throttle

- Model is valid for frictionless, adiabatic flow through smoothly convergent-divergent nozzle only!
- Discharge coefficient, C_d is used to 'correct' for reality i.e.
- C_d is not constant it depends on;
  - Throttle position, α
  - Throttle pressure ratio, $\frac{P}{P_{amb}}$
- In reality this tends to be mapped for a specific throttle using a flow bench

Intake manifold



- Can be represented as open system of constant volume.
- System stores mass and energy, represented by state variables P and T.
- Mass balance;

$$\frac{dm}{dt} = \dot{m}_{in} - \dot{m}_{out} \qquad (1)$$

- Energy balance;

$$\frac{dE}{dt} = \dot{m}_{in} h_{0_{in}} - \dot{m}_{out} h_{0_{out}} + \dot{Q} \qquad (2)$$

- Where;

$$h_0 = C_p T + \frac{u^2}{2}$$

And the energy within the volume is;

$$E = mc_v T + \frac{mu^2}{2} + mgz$$

Loughborough University

Intake manifold

- Making some assumptions
  - GPE change is 0
  - KE change is 0
- So that;

$$E = mc_vT + \cancel{\frac{mu^2}{2}} + \cancel{mgz} = mc_vT$$

$$h_0 = C_pT + \cancel{\frac{u^2}{2}} = C_pT \qquad (3)$$

- Taking the derivative of $E = mc_vT$ wrt to t;

$$\frac{dE}{dt} = c_vT\frac{dm}{dt} + c_vm\frac{dT}{dt} \qquad (4)$$

- And by substituting 1, 3, 4 into 2;

$$c_vT(\dot{m}_{in} - \dot{m}_{out}) + c_vm\frac{dT}{dt} = \dot{m}_{in}C_pT_{in} - \dot{m}_{out}c_pT_{out} + \dot{Q} \qquad (5)$$

Loughborough University

Intake manifold

- Coupling the energy and mass balances using the ideal gas law;

$$m = \frac{PV}{RT} \qquad (6)$$

- Taking the derivative;

$$\frac{dm}{dt} = \frac{V}{RT}\frac{dP}{dt} - \frac{PV}{RT^2}\frac{dT}{dt} \qquad (7)$$

- Substituting (1, 6 and 7 into 5) and assuming $T_{out} = T$;

$$\boxed{\frac{dT}{dt} = \left[c_p \dot{m}_{in} T_{in} - c_p \dot{m}_{out} T - c_v T \dot{m}_{in} + \frac{dQ}{dt}\right]\frac{RT}{c_v PV}} \qquad (8)$$

$$\boxed{\frac{dP}{dt} = \left[c_p \dot{m}_{in} T_{in} - c_p \dot{m}_{out} T + \frac{dQ}{dt}\right]\frac{R}{c_v V}} \qquad (9)$$

And;

$$\frac{dQ}{dt} = hA_{wall}(T_{wall} - T) \qquad (7)$$

Torque model

- Torque produced is a function of;
  - Spark advance
  - Inducted air mass flow
  - AFR
- Data is usually obtained experimentally and incorporated within a regression model.
- Friction torque is deducted (imep – bmep) to establish output torque.
- Fmep [bar] is calculated;

$$fmep = 0.97 + 0.15\left(\frac{N}{1000}\right) + 0.05\left(\frac{N}{1000}\right)^2$$

- And;

$$T_f = \frac{fmepV_{sw}}{4\pi} = \frac{\left[0.97 + 0.15\left(\frac{N}{1000}\right) + 0.05\left(\frac{N}{1000}\right)^2\right]V_{sw}}{4\pi}$$

Loughborough University

Parameterisation effort

- Model has 5 unknown parameters, C_d, η_{vol}, h, V and V_{disp}.
- With $\eta_{vol} = f(P, T, N, IVO, EVC)$
- η_{vol} is obtained by experiment at some P, T, N, IVO, EVC. Recall;

$$\eta = \frac{120\dot{m}_{actual}}{\rho V_{disp} N_{eng}}$$

- C_d is also experimentally obtained (usually on flow rigs)
- Obtaining h in reality is very difficult and this is normally one of the tuned parameters.
- V and V_{disp} are obtained relatively easily but can also be used to tune the model response to match reality.

Other considerations

- Adding a turbocharger complicates matters significantly and introduces a causality loop.
  - The loop is normally broken by a delay.
- Heat transfer from the exhaust manifold has a significant effect on the turbo performance.
- Errors in the ‘turbo loop’ are accumulated within the loop.
- Each additional volume adds two model states (T and P) increasing significantly the computational burden.
- Volumes of very different sizes result in stiff models i.e. slow and fast dynamics.



Crossley and Cook Model



Crossley and Cook Model

Throttle



Crossley and Cook Model

Intake Manifold



Loughborough University

Crossley and Cook Model

Torque Generation



Loughborough University