

## Bamboo Team Notes

## Contents

## 1 Number theory

1.1	Count primes up to N	1
1.2	Extended Euclide	1
1.3	System of linear equations	1
1.4	Pollard Rho	2

## 2 String

2.1	Suffix Array	2
2.2	Aho Corasick	3
2.3	Z algorithm	3
2.4	Manacher	3
2.5	Suffix Automaton	3

## 3 Combinatorial optimization

## 4 Geometry

4.1	Geometry	4
-----	----------	---

## 5 Numerical algorithms

5.1	Gaus Elimination	6
5.2	Simplex Algorithm	6
5.3	NTT	6
5.4	FFT	7
5.5	Bitwise FFT	7
5.6	FFT chemthan	8
5.7	Partition Formula	9
5.8	generating function	9

## 6 Graph algorithms

6.1	Bridges and Articulations	9
6.2	Bipartite Maximum Matching	9
6.3	General Matching	9
6.4	Dinic Flow	10
6.5	Min Cost-Max Flow	10
6.6	Bounded Feasible Flow	11
6.7	Hungarian Algorithm	11
6.8	Undirected mincut	12
6.9	Eulerian Path/Circuit	12

## 7 Data structures

7.1	Treap	12
7.2	Big Integer	12
7.3	Convex Hull IT	13

## 8 Miscellaneous

8.1	RNG	14
-----	-----	----

## 1 Number theory

## 1.1 Count primes up to N

```
// To initialize, call init_count_primes() first.
// Function count_primes(N) will compute the number of prime numbers lower than
// or equal to N.
//
// Time complexity: Around  $O(N^{0.75})$ 
//
// Constants to configure:
// - MAX is the maximum value of sqrt(N) + 2
bool prime[MAX];
int prec[MAX];
```

```
vector<int> P;
llint rec(llint N, int K) {
    if (N <= 1 || K < 0) return 0;
    if (N <= P[K]) return N-1;

    if (N < MAX && llint(P[K])*P[K] > N) return N-1 - prec[N] + prec[P[K]];
    const int LIM = 250;
    static int memo[LIM*LIM][LIM];
    bool ok = N < LIM*LIM;
    if (ok && memo[N][K]) return memo[N][K];
    llint ret = N/P[K] - rec(N/P[K], K-1) + rec(N, K-1);
    if (ok) memo[N][K] = ret;
    return ret;
}

llint count_primes(llint N) {
    if (N < MAX) return prec[N];
    int K = prec[(int)sqrt(N) + 1];
    return N-1 - rec(N, K) + prec[P[K]];
}

void init_count_primes() {
    prime[2] = true;
    for (int i = 3; i < MAX; i += 2) prime[i] = true;
    for (int i = 3; i+1 < MAX; i += 2) if (prime[i])
        for (int j = i+1; j < MAX; j += i+1)
            prime[j] = false;
    REP(i, MAX) if (prime[i]) P.push_back(i);
    FOR(i, 1, MAX) prec[i] = prec[i-1] + prime[i];
}
```

## 1.2 Extended Euclide

```
int bezout(int a, int b) {
    // return x such that ax + by == gcd(a, b)
    int xa = 1, xb = 0;
    while (b) {
        int q = a / b;
        int r = a - q * b, xr = xa - q * xb;
        a = b; xa = xb;
        b = r; xb = xr;
    }
    return xa;
}

pair<int, int> solve(int a, int b, int c) {
    // solve ax + by == c
    int d = __gcd(a, b);
    int x = bezout(a, b);
    int y = (d - a * x) / b;
    c /= d;
    return make_pair(x * c, y * c);
}

int main() {
    int a = 100, b = 128;
    int c = __gcd(a, b);
    int x = bezout(a, b);
    int y = (c - a * x) / b;
    cout << x << ' ' << y << endl;
    pair<int, int> xy = solve(100, 128, 40);
    cout << xy.first << ' ' << xy.second << endl;
    return 0;
}
```

## 1.3 System of linear equations

```
// extended version, uses diophantine equation solver to solve system of congruent equations
pair<int, int> solve(int a, int b, int c) {
    int cc = c;
    // solve ax + by == c
    int d = __gcd(a, b);
    int x = bezout(a / d, b / d);
    int y = (d - a * x) / b;
    c /= d;
    return make_pair(x * c, y * c);
}

int lcm(int a, int b) {
    return a / __gcd(a, b) * b;
}

// use this if input is large, make sure (#define int long long)
int mul(int a, int b, int p) {
    a %= p, b %= p;
```

```

int q = (int) ((long double) a * b / p);
int r = a * b - q * p;
while (r < 0) r += p;
while (r >= p) r -= p;
return r;
}

int solveSystem(vector<int> a, vector<int> b) {
    // xi mod bi = ai
    int A = a[0], B = b[0];
    // x mod B = A
    for (int i = 1; i < a.size(); ++i) {
        int curB = b[i], curA = a[i];
        // x = Bi + A = curB * j + curA
        pair<int, int> ij = solve(B, -curB, curA - A);
        if (B * ij.first + A != curB * ij.second + curA) return -1;
        int newB = lcm(B, curB);
        int newA = (mul(B, ij.first, newB) + A) % newB;
        if (newA < 0) newA += newB;
        A = newA; B = newB;
        if (i + 1 == a.size()) return A;
    }
    return -1;
}

int main() {
    vector<int> a = {0, 3, 3};
    vector<int> b = {3, 6, 9};
    cout << solveSystem(a, b) << endl;
    return 0;
}

```

## 1.4 Pollard Rho

```

#include <bits/stdc++.h>

using namespace std;

struct PollardRho {
    long long n;
    map<long long, int> ans;
    PollardRho(long long n) : n(n) {}
    long long random(long long u) {
        return abs(rand()) % u;
    }
    long long mul(long long a, long long b, long long p) {
        a %= p; b %= p;
        long long q = (long long) ((long double) a * b / p);
        long long r = a * b - q * p;
        while (r < 0) r += p;
        while (r >= p) r -= p;
        return r;
    }
    long long pow(long long u, long long v, long long n) {
        long long res = 1;
        while (v) {
            if (v & 1) res = mul(res, u, n);
            u = mul(u, u, n);
            v >>= 1;
        }
        return res;
    }
    bool rabin(long long n) {
        if (n < 2) return 0;
        if (n == 2) return 1;
        long long s = 0, m = n - 1;
        while (m % 2 == 0) {
            s++;
            m >>= 1;
        }
        // 1 - 0.9 ^ 40
        for (int it = 1; it <= 40; it++) {
            long long u = random(n - 2) + 2;
            long long f = pow(u, m, n);
            if (f == 1 || f == n - 1) continue;
            for (int i = 1; i < s; i++) {
                f = mul(f, f, n);
                if (f == 1) return 0;
                if (f == n - 1) break;
            }
            if (f != n - 1) return 0;
        }
        return 1;
    }
    long long f(long long x, long long n) {

```

```

        return (mul(x, x, n) + 1) % n;
    }
    long long findfactor(long long n) {
        long long x = random(n - 1) + 2;
        long long y = x;
        long long p = 1;
        while (p == 1) {
            x = f(x, n);
            y = f(f(y, n), n);
            p = __gcd(abs(x - y), n);
        }
        return p;
    }
    void pollard_rho(long long n) {
        if (n <= 1000000) {
            for (int i = 2; i * i <= n; i++) {
                while (n % i == 0) {
                    ans[i]++;
                    n /= i;
                }
            }
            if (n > 1) ans[n]++;
            return;
        }
        if (rabin(n)) {
            ans[n]++;
            return;
        }
        long long p = 0;
        while (p == 0 || p == n) {
            p = findfactor(n);
        }
        pollard_rho(n / p);
        pollard_rho(p);
    }
};

int main() {
    long long n;
    cin >> n;
    PollardRho f(n);
    f.pollard_rho(f.n);
    for (auto x : f.ans) {
        cout << x.first << " " << x.second << endl;
    }
}

```

## 2 String

### 2.1 Suffix Array

```

#include <bits/stdc++.h>

using namespace std;

struct SuffixArray {
    static const int N = 100010;

    int n;
    char *s;
    int sa[N], tmp[N], pos[N];
    int len, cnt[N], lcp[N];

    SuffixArray(char *t) {
        s = t;
        n = strlen(s + 1);
        buildSA();
    }

    bool cmp(int u, int v) {
        if (pos[u] != pos[v]) {
            return pos[u] < pos[v];
        }
        return (u + len <= n && v + len <= n) ? pos[u + len] < pos[v + len] : u > v;
    }

    void radix(int delta) {
        memset(cnt, 0, sizeof cnt);
        for (int i = 1; i <= n; i++) {
            cnt[i + delta] += n ? pos[i + delta] : 0;
        }
        for (int i = 1; i <= N; i++) {
            cnt[i] += cnt[i - 1];

```

```

    }
    for (int i = n; i > 0; i--) {
        int id = sa[i];
        tmp[cnt[id + delta] <= n ? pos[id + delta] : 0]-- = id;
    }
    for (int i = 1; i <= n; i++) {
        sa[i] = tmp[i];
    }
}

void buildSA() {
    for (int i = 1; i <= n; i++) {
        sa[i] = i;
        pos[i] = s[i];
    }
    len = 1;
    while (1) {
        radix(len);
        radix(0);
        tmp[1] = 1;
        for (int i = 2; i <= n; i++) {
            tmp[i] = tmp[i - 1] + cmp(sa[i - 1], sa[i]);
        }
        for (int i = 1; i <= n; i++) {
            pos[sa[i]] = tmp[i];
        }
        if (tmp[n] == n) {
            break;
        }
        len <<= 1;
    }

    len = 0;
    for (int i = 1; i <= n; i++) {
        if (pos[i] == n) {
            continue;
        }
        int j = sa[pos[i] + 1];
        while (s[i + len] == s[j + len]) {
            len++;
        }
        lcp[pos[i]] = len;
        if (len) {
            len--;
        }
    }
}
};

```

## 2.2 Aho Corasick

```

struct AhoCorasick {
    const int N = 30030;

    int fail[N];
    int to[N][26];
    int ending[N];
    int sz;

    void add(const string &s) {
        int node = 1;
        for (int i = 0; i < s.size(); ++i) {
            if (!to[node][s[i] - 'a']) {
                to[node][s[i] - 'a'] = ++sz;
            }
            node = to[node][s[i] - 'a'];
        }
        ending[node] = true;
    }

    void push() {
        queue<int> Q;
        Q.push(1);
        fail[1] = 1;
        while (!Q.empty()) {
            int u = Q.front(); Q.pop();
            for (int i = 0; i < 26; ++i) {
                int &v = to[u][i];
                if (!v) {
                    v = u == 1 ? 1 : to[fail[u]][i];
                } else {
                    fail[v] = u == 1 ? 1 : to[fail[u]][i];
                    Q.push(v);
                }
            }
        }
    }
};

```

## 2.3 Z algorithm

```

vector<int> calcZ(const string &s) {
    int L = 0, R = 0;
    int n = s.size();
    vector<int> Z(n);
    Z[0] = n;
    for (int i = 1; i < n; i++) {
        if (i > R) {
            L = R = i;
            while (R < n && s[R] == s[R - L]) R++;
            Z[i] = R - L; R--;
        } else {
            int k = i - L;
            if (Z[k] < R - i + 1) Z[i] = Z[k];
            else {
                L = i;
                while (R < n && s[R] == s[R - L]) R++;
                Z[i] = R - L; R--;
            }
        }
    }
    return Z;
}

```

## 2.4 Manacher

```

struct Manacher {
    int n;
    vector<int> d; //Radius of odd palindromes
    vector<int> e; //Radius of even palindromes
    int build(char* s) {
        n = strlen(s), d.resize(n), e.resize(n);
        int res = 0;
        int l = 0, r = -1;
        for (int i = 0; i < n; ++i) {
            int k = (i > r) ? 1 : min(d[l + r - i], r - i) + 1;
            while (i - k >= 0 && i + k < n && s[i - k] == s[i + k]) k++;
            d[i] = --k;
            res = max(res, k + k + 1);
            if (r < i + k) {
                l = i - k;
                r = i + k;
            }
        }
        l = 0; r = -1;
        for (int i = 0; i < n; ++i) {
            int k = (i > r) ? 1 : min(e[l + r - i + 1], r - i + 1) + 1;
            while (i - k >= 0 && i + k - 1 < n && s[i - k] == s[i + k - 1]) k++;
            e[i] = --k;
            res = max(res, k + k);
            if (r < i + k - 1) {
                l = i - k;
                r = i + k - 1;
            }
        }
        return res;
    }
};

```

## 2.5 Suffix Automaton

```

//set last = 0 everytime we add new string
struct SuffixAutomaton {
    static const int N = 100000;
    static const int CHARACTER = 26;
    int suf[N * 2], nxt[N * 2][CHARACTER], cnt, last, len[N * 2];

    SuffixAutomaton() {
        memset(suf, -1, sizeof suf);
        memset(nxt, -1, sizeof nxt);
        memset(len, 0, sizeof len);
        last = cnt = 0;
    }
};

```

```

int getNode(int last, int u) {
    int q = nxt[last][u];
    if (len[last] + 1 == len[q]) {
        return q;
    }
    int clone = ++cnt;
    len[clone] = len[last] + 1;
    for (int i = 0; i < CHARACTER; i++) {
        nxt[clone][i] = nxt[q][i];
    }
    while (last != -1 && nxt[last][u] == q) {
        nxt[last][u] = clone;
        last = suf[last];
    }
    suf[clone] = suf[q];
    return suf[q] = clone;
}

void add(int u) {
    if (nxt[last][u] == -1) {
        int newNode = ++cnt;
        len[newNode] = len[last] + 1;
        while (last != -1 && nxt[last][u] == -1) {
            nxt[last][u] = newNode;
            last = suf[last];
        }
        if (last == -1) {
            suf[newNode] = 0;
            last = newNode;
            return;
        }
        suf[newNode] = getNode(last, u);
        last = newNode;
    } else {
        last = getNode(last, u);
    }
}
};

```

## 3 Combinatorial optimization

## 4 Geometry

### 4.1 Geometry

```

#define EPS 1e-6
inline int cmp(double a, double b) { return (a < b - EPS) ? -1 : ((a > b + EPS) ? 1 : 0); }
struct Point {
    double x, y;
    Point() { x = y = 0.0; }
    Point(double x, double y) : x(x), y(y) {}

    Point operator + (const Point& a) const { return Point(x+a.x, y+a.y); }
    Point operator - (const Point& a) const { return Point(x-a.x, y-a.y); }
    Point operator * (double k) const { return Point(x*k, y*k); }
    Point operator / (double k) const { return Point(x/k, y/k); }

    double operator * (const Point& a) const { return x*a.x + y*a.y; } // dot product
    double operator % (const Point& a) const { return x*a.y - y*a.x; } // cross product
    double norm() { return x*x + y*y; }
    double len() { return sqrt(norm()); } // hypot(x, y);
    Point rotate(double alpha) {
        double cosa = cos(alpha), sina = sin(alpha);
        return Point(x * cosa - y * sina, x * sina + y * cosa);
    }
};

double angle(Point a, Point o, Point b) { // min of directed angle AOB & BOA
    a = a - o; b = b - o;
    return acos((a * b) / sqrt(a.norm()) / sqrt(b.norm()));
}

double directed_angle(Point a, Point o, Point b) { // angle AOB, in range [0, 2*PI)
    double t = -atan2(a.y - o.y, a.x - o.x)
        + atan2(b.y - o.y, b.x - o.x);
    while (t < 0) t += 2*PI;
    return t;
}

// Distance from p to Line ab (closest Point --> c)
double distToLine(Point p, Point a, Point b, Point &c) {
    Point ap = p - a, ab = b - a;
    double u = (ap * ab) / ab.norm();
    c = a + (ab * u);
    return (p-c).len();
}

```

```

}
// Distance from p to segment ab (closest Point --> c)
double distToLineSegment(Point p, Point a, Point b, Point &c) {
    Point ap = p - a, ab = b - a;
    double u = (ap * ab) / ab.norm();
    if (u < 0.0) {
        c = Point(a.x, a.y);
        return (p - a).len();
    }
    if (u > 1.0) {
        c = Point(b.x, b.y);
        return (p - b).len();
    }
    return distToLine(p, a, b, c);
}
// NOTE: WILL NOT WORK WHEN a = b = 0.
struct Line {
    double a, b, c;
    Point A, B; // Added for polygon intersect line. Do not rely on assumption that these are valid

    Line(double a, double b, double c) : a(a), b(b), c(c) {}

    Line(Point A, Point B) : A(A), B(B) {
        a = B.y - A.y;
        b = A.x - B.x;
        c = -(a * A.x + b * A.y);
    }

    Line(Point P, double m) {
        a = -m; b = 1;
        c = -(a * P.x + (b * P.y));
    }

    double f(Point A) {
        return a*A.x + b*A.y + c;
    }
};

bool areParallel(Line l1, Line l2) {
    return cmp(l1.a*l2.b, l1.b*l2.a) == 0;
}

bool areSame(Line l1, Line l2) {
    return areParallel(l1, l2) && cmp(l1.c*l2.a, l2.c*l1.a) == 0
        && cmp(l1.c*l2.b, l1.b*l2.c) == 0;
}

bool areIntersect(Line l1, Line l2, Point &p) {
    if (areParallel(l1, l2)) return false;
    double dx = l1.b*l2.c - l2.b*l1.c;
    double dy = l1.c*l2.a - l2.c*l1.a;
    double d = l1.a*l2.b - l2.a*l1.b;
    p = Point(dx/d, dy/d);
    return true;
}

void closestPoint(Line l, Point p, Point &ans) {
    if (fabs(l.b) < EPS) {
        ans.x = -(l.c) / l.a; ans.y = p.y;
        return;
    }
    if (fabs(l.a) < EPS) {
        ans.x = p.x; ans.y = -(l.c) / l.b;
        return;
    }
    Line perp(l.b, -l.a, -(l.b*p.x - l.a*p.y));
    areIntersect(l, perp, ans);
}

void reflectionPoint(Line l, Point p, Point &ans) {
    Point b;
    closestPoint(l, p, b);
    ans = p + (b - p) * 2;
}

struct Circle : Point {
    double r;
    Circle(double x = 0, double y = 0, double r = 0) : Point(x, y), r(r) {}
    Circle(Point p, double r) : Point(p), r(r) {}
    bool contains(Point p) { return (>this - p).len() <= r + EPS; }
};

// Find common tangents to 2 circles
// Tested:
// - http://codeforces.com/gym/100803/ - H
// Helper method
void tangents(Point c, double r1, double r2, vector<Line> &ans) {
    double r = r2 - r1;
    double z = sqrt(c.x * c.x + c.y * c.y);
    double d = z - sqrt(r);
    if (d < -EPS) return;
    d = sqrt(fabs(d));
    Line l((c.x + r + c.y * d) / z,
        (c.y + r - c.x * d) / z,
        r1);
    ans.push_back(l);
}

// Actual method: returns vector containing all common tangents
vector<Line> tangents(Circle a, Circle b) {
    vector<Line> ans; ans.clear();
}

```

```

for (int i=-1; i<=1; i+=2)
    for (int j=-1; j<=1; j+=2)
        tangents(b-a, a.r+1, b.r+j, ans);
for (int i = 0; i < ans.size(); ++i)
    ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;
vector<Line> ret;
for (int i = 0; i < (int) ans.size(); ++i) {
    bool ok = true;
    for (int j = 0; j < i; ++j)
        if (areSame(ret[j], ans[i])) {
            ok = false;
            break;
        }
    if (ok) ret.push_back(ans[i]);
}
return ret;
}

// Circle & line intersection
vector<Point> intersection(Line l, Circle cir) {
    double r = cir.r, a = l.a, b = l.b, c = l.c + l.a*cir.x + l.b*cir.y;
    vector<Point> res;
    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b)+EPS) return res;
    else if (fabs(c*c - r*r*(a*a+b*b)) < EPS) {
        res.push_back(Point(x0, y0) + Point(cir.x, cir.y));
        return res;
    }
    else {
        double d = r*r - c*c/(a*a+b*b);
        double mult = sqrt(d / (a*a+b*b));
        double ax, ay, bx, by;
        ax = x0 + b * mult;
        bx = x0 - b * mult;
        ay = y0 + a * mult;
        by = y0 - a * mult;
        res.push_back(Point(ax, ay) + Point(cir.x, cir.y));
        res.push_back(Point(bx, by) + Point(cir.x, cir.y));
        return res;
    }
}

// helper functions for commonCircleArea
double cir_area_solve(double a, double b, double c) {
    return acos((a*a + b*b - c*c) / 2 / a / b);
}

double cir_area_cut(double a, double r) {
    double s1 = a * r * r / 2;
    double s2 = sin(a) * r * r / 2;
    return s1 - s2;
}

double commonCircleArea(Circle c1, Circle c2) { //return the common area of two circle
    if (c1.r < c2.r) swap(c1, c2);
    double d = (c1 - c2).len();
    if (d + c2.r <= c1.r + EPS) return c2.r*c2.r*M_PI;
    if (d >= c1.r + c2.r - EPS) return 0.0;
    double a1 = cir_area_solve(d, c1.r, c2.r);
    double a2 = cir_area_solve(d, c2.r, c1.r);
    return cir_area_cut(a1*2, c1.r) + cir_area_cut(a2*2, c2.r);
}

// Check if 2 circle intersects. Return true if 2 circles touch
bool areIntersect(Circle u, Circle v) {
    if (cmp((u - v).len(), u.r + v.r) > 0) return false;
    if (cmp((u - v).len() + v.r, u.r) < 0) return false;
    if (cmp((u - v).len() + u.r, v.r) < 0) return false;
    return true;
}

// If 2 circle touches, will return 2 (same) points
// If 2 circle are same -> be careful
vector<Point> circleIntersect(Circle u, Circle v) {
    vector<Point> res;
    if (!areIntersect(u, v)) return res;
    double d = (u - v).len();
    double alpha = acos((u.r * u.r + d*d - v.r * v.r) / 2.0 / u.r / d);

    Point p1 = (v - u).rotate(alpha);
    Point p2 = (v - u).rotate(-alpha);
    res.push_back(p1 / p1.len() * u.r + u);
    res.push_back(p2 / p2.len() * u.r + u);
    return res;
}

Point centroid(Polygon p) {
    Point c(0, 0);
    double scale = 6.0 * signed_area(p);
    for (int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*(p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

// Cut a polygon with a line. Returns one half.
// To return the other half, reverse the direction of Line l (by negating l.a, l.b)
// The line must be formed using 2 points
Polygon polygon_cut(const Polygon& P, Line l) {

```

```

Polygon Q;
for (int i = 0; i < P.size(); ++i) {
    Point A = P[i], B = (i == P.size()-1) ? P[0] : P[i+1];
    if (ccw(l.A, l.B, A) != -1) Q.push_back(A);
    if (ccw(l.A, l.B, A)+ccw(l.A, l.B, B) < 0) {
        Point p; areIntersect(Line(A, B), l, p);
        Q.push_back(p);
    }
}
return Q;
}

// Find intersection of 2 convex polygons
// Helper method
bool intersect_lpt(Point a, Point b,
    Point c, Point d, Point &r) {
    double D = (b - a) % (d - c);
    if (cmp(D, 0) == 0) return false;
    double t = ((c - a) % (d - c)) / D;
    double s = -((a - c) % (b - a)) / D;
    r = a + (b - a) * t;
    return cmp(t, 0) >= 0 && cmp(t, 1) <= 0 && cmp(s, 0) >= 0 && cmp(s, 1) <= 0;
}

Polygon convex_intersect(Polygon P, Polygon Q) {
    const int n = P.size(), m = Q.size();
    int a = 0, b = 0, aa = 0, ba = 0;
    enum { Pin, Qin, Unknown } in = Unknown;
    Polygon R;
    do {
        int a1 = (a+n-1) % n, b1 = (b+m-1) % m;
        double C = (P[a] - P[a1]) % (Q[b] - Q[b1]);
        double A = (P[a1] - Q[b]) % (P[a] - Q[b]);
        double B = (Q[b1] - P[a]) % (Q[b] - P[a]);
        Point r;
        if (intersect_lpt(P[a], P[a1], Q[b], Q[b1], r)) {
            if (in == Unknown) aa = ba = 0;
            R.push_back(r);
            in = B > 0 ? Pin : A > 0 ? Qin : in;
        }
        if (C == 0 && B == 0 && A == 0) {
            if (in == Pin) { b = (b + 1) % m; ++ba; }
            else { a = (a + 1) % n; ++aa; }
        }
        else if (C > 0) {
            if (A > 0) { if (in == Pin) R.push_back(P[a]); a = (a+1)%n; ++aa; }
            else { if (in == Qin) R.push_back(Q[b]); b = (b+1)%m; ++ba; }
        }
        else {
            if (B > 0) { if (in == Qin) R.push_back(Q[b]); b = (b+1)%m; ++ba; }
            else { if (in == Pin) R.push_back(P[a]); a = (a+1)%n; ++aa; }
        }
    } while ((aa < n || ba < m) && aa < 2*n && ba < 2*m);
    if (in == Unknown) {
        if (in_convex(Q, P[0])) return P;
        if (in_convex(P, Q[0])) return Q;
    }
    return R;
}

// Find the diameter of polygon.
// Rotating callipers
double convex_diameter(Polygon pt) {
    const int n = pt.size();
    int is = 0, js = 0;
    for (int i = 1; i < n; ++i) {
        if (pt[i].y > pt[is].y) is = i;
        if (pt[i].y < pt[js].y) js = i;
    }
    double maxd = (pt[is]-pt[js]).norm();
    int i, maxi, j, maxj;
    i = maxi = is;
    j = maxj = js;
    do {
        int jj = j+1; if (jj == n) jj = 0;
        if ((pt[i] - pt[jj]).norm() > (pt[i] - pt[j]).norm()) j = (j+1) % n;
        else i = (i+1) % n;
        if ((pt[i]-pt[j]).norm() > maxd) {
            maxd = (pt[i]-pt[j]).norm();
            maxi = i; maxj = j;
        }
    } while (i != is || j != js);
    return maxd; /* farthest pair is (maxi, maxj). */
}

// Check if we can form triangle with edges x, y, z.
bool isSquare(long long x) { /* */ }
bool isIntegerCoordinates(int x, int y, int z) {
    long long s = (long long) (x+y+z)*(x+y-z)*(x+z-y)*(y+z-x);
    return (s%4==0 && isSquare(s/4));
}

// Pick theorem
// Given non-intersecting polygon.
// S = area
// I = number of integer points strictly Inside
// B = number of points on sides of polygon
// S = I + B/2 - 1
// Smallest enclosing circle:

```

```
// Given N points. Find the smallest circle enclosing these points.
// Amortized complexity: O(N)
struct SmallestEnclosingCircle {
    Circle getCircle(vector<Point> points) {
        assert(!points.empty());
        random_shuffle(points.begin(), points.end());
        Circle c(points[0], 0);
        int n = points.size();
        for (int i = 1; i < n; i++)
            if ((points[i] - c).len() > c.r + EPS) {
                c = Circle(points[i], 0);
                for (int j = 0; j < i; j++)
                    if ((points[j] - c).len() > c.r + EPS) {
                        c = Circle((points[i] + points[j]) / 2, (points[i] - points[j]).len() / 2);
                        for (int k = 0; k < j; k++)
                            if ((points[k] - c).len() > c.r + EPS)
                                c = getCircle(points[i], points[j], points[k]);
                    }
            }
        return c;
    }
};

// NOTE: This code work only when a, b, c are not collinear and no 2 points are same --> DO NOT
// copy and use in other cases.
Circle getCircle(Point a, Point b, Point c) {
    assert(a != b && b != c && a != c);
    assert(ccw(a, b, c));
    double d = 2.0 * (a.x * (b.y - c.y) + b.x * (c.y - a.y) + c.x * (a.y - b.y));
    assert(fabs(d) > EPS);
    double x = (a.norm() * (b.y - c.y) + b.norm() * (c.y - a.y) + c.norm() * (a.y - b.y)) / d;
    double y = (a.norm() * (c.x - b.x) + b.norm() * (a.x - c.x) + c.norm() * (b.x - a.x)) / d;
    Point p(x, y);
    return Circle(p, (p - a).len());
}
};
```

## 5 Numerical algorithms

### 5.1 Gauss Elimination

```
const int INF = 1e9;
const double EPS = 1e-9;
int gauss(vector<vector<double>> &a, vector<double> &ans) {
    int m = a.size(), n = a[0].size() - 1;
    vector<int> where(n, -1); // corresponding row for each column
    for (int row = 0, col = 0; col < n; ++col) {
        // find the maximum abs value on the current column to reduce precision errors
        int maxRow = row;
        for (int i = row + 1; i < m; ++i) {
            if (abs(a[i][col]) > abs(a[maxRow][col]))
                maxRow = i;
        }
        // if cannot find anything rather than zero then forget the current column
        if (abs(a[maxRow][col]) < EPS) continue;
        if (maxRow != row) swap(a[maxRow], a[row]);
        where[col] = row;
        for (int i = 0; i < m; ++i) if (i != row) {
            double coef = a[i][col] / a[row][col];
            for (int j = col; j < n; ++j) {
                a[i][j] -= a[row][j] * coef;
            }
        }
        ++row; // only when found a non-zero element
    }
    ans.assign(m, 0); // default value = 0
    for (int i = 0; i < n; ++i) if (where[i] != -1) {
        ans[i] = a[where[i]][n] / a[where[i]][i];
    }
    // recheck
    for (int i = 0; i < m; ++i) {
        double sum = 0;
        for (int j = 0; j < n; ++j) {
            sum += a[i][j] * ans[j];
        }
        if (abs(sum - a[i][n]) > EPS) return 0; // no solution
    }
    // search for independent variables
    for (int i = 0; i < n; ++i) if (where[i] == -1) return INF; // infinite many solution
    return 1; // one solution saved in vector ans
}
```

### 5.2 Simplex Algorithm

```
/**
 * minimize c^T * x
 * subject to Ax <= b
 * and x >= 0
 * The input matrix a will have the following form
 * 0 c c c c
 * b A A A A
 * b A A A A
 * b A A A A
 * Result vector will be: val x x x x
 */
typedef long double ld;
const ld EPS = 1e-8;
struct LPSolver {
    static vector<ld> simplex(vector<vector<ld>> a) {
        int n = (int) a.size() - 1;
        int m = (int) a[0].size() - 1;
        vector<int> left(m + 1);
        vector<int> up(m + 1);
        iota(left.begin(), left.end(), m);
        iota(up.begin(), up.end(), 0);
        auto pivot = [&](int x, int y) {
            swap(left[x], up[y]);
            ld k = a[x][y];
            a[x][y] = 1;
            vector<int> pos;
            for (int j = 0; j <= m; j++) {
                a[x][j] /= k;
                if (fabs(a[x][j]) > EPS) pos.push_back(j);
            }
            for (int i = 0; i <= n; i++) {
                if (fabs(a[i][y]) < EPS || i == x) continue;
                k = a[i][y];
                a[i][y] = 0;
                for (int j : pos) a[i][j] -= k * a[x][j];
            }
        };
        while (1) {
            int x = -1;
            for (int i = 1; i <= n; i++) {
                if (a[i][0] < -EPS && (x == -1 || a[i][0] < a[x][0])) {
                    x = i;
                }
            }
            if (x == -1) break;
            int y = -1;
            for (int j = 1; j <= m; j++) {
                if (a[x][j] < -EPS && (y == -1 || a[x][j] < a[x][y])) {
                    y = j;
                }
            }
            if (y == -1) return vector<ld>(); // infeasible
            pivot(x, y);
        }
        while (1) {
            int y = -1;
            for (int j = 1; j <= m; j++) {
                if (a[0][j] > EPS && (y == -1 || a[0][j] > a[0][y])) {
                    y = j;
                }
            }
            if (y == -1) break;
            int x = -1;
            for (int i = 1; i <= n; i++) {
                if (a[i][y] > EPS && (x == -1 || a[i][y] < a[x][y] / a[x][y])) {
                    x = i;
                }
            }
            if (x == -1) return vector<ld>(); // unbounded
            pivot(x, y);
        }
        vector<ld> ans(m + 1);
        for (int i = 1; i <= n; i++) {
            if (left[i] <= m) ans[left[i]] = a[i][0];
        }
        ans[0] = -a[0][0];
        return ans;
    }
};
```

### 5.3 NTT

```
//Poly Invert: R(2n) = 2R(n) - R(n) ^ 2 * F where R(z) = invert F(z)
//Poly Sqrt: 2 * S(2n) = S(n) + F * S(n) ^ -1
const int MOD = 998244353;
struct NTT {
    int base = 1;
```

```

int maxBase = 0;
int root = 2;
vector<int> w = {0, 1};
vector<int> rev = {0, 1};
NTT () {
    int u = MOD - 1;
    while (u % 2 == 0) {
        u >>= 1;
        maxBase++;
    }
    while (power(root, 1 << maxBase) != 1 || power(root, 1 << (maxBase - 1)) == 1) root++;
}
void ensure(int curBase) {
    assert(curBase <= maxBase);
    if (curBase <= base) return;
    rev.resize(1 << curBase);
    for (int i = 0; i < (1 << curBase); i++) {
        rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (curBase - 1));
    }
    w.resize(1 << curBase);
    for (; base < curBase; base++) {
        int wc = power(root, 1 << (maxBase - base - 1));
        for (int i = 1 << (base - 1); i < (1 << base); i++) {
            w[i << 1] = w[i];
            w[i << 1 | 1] = mul(w[i], wc);
        }
    }
}
void fft(vector<int> &a) {
    int n = a.size();
    int curBase = 0;
    while ((1 << curBase) < n) curBase++;
    int shift = base - curBase;
    for (int i = 0; i < n; i++) {
        if (i < (rev[i] >> shift)) swap(a[i], a[rev[i] >> shift]);
    }
    for (int k = 1; k < n; k <<= 1) {
        for (int i = 0; i < n; i++) {
            for (int j = i; j < n; j += k * 2) {
                int foo = a[j];
                int bar = mul(a[j + k], w[i + k]);
                a[j] = add(foo, bar);
                a[j + k] = sub(foo, bar);
            }
        }
    }
}
vector<int> mult(vector<int> a, vector<int> b) {
    int nResult = a.size() + b.size() - 1;
    int curBase = 0;
    while ((1 << curBase) < nResult) curBase++;
    ensure(curBase);
    int n = 1 << curBase;
    a.resize(n), b.resize(n);
    fft(a);
    fft(b);
    int invN = inv(n);
    for (int i = 0; i < n; i++) {
        a[i] = mul(mul(a[i], b[i]), invN);
    }
    reverse(a.begin() + 1, a.end());
    fft(a);
    a.resize(nResult);
    return a;
}
vector<int> polyInv(vector<int> r, vector<int> f) {
    vector<int> foo = mult(r, f);
    foo.resize(f.size());
    foo[0] = sub(2, foo[0]);
    for (int i = 1; i < foo.size(); i++) {
        foo[i] = sub(0, foo[i]);
    }
    vector<int> res = mult(r, foo);
    res.resize(f.size());
    return res;
}
vector<int> polySqrt(vector<int> s, vector<int> invS, vector<int> f) {
    vector<int> res = mult(f, invS);
    res.resize(f.size());
    for (int i = 0; i < s.size(); i++) {
        res[i] = add(res[i], s[i]);
    }
    for (int i = 0; i < res.size(); i++) {
        res[i] = mul(res[i], INV_2);
    }
    return res;
}
vector<int> getSqrt(vector<int> c, int sz) {
    vector<int> sqrtC = {1}, invSqrtC = {1}; //change this if c[0] != 1
    for (int k = 1; k < (1 << sz); k <<= 1) {
        vector<int> foo(c.begin(), c.begin() + (k * 2));
        vector<int> bar = sqrtC;

```

```

        bar.resize(bar.size() * 2, 0);
        vector<int> tempInv = polyInv(invSqrtC, bar);
        sqrtC = polySqrt(sqrtC, tempInv, foo);
        invSqrtC = polyInv(invSqrtC, sqrtC);
    }
    return sqrtC;
}
vector<int> getInv(vector<int> c, int sz) {
    vector<int> res = {INV_2}; // change this if c[0] != 2
    for (int k = 1; k < (1 << sz); k <<= 1) {
        vector<int> foo(c.begin(), c.begin() + (k * 2));
        res = polyInv(res, foo);
    }
    return res;
}
} ntt;

```

## 5.4 FFT

```

typedef complex<double> cmplx;
typedef vector<complex<double> > VC;
const double PI = acos(-1);
struct FFT {
    static void fft(VC &u, int sign) {
        int n = u.size();
        double theta = 2. * PI * sign / n;
        for (int m = n; m >= 2; m >>= 1, theta *= 2.) {
            cmplx w(1, 0), wDelta = polar(1., theta);
            for (int i = 0, mh = m >> 1; i < mh; i++) {
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    cmplx temp = u[j] - u[k];
                    u[j] += u[k];
                    u[k] = w * temp;
                }
                w *= wDelta;
            }
        }
        for (int i = 1, j = 0; i < n; i++) {
            for (int k = n >> 1; k > (j ^ k); k >>= 1);
            if (j < i) {
                swap(u[i], u[j]);
            }
        }
    }
}
static vector<int> mul(const vector<int> &a, const vector<int> &b) {
    int newSz = a.size() + b.size() - 1;
    int fftSz = 1;
    while (fftSz < newSz) {
        fftSz <<= 1;
    }
    VC aa(fftSz, 0.), bb(fftSz, 0.);
    for (int i = 0; i < a.size(); i++) {
        aa[i] = a[i];
    }
    for (int i = 0; i < b.size(); i++) {
        bb[i] = b[i];
    }
    fft(aa, 1);
    fft(bb, 1);
    for (int i = 0; i < fftSz; i++) {
        aa[i] *= bb[i];
    }
    fft(aa, -1);
    vector<int> res(newSz);
    for (int i = 0; i < newSz; i++) {
        res[i] = (int)(aa[i].real() / fftSz + 0.5);
    }
    return res;
}
};

```

## 5.5 Bitwise FFT

```

/*
 * matrix:
 * +1 +1
 * +1 -1
 */
void XORFFT(int a[], int n, int p, int invert) {
    for (int i = 1; i < n; i <<= 1) {
        for (int j = 0; j < n; j += i << 1) {

```

```

    for (int k = 0; k < i; k++) {
        int u = a[j + k], v = a[i + j + k];
        a[j + k] = u + v;
        if (a[j + k] >= p) a[j + k] -= p;
        a[i + j + k] = u - v;
        if (a[i + j + k] < 0) a[i + j + k] += p;
    }
}

if (invert) {
    long long inv = fpow(n, p - 2, p);
    for (int i = 0; i < n; i++) a[i] = a[i] * inv % p;
}

/*
 * Matrix:
 * +1 +1
 * +1 +0
 */
void ORFFT(int a[], int n, int p, int invert) {
    for (int i = 1; i < n; i <= 1) {
        for (int j = 0; j < n; j += i <= 1) {
            for (int k = 0; k < i; k++) {
                int u = a[j + k], v = a[i + j + k];
                if (!invert) {
                    a[j + k] = u + v;
                    a[i + j + k] = u;
                    if (a[j + k] >= p) a[j + k] -= p;
                }
                else {
                    a[j + k] = v;
                    a[i + j + k] = u - v;
                    if (a[i + j + k] < 0) a[i + j + k] += p;
                }
            }
        }
    }
}

/*
 * matrix:
 * +0 +1
 * +1 +1
 */
void ANDFFT(int a[], int n, int p, int invert) {
    for (int i = 1; i < n; i <= 1) {
        for (int j = 0; j < n; j += i <= 1) {
            for (int k = 0; k < i; k++) {
                int u = a[j + k], v = a[i + j + k];
                if (!invert) {
                    a[j + k] = v;
                    a[i + j + k] = u + v;
                    if (a[i + j + k] >= p) a[i + j + k] -= p;
                }
                else {
                    a[j + k] = v - u;
                    if (a[j + k] < 0) a[j + k] += p;
                    a[i + j + k] = u;
                }
            }
        }
    }
}
}

```

## 5.6 FFT chemthan

```

#define double long double
namespace FFT {
    const int maxf = 1 << 17;
    struct cp {
        double x, y;
        cp(double x = 0, double y = 0) : x(x), y(y) {}
        cp operator + (const cp& rhs) const {
            return cp(x + rhs.x, y + rhs.y);
        }
        cp operator - (const cp& rhs) const {
            return cp(x - rhs.x, y - rhs.y);
        }
        cp operator * (const cp& rhs) const {
            return cp(x * rhs.x - y * rhs.y, x * rhs.y + y * rhs.x);
        }
        cp operator !() const {
            return cp(x, -y);
        }
    } rts[maxf + 1];
    cp fa[maxf], fb[maxf];
    cp fc[maxf], fd[maxf];

    int bitrev[maxf];
}

```

```

void fftinit() {
    int k = 0; while ((1 << k) < maxf) k++;
    bitrev[0] = 0;
    for (int i = 1; i < maxf; i++) {
        bitrev[i] = bitrev[i >> 1] >> 1 | ((i & 1) << k - 1);
    }
    double PI = acos((double) -1.0);
    rts[0] = rts[maxf] = cp(1, 0);
    for (int i = 1; i + i <= maxf; i++) {
        rts[i] = cp(cos(i * 2 * PI / maxf), sin(i * 2 * PI / maxf));
    }
    for (int i = maxf / 2 + 1; i < maxf; i++) {
        rts[i] = !rts[maxf - i];
    }
}

void dft(cp a[], int n, int sign) {
    static int isinit;
    if (!isinit) {
        isinit = 1;
        fftinit();
    }
    int d = 0; while ((1 << d) * n != maxf) d++;
    for (int i = 0; i < n; i++) {
        if (i < (bitrev[i] >> d)) {
            swap(a[i], a[bitrev[i] >> d]);
        }
    }
    for (int len = 2; len <= n; len <= 1) {
        int delta = maxf / len * sign;
        for (int i = 0; i < n; i += len) {
            cp *x = a + i, *y = a + i + (len >> 1), *w = sign > 0 ? rts : rts + maxf;
            for (int k = 0; k < len; k++) {
                cp z = *y * *w;
                *y = *x - z, *x = *x + z;
                x++, y++, w += delta;
            }
        }
    }
    if (sign < 0) {
        for (int i = 0; i < n; i++) {
            a[i].x /= n;
            a[i].y /= n;
        }
    }
}

void multiply(int a[], int b[], int na, int nb, long long c[]) {
    int n = na + nb - 1; while (n != (n & -n)) n += n & -n;
    for (int i = 0; i < n; i++) fa[i] = fb[i] = cp();
    for (int i = 0; i < na; i++) fa[i] = cp(a[i]);
    for (int i = 0; i < nb; i++) fb[i] = cp(b[i]);
    dft(fa, n, 1), dft(fb, n, 1);
    for (int i = 0; i < n; i++) fa[i] = fa[i] * fb[i];
    dft(fa, n, -1);
    for (int i = 0; i < n; i++) c[i] = (long long) floor(fa[i].x + 0.5);
}

void multiply(int a[], int b[], int na, int nb, int c[], int mod = (int) 1e9 + 7) {
    int n = na + nb - 1;
    while (n != (n & -n)) n += n & -n;
    for (int i = 0; i < n; i++) fa[i] = fb[i] = cp();
    static const int magic = 15;
    for (int i = 0; i < na; i++) fa[i] = cp(a[i] >> magic, a[i] & (1 << magic) - 1);
    for (int i = 0; i < nb; i++) fb[i] = cp(b[i] >> magic, b[i] & (1 << magic) - 1);
    dft(fa, n, 1), dft(fb, n, 1);
    for (int i = 0; i < n; i++) {
        int j = (n - i) % n;
        cp x = fa[i] + !fa[j];
        cp y = fb[i] + !fb[j];
        cp z = !fa[j] - fa[i];
        cp t = !fb[j] - fb[i];
        fc[i] = (x * t + y * z) * cp(0, 0.25);
        fd[i] = x * y * cp(0, 0.25) + z * t * cp(-0.25, 0);
    }
    dft(fc, n, -1), dft(fd, n, -1);
    for (int i = 0; i < n; i++) {
        long long u = ((long long) floor(fc[i].x + 0.5)) % mod;
        long long v = ((long long) floor(fd[i].x + 0.5)) % mod;
        long long w = ((long long) floor(fd[i].y + 0.5)) % mod;
        c[i] = ((u << 15) + v + (w << 30)) % mod;
    }
}

vector<int> multiply(vector<int> a, vector<int> b, int mod = (int) 1e9 + 7) {
    static int fa[maxf], fb[maxf], fc[maxf];
    int na = a.size(), nb = b.size();
    for (int i = 0; i < na; i++) fa[i] = a[i];
    for (int i = 0; i < nb; i++) fb[i] = b[i];
    multiply(fa, fb, na, nb, fc, mod);
    int k = na + nb - 1;
    vector<int> res(k);
    for (int i = 0; i < k; i++) res[i] = fc[i];
    return res;
}
}

```



## 5.7 Partition Formula

```
/**
 * generating function : PI: (1 / (1 - x ^ k))
 * p(n) = p(n-1) + p(n-2) - p(n-5) - p(n-7) + p(n-12) + p(n-15) - p(n-22) - ...
 * p_k = k * (3k - 1) / 2 with k = 1, -1, 2, -2, 3, -3, ...
 */
```

## 5.8 generating function

```
// 1 / ( (1-ax) ^ (k+1) ) = sum_{0->INF} { a^n * C(n+k, k) * x^n }
```

# 6 Graph algorithms

## 6.1 Bridges and Articulations

```
vector<int> adj[MAXN];
int num[MAXN];
int low[MAXN];
int tms;
int root, nchild;

void dfs(int u, int p = -1) {
    num[u] = low[u] = ++tms;
    for (int i = 0; i < (int) adj[u].size(); i++) {
        int v = adj[u][i];
        if (!num[v]) {
            if (u == root) nchild++;
            dfs(v, u);
            if (low[v] >= num[u]) {
                //u is an articulation point
            }
            if (low[v] > num[u]) {
                //u -> v is a bridge
            }
            low[u] = min(low[u], low[v]);
        }
        else if (v != p) {
            low[u] = min(low[u], num[v]);
        }
    }
}

int main() {
    dfs(root = 0);
    if (nchild > 1) {
        //root is an articulation point
    }
    return 0;
}
```

## 6.2 Bipartite Maximum Matching

```
struct BipartiteGraph {
    vector< vector<int> > a;
    vector<int> match;
    vector<bool> was;
    int m, n;

    BipartiteGraph(int m, int n) {
        // zero-indexed
        this->m = m; this->n = n;
        a.resize(m);
        match.assign(n, -1);
        was.assign(n, false);
    }

    void addEdge(int u, int v) {
        a[u].push_back(v);
    }

    bool dfs(int u) {
```

```
        for (int v : a[u]) if (!was[v]) {
            was[v] = true;
            if (match[v] == -1 || dfs(match[v])) {
                match[v] = u;
                return true;
            }
        }
        return false;
    }

    int maximumMatching() {
        vector<int> buffer;
        for (int i = 0; i < m; ++i) buffer.push_back(i);
        bool stop = false;
        int ans = 0;
        do {
            stop = true;
            for (int i = 0; i < n; ++i) was[i] = false;
            for (int i = (int)buffer.size() - 1; i >= 0; --i) {
                int u = buffer[i];
                if (dfs(u)) {
                    ++ans;
                    stop = false;
                    buffer[i] = buffer.back();
                    buffer.pop_back();
                }
            }
        } while (!stop);
        return ans;
    }

    vector<int> konig() {
        // returns minimum vertex cover, run this after maximumMatching()
        vector<bool> matched(m);
        for (int i = 0; i < n; ++i) {
            if (match[i] != -1) matched[match[i]] = true;
        }
        queue<int> Q;
        was.assign(m + n, false);
        for (int i = 0; i < m; ++i) {
            if (!matched[i]) {
                was[i] = true;
                Q.push(i);
            }
        }
        while (!Q.empty()) {
            int u = Q.front(); Q.pop();
            for (int v : a[u]) if (!was[m + v]) {
                was[m + v] = true;
                if (match[v] != -1 && !was[match[v]]) {
                    was[match[v]] = true;
                    Q.push(match[v]);
                }
            }
        }
        vector<int> res;
        for (int i = 0; i < m; ++i) {
            if (!was[i]) res.push_back(i);
        }
        for (int i = m; i < m + n; ++i) {
            if (was[i]) res.push_back(i);
        }
        return res;
    }
};
```

## 6.3 General Matching

```
/*
 * Complexity: O(E*sqrt(V))
 * Indexing from 1
 */
struct Blossom {
    static const int MAXV = 1e3 + 5;
    static const int MAXE = 1e6 + 5;
    int n, E, lft[MAXV], next[MAXE], adj[MAXE];
    int nxt[MAXV], mat[MAXV], dad[MAXV], col[MAXV];
    int que[MAXV], qh, qt;
    int vis[MAXV], act[MAXV];
    int tag, total;

    void init(int n) {
        this->n = n;
        for (int i = 0; i <= n; i++) {
```

```

        lst[i] = nxt[i] = mat[i] = vis[i] = 0;
    }
    E = 1, tag = total = 0;
}
void add(int u, int v) {
    if (!mat[u] && !mat[v]) mat[u] = v, mat[v] = u, total++;
    E++, adj[E] = v, next[E] = lst[u], lst[u] = E;
    E++, adj[E] = u, next[E] = lst[v], lst[v] = E;
}
int lca(int u, int v) {
    tag++;
    for(;; swap(u, v)) {
        if (u) {
            if (vis[u == dad[u]] == tag) {
                return u;
            }
            vis[u] = tag;
            u = nxt[mat[u]];
        }
    }
}
void blossom(int u, int v, int g) {
    while (dad[u] != g) {
        nxt[u] = v;
        if (col[mat[u]] == 2) {
            col[mat[u]] = 1;
            que[++qt] = mat[u];
        }
        if (u == dad[u]) dad[u] = g;
        if (mat[u] == dad[mat[u]]) dad[mat[u]] = g;
        v = mat[u];
        u = nxt[v];
    }
}
int augment(int s) {
    for (int i = 1; i <= n; i++) {
        col[i] = 0;
        dad[i] = 1;
    }
    qh = 0; que[qt = 1] = s; col[s] = 1;
    for (int u, v, i; qh < qt; ) {
        act[u = que[++qh]] = 1;
        for (i = lst[u]; i; i = next[i]) {
            v = adj[i];
            if (col[v] == 0) {
                nxt[v] = u;
                col[v] = 2;
                if (!mat[v]) {
                    for (; v; v = u) {
                        u = mat[nxt[v]];
                        mat[v] = nxt[v];
                        mat[nxt[v]] = v;
                    }
                    return 1;
                }
                col[mat[v]] = 1;
                que[++qt] = mat[v];
            }
            else if (dad[u] != dad[v] && col[v] == 1) {
                int g = lca(u, v);
                blossom(u, v, g);
                blossom(v, u, g);
                for (int j = 1; j <= n; j++) {
                    dad[j] = dad[dad[j]];
                }
            }
        }
    }
    return 0;
}
int maxmat() {
    for (int i = 1; i <= n; i++) {
        if (!mat[i]) {
            total += augment(i);
        }
    }
    return total;
}
}

```

## 6.4 Dinic Flow

```

const int V = 1e5;
const int INF = 1e9;
struct Flow {
    vector<int> adj[V];
    int to[V], c[V], f[V];
    int n, s, t, cnt;

```

```

    int d[V];
    int cur[V];
    Flow(int n, int s, int t) {
        this->n = n;
        this->s = s;
        this->t = t;
        cnt = 0;
    }
    int addEdge(int u, int v, int _c) {
        to[cnt] = v, c[cnt] = _c, f[cnt] = 0;
        adj[u].push_back(cnt++);
        to[cnt] = u, c[cnt] = 0, f[cnt] = 0;
        adj[v].push_back(cnt++);
    }
    bool bfs() {
        for (int i = 0; i < n; i++) d[i] = -1;
        d[s] = 0;
        queue<int> q;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int id : adj[u]) {
                int v = to[id];
                if (d[v] == -1 && f[id] < c[id]) {
                    d[v] = d[u] + 1;
                    q.push(v);
                }
            }
        }
        return d[t] != -1;
    }
    int dfs(int u, int res) {
        if (u == t) return res;
        for (int &it = cur[u]; it < adj[u].size(); it++) {
            int id = adj[u][it];
            int v = to[id];
            if (d[v] == d[u] + 1 && f[id] < c[id]) {
                int foo = dfs(v, min(c[id] - f[id], res));
                if (foo) {
                    f[id] += foo;
                    f[id ^ 1] -= foo;
                    return foo;
                }
            }
        }
        return 0;
    }
    int maxFlow() {
        int res = 0;
        while (bfs()) {
            for (int i = 0; i < n; i++) cur[i] = 0;
            while (1) {
                int foo = dfs(s, INF);
                if (!foo) break;
                res += foo;
            }
        }
        return res;
    }
};

```

## 6.5 Min Cost-Max Flow

```

struct Flow {
    static const int V = 100000;
    int head[V], to[V], c[V], cost[V], f[V], nxt[V], h[V], par[V], inQueue[V];
    int s, t, n, cnt;
    queue<int> q;
    Flow(int n, int s, int t) {
        this->n = n;
        this->s = s;
        this->t = t;
        cnt = 0;
        for (int i = 0; i < n; i++) {
            head[i] = -1;
            inQueue[i] = 0;
        }
    }
    int addEdge(int u, int v, int _c, int _cost) {
        to[cnt] = v, c[cnt] = _c, cost[cnt] = _cost, f[cnt] = 0, nxt[cnt] = head[u], head[u] = cnt++;
        to[cnt] = u, c[cnt] = 0, cost[cnt] = -_cost, f[cnt] = 0, nxt[cnt] = head[v], head[v] = cnt++;
        return cnt - 2;
    }
    pair<int, int> maxFlow() {
        int res = 0, minCost = 0;
        while (1) {
            for (int i = 0; i < n; i++) {

```

```

        par[i] = -1;
        h[i] = 2e9;
    }
    h[s] = 0;
    q.push(s);
    inQueue[s] = 1;
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        inQueue[u] = 0;
        for (int id = head[u]; id != -1; id = nxt[id]) {
            int v = to[id];
            if (h[v] > h[u] + cost[id] && f[id] < c[id]) {
                h[v] = h[u] + cost[id];
                par[v] = id;
                if (!inQueue[v]) {
                    inQueue[v] = 1;
                    q.push(v);
                }
            }
        }
    }
    if (par[t] == -1) {
        break;
    }
    int x = t;
    int now = 2e9;
    while (x != s) {
        int id = par[x];
        now = min(now, c[id] - f[id]);
        x = to[id ^ 1];
    }
    x = t;
    while (x != s) {
        int id = par[x];
        minCost += cost[id] * now;
        f[id] += now;
        f[id ^ 1] -= now;
        x = to[id ^ 1];
    }
    res += now;
}
return make_pair(res, minCost);
};

```

## 6.6 Bounded Feasible Flow

```

struct BoundedFlow {
    int low[N][N], high[N][N];
    int c[N][N];
    int f[N][N];
    int n, s, t;

    void reset() {
        memset(low, 0, sizeof low);
        memset(high, 0, sizeof high);
        memset(c, 0, sizeof c);
        memset(f, 0, sizeof f);
        n = s = t = 0;
    }

    void addEdge(int u, int v, int d, int c) {
        low[u][v] = d; high[u][v] = c;
    }

    int flow;
    int trace[N];

    bool findPath() {
        memset(trace, 0, sizeof trace);
        queue<int> Q;
        Q.push(s);
        while (!Q.empty()) {
            int u = Q.front(); Q.pop();
            for (int v = 1; v <= n; ++v) if (c[u][v] > f[u][v] && !trace[v]) {
                trace[v] = u;
                if (v == t) return true;
                Q.push(v);
            }
        }
        return false;
    }

    void incFlow() {
        int delta = INF;
        for (int v = t; v != s; v = trace[v])
            delta = min(delta, c[trace[v]][v] - f[trace[v]][v]);
        for (int v = t; v != s; v = trace[v])

```

```

            f[trace[v]][v] += delta, f[v][trace[v]] -= delta;
            flow += delta;
        }

    int maxFlow() {
        flow = 0;
        while (findPath()) incFlow();
        return flow;
    }

    bool feasible() {
        c[t][s] = INF;
        s = n + 1; t = n + 2;
        int sum = 0;
        for (int u = 1; u <= n; ++u) for (int v = 1; v <= n; ++v) {
            c[s][v] += low[u][v];
            c[u][t] += low[u][v];
            c[u][v] += high[u][v] - low[u][v];
            sum += low[u][v];
        }
        n += 2;
        return maxFlow() == sum;
    }
};

```

## 6.7 Hungarian Algorithm

```

struct BipartiteGraph {
    const int INF = 1e9;

    vector<vector<int>> > c; // cost matrix
    vector<int> fx, fy; // potentials
    vector<int> matchX, matchY; // corresponding vertex
    vector<int> trace; // last vertex from the left side
    vector<int> d, arg; // distance from the tree && the corresponding node
    queue<int> Q; // queue used for BFS

    int n; // assume that |L| = |R| = n
    int start; // current root of the tree
    int finish; // leaf node of the augmenting path

    BipartiteGraph(int n) {
        this->n = n;
        c = vector<vector<int>>(n + 1, vector<int>(n + 1, INF));
        fx = fy = matchX = matchY = trace = d = arg = vector<int>(n + 1);
    }

    void addEdge(int u, int v, int cost) { c[u][v] = min(c[u][v], cost); }
    int cost(int u, int v) { return c[u][v] - fx[u] - fy[v]; }

    void initBFS(int root) {
        start = root;
        Q = queue<int>(); Q.push(start);
        for (int i = 1; i <= n; ++i) {
            trace[i] = 0;
            d[i] = cost(start, i);
            arg[i] = start;
        }
    }

    int findPath() {
        while (!Q.empty()) {
            int u = Q.front(); Q.pop();
            for (int v = 1; v <= n; ++v) if (trace[v] == 0) {
                int w = cost(u, v);
                if (w == 0) {
                    trace[v] = u;
                    if (matchY[v] == 0) return v;
                    Q.push(matchY[v]);
                }
                if (d[v] > w) d[v] = w, arg[v] = u;
            }
        }
        return 0;
    }

    void enlarge() {
        for (int y = finish, next; y; y = next) {
            int x = trace[y];
            next = matchX[x];
            matchX[x] = y;
            matchY[y] = x;
        }
    }

    void update() {
        int delta = INF;
        for (int i = 1; i <= n; ++i) if (trace[i] == 0) delta = min(delta, d[i]);
    }
};

```

```

    fx[start] += delta;
    for (int i = 1; i <= n; ++i) {
        if (trace[i] != 0) {
            fx[matchY[i]] += delta;
            fy[i] -= delta;
        } else {
            d[i] -= delta;
            if (d[i] == 0) {
                trace[i] = arg[i];
                if (matchY[i] == 0)
                    finish = i;
                else
                    Q.push(matchY[i]);
            }
        }
    }
}

void hungarian() {
    for (int i = 1; i <= n; ++i) {
        initBFS(i);
        do {
            finish = findPath();
            if (finish == 0) update();
        } while (finish == 0);
        enlarge();
    }
}

void show() {
    int ans = 0;
    for (int i = 1; i <= n; ++i) if (matchX[i]) ans += c[i][matchX[i]];
    cout << ans << endl;
    for (int i = 1; i <= n; ++i) cout << i << ' ' << matchX[i] << endl;
}
};

```

## 6.8 Undirected mincut

```

/*
 * Find minimum cut in undirected weighted graph
 * Complexity:  $O(V^3)$ 
 */
#define SW StoerWagner
#define cap_t int
namespace StoerWagner {
    int n;
    vector<vector<cap_t>> graph;
    vector<int> cut;

    void init(int _n) {
        n = _n;
        graph = vector<vector<cap_t>>(n, vector<cap_t>(n, 0));
    }

    void addEdge(int a, int b, cap_t w) {
        if (a == b) return;
        graph[a][b] += w;
        graph[b][a] += w;
    }

    pair<cap_t, pair<int, int>> stMinCut(vector<int> &active) {
        vector<cap_t> key(n);
        vector<int> v(n);
        int s = -1, t = -1;
        for (int i = 0; i < active.size(); i++) {
            cap_t maxv = -1;
            int cur = -1;
            for (auto j : active) {
                if (v[j] == 0 && maxv < key[j]) {
                    maxv = key[j];
                    cur = j;
                }
            }
            t = s;
            s = cur;
            v[cur] = 1;
            for (auto j : active) key[j] += graph[cur][j];
        }
        return make_pair(key[s], make_pair(s, t));
    }

    cap_t solve() {
        cap_t res = numeric_limits<cap_t>::max();
        vector<vector<int>> grps;
        vector<int> active;
        cut.resize(n);
        for (int i = 0; i < n; i++) grps.emplace_back(1, i);
        for (int i = 0; i < n; i++) active.push_back(i);
        while (active.size() >= 2) {
            auto stcut = stMinCut(active);

```

```

            if (stcut.first < res) {
                res = stcut.first;
                fill(cut.begin(), cut.end(), 0);
                for (auto v : grps[stcut.second.first]) cut[v] = 1;
            }
            int s = stcut.second.first, t = stcut.second.second;
            if (grps[s].size() < grps[t].size()) swap(s, t);
            active.erase(find(active.begin(), active.end(), t));
            grps[s].insert(grps[s].end(), grps[t].begin(), grps[t].end());
            for (int i = 0; i < n; i++) {
                graph[i][s] += graph[i][t];
                graph[i][t] = 0;
            }
            for (int i = 0; i < n; i++) {
                graph[s][i] += graph[t][i];
                graph[t][i] = 0;
            }
            graph[s][s] = 0;
        }
        return res;
    }
}

```

## 6.9 Eulerian Path/Circuit

```

struct EulerianGraph {
    vector<vector<pair<int, int>>> a;
    int num_edges;

    EulerianGraph(int n) {
        a.resize(n + 1);
        num_edges = 0;
    }

    void add_edge(int u, int v, bool undirected = true) {
        a[u].push_back(make_pair(v, num_edges));
        if (undirected) a[v].push_back(make_pair(u, num_edges));
        num_edges++;
    }

    vector<int> get_eulerian_path() {
        vector<int> path, s;
        vector<bool> was(num_edges);
        s.push_back(1); // start of eulerian path
        while (!s.empty()) {
            int u = s.back();
            bool found = false;
            while (!a[u].empty()) {
                int v = a[u].back().first;
                int e = a[u].back().second;
                a[u].pop_back();
                if (was[e]) continue;
                was[e] = true;
                s.push_back(v);
                found = true;
                break;
            }
            if (!found) {
                path.push_back(u);
                s.pop_back();
            }
        }
        reverse(path.begin(), path.end());
        return path;
    }
};

```

## 7 Data structures

### 7.1 Treap

```

class Treap {
    struct Node {
        int key;
        uint32_t prior;
        bool rev_lazy;
        int size;
        Node *l, *r;
        Node(int key): key(key), prior(rand()), rev_lazy(false), size(1), l(nullptr), r(nullptr) {}
        ~Node() { delete l; delete r; }
    };

```

```

};

inline int size(Node *x) { return x ? x->size : 0; }

void push(Node *x) {
    if (x && x->rev_lazy) {
        x->rev_lazy = false;
        swap(x->l, x->r);
        if (x->l) x->l->rev_lazy ^= true;
        if (x->r) x->r->rev_lazy ^= true;
    }
}

inline void update(Node *x) {
    if (x) {
        x->size = size(x->l) + size(x->r) + 1;
    }
}

void join(Node *t, Node *l, Node *r) {
    push(l); push(r);
    if (!l || !r)
        t = l ? l : r;
    else if (l->prior < r->prior)
        join(l->r, l->r, r), t = l;
    else
        join(r->l, l, r->l), t = r;
    update(t);
}

void splitByKey(Node *v, int x, Node* &l, Node* &r) {
    if (!v) return void(l = r = nullptr);
    push(v);
    if (v->key < x)
        splitByKey(v->r, x, v->r, r), l = v;
    else
        splitByKey(v->l, x, l, v->l), r = v;
    update(v);
}

void splitByIndex(Node *v, int x, Node* &l, Node* &r) {
    if (!v) return void(l = r = nullptr);
    push(v);
    int index = size(v->l) + 1;
    if (index < x)
        splitByIndex(v->r, x - index, v->r, r), l = v;
    else
        splitByIndex(v->l, x, l, v->l), r = v;
    update(v);
}

void show(Node *x) {
    if (!x) return;
    push(x);
    show(x->l);
    cerr << x->key << ' ';
    show(x->r);
}

Node *root;
Node *l, *m, *r;

public:
Treap() { root = NULL; }
~Treap() { delete root; }
int size() { return size(root); }

int insert(int x) {
    splitByKey(root, x, l, m);
    splitByKey(m, x + 1, m, r);
    int ans = 0;
    if (!m) m = new Node(x), ans = size(l) + 1;
    join(l, l, m);
    join(root, l, r);
    return ans;
}

int erase(int x) {
    splitByKey(root, x, l, m);
    splitByKey(m, x + 1, m, r);
    int ans = 0;
    if (m) {
        ans = size(l) + 1;
        delete m;
    }
    join(root, l, r);
    return ans;
}

void insertAt(int pos, int x) {
    splitByIndex(root, pos, l, r);
    join(l, l, new Node(x));
}

```

```

        join(root, l, r);
    }

void eraseAt(int x) {
    splitByIndex(root, x, l, m);
    splitByIndex(m, 2, m, r);
    delete m;
    join(root, l, r);
}

void updateAt(int pos, int newValue) {
    eraseAt(pos);
    insertAt(pos, newValue);
}

int valueAt(int pos) {
    splitByIndex(root, pos, l, m);
    splitByIndex(m, 2, m, r);
    int res = m->key;
    join(l, l, m);
    join(root, l, r);
    return res;
}

void reverse(int from, int to) {
    splitByIndex(root, from, l, m);
    splitByIndex(m, to - from + 2, m, r);
    m->rev_lazy ^= 1;
    join(l, l, m);
    join(root, l, r);
}

void show() {
    cerr << "Size = " << size() << " ";
    cerr << "[ ";
    show(root);
    cerr << "]\n";
}
};

```

## 7.2 Big Integer

```

typedef vector<int> bigInt;
const int BASE = 1000;
const int LENGTH = 3;

// * Refine function
bigInt& fix(bigInt &a) {
    a.push_back(0);
    for (int i = 0; i + 1 < a.size(); ++i) {
        a[i + 1] += a[i] / BASE; a[i] %= BASE;
        if (a[i] < 0) a[i] += BASE, --a[i + 1];
    }
    while (a.size() > 1 && a.back() == 0) a.pop_back();
    return a;
}

// * Constructors
bigInt big(int x) {
    bigInt result;
    while (x > 0) {
        result.push_back(x % BASE);
        x /= BASE;
    }
    return result;
}

bigInt big(string s) {
    bigInt result(s.size() / LENGTH + 1);
    for (int i = 0; i < s.size(); ++i) {
        int pos = (s.size() - i - 1) / LENGTH;
        result[pos] = result[pos] * 10 + s[i] - '0';
    }
    return fix(result), result;
}

// * Compare operators

int compare(bigInt &a, bigInt &b) {
    if (a.size() != b.size()) return (int)a.size() - (int)b.size();
    for (int i = (int)a.size() - 1; i >= 0; --i)
        if (a[i] != b[i]) return a[i] - b[i];
    return 0;
}

#define DEFINE_OPERATOR(x) bool operator x (bigInt &a, bigInt &b) { return compare(a, b) x 0; }
DEFINE_OPERATOR(==)

```

```

DEFINE_OPERATOR(!=)
DEFINE_OPERATOR(>)
DEFINE_OPERATOR(<)
DEFINE_OPERATOR(>=)
DEFINE_OPERATOR(<=)
#undef DEFINE_OPERATOR

// * Arithmetic operators

void operator += (bigInt &a, bigInt b) {
    a.resize(max(a.size(), b.size()));
    for (int i = 0; i < b.size(); ++i)
        a[i] += b[i];
    fix(a);
}

void operator -= (bigInt &a, bigInt b) {
    for (int i = 0; i < b.size(); ++i)
        a[i] -= b[i];
    fix(a);
}

void operator *= (bigInt &a, int b) {
    for (int i = 0; i < a.size(); ++i)
        a[i] *= b;
    fix(a);
}

void divide(bigInt a, int b, bigInt &q, int &r) {
    for (int i = int(a.size()) - 1; i >= 0; --i) {
        r = r * BASE + a[i];
        q.push_back(r / b); r %= b;
    }
    reverse(q.begin(), q.end());
    fix(q);
}

bigInt operator + (bigInt a, bigInt b) { a += b; return a; }
bigInt operator - (bigInt a, bigInt b) { a -= b; return a; }
bigInt operator * (bigInt a, int b) { a *= b; return a; }

bigInt operator / (bigInt a, int b) {
    bigInt q; int r = 0;
    divide(a, b, q, r);
    return q;
}

int operator % (bigInt a, int b) {
    bigInt q; int r = 0;
    divide(a, b, q, r);
    return r;
}

bigInt operator * (bigInt a, bigInt b) {
    bigInt result (a.size() + b.size());
    for (int i = 0; i < a.size(); ++i)
        for (int j = 0; j < b.size(); ++j)
            result[i + j] += a[i] * b[j];
    return fix(result);
}

// * I/O routines

istream& operator >> (istream& cin, bigInt &a) {
    string s; cin >> s;
    a = big(s);
    return cin;
}

ostream& operator << (ostream& cout, const bigInt &a) {
    cout << a.back();
    for (int i = (int)a.size() - 2; i >= 0; --i)
        cout << setw(LENGTH) << setfill('0') << a[i];
    return cout;
}

```

## 7.3 Convex Hull IT

```

struct Line {
    long long a, b; // y = ax + b
    Line(long long a = 0, long long b = -INF): a(a), b(b) {}
    long long eval(long long x) {
        return a * x + b;
    }
};

struct Node {
    Line line;
    int l, r;
    Node *left, *right;

    Node(int l, int r): l(l), r(r), left(NULL), right(NULL), line() {}

    void update(int i, int j, Line newLine) {
        if (r < i || j < l) return;
        if (i <= l && r <= j) {
            Line AB = line, CD = newLine;
            if (AB.eval(valueX[l]) < CD.eval(valueX[l])) swap(AB, CD);
            if (AB.eval(valueX[r]) >= CD.eval(valueX[r])) {
                line = AB;
                return;
            }
            int mid = valueX[l + r >> 1];
            if (AB.eval(mid) < CD.eval(mid))
                line = CD, left->update(i, j, AB);
            else
                line = AB, right->update(i, j, CD);
            return;
        }
        left->update(i, j, newLine);
        right->update(i, j, newLine);
    }

    long long getMax(int i) {
        if (l == r) return line.eval(valueX[i]);
        if (i <= (l + r >> 1)) return max(line.eval(valueX[i]), left->getMax(i));
        return max(line.eval(valueX[i]), right->getMax(i));
    }
};

Node* build(int l, int r) {
    Node *x = new Node(l, r);
    if (l == r) return x;
    x->left = build(l, l + r >> 1);
    x->right = build((l + r >> 1) + 1, r);
    return x;
}

```

## 8 Miscellaneous

### 8.1 RNG

```

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
//use mt19937_64 if we want 64-bit number

```