

Paper B-03: Internet Routing: A Constraint-Driven Flux Dynamics (CDFD) Perspective

Steve Bico Mujjabi, MD

Independent Researcher

ORCID: 0009-0001-0556-5516

May 2026

Abstract

This paper asks whether Constraint-Driven Flux Dynamics (CDFD) and Adaptive Flux Limitation (AFL) can give the named system a sharper audit language. The working variables are driving flux Φ , constraint C , surface responsiveness S , and structural memory M_s . The useful question is plain: what can be measured, what would count as overload, and what result would make the mapping fail?

1 Series Context

Part I sets the flow–constraint language used here [1]. Part II develops the Life Number and the origins-of-life use of the same notation [2]. Part III applies AFL to biology and medicine [3]. Part IV is the cross-domain stress test: it asks where the notation clarifies measurement, and where it becomes only a metaphor.

2 Introduction

Notation. In Part IV, C names the active constraint or capacity burden in the system being discussed. Φ is the driving flow, S is the surface response, and M_s is retained structural memory. Λ appears only where the Part II Life Number is being referenced [2]. Other Greek symbols are local coefficients whose meaning is set by the equation in which they appear.

2.1 The Mujjabi Universal Capacity Law

Building directly upon the Fundamental Physics (Part I) [1], the **Mujjabi Universal Capacity Law** proposes that across all scales—from black hole event horizons to global financial markets and power grids—driving high flux (Φ) against a rigid topological constraint (C) can drive system saturation. When Φ/C approaches critical thresholds, the system does not scale linearly; it undergoes a topological phase transition.

2.2 The Mujjabi Universal Memory Law

The **Mujjabi Universal Memory Law** frames persistent systemic collapse. When a complex network fails to clear its structural memory (M_s) and its relaxation parameter decays ($\tau_{relax} \rightarrow \infty$), temporary stressors become permanent rigidities. This is the proposed CDFD mechanism behind ecological death, economic depressions, and infrastructural gridlock.

The internet is an unprecedented experiment in macroscopic information transport. When a user requests a video stream, the data is sliced into packets and fired across optical fibers, dynamically navigating around severed cables and overloaded servers to reach its destination.

Unlike the electrical grid, which has a rigid physical topology, the internet possesses high software plasticity. However, the physical hardware underlying the web still enforces hard thermodynamic and capacity constraints. The internet is a living CDFD surface, constantly breathing in data flux and exhaling information.

3 The Network as an Adaptive Surface

We evaluate the health of a data center or routing node via the Universal Adaptive Ratio:

$$\Psi_s = \left(\frac{\Phi}{C} \right) \cdot S \cdot M_s \quad (1)$$

For an autonomous internet node:

- **Flux** (Φ): The gigabits per second of incoming and outgoing data packets.
- **Constraint** (C): The physical bandwidth limits of the fiber optic cables and the processing friction (latency) of the routers.
- **Responsiveness** (S): The node's buffer memory capacity and the elasticity of its load-balancing algorithms, allowing it to temporarily absorb traffic spikes.
- **Memory** (M_s): The Border Gateway Protocol (BGP) routing tables and DNS caches. If routing tables are updated too slowly, the network "remembers" obsolete paths, locking the system's topology into an inefficient state.

3.1 congestion (chronic C saturation) Collapse and BGP Failures

A healthy router operates at $\Psi_s \approx 1$, passing packets (Φ) as fast as they arrive without violating its bandwidth constraints (C).

Consider a Distributed Denial of Service (DDoS) attack. A massive, artificial spike in flux Φ hits the target node. The physical constraint C remains fixed. The node's responsiveness S (its packet buffer) fills up instantly. The adaptive ratio skyrockets ($\Psi_s \gg 1$). To protect the hardware and the network, the router simply drops the excess packets, functionally forcing the excess flux into dissipation.

A more insidious failure occurs via BGP misconfigurations. If an upstream ISP broadcasts a faulty route, the memory M_s of millions of routers locks onto a "black hole" path. The local constraint C effectively becomes infinite for that specific traffic flow. The adaptive ratio crashes

($\Psi_s \ll 1$). Data ceases to flow globally, not because of a physical hardware failure, but because the systemic memory has pathologically overridden the network’s capacity to adapt.

4 Measurement Layer

The first job in any domain is to choose proxies before drawing conclusions. Φ may be a rate of material, energy, information, capital, or signal flow. C is the bottleneck that slows or redirects that flow. S measures the system’s ability to reconfigure under stress, and M_s records the past load that still changes present behavior. A useful application gives those four terms observable definitions, a time scale, and a failure condition. If a standard domain model explains the same data more cleanly, the CDFD/AFL mapping should give way.

4.1 Current Runtime Diagnostic: Universal Network Cascade

The diagnostic script `Part_E_Synthesis/supplementary/run_partiv_discovery.py` keeps this paper tied to the current CDFD Runtime [4], including RK4 field updates, surface dynamics, structural-memory diffusion, and a finite-value audit. In the May 2026 run, the localized hub-drive stress test ended with hub $\Psi_s = 14.8$, peak network $\Psi_s = 14.8$, 21 nodes above $\Psi_s > 1.5$, and 37 maximum memory-locked nodes. I treat those numbers as a runtime sanity check and as a target for later domain measurement, not as a substitute for field data.

5 Conclusion

The internet is governed by the exact same physical logic as biological circulatory systems. TCP window scaling is essentially an algorithmic implementation of Adaptive Flux Limitation, natively seeking to keep $\Psi_s \approx 1$. By recognizing information transport as a CDFD phenomenon, we can design future decentralized networks that treat routing memory not as a static table, but as a fluid, thermodynamically responsive tissue.

Conflict of Interest

The author declares no conflict of interest.

Data Availability

Release-local runtime diagnostics are available under each Part’s `outputs/` folder, with release-wide synthesis artifacts under `Part_E_Synthesis/supplementary/`, `Part_E_Synthesis/outputs/`, and `Part_E_Synthesis/figures/`.

6 Reference Layer

References

- [1] Steve Bico Mujjabi. Cdfd part i: Fundamental physics - constraint-driven field theory and flux dynamics, 2026.
- [2] Steve Bico Mujjabi. Cdfd part ii: Origins of life and tri-regime bioenergetics - constraint-driven flux dynamics, 2026.
- [3] Steve Bico Mujjabi. Cdfd part iii: Adaptive flux limitation biology and medicine - constraint-driven flux dynamics, 2026.
- [4] Steve Bico Mujjabi. Cdfd runtime: Constraint-driven flux dynamics and cdfl execution engine, 2026.