

Paper B-10: Autonomous Systems: A Constraint-Driven Flux Dynamics (CDFD) Perspective

Steve Bico Mujjabi, MD

Independent Researcher

ORCID: 0009-0001-0556-5516

May 2026

Abstract

This paper asks whether Constraint-Driven Flux Dynamics (CDFD) and Adaptive Flux Limitation (AFL) can give the named system a sharper audit language. The working variables are driving flux Φ , constraint C , surface responsiveness S , and structural memory M_s . The useful question is plain: what can be measured, what would count as overload, and what result would make the mapping fail?

1 Series Context

Part I sets the flow–constraint language used here [1]. Part II develops the Life Number and the origins-of-life use of the same notation [2]. Part III applies AFL to biology and medicine [3]. Part IV is the cross-domain stress test: it asks where the notation clarifies measurement, and where it becomes only a metaphor.

2 Introduction

Notation. In Part IV, C names the active constraint or capacity burden in the system being discussed. Φ is the driving flow, S is the surface response, and M_s is retained structural memory. Λ appears only where the Part II Life Number is being referenced [2]. Other Greek symbols are local coefficients whose meaning is set by the equation in which they appear.

2.1 The Mujjabi Universal Capacity Law

Building directly upon the Fundamental Physics (Part I) [1], the **Mujjabi Universal Capacity Law** proposes that across all scales—from black hole event horizons to global financial markets and power grids—driving high flux (Φ) against a rigid topological constraint (C) can drive system saturation. When Φ/C approaches critical thresholds, the system does not scale linearly; it undergoes a topological phase transition.

2.2 The Mujjabi Universal Memory Law

The **Mujjabi Universal Memory Law** frames persistent systemic collapse. When a complex network fails to clear its structural memory (M_s) and its relaxation parameter decays ($\tau_{relax} \rightarrow \infty$), temporary stressors become permanent rigidities. This is the proposed CDFD mechanism behind ecological death, economic depressions, and infrastructural gridlock.

A robot navigating a busy city street is a thermodynamic engine attempting to process a chaotic stream of informational and physical variables. When a self-driving car encounters a novel situation (e.g., an unpredictable pedestrian), it must instantly adjust its velocity and trajectory.

If the robot's programming is too rigid, it will simply freeze in place, unable to compute a safe path. In CDFD terms, the robot has encountered an infinite topological constraint.

3 The Robotic Adaptive Surface

We govern autonomous behavior using the Universal Adaptive Ratio:

$$\Psi_s = \left(\frac{\Phi}{C} \right) \cdot S \cdot M_s \quad (1)$$

For an autonomous agent (like a drone or self-driving car):

- **Flux** (Φ): The rate of sensory data ingestion (LIDAR, cameras) and the corresponding kinetic motor output (speed/movement).
- **Constraint** (C): The physical obstacles in the environment, combined with the hard-coded safety limits programmed into the robot's control matrix.
- **Responsiveness** (S): The computational speed of the inference engine and the physical agility of the robotic actuators.
- **Memory** (M_s): The trained neural network weights and prior mapping data. If the robot relies too heavily on a pre-computed map, its memory is highly locked, making it vulnerable to sudden environmental changes.

3.1 The Algorithmic Freeze State

In a perfectly mapped environment, the robot flows smoothly. The sensory flux Φ is easily processed against known constraints C , maintaining $\Psi_s \approx 1$.

Consider a scenario where the environment suddenly changes (e.g., a construction zone blocks the mapped road). The external constraint C spikes dramatically. If the robot's memory (M_s) dictates that it must strictly follow the pre-computed path, it cannot find a valid mathematical solution. The effective responsiveness S drops to zero. The adaptive ratio crashes ($\Psi_s \ll 1$).

The robot enters a "freeze" state, simply halting all kinetic flux Φ . It has suffered a topological stroke. To achieve true autonomy, the robotic architecture must possess an internal

mechanism to instantly discard its restrictive memory (M_s) when C spikes, allowing it to dynamically explore novel, low-constraint topological pathways without breaking its core safety parameters.

4 Measurement Layer

The first job in any domain is to choose proxies before drawing conclusions. Φ may be a rate of material, energy, information, capital, or signal flow. C is the bottleneck that slows or redirects that flow. S measures the system’s ability to reconfigure under stress, and M_s records the past load that still changes present behavior. A useful application gives those four terms observable definitions, a time scale, and a failure condition. If a standard domain model explains the same data more cleanly, the CDFD/AFL mapping should give way.

4.1 Current Runtime Diagnostic: Universal Network Cascade

The diagnostic script `Part_E_Synthesis/supplementary/run_partiv_discovery.py` keeps this paper tied to the current CDFD Runtime [4], including RK4 field updates, surface dynamics, structural-memory diffusion, and a finite-value audit. In the May 2026 run, the localized hub-drive stress test ended with hub $\Psi_s = 14.8$, peak network $\Psi_s = 14.8$, 21 nodes above $\Psi_s > 1.5$, and 37 maximum memory-locked nodes. I treat those numbers as a runtime sanity check and as a target for later domain measurement, not as a substitute for field data.

5 Conclusion

Autonomy is not merely a software problem; it is a topological challenge of maintaining continuous fluid motion through a highly constrained physical space. By framing robotics within CDFD, engineers can design control loops that natively seek out the $\Psi_s \approx 1$ equilibrium, resulting in agents that fluidly adapt to chaos rather than rigidly freezing in the face of structural uncertainty.

Conflict of Interest

The author declares no conflict of interest.

Data Availability

Release-local runtime diagnostics are available under each Part’s `outputs/` folder, with release-wide synthesis artifacts under `Part_E_Synthesis/supplementary/`, `Part_E_Synthesis/outputs/`, and `Part_E_Synthesis/figures/`.

6 Reference Layer

References

- [1] Steve Bico Mujjabi. Cdfd part i: Fundamental physics - constraint-driven field theory and flux dynamics, 2026.
- [2] Steve Bico Mujjabi. Cdfd part ii: Origins of life and tri-regime bioenergetics - constraint-driven flux dynamics, 2026.
- [3] Steve Bico Mujjabi. Cdfd part iii: Adaptive flux limitation biology and medicine - constraint-driven flux dynamics, 2026.
- [4] Steve Bico Mujjabi. Cdfd runtime: Constraint-driven flux dynamics and cdfl execution engine, 2026.