

Paper D-11: Supply Chains: A Constraint-Driven Flux Dynamics (CDFD) Perspective

Steve Bico Mujjabi, MD
Independent Researcher
ORCID: 0009-0001-0556-5516

May 2026

Abstract

This paper asks whether Constraint-Driven Flux Dynamics (CDFS) and Adaptive Flux Limitation (AFL) can give the named system a sharper audit language. The working variables are driving flux Φ , constraint C , surface responsiveness S , and structural memory M_s . The useful question is plain: what can be measured, what would count as overload, and what result would make the mapping fail? In this paper we apply Adaptive Flux Limitation (AFL) to supply chain dynamics, modelling goods throughput as constrained transport governed by the potential $\Phi = \Phi_{demand} + \Phi_{production} + \Phi_{logistics}$ and constraint $C = C_{inventory} + C_{transport} + C_{supplier}$. The 2021–2022 global supply chain crisis — generating \$1 trillion in logistics cost overruns — is the AFL demonstration event for JIT fragility at planetary scale. The AFL framework derives optimal inventory safety stock, bullwhip dampening strategies, and resilient network topology from first principles.

Status: Inferred from AFL first principles; quantitative predictions are hypothesis-level.

Series tag: Dom-D10

Greek-symbol convention. Unless a manuscript states a tighter equation-local meaning, Greek symbols are local CDFS variables or coefficients, not universal constants. Here Φ denotes driving flux, Ψ_s denotes the adaptive operating ratio, Ω denotes a domain or state space, and Λ denotes the Life Number where used. The coefficients α , β , and γ denote accumulation or reinforcement, relaxation or decay, and diffusion, coupling, or redistribution. The symbols δ and ϵ denote perturbation or tolerance scales, while η , λ , μ , ν , ρ , σ , τ , and ϕ denote local efficiency, rate, baseline, frequency, density or correlation, noise or variance, time-scale, and phase or field terms. Subscripts restrict any coefficient to the named pathway, tissue, domain, or experiment.

1 Series Context

Part I sets the flow–constraint language used here [1]. Part II develops the Life Number and the origins-of-life use of the same notation [2]. Part III applies AFL to biology and medicine [3]. Part IV is the cross-domain stress test: it asks where the notation clarifies measurement, and where it becomes only a metaphor.

2 Introduction

2.1 The Mujjabi Universal Capacity Law

Building directly upon the Fundamental Physics (Part I) [1], the **Mujjabi Universal Capacity Law** proposes that across all scales—from black hole event horizons to global financial markets and power grids—driving high flux (Φ) against a rigid topological constraint (C) can drive system saturation. When Φ/C approaches critical thresholds, the system does not scale linearly; it undergoes a topological phase transition.

2.2 The Mujjabi Universal Memory Law

The **Mujjabi Universal Memory Law** frames persistent systemic collapse. When a complex network fails to clear its structural memory (M_s) and its relaxation parameter decays ($\tau_{relax} \rightarrow \infty$), temporary stressors become permanent rigidities. This is the proposed CDFS mechanism behind ecological death, economic depressions, and infrastructural gridlock.

Modern supply chains span 100+ countries and 10^4 + nodes, delivering >80% of global consumer goods. The semiconductor supply chain alone involves 50+ countries, 500+ critical suppliers, and 10^3 + product variants. Their vulnerability to disruption was demonstrated catastrophically during 2020–2022: COVID-19 factory shutdowns in Asia triggered container shipping shortages, port backlogs, semiconductor supply gaps, and consumer good shortages that persisted for 18–24 months.

AFL provides a unified framework for supply chain dynamics: goods throughput is constrained transport through a hierarchical network; bottleneck nodes are AFL constraint hubs; disruption cascade is AFL $\Psi_s^* > 1.2$ propagation; the bullwhip effect is an AFL limit cycle from delayed constraint updating; JIT systems operate at the AFL $\Psi_s^* = 1.0$ knife-edge with zero resilience.

The AFL supply chain framework connects to all other Part IV papers: logistics is the physical infrastructure of trade networks (Paper 27); supply chain disruption is a trigger for systemic crises (Paper 33); JIT fragility parallels the constraint-removal vulnerability in trophic networks (Paper 42) and neural systems (Paper 35).

3 Core Hypothesis

Supply chains are multi-tier AFL networks in which goods throughput Φ is constrained by inventory buffers and transport capacity C : $\Psi_s^ \approx 1$ is the efficient delivery regime; $\Psi_s^* > 1.2$ is the disruption cascade regime; the bullwhip effect is an AFL limit cycle; and JIT systems are critically fragile because $\Psi_{s,JIT} = 1.0$ leaves zero headroom for perturbation.*

AFL supply chain hypothesis: the Ford-Richardson bullwhip model — where retailers over-order in response to demand shocks, amplifying signal as it propagates upstream — is the AFL limit cycle for a system with time-delayed constraint feedback. The amplification ratio (bullwhip ratio) is:

$$\text{Bullwhip ratio} = \frac{\text{Var}(J_{\text{upstream}})}{\text{Var}(J_{\text{downstream}})} = 1 + \frac{2L}{\beta_{\text{reorder}}} + \frac{2L^2}{\beta_{\text{reorder}}^2}, \quad (1)$$

where L is the order-to-delivery lead time and β_{reorder} is the demand forecast update rate. AFL derives this from the delay-differential AFL system. **Status: Bullwhip derivation is analytic; AFL calibration requires supply chain time-series data.**

4 Supply Chain Potential Fields

We define the generalised supply chain potential:

$$\Phi = \Phi_{\text{demand}} + \Phi_{\text{production}} + \Phi_{\text{logistics}} \quad (2)$$

where:

- Φ_{demand} — end-consumer demand potential (retail demand, order backlog, market clearing prices; the ultimate driving force for all upstream supply activity; propagates upstream through the supply chain with amplification);
- $\Phi_{\text{production}}$ — production capacity potential (manufacturing throughput, capacity utilisation rate; the primary AFL production flux; constrained by capital equipment, labour, and material inputs);

- $\Phi_{logistics}$ — logistics throughput potential (container shipping capacity, trucking availability, air freight; the transport AFL flux connecting production to demand; severely constrained during 2021–2022 by port backlogs and container imbalances).

5 Supply Chain Constraint Axes

$$C = C_{inventory} + C_{transport} + C_{supplier} + C_{labour} \quad (3)$$

Table 1: Supply chain constraint axes and AFL roles.

Constraint axis	Physical substrate	AFL role
$C_{inventory}$	Safety stock, warehouse capacity	Buffer against demand/supply mismatch
$C_{transport}$	Shipping, rail, truck capacity	Goods flow rate constraint
$C_{supplier}$	Supplier reliability and redundancy	Input availability constraint
C_{labour}	Workforce availability, skill match	Production execution constraint
$C_{regulatory}$	Customs, tariffs, trade law	Compliance-induced throughput friction

5.1 Adaptive Surface Dynamics: Memory and Responsiveness

The operating ratio Ψ_s^* is mediated by adaptive surface components:

$$\Psi_s^* = (\Phi/C) \cdot S \cdot M_s \quad (4)$$

where S (Surface Responsiveness) and M_s (Surface Memory) evolve as:

$$\frac{dS}{dt} = \kappa_s(\Psi_s^* - S) \quad (5)$$

$$\frac{dM_s}{dt} = \Phi S - d_m M_s \quad (6)$$

These components represent the homeostatic capacity of the system to regulate its own operating ratio through memory and responsiveness.

6 Flux Law

Supply chain goods throughput:

$$J_{goods} = -\frac{1}{C} \nabla \Phi \quad (7)$$

where $\nabla \Phi$ represents the gradient in demand potential from retail (high Φ_{demand}) to raw material suppliers (low Φ_{demand}), and C is the composite supply chain constraint.

Hub constraint with spatial diffusion:

$$\frac{dC_{hub}}{dt} = \alpha_{congestion} |J_{inbound}| - \beta_{processing} C_{hub} + \gamma_{network} \nabla^2 C_{hub}, \quad (8)$$

where the spatial diffusion term $\gamma_{network} \nabla^2 C_{hub}$ represents constraint redistribution across the supply network — rerouting from congested hubs to alternative nodes.

7 Conservation Dynamics

Supply chain inventory evolves as:

$$\frac{\partial \Phi}{\partial t} = \nabla \cdot \left(\frac{1}{C} \nabla \Phi \right) + S \quad (9)$$

where S represents:

- **Production injection:** $S_{production}$ adds goods to the supply pipeline at manufacturing nodes;
- **Demand withdrawal:** $S_{retail} < 0$ removes goods at retail nodes;
- **Disruption:** $S_{disruption} < 0$ sudden removal of goods (factory closure, port blockage, natural disaster).

8 Adaptive Constraint Dynamics

Supply chain constraint evolves dynamically:

$$\frac{dC}{dt} = \alpha_{utilisation} |J_{goods}| - \beta_{replenishment} C \quad (10)$$

where:

- $\alpha_{utilisation}$: constraint stress from throughput (high goods flow depletes inventory buffers, saturates transport capacity, and increases supplier lead times);
- $\beta_{replenishment}$: constraint replenishment rate (inventory restocking, capacity expansion, new supplier qualification; typically $1/\beta_{replenishment} = 3\text{--}6$ month lead time for major capacity additions).

8.1 Adaptive Surface Dynamics: Memory and Responsiveness

The operating ratio Ψ_s^* is mediated by adaptive surface components:

$$\Psi_s^* = (\Phi/C) \cdot S \cdot M_s \quad (11)$$

where S (Surface Responsiveness) and M_s (Surface Memory) evolve as:

$$\frac{dS}{dt} = \kappa_s (\Psi_s^* - S) \quad (12)$$

$$\frac{dM_s}{dt} = \Phi S - d_m M_s \quad (13)$$

These components represent the homeostatic capacity of the system to regulate its own operating ratio through memory and responsiveness.

9 Flux–Constraint Number and Supply Chain States

$$\Psi_{s,supply-chain} = \frac{J_{goods}}{C_{inventory} + C_{transport} + C_{supplier}} \quad (14)$$

9.1 Resilient Regime ($\Psi_s^* < 0.8$)

Goods throughput well below constraint capacity. Excess inventory buffers; multiple transport options; supplier redundancy. AFL predicts high resilience to disruption: single node failures are absorbed by $C > J$ headroom. Post-war US manufacturing (1950s) operated in this regime — high inventory, high reliability, low efficiency.

9.2 Efficient Operating Regime ($\Psi_s^* \approx 1$)

Throughput matches constraint capacity. Lean inventory; efficient transport; competitive supplier pricing. AFL predicts high throughput efficiency with moderate resilience. Well-managed JIT systems target this regime but are vulnerable to drift toward $\Psi_s^* > 1$.

9.3 Disruption Cascade Regime ($\Psi_s^* > 1.2$)

Throughput exceeds constraint capacity. AFL cascade: node i failure ($\Psi_{s,i} \rightarrow \infty$) propagates to dependent nodes j when $\gamma_{ij}(\Psi_{s,i} - 1) > C_j - J_j$. The 2021–2022 supply chain crisis: COVID-19 factory closures (China, Vietnam) drove $\Psi_{s,semiconductor} \gg 1.2$; automotive industry (>90% dependent on single-source chips) cascade to $\Psi_{s,auto} > 1.2$; \$200+ billion in delayed vehicle production.

10 The Bullwhip Effect as AFL Limit Cycle

The bullwhip effect is the AFL limit cycle arising from delayed demand signal propagation through supply tiers:

$$\frac{d\Phi_{retailer}}{dt} = J_{demand} - J_{retail-order} \quad (15)$$

$$\frac{dJ_{wholesale-order}}{dt} = \alpha_{forecast}(\Phi_{retailer} - \Phi_{target}) - \beta_{order}J_{wholesale-order} \quad (16)$$

$$\frac{dJ_{supplier-order}}{dt} = \alpha_{forecast}(J_{wholesale} - J_{target}) - \beta_{supplier}J_{supplier} \quad (17)$$

The delay between demand signal and supply response ($L = 1/\beta_{order}$) creates a phase lag that drives oscillation. The bullwhip ratio (variance amplification per tier):

$$\text{BW ratio per tier} = 1 + \frac{2}{\beta_{order}L} + \frac{2}{(\beta_{order}L)^2}. \quad (18)$$

For $L = 4$ weeks and $\beta_{order}^{-1} = 2$ weeks: BW ratio $\approx 1 + 1 + 0.5 = 2.5$ per tier. A 3-tier supply chain amplifies demand variance by $2.5^3 \approx 15.6\times$. The 2021–2022 semiconductor shortage: $\sim 10\%$ demand increase in consumer electronics amplified to $>150\%$ order increase for upstream chip foundries — consistent with a 3-tier supply chain AFL bullwhip with ratio $\approx 15\times$.

AFL bullwhip dampening: reduce L (shorten lead times via nearshoring, express shipping), increase β_{order} (more frequent demand-signal updates, vendor-managed inventory), or raise $C_{inventory}$ (safety stock absorbs the limit cycle oscillation amplitude).

11 JIT Fragility Theorem

AFL JIT Fragility Theorem: Just-in-time production sets $C_{inventory} \rightarrow 0$, driving $\Psi_{s,global} \rightarrow 1.0$, which eliminates all resilience to perturbation and ensures cascade disruption from any single node failure.

Formal statement: let $C_{JIT} = C_{transport} + C_{supplier}$ (no inventory buffer). Then:

$$\Psi_{s,JIT} = \frac{J_{goods}}{C_{JIT}} = 1.0 \quad (\text{at design capacity}). \quad (19)$$

Any perturbation $\delta J > 0$ drives $\Psi_{s,JIT} > 1$. Since $C_{inventory} = 0$ provides no buffer, the system immediately enters AFL cascade regime. AFL predicts cascade depth from the coupling matrix γ_{ij} : single-source dependencies (one supplier for a critical component) have $\gamma_{ij} = 1$, guaranteeing full cascade propagation.

Toyota Production System originally maintained $C_{inventory} = \epsilon$ (minimal but nonzero buffer) precisely at each production station. Derivatives of JIT that reduced $\epsilon \rightarrow 0$ (pure demand-pull with zero safety stock) maximised efficiency but also maximised fragility:

$$\text{Resilience} = C_{inventory}/J_{goods} = 1 - \Psi_{s,JIT}. \quad (20)$$

AFL-optimal supply chain design: set $C_{inventory}$ such that $\Psi_{s,JIT} = 0.85\text{--}0.90$ (15–10% buffer above demand), accepting 10–15% inventory holding cost as insurance against cascade disruption cost.

12 Optimal Redundancy from AFL

AFL derives the optimal safety stock for a node i :

$$C_i^{opt} = J_i + \max_{j \in \text{upstream}} \left(\Delta J_{reroute}^{(j)} \right), \quad (21)$$

where $\Delta J_{reroute}^{(j)}$ is the maximum additional throughput that node i must absorb if upstream node j fails. This AFL redundancy criterion states: maintain enough capacity to absorb the failure of the single most-critical upstream node.

For the global semiconductor supply chain:

- TSMC produces $\sim 90\%$ of advanced chips globally;
- AFL predicts that global electronics $C_{inventory}$ should equal $J_{TSMC,peak} + \Delta J_{reroute,TSMC}$ (capacity to absorb TSMC disruption);
- Current global chip inventory $\approx 3\text{--}4$ months of demand (AFL buffer fraction ≈ 0.25 ; $\Psi_s^* \approx 0.80$) — inadequate for a 6+ month disruption.

13 Cascade Propagation in Supply Networks

Supply chain cascade follows AFL propagation:

$$\Psi_{s,i} > 1.2 \quad \Rightarrow \quad \Psi_{s,j} > 1.2 \quad \text{for } j \text{ dependent on } i, \quad (22)$$

when $\gamma_{ij}(\Psi_{s,i} - 1) > C_j - J_j$.

Cascade taxonomy:

- **Single-source cascade:** $\gamma_{ij} = 1$ for critical components; any $\Psi_{s,i} > 1$ triggers full cascade; JIT exacerbates this;
- **Geographic concentration cascade:** clustering of suppliers in one region (China, Taiwan, South Korea) creates correlated $\Psi_{s,i} > 1$ events from regional disruptions (earthquake, pandemic, political conflict);
- **Logistics cascade:** port congestion ($\Psi_{s,port} > 1.2$) propagates to all supply chains routing through that hub.

2021 Suez Canal blockage (6 days): $\sim 12\%$ of global trade routes through Suez; $J_{global,Suez} = 370$ ships/day; blockage set $C_{Suez} \rightarrow 0$; 400 ships queued ($\Psi_{s,shipping} \gg 1.2$); global shipping $C_{transport}$ fell 5%; 54% rise in container freight rates within 30 days.

14 Spatial Self-Organisation of Supply Networks

Supply chains organise into hub-and-spoke AFL structures:

- **Regional hubs:** logistics centres at port/transport nodes; AFL maximum-flow routing concentrates goods at minimum-constraint paths;
- **Tiered supplier structure:** Tier 1 (OEM suppliers), Tier 2 (component suppliers), Tier 3 (raw material); each tier represents an AFL node with its own Ψ_s^* ;
- **Geographic clustering** (Silicon Valley, Shenzhen, Bangalore): AFL constraint reduction from spatial proximity (lower transport C , talent pool, knowledge spillovers); same mechanism as urban agglomeration (Paper 29).

15 Predictions

1. **Bullwhip amplification:** demand variance amplification between supply tiers scales as $(1 + 2/(\beta L) + 2/(\beta L)^2)$; AFL predicts this from lead time L and reorder frequency β ; testable from supplier order data;
2. **JIT cascade threshold:** supply chains with $\Psi_{s,inventory} > 0.90$ experience cascade disruption from >3 standard deviation demand shocks; AFL predicts critical Ψ_s^* from network connectivity matrix;
3. **Optimal safety stock:** $C_{inventory}^{opt} = J \cdot (1 + k \cdot \sigma_{demand})$ where $k \approx 1.65$ (95th percentile demand), giving $\Psi_{s,target} = 1/(1 + k\sigma)$; AFL predicts holding cost vs disruption risk tradeoff curve;
4. **Nearshoring benefit:** reducing lead time L by 50% (nearshoring) reduces bullwhip ratio by $>60\%$ (since BW ratio scales as L^2); AFL quantifies this tradeoff against cost premium of near-shore production;
5. **Cascade containment:** AFL predicts that maintaining $\Psi_{s,node} < 0.85$ at all nodes (15% headroom) limits cascade depth to 1–2 tiers even for $\gamma_{ij} = 1$ dependencies; testable from supply chain simulation.

Status: Predictions 1, 3 supported by supply chain management literature; predictions 2, 4, 5 are AFL-derived hypotheses.

16 Computational Interpretation

The companion script `supplementary_dom_10.py` implements AFL supply chain dynamics:

- 3-tier bullwhip: retailer-wholesaler-supplier; demand shock at retailer; upstream variance amplification computed; comparison with AFL bullwhip ratio formula;
- JIT vs safety stock: $\Psi_{s,JIT} = 1.0$ vs $\Psi_{s,SS} = 0.85$; disruption at $t=100$; cascade depth comparison;
- semiconductor cascade: 20-node supply network with single-source dependencies; TSMC disruption; cascade propagation time and depth;
- optimal redundancy: $C_{inventory}^{opt}$ sweep; holding cost vs disruption probability tradeoff;
- outputs: bullwhip time series, JIT cascade map, optimal Ψ_s^* curve, cascade containment.

17 Discussion

AFL provides a unified framework for supply chain management: goods flow is AFL transport; inventory is AFL constraint buffer; bullwhip is AFL limit cycle; JIT fragility is the AFL consequence of $\Psi_s^* = 1.0$ operation; cascade is AFL propagation; optimal design is AFL Ψ_s^* -calibration.

The AFL supply chain framework reveals a fundamental tension in supply chain optimisation: efficiency maximisation (JIT, lean inventory, single-source suppliers) drives $\Psi_s^* \rightarrow 1.0$, which maximises throughput-per-unit-constraint but eliminates resilience; risk management (safety stock, supplier diversity, geographic distribution) maintains $\Psi_s^* < 0.85$, accepting efficiency cost to buy resilience.

AFL resolves this tension: the optimal Ψ_s^* target is not 1.0 (efficiency maximum) or 0.5 (resilience maximum), but the Ψ_s^* value that minimises total expected cost including disruption losses. AFL predicts this optimum at $\Psi_s^* \approx 0.85\text{--}0.90$ for most supply chains, where the marginal cost of additional buffer (δC) equals the marginal resilience gain ($\delta \text{cascade-cost} / \delta C$).

18 Measurement Layer

The first job in any domain is to choose proxies before drawing conclusions. Φ may be a rate of material, energy, information, capital, or signal flow. C is the bottleneck that slows or redirects that flow. S measures the system's ability to reconfigure under stress, and M_s records the past load that still changes present behavior. A useful application gives those four terms observable definitions, a time scale, and a failure condition. If a standard domain model explains the same data more cleanly, the CDFD/AFL mapping should give way.

18.1 Current Runtime Diagnostic: Universal Network Cascade

The diagnostic script `Part_E_Synthesis/supplementary/run_partiv_discovery.py` keeps this paper tied to the current CDFD Runtime [4], including RK4 field updates, surface dynamics, structural-memory diffusion, and a finite-value audit. In the May 2026 run, the localized hub-drive stress test ended with hub $\Psi_s = 14.8$, peak network $\Psi_s = 14.8$, 21 nodes above $\Psi_s > 1.5$, and 37 maximum memory-locked nodes. I treat those numbers as a runtime sanity check and as a target for later domain measurement, not as a substitute for field data.

19 Conclusion

Supply chains are multi-tier AFL networks. Goods throughput, inventory constraint, bullwhip dynamics, JIT fragility, and cascade disruption all emerge from the universal AFL equation with supply chain (Φ, C) interpretation. AFL connects supply chain management to all other Part IV papers through the universal flux–constraint framework, demonstrating that global supply chains are the logistical substrate of civilisational AFL dynamics (Papers 25–34).

References

- [1] Steve Bico Mujjabi. Cdfd part i: Fundamental physics - constraint-driven field theory and flux dynamics, 2026.
- [2] Steve Bico Mujjabi. Cdfd part ii: Origins of life and tri-regime bioenergetics - constraint-driven flux dynamics, 2026.
- [3] Steve Bico Mujjabi. Cdfd part iii: Adaptive flux limitation biology and medicine - constraint-driven flux dynamics, 2026.
- [4] Steve Bico Mujjabi. Cdfd runtime: Constraint-driven flux dynamics and cdf execution engine, 2026.