

Paper B-12: Engineering Synthesis: A Constraint-Driven Flux Dynamics (CDFD) Perspective

Steve Bico Mujjabi, MD

Independent Researcher

ORCID: 0009-0001-0556-5516

May 2026

Abstract

This paper closes the Part B engineered-systems sequence. It treats infrastructure, electrical grids, routing networks, distributed computation, cloud systems, knowledge graphs, autonomous systems, and computational architecture as engineering examples of the same CDFD/AFL modelling form. The claim is not that these systems share one material mechanism. The narrower claim is that throughput Φ , constraint C , responsiveness S , and structural memory M_s provide a common audit language for overload, backlog, fragility, and recovery. Release-local runtime outputs are model diagnostics and tests that could break the mapping, not engineering certification.

1 Series Context

Part I sets the flow–constraint language used here [1]. Part II develops the Life Number and the origins-of-life use of the same notation [2]. Part III applies AFL to biology and medicine [3]. Part B applies the shared notation to engineered systems, where every claim still needs ordinary engineering measurement.

Greek-symbol convention. Unless a manuscript states a tighter equation-local meaning, Greek symbols are local CDFD variables or coefficients, not universal constants. Here Φ denotes driving flux, Ψ_s denotes the adaptive operating ratio, and Λ denotes the Life Number where used [2]. The coefficients α , β , and γ denote accumulation or reinforcement, relaxation or decay, and diffusion, coupling, or redistribution. Subscripts restrict coefficients to the named pathway, device, network, or experiment.

2 Purpose

Part B translates Adaptive Flux Limitation (AFL) into engineered systems. The sequence begins with physical infrastructure and electrical grids, moves through routing, distributed computation, cloud systems, knowledge graphs, and autonomous systems, then ends with hardware architecture. This synthesis keeps the public release boundary clear: CDFD/AFL supplies a modelling vocabulary, not operational design authority.

3 Common Engineering Map

CDFD term	Engineering reading	Example observable
Φ	throughput or demand drive	current, packets, jobs, vehicles, queries
C	active constraint	line capacity, latency, lock contention, thermal budget
S	responsiveness	rerouting, autoscaling, buffering, adaptive control
M_s	structural memory	legacy topology, statefulness, cached assumptions
Ψ_s	operating ratio	overload, backlog, underuse, or balanced flow

The shared model is useful only after each term is tied to measurable proxies and failure conditions. Without those proxies, the mapping remains an analogy.

4 Sequence-Level Lessons

1. Infrastructure and grids show the cost of fixed physical constraints when flow surges faster than capacity can relax.
2. Internet, cloud, and distributed-compute papers show how software systems can trade statefulness for responsiveness.
3. Knowledge graphs and autonomous systems show that informational systems also carry memory, backlog, and routing constraints.
4. Computational architecture shows the same audit pattern at chip and memory-hierarchy scale, where throughput is bounded by locality, power, and translation constraints.

5 Measurement Layer

The first job in any domain is to choose proxies before drawing conclusions. Φ may be a rate of material, energy, information, capital, or signal flow. C is the bottleneck that slows or redirects that flow. S measures the system's ability to reconfigure under stress, and M_s records the past load that still changes present behavior. A useful application gives those four terms observable definitions, a time scale, and a failure condition. If a standard domain model explains the same data more cleanly, the CDFD/AFL mapping should give way.

6 Current Runtime Diagnostic

The diagnostic script `Part_E_Synthesis/supplementary/run_partiv_discovery.py` does not simulate every Part B system. It runs a current-runtime domain adapter sweep and a universal network-cascade stress test. The Part B rows in `Part_B_Engineered_Systems/outputs/domain` provide a compact audit for energy systems, network routing, cloud capacity, and artificial intelligence. Those rows check finite-value behavior and regime reporting; engineering claims still need engineering measurements.

7 Falsification Targets

The Part B synthesis weakens if an engineered system cannot define measurable throughput and constraint proxies, if those proxies fail to predict overload or recovery behavior better than existing domain models, or if adding CDFD/AFL variables only renames known quantities without improving auditability.

8 Conclusion

The engineered-systems sequence frames infrastructure, computation, networks, and autonomy as systems where flow, constraint, responsiveness, and memory can be audited together. That framing is useful when it produces measurable failure conditions and reproducible diagnostics. It remains hypothesis-level until it is compared against domain-specific data and engineering baselines.

Conflict of Interest

The author declares no conflict of interest.

Data Availability

Release-local runtime diagnostics are available under each Part's `outputs/` folder, with release-wide synthesis artifacts under `Part_E_Synthesis/supplementary/`, `Part_E_Synthesis/outputs` and `Part_E_Synthesis/figures/`.

9 Reference Layer

References

- [1] Steve Bico Mujjabi. Cdfd part i: Fundamental physics - constraint-driven field theory and flux dynamics, 2026.
- [2] Steve Bico Mujjabi. Cdfd part ii: Origins of life and tri-regime bioenergetics - constraint-driven flux dynamics, 2026.
- [3] Steve Bico Mujjabi. Cdfd part iii: Adaptive flux limitation biology and medicine - constraint-driven flux dynamics, 2026.