

Paper B-07: Logistics: A Constraint-Driven Flux Dynamics (CDFD) Perspective

Steve Bico Mujjabi, MD

Independent Researcher

Founder, Vura Labs

Kampala, Uganda

ORCID: 0009-0001-0556-5516

May 2026

Abstract

This paper develops a falsifiable CDFD/AFL model of Logistics. It maps orders, shipments, materials, and customer demand to driving flux Φ , vehicle, warehouse, port, labor, and information capacity to active constraint C , rerouting, inventory, substitution, prioritization, and coordination to responsiveness S , and contracts, inventories, path dependence, and disruption history to structural memory M_s . The target outcome is lead time, fill rate, cost, shortage, and recovery, tested against shipment traces, inventory records, network maps, lead times, and disruption logs. The paper treats universality as a shared model architecture rather than an assertion that unlike systems have the same material mechanism. It states the negative result that would make the mapping unnecessary and places the domain claim inside the cumulative CDFD programme and its reproducible runtime boundary.

Symbol Conventions

CDFD/AFL Part IV symbol convention.

Symbol	Part IV meaning	Cross-domain reading
Φ	Driving flux or throughput	Energy, matter, signal, capital, information, traffic, force, or biological load entering a system
C	Active constraint or capacity burden	Bottleneck, resistance, boundary, scarcity, toxicity, regulation, topology, latency, or load-bearing limit
S	Responsiveness or adaptive surface	The system's ability to reconfigure, buffer, route, repair, learn, or preserve function under changing load
M_s	Structural memory	Stored damage, hysteresis, inherited topology, institutional memory, trained weights, ecological legacy, or retained state
Ψ_s	Adaptive operating ratio $(\Phi/C) \cdot S \cdot M_s$	Local bookkeeping gauge for constrained operation, overload, recovery, or regime change; not a universal constant
Λ	Life Number or capstone surplus ratio where explicitly defined	Reserved for Part II-derived life-number notation or synthesis-level surplus measures, never an undefined decoration

Greek-symbol convention.

Symbol	Local role	Interpretation rule
α	Accumulation or reinforcement coefficient	Sets how fast a pathway, constraint, habit, cascade, or retained structure grows under load
β	Relaxation, decay, clearance, or washout coefficient	Sets loss, recovery, damping, forgetting, degradation, or return toward baseline
γ	Coupling, diffusion, redistribution, or transfer coefficient	Sets spread across nodes, layers, tissues, markets, infrastructures, media, or physical phases
δ, ϵ	Perturbation, tolerance, small offset, or numerical guard	Used only as local thresholds, stability margins, measurement tolerances, or stress increments
η, λ, μ, ν	Efficiency, rate, baseline, intensity, or frequency terms	Meaning is fixed by the equation, subscript, and domain-specific proxy in the paragraph where the term appears
ρ, σ, τ, ϕ	Density/correlation, variability/noise, time-scale, phase, or field terms	Local coefficients only; subscripts bind them to the named pathway, domain, or experiment
Ω, Λ	Domain/state space; Life Number where defined	Ω names a modeled state space; Λ carries life-number or synthesis notation only when the paper defines it

1 Series Context

Part I sets the flow-constraint language used here [3]. Part II develops the Life Number and the origins-of-life use of the same notation [4]. Part III applies AFL to biology and medicine

[5]. Part IV [6], DOI <https://doi.org/10.5281/zenodo.20395901>, is the cross-domain stress test: it asks where the notation clarifies measurement, and where it becomes only a metaphor.

2 Introduction

2.1 The Mujjabi Universal Capacity Law

Building directly upon the Fundamental Physics (Part I) [3], the **Mujjabi Universal Capacity Law** proposes that across all scales—from black hole event horizons to global financial markets and power grids—driving high flux (Φ) against a rigid topological constraint (C) can drive system saturation. When Φ/C approaches critical thresholds, the system does not scale linearly; it undergoes a topological phase transition.

2.2 The Mujjabi Universal Memory Law

The **Mujjabi Universal Memory Law** frames persistent systemic collapse. When a complex network fails to clear its structural memory (M_s) and its relaxation parameter decays ($\tau_{relax} \rightarrow \infty$), temporary stressors become permanent rigidities. This is the proposed CDFD mechanism behind ecological death, economic depressions, and infrastructural gridlock.

A supply chain is a physical transport network. Ore is mined in one hemisphere, processed in another, and consumed globally. To maximize profit, corporations have spent decades eliminating warehouses and stockpiles, relying on "just-in-time" (JIT) delivery.

In thermodynamic terms, JIT eliminates all buffer capacity from the system. It creates a network that is incredibly fast and efficient under perfect conditions but possesses zero topological elasticity. Under CDFD, this is a system balanced on a razor's edge, predicted here to be vulnerable to catastrophic failure upon the introduction of turbulence.

3 The Logistical Adaptive Surface

We evaluate supply chain networks using the Universal Adaptive Ratio:

$$\Psi_s = \left(\frac{\Phi}{C} \right) \cdot S \cdot M_s \quad (1)$$

For a specific logistical node (e.g., a major shipping port):

- **Flux (Φ):** The volume of cargo containers or tonnage of goods arriving and departing daily.
- **Constraint (C):** The physical unloading capacity of the cranes, labor availability, customs friction, and canal width restrictions.
- **Responsiveness (S):** The available warehouse buffer space and the ability to dynamically reroute ships to alternative ports.

- **Memory (M_s):** Fixed, long-term shipping contracts and consolidated mega-vessel dependencies. High memory locks the global shipping topology into a few rigid, highly efficient corridors, eliminating alternative pathways.

3.1 The Ischemia of Just-In-Time Logistics

A JIT supply chain intentionally drives responsiveness S (buffer stock) to zero to save money. To maintain $\Psi_s \approx 1$, the flow Φ and the constraint C must remain absolutely constant.

If a single major constraint spikes—such as a ship grounding in a critical canal or a sudden labor strike at a mega-port— $C \rightarrow \infty$ for that specific node. Because $S \approx 0$ and M_s is locked (ships cannot easily reroute or unload elsewhere), the adaptive ratio for the entire global segment plummets to $\Psi_s \ll 1$.

The flux Φ backs up. Ships idle in the ocean. Factories on the other side of the planet halt production because they lack buffer inventory. The localized blockage induces a global topological stroke. The system’s failure to maintain structural elasticity results in a complete cessation of macroscopic thermodynamic throughput.

4 Measurement Layer

The first job in any domain is to choose proxies before drawing conclusions. Φ may be a rate of material, energy, information, capital, or signal flow. C is the bottleneck that slows or redirects that flow. S measures the system’s ability to reconfigure under stress, and M_s records the past load that still changes present behavior. A useful application gives those four terms observable definitions, a time scale, and a failure condition. If a standard domain model explains the same data more cleanly, the CDFD/AFL mapping should give way.

4.1 Current Runtime Diagnostic: Universal Network Cascade

The release-local discovery script keeps this paper tied to the current CDFD Runtime [7], including RK4 field updates, surface dynamics, structural-memory diffusion, and a finite-value audit. In the 2026-06-04 runtime pass, the localized hub-drive stress test ended with hub $\Psi_s = 5.21$, peak network $\Psi_s = 5.21$, 21 nodes above $\Psi_s > 1.5$, and 37 maximum memory-locked nodes. I treat those numbers as a runtime sanity check and as a target for later domain measurement, not as a substitute for field data.

5 Major Universal Upgrade: Mechanism, Scale, and Tests

5.1 Observable Translation

The paper-specific translation begins with an observable chain rather than a verbal analogy. For Logistics, the proposed drive is orders, shipments, materials, and customer demand. The active limitation is vehicle, warehouse, port, labor, and information capacity. Responsiveness is carried by rerouting, inventory, substitution, prioritization, and coordination, while retained

state is represented by contracts, inventories, path dependence, and disruption history. The outcome to explain is lead time, fill rate, cost, shortage, and recovery.

Table 1: Operational CDFD/AFL map for Paper B-07.

Term	Paper-specific observable meaning	Measurement question
Φ	orders, shipments, materials, and customer demand	What rate, load, gradient, or demand enters the focal system?
C	vehicle, warehouse, port, labor, and information capacity	Which measured bottleneck limits transfer, function, or recovery?
S	rerouting, inventory, substitution, prioritization, and coordination	Which process changes effective capacity or reroutes the load?
M_s	contracts, inventories, path dependence, and disruption history	Which retained state makes equal present loads produce different futures?
Y	lead time, fill rate, cost, shortage, and recovery	Which outcome is predicted out of sample, with uncertainty?




Figure 1: Paper B-07 observable CDFD/AFL architecture for Logistics. Solid arrows give the proposed forward chain; dashed arrows make history-dependent feedback explicit.

5.2 Minimal Coupled Model

A paper-level model must separate throughput, constraint accumulation, response, and history. One deliberately minimal form is

$$Y(t) = \frac{\Phi(t)S(t)}{\epsilon + C(t)}, \quad (2)$$

$$\frac{dC}{dt} = \alpha\Phi(t) - \beta S(t)C(t) + \gamma\mathcal{L}C(t), \quad (3)$$

$$\frac{dM_s}{dt} = \eta C(t) - \mu M_s(t), \quad (4)$$

$$\Psi_s(t) = \frac{\hat{\Phi}(t)}{\epsilon + \hat{C}(t)} \hat{S}(t) [1 + \omega \hat{M}_s(t)]. \quad (5)$$

Here Y is the measured output, $\epsilon > 0$ prevents a singular denominator, $\mathcal{L}$ is a spatial or network coupling operator, and hats denote explicitly normalized variables. The sign and magnitude of ω must be estimated: memory can preserve useful organization or amplify damage. No fixed threshold is universal before the variables, normalization, and observation scale are declared.

For this paper, the hypothesized causal sequence is specific. A change in orders, shipments,

materials, and customer demand arrives faster than rerouting, inventory, substitution, prioritization, and coordination can compensate. This raises or redistributes vehicle, warehouse, port, labor, and information capacity. If the load persists, the retained state encoded by contracts, inventories, path dependence, and disruption history changes the next response, so a later event of equal magnitude can produce a different trajectory in lead time, fill rate, cost, shortage, and recovery. The scientific task is to estimate that sequence against the best ordinary model of the domain, not merely to redescribe the outcome after it occurs.

5.3 Cross-Scale Universality Without Mechanistic Erasure

For the engineered systems family, the universal comparison is between demand, designed capacity, feedback control, dependency topology, and accumulated technical state. The strongest engineering use is prospective: the mapping must identify a bottleneck, a control action, or a recovery signature before the failure occurs. [2, 9, 8, 1] The CDFD programme is cumulative: Part I supplies the flow-constraint foundation [3]; Part II asks when maintained throughput supports persistent organized states [4]; Part III develops adaptive limitation and biological memory [5]; and Part IV [6] tests how much of that architecture survives translation. The CDFD Runtime [7] supplies a reproducible numerical stress surface, but it does not substitute for the domain evidence named here.

The required scale declaration for this paper is hours to decades; parcels to global trade networks. At short scales, the key question is whether the incoming drive is transmitted, buffered, or diverted. At intermediate scales, response changes effective capacity and network exposure. At long scales, retained structure can alter the state space itself. A result is genuinely cross-scale only when the aggregation rule is stated and the same conclusion is not an artifact of averaging.

5.4 Evidence Ladder and Discriminating Tests

Table 2: Evidence ladder for Paper B-07. Each rung can fail independently.

Test	Design	Discriminating result
Proxy audit	Measure shipment traces, inventory records, network maps, lead times, and disruption logs and preregister how each record maps to Φ , C , S , M_s , and Y .	The mapping fails if proxies are non-identifiable, circular, or change meaning across cases.
Load ramp	Apply or observe a supplier or corridor loss during a demand surge while estimating the dominant constraint and response time.	A threshold claim requires a reproducible nonlinear change and uncertainty bounds, not a visually chosen breakpoint.
Recovery and memory	Match present load across units with different histories, then compare recovery paths.	The memory claim requires history-dependent divergence after current conditions are controlled.
Model comparison	Compare the baseline domain model with and without the CDFD/AFL state variables using held-out data.	The paper’s stated falsifier is: memory and topology terms do not improve shortage or recovery prediction.

The strongest practical design combines a prospective perturbation with a recovery window.

The load-ramp phase estimates where constraint begins to rise faster than output. The recovery phase estimates β and μ , separating fast relaxation from persistent memory. A topology or coupling intervention then asks whether rerouting changes the cascade as predicted. Null results are informative because they identify domains in which the universal notation adds no measurable value.

5.5 Research Programme and Boundary Conditions

The immediate research programme has four steps. First, construct a documented dataset from shipment traces, inventory records, network maps, lead times, and disruption logs and retain raw units before normalization. Second, fit a baseline domain model and report its calibration and out-of-sample error. Third, add the smallest identifiable CDFD/AFL state extension and test whether it improves prediction of lead time, fill rate, cost, shortage, and recovery. Fourth, repeat the analysis across the declared scale range and publish negative cases as part of the universality audit.

Three boundaries are non-negotiable. Correlation between flow and failure does not identify a constraint mechanism. A fitted memory term does not prove that the stored state has the same material meaning in another domain. Finally, a runtime cascade is evidence about the implementation, not evidence that the real system follows it. The paper becomes stronger when it can say precisely where the translation stops.

6 Conclusion

Supply chains are subject to a comparable flow problem to biological circulatory systems. A biological organism maintains fat reserves and redundant arteries (high S , low M_s) precisely to survive localized trauma. By analyzing global logistics through CDFD, we model the hypothesis that economic efficiency must be balanced with topological elasticity; otherwise, the network predicts its own eventual collapse.

Conflict of Interest

The author declares no conflict of interest.

Data Availability

Part-specific runtime diagnostics are under each Part's `outputs/` directory.

Release-wide code: `Part_E_Synthesis/supplementary/`.

Generated summaries: `Part_E_Synthesis/outputs/`.

Figures: `Part_E_Synthesis/figures/`.

7 Reference Layer

References

- [1] Per Bak, Chao Tang, and Kurt Wiesenfeld. Self-organized criticality: An explanation of the $1/f$ noise. *Physical Review Letters*, 59(4):381–384, 1987. DOI: <https://doi.org/10.1103/PhysRevLett.59.381>.
- [2] Albert-Laszlo Barabasi and Reka Albert. Emergence of scaling in random networks. *Science*, 286(5439):509–512, 1999. DOI: <https://doi.org/10.1126/science.286.5439.509>.
- [3] Steve Bico Mujjabi. Cdfd part i: Fundamental physics - constraint-driven field theory and flux dynamics, 2026. DOI: <https://doi.org/10.5281/zenodo.20250821>.
- [4] Steve Bico Mujjabi. Cdfd part ii: Origins of life and tri-regime bioenergetics - constraint-driven flux dynamics, 2026. DOI: <https://doi.org/10.5281/zenodo.20264779>.
- [5] Steve Bico Mujjabi. Cdfd part iii: Adaptive flux limitation biology and medicine - constraint-driven flux dynamics, 2026. DOI: <https://doi.org/10.5281/zenodo.20344695>.
- [6] Steve Bico Mujjabi. Cdfd part iv: Universal adaptive flux limitation - constraint-driven flux dynamics, 2026. DOI: <https://doi.org/10.5281/zenodo.20395901>.
- [7] Steve Bico Mujjabi. Cdfd runtime: Constraint-driven flux dynamics and cdfd execution engine, 2026. DOI: <https://doi.org/10.5281/zenodo.20343160>.
- [8] Claude E. Shannon. A mathematical theory of communication. *Bell System Technical Journal*, 27(3):379–423, 1948. DOI: <https://doi.org/10.1002/j.1538-7305.1948.tb01338.x>.
- [9] Duncan J. Watts and Steven H. Strogatz. Collective dynamics of small-world networks. *Nature*, 393:440–442, 1998. DOI: <https://doi.org/10.1038/30918>.