# String Methods

codecademy

## Python String .format()

The Python string method .format() replaces empty brace ( {} ) placeholders in the string with its arguments.
If keywords are specified within the placeholders, they are replaced with the corresponding named arguments to the method.

```
msg1 = 'Fred scored {} out of {} points.'
msg1.format(3, 10)
# => 'Fred scored 3 out of 10 points.'

msg2 = 'Fred {verb} a {adjective}
{noun}.'
msg2.format(adjective='fluffy',
verb='tickled', noun='hamster')
# => 'Fred tickled a fluffy hamster.'
```

## String Method `.lower()`

The string method .lower() returns a string with all uppercase characters converted into lowercase.

```
greeting = "Welcome To Chili's"

print(greeting.lower())
# Prints: welcome to chili's
```

## String Method `.strip()`

The string method .strip() can be used to remove characters from the beginning and end of a string. A string argument can be passed to the method, specifying the set of characters to be stripped. With no arguments to the method, whitespace is removed.

```
text1 = '   apples and oranges   '
text1.strip()       # => 'apples and oranges'

text2 = '...+...lemons and limes...-...'

# Here we strip just the "." characters
text2.strip('.')    # => '+...lemons and limes...-'

# Here we strip both "." and "+" characters
text2.strip('.+')   # => 'lemons and limes...-'

# Here we strip ".", "+", and "-" characters
text2.strip('.+-')  # => 'lemons and limes'
```

## String Method `.title()`

The string method .title() returns the string in title case. With title case, the first character of each word is capitalized while the rest of the characters are lowercase.

```
my_var = "dark knight"
print(my_var.title())

# Prints: Dark Knight
```

## String Method `.split()`

The string method .split() splits a string into a list of items:

- If no argument is passed, the default behavior is to split on whitespace.
- If an argument is passed to the method, that value is used as the delimiter on which to split the string.

```
text = "Silicon Valley"

print(text.split())
# Prints: ['Silicon', 'Valley']

print(text.split('i'))
# Prints: ['S', 'l', 'con Valley']
```

## Python string method `.find()`

The Python string method `.find()` returns the index of the first occurrence of the string passed as the argument. It returns `-1` if no occurrence is found.

```
mountain_name = "Mount Kilimanjaro"
print(mountain_name.find("o")) # Prints 1 in the console.
```

## String replace

The `.replace()` method is used to replace the occurence of the first argument with the second argument within the string.
The first argument is the old substring to be replaced, and the second argument is the new substring that will replace every occurence of the first one within the string.

```
fruit = "Strawberry"
print(fruit.replace('r', 'R'))

# StRawbeRRy
```

## String Method `.upper()`

The string method `.upper()` returns the string with all lowercase characters converted to uppercase.

```
dinosaur = "T-Rex"

print(dinosaur.upper())
# Prints: T-REX
```

## String Method `.join()`

The string method `.join()` concatenates a list of strings together to create a new string joined with the desired delimiter.
The `.join()` method is run on the delimiter and the array of strings to be concatenated together is passed in as an argument.

```
x = "-".join(["Codecademy", "is", "awesome"])

print(x)
# Prints: Codecademy-is-awesome
```

Print