SOURCE CODE

Web sitemap :

```xml
<?xml version="1.0" encoding="utf-8" ?>
<siteMap xmlns="http://schemas.microsoft.com/AspNet/SiteMap-File-1.0" >
  <siteMapNode url="" title="Home"  description="">
    <siteMapNode url="~/Login.aspx" title="Login"  description="" />
    <siteMapNode url="~/Subject.aspx" title="Subject"  description="" />
  </siteMapNode>
</siteMap>
```

UImaster.master page:

```aspx
<%@ Master Language="C#" AutoEventWireup="true" CodeBehind="Site.Mobile.master.cs"
Inherits="ManagingSchl.Site_Mobile" %>
<%@ Register Src="~/ViewSwitcher.ascx" TagPrefix="friendlyUrls"
TagName="ViewSwitcher" %>

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <meta name="viewport" content="width=device-width" />
    <title></title>
    <asp:ContentPlaceHolder runat="server" ID="HeadContent" />
</head>
<body>
    <form id="form1" runat="server">
    <div>
        <h1>Mobile Master Page</h1>
        <asp:ContentPlaceHolder runat="server" ID="FeaturedContent" />
        <section class="content-wrapper main-content clear-fix">
            <asp:ContentPlaceHolder runat="server" ID="MainContent" />
        </section>
        <friendlyUrls:ViewSwitcher runat="server" />
    </div>
    </form>
</body>
</html>
```

Login.aspx:

```aspx
<%@ Page Title="" Language="C#" MasterPageFile="~/Site1.Master"
AutoEventWireup="true" CodeBehind="Login.aspx.cs" Inherits="ManagingSchl.Login" %>
<asp:Content ID="Content1" ContentPlaceHolderID="head" runat="server">
</asp:Content>
<asp:Content ID="Content2" ContentPlaceHolderID="ContentPlaceHolder1"
runat="server">
    <p>
    This is Login Page</p>
</asp:Content>
```

Subject.aspx:

```
<%@ Page Title="" Language="C#" MasterPageFile="~/UImaster.Master"
AutoEventWireup="true" CodeBehind="Subject.aspx.cs" Inherits="UIProject.Subject" %>
<asp:Content ID="Content1" ContentPlaceHolderID="head" runat="server">
</asp:Content>
<asp:Content ID="Content2" ContentPlaceHolderID="ContentPlaceHolder1"
runat="server">
    <p>
     </p>
<p>
    This is Subject Page</p>
</asp:Content>
```