```
CREATE DATABASE employee_db;
USE employee_db;

SHOW DATABASES;

CREATE TABLE departments (
    dept_id INT PRIMARY KEY,
    dept_name VARCHAR(30),
    location VARCHAR(30)
);

INSERT INTO departments VALUES
(101, 'IT', 'Hyderabad'),
(102, 'HR', 'Karimnagar'),
(103, 'Non-IT', 'Bangalore');

CREATE TABLE employees (
    emp_id INT PRIMARY KEY,
    emp_name VARCHAR(50),
    gender VARCHAR(20),
    age INT,
    dept_id INT,
    city VARCHAR(30),
    FOREIGN KEY (dept_id) REFERENCES departments(dept_id)
);

INSERT INTO employees VALUES
(1, 'Mamatha', 'Female', 21, 101, 'Hyderabad'),
(2, 'Ravi', 'Male', 22, 101, 'Warangal'),
(3, 'Priya', 'Female', 20, 102, 'Karimnagar'),
(4, 'Bhavani', 'Female', 21, 103, 'Sircilla'),
(5, 'Sneha', 'Female', 23, 102, 'Hyderabad');

CREATE TABLE salaries (
    salary_id INT PRIMARY KEY,
    emp_id INT UNIQUE,
    salary INT,
    FOREIGN KEY (emp_id) REFERENCES employees(emp_id)
);

INSERT INTO salaries VALUES
(1, 1, 50000),
(2, 2, 25000),
(3, 3, 30000),
(4, 4, 15000),
(5, 5, 45000);

SHOW TABLES;

SELECT * FROM departments;
SELECT * FROM employees;
SELECT * FROM salaries;
```

departments

dept_id	dept_name	location
101	IT	Hyderabad
102	HR	Karimnagar
103	Non-IT	Bangalore

employees

emp_id	emp_name	gender	age	dept_id	city
1	Mamatha	Female	21	101	Hyderabad
2	Ravi	Male	22	101	Warangal

emp_id	emp_name	gender	age	dept_id	city
3	Priya	Female	20	102	Karimnagar
4	Bhavani	Female	21	103	Sircilla
5	Sneha	Female	23	102	Hyderabad

salaries

salary_id	emp_id	salary
1	1	50,000
2	2	25,000
3	3	30,000
4	4	15,000
5	5	45,000