Employee Database – Creation

Complete MySQL setup: database, three related tables, sample records and verification outputs

What this PDF contains

This file creates the **employee_db** database and its three tables: departments, employees and salaries. It also inserts five sample employees and shows the expected results.

Important before running

The DROP TABLE statements below remove existing data from these three tables before recreating them. Use them only if you are happy to reset this practice database. They do not drop the whole database.

1. Complete creation code

```
-- 1. Create and select the database
CREATE DATABASE IF NOT EXISTS employee_db;
USE employee_db;

-- 2. Display databases
SHOW DATABASES;

-- 3. Remove old tables in child-to-parent order
DROP TABLE IF EXISTS salaries;
DROP TABLE IF EXISTS employees;
DROP TABLE IF EXISTS departments;

-- 4. Create departments table
CREATE TABLE departments (
    dept_id INT PRIMARY KEY,
    dept_name VARCHAR(30),
    location VARCHAR(30)
);

-- 5. Insert department records
INSERT INTO departments VALUES
(101, 'IT', 'Hyderabad'),
(102, 'HR', 'Karimnagar'),
(103, 'Non-IT', 'Bangalore');

-- 6. Create employees table
CREATE TABLE employees (
    emp_id INT PRIMARY KEY,
    emp_name VARCHAR(50),
    gender VARCHAR(20),
    age INT,
    dept_id INT,
    city VARCHAR(30),
    FOREIGN KEY (dept_id) REFERENCES departments(dept_id)
);

-- 7. Insert employee records
INSERT INTO employees VALUES
(1, 'Mamatha', 'Female', 21, 101, 'Hyderabad'),
(2, 'Ravi', 'Male', 22, 101, 'Warangal'),
(3, 'Priya', 'Female', 20, 102, 'Karimnagar'),
(4, 'Bhavani', 'Female', 21, 103, 'Sircilla'),
(5, 'Sneha', 'Female', 23, 102, 'Hyderabad');

-- 8. Create salaries table
CREATE TABLE salaries (
    salary_id INT PRIMARY KEY,
    emp_id INT UNIQUE,
    salary INT,
    FOREIGN KEY (emp_id) REFERENCES employees(emp_id)
);

-- 9. Insert salary records
INSERT INTO salaries VALUES
(1, 1, 50000),
(2, 2, 25000),
(3, 3, 30000),
```

```
(4, 4, 15000),
(5, 5, 45000);

-- 10. Verify all tables
SHOW TABLES;
```

2. Expected output – departments

dept_id	dept_name	location
101	IT	Hyderabad
102	HR	Karimnagar
103	Non-IT	Bangalore

3. Expected output – employees

emp_id	emp_name	gender	age	dept_id	city
1	Mamatha	Female	21	101	Hyderabad
2	Ravi	Male	22	101	Warangal
3	Priya	Female	20	102	Karimnagar
4	Bhavani	Female	21	103	Sircilla
5	Sneha	Female	23	102	Hyderabad

4. Expected output – salaries

salary_id	emp_id	salary
1	1	50,000
2	2	25,000
3	3	30,000
4	4	15,000
5	5	45,000

5. Check the records yourself

```
SELECT * FROM departments;
SELECT * FROM employees;
SELECT * FROM salaries;
SHOW TABLES;
```

Expected table names: departments, employees, salaries.