

Enterprise ITSM Standard Operating Procedures (SOP) Corpus

Note: This document serves as the simulated text extraction of 5 enterprise PDF manuals.

Document 1: Database Migration Protocol (PostgreSQL)

Document ID: SOP-DB-004 **Version:** 4.2 **Last Updated:** 2023-09-15 **Owner:** Database Administration Team

1. Overview

This protocol outlines the steps for migrating PostgreSQL databases from version 13.x to 15.x. All migrations must be executed during the standard maintenance window (Saturdays, 02:00 AM - 05:00 AM EST).

2. Pre-Migration Requirements

- Source Server must be running PostgreSQL 13.4 or higher.
- Target Server must have PostgreSQL 15.2 installed.
- Minimum disk space requirement on the target server is 1.5x the size of the source database.

3. Configuration Changes

Prior to initializing the migration, the following parameters must be updated in `postgresql.conf` on the target server:

- `max_connections = 500` (Increased from default 100)
- `shared_buffers = 16GB`
- `work_mem = 64MB`

4. Rollback Procedure

If the migration fails or takes longer than 150 minutes, immediately initiate the rollback procedure by running the `/opt/scripts/pg_rollback_v2.sh` script.

Document 2: Active Directory Password & Lockout Management

Document ID: SOP-IDM-012 **Version:** 1.1 **Last Updated:** 2024-01-10 **Owner:** Identity and Access Management (IAM)

1. Account Lockout Policy

User accounts are automatically locked after 5 consecutive failed login attempts within a 15-minute window. The automated lockout duration is 30 minutes, after which the system will auto-unlock the account.

2. Manual Unlock via Agent

If a user requires immediate access:

1. Verify user identity using their Employee ID and Manager's Name.

2. Connect to primary Domain Controller: `AD-CORE-01.internal.corp` .
3. Execute PowerShell command: `Unlock-ADAccount -Identity <username> .`
4. If the user is on the legacy system (pre-2022 hires), connect to `AD-LEGACY-02` instead.

3. Error Codes

- **AuthErr-774:** Password expired. Force reset required.
- **AuthErr-775:** Account locked due to brute force protection.
- **AuthErr-779:** Account disabled by HR (Contact HR Ops).

Document 3: GlobalProtect VPN Configuration and Troubleshooting

Document ID: SOP-NET-088 **Version:** 3.5 **Last Updated:** 2023-11-20 **Owner:** Network Security

1. Client Versions

The currently supported GlobalProtect client version is `6.1.2` . Any user running version `5.x` must be forced to upgrade via the portal before connecting.

2. Common Errors & Resolutions

- **Error 45 (Network Unreachable):** Usually caused by ISP MTU mismatches.
 - *Resolution:* Instruct the user to open the VPN client settings and manually set the MTU size to `1350` .
- **Error 99 (Certificate Invalid):** Occurs when the local machine certificate has expired. The enterprise root cert was renewed on `2023-10-01` .
 - *Resolution:* Run `certmgr.msc` and push the new cert from `\\sec-file-share\certs\GP_Root_2024.cer` .

Document 4: Network Switch Firmware Upgrade (Cisco Nexus)

Document ID: SOP-INF-045 **Version:** 2.0 **Last Updated:** 2023-05-12 **Owner:** Infrastructure Operations

1. Upgrade Path Constraints

Cisco Nexus 9000 series switches cannot be directly upgraded from firmware `v9.1` to `v9.3` .

- **Mandatory Path:** `v9.1` -> `v9.2(3)` -> `v9.3(5)` .
- Attempting a direct upgrade will result in a boot-loop.

2. Procedure

1. Backup running config to TFTP server at `192.168.100.55` .
2. Upload new NX-OS binary using SCP.
3. Validate checksum using `show file bootflash:nxos.9.3.5.bin md5sum` . The correct MD5 hash is `a1b2c3d4e5f6...` .
4. Execute `install all nxos bootflash:nxos.9.3.5.bin` .

Document 5: Enterprise WebLogic Application Server Patching

Document ID: SOP-APP-009 **Version:** 1.8 **Last Updated:** 2024-02-28 **Owner:** Middleware Team

1. Pre-Patching Validations

Before applying WebLogic Critical Patch Updates (CPUs), ensure the underlying Java Development Kit (JDK) is compatible.

- WebLogic 14.1.1 requires **JDK 11.0.17** or higher. Do NOT use JDK 17, as it is currently unsupported for legacy ERP applications.

2. Backup Protocol

Always take a complete backup of the WebLogic domain directory.

- *Command:* `tar -czvf /opt/oracle/backups/domain_backup_$(date +%F).tar.gz /opt/oracle/user_projects/domains/base_domain/`

3. Post-Patch Verification

After starting the Admin Server, parse the `AdminServer.log` for the string "Server state changed to RUNNING". If the server is in "ADMIN" state, it indicates a failed patch deployment affecting JDBC data sources.