SELECTIVE ADVERSARIAL SEARCH FOR CHESS UNDER TIME CONSTRAINTS

ABSTRACT

A chess engine must compare adversarial continuations within a limited time budget. Its decisions depend on both the positions it examines and the values assigned to its search frontier. We describe a classical search method that combines negamax backups with alpha–beta pruning, a phase-dependent positional evaluation, and tactical continuation at the nominal horizon. Iterative deepening maintains a completed decision as search proceeds. Move ordering and transposition reuse reduce repeated work, while bounded extensions and late move reductions allocate depth according to tactical relevance. An opening book provides a separate decision rule for covered early positions. We give a common mathematical formulation of these components and identify the assumptions under which pruning preserves a fixed-tree minimax value. The resulting account specifies the decision procedure and its approximation limits; playing strength and the effects of individual components remain open to empirical evaluation.

1 INTRODUCTION

Chess makes the cost of deliberation explicit. Every legal move permits a set of opponent replies, each of which creates further choices. A useful decision therefore requires an estimate of what both players can achieve along a continuation. Exhaustive analysis becomes infeasible as the horizon grows, so a practical engine must decide where to stop, how to value the resulting positions, and which parts of the tree deserve additional computation.

The classical approach couples a search procedure with a positional evaluation (Shannon, 1950). Search exposes consequences that are difficult to recognize from the current board alone. Evaluation supplies information about continuations beyond the examined horizon. These components interact: an immediate material gain may disappear after a recapture, and a forcing sequence may remain unresolved when a uniform depth limit is reached. The choice of search frontier is consequently part of the decision method.

Approach and scope. We study this interaction in a chess engine with fixed evaluation parameters and a finite deliberation budget. The engine searches in the negamax form of minimax. Alpha–beta bounds eliminate continuations that cannot affect an ancestor's decision, and tactical search refines frontier positions. Depth is allocated selectively through extensions and reductions. Search results also inform move ordering and can be reused when the same position is encountered again. Iterative deepening connects these mechanisms to a deadline by retaining the action from the latest completed root search.

The paper describes an integration of established techniques. Its purpose is to make the decision rule precise at the level of states, values, search bounds, and resource allocation. We formulate the positional evaluator, specify the interaction between the main search and its tactical frontier, and state the scope of the fixed-tree pruning guarantee. This treatment also exposes the approximations introduced by reduced searches, compact transposition keys, and finite horizons. Quantitative assessment is reserved for the experiments section.

2 RELATED WORK

Classical chess search. Shannon (1950) formulated computer chess around the combination of look-ahead search and position evaluation. Knuth and Moore (1975) analyzed alpha–beta pruning and the dependence of its cost on move ordering. Schaeffer (1989) examined the history heuristic together with other search enhancements, including transposition tables and killer moves. These techniques provide the search foundation used here. Their interaction matters because a promising move examined early can establish a bound that avoids substantial work later in the same search.

Selective analysis and evaluation. The design of Deep Blue illustrates the importance of nonuniform search, extensions, quiescence analysis, and structured chess knowledge (Campbell et al., 2002). These mechanisms address different sources of error: evaluation estimates positional value, while additional search resolves concrete tactical consequences. Our formulation uses a compact collection of material, placement, pawn, king, and center terms, together with a bounded selective search. The description concerns the roles of these components and the decision rules that connect them.

Learning and search. AlphaZero combines self-play learning with neural policy and value functions and Monte-Carlo tree search (Silver et al., 2018). Grill et al. (2020) interpret its action-selection mechanism through regularized policy optimization. These works show how a search procedure can operate with learned estimates and action preferences. In the present engine, evaluation parameters are prescribed, action preferences come from search statistics and chess features, and values are propagated by adversarial negamax backups. The common issue is how a limited search budget is allocated across candidate continuations.

3 Problem Formulation

Game model. Let $\mathcal{S}$ be the set of legal game states. A state s contains the board, the player to move $c(s)$, castling and en-passant rights, and the history needed to determine draw conditions. We write $\bar{c}$ for the opponent of player c, $\mathcal{A}(s)$ for the legal actions, and $T(s, a)$ for the deterministic successor. Each transition changes the player to move. A *ply* is one such transition.

Let $\mathcal{Z} \subset \mathcal{S}$ denote terminal states. Search assigns a draw value of zero and a checkmate value from the perspective of the player to move:

$$\tau(s, \ell) = \begin{cases} -M + \ell, & \text{if the player to move is checkmated,} \\ 0, & \text{if the search recognizes a draw,} \end{cases} \qquad s \in \mathcal{Z}, \tag{1}$$

where ℓ is the distance from the current root. For the static evaluator E_θ defined in Section 4.1, choose $M - L_{\max} > \sup_{s \notin \mathcal{Z}} |E_\theta(s)|$ so that mate values dominate heuristic scores. Negating the terminal value along a path gives a preference for an earlier forced win and a later forced loss. Draw detection covers stalemate, insufficient material, repetition, and the move-count rule adopted by the engine.

Decision objective. For a nonterminal state, the decision procedure receives a time allowance B and a maximum nominal depth $d_{\max}$. Its output is a legal action $\hat{a} \in \mathcal{A}(s)$. The underlying game objective is the zero-sum terminal outcome. Within the available budget, the engine approximates that objective through a finite tree whose frontier is scored by a heuristic evaluator. An evaluation score is an ordinal measure of positional preference; it carries no calibrated interpretation as a probability of winning.

4 Method

The decision procedure has three stages. It first checks whether an eligible opening-book action is available. Otherwise, it performs root searches at increasing nominal depths. Each search combines bounded adversarial backups with positional evaluation and tactical continuation at the frontier. Algorithm 1 gives the resulting budgeted decision rule.

4.1 Positional Evaluation

For player c, let $F_\theta(s, c)$ measure the strength of that player's position. The parameter collection θ contains fixed piece values, positional tables, and feature weights. We decompose the score as

$$F_\theta(s, c) = M_c(s) + L_c(s) + P_c(s) + K_c(s) + C_c(s) + W_c(s). \tag{2}$$

The terms represent material, piece placement, pawn structure, king safety, central control, and endgame conversion. All use a common score scale. Table 1 summarizes the information they encode.

Table 1: Components of the positional evaluator. Parameters specify the relative strength of each feature within the shared score scale.

Term	Chess information
M_c	Weighted counts of pawns, knights, bishops, rooks, and queens.
L_c	Piece-specific square preferences, with phase-dependent tables for pawns and kings.
P_c	Advancement of passed pawns and penalties for isolated pawns.
K_c	Pawn cover and exposed files near the king, weighted by game phase and opposing heavy pieces.
C_c	Occupation and attacks on central squares and the surrounding ring.
W_c	King coordination and opposing king displacement during conversion of a material lead.

Material and placement. Write $\mathcal{P}_c(s)$ for the pieces of player c, and let $t(p)$ and $q(p)$ denote a piece's type and square. Material and placement take the form

$$M_c(s) = \sum_{p \in \mathcal{P}_c(s)} v_{t(p)}, \qquad L_c(s) = \sum_{p \in \mathcal{P}_c(s)} b_{t(p)}\big(q(p), c; \phi_c(s)\big). \tag{3}$$

The king's material weight is zero because checkmate is handled by Equation (1). Square tables use a consistent orientation for both colors.

Phase and structure. The phase variable is determined by the opponent's remaining material outside pawns and kings. If that material is $m_{\bar{c}}^{\mathrm{np}}(s)$ and the reference scale is $m_0 > 0$, then

$$\phi_c(s) = \max\left\{0, 1 - \frac{m_{\bar{c}}^{\mathrm{np}}(s)}{m_0}\right\}, \qquad b_t(q, c; \phi) = (1-\phi) b_t^{\mathrm{early}}(q, c) + \phi b_t^{\mathrm{late}}(q, c). \tag{4}$$

Nonnegative material gives $\phi_c(s) \in [0, 1]$. For piece types with a single table, the two endpoint tables coincide. This construction allows pawn advancement and king activity to gain value as the opposing force is reduced. The two players can have different phase values in an asymmetric position.

The remaining terms express structural features of the current board. A passed pawn has no opposing pawn ahead on its own or an adjacent file; its bonus grows as promotion approaches. Isolated pawns lack a friendly pawn on an adjacent file. King safety penalizes missing pawn cover and nearby files exposed to heavy pieces, with reduced weight in the endgame. Central control rewards both occupation and attacks. The conversion term becomes active with a sufficient material lead and favors coordinated king activity against an opposing king away from the center.

Evaluation perspective. The static value uses the perspective required by negamax:

$$E_\theta(s) = F_\theta(s, c(s)) - F_\theta(s, \overline{c(s)}) - \kappa\, \mathbf{1}\{c(s) \text{ is in check}\}, \tag{5}$$

where $\kappa \geq 0$ is the check penalty. The evaluator is fixed throughout a search. Search statistics affect exploration order but do not update θ.

4.2 Adversarial Backups and Search Bounds

We first define a reference search with a fixed nominal horizon. Let $Q_\theta(s, \ell)$ be the tactical frontier value specified in Section 4.3. With a maximum path length $L_{\max}$, the reference value is

$$V_d(s, \ell) = \begin{cases} \tau(s, \ell), & s \in \mathcal{Z}, \\ E_\theta(s), & \ell \geq L_{\max}, \\ Q_\theta(s, \ell), & d \leq 0, \\ \max\limits_{a \in \mathcal{A}(s)} \big[-V_{d-1}(T(s, a), \ell + 1)\big], & \text{otherwise.} \end{cases} \tag{6}$$

The sign change accounts for alternating players in a zero-sum game. At a completed root search with $d \geq 1$, the corresponding decision is

$$a_d \in \arg\max_{a \in \mathcal{A}(s)} \big[-V_{d-1}(T(s, a), 1)\big]. \tag{7}$$

This maximization assumes that each opponent reply is selected to maximize the opponent's value. It therefore evaluates a candidate through the strongest response found within the examined tree.

Alpha–beta bounds. Alpha–beta search evaluates this recursion with a window $[\alpha, \beta)$. The lower threshold α tracks the best established alternative; the upper threshold β is inherited from an ancestor's alternatives. If action a_i has returned value q_i, the update is

$$\alpha_{i+1} = \max\{\alpha_i, q_i\}, \qquad \alpha_{i+1} \geq \beta \implies \text{stop expanding the remaining actions.} \tag{8}$$

A recursive negamax call uses the reversed window $[-\beta, -\alpha_i)$. A cutoff establishes a sufficient bound for an ancestor's choice. The returned quantity may therefore be a bound on a node's value.

4.3 Tactical Continuation at the Frontier

A depth limit can interrupt an exchange immediately after one side captures a piece. Static evaluation at that point can assign value to a gain that the opponent can immediately recover. Quiescence search extends the frontier through a restricted set of tactical actions.

Tactical actions and backups. For a nonterminal state, define

$$\mathcal{C}(s) = \begin{cases} \mathcal{A}(s), & c(s) \text{ is in check,} \\ \{a \in \mathcal{A}(s) : a \text{ captures or promotes}\}, & \text{otherwise.} \end{cases} \tag{9}$$

Let $g(s) = -\infty$ when the player to move is in check, and $g(s) = E_\theta(s)$ otherwise. The unpruned tactical target is

$$Q_\theta(s, \ell) = \begin{cases} \tau(s, \ell), & s \in \mathcal{Z}, \\ E_\theta(s), & \ell \geq L_{\max}, \\ \max\left\{ g(s),\ \max\limits_{a \in \mathcal{C}(s)} [-Q_\theta(T(s, a), \ell + 1)] \right\}, & \text{otherwise.} \end{cases} \tag{10}$$

We use $\max \varnothing = -\infty$. Away from check, the static score serves as the *stand-pat* candidate. In check, every legal evasion is considered and the stand-pat candidate is disabled. The path cap ensures termination even when tactical continuations include long sequences of checks.

Alpha–beta bounds also apply within this tactical tree. The stand-pat candidate is a heuristic assumption about the value of stopping local tactical analysis. Positions involving zugzwang can violate that assumption. Tactical continuation resolves only the classes of moves in Equation (9); quiet threats can remain beyond its frontier.

4.4 Selective Depth Allocation

Uniform depth assigns the same remaining horizon to actions with very different tactical consequences. The engine modifies this allocation in two ways. An extension preserves additional depth for checks and advanced pawn moves. A reduction first examines eligible late quiet moves at a shorter horizon. Eligibility excludes captures, promotions, positions already in check, and moves receiving an extension.

Depth allocation. For an action a_i in search order, write

$$d_i = d - 1 + e(s, a_i), \qquad d_i^{\text{test}} = d_i - r(s, a_i, d, i), \tag{11}$$

where $e \geq 0$ and $r \geq 0$ are bounded integer adjustments. A pathwise extension allowance limits accumulated extensions, and $L_{\max}$ bounds the total path length.

Reduced-depth probes. Let $\mathsf{S}(s, d, \alpha, \beta)$ denote the practical bounded search, with root distance and path allowances implicit. For an eligible reduced action with successor $s_i = T(s, a_i)$, a narrow-window probe computes

$$\widetilde{q}_i = -\mathsf{S}\big(s_i, d_i^{\text{test}}, -\alpha_i - \delta, -\alpha_i\big), \tag{12}$$

where $\delta > 0$ is the score resolution. If $\widetilde{q}_i > \alpha_i$, the action is searched again at depth d_i with the full current window. Other actions are searched directly at depth d_i.

The probe asks whether the action can improve the incumbent value. Its shorter horizon provides a low-cost test, but can underestimate a continuation whose benefit appears later. Re-search recovers some promising actions; a reduced action that fails the test receives no deeper verification. The practical search can consequently select a different action from the fixed-horizon rule in Equation (7).

4.5 Ordering and Transposition Reuse

Move ordering uses information from the current position and previous search work. A stored best move receives priority, captures are ranked using the values of the victim and attacker, and promotions receive a tactical preference. Quiet actions are also ranked through killer moves and a history score. Killer moves record quiet actions that caused a cutoff at the same root distance. The history score accumulates credit for quiet actions that caused cutoffs, with larger credit for greater search depth (Schaeffer, 1989). These statistics are exploration preferences within the current decision process.

Cached bounds. A transposition record stores a position key, the searched depth, the returned score, its bound type, and a preferred action. Under a compatible horizon and search context, a record with score v has one of three meanings:

$$V = v \quad \text{(exact)}, \qquad V \geq v \quad \text{(lower bound)}, \qquad V \leq v \quad \text{(upper bound)}. \tag{13}$$

An eligible exact record supplies a value directly. A lower bound at least β, or an upper bound at most α, suffices to end the current query. The stored action can guide ordering even when the value is ineligible.

The engine uses a compact key for the board position and move-count state, filters reuse at nodes with detected repetition, and accepts records whose stored depth meets the current depth request. Mate values are normalized for root distance before reuse. These rules support practical reuse; compatibility with the full history and selective-search context remains a separate requirement. In particular, an entry from a deeper horizon supplies information from a different search tree.

4.6 Opening Knowledge and Budgeted Decisions

The opening book maps covered early positions to legal candidate actions with nonnegative weights $w(s, a)$. For a relative threshold $\eta \in (0, 1]$, define

$$\mathcal{B}_\eta(s) = \left\{ a \in \mathcal{B}(s) : w(s, a) \geq \eta \max_{b \in \mathcal{B}(s)} w(s, b) \right\}. \tag{14}$$

When this set is nonempty and the state lies within the permitted opening prefix, an action is sampled uniformly from $\mathcal{B}_\eta(s)$. For other nonterminal states, the engine invokes search. The book weights are external inputs to this rule.

Iterative deepening. Search proceeds at nominal depths $1, 2, \ldots, d_{\max}$. Let t_d be the elapsed time when iteration d completes and $\hat{a}_d$ its returned action. The budgeted decision is

$$\hat{a}_B = \hat{a}_{d^\star}, \qquad d^\star = \max\{d \leq d_{\max} : t_d \leq B\}, \tag{15}$$

whenever at least one iteration completes. A legal fallback is retained for earlier interruption. The engine can also stop after finding a mate-valued result. A partially explored iteration leaves the last completed decision available.

Algorithm 1 Budgeted chess decision

Require: Nonterminal state s, time allowance B, depth limit $d_{\max}$
If $\mathcal{B}_\eta(s)$ is eligible, return a uniform sample from it
Retain a legal fallback action $\hat{a} \in \mathcal{A}(s)$
for $d = 1, \ldots, d_{\max}$ **do**
    Run selective search at depth d within the remaining time allowance
    If interrupted, stop and retain the previous action
    Retain its returned action as $\hat{a}$
    Stop if a mate-valued result is found
end for
return $\hat{a}$

5 SEARCH PROPERTIES

The value-preserving property of alpha–beta concerns a fixed search tree with compatible leaf values and reused bounds (Knuth and Moore, 1975).

Proposition 1 (Fixed-tree pruning)**.** *Consider a finite alternating game tree with fixed leaf scores from the player-to-move perspective. Alpha–beta search with a full root window returns its exhaustive negamax value, provided every reused bound is valid for the queried subtree. Move ordering can change the amount of work and the choice among tied actions.*

Proof. Negamax propagates each child value with a sign change. After any prefix of the action list, α is at least the largest established candidate. When a candidate reaches β, an ancestor already has an alternative that makes the unexamined remainder irrelevant to its maximizing choice. Pruning that remainder preserves the ancestor's backed-up value. Applying this argument inductively from the leaves to the full-window root proves the claim. □

Scope of the guarantee. The proposition applies to a tactical frontier treated as part of the fixed tree. It also applies to extensions whose allocation is fixed in advance. Late move reductions make depth depend on ordering and intermediate bounds, and cross-depth transposition reuse can change the evaluated horizon. Equation (15) therefore returns the outcome of a completed *selective* iteration.

Computational cost. For a regular tree with branching factor b and depth D, exhaustive search examines b^D leaves. With ideal move ordering and even D, alpha–beta needs $2b^{D/2} - 1$ leaves in the classical best case (Knuth and Moore, 1975). The worst-case order remains exponential. Extensions and tactical search increase the effective depth; reductions decrease work selectively. With at most H transposition records, depth-first traversal stores $O(bD + H)$ move and cache information, excluding the input game history. Wall-clock cost additionally depends on legal-move generation and evaluation.

6 EXPERIMENTS

7 DISCUSSION AND LIMITATIONS

The method has three main approximation limits. First, fixed positional features provide incomplete information about long-term chess outcomes. Phase-dependent tables and structural bonuses encode selected preferences, and their weights require empirical assessment. Heuristic scores alone establish no playing strength or calibration.

Second, finite and selective horizons can miss decisive continuations. Quiescence examines captures, promotions, and check evasions, while quiet tactical ideas may remain unresolved. Stand-pat evaluation assumes that a nonchecked player can maintain the assessed value. Reduced-depth probes can discard a useful action before its benefit becomes visible, and reaching the absolute path cap terminates tactical analysis even in an unsettled position.

Third, reuse depends on information that a compact position key only partially represents. Distinct repetition histories and extension contexts can produce different search values for the same keyed position. Repetition filtering reduces some problematic reuse, but complete compatibility requires those contexts to agree. Accepting a deeper record also changes the finite-horizon query. In addition, the search treats its recognized move-count and repetition draw conditions as terminal; an explicit player decision about claiming a draw is outside this model.

A completed deeper iteration supplies a new decision, with no guarantee that playing strength improves monotonically with depth. Empirical claims about strength, efficiency, and component interactions require controlled comparisons at matched resource budgets. The present paper establishes the method specification and the scope of its analytical properties.

8 Conclusion

We have described a budgeted chess decision procedure built from positional evaluation and selective adversarial search. Negamax specifies the backup rule; alpha–beta uses bounds to avoid unnecessary expansion on a fixed tree. Tactical continuation, depth adjustments, ordering, and transposition reuse determine which continuations receive computation. Iterative deepening connects these components to an interruptible decision process, and the opening book supplies actions in covered early positions. The formulation makes the assumptions of each component explicit and provides a basis for subsequent empirical evaluation.

References

Campbell, M., Hoane, Jr., A. J., and Hsu, F.-h. (2002). Deep Blue. *Artificial Intelligence*, 134(1–2):57–83.

Grill, J.-B., Altché, F., Tang, Y., Hubert, T., Valko, M., Antonoglou, I., and Munos, R. (2020). Monte-Carlo tree search as regularized policy optimization. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 3769–3778. PMLR.

Knuth, D. E. and Moore, R. W. (1975). An analysis of alpha-beta pruning. *Artificial Intelligence*, 6(4):293–326.

Schaeffer, J. (1989). The history heuristic and alpha-beta search enhancements in practice. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 11(11):1203–1212.

Shannon, C. E. (1950). Programming a computer for playing chess. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 41(314):256–275.

Silver, D., Hubert, T., Schrittwieser, J., Antonoglou, I., Lai, M., Guez, A., Lanctot, M., Sifre, L., Kumaran, D., Graepel, T., Lillicrap, T., Simonyan, K., and Hassabis, D. (2018). A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science*, 362(6419):1140–1144.