Instalación de Python y el entorno virtual

```
Danigbani-Aspire-4352:-

Prepar ando para desempaquetar .../python3-setuptools_20.7.0-1_all.deb ...

Desempaquetando python3-setuptools (20.7.0-1) ...

Selectionando el paquete python3-wheel previamente no selectionado.

Prepar ando para desempaquetar .../python3-wheel p.2.9.0-1_all.deb ...

Desempaquetando python3-wheel (0.29.0-1) ...

Desempaquetando python3-wheel (0.29.0-1) ...

Desempaquetando python3-wheel (0.29.0-1) ...


Configurando bitsparadores para nan-db (2.7.5-1) ...

Configurando libpython3-sedvila86 (3.5.1-3) ...

Configurando python3-devila86 (3.5.1-3) ...

Configurando python3-devila86 (3.5.1-3) ...

Configurando python3-sedvila86 (3.5.1-3)
```



```
oani@bani-Aspire-4352: ~
                      show
search
wheel
                                                                                                        Show information about installed packages.
                                                                                                      Show information about installed packages. Search PyPI for packages. Build wheels from your requirements. Compute hashes of package archives. A helper command used for command completion Show help for commands.
                       hash
                       completion
help
                 General Options:
-h, --help
--isolated
                                                                                                     Show help.
Run pip in an isolated mode, ignoring environment variables and user configuration.
Give more output. Option is additive, and can be used up to 3 times.
Show version and exit.
Give less output.
Path to a verbose appending log.
Specify a proxy in the form [user:passwd@]proxy.server:port.
Maximum number of retries each connection should attempt (default 5 times).
Set the socket timeout (default 15 seconds).
Default action when a path already exists: (s)witch, (i)gnore, (w)ipe, (b)ackup.
Mark this host as trusted, even though it does not have valid or any HTTPS.
Path to alternate CA bundle.
Path to SSL client certificate, a single file containing the private key and the certificate in PEM format.
Store the cache data in <dir>
Disable the cache.
                     -v, --verbose
-V, --version
-q, --quiet
--log <path>
                     --proxy <proxy>
--retries <retries>
--timeout <sec>
                     --exists-action <action>
--trusted-host <hostname>
--cert <path>
--client-cert <path>
--cache-dir <ddr>
--no-cache-dir
 顨
                bani@bani-Aspire-4352:~$ pip3 install virtualenv
Collecting virtualenv
Downloading https://files.pythonhosted.org/packages/b6/30/96a02b2287098b23b875bc8c2f58071c35d2efe84f747b64d523721dc2b5/virtualenv-16.0.0-py2.
py3-none-any.whl (1.9MB)
100% | 1.9MB 233kB/s
                       --disable-pip-version-check
 a
                 Installing collected packages: virtualenv
Successfully installed virtualenv-15.0.1
               bani@bani-Aspire-4352:-$ pip3 install --upgrade pip' command.

bani@bani-Aspire-4352:-$ pip3 install --upgrade pip

Collecting pip

Downloading https://files.pythonhosted.org/packages/5f/25/e52d3f31441505a5f3af41213346e5b6c221c9e086a166f3703d2ddaf940/pip-18.0-py2.py3-none-
any.whl (1.3MB)
| 1.3MB 322kB/s
                100% |
Installing collected packages: pip
Successfully installed pip-18.0
bani@bani-Aspire-4352:~$
```

