

Restaurant POS System

Complete API Documentation

BASE URL	https://posapi.uvanij.com/api/
AUTHENTICATION	Authorization: Bearer <posToken> and x-access-token: <posToken>
CENTRAL API CLIENT	lib/services/api_service.dart
CONSTANTS FILE	lib/core/constants/api_constants.dart
LAST UPDATED	July 27, 2026

6

MODULES

19

ENDPOINTS

100%

POST-BASED

Contents

● MODULE 1	Authentication & Session Management	1 endpoint
● MODULE 2	Dashboard, Outlets & Table Management	5 endpoints
● MODULE 3	Menu Management & Product Catalog	3 endpoints
● MODULE 4	Order Taking, KOT & Cart Engine	2 endpoints
● MODULE 5	Billing, Tax & Payment Processing	7 endpoints
● MODULE 6	Offline Data Synchronization Engine	1 endpoint

 MODULE 1

Authentication & Session Management

1.1

Authenticate User Credentials

POST

User/authenticate

https://posapi.uvanij.com/api/User/authenticate

Validates user credentials, returns bearer JWT token, user profile metadata, and assigned outlet location ID.

SERVICE FILE

lib/services/api_service.dart

apiRequestHttpRawBody

CONSTANT

ApiConstants.auth

RESPONSE MODEL

AuthApiResModel

lib/data/models/auth_api_res_model.dart

USED BY

PROVIDER

lib/presentation/view_models/providers/auth_provider.dart

login()

VIEWS

lib/presentation/views/auth/login_view.dart,

lib/presentation/views/auth/widgets/email_form_widget.dart

REQUEST BODY

```
{
  "userId": "username_or_email",
  "password": "user_password",
  "companyCode": "",
  "connectionString": "",
  "url": ""
}
```

FUNCTIONAL ROLE

Authenticates the staff/waiter login. Upon successful verification, the response contains posToken (saved to local Hive storage for subsequent API requests), user details (userId, userName, companySiteUrl), and locationId (stored as the active outletId).

Dashboard, Outlets & Table Management

2.1 Get Order Channel Types

POST

Setting/GetOrderChannelTypes

https://posapi.uvanij.com/api/Setting/GetOrderChannelTypes

Fetches available dining/order channels (e.g., Table, Takeaway, Room Service, Delivery) for a company.

SERVICE FILElib/services/api_service.dartgetOrderChannelTypes()

CONSTANTApiConstants.getOrderChannelTypes

RESPONSE MODELOrderChannelTypesModel lib/data/models/order_channel_types_model.dart

USED BY

PROVIDERlib/presentation/view_models/providers/table_provider.dartloadOrderChannelTypes()

VIEWlib/presentation/views/dashboard/dashboard_view.dart

REQUEST BODY

```
{
  "companyId": 18
}
```

FUNCTIONAL ROLE

Retrieves configured channel types to render dynamic tab headers on the Dashboard view.

2.2 Get Tables & Order Channels By Outlet & Type

POST

Setting/OrderChannellistByType

https://posapi.uvanij.com/api/Setting/OrderChannellistByType

Fetches the list of tables/dining channels for an outlet, including table seating capacity and active order status.

SERVICE FILElib/services/api_service.dartgetOrderChannelListByType(), getTablesByOutlet(), getTablesByOutletEnhanced()

CONSTANTApiConstants.getTablesByOutlet

REPOSITORY FILElib/data/repositories/table_repository.dartfetchTablesFromOrderChannelAPI()

RESPONSE MODELOrderChannelListApiResponseModel lib/data/models/order_channel_list_api_response_model.dart

USED BY

REPOSITORYlib/data/repositories/table_repository.dart

PROVIDERlib/presentation/view_models/providers/table_provider.dartfetchTables(), loadTables()

VIEWSlib/presentation/views/dashboard/dashboard_view.dart, lib/presentation/views/dashboard/widgets/enhanced_table_card.dart

REQUEST BODY

```
{
  "orderChanelType": "Table",
  "outletId": 10080
}
```

FUNCTIONAL ROLE

Serves as the backbone of table management on the dashboard. Returns each table's ID (orderChannelId), name, capacity, and active order array (orderList) containing order ID, order number, and billing status (isBilled).

2.3 Save / Create Order Head

POST

Order/saveOrderHead

<https://posapi.uvanij.com/api/Order/saveOrderHead>

Initializes a new order header for a table or takeaway channel, changing table status to Occupied and returning a generated orderId.

SERVICE FILE lib/services/api_service.dart `saveOrderHead()`, `createOrderHead()`

CONSTANT ApiConstants.createOrderHead

RESPONSE MODEL CreateOrderHeadApiResModel lib/data/models/create_order_head_api_res_model.dart

USED BY

PROVIDERS lib/presentation/view_models/providers/table_provider.dart (`occupyTable()`),
lib/presentation/view_models/providers/animated_cart_provider.dart (`createOrderHead()`),
lib/presentation/view_models/providers/order_provider.dart

VIEWS lib/presentation/views/dashboard/widgets/table_action_dialogs.dart,
lib/presentation/views/order_taking/cart/cart_view.dart

REQUEST BODY

```
{
  "orderChannelId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "waiterId": "cceb307f-2f01-4e0e-8f28-e07ba8e941ac",
  "customerName": "Guest Table 5",
  "outletId": 10080,
  "userId": "user_123",
  "custPhoneNo": "9876543210",
  "totalAdult": 2,
  "totalChild": 0,
  "custEmailId": ""
}
```

FUNCTIONAL ROLE

Invoked when occupying a table or starting a new order. Creates an entry in the backend order head table and generates an orderId needed to append KOT items and generate bills.

2.4 Get Running Table Orders

POST

Order/getRunningTable

<https://posapi.uvanij.com/api/Order/getRunningTable>

Retrieves active/running orders associated with a given table ID.

SERVICE FILE lib/services/api_service.dart `getRunningTable()`

RESPONSE MODEL Map<String, dynamic> Raw JSON containing running order array

USED BY

PROVIDERS lib/presentation/view_models/providers/table_provider.dart (`getRunningTableData()`),
lib/presentation/view_models/providers/orders_management_provider.dart

VIEWS lib/presentation/views/dashboard/dashboard_view.dart,
lib/presentation/views/dashboard/widgets/multi_order_management_dialog.dart,
lib/presentation/views/orders/orders_management_view.dart

REQUEST BODY

```
{
  "searchString": "",
  "outletId": 10080,
  "orderChannelId": "table_guid_id",
  "isDesc": true
}
```

FUNCTIONAL ROLE

Supports multi-order tracking per table, allowing waiters to view running orders on occupied tables.

2.5 Update Order Head Status

POST

Order/UpdateOrderHeadStatus

<https://posapi.uvanij.com/api/Order/UpdateOrderHeadStatus>

Updates the order status (Occupied, Billed, Settled, Vacated, Cancelled).

SERVICE FILE `lib/services/api_service.dart` `updateOrderHeadStatus()`

RESPONSE MODEL `Map<String, dynamic>` Status update result map

USED BY

PROVIDERS `lib/presentation/view_models/providers/table_provider.dart` (`updateTableStatus()`, `clearTable()`),
`lib/presentation/view_models/providers/orders_management_provider.dart` (`updateOrderStatus()`)

VIEWS `lib/presentation/views/dashboard/widgets/table_action_dialogs.dart`,
`lib/presentation/views/dashboard/widgets/multi_order_management_dialog.dart`

REQUEST BODY

```
{
  "companyId": 18,
  "orderHeadId": "order_guid_id",
  "statusId": 7,
  "userId": "user_guid_id"
}
```

FUNCTIONAL ROLE

Transitions order states across the table lifecycle (e.g. status ID 6 = Occupied, status ID 7 = Settled/Vacated).

Menu Management & Product Catalog

3.1 Get All Product Categories

POST

product/GetAllProductCategory

https://posapi.uvanij.com/api/product/GetAllProductCategory

Fetches food categories (Appetizers, Main Course, Drinks, Desserts) for an outlet.

SERVICE FILElib/services/api_service.dart *getAllProductCategories()*

RESPONSE MODELCategory list JSON response

USED BY

PROVIDERlib/presentation/view_models/providers/menu_provider.dart*fetchCategories()*

VIEWlib/presentation/views/menu_management/menu_view.dart

REQUEST BODY

```
{
  "outletId": 10080
}
```

FUNCTIONAL ROLE

Dynamically populates menu category filter tabs in the order taking view.

3.2 Get Item / Product Search

POST

Product/GetItemSearch

https://posapi.uvanij.com/api/Product/GetItemSearch

Searches and retrieves menu items/dishes by category or keyword.

SERVICE FILElib/services/api_service.dart *apiRequestHttpRawBody*

CONSTANTApiConstants.getItemSearch

RESPONSE MODELProduct list JSON array Item ID, Name, Price, Category ID, Image URL

USED BY

PROVIDERlib/presentation/view_models/providers/menu_provider.dart*fetchMenuItems(), searchProducts()*

VIEWSlib/presentation/views/menu_management/menu_view.dart, lib/presentation/views/menu_management/widgets/menu_grid.dart

REQUEST BODY

```
{
  "outletId": 10080,
  "categoryId": 0,
  "searchKey": ""
}
```

FUNCTIONAL ROLE

Fetches products to render the menu grid in order taking screens.

3.3 Get Customer Wishlist Items

POST

frontend/GetCustomerWishItems

<https://posapi.uvanij.com/api/frontend/GetCustomerWishItems>

Fetches saved customer favorite/wishlist food items.

SERVICE FILE lib/data/repositories/wishlist_repository.dart `getCustomerWishItems()`

RESPONSE MODEL WishListApiResModel lib/data/models/wishlist_api_res_model.dart

USED BY

REPOSITORY lib/data/repositories/wishlist_repository.dart

REQUEST BODY

```
{
  "wishlistCategoryId": 237,
  "customerId": 300,
  "companyId": 112
}
```

FUNCTIONAL ROLE

Loads customer favorite items for quick ordering.

Order Taking, KOT & Cart Engine

4.1 Create KOT With Order Details

POST

Order/CreateKotWithOrderDetails

<https://posapi.uvanij.com/api/Order/CreateKotWithOrderDetails>

Generates a Kitchen Order Ticket (KOT) and attaches line items to an active order ID.

SERVICE FILE lib/services/api_service.dart `createKotWithOrderDetails()`

CONSTANT ApiConstants.createKotWithOrderDetails

RESPONSE MODEL CreateKotWithOrderDetailsApiResponseModel lib/data/models/create_kot_with_order_details_api_res_model.dart

USED BY

PROVIDER lib/presentation/view_models/providers/animated_cart_provider.dart `generateKOT()`

VIEWS lib/presentation/views/order_taking/cart/cart_view.dart,
lib/presentation/views/order_taking/cart/widgets/kot_pdf_viewer_dialog.dart

REQUEST BODY

```
{
  "userId": "user_guid_id",
  "outletId": 10080,
  "orderId": "order_guid_id",
  "kotNote": "Less spicy, extra cheese",
  "orderDetails": [
    {
      "itemId": "item_guid_1",
      "itemName": "Paneer Butter Masala",
      "quantity": 2,
      "rate": 250.0,
      "amount": 500.0,
      "specialInstruction": "Make it medium spicy"
    }
  ]
}
```

FUNCTIONAL ROLE

Dispatches items from the cart to kitchen printers, updates order status, and generates a printable KOT voucher.

4.2 Get Order Details By ID

POST

Order/getOrderDetailById

<https://posapi.uvanij.com/api/Order/getOrderDetailById>

Fetches complete order item details for editing or review.

SERVICE FILE lib/services/api_service.dart `getOrderDetailById()`

RESPONSE MODEL OrderDetailApiResponseModel lib/data/models/order_detail_api_response_model.dart

USED BY

PROVIDERS lib/presentation/view_models/providers/animated_cart_provider.dart (`loadOrderDetails()`),
lib/presentation/view_models/providers/orders_management_provider.dart (`fetchOrderDetails()`)

VIEWS lib/presentation/views/order_taking/cart/cart_view.dart, lib/presentation/views/orders/widgets/order_detail_view.dart

REQUEST BODY

```
{
  "orderId": "order_guid_id"
}
```

FUNCTIONAL ROLE

Loads existing order line items into the cart view when an occupied table is reopened.



Billing, Tax & Payment Processing

5.1 Get All Taxes

POST

Order/getTaxDt<https://posapi.uvanij.com/api/Order/getTaxDt>

Retrieves tax configuration rates (GST 5%, CGST 2.5%, SGST 2.5%) for a company.

SERVICE FILE `lib/services/api_service.dart` `getAllTaxes()`

RESPONSE MODEL Tax details JSON response

USED BY

PROVIDER `lib/presentation/view_models/providers/tax_provider.dart` `fetchTaxes()`

VIEW `lib/presentation/views/billing/widgets/generate_bill_summary_dialog.dart`

REQUEST BODY

```
{
  "companyId": 18
}
```

FUNCTIONAL ROLE

Calculates GST and tax breakdowns during bill summary generation.

5.2 Get Payment Modes

POST

Order/GetPaymentMode<https://posapi.uvanij.com/api/Order/GetPaymentMode>

Fetches available payment methods (Cash, Card, UPI, QR Code, Online).

SERVICE FILE `lib/services/api_service.dart` `getAllPaymentModes()`

CONSTANT `ApiConstants.getPaymentModes`

RESPONSE MODEL `PaymentModeApiResModel` `lib/data/models/payment_mode_api_res_model.dart`

USED BY

PROVIDER `lib/presentation/view_models/providers/billing_provider.dart` `loadPaymentModes()`

VIEW `lib/presentation/views/billing/widgets/generate_bill_summary_dialog.dart`

REQUEST BODY

```
{}
```

Empty JSON map as required by endpoint

FUNCTIONAL ROLE

Renders full-width selectable payment mode chips in the bill summary popup dialog.

5.3 Get Order Detail For Bill

POST

Order/GetOrderDetailForBill

<https://posapi.uvanij.com/api/Order/GetOrderDetailForBill>

Fetches order breakdown specifically structured for bill generation.

SERVICE FILE lib/services/api_service.dart `getOrderDetailForBill()`

RESPONSE MODEL GetOrderDetailForBillResponse lib/data/models/bill_generation_models.dart

USED BY

PROVIDER lib/presentation/view_models/providers/billing_provider.dart `loadOrderDetailForBill()`

VIEW lib/presentation/views/billing/widgets/generate_bill_summary_dialog.dart

REQUEST BODY

```
{
  "orderId": "order_guid_id"
}
```

FUNCTIONAL ROLE

Supplies item totals, subtotal, discount, and tax calculations for the bill preview modal.

5.4 Get Customer By Mobile Number

POST

Order/getCustomerByMobileNo

<https://posapi.uvanij.com/api/Order/getCustomerByMobileNo>

Searches customer profiles by 10-digit phone number.

SERVICE FILE lib/services/api_service.dart `getCustomerByMobileNo()`

RESPONSE MODEL CustomerByMobileResponse lib/data/models/bill_generation_models.dart

USED BY

PROVIDER lib/presentation/view_models/providers/billing_provider.dart `fetchCustomerByPhone()`

VIEW lib/presentation/views/billing/widgets/generate_bill_summary_dialog.dart

REQUEST BODY

```
{
  "contactNo": "9876543210"
}
```

FUNCTIONAL ROLE

Auto-fills customer profile info when entering a 10-digit mobile number during billing.

5.5 Create Bill

POST

Order/CreateBill

<https://posapi.uvanij.com/api/Order/CreateBill>

Generates a final bill record and produces a printable PDF receipt.

SERVICE FILE `lib/services/api_service.dart` `createBill()`

RESPONSE MODEL `CreateBillResponse` `lib/data/models/bill_generation_models.dart`

USED BY

PROVIDER `lib/presentation/view_models/providers/billing_provider.dart` `generateBill()`

VIEW `lib/presentation/views/billing/widgets/generate_bill_summary_dialog.dart`

REQUEST BODY

```
{
  "orderId": "order_guid_id",
  "subTotal": 500.0,
  "taxAmount": 25.0,
  "discountAmount": 0.0,
  "grandTotal": 525.0,
  "paymentModeId": 1,
  "customerPhone": "9876543210",
  "userId": "user_guid_id"
}
```

FUNCTIONAL ROLE

Saves the bill, returns billId and printable bill details for BillPDFViewerDialog.

5.6 Save Payment

POST

Order/SavePayment

<https://posapi.uvanij.com/api/Order/SavePayment>

Records payment transaction and settles bill/table.

SERVICE FILE `lib/services/api_service.dart` `savePayment()`

RESPONSE MODEL `SavePaymentResponse` `lib/data/models/bill_generation_models.dart`

USED BY

PROVIDER `lib/presentation/view_models/providers/billing_provider.dart` `processPayment()`

VIEW `lib/presentation/views/payment/payment_page.dart`

REQUEST BODY

```
{
  "billId": "bill_guid_id",
  "paymentModeId": 1,
  "amountPaid": 525.0,
  "transactionReference": "TXN987654",
  "userId": "user_guid_id"
}
```

FUNCTIONAL ROLE

Finalizes bill settlement, updating order status to Paid and table status to Settled/Available.

5.7 Get Bill Detail By Bill ID

POST

Order/getBillDetailByBillId

<https://posapi.uvanij.com/api/Order/getBillDetailByBillId>

Fetches complete bill details by billId for reprint or verification.

SERVICE FILE lib/services/api_service.dart *getBillDetailByBillId()*

RESPONSE MODEL BillDetailsResponse lib/data/models/bill_details_response.dart

USED BY

PROVIDER lib/presentation/view_models/providers/billing_provider.dart *fetchBillDetail()*

VIEWS lib/presentation/views/billing/widgets/bill_success_dialog.dart,
lib/presentation/views/billing/widgets/bill_pdf_viewer_dialog.dart

REQUEST BODY

```
{
  "billId": "bill_guid_id"
}
```

FUNCTIONAL ROLE

Retrieves structured invoice items, tax lines, and payment status for receipt printing.



Offline Data Synchronization Engine

6.1 Sync Tables & Orders (Background Queue)

POST

`tables ($baseUrl/tables), orders ($baseUrl/orders)`

`https://your-api-server.com/api/tables` & `https://your-api-server.com/api/orders`

Syncs offline Hive storage items to the backend when internet connectivity is re-established.

SERVICE FILE `lib/services/sync_service.dart` `_syncTables()`, `_syncOrders()`, `syncAllData()`

USED BY

SERVICE `lib/services/sync_service.dart`

REQUEST BODY

No request body — see functional description

FUNCTIONAL ROLE

Scans unsynced Hive records (`table.synced == false`, `order.synced == false`) and pushes them to the server via background batch requests.

Summary Matrix — All Endpoints

A consolidated, at-a-glance reference of every endpoint covered in this document.

#	ENDPOINT / ROUTE	METHOD	PURPOSE	SERVICE FILE	PROVIDER / REPOSITORY	VIEW / UI COMPONENT
1	User/authenticate	POST	User login & token auth	api_service.dart	auth_provider.dart	login_view.dart
2	Setting/GetOrderChannelTypes	POST	Get order channel types	api_service.dart	table_provider.dart	dashboard_view.dart
3	Setting/OrderChannelListByType	POST	Get tables by outlet & type	api_service.dart, table_repository.dart	table_provider.dart	dashboard_view.dart, enhanced_table_card.dart
4	Order/saveOrderHead	POST	Create new order header	api_service.dart	table_provider.dart, animated_cart_provider.dart	table_action_dialogs.dart, cart_view.dart
5	Order/getRunningTable	POST	Get running table orders	api_service.dart	table_provider.dart, orders_management_provider.dart	multi_order_management_dialog.dart, orders_management_view.dart
6	Order/UpdateOrderHeadStatus	POST	Update order/table status	api_service.dart	table_provider.dart, orders_management_provider.dart	table_action_dialogs.dart
7	product/GetAllProductCategory	POST	Get menu categories	api_service.dart	menu_provider.dart	menu_view.dart
8	Product/GetItemSearch	POST	Search & fetch menu items	api_service.dart	menu_provider.dart	menu_view.dart, menu_grid.dart
9	frontend/GetCustomerWishItems	POST	Get customer wishlist items	wishlist_repository.dart	wishlist_repository.dart	Wishlist view
10	Order/CreateKotWithOrderDetails	POST	Create KOT with items	api_service.dart	animated_cart_provider.dart	cart_view.dart, kot_pdf_viewer_dialog.dart
11	Order/getOrderDetailById	POST	Get detailed order items	api_service.dart	animated_cart_provider.dart, orders_management_provider.dart	cart_view.dart, order_detail_view.dart
12	Order/getTaxDt	POST	Get company tax rates	api_service.dart	tax_provider.dart	generate_bill_summary_dialog.dart
13	Order/GetPaymentMode	POST	Get payment modes	api_service.dart	billing_provider.dart	generate_bill_summary_dialog.dart
14	Order/GetOrderDetalForBill	POST	Get order details for bill	api_service.dart	billing_provider.dart	generate_bill_summary_dialog.dart
15	Order/getCustomerByMobileNo	POST	Customer phone lookup	api_service.dart	billing_provider.dart	generate_bill_summary_dialog.dart
16	Order/CreateBill	POST	Generate official bill	api_service.dart	billing_provider.dart	generate_bill_summary_dialog.dart
17	Order/SavePayment	POST	Record payment settlement	api_service.dart	billing_provider.dart	payment_page.dart
18	Order/getBillDetailByBillId	POST	Get bill receipt details	api_service.dart	billing_provider.dart	bill_success_dialog.dart, bill_pdf_viewer_dialog.dart
19	\$baseUrl/tables & orders	POST	Offline sync queue	sync_service.dart	sync_service.dart	Background Sync Task