

MOTORS

General Purpose AC Motors

GRAINGER CHOICE®

Find the ★. Find Solutions. Find Great Prices.



No. 5K191



No. 6K562



Capacitor-Start Totally Enclosed Fan-Cooled Rigid Base-Mount Motors

- Rotation: CW/CCW
- Bearings: ball
- Max. ambient temp.: 40°C

For use in dirty, dusty, and nonhazardous environments. Can be used in place of open dripproof motors. UL Recognized and CSA Certified or UL Recognized for US and Canada.

HP	Nameplate RPM	Frame	Thermal Protection	Voltage	Full Load Amps	Service Factor	Ins. Class	Overall Length	Item No.
1/4	1725	48	Auto	115/208-230	5.6/2.7-2.8	1.00	B	10 1/2"	5K191
	1725	56	None	115/208-230	5.6/2.7-2.8	1.15	B	11"	5K262
	1725	56	Auto	115/208-230	5.6/2.7-2.8	1.15	B	11"	5K263
	1140	56	None	115/208-230	6.9/3.0-3.4	1.15	B	11 3/8"	5KUE5
1/2	3450	48	Auto	115/208-230	4.7/2.4-2.3	1.00	B	9 3/4"	5K481
	3450	48	None	115/208-230	4.7/2.4-2.3	1.00	F	10"	5KUE6
	1725	48	Auto	115/208-230	6.6/3.0-3.3	1.15	B	10 1/4"	5K192
	1725	56	None	115/208-230	6.0/3.0-3.0	1.15	B	11"	4K936
3/4	1725	56	Auto	115/208-230	7.0/3.3-3.5	1.15	B	10 5/8"	5K121
	1725	56	Manual	115/208-230	6.6/3.0-3.3	1.15	B	11"	5KUE8
	1140	56	None	115/208-230	6.8/3.4-3.4	1.00	B	11 3/8"	5K502
	3450	48	Auto	115/208-230	6.3/3.4-3.3	1.00	B	10 3/8"	6K482
1	3450	48	Manual	115/208-230	6.5/3.5-3.4	1.00	B	11 1/2"	5KUE9
	3450	48	None	115/208-230	6.5/3.5-3.4	1.00	B	10 3/8"	5KUF0
	3450	56	Manual	115/208-230	8.0/3.8-4.0	1.00	B	11 3/8"	6K184
	3450	56	Auto	115/208-230	8.6/4.1-4.4	1.00	B	11 7/8"	5KUF1
1 1/2	3450	56	None	115/208-230	8.6/4.1-4.4	1.00	B	11 3/8"	5KUF2
	1725	48	Auto	115/208-230	8.5/4.2-4.3	1.00	F	11 1/8"	5K193
	1725	48	None	115/208-230	8.2/4.1-4.1	1.00	B	11"	6K177
	1725	56	Auto	115/208-230	9.0/4.3-4.5	1.15	B	11 3/8"	6K122
2	1725	56	Manual	115/208-230	9.0/4.3-4.5	1.15	B	11"	6K637
	1725	56	None	115/208-230	9.0/4.3-4.5	1.15	B	11 3/8"	6K937
	1140	56	None	115/208-230	10.6/5.4-5.3	1.00	F	13 3/8"	5K672
	3450	48	None	115/208-230	11.1/5.4-5.6	1.00	F	12"	5KUF4
3	3450	56	Manual	115/208-230	10.4/5.3-5.2	1.00	B	11 1/8"	6K358
	3450	56	Auto	115/208-230	10.4/5.3-5.2	1.15	B	11 3/8"	6K483
	1725	56	Auto	115/208-230	11.4/5.7-5.7	1.15	F	11 7/8"	6K123
	1725	56	Manual	115/208-230	11.4/5.7-5.7	1.15	B	11 7/8"	6K639
4	1725	56	None	115/208-230	11.4/5.7-5.7	1.15	F	11 3/8"	6K938
	1140	56H	None	115/208-230	10.6/5.4-5.3	1.15	B	13 3/8"	5KUF6
	3450	56	Manual	115/208-230	13.6/6.9-6.8	1.00	B	12 3/8"	5K960
	3450	56	Auto	115/208-230	13.6/6.9-6.8	1.00	B	12 3/8"	6K484
5	3450	56	None	115/208-230	13.6/6.9-6.8	1.00	B	12 3/8"	5KUF7
	1740	182	None	115/230	13.8/6.9	1.00	F	14 1/8"	5K485
	1725	56H	None	115/208-230	14.0/6.9-7.0	1.15	B	12 3/8"	1K065
	1725	56H	Auto	115/208-230	9.9/5.2-5.0	1.15	B	12 1/8"	6K562
6	1725	56H	Manual	115/208-230	14.0/6.9-7.0	1.15	B	12 3/8"	6K640
	1725	56HZ	None	115/208-230	14.0/6.9-7.0	1.15	B	12 3/4"	6K407
	1725	56HZ	Manual	115/208-230	14.0/6.9-7.0	1.15	B	12 3/4"	6K418
	1725	56HZ	Auto	115/208-230	14.0/6.9-7.0	1.15	B	12 3/4"	5KUF8
7 1/2	1725	143T	None	115/208-230	14.0/6.9-7.0	1.15	B	12 3/4"	6K827
	3450	56H	Manual	115/208-230	14.6/8.1-7.4	1.00	B	12 7/8"	6K338
	3450	56H	Auto	115/208-230	14.6/8.1-7.4	1.00	B	12 7/8"	6KJ53
	3450	143T	None	115/208-230	14.6/8.1-7.4	1.00	B	13 1/4"	3K300
8	1750	184	None	115/230	18.4/9.2	1.00	F	15 1/8"	5K486
	1725	56H	None	115/208-230	14.4/8.0-7.2	1.15	B	13 3/8"	1K066
	1725	56H	Auto	115/208-230	14.4/8.0-7.2	1.15	B	13-14 1/8"	5K565
	1725	56H	Manual	115/208-230	14.4/8.0-7.2	1.15	B	13 3/8"	5K641
9	1725	56HZ	None	115/208-230	14.4/8.0-7.2	1.15	B	14 1/4"	6K419
	1725	56HZ	Manual	115/208-230	14.4/8.0-7.2	1.15	B	14 1/4"	6K420
	1725	56HZ	Auto	115/208-230	14.4/8.0-7.2	1.15	B	14 1/4"	5KUG0
	1725	145T	None	115/208-230	14.4/8.0-7.2	1.15	B	14 1/4"	6K828
10	3450	56H	Manual	115/208-230	19.5/10.8-9.7	1.00	B	13 3/8"	5K961
	3450	56H	Auto	115/208-230	19.5/10.8-9.7	1.15	B	13 3/8"	5KUG3
	3450	56H	None	115/208-230	19.5/10.8-9.7	1.00	B	13 3/8"	5KUG4
	3450	145T	None	115/208-230	19.5/10.8-9.7	1.00	B	14 1/4"	3K344
11	1740	182T	None	115/230	23.6/11.8	1.00	F	15 1/8"	5K966
	1725	56H	None	115/208-230	18.9/10.3-9.4	1.00	F	13 3/8"	1K067
	1725	56H	Auto	115/208-230	18.9/10.3-9.4	1.00	F	14 1/8"	5KUG5
	1725	56HZ	Auto	115/230	18.9/9.4	1.00	F	14 1/8"	5KUG6
12	1725	56HZ	None	115/208-230	18.8/10.2-9.4	1.00	B	14 3/8"	5KUG7
	3540	182T	None	115/230	32.0/16.0	1.00	F	16 3/8"	6K145
	3450	145T	None	230	15.4	1.00	F	15"	5KUG8
	1740	184T	None	115/230	30.0/15.0	1.00	F	17 3/8"	5K967
13	3540	184T	None	230	19.6	1.15	F	17 1/2"	6K146
	1745	213T	None	230	23.0	1.00	F	19 3/8"	5K968
	1740	184T	None	230	22.0	1.00	F	18 1/8"	2TJ12
	3530	213T	None	230	30.3	1.00	F	20"	6K179
14	1745	215T	None	230	30	1.00	F	22 1/8"	6K176
	3535	215T	None	230	41.5	1.00	F	22 1/8"	5UKH0
	1730	215T	None	230	38.0	1.00	F	22 1/8"	5UKH1

* Capacitor-start, capacitor-run. † Totally enclosed nonventilated.

DOWNLOAD the Grainger Mobile App!

- Easy Search
- Create Lists
- Track Orders
- On-The-Go Inventory



Apple, the Apple logo and iPhone are trademarks of Apple Inc. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.

