



Band Mount



Cradle Base Mount



Ring Mount



Stud Mount



T-Flex Mount



## Shaded Pole Direct-Drive Blower/Fan Motors

- 42Y frame (5" body dia.)
- Enclosure: open air-over, except No. 4UU91 is totally enclosed air-over
- Thermal protection: auto
- Service factor: 1.0
- Bearings: sleeve
- Max. ambient temp.: 40°C
- Duty: continuous air-over

These motors are suitable for unit heaters, condensers, furnace blowers, air circulators, fans, and a wide range of other shaft-mounted fan and blower equipment. No. 4UU91 has a 5.0 cu.-in. junction box. Nos. 4KA23, 4KA20, and 4KA22 are used in Coleman furnaces. No. 4KA49 has a 2½" ring dia. and is for Lear-Siegler furnaces. All models are UL Recognized and CSA Certified.

Mounting	HP	Nameplate RPM	Rotation	Voltage	Full Load Amps	Ring to Ring Center	Stud Pattern	Shaft Dia.	Shaft Length	Mfr. Model	Item No.
<b>1-Speed</b>											
Band	½	1050	CCWLE	115	3.1	—	—	½"	2½"	BL6409	4KA23
	⅞	1050	CCWLE	115	3.9	—	—	½"	2½"	BL6408	4KA20
	⅞	1000	CCWLE	115	7.8	—	—	½"	2½"	BL6407	4KA22
Cradle Base	⅞	1000	CCWLE	115	3.2	4⅞"	—	¾"	3¼"	9694	4UU96
	⅞	1050	CWSE	115/208-230	4.0/2.0-2.0	4⅞"	2½" x 2½"	¾"	2¼"	RF6402	4UU74
	⅞	1050	CCWLE	115/208-230	4.0/2.0-2.0	4⅞"	2½" x 2½"	¾"	2¼"	RF6403	4UU76
	⅞	1550	CWLE	115/208-230	4.0/2.0-2.0	4⅞"	2½" x 2½"	¾"	2¼"	RF4400	4UU75
	⅞	1550	CCWLE	115/208-230	4.0/2.0-2.0	4⅞"	2½" x 2½"	¾"	2¼"	RF4401	4UU77
	⅞	1550	CWLE	230	2.9	4⅞"	—	½"	2½"	9638	4MA15 †
	⅞	1550	CWLE	115	6.4	4⅞"	—	½"	2½"	9640	4MA23 †
	⅞	1550	CCWSE	208-230	3.2	4⅞"	—	½"	2½"	593	4MA13 †
	⅞	1550	CWSE	115/208-230	2.8/1.4	5⅞"	2½" x 2½"	¾"	2¼"	612A	4UU73
	⅞	1550	CCWSE	115/208-230	2.8/1.4-1.4	5⅞"	2½" x 2½"	¾"	2¼"	613A	4UU78
Ring	⅞	1050	CCWLE	115	5.2	4⅞"	—	½"	4"	9706	4VU34
	⅞	1050	CCWLE	115	5.2	4⅞"	2¼" x 3⅞"	½"	5"	BLR6403	4UU99
	⅞	1050	CWSE	115	4.2	4¼"	—	½"	2⅞"	9646	4KA49
	⅞	1050	CCWLE	115	5.5	4⅞"	2¼" x 3⅞"	½"	3"	BLR6402	4UU97
	⅞	1050	CCWLE	115	7.0	4⅞"	2⅞" x 4"	½"	3¼"	345A	4VU35
	⅞	1050	CCWLE	115	6.7	4⅞"	2⅞" x 4"	½"	3¼"	9690	4UU89
	⅞	1050	CCWLE	115	9.4	5⅞"	2¼" x 3⅞"	½"	3⅞"	BLR6405	4UU81
Stud	⅞	1050	CCWLE	115	2.8	—	2¼" x 3⅞"	¾"	1⅞"	BLR6407	4UU94 *
	⅞	1050	CCWLE	115	3.3	—	2¼" x 3⅞"	½"	2½"	U6433	4UU91
T-Flex	⅞	1050	CCWLE	115	6.5	—	—	½"	3½"	ONR6026	4MB32
	⅞	1050	CCWLE	115	8.9	—	—	½"	4¼"	BL6531	4MB34
<b>2-Speed</b>											
Stud	⅞	1050	CCWLE	115	3.48	—	2¼" x 3⅞"	¾"	1⅞"	BLR6405	4UU92 *
<b>3-Speed</b>											
Ring	⅞	1050	CCWLE	115	5.1	4⅞"	2⅞" x 4"	½"	3¼"	9703	4UU83
	⅞	1050	CCWLE	115	6.3	4⅞"	2¼" x 3⅞"	½"	3⅞"	9701	4UU79
	⅞	1050	CCWLE	115	6.8	5⅞"	2⅞" x 4"	½"	5"	9695	4UY10
	⅞	1050	CCWLE	208-230	3.4	5⅞"	2⅞" x 4"	½"	5"	9696	4UY11
T-Flex	⅞	1050	CCWLE	115	8.2	5⅞"	2¼" x 3⅞"	½"	3⅞"	BLR6404	4UU80
	⅞	1050	CCWLE	115	8.2	—	—	½"	4⅞"	BL6534	4MB48

Mounting	HP	Nameplate RPM	Rotation	Voltage	Full Load Amps	Ring to Ring Center	Bolt Circle Dia.	Shaft Dia.	Shaft Length	Mfr. Model	Item No.
<b>1-Speed, 3 Mounting Studs</b>											
Ring	⅞	1050	CCWLE	115	5.2	4⅞"	4⅞"	½"	5"	BL6410	4KA21
	⅞	1050	CCWLE	208-230	2.6	4⅞"	4⅞"	½"	5"	B6411	4KA45
	⅞	1050	CCWLE	115	6.0	4⅞"	4⅞"	½"	5"	BL6413	4KA46
<b>3-Speed, 3 Mounting Studs</b>											
Ring	⅞	1050	CCWLE	208-230	3.2	4⅞"	4⅞"	½"	5"	B6415	4KA42
	⅞	1050	CWSE	208-230	3.4	4⅞"	4⅞"	½"	3⅞"	429	4KA48
<b>4-Speed, 3 Mounting Studs</b>											
Ring	⅞	1050	CCWLE	115	7.1	4⅞"	4⅞"	½"	2⅞"	BL6416	4KA40
	⅞	1050	CWSE	115	7.9	4⅞"	4⅞"	½"	3⅞"	559	4KA47

\* Studs located on opposite shaft end of motor. † Include BX connector.



## ECM Fan Coil Motor

- Speeds: 3
  - 42 frame (5" body dia.)
  - Enclosure: open air-over
  - Thermal protection: auto
  - Mounting: cradle base
  - Bearings: ball
  - Max. ambient temp.: 40°C
  - Duty: continuous
- For use in air conditioners, fan coil units, and blower applications. UL Recognized.



HP	Nameplate RPM	Rotation	Voltage	Full Load Amps	Shaft Dia.	Shaft Length	Length Less Shaft	Mfr. Model	Item No.
⅞	1100	CWLE	115	1.6	½"	9⅞"	3⅞"	CS89	10C902