




## PSC Direct-Drive Blower/Fan Motors

- Enclosure: open air-over
- Thermal protection: auto
- Service factor: 1.0
- 1/2" shaft dia.
- Duty: continuous

For furnace blowers and other shaft-mounted fan and blower applications.  
Motors are UL Recognized and CSA Certified.



HP	Nameplate RPM	Rotation	Voltage	Full Load Amps	Ins. Class	Mounting	Ring to Ring Center	Resilient Ring Dia.	Stud Pattern	Shaft Length	Length Less Shaft	Max. Ambient Temp.	Brand	Item No.	Capacitor Req.
<b>42Y Frame, 5" Body Dia., Sleeve Bearings</b>															
<b>1 Speed</b>															
1/8	1075	CW/CCW	115	2.7	B	Stud	4 1/16"	2 1/2"	3 1/4" x 3 1/4"	6"	4 1/16"	40°C	Century	4MA96	2MDV4
<b>3 Speed</b>															
1/10	1625	CW/CCW	115	2.1	B	Stud	4 1/16"	2 1/2"	3 1/4" x 3 1/4"	5 1/4"	5 3/8"	40°C	Century	4UY12	2MDV4
	1075	CW/CCW	115	1.6	B	Ring	4 1/16"	2 1/2"	2 5/16" x 4"	5 1/4"	5 3/8"	40°C	Century	4UY13	2MDV4
1/8	1625	CW/CCW	115	2.5	B	Stud	4 5/16"	2 1/2"	3 1/4" x 3 1/4"	6"	4 1/16"	40°C	Century	4MB16	2MDV4
	1075	CW/CCW	115	1.9	B	Ring	5 5/16"	2 1/2"	3 1/4" x 3 1/4"	5 1/4"	5 1/16"	40°C	Century	4UY18	2MDV4
1/6	1075	CW/CCW	115	3.1	B	Ring	5 5/16"	2 1/2"	2 5/16" x 4"	5 1/4"	5 1/16"	40°C	Century	4UY19	2MDV4
	1075	CW/CCW	115	3.2	B	Stud	4 9/16"	2 1/2"	3 1/8" x 3 1/8"	5"	4 1/16"	40°C	Century	4MB18	2MDV6
1/6	1075	CW/CCW	230	1.3	B	Stud	4 9/16"	2 1/2"	3 1/8" x 3 1/8"	5"	4 1/16"	40°C	Century	4MB20	2MDV6
	1075	CW/CCW	230	1.3	B	Ring	4 9/16"	2 1/2"	3 1/8" x 3 1/8"	5"	4 1/16"	40°C	Century	4KA44	2MDV6
1/6	1625	CW/CCW	115	4.0	B	Ring	5 1/16"	2 1/2"	3 1/4" x 3 1/4"	5 1/4"	6 3/8"	40°C	Century	4UY20	2MDV6
	1075	CW/CCW	115	4.7	B	Stud	4 1/16"	2 1/2"	3 1/8" x 3 1/8"	4 1/8"	5 3/8"	40°C	Century	4MB22	2MDV4
1/4	1075	CW/CCW	115	4.8	B	Ring	5 1/16"	2 1/2"	2 5/16" x 4"	5 1/4"	6 3/8"	40°C	Century	4UY21	2MDV6
	1075	CW/CCW	208-230	2.0	B	Ring	5 5/16"	2 1/2"	2 5/16" x 4"	5 1/4"	5 1/16"	40°C	Century	4UY23	2MDV4
1/4	1075	CW/CCW	230	2.0	B	Stud	4 1/16"	2 1/4"	3 1/8" x 3 1/8"	4 1/8"	5 3/8"	40°C	Century	4MB24	2MDV4
	1075	CW/CCW	115	6.3	B	Stud	4 1/16"	2 1/4"	3 1/8" x 3 1/8"	4 1/8"	5 3/8"	40°C	Century	4MB26	2MDV9
<b>48 Frame, 5 5/8" Body Dia., Ball Bearings</b>															
1/4	1075	CW/CCW	115	3.6	B	Stud	5 1/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 3/8"	40°C	Genteq	13G414	Included
	1075	CW/CCW	208-230	1.7	B	Stud	5 1/8"	2 1/2"	3 3/8" x 3 3/8"	6 1/2"	5 3/8"	40°C	Genteq	13G418	Included
1/4	1075	CW/CCW	460	1.1	B	Stud	5 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 1/16"	40°C	Genteq	13G405 *	Included
	1075	CW/CCW	115	4.7	B	Stud	5 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 1/16"	40°C	Genteq	13G415	Included
1/8	1075	CW/CCW	208-230	2.5	B	Stud	5 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 1/16"	40°C	Genteq	13G419 *	Included
	1075	CW/CCW	460	1.6	B	Stud	5 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 3/8"	40°C	Genteq	13G406 *	Included
1/2	1075	CW/CCW	115	8.6	B	Stud	6 3/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 3/8"	40°C	Genteq	13G416	Included
	1075	CW/CCW	208-230	3.8	B	Stud	6 1/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 3/8"	40°C	Genteq	13G420 *	Included
3/4	1075	CW/CCW	115	10.0	B	Stud	6 3/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 3/8"	40°C	Genteq	13G417	Included
3/4	1075	CW/CCW	277/230	0.78	B	Stud	4 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	4 1/16"	40°C	Genteq	13G399 *	Included
	1075	CW/CCW	277	1.1	B	Stud	5 1/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 3/8"	40°C	Genteq	13G401 *	Included
1/2	1075	CW/CCW	277	0.87	B	Stud	5 5/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	5 1/16"	40°C	Genteq	13G402 *	Included
	1075	CW/CCW	277	3.1	B	Stud	6 1/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 3/8"	40°C	Genteq	13G403 *	Included
3/4	1075	CW/CCW	277	3.6	B	Stud	6 3/8"	2 1/4"	3 3/8" x 3 3/8"	6 1/2"	6 1/16"	40°C	Genteq	13G404 *	Included
<b>48Y Frame, 5 5/8" Body Dia., Sleeve Bearings</b>															
<b>1 Speed</b>															
1/8	1550	CCWLE	115/208-230	2.7/1.2-1.4	B	Ring	4 1/16"	2 1/4"	—	4"	5 1/8"	40°C	Century	4UU84	Included
	1050	CCWLE	115	2.4	A	Ring	4 1/16"	2 1/2"	3 3/8" x 3 3/8"	4 1/16"	5 5/8"	40°C	Century	4UU71	Included
1/6	1550	CCWLE	115/208-230	2.8/1.4-1.4	B	Ring	4 1/16"	2 1/4"	—	4"	4 1/8"	40°C	Century	4UU66	2MDV7
	1075	CW/CCW	208-230	0.95	B	Ring	4 1/4"	2 1/4"	3 3/8" x 3 3/8"	5"	4 3/4"	60°C	Century	4HCH4	2MDV4
1/6	1050	CCWLE	115/208-230	3.3/1.5-1.7	B	Ring	4 5/16"	2 1/2"	3 3/8" x 3 3/8"	3 3/8"	5 3/8"	40°C	Century	2CDU1	2MDV4
	1550	CCWLE	115/208-230	4.9/2.5-2.5	B	Ring	5 1/16"	2 1/4"	—	4"	5 1/2"	40°C	Century	4UU68	2MDV3
1/4	1075	CCWLE	115	3.6	B	Ring	4 1/16"	2 1/4"	2 9/16" x 4 1/16"	2 1/2"	5 1/8"	40°C	Century	4UU86	Included
	1075	CW/CCW	208-230	1.5	B	Ring	4 9/16"	2 1/4"	3 3/8" x 3 3/8"	5"	5"	60°C	Century	5ELK6	2MDV4
<b>3 Speed</b>															
1/6	1075	CW/CCW	115	3.2	B	Ring	4 7/8"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	4 7/8"	50°C	Century	4MB30	2MDV6
	1075	CW/CCW	115	2.7	B	T-Flex	—	—	—	5 1/2"	4 1/4"	40°C	Century	4MB50	2MDV4
1/4	1625	CW/CCW	115	3.0	A	Stud	4 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	40°C	Century	4MA80	2MDV7
	1625	CW/CCW	208-230	1.8	A	Stud	4 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	40°C	Century	4MA82	2MDV4
1/4	1075	CW/CCW	208-230	1.6	B	T-Flex	—	—	—	6"	4 1/8"	50°C	Century	4MB52 *	2MDV4
	1625	CW/CCW	115	4.0	A	Stud	5 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	40°C	Century	4MA84	2MDV9
1/4	1625	CW/CCW	208-230	2.0	A	Stud	5 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	50°C	Century	4MA86	2MDV4
	1075	CW/CCW	115	4.2	A	Stud	5 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	50°C	Century	4MA66	2MDV6
1/8	1075	CW/CCW	208-230	2.4	B	T-Flex	—	—	—	6"	4 3/8"	50°C	Century	4MB54 *	2MDV6
	1075	CW/CCW	208-230	3.2	A	Stud	5 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	5 5/8"	50°C	Century	4MA68	2MDV4
1/8	1075	CW/CCW	115	4.9	B	Ring	5"	2 1/4"	2 9/16" x 4 1/16"	5"	5 1/2"	40°C	Century	4UU88	2MDV6
	1625	CW/CCW	115	7.6	A	Stud	5 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 1/8"	40°C	Century	4MA88	2MDV9
1/2	1625	CW/CCW	208-230	2.8	A	Stud	5 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 1/8"	40°C	Century	4MA90	2MDV6
	1075	CW/CCW	115	5.6	A	Stud	5 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 1/8"	50°C	Century	4MA70	2MDV7
1/2	1075	CW/CCW	208-230	3.3	B	T-Flex	—	—	—	6"	4 7/8"	50°C	Century	4MB56	2MDV7
	1075	CW/CCW	208-230	2.7	A	Stud	5 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 1/8"	50°C	Century	4MA72	2MDV6
1/2	1625	CW/CCW	115	8.5	A	Stud	6 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 3/8"	40°C	Century	4MA92	2MDV9
	1625	CW/CCW	208-230	4.0	A	Stud	6 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 3/8"	40°C	Century	4MA94	2MDV6
3/4	1075	CW/CCW	115	9.8	B	Stud	6 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 3/8"	50°C	Century	4MA74	2MDV9
	1075	CW/CCW	208-230	5.0	B	T-Flex	—	—	—	6"	5 3/8"	50°C	Century	4MB58	2MDV7
3/4	1075	CW/CCW	208-230	4.9	B	Stud	5 1/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 3/8"	50°C	Century	4MA76	2MDV7
<b>4 Speed</b>															
3/4	1075	CW/CCW	115	3.9	B	T-Flex	—	—	3 3/8" x 3 3/8"	5 1/2"	5 3/8"	50°C	Century	2CDT9	2MDV4
1/2	1075	CW/CCW	115	5.6	B	T-Flex	—	—	—	5 1/2"	4 1/16"	40°C	Century	2FGP7	2MDV4
1/2	1075	CW/CCW	115	8.9	B	T-Flex	—	—	3 3/8" x 3 3/8"	5 1/2"	5 1/2"	40°C	Century	2FGR1	2MDV6
3/4	1075	CW/CCW	115	10.9	A	T-Flex	—	—	—	6"	5 5/8"	50°C	Century	4MB40 *	2MDV9
<b>5 Speed</b>															
3/4	1075	CW/CCW	115	8.0	B	Stud	6 3/16"	2 1/4"	3 3/8" x 3 3/8"	5 1/16"	6 3/8"	40°C	Century	4MA78	2MDV6

\* 60/50 Hz.