MISUMIUSA.COM

Product Name	Slide Screws	Lead Screws	Ball Screws
Page	pg. XX	pg. XX	pg. XX
Usage/Picture		1	THE STATE OF THE S
Max . Available Size (Dia x Length) (mm)	12 x 550 mm	50 x 1200 mm	32 x 2000 mm
Accuracy	Medium	Medium	High
Allowable Rotational Speed	Low Speed	Medium Speed	High Speed
Max Allowable Axial Load (Ref. Only)	540 N	30,000 N	9,960 N
Efficiency	0.7	0.8	0.95
Friction	High	High	Low
Grease	Not Required	Not Required	Required
Noise Level	Low	Low/Medium	High
Cost \$	\$\$	\$	\$\$\$\$





#MTWK Lead Screw, Ends Fit Support Units



#MTWZ Lead Screws – Fixed Side Support Units



#MTUZ Lead Screws – Support Side Support Units



#MRWZRound Support Units – Fixed Side



#MRUZLead Screw Support Units – Round,
Support Side



#MTSCCompact Flanged Lead Screw Nuts



#MTS5Flanged Lead Screw Nuts with Pilot, Right-Hand Thread



#MTSJ Flanged Lead Screw Nuts – Slotted Holes, Right-Hand Thread



#MTRFFlanged Lead Screw Nuts –
Fine Pitch



#MTSEFlanged Lead Screw Nuts – with Tapped Holes, Right-Hand Thread



#MTBL Lead Screw Nuts – Anti-Backlash



#MTSM Oil-Free Lead Screw Nuts – Flanged



#MTSS Lead Screw Nuts – Straight



#MTS3Resin Lead Screw Nuts – Heavy Load



#MTSFResin Lead Screw Nuts



#MTSNBlock Style Lead Screw Nuts



#MTSH Wide Block Lead Screw Nuts



#DNBALead Screw Nut Brackets



#MTKL Spacers for Wide Block