#### CHAPTERS

#### Tables/ Breadboards

Mechanics

Optomechanic Devices

Kite

Lah Sunnlies

#### **V**SECTIONS

**Breadboards** 

#### Breadboard Supports

Breadboard Accessories

ScienceDesk

ScienceDesk

**Optical Tables** 

**Table Supports** 

Optical Table Accessories

### Rigid, Lightweight, Non-Isolating Support Frames

#### **Features**

- Accommodates Breadboards from Our PBG Series (Pages 4 - 5)
- All Steel Construction
- Casters and Leveling Feet Included
- Compatible with Metric and Imperial Breadboards
- Sorbothane Pads Provide Damping Between Table and Frame

This breadboard frame is designed for use with our PBG Series and is ideal for teaching labs or other applications that are not sensitive to external vibration. Its lightweight construction and included casters allow the user to maneuver the workstation easily to any desired location. This alternative to rigid frames can be useful in providing an extra work surface and support for breadboards at an economical price.

These frames, which are stocked for immediate shipment, are excellent for use with our UltraLight series breadboards (see pages 4 - 5). For applications with heavier load requirements, please refer to our Rigid Support Frames earlier in this section.



#### **Specifications**

- Load Capacity, Including Breadboard: 440 lbs (200 kg)
- Working Height: 29" (735 mm) Plus Height of Breadboard
- Finish: Dark Gray
- Includes Casters and Leveling Feet

- Unpackaged Weight:
  - PFM52501: 36.3 lbs (16.5 kg)
  - PFM52502: 40.7 lbs (18.5 kg)
  - PFM52503: 38.6 lbs (17.5 kg)
  - PFM52504: 43.0 lbs (19.5 kg)

#### Lightweight, Non-Isolating Support Frames, 29" (735 mm) Height

ITEM #*	\$	£	€	RMB	DESCRIPTION
PFM52501	\$ 375.00	£ 270.00	€ 326,25	¥ 2,988.75	Lightweight Frame, 3' x 2' (900 mm x 600 mm)
PFM52503	\$ 385.00	£ 277.20	€ 334,95	¥ 3,068.45	Lightweight Frame, 3' x 2.5' (900 mm x 750 mm)
PFM52502	\$ 385.00	£ 277.20	€ 334,95	¥ 3,068.45	Lightweight Frame, 4' x 2' (1200 mm x 600 mm)
PFM52504	\$ 395.00	£ 284.40	€ 343,65	¥ 3,148.15	Lightweight Frame, 4' x 2.5' (1200 mm x 750 mm)

<sup>\*</sup>Please contact your local sales office for a quotation including shipping.

## Have you seen our...



# Optical Power and Energy Meters

Choose from 5 Consoles and Over 25 Sensors to Find Your Ideal Solution

- Wavelength Ranges: 185 nm 25 μm
- ◆ Power Ranges: 100 pW 250 W

See our entire Power Meter Line on pages 1542 - 1555