

## High-Pressure Stainless Steel Threaded Pipe Fittings (Continued from previous page)

### NPT Plugs with Hex Drive

- Use with air, natural gas, oil, steam, water
- Maximum Pressure: 3,000 psi @ 72° F; 600 psi @ 220° F for steam

Plugs are hollow and made of 316 stainless steel. They meet MS-27769, SAE AS4842, and SAE AS71051.

Pipe Size	Drive Size		
1/16	5/32"	1725K11	\$2.87
1/8	3/16"	1725K12	3.60
1/4	1/4"	1725K13	4.50
3/8	5/16"	1725K14	12.27
1/2	3/8"	1725K15	23.14
3/4	9/16"	1725K16	53.00
1	5/8"	1725K17	120.00



### NPT Connectors with Intermittent Swivel—90° Elbows

- Use with air, coolant, diesel fuel, oil, water
- Maximum Pressure: See table

Fittings rotate 360° as needed to allow movement in a rigid metal piping system. They are machined 316 stainless steel. Not rated for Class.



Pipe Size	Max. psi @ 72° F		
1/4	3,000	9393K65	\$133.08
3/8	3,000	9393K61	113.58
1/2	2,500	9393K62	113.58
3/4	1,200	9393K63	187.65

### NPT Reducers

- Use with air, hydraulic fluid, natural gas, oil, steam, water
- Maximum Pressure:  
304 SS: 2,500 psi @ 72° F;  
1,900 psi @ 350° F for steam  
316 SS: 3,000 psi @ 72° F;  
2,800 psi @ 350° F for steam

Reducers meet ASTM A182.  
Straights also meet ANSI/ASME B16.11.



Pipe Size		304 Stainless Steel		316 Stainless Steel		Pipe Size		304 Stainless Steel		316 Stainless Steel	
(A)	(B)					(A)	(B)				
1/4	1/8	45525K641	\$7.13	4443K741	\$11.12	1	1/2	45525K648	\$24.55	4443K777	\$32.87
3/8	1/8	45525K642	8.87	4443K771	10.85	1	3/4	45525K649	25.18	4443K745	32.87
3/8	1/4	45525K643	9.10	4443K742	10.85	1 1/4	3/4	45525K651	46.32	4443K779	64.96
1/2	1/8	45525K115	10.29	4443K116	13.28	1 1/4	1	45525K652	47.50	4443K746	64.96
1/2	1/4	45525K644	11.77	4443K772	14.47	1 1/2	1/2	45525K117	54.58	4443K118	72.70
1/2	3/8	45525K645	12.67	4443K743	14.47	1 1/2	1	45525K653	60.84	4443K782	73.37
3/4	1/4	45525K313	16.56	4443K313	19.77	1 1/2	1 1/4	45525K654	62.40	4443K747	75.04
3/4	3/8	45525K646	17.00	4443K774	20.02	2	1 1/4	45525K655	75.47	4443K784	104.94
3/4	1/2	45525K647	17.83	4443K744	20.28	2	1 1/2	45525K656	77.14	4443K748	107.32
1	1/4	45525K116	19.50	4443K117	30.17						



Pipe Size		304 Stainless Steel		316 Stainless Steel		Pipe Size		304 Stainless Steel		316 Stainless Steel	
(A)	(B)					(A)	(B)				
1/4	1/8	4464K381	\$4.62	4443K731	\$5.03	1 1/4	1	4464K386	\$26.37	4443K736	\$34.06
3/8	1/8	4464K641	4.97	4443K751	5.51	1 1/2	1/8	4464K418	32.60	4443K442	39.47
3/8	1/4	4464K382	5.08	4443K732	5.79	1 1/2	1/4	4464K419	32.98	4443K443	37.73
1/2	1/8	4464K397	6.62	4443K411	7.43	1 1/2	3/8	4464K421	33.37	4443K421	38.62
1/2	1/4	4464K642	6.77	4443K752	7.62	1 1/2	1/2	4464K422	33.76	4443K422	39.04
1/2	3/8	4464K383	6.93	4443K733	7.81	1 1/2	3/4	4464K648	34.16	4443K423	39.04
3/4	1/8	4464K398	8.88	4443K412	9.83	1 1/2	1	4464K646	34.58	4443K762	39.47
3/4	1/4	4464K399	8.99	4443K413	9.94	1 1/2	1 1/4	4464K387	35.00	4443K737	40.37
3/4	3/8	4464K643	9.09	4443K754	10.06	2	3/8	4464K425	45.55	4443K446	53.78
3/4	1/2	4464K384	9.20	4443K734	10.17	2	1/2	4464K426	46.07	4443K424	54.38
1	1/8	4464K411	13.00	4443K414	14.24	2	3/4	4464K427	46.61	4443K425	55.00
1	1/4	4464K412	13.15	4443K415	14.47	2	1	4464K649	47.16	4443K426	55.63
1	3/8	4464K413	13.30	4443K416	14.63	2	1 1/4	4464K647	47.72	4443K764	56.28
1	1/2	4464K644	13.45	4443K757	14.96	2	1 1/2	4464K388	48.30	4443K738	56.94
1	3/4	4464K385	13.36	4443K735	15.31	2 1/2	2	4464K391	86.33	4443K427	119.82
1 1/4	1/8	4464K414	24.87	4443K441	33.31	3	1	4464K431	154.61	4443K449	213.40
1 1/4	1/4	4464K415	24.87	4443K417	32.58	3	2	4464K392	154.61	4443K739	213.40
1 1/4	3/8	4464K416	25.35	4443K418	32.94	3	2 1/2	4464K432	154.61	4443K114	213.40
1 1/4	1/2	4464K417	25.75	4443K419	33.31	4	2	4464K433	243.20	4443K115	290.80
1 1/4	3/4	4464K645	26.05	4443K759	33.31	4	3	4464K393	243.20	4443K553	290.80

### NPT Tee Outlets

- Use with air, natural gas, oil, steam, water
- Maximum Pressure:  
See table;  
600 psi @ 220° F for steam

Tee outlets allow you to create a threaded outlet anywhere along a pipe. They are also known as branch connectors and are comparable to Thredolet. To install, drill a hole in your pipe to match the fitting's pipe size and weld in place. Fittings meet ANSI/ASME B16.11 and MSS SP-97.



To Order: Please specify For Pipe Size within the range shown.

Pipe Size	For Pipe Size	Ht.	Max. psi @ 72° F	304/304L Stainless Steel	316/316L Stainless Steel
1/4	1/4 to 3/6	3/4"	3,000	4565T31	\$35.89
3/8	3/8 to 3/6	13/16"	3,000	4565T32	36.69
1/2	1/2 to 3/6	1"	3,000	4565T33	37.52
3/4	3/4 to 3/6	1 1/16"	3,000	4565T34	42.20
1	1 to 3/6	1 5/16"	3,000	4565T35	54.76
1 1/4	1 1/4 to 3/6	1 9/16"	3,000	4565T36	90.62
1 1/2	1 1/2 to 3/6	1 3/8"	2,800	4565T37	100.17
2	2 to 3/6	1 1/2"	2,500	4565T38	114.71