

Problem Scenario:

There is a parent organization called “**Acmeshell Group**”, which has two child companies named **QuickTechie** and **BlueWorld** . Both the company’s employee information is given in two separate text file as below.

Quicktechie.txt

- 1, Michael, California
- 2, Kris, London
- 3, Martin, Hong Kong
- 4, Carol, Canada
- 5, Sita, India

Blueworld.txt

- 6, John, New York
- 7, Ben, London
- 8, Carl, Tokyo
- 9, Smith, Singapore
- 10, Will, Jordon

Ques 1 : Which command will you use to check all available command line options on HDFS

ANS: `hdfs dfs`

Ques 2: Get help on individual commands.

ANS: `hdfs dfs -help <cmd>`

Ques 3: Create a new empty directory named Employee using command line on hdfs.

ANS: `hdfs dfs -mkdir Employee`

Ques 4: Create a file named quicktechie.txt with the data on local system.

ANS: `printf '1, Michael, California\n2, Kris, London\n3, Martin, Hong Kong\n4, Carol, Canada\n5, Sita, India\n' > Quicktechie.txt`

Ques 5: Create a file named Blueworld.txt with the data given on local system.

ANS: `printf '6, John, New York\n7, Ben, London\n8, Carl, Tokyo\n9, Smith, Singapore\n10, Will, Jordon\n' > Blueworld.txt`

Ques 6: Put both the files using command line in hdfs.

ANS: `hdfs dfs -put Blueworld.txt Quicktechie.txt /user/training/Employee/`

Ques 7: Merge all the files in Employee directory and name it as MergedEmployee.txt

ANS:`hdfs dfs -cat /user/training/Employee/Quicktechie.txt /user/training/Employee/Blueworld.txt | hdfs dfs -put -`

```
/user/training/Employee/MergedEmployee.  
txt
```

Ques 8: Read the content of the file.

ANS: `hdfs dfs -cat
/user/training/Employee/MergedEmployee.
txt`

Ques 9: Copy the file using command line and make a new file named Copied.txt in local.

ANS: `hdfs dfs -get
/user/training/Employee/MergedEmployee.
txt /home/Copied.txt`

Ques 10: Add content in the new file created using Hue.

Ques 11. Get the file back from HDFS to local file system.