

Problem Scenario: hi

Loudacre Inc. is a leading electronics retailer

- More than 1,000 brick and mortar stores
- Dualcore also has a thriving e-commerce Web site

Loudacre has hired you to help find value in its data

- You will process and analyse data from internal and external sources
- Identify opportunities to increase revenue
- Find new ways to reduce costs
- Help other departments achieve their goals

Ques 1: List all the databases in the RDBMS

ANS: `sqoop list-databases --connect jdbc:mysql://localhost --username training --password training`

Ques 2: Make a directory on HDFS named as /Loudacre

ANS: `hdfs dfs -mkdir Loudacre`

Ques 3: Import accounts, accountdevice, webpage into the directory /Loudacre separately

ANS:

- `sqoop import --connect jdbc:mysql://localhost/loudacre --username training --password training --table accountdevice --target-dir /user/training/Loudacre/accountdevice --m 4`
- `sqoop import --connect jdbc:mysql://localhost/loudacre --username training --password training --table accounts --target-dir /user/training/Loudacre/accounts --m 4`
- `sqoop import --connect jdbc:mysql://localhost/loudacre --username training --password training --table webpage --target-dir /user/training/Loudacre/webpage --m 4`

Ques 4: Import table accounts in /user/training changing the mappers to 10 and changing the field terminator to ':'. Also split them on the basis of state.

ANS: `sqoop import --connect jdbc:mysql://localhost/loudacre
--username training --password training --table accounts
--target-dir /user/training/accounts --m 10
--fields-terminated-by : --delete-target-dir --split-by state`

Ques 5: Import the Complete names of people having accounts in Loudacre

ex: `firstname <space> last_name` ex: Britney Spears

ANS: `sqoop import --connect jdbc:mysql://localhost/loudacre
--username training --password training --table accounts
--target-dir /user/training/accounts_names
--fields-terminated-by ' ' --delete-target-dir --columns
"first_name,last_name"`

Ques 6: Import only those records where device_id is between 10 and 50 in table accountdevice.

ANS: `sqoop import --connect jdbc:mysql://localhost/loudacre
--username training --password training --table accountdevice
--target-dir /user/training/accountdevice --where "device_id
between 10 and 50"`

Ques 7: Copy the acct no. from the table customerservicerep where customer name is Roger Miller.

ANS: `sqoop import --connect jdbc:mysql://localhost/loudacre
--username training --password training --table
customerservicerep --target-dir
/user/training/Loudacre/RogerMiller_acct --where "cs_name =
'Roger Miller'" --columns "acct_num"`