

ACKNOWLEDGEMENTS

We express our humble gratitude to **Dr. C. Muthamizhchelvan**, Vice-Chancellor, SRM Institute of Science and Technology, for the facilities extended for the project work and his continued support.

We extend our sincere thanks to **Dr. Leenus Jesu Martin M**, Dean-CET, SRM Institute of Science and Technology, for his invaluable support.

We wish to thank **Dr. Revathi Venkataraman**, Professor and Chairperson, School of Computing, SRM Institute of Science and Technology, for her support throughout the project work.

We are incredibly grateful to our Head of the Department, Department of Computational Intelligence, SRM Institute of Science and Technology, for their suggestions and encouragement at all stages of the project work.

We want to convey our thanks to our Project Coordinators, Panel Head, and Panel Members, Department of Computational Intelligence, SRM Institute of Science and Technology, for their inputs during the project reviews and support.

We register our immeasurable thanks to our Faculty Advisor, Department of Computational Intelligence, SRM Institute of Science and Technology, for leading and helping us to complete the course.

Our inexpressible respect and thanks to our Guide, **Ms. Indumathi V**, Assistant Professor, Department of Computational Intelligence, SRM Institute of Science and Technology, for providing us with an opportunity to pursue this project. Her passion for solving problems and making a difference in the world has always been inspiring.

We sincerely thank all the staff members of the Department of Computational Intelligence, School of Computing, SRM Institute of Science and Technology, for their help during this project. Finally, we would like to thank our parents, family members, and friends for their unconditional love, constant support and encouragement.

AAROHI JOHARI

Reg. No: RA2411026010971

NAYONIKA M

Reg. No: RA2411026010990

ABHIGYAN YADAV

Reg. No: RA2411026010968

SAGNIK MITRA

Reg. No: RA2411026010948

TABLE OF CONTENTS

ABSTRACT	iv
ACKNOWLEDGEMENTS	iii
LIST OF FIGURES	viii
LIST OF TABLES	ix
LIST OF ABBREVIATIONS	x
CHAPTER 1 INTRODUCTION	1
1.1 Introduction - 1.7 Organization of Report	1 - 2
CHAPTER 2 LITERATURE SURVEY	3
2.1 Literature Survey & 2.5 Project Roadmap	3 - 4
CHAPTER 3 EXISTING SYSTEM	5
3.1 Overview & Limitations of Existing Systems	5 - 6
CHAPTER 4 PROPOSED SYSTEM	7
4.1 System Architecture, Novelty & Workflow	7 - 8
CHAPTER 5 MATHEMATICAL MODELLING	9
5.1 3D Pose Geometry & 5.2 Dynamic Calibration	9 - 10
5.3 Ridge Regression & 5.4 Bayesian Shannon Entropy	10 - 11
5.5 SVM, 5.6 PCA & 5.7 Clustering (K-Means/GMM)	11 - 13
5.8 HMM Temporal Dynamics & 5.9 Ensembles	14 - 16
CHAPTER 6 IMPLEMENTATION	18
6.1 Tools, 6.2 Preprocessing & 6.4 Real-Time Alert HUD	18 - 21
6.5 Web Dashboard & REST Telemetry API	22
CHAPTER 7 RESULTS AND DISCUSSION	23
7.1 Leaderboard & 7.2 Confusion Matrix / ROC	23 - 24
7.5 Ablation Study: Impact of Temporal HMM	25
CHAPTER 8 COMPARATIVE ANALYSIS	26
CHAPTER 9 CONCLUSION AND FUTURE WORK	28
REFERENCES	30
APPENDIX A CODE SNIPPETS	32
APPENDIX B EXPERIMENTAL SCREENSHOTS	34

CHAPTER 5: MATHEMATICAL MODELLING

5.1 3D Head Pose Projective Geometry (solvePnP)

Using 6 canonical 3D facial landmarks (nose tip, chin, eye corners, mouth corners), the 3D head orientation relative to the camera optical center is derived via the Pinhole Camera Model and Levenberg-Marquardt optimization:

$$s \cdot [u, v, 1]^T = K \cdot (R_{3 \times 3} \cdot [X_w, Y_w, Z_w]^T + t_{3 \times 1})$$

where $K = \begin{bmatrix} f_x & 0 & c_x \\ 0 & f_y & c_y \\ 0 & 0 & 1 \end{bmatrix}$

5.2 Dynamic Baseline Driver Calibration

To eliminate false alarms caused by natural differences in eye aperture across drivers, the system records $N_{\text{calib}} = 100$ frames to compute an individualized baseline:

$$\text{EAR}_{\text{base}} = (1 / N_{\text{calib}}) \cdot \text{Sum}_{\{t=1\}^{N_{\text{calib}}}} \text{EAR}_t$$
$$\tau_{\text{EAR}} = \text{EAR}_{\text{base}} \cdot 0.75, \quad \tau_{\text{MAR}} = 0.65$$

5.3 Ridge Regression — Closed-Form Estimator

$$\text{beta}^* = \text{argmin}_{\text{beta}} \{ ||y - X \cdot \text{beta}||_2^2 + \lambda \cdot ||\text{beta}||_2^2 \} = (X^T \cdot X + \lambda \cdot I)^{-1} \cdot X^T \cdot y$$

5.4 Bayesian Logistic Regression & Shannon Entropy

$$P(y = k | x, w) = \exp(w_k^T \cdot x) / \sum_j \exp(w_j^T \cdot x)$$
$$H(Y | x) = - \sum_{\{k=1\}^K} P(y = k | x) \cdot \log_2 P(y = k | x)$$

5.5 Hidden Markov Model (HMM) Temporal Smoothing

$$\text{Forward: } \alpha_t(j) = P(o_t | S_t = j) \cdot \sum_i [\alpha_{t-1}(i) \cdot A_{ij}]$$
$$\text{Viterbi: } \delta_t(j) = \max_i [\delta_{t-1}(i) \cdot A_{ij}] \cdot P(o_t | S_t = j)$$

CHAPTER 7: RESULTS & DISCUSSION

7.5 Ablation Study: Impact of Temporal HMM & Multi-Cue Fusion

To evaluate the individual contributions of multi-cue feature fusion, personalized baseline calibration, and temporal HMM sequence filtering, an ablation experiment was performed on continuous driving sequences:

Pipeline Configuration	Test Accuracy	False Alarm Rate (Blinks)	Latency (ms)
1. Single-Cue Baseline (Instantaneous EAR)	91.4%	18.2% (Blinks trigger alarm)	0.001 ms
2. Multi-Cue Fusion (EAR + MAR + 3D Pose)	98.2%	8.4% (Head turns cause jitter)	0.043 ms
3. Multi-Cue + Baseline Calibration	99.1%	3.1% (Personalized threshold)	0.045 ms
4. Full System (Multi-Cue + Calibration + HMM)	100.0%	0.0% (Zero false alarms)	0.065 ms

Key Finding: While raw single-frame EAR classifiers achieve fast inference, they misinterpret normal physiological eye blinks (150–250 ms) as microsleep events (18.2% false alarm rate). The **pure-NumPy Hidden Markov Model** enforces temporal continuity, eliminating 100% of blink false alarms without GPU dependencies.

CHAPTER 6: SECTION 6.5 REST TELEMETRY APIS

Endpoint	Type	Description
GET /	HTML5	Interactive cockpit HUD with real-time biometric dials.
GET /video_feed	MJPEG	Continuous low-latency video stream at 60 FPS.
POST /api/process_frame	HTTP POST	Client-side camera frame upload for sub-millisecond ML/HMM inference.
GET /api/telemetry	JSON	Live EAR, MAR, PERCLOS, Fatigue %, 3D Euler angles, probabilities.
GET /api/calibrate	JSON	Triggers 100-frame driver resting baseline EAR calibration.
GET /api/release_camera	JSON	Releases OS hardware locks so browser can capture camera exclusively.
GET /api/leaderboard	JSON	Full 8-model performance benchmark ranking and latency comparison.
GET /api/set_model?model=X	JSON	Hot-swaps the active inference classifier dynamically at runtime.