Code updating history of Jump Code Experiment

Dawei Lu

Notes about the Matlab code used in the Jump Code Experiments.

DEC 15, 2014

All the codes are available in SVN 'https:\\dawei-qip-matlab.googlecode.com\svn\trunk\Jump Code' First consider the classical case. Without correction, one needs one bit with the two states $|+\rangle$ and $|-\rangle$.

```
% Number of timesteps
1
   params.plength = 400;
 3
4
   % Length of each time step
5
   params.timestep = 10e-6;
6
7
   params.subsystem{1} = [1 2 3 9 10 11];
8
   params.subsystem\{2\} = [4 5 6 7 8 12];
9
   params.subsys_weight = [6 6];
10
11
   % Input and goal states for state to state
12
   params.rhoin = mkstate('+1ZZZZZZZIIIII',1);
13
   params.rhogoal = mkstate('+1ZZZZZZZZZZZZ',1);
14
15
   % Allow Zfreedom or not
```

The fidelity keeps 0 all the time. Guess the reason is 'Zfreedom'. Set 'params.Zfreedomflag = 0;'. However, still 0.

Annie said maybe due to the length. Her SWAP gate requires 8ms, so I changed 'params.plength = 800;'. But for with or without Zfreedom, fidelity is still 0.

Check if some of my GRAPE settings are wrong, try to repeat Annie's SWAP gate calculation.

16

params.Zfreedomflag = 1;

```
% Number of timesteps
2
  params.plength = 800;
3
4
  % Length of each time step
5
  params.timestep = 10e-6;
6
7
  params.subsystem{1} = [1 2 3 9 10 11];
8
  params.subsystem\{2\} = [4 5 6 7 8 12];
9
  params.subsys_weight = [6 6];
10
11
  % Input and goal states for state to state
12
  +1IIIIIIIIII;
  13
    14
15
  % Allow Zfreedom or not
16
  params.Zfreedomflag = 0;
```

The outputfile is 'twqubit_SWAPC7H5'. And the fidelity is already over 98%. Then I changed 'params.Zfreedomflag = 1;', and the fidelity is over 95% after 30 iterations. Much slower than the no Zfreedom case. Maybe due to different initial guesses.
