

December 13, 2014

Notes on the 12 qubit PPS

Dawei Lu

Notes about the problems in the 12 qubit PPS preparation, including Matlab codes and Experiments.

DEC 12, 2014

Calculating the state to state GRAPE on Ordi2. In pulsefinder folder. paramsfile is 'twqubit_subS2S.m', and the output file is 'twqubit_7zto12z'.

The GRAPE is to evolve ZZZZZZIIIII to ZZZZZZZZZZZZ. As the couplings between nearest-neighbored C and H are about 150Hz. I set the GRAPE

```

1 % Number of timesteps
2 params.plength = 400;
3
4 % Length of each time step
5 params.timestep = 10e-6;
6
7 params.subsystem{1} = [1 2 3 9 10 11];
8 params.subsystem{2} = [4 5 6 7 8 12];
9 params.subsys_weight = [6 6];
10
11 % Input and goal states for state to state
12 params.rhoin = mkstate('+1ZZZZZZIIIII',1);
13 params.rhogoal = mkstate('+1ZZZZZZZZZZZ',1);
14
15 % Allow Zfreedom or not
16 params.Zfreedomflag = 1;

```

The fidelity keeps 0 all the time. Guess the reason is 'Zfreedom'. Set 'params.Zfreedomflag = 0;'. However, still 0.

Annie said maybe due to the length. Her SWAP gate requires 8ms, so I changed 'params.plength = 800;'. But for with or without Zfreedom, fidelity is still 0.

Check if some of my GRAPE settings are wrong. try to repeat Annie's SWAP gate calculation.

```

1 % Number of timesteps
2 params.plength = 800;
3
4 % Length of each time step
5 params.timestep = 10e-6;
6
7 params.subsystem{1} = [1 2 3 9 10 11];
8 params.subsystem{2} = [4 5 6 7 8 12];
9 params.subsys_weight = [6 6];
10
11 % Input and goal states for state to state
12 params.rhoin = mkstate('+1IIIIIIIZIIII+1IIIIIIIZIII+1IIIIIIIZII+1IIIIIIIZI
    +1IIIIIIIZ',1);
13 params.rhogoal = mkstate('+1IIIIIIIZIIII+1IIIIIIIZIII+1IIIIIIIZII+1
    IIIIIIIIZI+1IIIIIIIZIIIZ',1);
14
15 % Allow Zfreedom or not
16 params.Zfreedomflag = 0;

```

The outputfile is 'twqubit_SWAPC7H5'. And the fidelity is already over 98%.