



# PCB MANUFACTURING SPECIFICATIONS

## "=ProjectTitle"

### SPECIFICATIONS

NOTE #	NOTE
1	ALL SPECIFICATIONS REFERENCED ARE OF THE REVISION SPECIFIED IN THE TITLE BLOCK
2	SUPPLIER SHALL NOT MODIFY THE DESIGN OR APPROVED STACK-UP WITHOUT WRITTEN PERMISSION
3	ALL MATERIALS SHALL BE RoHS COMPLIANT AND FINAL PRODUCT SHALL BE ACCEPTABLE TO USE IN RoHS ASSEMBLY. RoHS LOGO SHALL BE MARKED IN SILKSCREEN INK BY THE SUPPLIER WHERE INDICATED BY THE TEXT "PLACE MARKINGS HERE"
4	COPPER FOIL: REFER TO LAYER STACK LEGEND FOR Cu THICKNESS DETAILS. ALL Cu THICKNESSES ARE FINISHED AND INCLUDE BASE FOIL PLUS Cu PLATING ON PLATED LAYERS
5	ELECTRICAL TEST: ALL PRINTED CIRCUITS SHALL BE 100% ELECTRICALLY TESTED FOR OPENS/SHORTS USING PROVIDED NETLIST. REJECTED PRINTED BOARDS MUST BE CLEARLY MARKED WITH NON-CONDUCTIVE, PERMANENT INK.
6	MARKINGS: VENDOR MARKING AND DATE/LOT CODES SHALL BE LOCATED ON THE BOARD IN THE RESERVED AREA AS SPECIFIED IN THE GERBER LAYER "PCBM_NOTES" BY THE TEXT "PLACE MARKINGS HERE".
7	MARKINGS: THE SIDE ONTO WHICH PLACE THE MARKINGS IS AT THE SUPPLIER DISCRESSION UNLESS OTHERWISE NOTED ONTO THE LAYER "PCBM_NOTES"
8	SUPPLIER SHALL CHECK PCBM_NOTES LAYER BEFORE ASKING FOR CLARIFICATIONS
9	MANUFACTURE TENTED/PLUGGED VIAS AS SPECIFIED IN THE GERBER FILES

### SPECIFICATIONS

LENGHT	20.00mm
WIDTH	48.00mm
LAYERS	2
MATERIAL	FR-4
MATERIAL MIN TG	130-140
TRACK WIDTH/CLEARANCE	10 mils / 10 mils
THICKNESS	0.6mm
COPPER THICKNESS	35um (1oz)
SOLDERMASK	YES, TOP AND BOTTOM
SOLDERMASK COLOR	GREEN
SILKSCREEN	YES, TOP AND BOTTOM
SILKSCREEN COLOR	WHITE
SURFACE FINISH	HASL LEAD FREE
GOLD FINGERS	NO
CHAMFERING	YES
IMPEDANCE CONTROL	YES
HALF-CUT/CASTELLATED HOLES	NO
BURIED/BLIND VIAS	NO
VIAS FILLED WITH RESIN	NO
CARBON MASK	NO
COUNTERSINKS/COUNTERBORES	NO
Z-AXIS MILLING	NO
PEELABLE SOLDERMASK	NO

### Layer Stack Legend

Material	Layer	Thickness	Dielectric Material	Type	Gerber
	Top Overlay			Legend	GTO
Surface Material	Top Solder	0.02mm	Solder Resist	Solder Mask	GTS
Copper	Top Layer	0.04mm		Signal	GTL
Core		0.50mm	FR-4	Dielectric	
Copper	Bottom Layer	0.04mm		Signal	GBL
Surface Material	Bottom Solder	0.02mm	Solder Resist	Solder Mask	GBS
	Bottom Overlay			Legend	GBO


Total thickness: 0.60mm

NON-COPPER LAYER THICKNESS FOR REFERENCE ONLY  
LAYERS OF TYPE "INTERNAL PLANE" ARE NEGATIVE


Title: =ProjectTitle			Author:	<b>CONFIDENTIAL</b>  My Company Address Line 1 Address Line 2 Address Line 3 Address Line 4	[YOUR LOGO HERE]	6
			Approved:			
Size: A3	Prj: =ProjectTitle		Edited: 22-11-2024			
Unit: mm			Variant: [No Variations]			
Date: 23-11-2024 03:06 AM			SW version: 24.10.1.45			
Sheet 1 of 3						
Git Hash: 431 [No modification]						
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB MANUFACTURING U						

[YOUR LOGO HERE]

Mechanical 1 (Scale 5:2)




Drill Drawing View (Scale 5:2)



Drill Table

Symbol	Count	Hole Size	Plated	Hole Tolerance
x	105	0.30mm	Есть	
o	4	0.50mm	Есть	
+	4	0.60mm	Есть	
x	2	0.65mm	Нет	
v	30	1.00mm	Есть	
d	2	2.20mm	Есть	
	147 Total			

Dimensions (Scale 5:2)




ALWAYS CAREFULLY READ  
THE NOTES ON THIS LAYER!


Title: =ProjectTitle			Author:	<b>CONFIDENTIAL</b>  My Company Address Line 1 Address Line 2 Address Line 3 Address Line 4	[YOUR LOGO HERE]	6
Size: A3			Approved:			
Unit: mm	Prj: =ProjectTitle		Edited: 22-11-2024			
Date: 23-11-2024 03:06 AM Sheet 2 of 3			Variant: [No Variations]			
Git Hash: 431 [No modification]			SW version: 24.10.1.45			
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB MANUFACTURING US						

[YOUR LOGO  
HERE]


Top Layer (Scale 5:2)




Top Paste (Scale 5:2)




Top Solder (Scale 5:2)




Top Overlay (Scale 5:2)




Bottom Layer (Scale 5:2)




Bottom Paste (Scale 5:2)



Top Paste (Scale 5:2)



Bottom Overlay (Scale 5:2)



Title: =ProjectTitle		Author:	CONFIDENTIAL
Size: A3	Prj: =ProjectTitle	Approved:	My Company
Unit: mm		Edited: 22-11-2024	
Date: 23-11-2024 03:06	AMSheet 3 of 3	Variant: [No Variations]	Address Line 1
Git Hash: 431 [No modification]		SW version: 24.10.1.45	Address Line 2
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB MANUFACTURING_US			Address Line 3
			Address Line 4

YOUR LOGO  
HERE

# PCB ASSEMBLY SPECIFICATIONS


## "=ProjectTitle"

### Variant: "[No Variations]"


#### SPECIFICATIONS

NOTE #	NOTE
1	ALL SPECIFICATIONS REFERENCED SHALL BE OF THE LATEST REVISION UNLESS OTHERWISE NOTED
2	SUPPLIER SHALL NOT MODIFY THE DESIGN WITHOUT WRITTEN PERMISSION
3	REFER TO EXCEL BOM FOR UP-TO-DATE INFORMATION
4	THE BOM IN THIS DOCUMENT IS PURELY AN AID TO ASSEMBLY OPERATIONS AND MAY NOT HAVE THE MOST UP-TO-DATE DATA OR ALL APPROVED COMPONENT ALTERNATIVE.


View from Front side (Scale 2:1)




View from Back side (Scale 2:1)



View from Top side (Scale 2:1)




View from Bottom side (Scale 2:1)



Title: =ProjectTitle			Author:	<b>CONFIDENTIAL</b>  My Company Address Line 1 Address Line 2 Address Line 3 Address Line 4 <div>[YOUR LOGO HERE]</div>	6
			Approved:		
Size: A3	Prj: =ProjectTitle		Edited: 22-11-2024		
Unit: mm			Variant: [No Variations]		
Date: 23-11-2024 03:06			SW version: 24.10.1.45		
AMSHEET 1 of 9					
Git Hash: 431 [No modification]					
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR					

Realistic View TOP



Title: =ProjectTitle			Author:		CONFIDENTIAL		[YOUR LOGO HERE]	6
Size: A3			Approved:		My Company			
Unit: mm			Prj: =ProjectTitle		Edited: 22-11-2024			
Date: 23-11-2024 03:06 AM			Sheet 2 of 9		Variant: [No Variations]			
Git Hash: 431 [No modification]			SW version: 24.10.1.45		Address Line 1			
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR					Address Line 2			
					Address Line 3			
					Address Line 4			

[YOUR LOGO HERE]

A

B

C

D

E

F

G

H

1

2


3

4

5


6

View from Top side (Scale 4:1)



DIODE ORIENTATION

Name	ANODE
Short name	A
Pin number	2
Silkscreen	thin line
assembly view	no dot ( )




Name	CATHODE
Short name	K
Pin number	1
Silkscreen	thick line / dot
assembly view	dot (•)

Title: =ProjectTitle			Author:	<b>CONFIDENTIAL</b>  My Company Address Line 1 Address Line 2 Address Line 3 Address Line 4	[YOUR LOGO HERE]	6		
			Approved:					
Size: A3	Prj: =ProjectTitle		Edited: 22-11-2024					
Unit: mm			Variant: [No Variations]					
Date: 23-11-2024 03:06 AMSheet 3 of 9			SW version: 24.10.1.45					
Git Hash: 431 [No modification]								
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR								

[YOUR LOGO HERE]




View from Top side (Scale 5:1)



DIODE ORIENTATION

Name	ANODE
Short name	A
Pin number	2
Silkscreen	thin line
assembly view	no dot ( )




Name	CATHODE
Short name	K
Pin number	1
Silkscreen	thick line / dot
assembly view	dot (•)

Title: =ProjectTitle		Author:	<div>CONFIDENTIAL</div> <div>My Company</div> <div>Address Line 1</div> <div>Address Line 2</div> <div>Address Line 3</div> <div>Address Line 4</div> <div>[YOUR LOGO HERE]</div>	6
		Approved:		
Size: A3	Prj: =ProjectTitle	Edited: 22-11-2024		
Unit: mm		Variant: [No Variations]		
Date: 23-11-2024 03:06 AMSheet 4 of 9		SW version: 24.10.1.45		
Git Hash: 431 [No modification]				
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UART				



Realistic View BOTTOM



Title: =ProjectTitle			Author:	<b>CONFIDENTIAL</b>  My Company Address Line 1 Address Line 2 Address Line 3 Address Line 4	[YOUR LOGO HERE]	6
Size: A3			Approved:			
Unit: mm	Prj: =ProjectTitle		Edited: 22-11-2024			
Date: 23-11-2024 03:06 AM Sheet 5 of 9			Variant: [No Variations]			
Git Hash: 431 [No modification]			SW version: 24.10.1.45			
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR						


[YOUR LOGO HERE]

View from Bottom side (Scale 4:1)



DIODE ORIENTATION

Name	ANODE
Short name	A
Pin number	2
Silkscreen	thin line
assembly view	no dot ( )



Name	CATHODE
Short name	K
Pin number	1
Silkscreen	thick line / dot
assembly view	dot (•)

Title: =ProjectTitle			Author:	CONFIDENTIAL	[YOUR LOGO HERE]	6	
Size: A3			Approved:				My Company
Unit: mm	Prj: =ProjectTitle		Edited: 22-11-2024				
Date: 23-11-2024 03:06 AM			Variant: [No Variations]				Address Line 1
Sheet 6 of 9			SW version: 24.10.1.45	Address Line 2			
Git Hash: 431 [No modification]				Address Line 3			
				Address Line 4			
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR							

A

B

C

D

E

F

G

H

1

2


3

4

5


6

View from Bottom side (Scale 4:1)



DIODE ORIENTATION

Name	ANODE
Short name	A
Pin number	2
Silkscreen	thin line
assembly view	no dot ( )



Name	CATHODE
Short name	K
Pin number	1
Silkscreen	thick line / dot
assembly view	dot (•)

Title: =ProjectTitle		Author:	CONFIDENTIAL	[YOUR LOGO HERE]
Size: A3		Approved:		
Unit: mm	Prj: =ProjectTitle	Edited: 22-11-2024		
Date: 23-11-2024 03:06 AM Sheet 7 of 9		Variant: [No Variations]		
Git Hash: 431 [No modification]		SW version: 24.10.1.45	My Company	Address Line 1
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR				
			Address Line 2	
			Address Line 3	
			Address Line 4	

A

B

C

D

E

F

G

H

1

2


3

4


5

6

View from Front side (Scale 4:1)



View from Back side (Scale 4:1)



Title: =ProjectTitle			Author:	<div>CONFIDENTIAL</div> <div>My Company</div> <div>Address Line 1</div> <div>Address Line 2</div> <div>Address Line 3</div> <div>Address Line 4</div> <div>[YOUR LOGO HERE]</div>	6
Size: A3			Approved:		
Unit: mm	Prj: =ProjectTitle		Edited: 22-11-2024		
Date: 23-11-2024 03:06		Variant: [No Variations]	Address Line 3		
AMSheet 8 of 9		SW version: 24.10.1.45	Address Line 4		
Git Hash: 431 [No modification]					
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR					

	A	B	C	D	E	F	G	H	
1									1
2									2
3									3
4									4
5									5
6									6

Bill Of Materials

Line #	Description	Designator	Quantity	Manufacturer Part Number 1	Part Number	Layer
	Cap Cer 0.1UF 6.3V X7R 0603	C1I, C1R, C3U	3	KGM15AR70J104KM		
	Multilayer Ceramic Capacitor, 10 uF, 10 V, ± 10%, X5R, 0603 [1608 Metric]	C1L	1			
	Multilayer Ceramic Capacitor, 0.1 uF, 10 V, ± 10%, X7R, 0603 [1608 Metric]	C1P, C1U, C2L, C2U, C4I	5	C0603C104K8RAC7867		
	Cap Ceramic 0.001uF 6.3V C0G 10% SMD 0603 125°C Paper T/R	C2I	1			
	Ceramic Capacitor, Multilayer, Ceramic, 10V, 10% +Tol, 10% -Tol, X5R, 15% TC, 1uF, 0603	C2R, C5I	2			
	Cap Ceramic 0.001uF 10V X7R 10% SMD 0603 125°C Paper T/R	C3I	1			
	Multilayer Ceramic Capacitor, 10 uF, 6.3 V, ± 10%, X5R, 0603 [1608 Metric]	C3L	1	CL10A106KQ8NNNC		
	Multilayer Ceramic Capacitor, 4.7 uF, 10 V, ± 10%, X5R, 0603 [1608 Metric]	C4U	1	CL10A475KP8NNNC		
	LED 0603 YELLOW SMD	D1L	1			
	TVS DIODE 5V 15V SOT23-6	D1U	1			
	Fuse PPTC SMD 0603	F1P	1			
	USB Connector Type C SMT 16 Pin (Power pins joints = 12 pins)	J1C	1			
		J2C	1			
		J3C	1			
	PMPB14XPZ	Q1P	1	PMPB14XPZ		
	Trans Gp Bjt NPN 25V 1.5A 300MW 3-PIN SOT-23 T/r	Q1R, Q2R	2	SS8050-G		
	Surface Mount Thick Film Chip Resistor 0603 Case 1.69K Ohms 1% Tolerance 100 PPM	R0L	1	MCR03EZPFX1691		
	SMD Chip Resistor, 5.1 kOhm, ± 1%, 100 mW, 0603 [1608 Metric], Thick Film, General Purpose	R1C, R2C	2	CRCW06035K10FKEA		
	Res Thick Film 0603 33K Ohm 1% 0.1W(1/10W) ±100ppm/C Pad SMD Automotive T/R	R1L	1	ERJ-3EKF3302V		
	SMD Chip Resistor, 100 kOhm, ± 1%, 100 mW, 0603 [1608 Metric], Thick Film, General Purpose	R1P	1	AC0603FR-07100KL		
	SMD Chip Resistor, 10 kOhm, ± 1%, 100 mW, 0603 [1608 Metric], Thick Film, General Purpose	R1R, R1U, R2R, R2U, R3L, R3R, R4R	7	RC0603FR-0710KL		
	SMD Chip Resistor, 20 kOhm, ± 1%, 100 mW, 0603 [1608 Metric], Thick Film, General Purpose	R2L	1	CR0603-FX-2002ELF		
	Res Thick Film 0603 2.49K Ohm 1% 1/10W ±100ppm/°C Molded SMD SMD Paper T/R	R4L	1			
	DGTL ISO 3750VRMS 4CH GP 16SOIC	U1I	1			
	LDO U-Reg Adj 0, 3A SOT23-5	U1L	1			
	Single-Chip USB to UART Bridge, 1024 Bytes EEPROM, -40 to 85 degC, 28-pin QFN, Tube	U1U	1			
	MM3Z12VST1G Zener Diode, 12V 2% 200 mW SMT 2-Pin SOD-323   ON Semiconductor MM3Z12VST1G	ZD1P	1			

Please consider LCSC (立创商城) as our first supplier

BOM FOR REFERENCE ONLY

ALWAYS REFER TO THE LATEST EXCEL BOM PROVIDED

Title: =ProjectTitle		Author:		CONFIDENTIAL	
Size: A3	Prj: =ProjectTitle	Approved:		My Company	
Unit: mm		Edited: 22-11-2024		Address Line 1	
Date: 23-11-2024 03:06 AM	Sheet 9 of 9	Variant: [No Variations]		Address Line 2	
Git Hash: 431 [No modification]		SW version: 24.10.1.45		Address Line 3	
File: C:\Users\desktop\Documents\Project Files\Altium\Projects\Project - Development\USB-UART-ISO-CP2102\PCB ASSEMBLY USB-UAR					

YOUR LOGO

HERE