



SPECIFICATION	
VALVE OPENING INTERVAL	- 0.5-35min(adjustable)
VALE DISCHARGE	- 0.5-20sec(adjustable)
POWER CONSUMPTION	- 10W
MAX.OPERATING TEMPERATURE	- 90° C
MAX.OPERATING PRESSURE	- 16 bar(g)
ORIFICE	- 3mm
INLET / OUTLET	- 1/2" BSP(F)
TYPE	- DIRECT OPERATED
MAX.DISCHARGE	●7bor - 60 Lt/hr
WEIGHT	- 0.5 Kg
ELECTRICAL/POWER SUPPLY	-220V±10%,50Hz,1Ph
QUALITY OF PILOT AIR	-DRY AIR

ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED					
TOLERANCES UNLESS OTHERWISE NOTED					
MACHINED SURFACES AS PER IS : 2102(mm)					
DIMS.	0.5/6	6/30	30/120	120/315	315/1000
TOL.	±0.1	±0.2	±0.3	±0.5	±0.8
UNMACHINED SURFACE ±0.5					
ANGULAR ±1° SURFACE FINISH					
BREAK ALL EDGES 0.1 - 0.25 R					

	THIRD ANGLE PROJ.
DRAWN	DATE
CHECKED	DATE
APPROVED	DATE

GEM EQUIPMENTS LTD	
COIMBATORE-641 407	
TITLE	
GA GRATING FOR	
AUTO DRAIN VALVE (GZ-LD)	
SIZE	REV
DWG. NO.	0
4396 26	
SCALE : NTS	
SHEET 1 OF 1	

REG.NO.	NO.	REVISION	NAME	DATE