

Table of Content

PAGE	COMPONENT/ FUNCTION
001	INDEX
002	BLOCK_DIAGRAM
003	EFUSE_AND_REGULATOR
004	COMMUNICATION
005	CURRENT_SOURCE
006	SWITCHING

NANORACK LASER

Schematic V1.0.0


Project: **NANORACK_LASER.PrjPcb**

Page Contents: **INDEX.SchDoc**

Revision: **1.0.0** Design: **Hung Nguyen Duy** Date: **9/4/2024**

Size: **A3** Document Number: Sheet: **1** of **6**






Project: **NANORACK_LASER.PrjPcb**

Page Contents: **BLOCK_DIAGRAM.SchDoc**


Revision: **1.0.0** Design: **Hung Nguyen Duy** Date: **9/4/2024**

Size: **A3** Document Number: Sheet: **2** of **6**





EFUSE



REGULATOR

$$SR\left(\frac{V}{ms}\right) = \frac{V_{IN}(V)}{t_R(ms)}$$

$$C_{avdt}(pF) = \frac{2000}{SR\left(\frac{V}{ms}\right)}$$

$$I_{INRUSH}(mA) = SR(V/ms) \times C_{OUT}(uF)$$

$$R_{LIM}(\Omega) = \frac{3334}{I_{LIM}(A)}$$

$$R_2 = \frac{R_1 \times 1,221}{V_{OUT} - 1,221}$$


Project: **NANORACK_LASER.PrjPcb**

Page Contents: **EFUSE_AND_REGULATOR.SchDoc**

Revision: **1.0.0** Design: **Hung Nguyen Duy** Date: **9/4/2024**

Size: **A3** Document Number: Sheet: **3** of **6**






Project: **NANORACK_LASER.PrjPcb**

Page Contents: **COMMUNICATION.SchDoc**

Revision: **1.0.0** Design: **Hung Nguyen Duy** Date: **9/26/2024**

Size: **A3** Document Number: Sheet: **4** of **6**





Project: **NANORACK_LASER.PrjPcb**

Page Contents: **CURRENT_SOURCE.SchDoc**

Revision: **1.0.0** Design: **Hung Nguyen Duy** Date: **9/4/2024**

Size: **A3** Document Number: Sheet: **5** of **6**



