PRN232 FINAL ASSIGNMENT

System Architecture & Database Design

EXE Group Management System

Table 1. Project information

Item	Details
Course	PRN232 – Building Cross-Platform Back-End Application with .NET
Project	EXE Group Management System
Class / group	SE18xx – Group N
Semester	Fall 2026 (FA26)
Architectural style	Microservices architecture, documented with the C4 model (Level 1 & Level 2)
Team	See Team Members & Responsibilities below
Instructor	PhuongLHK
Document version	2.0 – November 1, 2026

Team Members & Responsibilities

Table 2. Team members and responsibilities

No.	Full name	Student ID	Main responsibilities
1	Member 1	SExxxxxx	Platform and API Gateway: solution skeleton, shared building blocks, Docker Compose, CI, YARP gateway (JWT, Swagger UI), README and demo script
2	Member 2	SExxxxxx	Identity Service (sign-in, JWT, users, roles) and Join Request Service REST API
3	Member 3	SExxxxxx	Group Service REST API: semesters, courses, classes, rosters, groups, lecturer dashboard
4	Member 4	SExxxxxx	gRPC GroupMembership server and client, Transactional Outbox, Redis Streams consumer, background jobs
5	Member 5	SExxxxxx	React Single-Page App for all roles, nginx

Highlighted cells are placeholders – replace them with the real class, names and student IDs before submission, then delete this note.

Revision History

Table 3. Revision history

Version	Date	Changes
1.0	October 14, 2026	Initial architecture and database design.
2.0	November 1, 2026	Container diagram redrawn left to right with fewer words (lecturer feedback) and context diagram aligned; all diagrams redrawn for portrait pages with straight, orthogonal connectors; class rosters added; Redis Streams chosen as message broker; gRPC and event contracts, join-request state machine with idempotent processing, complete REST API, background jobs and deployment defined; conceptual ERD reworked; physical design split per database with a reference DDL tested on SQL Server.

Table of Contents

1. Context 3
2. Problems 3
3. Solutions 3
3.1. Proposed Solution 3
3.2. Design Rationale – Why Both gRPC and Events 4
3.3. Scope Definition 4
4. Main Actors 5
4.1. Actor Descriptions 5
4.2. Permission Matrix 5
5. Main Features & Business Rules 6
5.1. Functional Requirements 6
5.2. Business Rules 6
5.3. Join Request Lifecycle 7
5.4. RESTful API Endpoints 8
5.4.1. Conventions 8
5.4.2. Identity Service 9
5.4.3. Group Service 9
5.4.4. Join Request Service 10
6. System Architecture – C4 Model (Level 1 & Level 2) 11
6.1. Level 1: System Context Diagram 11
6.2. Level 2: Container Diagram 12
6.3. Container Responsibilities 12
6.4. Inter-Service Workflow – Approving a Join Request 13
6.5. Inter-Service Contracts 14
6.5.1. gRPC – GroupMembership Service (Group Service) 14
6.5.2. Events – Redis Streams 15
6.6. Background Jobs 16
7. Technology 16
7.1. Technology Stack 16
7.2. Cross-Cutting Concerns 17
7.3. Deployment – Docker Compose 17
7.4. Requirement Traceability & Bonus Features 18
8. Conceptual ERD 19
9. Physical Database Design 20
9.1. Physical Database Diagrams 20
9.2. Data Dictionary 22
9.2.1. IdentityDb (owned by Identity Service) 22
9.2.2. GroupDb (owned by Group Service) 23
9.2.3. RequestDb (owned by Join Request Service) 26
9.3. Indexes, Constraints & Business-Rule Matrix 27
9.4. Cross-Service Logical References 28
9.5. Migrations & Reference DDL 28
Appendix A. gRPC Contract – group_membership.proto 29
Appendix B. Glossary 30

1. Context

In the EXE (Experiential Entrepreneurship) courses, students must form project groups to develop a startup idea within the rules of their class and semester. Today, teammates are found through fragmented channels – chat groups, spreadsheets and face-to-face talks. With no single source of truth, the head-count of each group, the groups that still have open slots, the pending join requests and the students who still have no group are scattered and hard to track for students, lecturers and administrators alike.

The **EXE Group Management System** replaces these channels with one platform that applies the class rules automatically. It is designed as a distributed .NET system that also demonstrates every PRN232 requirement: RESTful APIs with JWT, a gRPC service, a message broker, background jobs and container-based deployment.

2. Problems

- **P1 – Eligible groups are hard to find.** Students cannot easily see which groups of their class match their interests and still have free slots.
- **P2 – Manual request handling and over-capacity.** Team Leaders collect join requests by hand, so requests get lost, and two approvals at the same moment can push a group above the class's maximum size.
- **P3 – Duplicate or invalid memberships.** Without backend validation a student can end up in more than one group of the same EXE class, or in a group of a class they are not enrolled in.
- **P4 – No visibility for lecturers and administrators.** Lecturers cannot monitor grouping progress, under-filled groups or the students of their classes who still have no group.

3. Solutions

3.1. Proposed Solution

The team builds the EXE Group Management System, a distributed web application that centralizes group formation, join requests and class monitoring:

- **S1 – One workflow for forming groups (P1, P2).** The Single-Page App lets students create groups, search, filter, sort and page through open groups, and submit or cancel join requests; Team Leaders review all requests of their group in one place.
- **S2 – Rules enforced in the backend (P2, P3).** Enrollment and one group per student per class are guaranteed by database constraints (composite foreign keys and unique indexes). The class's MaxMembers and Deadline are checked in the same transaction as every membership change, protected by optimistic concurrency, and a background job locks the groups when the deadline passes.
- **S3 – Class rosters and a monitoring dashboard (P4).** Administrators import the roster of every EXE class; lecturers see grouped and ungrouped students, groups by status and under-filled groups (below MinMembers).
- **S4 – Role- and resource-based access control.** Global roles (Student, Lecturer, Administrator) come from the JWT; the Team Leader permission is checked per group against `Groups.LeaderId` – directly in Group Service and through gRPC from Join Request Service.

- **S5 – Microservices with synchronous and asynchronous communication.** Identity, Group and Join Request services behind a YARP API Gateway, each owning its database; gRPC for immediate checks and the atomic “add member” operation; Redis Streams with a Transactional Outbox and background jobs for reliable events.

3.2. Design Rationale – Why Both gRPC and Events

Approving a join request needs an immediate and authoritative answer: is the group still open, is the approver its leader, is there a free slot? Group Service owns that data, so Join Request Service asks it synchronously over gRPC (`GetGroupContext`, `AddMemberIfEligible`) and can reject a request at once with a precise reason.

The outcome of a successful approval is recorded as a `GroupMemberAdded` event in Group Service's outbox, in the same transaction as the new membership, and Join Request Service marks the request **Approved** only when it consumes that event. This gives one reliable path to the final state even when a gRPC reply is lost after the member was added, and the same events drive automatic housekeeping: cancelling the student's other pending requests and rejecting requests to groups that become full, locked or dissolved.

3.3. Scope Definition

Table 4. MVP scope

In MVP scope	Out of MVP scope / future extensions
JWT sign-in, role- and resource-based authorization, own profile update.	University SSO / OAuth; refresh tokens and server-side token revocation (logout = the client discards its short-lived token).
Administration of users, roles, semesters, courses, classes (MinMembers, MaxMembers, Deadline) and class rosters.	Automatic synchronization with the university timetable / LMS (rosters are imported by the administrator); reopening a closed class.
Group create, edit, dissolve, leadership transfer, leave/remove member; search, filter, sort and paginate groups.	AI-based team matching and compatibility scoring.
Join-request workflow (submit, cancel, approve, reject) over REST, gRPC and Redis Streams, with automatic cleanup of stale requests.	Real-time chat, video calls and meeting scheduling.
Lecturer dashboard; five background jobs; Docker Compose deployment.	E-mail / push notifications – a future Notification service can subscribe to the same group-events stream.

4. Main Actors

4.1. Actor Descriptions

Table 5. Actors

Actor	Type	Responsibilities and permissions
Student	Person	Is enrolled in one or more EXE classes. Views own classes, searches groups, and creates a group or submits/cancels join requests in a class where they have no group yet.
Team Leader	Person (contextual role)	A student who leads a specific group (`Groups.LeaderId`). Edits the group, approves or rejects its join requests, removes members, transfers leadership or dissolves the group. Checked per group – not a JWT role.
Lecturer	Person	Views assigned classes, grouping progress, under-filled groups and ungrouped students.
Administrator	Person	Manages user accounts and roles, semesters, courses, classes (lecturer, MinMembers, MaxMembers, Deadline) and class rosters.

4.2. Permission Matrix

Table 6. Permission matrix

Capability	Student	Team Leader	Lecturer	Administrator
View, search, filter and sort groups	✓ [1]	✓	✓ [2]	✓
Create a group	✓ [3]	– [4]	–	–
Edit group, transfer leadership, dissolve group	–	✓ (own group)	–	–
Remove a member from the group	–	✓ (own group)	–	–
Leave a group	✓ (member)	– [5]	–	–
Submit a join request	✓ [3]	– [4]	–	–
Cancel own pending join request	✓	–	–	–
View, approve and reject join requests of a group	–	✓ (own group)	–	–
View class overview and ungrouped students	–	–	✓ [2]	✓
Manage semesters, courses, classes, limits and deadlines	–	–	–	✓
Manage class rosters (enrollments)	–	–	–	✓
Manage user accounts and roles	–	–	–	✓

[1] Groups of the classes the student is enrolled in. [2] Classes the lecturer is assigned to. [3] Only in a class where the student is enrolled and has no group yet, before the class Deadline. [4] A Team Leader already belongs to a group in that class; in other classes they act as a Student. [5] The leader must transfer leadership first, or dissolve the group when they are its only member.

5. Main Features & Business Rules

5.1. Functional Requirements

Table 7. Functional requirements

ID	Feature	Description	Priority	Service
FR-01	JWT authentication	Sign-in issues a 60-minute JWT access token; every service validates it (issuer, audience, signing key). Logout is client-side (token discarded).	Must	Identity
FR-02	Role & resource authorization	Global roles from the JWT; Team Leader checked against `Groups.LeaderId` – locally in Group Service, via gRPC from Join Request Service.	Must	All
FR-03	Group discovery	Search by title/description; filter by class, status and open slots; sort by created date, title or member count; paging with page, pageSize and total count.	Must	Group
FR-04	Group management	Create (creator becomes leader and first member), edit, transfer leadership, dissolve, leave or remove members – before the deadline.	Must	Group
FR-05	Join requests	Submit (Pending, with the requester's code and name as snapshots), cancel own Pending request, list own requests; leaders list the requests of their group.	Must	Join Request
FR-06	Review join requests	Approve (gRPC `AddMemberIfEligible` + confirmation event on Redis Streams) or reject with an optional text.	Must	Join Request, Group
FR-07	Grouping rules	Enrollment and one group per student per class (database constraints); MaxMembers and Deadline (checked in the membership transaction and by the deadline job).	Must	Group
FR-08	Academic configuration	CRUD of semesters, courses and classes (lecturer, MinMembers, MaxMembers, Deadline – rule BR-09); class roster import.	Must	Group
FR-09	Lecturer dashboard	Class overview: grouped and ungrouped students, groups by status, under-filled groups.	Should	Group
FR-10	User & role management	Create, update and lock users; assign roles; update own profile.	Should	Identity
FR-11	Background processing	Outbox publishing, event consumption, deadline enforcement, processing reconciliation and data cleanup (section 6.6).	Must	Group, Join Request

Priorities use MoSCoW: Must = required for the MVP and the demo; Should = delivered when time allows. FR-08 and FR-11 are Must because FR-06 and FR-07 depend on class settings and on the background jobs.

5.2. Business Rules

- **BR-01 Enrollment.** A student can create or join a group only in a class whose roster contains them.
- **BR-02 One group per class.** A student belongs to at most one group in each class.
- **BR-03 Leadership.** Every group that is not Dissolved has exactly one leader, who is always one of its members. Leadership can be transferred to another member; the leader can leave only after transferring it. A group can be dissolved only when the leader is its sole member: the membership is removed, the group becomes Dissolved (member count 0, LeaderId kept for history) and GroupClosed (GROUP_DISSOLVED) is published.

- **BR-04 Capacity.** A group never exceeds the class's MaxMembers; it becomes Full at that size and returns to Recruiting when a member leaves or is removed before the deadline. Groups below MinMembers are reported as under-filled.
- **BR-05 Deadline.** After the class Deadline (UTC) no group can be created, joined, left or dissolved and no member can be removed; the deadline job closes the class and locks its groups.
- **BR-06 One active request.** A student has at most one active (Pending or Processing) request to the same group.
- **BR-07 Automatic cleanup.** When a student joins a group, their other Pending requests in that class are cancelled; when a group becomes Full, Locked or Dissolved, its Pending requests are rejected. Only requests created before the triggering event are affected.
- **BR-08 Configurable per class.** MinMembers, MaxMembers and Deadline are set per class by the administrator, never hard-coded.
- **BR-09 Changing class settings.** Lowering MaxMembers below the size of an existing group is rejected (409); otherwise the Full/Recruiting status of every group is recalculated in the same transaction and GroupClosed (GROUP_FULL) is published for groups that become full. The Deadline can be changed only while the class is Open.

5.3. Join Request Lifecycle

A join request has five states: **Pending** (waiting for the leader), **Processing** (approved; Group Service is adding the member), **Approved** (membership confirmed by the `GroupMemberAdded` event), **Rejected** (by the leader or by a rule) and **Cancelled** (by the student, or automatically after joining another group).

Table 8. Join request state transitions

#	From	Trigger	Guard	To	Actor
T1	–	Submit	Eligible per GetGroupContext (enrolled, no group in the class, group Recruiting, before deadline); no active request to this group	Pending	Student
T2	Pending	Cancel	Caller is the requester	Cancelled	Student
T3	Pending	Reject	Caller is the group's leader (GetGroupContext)	Rejected (REJECTED_BY_ LEADER)	Team Leader
T4	Pending	Approve	Caller is the group's leader; conditional update on Status = Pending	Processing	Team Leader
T5	Processing	AddMemberIfEligible returns a rule result (GROUP_FULL, GROUP_LOCKED, GROUP_ DISSOLVED, DEADLINE_ PASSED, ALREADY_IN_ OTHER_GROUP, NOT_ ENROLLED, GROUP_NOT_ FOUND)	–	Rejected (ReasonCode = result)	System
T6	Processing	GroupMemberAdded consumed for this RequestId	Event not processed before (ProcessedEvents)	Approved	Consumer job
T7	Processing	Transport error, timeout or unexpected status	–	Processing (retried later)	System

#	From	Trigger	Guard	To	Actor
T8	Pending	GroupMemberAdded for the same student in another group of the class	CreatedAt < event occurredAtUtc	Cancelled (JOINED_ANOTHER_GROUP)	Consumer job
T9	Pending	GroupClosed for the group	CreatedAt < event occurredAtUtc	Rejected (GROUP_FULL / GROUP_LOCKED / GROUP_DISSOLVED)	Consumer job
T10	Processing	AddMemberIfEligible returns NOT_LEADER (leadership changed meanwhile)	–	Pending (DecidedBy, DecidedAt cleared)	System

Every transition is a conditional update (`WHERE Status = <expected>`) protected by `RowVersion`; if no row is affected the API returns 409 Conflict. Cancel is allowed only from Pending, so a request cannot be cancelled while Group Service is adding the member. One list of reason codes is shared by the gRPC results, the events and `JoinRequests.ReasonCode`:

Table 9. Reason codes

Reason code	Meaning
`GROUP_FULL`	The group reached the class's MaxMembers.
`GROUP_LOCKED`	The class deadline passed and the group was locked.
`GROUP_DISSOLVED`	The group was dissolved by its leader.
`DEADLINE_PASSED`	The class deadline passed before the member could be added.
`ALREADY_IN_OTHER_GROUP`	The student already belongs to another group of the class.
`NOT_ENROLLED`	The student is not on the class roster.
`GROUP_NOT_FOUND`	The group does not exist.
`JOINED_ANOTHER_GROUP`	Automatic cancellation: the student joined another group of the class.
`REJECTED_BY_LEADER`	The Team Leader rejected the request (optional text in ReasonText).

5.4. RESTful API Endpoints

5.4.1. Conventions

- Resource-oriented, plural, kebab-case URLs under `/api`; JSON bodies; every route passes through the API Gateway (the web container proxies `/api` to it, so the browser stays on one origin).
- Authorization is expressed with roles and policies (e.g. `[Authorize(Roles = "Administrator")]`, resource checks), not with URL prefixes.
- List endpoints accept `page`, `pageSize` (default 20, max 100), `sortBy`, `sortDir` and `search`, and return `{ items, page, pageSize, totalCount, totalPages }`.
- Status codes: 200/201 (with Location)/204 on success, 400 validation, 401/403 authentication/authorization, 404 not found, 409 business-rule or concurrency conflict. Errors use RFC 7807 ProblemDetails with a traceId.
- Approve returns 202 Accepted with `Location: /api/join-requests/{id}` and `{ requestId, status: "Processing" }`; the Single-Page App polls that resource every 1–2 s (up to about 30 s) until it is Approved or Rejected.
- Join-request state changes are explicit actions (`POST /{id}/approve`, `/reject`, `/cancel`) because they are state transitions, not field edits.
- Transport security: in production TLS terminates at nginx and the gateway; the local Docker Compose demo uses plain HTTP.

5.4.2. Identity Service

Table 10. Identity Service endpoints

Method	Endpoint	Role	Purpose
POST	`/api/auth/login`	Anonymous	Verify credentials and issue a JWT access token (60 min).
GET	`/api/auth/me`	Any signed-in user	Current profile and roles.
PUT	`/api/auth/me`	Any signed-in user	Update own profile (full name).
GET	`/api/users`	Administrator	Search users; filter by `role` and `status`; sort and paging.
GET	`/api/users/{id}`	Administrator	User details.
POST	`/api/users`	Administrator	Create an account with roles (Student accounts require a user code).
PUT	`/api/users/{id}`	Administrator	Update e-mail, user code and full name.
PATCH	`/api/users/{id}/status`	Administrator	Lock or unlock an account (accounts are deactivated, not deleted).
PUT	`/api/users/{id}/roles`	Administrator	Replace the role set of a user.

5.4.3. Group Service

Table 11. Group Service endpoints

Method	Endpoint	Role	Purpose
GET	`/api/semesters`	Any signed-in user	List semesters (paged, sortable).
POST / PUT / DELETE	`/api/semesters[/{id}]`	Administrator	Create, update, delete a semester (delete only when it has no classes).
GET	`/api/courses`	Any signed-in user	List courses (paged, sortable).
POST / PUT / DELETE	`/api/courses[/{id}]`	Administrator	Create, update, delete a course (delete only when unused).
GET	`/api/classes`	Any signed-in user	Filter by `semesterId`, `courseId`, `search`; `mine=true` returns the classes the caller is enrolled in (with `myGroupId` and `isLeader`) or teaches.
GET	`/api/classes/{id}`	Any signed-in user	Class details with MinMembers, MaxMembers, Deadline, Status.
POST / PUT / DELETE	`/api/classes[/{id}]`	Administrator	Create; update lecturer, limits and deadline (rule BR-09); delete only when the class has no groups – its roster is deleted in the same transaction.
GET	`/api/classes/{id}/enrollments`	Lecturer (assigned), Administrator	Class roster; `grouped=false` lists the ungrouped students; search and paging.
POST	`/api/classes/{id}/enrollments`	Administrator	Enroll or refresh a batch of students picked from the user list (studentId plus code, name and e-mail snapshots; upsert).
DELETE	`/api/classes/{id}/enrollments/{studentId}`	Administrator	Remove a student who is not in a group.
GET	`/api/classes/{id}/overview`	Lecturer (assigned), Administrator	Grouping statistics: grouped / ungrouped counts, groups by status, under-filled groups.
GET	`/api/groups`	Any signed-in user (scoped)	Search groups of the caller's classes (Students: enrolled, Lecturers: assigned, Administrators: all); filter by `classId`, `status`, `hasOpenSlots`; sort by `createdAt`, `title` or `memberCount`; paging.

Method	Endpoint	Role	Purpose
GET	`/api/groups/{id}`	Any signed-in user (scoped)	Group details with member list (names from the roster snapshot).
POST	`/api/groups`	Student (eligible)	Create a group; the creator becomes Team Leader and first member.
PUT	`/api/groups/{id}`	Team Leader	Edit title and description.
DELETE	`/api/groups/{id}`	Team Leader	Dissolve the group: only when the leader is the sole member, before the deadline.
PUT	`/api/groups/{id}/leader`	Team Leader	Transfer leadership to another member.
DELETE	`/api/groups/{id}/members/{studentId}`	Member (self), Team Leader	Leave the group or remove a member, before the deadline; the leader must transfer leadership first.

5.4.4. Join Request Service

Table 12. Join Request Service endpoints

Method	Endpoint	Role	Purpose
GET	`/api/join-requests`	Student; Team Leader	`mine=true` returns own requests (with group title); `groupId={id}` returns the requests of the leader's group (with the requester's code and name); filter by `status`; paging.
GET	`/api/join-requests/{id}`	Requester, Team Leader	Request details and current status (used for polling after approve).
POST	`/api/join-requests`	Student (eligible)	Submit a request to a group → 201, status Pending.
POST	`/api/join-requests/{id}/cancel`	Requester	Cancel a Pending request → Cancelled.
POST	`/api/join-requests/{id}/approve`	Team Leader	Approve → 202 Accepted with `Location: /api/join-requests/{id}` and `{ requestId, status: Processing }`; 409 with the rule that failed.
POST	`/api/join-requests/{id}/reject`	Team Leader	Reject with an optional text → Rejected (REJECTED_BY_LEADER).

6. System Architecture – C4 Model (Level 1 & Level 2)

The architecture is described with the C4 model (c4model.com) at Level 1 (System Context) and Level 2 (Container); Levels 3 and 4 are out of scope. Both diagrams read from left to right and use the same people and relationship meanings, so Figure 2 is a direct zoom-in of Figure 1.

6.1. Level 1: System Context Diagram

Three kinds of people use the system. In the MVP the system has no external software-system dependencies – university SSO and LMS/timetable synchronization are out of scope (section 3.3) – so no external systems appear.




Figure 1. C4 Level 1 – System Context diagram for EXE Group Management System

6.2. Level 2: Container Diagram

Requests flow from left to right. Solid arrows are synchronous calls; dashed arrows are events through the Group Events stream, which is modeled as a container as c4model.com recommends (not the whole message bus). The nginx web container, which serves the Single-Page App files and forwards `/api` calls to the gateway (section 7.3), is omitted for compactness.




Figure 2. C4 Level 2 – Container diagram for EXE Group Management System

6.3. Container Responsibilities

Table 13. Container responsibilities

Container	Technology	Responsibilities
Single-Page App	React 18, TypeScript (Vite), served by nginx	UI for students, Team Leaders, lecturers and administrators; talks only to the API Gateway.
API Gateway	ASP.NET Core 8 + YARP	Single public API entry point; validates the JWT at the edge; routes by path prefix (section 7.3); forwards the Authorization and X-Correlation-ID headers; serves the Swagger UI.
Identity Service	ASP.NET Core 8 Web API	Sign-in and JWT issuing, user accounts, roles, own profile.

Container	Technology	Responsibilities
Group Service	ASP.NET Core 8 Web API + gRPC server	Semesters, courses, classes, rosters, groups and memberships; gRPC GroupMembership service; OutboxPublisher, DeadlineEnforcer and DataCleanup jobs.
Join Request Service	ASP.NET Core 8 Web API + gRPC client	Join-request lifecycle; calls Group Service over gRPC; GroupEventsConsumer, ProcessingReconciler and DataCleanup jobs.
IdentityDb	SQL Server 2022	Users, roles and their assignments (Identity Service only).
GroupDb	SQL Server 2022	Semesters, courses, classes, rosters, groups, memberships, idempotency records and the outbox (Group Service only).
RequestDb	SQL Server 2022	Join requests and processed event ids (Join Request Service only).
Group Events	Redis 7 Stream (key `group-events`)	Carries GroupMemberAdded and GroupClosed from Group Service (producer) to Join Request Service (consumer group `join-request-service`).

Each database is changed only by its owning service through EF Core migrations; there are no cross-database foreign keys. Display names are snapshots taken when data is written – ClassEnrollments for rosters and member lists, JoinRequests for the requester's code and name – so no service reads another service's database to render a list.

6.4. Inter-Service Workflow – Approving a Join Request

1. The Team Leader clicks Approve; the Single-Page App calls `POST /api/join-requests/{id}/approve` through the gateway [REST].
2. Join Request Service calls `GetGroupContext` [gRPC] and checks that the caller is the group's leader (otherwise 403; nothing changes).
3. It moves the request Pending → Processing with a conditional update and records DecidedBy/DecidedAt (409 if the request changed meanwhile).
4. It calls `AddMemberIfEligible(requestId, groupId, studentId, approverId)` [gRPC] with a 5-second deadline.
5. Group Service first checks idempotency: a request_id already in AddMemberRequests, or a student already in this group, returns ALREADY_ADDED; a student in another group of the class returns ALREADY_IN_OTHER_GROUP. Otherwise, in one transaction, it re-checks leader, enrollment, deadline, group status and capacity (RowVersion), inserts the GroupMembers and AddMemberRequests rows, updates CurrentMemberCount (Status = Full at the limit) and writes `GroupMemberAdded` – plus `GroupClosed (GROUP_FULL)` if the group became full – to OutboxEvents.
6. A rule result sets the request to Rejected with its ReasonCode (409 to the leader); NOT_LEADER returns it to Pending (403); success answers 202 Accepted (Processing).
7. OutboxPublisher publishes the events to the `group-events` stream within about 2 seconds and marks them published.
8. GroupEventsConsumer stores the EventId in ProcessedEvents and, in the same transaction, sets the request to Approved and cancels the student's other Pending requests in that class created before the event; it then acknowledges the message (XACK).
9. If no event arrives – for example because the gRPC call timed out – ProcessingReconciler repeats `AddMemberIfEligible` for requests still Processing 2 minutes after DecidedAt; the call is idempotent by request_id, so a member is never added twice.

Other flows use the same building blocks:

- **Submit a request** – Join Request Service calls `GetGroupContext` to check enrollment, no existing group in the class, group status and deadline, stores ClassId, StudentCode, StudentName and GroupTitle, and inserts the request as Pending (201).
- **Create a group** – Group Service inserts the group and the leader's membership and publishes `GroupMemberAdded` (requestId = null), which cancels the creator's Pending requests in that class.
- **Leave or remove a member** – Group Service deletes the membership before the deadline, decrements CurrentMemberCount and turns a Full group back to Recruiting; no event is needed.
- **Dissolve a group** – allowed when the leader is the sole member: the membership is deleted, the group becomes Dissolved with count 0, and `GroupClosed (GROUP_DISSOLVED)` rejects its Pending requests.
- **Deadline passes** – DeadlineEnforcer closes the class and locks its groups; the `GroupClosed (GROUP_LOCKED)` events make the consumer reject their Pending requests.

6.5. Inter-Service Contracts

6.5.1. gRPC – GroupMembership Service (Group Service)

Table 14. gRPC methods (messages <Method>Request and <Method>Reply)

Method	Request fields	Reply fields	Used for
`GetGroupContext`	group_id, student_id	exists, class_id, leader_id, group_status, deadline_utc, current_member_count, max_members, group_title, student_enrolled, student_has_group_in_class, student_code, student_full_name	Read-only. Submit (eligibility and snapshots); list, approve and reject (is the caller the leader?).
`AddMemberIfEligible`	request_id, group_id, student_id, approver_id	result, membership_id, current_member_count	Approve and ProcessingReconciler. Idempotent by request_id; adds the member, the idempotency record and the outbox event in one transaction.

Table 15. AddMemberIfEligible results (prefixed ADD_MEMBER_RESULT_ in the .proto)

Result	Meaning	Effect on the join request
`ADDED`	Member added; GroupMemberAdded written to the outbox.	Stays Processing until the event is consumed (202).
`ALREADY_ADDED`	request_id was already processed, or the student is already in this group – checked first, before any rule.	Same as ADDED – no second event.
`GROUP_FULL`	CurrentMemberCount reached MaxMembers.	Rejected, ReasonCode GROUP_FULL (409).
`GROUP_LOCKED`	The class deadline passed and the group is Locked.	Rejected, ReasonCode GROUP_LOCKED (409).
`GROUP_DISSOLVED`	The group was dissolved.	Rejected, ReasonCode GROUP_DISSOLVED (409).
`DEADLINE_PASSED`	The class deadline has passed (group not locked yet).	Rejected, ReasonCode DEADLINE_PASSED (409).
`ALREADY_IN_OTHER_GROUP`	The student already belongs to another group of the class.	Rejected, ReasonCode ALREADY_IN_OTHER_GROUP (409).
`NOT_ENROLLED`	The student is not on the class roster.	Rejected, ReasonCode NOT_ENROLLED (409).

Result	Meaning	Effect on the join request
GROUP_NOT_FOUND	The group does not exist.	Rejected, ReasonCode GROUP_NOT_FOUND (409).
NOT_LEADER	approver_id is no longer the group's leader.	Back to Pending (T10); 403 to an interactive caller, logged for the reconciler.
Transport error / timeout	UNAVAILABLE, DEADLINE_EXCEEDED, ABORTED (5 s client deadline).	Stays Processing; ProcessingReconciler retries (202).
Other status / UNSPECIFIED	INTERNAL, UNKNOWN, INVALID_ARGUMENT or result value 0.	Stays Processing, error logged; ProcessingReconciler retries.

The complete `group_membership.proto` is listed in Appendix A. Business outcomes are returned in the `result` field; gRPC status codes are reserved for transport problems. The gRPC endpoint (port 8081) is service-to-service only: no end-user JWT is forwarded, the trust boundary is the internal Docker network, and `approver_id` is the `sub` already validated by Join Request Service.

6.5.2. Events – Redis Streams

Group Service appends events to the stream `group-events` (`XADD … MAXLEN ~ 10000`). At start-up Join Request Service creates the consumer group `join-request-service` (`XGROUP CREATE … MKSTREAM`, ignoring BUSYGROUP) and then reads in a polling loop with `XREADGROUP` – StackExchange.Redis deliberately offers no blocking reads. Each message is acknowledged (`XACK`) after its database transaction commits, and messages left pending by a crashed consumer are re-claimed with `XAUTOCLAIM`. Delivery is at-least-once; duplicates are discarded through ProcessedEvents. Every message has the envelope fields `eventId`, `eventType`, `occurredAtUtc`, `correlationId` and `payload` (JSON).

Table 16. Events on the group-events stream

Event	Meaning	Payload	Consumer effect
GroupMemberAdded	A student became a member of a group (approval or group creation).	groupId, classId, studentId, requestId (null when the leader creates the group), currentMemberCount	Request → Approved (if Processing); the student's other Pending requests in the class created before occurredAtUtc → Cancelled (JOINED_ANOTHER_GROUP).
GroupClosed	A group stopped accepting members.	groupId, classId, reason (GROUP_FULL | GROUP_LOCKED | GROUP_DISSOLVED)	Pending requests of the group created before occurredAtUtc → Rejected with the reason.

6.6. Background Jobs

Table 17. Background jobs (BackgroundService + PeriodicTimer)

Job	Service	Schedule	Responsibility
OutboxPublisher	Group Service	Every 2 s	Reads unpublished OutboxEvents (oldest first), XADDs them to group-events, sets PublishedAtUtc; on failure increments RetryCount and stores LastError.
DeadlineEnforcer	Group Service	Every 1 min	Closes classes whose Deadline has passed, locks their Recruiting/Full groups and writes GroupClosed (GROUP_LOCKED) to the outbox.
GroupEventsConsumer	Join Request Service	Polling loop (0.5–1 s pause when idle)	Creates the consumer group at start-up (XGROUP CREATE … MKSTREAM); reads with XREADGROUP COUNT 50 (StackExchange.Redis has no blocking reads); applies events idempotently and XACKs after commit; every 30 s re-claims messages idle for 60 s with XAUTOCLAIM.
ProcessingReconciler	Join Request Service	Every 1 min	Calls AddMemberIfEligible again for requests still Processing 2 minutes after DecidedAt; safe because the call is idempotent by request_id.
DataCleanup	Group Service and Join Request Service	Daily, 02:00 UTC	Deletes OutboxEvents published more than 7 days ago and AddMemberRequests and ProcessedEvents older than 30 days; the stream itself is capped by XADD MAXLEN ~ 10000.

7. Technology

7.1. Technology Stack

Table 18. Technology stack

Layer / capability	Technology	Purpose and PRN232 alignment
Backend framework	ASP.NET Core 8 (.NET 8 LTS)	Layered architecture (Controllers → Services → Repositories), dependency injection, Options-based configuration, logging, global exception handling.
API Gateway	YARP 2.x	Single entry point, edge JWT validation, path-based routing, Swagger UI.
Persistence	EF Core 8, SQL Server 2022	Database per service, Code-First migrations, rowversion concurrency, filtered unique indexes, CHECK constraints.
Synchronous communication	gRPC: Grpc.AspNetCore, Grpc.Net.Client, Protocol Buffers over HTTP/2	GroupMembership service: GetGroupContext, AddMemberIfEligible (section 6.5.1).
Message broker	Redis 7 Streams via StackExchange.Redis 2.7+	Producer Group Service, consumer group Join Request Service; XADD, XREADGROUP (polling), XACK, XAUTOCLAIM.
Background processing	.NET BackgroundService + PeriodicTimer	Five jobs (section 6.6).
Security	JWT Bearer (HS256, key from configuration); ASP.NET Core PasswordHasher (PBKDF2)	Authentication in every service; role- and resource-based authorization. RS256 with a JWKS endpoint is a later hardening step.
API documentation	Swashbuckle (Swagger / OpenAPI 3)	One OpenAPI document per service, all shown in the gateway's Swagger UI at `/swagger`.
Frontend	React 18, TypeScript, Vite, nginx	Single-Page App that talks only to the gateway.
Deployment	Docker, Docker Compose	Seven containers (section 7.3).

Broker decision – Redis Streams. PRN232 allows Apache Kafka or Redis. Redis Streams was chosen because it runs as one lightweight container and still offers persistent streams, consumer groups, acknowledgements and a pending-entries list for redelivery – the at-least-once delivery that the outbox and the idempotent consumer rely on. Redis Pub/Sub was rejected because it does not store messages (an offline consumer loses them). Kafka would also fit, but adds a heavier JVM-based broker without a benefit at this scale.

7.2. Cross-Cutting Concerns

- **Configuration:** `appsettings.json` per service, overridden by environment variables from Docker Compose and a git-ignored `.env` file (e.g. `ConnectionStrings__GroupDb`, `Jwt__SigningKey`, `Redis__Connection`, `GrpcClients__GroupService`); no secrets in source control.
- **Logging and tracing:** structured logging with Serilog; the gateway creates an `X-Correlation-ID` that travels in HTTP headers, gRPC metadata and the event envelope, so one approval can be traced across all services.
- **Exception handling:** global middleware converts exceptions to RFC 7807 ProblemDetails; rule violations map to 409 and validation errors to 400.
- **Security:** only the web (3000) and gateway (8080) containers publish ports – SQL Server 1433 only in development; every service validates the JWT (same issuer, audience and key) and takes the caller from the `sub` claim; gRPC (8081) is reachable only on the internal Docker network.
- **Data access:** one DbContext and repositories per service; sequential GUID keys generated by EF Core (known before SaveChanges, less index fragmentation); all timestamps in UTC.
- **Health checks and seed data:** `/health/live` and `/health/ready` (database and Redis checks) are used by Docker Compose; in Development, Identity Service seeds the three roles and a first Administrator account.

7.3. Deployment – Docker Compose

Table 19. Docker Compose services

Service	Image / build	Ports	Depends on	Notes
web	nginx:1.27-alpine + React build	3000 → 80	gateway	Serves the Single-Page App and reverse-proxies /api and /swagger to the gateway (same origin, so no CORS).
gateway	Build: src/ApiGateway (YARP)	8080 → 8080	identity-service, group-service, join-request-service	Single public API entry point; validates the JWT; routes by path prefix; Swagger UI.
identity-service	Build: src/IdentityService	internal 8080	sqlserver	REST; owns IdentityDb.
group-service	Build: src/GroupService	internal 8080 (REST), 8081 (gRPC, HTTP/2 only)	sqlserver, redis	REST + gRPC server; outbox, deadline and cleanup jobs.
join-request-service	Build: src/JoinRequestService	internal 8080	sqlserver, redis, group-service	REST; gRPC client of http://group-service:8081; consumer, reconciler and cleanup jobs.
sqlserver	mcr.microsoft.com/mssql/server:2022-latest	1433 (development only)	–	One instance hosting IdentityDb, GroupDb and RequestDb; data volume.
redis	redis:7-alpine (appendonly yes)	internal 6379	–	Hosts the group-events stream; data volume.

Table 20. API Gateway routes (YARP)

Path prefix	Destination
`/api/auth/login`	identity-service – anonymous (no JWT required)
`/api/auth/**, /api/users/**`	identity-service
`/api/semesters/**, /api/courses/**, /api/classes/**, /api/groups/**`	group-service
`/api/join-requests/**`	join-request-service
`/swagger/{identity|group|join-request}/**`	OpenAPI document of the matching service (prefix removed); the Swagger UI at /swagger lists all three

Group Service listens on two Kestrel endpoints: 8080 (HTTP/1.1, REST) and 8081 (HTTP/2 only, gRPC), because gRPC without TLS (h2c) cannot share an HTTP/1.1 endpoint. EF Core migrations are applied at start-up in Development; elsewhere the team runs `dotnet ef database update` or `database/schema.sql`. Running `docker compose up -d` starts the whole system; the Single-Page App is at http://localhost:3000 and the Swagger UI at http://localhost:8080/swagger.

7.4. Requirement Traceability & Bonus Features

Table 21. PRN232 requirement traceability

Assignment section (PRN232 – Final Assignment)	How the design satisfies it	Demo step
§2.1 REST API: CRUD, layered architecture, JWT, search / filter / sort / paging	Three services behind a gateway (section 5.4); Controllers → Services → Repositories in every service (sections 7.1–7.2); FR-01 to FR-10	Sign in; CRUD a class; search groups with paging and sorting in Swagger
§2.2 Background job	Five jobs (section 6.6)	Approve a request and show OutboxPublisher and consumer logs; pass a deadline and show the groups locked
§2.3 Message broker: producer and consumer	Redis Streams `group-events`; producer Group Service (outbox), consumer Join Request Service (section 6.5.2)	Show the stream entries (XRANGE / RedisInsight) and the request turning Approved
§2.4 gRPC service and REST ↔ gRPC interaction	GroupMembership gRPC server in the independent group-service container (HTTP/2 port 8081); the Join Request Service REST API calls it on submit, list by group, approve and reject (sections 6.4–6.5.1)	Submit and approve a request; follow the gRPC calls by correlation id
§3 Deployment	Docker Compose with seven containers (section 7.3)	`docker compose up`; all health checks green
§4 Technical requirements	.NET 8, EF Core, SQL Server, DI, configuration, logging, exception handling, JWT, Swagger, Docker (sections 7.1–7.2)	Swagger UI; ProblemDetails on a rule violation
§5 Deliverables	EF Core migrations + reference DDL `database/schema.sql`, Dockerfiles, compose file, Swagger, README	–
§6 Demonstration – end-to-end workflow	Approve flow (section 6.4)	Student submits → leader approves → member added → other requests cancelled

Bonus features beyond the minimum requirements:

- API Gateway with YARP (single entry point, edge authentication, Swagger UI).
- Transactional Outbox, idempotent consumer (ProcessedEvents) and idempotent gRPC operation (AddMemberRequests) – an exactly-once effect on top of at-least-once delivery.
- Optimistic concurrency with rowversion for the last free slot and for request state transitions.

- Business rules enforced in the database – enrollment and class consistency through composite foreign keys, one group per class and one active request through (filtered) unique indexes, value checks through CHECK constraints – verified by running the DDL and 34 tests on SQL Server 2019.
- ProcessingReconciler and DataCleanup jobs, correlation-id tracing and health checks.

8. Conceptual ERD

Figure 3 shows the nine domain entities, colored by the bounded context (and database) that owns them. Solid lines are relationships inside one database; dashed lines are references between services that are maintained by the services, not by foreign keys. Cardinalities use crow's-foot notation, explained in the key under the figure. Attributes and data types belong to the physical design (section 9).




Figure 3. Conceptual ERD

- A USER can have several ROLEs (many-to-many).
- A SEMESTER contains, and a COURSE is offered in, many EXE_CLASSes; each EXE_CLASS is taught by one Lecturer (USER).
- CLASS_ENROLLMENT is the roster of an EXE_CLASS and links each enrolled Student (USER) to it.

- An enrolled student joins at most one GROUP of the class: each CLASS_ENROLLMENT has at most one GROUP_MEMBER (BR-02). A GROUP has at least one member – its Team Leader – until it is dissolved (BR-03).
- A GROUP receives JOIN_REQUESTs; a Student submits them and the group's Team Leader decides them.

9. Physical Database Design

Each service owns one database on a shared SQL Server 2022 instance: **IdentityDb**, **GroupDb** and **RequestDb**. The schemas are created by EF Core Code-First migrations; the equivalent reference DDL is delivered in `database/schema.sql`.

9.1. Physical Database Diagrams

Figures 4–6 show one diagram per database, in the same order as section 9.2 and at the same scale. Connectors are foreign keys in crow's-foot notation, labeled with the foreign-key columns. Columns marked LR refer to another service's database without a foreign key (section 9.4); complete types, defaults and constraints are listed in section 9.2.




Figure 4. IdentityDb (Identity Service)




Figure 5. GroupDb (Group Service)




Figure 6. RequestDb (Join Request Service)

9.2. Data Dictionary

Abbreviations: PK primary key, FK foreign key, AK alternate key, UX unique index, IX non-unique index, CK check constraint, LR logical reference (section 9.4). All timestamps are UTC.

9.2.1. IdentityDb (owned by Identity Service)

Table 22. IdentityDb.Users – User accounts for all roles

Column	Data type	Null	Key / constraint	Description
UserId	uniqueidentifier	No	PK	Surrogate key (sequential GUID generated by EF Core).
Email	nvarchar(255)	No	UX_Users_Email	University e-mail used to sign in.
UserCode	varchar(20)	Yes	UX_Users_UserCode (filtered)	Student code (e.g. SE180001) or staff code; required for Student accounts (validated by Identity Service); unique when present.
PasswordHash	nvarchar(500)	No	–	Salted PBKDF2 hash (ASP.NET Core PasswordHasher).
FullName	nvarchar(150)	No	–	Display name.
Status	varchar(20)	No	Default 'Active'; CK_Users_Status	Account state: Active, Locked.
CreatedAt	datetime2	No	Default SYSUTCDATETIME()	Creation time (UTC).
UpdatedAt	datetime2	Yes	–	Last update time (UTC).

Table 23. IdentityDb.Roles – Global roles (seeded): Student, Lecturer, Administrator

Column	Data type	Null	Key / constraint	Description
RoleId	uniqueidentifier	No	PK	Surrogate key (fixed seed values).
Name	varchar(50)	No	UX_Roles_Name	Role name: Student, Lecturer, Administrator.

Table 24. IdentityDb.UserRoles – Many-to-many assignment of roles to users

Column	Data type	Null	Key / constraint	Description
UserId	uniqueidentifier	No	PK; FK → Users(UserId)	References Users(UserId); cascade delete.
RoleId	uniqueidentifier	No	PK; FK → Roles(RoleId)	References Roles(RoleId).

9.2.2. GroupDb (owned by Group Service)

Table 25. GroupDb.Semesters – Academic semesters

Column	Data type	Null	Key / constraint	Description
SemesterId	uniqueidentifier	No	PK	Surrogate key.
Code	varchar(20)	No	UX_Semesters_Code	Short code, e.g. FA26.
Name	nvarchar(100)	No	–	Full name, e.g. Fall 2026.
StartDate	date	No	CK_Semesters_Dates	First day of the semester.
EndDate	date	No	CK_Semesters_Dates	Last day of the semester; must be after StartDate.

Table 26. GroupDb.Courses – EXE courses

Column	Data type	Null	Key / constraint	Description
CourseId	uniqueidentifier	No	PK	Surrogate key.
Code	varchar(20)	No	UX_Courses_Code	Course code, e.g. EXE101, EXE201.
Name	nvarchar(150)	No	–	Course title.

Table 27. GroupDb.ExeClasses – Class sections of an EXE course in a semester, with grouping rules

Column	Data type	Null	Key / constraint	Description
ClassId	uniqueidentifier	No	PK	Surrogate key.
SemesterId	uniqueidentifier	No	FK → Semesters(SemesterId); UX_ExeClasses_Semester_Course_Code	References Semesters(SemesterId).
CourseId	uniqueidentifier	No	FK → Courses(CourseId); UX_ExeClasses_Semester_Course_Code	References Courses(CourseId).
ClassCode	varchar(30)	No	UX_ExeClasses_Semester_Course_Code	Class code, e.g. SE1801; unique per semester and course.
LecturerId	uniqueidentifier	No	LR → Users	Assigned lecturer → IdentityDb.Users (logical reference).
MinMembers	int	No	CK_ExeClasses_Members	Groups below this size are reported as under-filled.
MaxMembers	int	No	CK_ExeClasses_Members	Maximum group size in this class (≥ MinMembers).
Deadline	datetime2	No	–	Grouping deadline (UTC); can change only while the class is Open.
Status	varchar(20)	No	Default 'Open'; CK_ExeClasses_Status	Open, Closed (set by the deadline job).
CreatedAt	datetime2	No	Default SYSUTCDATETIME()	Creation time (UTC).

Table 28. GroupDb.ClassEnrollments – Class roster: which students belong to which class

Column	Data type	Null	Key / constraint	Description
ClassId	uniqueidentifier	No	PK; FK → ExeClasses(ClassId)	References ExeClasses(ClassId).
StudentId	uniqueidentifier	No	PK; LR → Users	Student → IdentityDb.Users (logical reference).
StudentCode	varchar(20)	No	–	Snapshot of Users.UserCode; refreshed when the roster is imported again.
FullName	nvarchar(150)	No	–	Snapshot of Users.FullName, used for rosters, member lists and join requests.
Email	nvarchar(255)	No	–	Snapshot of Users.Email.
EnrolledAt	datetime2	No	Default SYSUTCDATETIME()	Enrollment time (UTC).

Table 29. GroupDb.Groups – Project groups formed inside a class

Column	Data type	Null	Key / constraint	Description
GroupId	uniqueidentifier	No	PK; AK_Groups_GroupId_ ClassId	Surrogate key.
ClassId	uniqueidentifier	No	FK → ExeClasses(ClassId); AK_Groups_GroupId_ ClassId; UX_Groups_Class_ Title (filtered)	References ExeClasses(ClassId).
LeaderId	uniqueidentifier	No	LR → Users	Team Leader → IdentityDb.Users; a member while the group is not Dissolved (kept for history afterwards).
Title	nvarchar(200)	No	UX_Groups_Class_Title (filtered)	Project topic / group name; unique in a class among groups that are not Dissolved.
Description	nvarchar(1000)	Yes	–	Startup idea and wanted skills.
CurrentMemberCount	int	No	Default 1; CK_Groups_ MemberCount	Cached head-count used for the capacity check; 0 only when Dissolved.
Status	varchar(20)	No	Default 'Recruiting'; CK_ Groups_Status; CK_ Groups_MemberCount	Recruiting, Full, Locked, Dissolved.
RowVersion	rowversion	No	Concurrency token	Optimistic concurrency token.
CreatedAt	datetime2	No	Default SYSUTCDATETIME()	Creation time (UTC).
UpdatedAt	datetime2	Yes	–	Last update time (UTC).

Table 30. GroupDb.GroupMembers – Membership of enrolled students in groups

Column	Data type	Null	Key / constraint	Description
MembershipId	uniqueidentifier	No	PK	Surrogate key.
GroupId	uniqueidentifier	No	FK → Groups(GroupId, ClassId)	With ClassId references Groups(GroupId, ClassId).
ClassId	uniqueidentifier	No	FK → Groups(GroupId, ClassId); FK → ClassEnrollments(ClassId, StudentId); UX_ GroupMembers_Class_ Student	Must equal the group's class (composite FK); part of the one-group-per-class key.
StudentId	uniqueidentifier	No	FK → ClassEnrollments(ClassId, StudentId); UX_ GroupMembers_Class_ Student; LR → Users	With ClassId references ClassEnrollments (only enrolled students); student → IdentityDb.Users.
JoinedAt	datetime2	No	Default SYSUTCDATETIME()	Time the membership was created (UTC).

Table 31. GroupDb.AddMemberRequests – Idempotency records of successful AddMemberIfEligible calls (one per join request)

Column	Data type	Null	Key / constraint	Description
RequestId	uniqueidentifier	No	PK; LR → JoinRequests	= RequestDb.JoinRequests. RequestId (request_id of AddMemberIfEligible) – the idempotency key.
GroupId	uniqueidentifier	No	FK → Groups(GroupId)	References Groups(GroupId); the group the student was added to.
StudentId	uniqueidentifier	No	LR → Users	Student who was added → IdentityDb.Users.
MembershipId	uniqueidentifier	No	–	GroupMembers row created by this request (no FK: the membership may end later).
ProcessedAtUtc	datetime2	No	Default SYSUTCDATETIME()	Time the member was added; rows are cleaned up after 30 days.

Table 32. GroupDb.OutboxEvents – Transactional outbox: events written in the same transaction as the business change

Column	Data type	Null	Key / constraint	Description
EventId	uniqueidentifier	No	PK	Event id; idempotency key on the consumer side.
EventType	varchar(100)	No	–	GroupMemberAdded or GroupClosed.
AggregateId	uniqueidentifier	No	–	GroupId the event is about (no FK).
Payload	nvarchar(max)	No	CK_OutboxEvents_Payload	JSON payload (CHECK ISJSON).
CorrelationId	varchar(64)	Yes	–	Correlation id of the originating request.
OccurredAtUtc	datetime2	No	Default SYSUTCDATETIME()	Time the event was recorded.
PublishedAtUtc	datetime2	Yes	–	NULL until published to the Redis stream.
RetryCount	int	No	Default 0	Failed publish attempts.
LastError	nvarchar(1000)	Yes	–	Last publish error, for diagnostics.

9.2.3. RequestDb (owned by Join Request Service)

Table 33. RequestDb.JoinRequests – Requests from students to join a group, with their lifecycle state

Column	Data type	Null	Key / constraint	Description
RequestId	uniqueidentifier	No	PK	Surrogate key; also the idempotency key of AddMemberIfEligible.
GroupId	uniqueidentifier	No	UX_JoinRequests_ ActiveRequest (filtered); LR → Groups	Target group → GroupDb.Groups (logical reference).
ClassId	uniqueidentifier	No	LR → ExeClasses	Class of the group, copied from GetGroupContext at submit time.
StudentId	uniqueidentifier	No	UX_JoinRequests_ ActiveRequest (filtered); LR → Users	Requesting student (JWT sub) → IdentityDb.Users.
StudentCode	varchar(20)	No	–	Snapshot of the requester's student code (from GetGroupContext).
StudentName	nvarchar(150)	No	–	Snapshot of the requester's full name, shown to the Team Leader.
GroupTitle	nvarchar(200)	No	–	Snapshot of the group title, shown in the student's request list.
Status	varchar(20)	No	Default 'Pending'; CK_ JoinRequests_Status	Pending, Processing, Approved, Rejected, Cancelled.
Message	nvarchar(500)	Yes	–	Optional introduction from the student.
DecidedBy	uniqueidentifier	Yes	LR → Users	Team Leader who approved/rejected → IdentityDb.Users.
DecidedAt	datetime2	Yes	–	Time of the approve/reject decision; for Processing, when the request entered Processing (used by ProcessingReconciler).
ReasonCode	varchar(40)	Yes	CK_JoinRequests_ ReasonCode	Machine-readable reason (list in section 5.3).
ReasonText	nvarchar(500)	Yes	–	Free text from the Team Leader when rejecting.
RowVersion	rowversion	No	Concurrency token	Optimistic concurrency token for state transitions.
CreatedAt	datetime2	No	Default SYSUTCDATETIME()	Submission time (UTC).
UpdatedAt	datetime2	Yes	–	Last state change (UTC).

Table 34. RequestDb.ProcessedEvents – Inbox of consumed event ids (idempotent consumer)

Column	Data type	Null	Key / constraint	Description
EventId	uniqueidentifier	No	PK; LR → OutboxEvents	Id of a consumed event = GroupDb.OutboxEvents.EventId (carried in the stream message).
EventType	varchar(100)	No	–	GroupMemberAdded or GroupClosed.
ProcessedAtUtc	datetime2	No	Default SYSUTCDATETIME()	Time the event was applied; rows are cleaned up after 30 days.

9.3. Indexes, Constraints & Business-Rule Matrix

Table 35. Indexes, constraints and business rules

Rule	Implementation (SQL Server / EF Core)	Behavior on violation or conflict
BR-01 Enrollment	`FK_GroupMembers_ClassEnrollments` (ClassId, StudentId) → ClassEnrollments; `GetGroupContext.student_enrolled` on submit	Insert rejected → NOT_ENROLLED (409)
BR-02 One group per class	Membership lookup first (idempotency); `UX_GroupMembers_Class_Student` (ClassId, StudentId) as the last line of defense	Same group → ALREADY_ADDED; other group → ALREADY_IN_OTHER_GROUP (409); a duplicate-key error 2601 from a race is re-read and mapped the same way
Member class = group class	`AK_Groups_GroupId_ClassId` + `FK_GroupMembers_Groups` (GroupId, ClassId)	Insert rejected (programming error) → 500, logged
BR-03 Leadership	`Groups.LeaderId` NOT NULL; transfer, leave and dissolve check “leader is a member” in one transaction; `CK_Groups_MemberCount` (count 0 only when Dissolved)	409; dissolving deletes the last membership in the same transaction
BR-04 Capacity	CurrentMemberCount < MaxMembers checked in the transaction; `Groups.RowVersion` concurrency token (`IsRowVersion()`)	Concurrency conflict → reload and retry up to 3 times; GROUP_FULL when no slot is left; ABORTED (transient) after 3 conflicts
BR-05 Deadline	Deadline (UTC) compared in every membership transaction; DeadlineEnforcer sets ExeClasses.Status = Closed and Groups.Status = Locked	DEADLINE_PASSED or GROUP_LOCKED (409)
BR-06 One active request	`UX_JoinRequests_ActiveRequest` (GroupId, StudentId) WHERE Status IN ('Pending', 'Processing')	Duplicate-key error 2601 → 409, request already active
BR-07 Automatic cleanup	Consumer updates through `IX_JoinRequests_Student_Class_Status` (T8) and `IX_JoinRequests_Group_Status` (T9), only for requests with CreatedAt < occurredAtUtc	–
BR-08 / BR-09 Class settings	ExeClasses.MinMembers, MaxMembers, Deadline + `CK_ExeClasses_Members`; PUT /api/classes/{id} recalculates group statuses in one transaction	409 when the new MaxMembers is below the largest group or the class is Closed
Request transitions	`UPDATE … WHERE RequestId = @id AND Status = @expected` + `JoinRequests.RowVersion`	0 rows affected → 409 Conflict
Idempotent AddMemberIfEligible	`AddMemberRequests` (PK RequestId) written with GroupMembers and OutboxEvents in one transaction	Repeated request_id → ALREADY_ADDED, no second event
Unique names and codes	`UX_Groups_Class_Title` (WHERE Status <> 'Dissolved'), `UX_ExeClasses_Semester_Course_Code`, `UX_Semesters_Code`, `UX_Courses_Code`, `UX_Roles_Name`, `UX_Users_Email`, `UX_Users_UserCode` (WHERE UserCode IS NOT NULL)	Duplicate-key error 2601 → 409 with the conflicting field
Valid values	CHECK constraints: status columns, reason codes, EndDate > StartDate, 1 ≤ MinMembers ≤ MaxMembers, member count vs Dissolved, ISJSON(Payload)	Validated in the API first (400); the CHECK is the last line of defense
Transactional outbox	GroupMembers, Groups, AddMemberRequests and OutboxEvents written in one SaveChanges transaction; `IX_OutboxEvents_Unpublished` (OccurredAtUtc) WHERE PublishedAtUtc IS NULL	Broker down → events stay unpublished and are retried (RetryCount, LastError)
Idempotent consumer	INSERT ProcessedEvents (PK EventId) and UPDATE JoinRequests in one transaction; XACK only after commit	Primary-key error 2627 → duplicate, skipped and acknowledged
No cascading deletes	All foreign keys ON DELETE NO ACTION (EF `DeleteBehavior.NoAction`), except UserRoles → Users; DELETE /api/classes/{id} only without groups, deleting the roster in the same transaction	Avoids SQL Server's “multiple cascade paths” error; blocked deletes return 409

Rule	Implementation (SQL Server / EF Core)	Behavior on violation or conflict
Supporting indexes	`IX_UserRoles_RoleId` (RoleId) `IX_ExeClasses_CourseId` (CourseId) `IX_ExeClasses_LecturerId` (LecturerId) `IX_ClassEnrollments_StudentId` (StudentId) `IX_Groups_Class_Status` (ClassId, Status) `IX_Groups_LeaderId` (LeaderId) `IX_GroupMembers_Group_Class` (GroupId, ClassId) `IX_AddMemberRequests_GroupId` (GroupId) `IX_AddMemberRequests_ProcessedAtUtc` (ProcessedAtUtc) `IX_OutboxEvents_Unpublished` (OccurredAtUtc) WHERE PublishedAtUtc IS NULL `IX_OutboxEvents_PublishedAtUtc` (PublishedAtUtc) WHERE PublishedAtUtc IS NOT NULL `IX_JoinRequests_Student_Class_Status` (StudentId, ClassId, Status) `IX_JoinRequests_Group_Status` (GroupId, Status) `IX_JoinRequests_Processing` (DecidedAt) WHERE Status = 'Processing' `IX_ProcessedEvents_ProcessedAtUtc` (ProcessedAtUtc)	Paging and filtering, dashboard queries, jobs and cleanup

9.4. Cross-Service Logical References

Table 36. Logical references between databases

Reference	Target	How integrity is kept
`GroupDb.ExeClasses.LecturerId`	IdentityDb.Users	The Administrator picks a user with the Lecturer role when creating or updating the class.
`GroupDb.ClassEnrollments.StudentId`	IdentityDb.Users	The Administrator enrolls existing Student accounts chosen from GET /api/users?role=Student; code, name and e-mail are stored as snapshots and refreshed when the roster is imported again.
`GroupDb.Groups.LeaderId`	IdentityDb.Users	A member of the group while it is not Dissolved (checked in Group Service).
`GroupDb.GroupMembers.StudentId`	IdentityDb.Users	The FK to ClassEnrollments guarantees the student is enrolled in the class.
`GroupDb.AddMemberRequests.StudentId`	IdentityDb.Users	Copied from the AddMemberIfEligible request.
`GroupDb.AddMemberRequests.RequestId`	RequestDb.JoinRequests.RequestId	The request_id of AddMemberIfEligible, sent only by Join Request Service (approve, ProcessingReconciler); used as the idempotency key, never looked up.
`RequestDb.JoinRequests.GroupId / ClassId`	GroupDb.Groups / ExeClasses	Validated through gRPC GetGroupContext when the request is submitted; StudentCode, StudentName and GroupTitle are snapshots from the same call.
`RequestDb.JoinRequests.StudentId / DecidedBy`	IdentityDb.Users	Taken from the validated JWT (sub claim) of the caller.
`RequestDb.ProcessedEvents.EventId`	GroupDb.OutboxEvents.EventId	Carried in the Redis Streams message envelope; used for de-duplication.

9.5. Migrations & Reference DDL

- Each service keeps its own DbContext and migrations (`dotnet ef migrations add InitialCreate`), applied at start-up in Development.
- EF Core mapping of the key constraints: `HasAlternateKey(g => new { g.GroupId, g.ClassId })` with `HasForeignKey(...).HasPrincipalKey(...)` for the composite FKs, `IsRowVersion()`, `HasIndex(...).IsUnique().HasFilter(...)`, `ToTable(t => t.HasCheckConstraint(...))` and `OnDelete(DeleteBehavior.NoAction)`.

- The reference DDL (`database/schema.sql`) mirrors the same model. It was executed on SQL Server 2019 (LocalDB) and passed 34 tests (constraints, concurrency and key queries) – for example a second group in the same class, a non-enrolled member, a member whose class differs from the group's class, a second active request, a repeated request_id, invalid status or reason codes, and an update with a stale RowVersion were all rejected, while the dissolve flow and the ungrouped-students query behaved as designed.

Appendix A. gRPC Contract – group_membership.proto

```
syntax = "proto3";

package exegroup.v1;

import "google/protobuf/timestamp.proto";

option csharp_namespace = "ExeGroup.Contracts.Grpc";

// Served by Group Service on http://group-service:8081 (HTTP/2 only, internal network);
// called by Join Request Service. All ids are GUID strings.
service GroupMembership {
  // Read-only snapshot: eligibility and display data on submit,
  // leadership check on list, approve and reject.
  rpc GetGroupContext (GetGroupContextRequest) returns (GetGroupContextReply);

  // Idempotent by request_id. Order of checks:
  // (1) request_id already processed, or student already in this group -> ALREADY_ADDED;
  // (2) student already in another group of the class -> ALREADY_IN_OTHER_GROUP;
  // (3) group, leader, enrollment, deadline, status and capacity rules;
  // (4) insert GroupMembers, AddMemberRequests and OutboxEvents in one transaction.
  rpc AddMemberIfEligible (AddMemberIfEligibleRequest) returns (AddMemberIfEligibleReply);
}

enum GroupStatus {
  GROUP_STATUS_UNSPECIFIED = 0;
  GROUP_STATUS_RECRUITING = 1;
  GROUP_STATUS_FULL = 2;
  GROUP_STATUS_LOCKED = 3;
  GROUP_STATUS_DISSOLVED = 4;
}

message GetGroupContextRequest {
  string group_id = 1;
  string student_id = 2;  // optional: empty when only the leader is checked
}

message GetGroupContextReply {
  bool exists = 1;
  string class_id = 2;
  string leader_id = 3;
  GroupStatus group_status = 4;
  google.protobuf.Timestamp deadline_utc = 5;
  int32 current_member_count = 6;
  int32 max_members = 7;
  string group_title = 8;
  // Fields 9-12 describe student_id; they are empty when student_id is empty.
  bool student_enrolled = 9;
  bool student_has_group_in_class = 10;
  string student_code = 11;       // snapshot from ClassEnrollments
  string student_full_name = 12;  // snapshot from ClassEnrollments
}

message AddMemberIfEligibleRequest {
  string request_id = 1;   // join request id = idempotency key
  string group_id = 2;
  string student_id = 3;
  string approver_id = 4;  // sub of the Team Leader, validated by Join Request Service
```

```
}

enum AddMemberResult {
  ADD_MEMBER_RESULT_UNSPECIFIED = 0;
  ADD_MEMBER_RESULT_ADDED = 1;
  ADD_MEMBER_RESULT_ALREADY_ADDED = 2;
  ADD_MEMBER_RESULT_GROUP_FULL = 3;
  ADD_MEMBER_RESULT_GROUP_LOCKED = 4;
  ADD_MEMBER_RESULT_GROUP_DISSOLVED = 5;
  ADD_MEMBER_RESULT_DEADLINE_PASSED = 6;
  ADD_MEMBER_RESULT_ALREADY_IN_OTHER_GROUP = 7;
  ADD_MEMBER_RESULT_NOT_ENROLLED = 8;
  ADD_MEMBER_RESULT_NOT_LEADER = 9;
  ADD_MEMBER_RESULT_GROUP_NOT_FOUND = 10;
}

message AddMemberIfEligibleReply {
  AddMemberResult result = 1;
  string membership_id = 2;  // set for ADDED and ALREADY_ADDED
  int32 current_member_count = 3;
}
```

Appendix B. Glossary

Table 37. Glossary

Term	Meaning
C4 model	Notation for software architecture diagrams at four zoom levels; this document uses Level 1 (System Context) and Level 2 (Container).
Container (C4)	A separately deployable or runnable unit – an application, a database or a message stream.
CRUD	Create, read, update, delete.
DDL	Data Definition Language – the SQL script that creates tables, keys and indexes.
EXE	Experiential Entrepreneurship courses (EXE101, EXE201) in which students build a startup project in groups.
gRPC / h2c	High-performance RPC over HTTP/2 with Protocol Buffers; h2c = HTTP/2 without TLS, used inside Docker.
JWT	JSON Web Token – signed access token carrying the user id (sub) and roles.
Key prefixes	PK primary key, FK foreign key, AK alternate key, UX unique index, IX non-unique index, CK check constraint.
LMS	Learning Management System of the university (out of scope).
LR (logical reference)	A column that refers to a row in another service's database without a foreign key.
MoSCoW	Prioritization scheme used in section 5.1: Must have, Should have (Could / Won't are not used).
MVP	Minimum Viable Product – the scope delivered in this assignment.
Outbox / idempotent consumer	Patterns that publish events reliably (written in the same transaction as the data) and apply each event only once (ProcessedEvents).
Redis Streams	Persistent append-only log in Redis with consumer groups and acknowledgements.
SPA	Single-Page Application – here the React “Single-Page App” container.
SSO	Single sign-on with the university identity provider (out of scope).
UTC	Coordinated Universal Time; all timestamps and deadlines are stored in UTC.
YARP	Yet Another Reverse Proxy – Microsoft's .NET library used to build the API Gateway.