

## Lab 1:

```
1 create role cashier_role;
```

Data Output Messages Notifications

CREATE ROLE

Query returned successfully in 36 msec.

```
1 create user mike with password 'mike123';  
2 create user jon with password 'jon123';
```

Data Output Messages Notifications

CREATE ROLE

Query returned successfully in 65 msec.

```
1 grant cashier_role to mike;>>  
2 grant cashier_role to jon;
```

Data Output Messages Notifications

GRANT ROLE

Query returned successfully in 29 msec.

```
1 grant select on film, staff to cashier_role;  
2 grant select, insert on payment to cashier_role;
```

Data Output Messages Notifications

GRANT

Query returned successfully in 34 msec.

## Lab 2:

```
1 alter table payment enable row level security;
```

Data Output Messages Notifications

ALTER TABLE

Query returned successfully in 21 msec.

```
1 create policy isolate_cashier_payments on payment
2 for select to cashier_role
3 using (
4 staff_id = (select staff_id from staff s
5 where lower(s.username) = current_user)
6 )
```

Data Output Messages Notifications

CREATE POLICY

Query returned successfully in 41 msec.

```
1 set role mike;
2 select count(*) from payment
```

Data Output Messages Notifications

Showing rows: 1 to 1 Page No: 1 of 1

|   | count<br>bigint |
|---|-----------------|
| 1 | 7293            |

```
1 set role jon;
2 select count(*) from payment
```

Data Output Messages Notifications

Showing rows: 1 to 1 Page No: 1 of 1

|   | count<br>bigint |
|---|-----------------|
| 1 | 7304            |