



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Chapter 3

Convex Optimization in Machine Learning

Mathematical Modeling

Le Hong Trang

*Faculty of Computer Science and Engineering
HCMC University of Technology*



① Least Squares Model

Regression analysis and data fitting
Trend analysis

② Support Vector Machines

Hard margin
Soft margin
Kernels

③ Image Restoration

④ How about Deep Networks? – Nonlinear Optimization!

Contents

Least Squares Model

Regression analysis and
data fitting
Trend analysis

Support Vector Machines

Hard margin
Soft margin
Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

① Least Squares Model

Regression analysis and data fitting
Trend analysis

② Support Vector Machines

Hard margin
Soft margin
Kernels

③ Image Restoration

④ How about Deep Networks? – Nonlinear Optimization!





Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

$$\min \|Ax - b\|_2^2 = \sum_{i=1}^k (a_i^T x - b_i)^2,$$

where $A \in \mathbb{R}^{k \times n}$ ($k \geq n$), $b \in \mathbb{R}^k$, a_i^T are rows of A , and $x \in \mathbb{R}^n$.

Solving least-squares problems

- Analytical solution: $x^* = (A^T A)^{-1} A^T b$.
- Reliable and efficient algorithms and software.
- Computation time proportional to $n^2 k$.
- A mature technology.

- Basis for regression analysis, optimal control, and many parameter estimation and data fitting methods.
- Easy to recognize.
- A few standard techniques increase flexibility
 - *Including weights*

$$\min \sum_{i=1}^k w_i (a_i^T x - b_i)^2.$$

- *Adding regularization terms*

$$\min \sum_{i=1}^k (a_i^T x - b_i)^2 + \rho \sum_{j=1}^n x_j^2.$$





Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

General statement

In a fitting problem, we are given data

$$(u_1, y_1), (u_2, y_2), \dots, (u_m, y_m)$$

with $u_i \in D$ and $y_i \in \mathbb{R}$, and seek a function $f \in \mathcal{F}$ that matches this data as closely as possible. For example in least-squares fitting we consider the problem

$$\min \sum_{j=1}^m (f(u_i) - y_i)^2,$$

which is a simple least-squares problem in the variable x .

We can add a variety of constraints

- inequalities that must be satisfied by f at various points,
- constraints on the derivatives of f ,
- monotonicity constraints,
- or moment constraints.



Polynomial fitting

Given data $u_1, u_1, \dots, u_m \in \mathbb{R}$ and $v_1, v_2, \dots, v_m \in \mathbb{R}$, we need to approximately fit a polynomial of the form

$$p(u) = x_1 + x_2 u + x_3 u^2 \dots + x_n u^{n-1}$$

to the data.

For each x we form the vector of errors,

$$e = (p(u_1) - v_1, p(u_2) - v_2, \dots, p(u_m) - v_m).$$

To find the polynomial that minimizes the norm of the error, we solve the norm approximation problem

$$\min \|e\| = \|Ax - v\|,$$

where $x \in \mathbb{R}^n$, $A_{ij} = u_i^{j-1}$, for $i = 1, 2, \dots, m$ and $j = 1, 2, \dots, n$

[Contents](#)

[Least Squares Model](#)

[Regression analysis and data fitting](#)

[Trend analysis](#)

[Support Vector Machines](#)

[Hard margin](#)


[Soft margin](#)

[Kernels](#)

[Image Restoration](#)

[How about Deep Networks? – Nonlinear Optimization!](#)

Polynomial fitting



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

- The problem of estimating underlying trends in time series data arises in a variety of disciplines.
- The l_1 trend filtering method produces trend estimates x that are piecewise linear from the time series y .

Optimization form

Given a time series data y , estimate x by solving

$$\min \frac{1}{2} \|y - x\|^2 + \lambda \|Dx\|_1,$$

where D is the second difference matrix, with rows $[0 \dots -1 \ 2 \ -1 \dots 0]$, $\lambda > 0$ is the regularization parameter.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin
Soft margin
Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Trend filter: time series analysis



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines


Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



Outline

① Least Squares Model

Regression analysis and data fitting
Trend analysis

② Support Vector Machines

Hard margin
Soft margin
Kernels

③ Image Restoration

④ How about Deep Networks? – Nonlinear Optimization!



Contents

Least Squares Model

Regression analysis and
data fitting
Trend analysis

Support Vector Machines

Hard margin
Soft margin
Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



A statement

A classification problem has two types of variables,

- $x_i \in \mathbb{R}^d$: the vector of observations (features) in the world,
- $y_i \in \mathbb{R}^d$: state (class) vector of the world.

The set of all samples in this world (or dataset) constructs the observation set $X \in \mathcal{R}^{n \times d}$ and state set $Y \in \mathbb{R}^{n \times d}$. The task of machine learning algorithm for classification is to find a mapping $X \rightarrow Y$ that achieves smallest number of misclassification.

Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

- *Propose a parametric family of decision boundaries, then pick the element in this family that produces the best classifier.*
- Take our decision boundary between two classes as a hyperplane, such that $w^T x + b = 0$,
 - w being the normal to the plane and b being the *bias term*.
- The decision function can be expressed as

$$f^*(x) = \begin{cases} 0, & \text{if } w^T x + b > 0, \\ 1, & \text{if } w^T x + b < 0. \end{cases}$$

The decision boundary

- Normal vector: w ; distance to origin: $d = b / \|w\|$.
- distance to a data point x_i : $|w^T x_i + b| / \|w\|$.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines


Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



The decision function

- Use labels $y \in \{-1, 1\}$ instead of $y \in \{0, 1\}$

$$f^*(x) = \begin{cases} -1, & \text{if } w^T x + b > 0, \\ 1, & \text{if } w^T x + b < 0, \end{cases}$$

then $f^*(x) = \text{sign}(w^T x + b)$.

A simple necessary and sufficient condition for a given training set $D = (x_1, y_1), (x_2, y_2), \dots, (x_n, y_n)$, is *linearly separable*, i.e.,

$$y_i(w^T x_i + b) > 0, \text{ for } i = 1, 2, \dots, n. \quad (1)$$



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



Question arising when dealing with nonlinear problems

- Trying to fit a nonlinear model? – not easy!
 - Idea: keep using the linear model
 - Map the problem a new (higher-dimensional) space (*called the feature space*) by doing a nonlinear transformation using suitably chosen basis functions;
 - Apply a linear model in *the feature space*.
 - Learning a linear boundary in a higher dimensional space will be equivalent to learning a nonlinear boundary in the current space.
- Known as the **kernel trick**.

Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

- If we introduce a mapping $\phi : X \rightarrow Z$ such that $\dim(Z) > \dim(X)$, we can achieve linear separability for some $k = \dim(Z)$.
- Instead of applying this mapping to each data point as $\phi(x)$, we can leverage the dot-product form

$$y_i \left(\sum_{j=1}^n \alpha_j y_j x_j^T x_i + b \right) \quad (2)$$

$$y_i \left(\sum_{j=1}^n \alpha_j y_j \phi(x_j)^T \phi(x_i) + b \right). \quad (3)$$

Then we apply the kernel trick, $K(x, z) = \phi(x)^T \phi(z)$.

- Some formulas for $K(x, z)$
 - ① $K(x, z) = x^T z$, linear kernel.
 - ② $K(x, z) = e^{-\frac{\|x-z\|^2}{\delta}}$, Gaussian kernel.
 - ③ $K(x, z) = (1 + x^T z)^k$, polynomial kernel.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Support Vector Machines (SVM)

- SVMs go one step further from the necessary and sufficient condition given by (1) and works on the *margin* defined by the distance from the boundary to the closest point,

$$\gamma = \min_i \frac{|w^T x_i + b|}{\|w\|}.$$

- Maximizing γ is ill-defined, since γ does not change if both w and b are scaled by a factor λ . We then need some sort of normalization,
 - this can be done by arbitrarily selecting some normalization on w , e.g. $\|w\| = 1$
- The SVM algorithm works with a more convenient normalization and makes $|w^T x + b| = 1$ for the closest point, i.e. $\min_i |w^T x_i + b|$ under $\gamma = \frac{1}{\|w\|}$.

SVM model

$$\begin{aligned} \min_{w,b} \quad & \frac{1}{2} \|w\|^2 \\ \text{s.t.} \quad & y_i(w^T x_i + b) \geq 1, \forall i. \end{aligned}$$



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels


Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

SVM – hard margin

$$\min_{w,b} \quad \frac{1}{2} \|w\|^2$$

$$\text{s.t.} \quad y_i(w^T x_i + b) \geq 1, \forall i.$$



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels


Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

SVM – soft margin

$$\min_{w,b,\xi} \quad \frac{1}{2} \|w\|^2$$

$$\text{s.t.} \quad y_i(w^T x_i + b) \geq 1 - \xi_i, \forall i, \\ \xi_i \geq 0, \forall i.$$



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin


Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

SVM – nonlinear classification with kernels

Using Gaussian kernel: $K(x, z) = e^{-\frac{\|x - z\|^2}{\delta}}$.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Outline

① Least Squares Model

Regression analysis and data fitting
Trend analysis

② Support Vector Machines

Hard margin
Soft margin
Kernels

③ Image Restoration

④ How about Deep Networks? – Nonlinear Optimization!



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



- original



- optical blur



- motion blur



- spatial quantization (discrete pixels)



- additive intensity noise



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

- A general noisy (including noise, blur, inpainting) image \mathbf{y} , of an original image \mathbf{x} , can be modeled

$$\mathbf{y} = \mathbf{B}\mathbf{x} + \mathbf{n},$$

where

- \mathbf{B} : a direct operator represented under matrix form,
- \mathbf{n} : noise.
- As common, images are adopted by vector notation
 - The pixels on an $M \times N$ image are stored as an (NM) -vector.
 - If the number of elements of \mathbf{x} is n then $\mathbf{x} \in \mathbb{R}^n$, while $\mathbf{y} \in \mathbb{R}^m$ (m and n can be different).

Remark

The problem of estimating \mathbf{x} from \mathbf{y} is *ill-posed*. This inverse problem can then be solved by adopting a some sort of regularization.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Unconstrained formulation

$$\hat{\mathbf{x}} = \arg \min_{\mathbf{x}} \frac{1}{2} \|\mathbf{B}\mathbf{x} - \mathbf{y}\|_2^2 + \tau \phi(\mathbf{x}),$$

where

- $\phi : \mathbb{R}^n \rightarrow \bar{\mathbb{R}}$ is the regularizer.
- τ is the regularization parameter.

Lagrangian (constrained form)

$$\begin{aligned} \min_{\mathbf{x}} \quad & \phi(\mathbf{x}) \\ \text{s.t.} \quad & \|\mathbf{B}\mathbf{x} - \mathbf{y}\| \leq \epsilon. \end{aligned}$$

Regularization functions

- $\phi(\mathbf{x}) = \|\mathbf{x}\|_1 = \sum_{i=1} |x_i|$: basis pursuit denoising (BPD).
- $\phi(\mathbf{x}) = \varphi(\mathbf{D}\mathbf{x})$: **total-variational** regularization.



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Image restoration: inpainting and noise by unconstrained model



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Original



Missing Samples - 40%



Restored Image






Image restoration: blurred by unconstrained model



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!

Image restoration: blurred and noise by constrained model



Contents

Least Squares Model

Regression analysis and
data fitting

Trend analysis

Support Vector Machines

Hard margin

Soft margin

Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!



Original



Blurred and noisy



Constrained model result



① Least Squares Model

Regression analysis and data fitting
Trend analysis

② Support Vector Machines

Hard margin
Soft margin
Kernels

③ Image Restoration

④ How about Deep Networks? – Nonlinear Optimization!



Contents

Least Squares Model

Regression analysis and
data fitting
Trend analysis

Support Vector Machines

Hard margin
Soft margin
Kernels

Image Restoration

How about Deep
Networks? – Nonlinear
Optimization!