Reproducible Target-Informed Gaussian-Process Optimization for Data-Efficient Electromagnetic Design

Le Dong
School of Electrical Engineering
Xi'an Jiaotong University
Xi'an, Shaanxi 710049, China
leroi_2024@stu.xjtu.edu.cn

***Abstract*—Electromagnetic component design often requires a target response within a strict tolerance band while minimizing a secondary objective under a limited computational budget. This work establishes a deterministic, target-informed Gaussian-process (GP) optimization workflow that combines center-point initialization, uncertainty-weighted feasibility search, fixed low-discrepancy starts for GP hyperparameter fitting, a dimension-dependent minimum sample threshold, a relative constrained-expected-improvement (cEI) stopping criterion, and a final verification batch. After its settings are fixed on 14 development targets, the workflow identifies the global optimum at all 73 held-out targets of a 1,110-design coil benchmark, requiring 21.81 model evaluations per target on average. Six-point random initialization with the same fitting and stopping criteria recovers 856/870 seed–target optima, whereas the center-initialized trajectories are deterministic. On a 21-target, eight-dimensional wireless-power-transfer (WPT) benchmark, both the proposed workflow and budget-matched conventional cEI find feasible designs for all 21 targets, compared with 10/21 for Sobol search. Adaptive stopping reduces evaluations by 30.3% with a 3.79% increase in mean DC resistance. In a 3-D Ansys Maxwell comparison at 1000 nH, both methods satisfy the constraint using 30 evaluations; the proposed workflow obtains $0.38368\ \Omega$ AC resistance, compared with $0.38954\ \Omega$ for the baseline.**

***Index Terms*—Bayesian optimization, constrained expected improvement, electromagnetic design, Gaussian process, wireless power transfer.**

I. Introduction

Electromagnetic design frequently asks for a configuration whose required response lies in a narrow band while another response is optimized. If a forward model returns constrained response $g(x)$ and scalar objective $J(x)$, the task is

$$\min_{x\in\mathcal{X}} J(x) \quad \text{s.t.} \quad |g(x)-g_t|/|g_t| \le \epsilon. \tag{1}$$

The objective can be resistance or a scalarized combination of loss, mass, temperature, material use, and efficiency. A low evaluation count is valuable when each observation requires simulation or measurement, but it also makes initialization, stochastic GP fitting, and stopping materially affect the returned design.

Gaussian-process Bayesian optimization (BO) is established in electromagnetic design. Online GP-assisted evolutionary search has been applied to antennas [3], machine-learning-assisted antenna optimization has combined learned representations and GPs [4], and BO has been used for WPT coil design [5]. Constrained expected improvement (cEI) is likewise established [2]. Existing studies commonly report performance under fixed budgets, but initialization, GP-fit reproducibility, adaptive stopping, and final verification are rarely evaluated together under an explicit function-evaluation budget. We study how these choices affect a target-conditioned optimizer when only a small number of model evaluations is available.

This question connects three issues that are often reported separately. Initial-design size and placement can materially affect small-budget BO [7]; random restarts in GP hyperparameter fitting can make identical data yield different numerical trajectories; and a fixed budget gives no task-dependent indication of when another model evaluation has little posterior value. Formal BO stopping criteria have been derived from posterior simple-regret reduction [8]. Here, a simpler engineering threshold is fixed on development targets and tested against exhaustive optima on held-out targets.

The contributions are: 1) matched surrogate and acquisition studies for the coil benchmark; 2) a reproducible workflow that combines deterministic feasibility discovery and GP fitting with $B = N_0 + N_{\text{seq}} + N_{\text{ver}}$ budget allocation and adaptive stopping; and 3) validation with 73 held-out exhaustive targets, 21 numerical WPT targets, and a matched-budget Maxwell case. The scope is observation-efficient and reproducible optimization on these electromagnetic models; no new acquisition function or general convergence result is claimed.

II. Models and Optimization Method

A. Two-Dimensional Coil Model

The first benchmark describes a multilayer air-core coil by radial layers $T \in \{1,\dots,10\}$ and turns per layer $n \in \{20,\dots,130\}$. With wire diameter $d = 0.68$ mm, pitch $p = 1.05d$, inner diameter $D_0 = 80$ mm, mean diameter $D = D_0 + Tp$, height $H = np$, radial thickness $C = Tp$, total

turns $N = Tn$, and resistivity $\rho = 1.851 \times 10^{-5}\ \Omega\cdot\text{mm}$, the analytical model is

$$L = \frac{0.08N^2D^2\,10^{-4}}{3D + 9H + 10C}\ \text{mH}, \qquad R = \frac{4\rho N D}{d^2}. \tag{2}$$

The domain contains 1,110 integer designs. A design is feasible when $|L - L_t|/L_t \le 0.025$, and the objective is the smallest feasible R. Enumeration supplies an independent reference optimum for each target $L_t = 1, \ldots, 87$ mH. For a feasible returned design, bounded loss is $u = r/(1 + r)$, where $r = R/R_{\text{exhaustive}} - 1$; infeasible returns have $u = 1$.

B. Reusable-Surrogate Screening

Before target-specific optimization, we compare reusable dual-response GPs and ten-member neural ensembles under the same $B = 15 + 12 = 27$ protocol: 15 globally reusable model-building observations and 12 target-specific validations. The random policies use 15 seeded uniform observations. Active policies begin with six of the same observations and acquire nine more using equally weighted, scale-normalized uncertainty in L and R. Every model family then uses the same validation score and decision pool.

Fig. 1 shows that active selection improves both families, with the GP giving the stronger result under this budget. Random GP sampling finds feasible designs in 99.66% of 870 cases and reaches 658 exact optima; active GP sampling finds feasible designs in every case, reaches 759 exact optima, and reduces all-case mean bounded loss from 0.0111 to 0.00218, an 80.3% reduction. For the tested 16–8 ReLU ensemble, active sampling raises exact recovery from 351 to 586 but leaves mean loss at 0.188. The target-conditioned experiments therefore use GP surrogates.




Fig. 1. Matched reusable-surrogate screen at nominal per-target $B = 27$. Both model families use 15 shared model-building observations and the same 12 target-specific validations. Lower bounded loss is better.

C. Direct-Search Reference

We also compare the selected reusable GP with simulated annealing (SA), which searches the integer domain directly using cached evaluations and stops after five cycles without a 1% feasible-objective improvement [9]. Both methods use the same $\pm 2.5\%$ feasibility rule and the same ten seeds. Fig. 2 shows trimmed mean bounded loss of 0.00139 for the GP and 0.0451 for SA, at 27 nominal evaluations versus 92.1. Moreover, the GP's 15 model-building observations are reused across all targets, whereas SA starts a separate search for every target. This result motivates the subsequent target-informed GP study.




Fig. 2. Reusable active GP versus direct SA. The upper panel reports targetwise-trimmed bounded loss and the lower panel reports forward-model evaluations.

D. Target-Conditioned Acquisition

Independent GPs model L and R with radial-basis-function kernels and white-noise terms [1]. For target L_t, the inductance GP gives

$$p_F(x) = \Phi\left(\frac{L_t(1+\epsilon) - \mu_L}{\sigma_L}\right) - \Phi\left(\frac{L_t(1-\epsilon) - \mu_L}{\sigma_L}\right). \tag{3}$$

After a feasible observation exists, cEI maximizes $a_{\text{cEI}}(x) = p_F(x)\text{EI}_R(x)$. A matched $6 + 9 + 12 = 27$ comparison over ten seeds and 87 targets obtains 860/870 exhaustive optima with cEI, versus 789 for constrained lower confidence bound and 836 for integrated variance reduction. Reallocating verification evaluations to sequential learning reaches 870/870 at $6 + 14 + 4 = 24$. These results motivate cEI and explicit budget allocation; full model-family and acquisition ablations are retained in the reproducibility package.

E. Deterministic Feasibility Discovery and Fitting

Before a feasible incumbent exists, maximizing p_F alone can make a one-observation GP locally confident in the wrong

region. We first observe the normalized domain center and then maximize

$$a_F(x) = 0.75\ \mathrm{norm}(p_F(x)) + 0.25\ \mathrm{norm}(\sigma_L(x)), \quad (4)$$

where $\mathrm{norm}(\cdot)$ denotes candidate-wise min–max scaling. Once feasibility is found, selection switches to ordinary cEI. Kernel hyperparameters remain at their initial values for the first three observations. Thereafter, marginal likelihood is optimized from the initial point and four fixed Halton points in the bounded log-hyperparameter domain, and the best of these $K = 5$ L-BFGS-B solutions is retained. Identical observations therefore yield identical fitted GPs.

Let R_k^* be the best feasible resistance after refit k. We monitor maximum relative cEI

$$\rho_k = \max_{x \in \mathcal{C}_k} \frac{p_F(x)\mathrm{EI}_R(x)}{R_k^*}. \quad (5)$$

The adaptive phase can stop only after at least $N_{\min} = 2d + 1$ model-building observations and after $\rho_k \leq 0.01$ for three consecutive refits. It then evaluates ten verification candidates ranked by $p_F \exp[-\mathrm{norm}(\mu_R)]$; the returned design is the lowest-resistance feasible observation. The 1% threshold is a termination measure based on posterior expected improvement over the searched candidates.

Each target follows five steps: (1) evaluate the domain center; (2) use (4) until a feasible observation is obtained; (3) refit both GPs from the fixed $K = 5$ hyperparameter starts and acquire by cEI; (4) apply the minimum sample threshold and require three consecutive stopping-threshold hits; and (5) evaluate the final verification batch and return the best observed feasible design. Computational cost is measured by forward-model evaluations, with initialization, adaptive sampling, and verification reported separately.

III. Experimental Protocol

The 2-D targets are the 87 integers from 1 to 87 mH. Stochastic comparisons use ten fixed seeds, producing 870 target–seed cases. Every baseline receives the same model-evaluation budget and decision pool within its comparison. The initial acquisition study uses six initial observations, nine sequential observations, and 12 final validations. The allocation study fixes six initial observations and moves evaluations between sequential learning and verification. All losses and exact-recovery counts are recomputed against enumeration.

The feasibility weight is screened at ten targets spanning the domain. A separate 2–5 mH diagnostic examines the misses observed for random-six cEI. Stopping is developed on the union of these sets, giving 14 distinct targets. After fixing the 75/25 score, $K = 5$, $\delta = 1\%$, patience three, and ten verification evaluations, the remaining 73 targets are held out as a single final test. Replaying seed labels for the deterministic workflow verifies that the implementation is invariant to the unused seed input.

The numerical WPT study uses every 50-nH target from 1000 through 2000 nH. It compares the frozen workflow with six-Sobol-point conventional cEI, a center-start p_F-then-cEI control, Sobol search, and forced continuation. Conventional cEI receives the automatic run's realized targetwise budget. A separate 1000-nH Maxwell 3-D eddy-current test gives both policies 20 model-building and ten verification evaluations; the solver returns mutual inductance and the sum of the impedance matrix's Tx/Rx AC self-resistances at 85 kHz.

TABLE I
Summary of the 2-D evidence. Development and held-out rows have different denominators and are not pooled.

Configuration	Cases	Exact	Mean evaluations
cEI, fixed $6 + 9 + 12$	870	860	27.00
cEI, reallocated $6 + 14 + 4$	870	870	24.00
Automatic, development	14	14	22.571
Automatic, held out	73	73	21.808
Random-six + same stopping	870	856	22.570
Deterministic center (unique)	87	87	21.932

Raw records, hyperparameters, candidate histories, rendering scripts, and reproducibility checks accompany the manuscript. They verify budgets, losses, recovery totals, stopping histories, deterministic replay, and numerical and Maxwell WPT decisions. Each optimizer accesses the analytical equations through the same forward-model interface.

IV. Two-Dimensional Validation

The feasibility weight, threshold, patience, and K are selected on 14 development targets. All settings are then frozen and one deterministic trajectory is run at each of the remaining 73 targets. Every held-out run finds a feasible design and recovers the exhaustive optimum; all stop naturally. Mean total cost is 21.81 evaluations, median 22, and range 19–25. Model-building counts are 9–15, so the $2d + 1 = 5$ minimum sample threshold is inactive for these trajectories; it protects against termination with insufficient data in higher-dimensional cases.

To separate deterministic fitting from starting-policy sensitivity, random-six initialization is also given the same 75/25 pre-feasibility score, fixed $K = 5$ fitting, 1% stopping rule, ten verification evaluations, and 27-evaluation ceiling. Across 870 seed–target cases it obtains 856 exact optima and seed-dependent decisions at eight targets. Pairing each random case with the deterministic result for the same target gives 14 deterministic wins, 856 ties, and no losses; mean costs are 22.57 and 21.93 evaluations.

At stopping, feasible-region posterior coverage on the 73 held-out tasks is 80.8%/96.5% at $1\sigma/2\sigma$ for L and 82.1%/96.3% for R, whereas global coverage is substantially poorer. The pre-verification incumbent is already optimal in all 73 cases, so the final batch acts as a conservative verification allocation in this experiment.

Table I separates the relevant comparisons. At $B = 27$, cEI is the strongest tested target-conditioned acquisition. Budget reallocation shows that additional sequential learning improves exact recovery. The final comparison gives random and deterministic starts identical fitting and stopping criteria; the deterministic policy removes the remaining seed dependence.




Fig. 3. Matched target-conditioned acquisition comparison at $B = 27$ over ten seeds and 87 targets. Lower bounded loss is better.

V. Application to Eight-Dimensional WPT Coil Design

A. Controlled Black-Box Benchmark

The source WPT model has eight intrinsic geometry variables and six pose variables [6]. We optimize the eight geometry variables: polygon side count $n_s \in [4, 10]$, turn count $n_t \in [5, 15]$, spacing $s \in [1, 3]$ mm, and inner radius $r_i \in [30, 80]$ mm for each transmitter and receiver. The counts are integral; s and r_i are continuous. Translation is fixed at $(0, 0, 70)$ mm and rotations are zero.

The constraint is $|M(x) - M_t|/M_t \leq 0.025$. Total DC resistance is computed from polygonal conductor centerline length,

$$R = \frac{\rho_{\mathrm{Cu}}}{A} \sum_{q \in \{t,r\}} \sum_{k=0}^{n_{t,q}-1} 2 n_{s,q} r_{q,k} \sin(\pi / n_{s,q}), \qquad (6)$$

where $r_{q,k} = r_{i,q} + k(s_q + w)$, $w = 0.68$ mm, $A = \pi(w/2)^2$, and $\rho_{\mathrm{Cu}} = 1.851 \times 10^{-5}$ $\Omega\cdot$mm. Leads are excluded. Mutual inductance is computed using the partial-inductance model in [6].

Both responses are presented to the optimizer as black-box outputs and learned by separate GPs. This provides a controlled comparison under equal evaluation budgets; the subsequent Maxwell experiment tests direct operation with a field solver.

The normalized center is evaluated first. Consecutive blocks of one unscrambled Sobol sequence provide deterministic candidates. Isotropic Matérn-5/2 GPs use the same fixed $K = 5$ fitting, 75/25 feasibility rule, 1% stopping threshold, patience three, and ten verification evaluations. With $d = 8$, $N_{\min} = 17$; at most 40 model-building evaluations plus ten verification evaluations are allowed. No setting is retuned after the 2-D study.

TABLE II
Eight-dimensional WPT benchmark. B_s and R_s are the automatic stopping cost and resistance; R_{50} is its forced-50 continuation. Five representative targets precede the full aggregate. Dashes indicate that no feasible design was found at the matched budget.

M_t (nH)	B_s	R_s	R_{50} Resistance (mΩ)	Conv.	Sobol
1000	33	259.7	259.7	259.7	–
1250	34	291.5	280.3	340.4	–
1500	44	305.8	305.8	305.6	343.9
1750	27	332.5	324.9	332.5	–
2000	27	377.0	343.7	371.1	422.8
Mean (21)	34.86	315.0	303.5	315.5	–
Feasible	–	21/21	21/21	21/21	10/21

B. Results

Across the 21 targets, automatic and conventional cEI both find feasible designs in 21/21 cases, versus 10/21 for Sobol. Their mean resistances are 0.31500 and 0.31549 Ω; wins/ties/losses are 8/3/10, with paired Wilcoxon $p = 0.913$. Four trajectories stop at the $2d + 1 = 17$ minimum sample threshold.

Twenty runs stop naturally; 1150 nH reaches the 40-evaluation cap. Compared with forced $B = 50$, stopping uses 30.3% fewer evaluations with 3.79% higher mean resistance. At 1500 nH, $M = 1466.48$ nH and $R = 0.30577$ Ω, leaving a 3.98-nH margin above the lower feasibility bound.

C. Field-Solver Application Check

At 1000 nH, the frozen automatic workflow stops after 20 model-building evaluations and then performs ten fixed verification evaluations. A matched baseline uses six fixed Sobol points, 14 conventional-cEI evaluations, and ten verification evaluations. Both find feasible designs. The automatic run yields seven feasible observations, $M = 998.929$ nH, and $R_{\mathrm{AC,Tx}} + R_{\mathrm{AC,Rx}} = 0.383681$ Ω; the baseline yields three, 1016.402 nH, and 0.389535 Ω. The automatic objective is 1.50% lower, while the baseline reaches feasibility earlier (evaluation 6 versus 12). A common mesh-convergence study is required to resolve this small resistance difference.

In the numerical 1500-nH example, Tx/Rx use 9/7 sides, 7/7 turns, 1.741/2.709-mm spacing, and 61.724/61.007-mm inner radii. Feasibility occurs at model evaluation 12; stopping at 34 plus ten verification evaluations gives $B = 44$, and forced continuation returns the same design.

VI. Discussion and Conclusion

The experiments support a compact engineering procedure: begin at the domain center, combine predicted feasibility with constraint uncertainty until a feasible observation exists, fit each GP from fixed low-discrepancy hyperparameter starts, require at least $2d + 1$ observations, and terminate after persistently low relative cEI before evaluating a final verification batch. This removes implementation-level seed variation and performs consistently across the complete 2-D target lattice. On the WPT




Fig. 4. Automatic budgeting. (a) Mean total evaluations on the 14-target development screen; every configuration reaches the exhaustive optimum. (b) Model-building trace for the representative 1500-nH WPT case. (c) Maximum relative cEI after feasibility; three consecutive values below 1% trigger stopping, followed by ten verification evaluations.




Fig. 5. Selected nominal-pose 1500-nH design. The aligned transmitter and receiver planes are separated by 70 mm.

benchmark, its principal benefit is reliable feasibility with an adaptive evaluation budget.

The 75/25 feasibility score and stopping threshold are empirical settings established on the development set. The 2-D study uses an analytical model, the numerical WPT study fixes the relative pose, and the Maxwell comparison contains one trajectory per policy; experimental hardware validation and broader high-fidelity studies remain future work. Code, data, and validation scripts are available at https://github.com/le-dong-xjtu/reproducible-target-informed-gp.

References

[1] C. E. Rasmussen and C. K. I. Williams, *Gaussian Processes for Machine Learning*. MIT Press, 2006.

[2] J. Gardner, M. Kusner, Z. Xu, K. Weinberger, and J. Cunningham, "Bayesian optimization with inequality constraints," in *Proc. ICML*, vol. 32, 2014, pp. 937–945.

[3] B. Liu *et al.*, "An efficient method for antenna design optimization based on evolutionary computation and machine learning techniques," *IEEE Trans. Antennas Propag.*, vol. 62, no. 1, pp. 7–18, 2014.

[4] Q. Wu, W. Chen, C. Yu, H. Wang, and W. Hong, "Machine-learning-assisted optimization for antenna geometry design," *IEEE Trans. Antennas Propag.*, vol. 72, no. 3, pp. 2083–2095, 2024.

[5] B. Sim *et al.*, "Bayesian optimization based fast and accurate wireless power transfer system coil optimization for high efficiency," in *Proc. IEEE WPTCE*, 2023.

[6] M. Asadi and A. M. Abazari, "A data-driven model to predict mutual inductance between planar coils with arbitrary specifications and positions," *IET Electr. Power Appl.*, vol. 19, Art. no. e70015, 2025.

[7] S. Furuuchi and S. Yamada, "Verifying the effect of initial sample size in Bayesian optimization," *Total Quality Science*, vol. 10, no. 1, pp. 8–19, 2024.

[8] H. Ishibashi, M. Karasuyama, I. Takeuchi, and H. Hino, "A stopping criterion for Bayesian optimization by the gap of expected minimum simple regrets," in *Proc. AISTATS*, vol. 206, 2023, pp. 6463–6497.

[9] S. Kirkpatrick, C. D. Gelatt, Jr., and M. P. Vecchi, "Optimization by simulated annealing," *Science*, vol. 220, no. 4598, pp. 671–680, 1983.