BLEACHED HARDWOOD PULP (EUCALYPTUS KRAFT 89%)



General Information

Chemical Formula	(C6H ₁₀ O ₅) _n where n=600 - 1000	HO HO HI
Synonym	Cellulosic Pulp	# # # # # # # # # # # # # # # # # # #
Origin	Vietnam	
H.S. Code	4703.29.00	
CAS No.	65996-61-4	
Molecular Weight (g mol-1)	90,000 – 150,000	

Application

Paper Industry	It is used in producing smooth papers for printing and writing. It is used to produce paper products with more uniform formation.	
Packaging Industry	It is used for packaging and cardboard.	
Household Industry	It is used for tissue making.	

Specification

Property	Units	Value
Brightness	% ISO	89
Dirt Count	mm²/kg	1.5
Coarseness	mg/m	0.078
Fiber Length	mm	0.76
Drainability	⁰ SR	30
Tensile Index	N.m²/g	57.5-65.7
Tear Index	mN.m²/g	7.5-8.5
Burst Index	kPa.m²/g	3.1-3.9
Gurley Porosity	s/100 ml	3.5-6.0
Bulk	cm ³ /g	1.55-1.62
Opacity	%	73.0-75.0

Packaging

- Bale Unit Weight: 250 kg, Bale Unit Size: 800L x 640W x 500 H mm
- Package Weight: 2000 kg, Package Size: 1280L x 800W x 2000 H mm



Fax: +65 6225 6286
Email: contact@chemtradeasia.com

