

Running and Managing Pods



Kien Bui

DevOps & Platform Engineer

Course Overview



Using the Kubernetes API

Managing Objects with Labels, Annotations,
and Namespaces

Running and Managing Pods

Overview

Understanding Pods

Controllers and Pods

Multi-container Pods

Managing Pod Health with Probes


What Is a Pod?



Wrapper around
your container
based application



One or more
containers



Resources

What Is a Pod? (con't)



Unit of scheduling

Allocating work

A process that's running in your cluster

Unit of deployment

Your application configuration

Resources - Networking and storage

Why do we need Pods?

Provide higher level abstraction
over a container for manageability

How Pods Manage Containers



Single Container
Pods



Multi-Container
Pods



Init Containers

Single Container Pods



Most common deployment scenario

Generally a single process running in a container

Often leads to easier application scaling

Controllers and Pods



Controllers keep your apps in the desired state

Responsible for starting and stopping Pods

Application scaling

Application recovery

You don't want to run bare/naked Pods

They won't be recreated in the event of a failure

Static Pods



Managed by the Kubelet on Nodes

Static Pod manifests

`staticPodPath` in Kubelet's configuration


`/etc/kubernetes/manifests`

`/var/lib/kubelet/config.yaml`

`staticPodPath` is watched

Creates a 'mirror' Pod

Working with Pods -kubectl



```
kubectl exec -it POD1 --container CONTAINER1 -- /bin/bash
```

```
kubectl logs POD1 --container CONTAINER1
```

```
kubectl port-forward pod POD1 LOCALPORT:CONTAINERPORT
```

Demo

Running Pods

- Bare Pods
- Creating Pods in a Deployment
- Using port-forward to access a Pod's application
- Static Pods

Multi-container Pods



Tightly coupled applications

Scheduling processes together

Requirement on some shared resource

Usually something generating data while the other process consumes

Don't use this to influence scheduling, we use other techniques for that!

Multi-container Pods

```
apiVersion: v1
kind: Pod
metadata:
  name: multicontainer-pod
spec:
  containers:
  - name: nginx
    image: nginx
    ports:
      - containerPort: 80
    ...
  - name: alpine
    image: alpine
```


Common Anti-Pattern for Multi-container Pods




Recovery Options

Limits Scaling

Shares Resources Inside a Pod




Networking



Storage


Shared Resources Inside a Pod - Networking



Shared loopback interface, used for communication over localhost

Be mindful of application port conflicts

Shared Resources Inside a Pod - Storage



Each container image has its own file system
Volumes are defined at the Pod level Shared
containers in a Pod Mounted into the conta
Common way for containers to exchange da

Demo

Running Multi-container Pods

Sharing data between containers in a Pod

Init Containers



Runs before main application container

Contain utilities or setup for apps

Run to completion

Can have more than one per Pod


Each is run sequentially

All init containers must run to successful completion for the Pod to start


When an init container fails...

Container `restartPolicy` applies

When to Use InitContainers



Run Tools or
Utilities



Separation of
Duties



Block Container
Startup

Pod with InitContainers

```
apiVersion: v1
kind: Pod
...
spec:
  initContainers:
    - name: init-service
      image: ubuntu
      command: ['sh', '-c', "echo waiting for service; sleep 2"]
    - name: init-database
      image: ubuntu
      command: ['sh', '-c', "echo waiting for database; sleep 2"]
  containers:
    - name: app-container
      image: nginx
```

Demo

Working with initcontainers

Pod Lifecycle


Creation



Administratively


Controller

Running



Scheduled to a Node

Termination



Process is terminated/crashed

Pod is deleted

Evicted due to lack of resources

Node failure or maintenance

No Pod is redeployed

Stopping/Terminating Pods

Grace Period Timer
(30 sec default)

Pods changes to
Terminating

SIGTERM

Service Endpoints
and Controllers
updated

IF > Grace Period
SIGKILL

API and etcd are
updated

```
kubectl delete pod <name> --grace-period=<seconds>
```

Force Deletion - Immediately delete records in API and etcd

```
kubectl delete pod <name> --grace-period=0 --force
```



Pods

Pod Termination Grace Period

```
apiVersion: v1
kind: Pod
metadata:
  name: hello-world-pod
spec:
  terminationGracePeriodSeconds: 10
  containers:
  - name: hello-world
    image: gcr.io/google-samples/hello-app:1.0
    ports:
    - containerPort: 80
```

Persistency of Pods




A Pod is never redeployed

If a Pod stops, a new one is created based on its Controller

Go back to the original container image(s) in the Pod definition

Persistency of Pods



Configuration is managed externally

Pod Manifests, secrets and `ConfigMaps`

Passing environment variables into containers

Data Persistency is managed externally

`PersistentVolume`

`PersistentVolumeClaim`

Container Restart Policy



A container in a Pod can restart independent of the Pod

Applies to containers inside a Pod and defined inside the Pod's Spec

The Pod is the environment the container runs in

Not rescheduled to another Node, but restarted by the Kubelet on that Node

Restarts with an exponential backoff, 10s, 20s, 40s capped at 5m and reset to 0 after 10m of successful runtime

Container Restart Policy



`Always` (default) - will restart all
containers inside a Pod

`OnFailure` - Non-graceful termination

`Never`

```
metadata:
  name: nginx-pod
spec:
  containers:
  - name: nginx
    image: nginx
  restartPolicy: OnFailure
```

Pod with Container Restart Policy

```
kubectl apply -f nginx.yaml
```

Demo

Pod lifecycle

Killing a container process

Container Restart Policy

Defining Pod Health



A Pod is considered `Ready` when all containers are `Ready`

But we'd like to be able to understand a little more about our applications

We can add additional intelligence to our Pod's state and health

Container Probes

`livenessProbe`

`readinessProbe`

`startupProbe`

livenessProbes



Runs a diagnostic check on a container

Per container setting

On failure, the kubelet restarts the container

Container Restart Policy

Give Kubernetes a better understanding of

readinessProbes



Runs a diagnostic check on the container

Per container setting

Won't receive traffic from a Service until it succeeds

On failure, removes Pod from load balancing

Applications that temporarily can't respond to a request

Prevents users from seeing errors



startupProbes

Runs a diagnostic check on the container

Ensuring all containers in a Pod are `Ready`

Per container setting

On startup, all other probes are disabled until the `startupProbe` succeeds

On failure, the kubelet restarts the container according to the container restart policy

Applications have long `startuptimes`

Compliments liveness and readiness probes

Types of Diagnostic Checks for Probes

Exec

tcpSocket

httpGet

Process exit code

Successfully Open
a Port

Return Code
200 => and < 400

Success

Failure

Unknown

Configuring Container Probes



`initialDelaySeconds` - number of seconds after the container has started before running container probes, default 0

`periodSeconds` - probe interval, default 10 seconds

`timeoutSeconds` Probe timeout 1seconds

`failureThreshold` - number of missed checks before reporting failure, default 3

`successThreshold` - number of probes to be considered successful and live, default 1

```
containers:
  ...
  livenessProbe:
    tcpSocket:
      port: 8080
    initialDelaySeconds: 15
    periodSeconds: 20
  readinessProbe:
    tcpSocket:
      port: 8080
    initialDelaySeconds: 5
    periodSeconds: 10
```

livenessProbes and readinessProbes

```
containers:  
  ...  
  startupProbe:  
    tcpSocket:  
      port: 8080  
    initialDelaySeconds: 10  
    periodSeconds: 5
```

startupProbes

Demo

Implementing container probes

- livenessProbes
- readinessProbes
- startupProbes

Summary

Understanding Pods

Controllers and Pods

Multi-container Pods

Managing Pod Health with Probes