Configuring and Managing Kubernetes Storage and Scheduling

CONFIGURING AND MANAGING STORAGE IN KUBERNETES

Kien Bui
DevOps & Platform Engineer

Course Overview

Configuring and Managing Storage in Kubernetes

Configuration as Data - Environment Variables, Secrets and ConfigMaps

Managing and Controlling the Kubernetes Scheduler

Overview

Persistent Storage in Containers

Kubernetes Storage Objects

Storage Lifecycle

Using Storage in Kubernetes

Persistent Storage and Containers

Containers are ephemeral



A container’s Writable Layer is deleted when the container is deleted

When a Pod is deleted, its container(s) is deleted from the Node

How can we persist data across a Pod’s lifecycle?

Storage API Objects in Kubernetes

Volume



Persistent Volume

Persistent Volume Claim



Storage Class

Storage in Kubernetes



Persistent Volume

Persistent Volume Claim



Volumes

Persistent storage deployed as part of the Pod spec

Implementation details for your storage

This can be challenging…

- Sharing code
- Same lifecycle as Pod

We can do better…

Persistent Volumes



Administrator defined storage in the Cluster

Implementation details for your storage

Lifecycle independent of the Pod

Managed by the Kubelet

- Maps the storage in the Node
- Exposes `PV` as a mount inside the container

https://kubernetes.io/docs/concepts/storage/persistent-volumes/

Types of Persistent Volumes

Networked	Block	Cloud
NFS	Fibre Channel	awsElasticBlockStore
azureFile	iSCSI	azureDisk
		gcePersistentDisk

https://kubernetes.io/docs/concepts/storage/persistent-volumes/#types-of-persistent-volumes

Persistent Volumes Claims

A request for storage by a user

- Size
- Access Mode
- Storage Class

Enable portability of your application configurations

The Cluster will map a PVC to a PV

Access Modes

`ReadWriteOnce (RWO)`	`ReadWriteMany (RWX)`	`ReadOnlyMany (ROX)`

Node level access, not Pod access

Static Provisioning Workflow

Create a `PersistentVolume`	Create a `PersistentVolumeClaim`	Define `Volume` in Pod Spec





Storage Lifecycle



PVC Created

Control Loop

Matches PVC->PV

Pod’s Lifetime

PVC Deleted

`Delete (default)`

`Retain`

Defining a Persistent Volume



```
type { nfs, fc, azureDisk, ... }

capacity

accessModes

persistentVolumeReclaimPolicy

Labels
```

Defining a Persistent Volume

```
apiVersion: v1
kind: PersistentVolume
metadata:
  name: pv-nfs-data
spec:
  capacity:
    storage: 10Gi
  accessModes:
    - ReadWriteMany
 nfs:
    server: 172.16.94.5
    path: "/export/volumes/pod"
```

Defining a Persistent Volume Claim

accessModes

resources

storageClassName

selector

Defining a Persistent Volume Claim

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: pvc-nfs-data
spec:
  accessModes:
    - ReadWriteMany
 resources:
    requests:
      storage: 10Gi
```

Using Persistent Volumes in Pods

```
...
spec:
 volumes:
  - name: webcontent
    persistentVolumeClaim:
      claimName: pvc-nfs-data
  containers:
  - name: nginx
    ...
    volumeMounts:
    - name: webcontent
      mountPath: "/usr/share/nginx/html/web-app"
```



Lab Environment



Demo

Storage Server Overview - NFS

Static Provisioning Persistent Volumes

Storage Lifecycle and Reclaim Policy

Storage Class



Define tiers/classes of storage

Enables Dynamic Provisioning

Define infrastructure specific parameters

Reclaim Policy

Dynamic Provisioning Workflow

Create a `StorageClass`

Create a `PersistentVolumeClaim`

Define `Volume` in Pod Spec

Creates a `PersistentVolume`





Defining a StorageClass

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: managed-premium
parameters:
  kind: Managed
  storageaccounttype: Premium_LRS
provisioner: kubernetes.io/azure-disk
```

Dynamic Provisioning

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: pvc-azure-managed
spec:
  accessModes:
  - ReadWriteOnce
  storageClassName: managed-premium
  resources:
    requests:
      storage: 10Gi
```

Demo

Dynamic Provisioning in the Cloud

Defining a custom `StorageClass`

Review

Persistent Storage in Containers

Kubernetes Storage Objects

Storage Lifecycle

Using Storage in Kubernetes

What's Next!

Configuration as Data - Environment Variables, Secrets and ConfigMaps