

R: A Hitchhikers Guide to Reproducible Research

- Message in a bottle

**Brendan Palmer,
Clinical Research Facility - Cork &
School of Public Health
 @B_A_Palmer**

Daily overview

09.30 **Practical**

- Catch up on Day 1 and walkthroughs

10.30 **Coffee break**

11.00 **Lecture/Practical**

- Introduction to the core tidyverse packages, demonstrations and walkthroughs

13.00 **Lunch break**

14.00 **Practical session**

- Worksheet

15.00 **Lecture/Practical**

- Lecture and demonstration of ggplot2 for data analysis

15.30 **Practical session**

- Worksheet


16.30 **Finish**

Rewind


- We took a dive into base R code on Day 1
- Open `Day_1/scripts/07_practice_worksheet_solutions.R`
- Any burning questions?

Levels of help within RStudio

1. Let R help you write your code using Tab



2. Hover over the error symbols to identify what the error is



```
> counties <- c("cork", "dublin",)
Error in c("cork", "dublin", ) : argument 3 is empty
> |
```

Levels of help within RStudio

3. Watch out for capitalisation and naming errors as the code might run, but all the arguments supplied may return "FALSE"

```
> counties <- c("cork", "dublin")
> cork_dublin_df <- hse_df %>%
+   filter(county %in% counties)
> |

> ncol(cork_dublin_df)
[1] 3
> nrow(cork_dublin_df)
[1] 0
> unique(hse_df$county)
[1] "Carlow"      "Cavan"      "Clare"      "Cork"      "Donegal"    "Dublin"     "Galway"
[8] "Kerry"       "Kildare"    "Kilkenny"   "Laois"     "Leitrim"    "Limerick"   "Longford"
[15] "Louth"      "Mayo"      "Meath"      "Monaghan"  "Offaly"     "Roscommon"  "Sligo"
[22] "Tipperary"  "Waterford" "Westmeath"  "Wexford"   "Wicklow"
> |

> unique(hse_df$county) %in% counties
[1] FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
[15] FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
> |
```

Levels of help within RStudio

4. `> ?gather`

- If you're unsure about a function, place the question mark before it to retrieve help documentation
- describes the various arguments to the function
- provides useful examples to guide you through common operations

Walkthrough example script





- `01_correct_the_errors`

Package Cheatsheets

- Cheatsheets are available for many commonly used packages



[DOWNLOAD](#) [SUPPORT](#) [COMMUNITY](#) 


[Products](#)  [Resources](#)  [Pricing](#) [About](#)  [Blogs](#) 

RStudio Cheat Sheets

The cheat sheets below make it easy to use some of our favorite packages. From time to time, we will add new cheat sheets. If you'd like us to drop you an email when we do, click the button below.

[SUBSCRIBE TO CHEAT SHEET UPDATES](#)

 [CONTRIBUTED CHEAT SHEETS](#)

 [TRANSLATIONS](#)

 [HOW TO CONTRIBUTE](#)

- Day_2 > docs > Cheatsheet-tidyverse_for_beginners.pdf

Package Vignettes

- A vignette is a long-form guide to your package
- Before R version 3.0, vignettes were standard pdfs
 - The development of R Markdown has made vignette building and navigation more accessible
- A vignette should divide functions into useful categories, and demonstrate how to coordinate multiple functions to solve problems (but this may not always be the case)
- You can see all the installed vignettes with;
`browseVignettes()`

Package Webpages

- Many packages are one offs;
 - developed by individuals/labs to solve specific problems
 - once funding expires, package development ends
 - may get released but never updated
- Popular packages are more stable and updated regularly;
 - new versions released periodically
 - dedicated webpages



ggplot2 part of the tidyverse
3.2.1

Navigating RStudio – some useful tips

- Open the script `02_rstudio_ide_tricks.R`