
SubZeroAstro

From subs to masters – zero hassle.

User Manual

A beginner's guide to culling, stacking, processing and finishing your astrophotos



Version 0.9.260 beta · Windows and Mac (Apple silicon)

by Brian A. Poteet, DVM · October 2026

Highlights – what makes SubZeroAstro special

The features that set SubZeroAstro apart, grouped by page, with the version each arrived in. Each one is explained in its chapter.

Across the whole app

Feature	What it does	Since
Ready-made data recognised	Telescope Live (PROC = True), MaxIm DL (CALSTAT), PixInsight and Siril calibration notes, and _cal / _c file names mark lights as already calibrated: no double calibration, no SkyFlat, no false warnings	0.9.49
Damaged-file detection	Spots FITS files whose picture data was turned into text by a bad download or copy, and says so instead of stacking noise	0.9.50
Clear Everything – Start From Scratch	One menu item, like PixInsight's Reset Engine: forgets measurements and progress, moves old masters aside, optionally resets settings (keeps folders and tools)	0.9.52
Crash recovery	Every page saves as it goes; after a crash or restart the app offers to bring you back to the same page	0.6
Stop Here – Continue in PixInsight	From pages 2, 3 or 4, hands the image over as PixInsight-ready XISF with a note of the processes to use next	0.7
Smart telescopes	Seestar, DWARF, Vespera, Stellina and eVscope raw subs and stacks are recognised and handled without calibration frames	0.6
XISF everywhere	Reads PixInsight XISF light frames, including every compression (zlib, LZ4, LZ4-HC, Zstandard)	0.9.28
Windows and Apple-silicon Mac	Both builds run a full self-test on real hardware before every release	0.9.0

Page 1 – Quality & Cull

Feature	What it does	Since
Tonight's Target Picker	What to shoot tonight from your site and patch of sky - hours in the dark, peak altitude, Moon, size in your frame; sends targets straight into N.I.N.A., built from your own template	0.9.131
Organize My Astro Files	Sorts a folder, drive or NAS of FITS/XISF subs and masters by rig (Light Frames / Calibration Frames) or by target - preview first, copy or move, undo; duplicates flagged and kept, set aside or deleted	0.9.129 / 0.9.130
Organize Automatically / Change My Library's Layout	An incoming folder (e.g. on a NAS) organized into the library every day, twice a week or weekly by the computer's own scheduler; a third layout (by target, then rig) and a fourth (by date, then target, then rig - 0.9.253); an organized library re-sorted into another layout in place	0.9.220
Star quality on every frame	FWHM, eccentricity, SNR, star count and background, with a badge and a score against frames of the same camera and filter	Stage 2
My Weather Forecast	The next seven nights at your site, hour by hour through the dark (cloud at three heights, rain, seeing, transparency, wind, dew), with a bottom line: image tonight, or process	0.9.230
Fetch From My ASIAIRs	New subs copied from every ASIAIR over the network into the incoming folder under each one's rig - never twice, .jpgs left behind, optionally freeing the ASIAIR's space; through the night or before each automatic organize	0.9.229
Guiding from N.I.N.A.	Guiding RMS and pier side per frame from N.I.N.A.'s Session Metadata plugin - charted, sorted, badged and used by Auto-cull (guided rigs only)	0.9.228
Watch for New Frames	Grades the night as it happens: new frames measured as they arrive, an alert for clouds, dew, focus, trailing or guiding after two poor frames in a row	0.9.228

Feature	What it does	Since
Same Framing Next Session	A plate-solved master's centre and camera position angle sent to N.I.N.A. as a target, so the next session lines up	0.9.228
Session chart	One dot per frame in capture order, nights separated; click to jump, drag a range to flag or reject	Stage 2
Auto-cull presets	Three strengths flag frames from FWHM, stars, SNR (catches thin cloud) and eccentricity; you review before rejecting, and it can be undone	0.3.0
Fast measuring over a NAS	Reads about a quarter of each file, 3–4× faster on network drives; results are saved, so reopening is nearly instant	Stage 2

Page 2 – Calibrate & Stack

Feature	What it does	Since
Automatic calibration matching	Bias, darks and flats picked by camera, gain, offset, temperature, exposure, filter, rig and nearest date, with ✓ ⚠ ✗ and a plain reason	0.4.0
SkyFlats (Mote Buster)	No flats? A flat is built from your own light frames; a poor one stops and asks before it is used	0.9.22
Build Calibration Masters	One folder of mixed bias, dark, flat and dark-flat subs is sorted, checked and turned into masters, no lights needed	0.9.24
Field-distortion correction	Meridian flips and other setups get a distortion model per frame, so corner stars stay sharp	0.9.43
Hot pixels removed	Cosmetic correction in every frame: hot pixels and cosmic-ray hits are replaced by their neighbours, so undithered data has no coloured specks	0.9.54
Hot-pixel-proof star matching	Single-pixel spikes are ignored, so frames with hundreds of hot pixels line up on the sky, not the sensor	0.9.51
Plate-solution guided alignment	Frames and masters that carry a plate solution are lined up from where they point on the sky, with the stars fine-tuning it - rescues matches that fail and catches ones that are wrong	0.9.53
Comet stacking	A second stack follows the comet; stars and comet are both sharp in the final master	0.9.22
Comet LRGB	Filters shot one after another (NINA Orbitals): the comet is lined up across the filters on page 4, the stars stay put	0.9.126

Page 3 – Astro Image Processing

Feature	What it does	Since
One run for every filter	Auto-crop, plate solve, gradient removal and the RC-Astro tools on every master of the target, with the same crop	0.5.0
RC-Astro without a terminal	BlurXTerminator, NoiseXTerminator and StarXTerminator through the RC-Astro CLI, on the fast GPU, licences activated with a pasted code	0.5.0
Persistent plate solving	ASTAP retries other field sizes and works when the header has no focal length	0.9.37
PixInsight next steps	Linear XISF/FITS plus a plan of the PixInsight processes still to run, with done steps ticked	0.5.0

Page 4 – Finishing Touches

Feature	What it does	Since
Masters kept with the project	Save Project As can copy the masters into the project folder - one folder per target	0.9.127

Feature	What it does	Since
Comet steps	Bring Out the Tail and Reveal Comet Jets (Larson-Sekanina), offered for comets after the stretch	0.9.126
Recommended next step	Tailored to your data (colour, mono, narrowband, smart scope) and the target (galaxy, nebula, cluster, comet)	0.7
Pick from your own image, then fine-tune	Small versions of your picture to choose from; clicking previews big without applying; plain-language sliders fine-tune it, and the app says how much of the picture they change	0.7 / 0.9.48
Do It Again	Repeatable steps (curves, saturation, noise, Mote Buster …) can be run once more on their own result	0.9.48
Adjust Colours, Full Window, zoom	Bring out one colour at a time; see the picture full-window and zoom in to full resolution at any step	0.9.58
“Processed with SubZeroAstro” credit	A small, optional credit line in the corner of finished pictures - moves aside for your signature; never on XISF / FITS data	0.9.59
Planetary nebulae recognised	From the name (M57, M27 …) the whole process is tailored: colour-preserving brightening, the nebula moved back from the stars image, Tame the Ring keeps the centre and halo	0.9.71-0.9.76
Mote Buster – Fix Dust Donuts	Measures each dust shadow ring by ring and divides it out with a synthetic flat, so the detail underneath comes back; run it in rounds	0.9.22 / 0.9.47
Every master used	Several masters per filter averaged (less noisy ones count more), other setups bent onto one grid, unmatched ones left out	0.9.41
Target description	A short write-up from Wikipedia plus SIMBAD facts, credited, saved next to your picture	0.9.34

Contents

1 Welcome to SubZeroAstro
- 1.1 What SubZeroAstro does
- 1.2 Everything in one app
- 1.3 Who this manual is for
- 1.4 Words you will meet
- 1.5 Your data, improved - never painted

2 What you need
- 2.1 Computer requirements
- 2.2 Companion programs (optional but recommended)
- 2.3 Your images

3 Installing SubZeroAstro
- 3.1 Windows
- 3.2 Mac (Apple silicon)
- 3.3 Updating to a new version
- 3.4 Removing SubZeroAstro

4 First-time setup
- 4.1 Tell SubZeroAstro where your tools are
- 4.2 Choose where results are saved
- 4.3 The calibration library
- 4.4 Settings worth knowing
- 4.5 Working with N.I.N.A.

5 Finding your way around
- 5.1 The banner and page buttons
- 5.2 The log and the status bar
- 5.3 Saved progress and undo
- 5.4 Stop Here – Continue in PixInsight
- 5.5 ⚡ Fast Track: the whole way in one go

6 Page 1 – Astro Image Quality and Cull
- 6.1 Loading your sub-frames
- 6.2 Reading the measurements
- 6.3 Choosing which frames to keep
- 6.4 Filters, FITS headers and the viewer
- 6.5 Tonight's Target Picker
- 6.6 On to stacking

7 Page 2 – Calibrate and Stack
- 7.1 The light frame groups
- 7.2 Calibration: what the ✓ ⚠ ✗ mean
- 7.3 Stacking options
- 7.4 Running the stack
- 7.5 Results
- 7.6 Build Calibration Masters (no lights needed)

8 Page 3 – Astro Image Processing
- 8.1 Masters and target sets
- 8.2 Crop

8.3 Plate solve
8.4 Remove gradients
8.5 The XTerminators
8.6 Saving the results
8.7 Running and the step history

9 Page 4 – Finishing Touches
9.1 How it works
9.2 Going back
9.3 The steps
9.4 Mote Buster: dust donuts
9.5 Stars: take out, brighten, colour, put back
9.6 Darker sky, Final Crop, Spot Fix and your signature
9.7 Saving and sharing
9.8 Starting your next target

10 Recipes for common setups
10.1 Colour camera (OSC), broadband
10.2 Colour camera with a dual-band filter
10.3 Mono camera: LRGB
10.4 Mono camera: narrowband (SHO)
10.5 Smart telescopes (Seestar, DWARF, Vespera)
10.6 Comets
10.7 Target types
10.8 Step-by-step recipes: how to use them
10.9 Recipe: colour camera, broadband (RGB, no filter or UV/IR cut)
10.10 Recipe: colour camera with one dual-band filter (HOO)
10.11 Recipe: colour camera with two dual-band filters (SHO)
10.12 Recipe: mono camera, RGB or LRGB
10.13 Recipe: mono camera, LRGB + Ha (galaxies)
10.14 Recipe: mono camera, narrowband (SHO or HOO)
10.15 Adjusting any recipe for your target

11 Troubleshooting and questions
11.1 Common questions
11.2 Getting help and reporting problems

12 Keyboard shortcuts
12.1 Page 1 – Quality and Cull
12.2 Page 4 – Finishing Touches

13 Files and folders SubZeroAstro creates
13.1 Next to your images
13.2 On your computer
13.3 Organize My Astro Files

14 Privacy, licence and credits
14.1 Privacy
14.2 Licence and credits

15 Processing Techniques and Tips
15.1 Tips for every target
15.2 Galaxies
15.3 Emission nebulae

15.4 Planetary nebulae
15.5 Dark nebulae and faint dust
15.6 Reflection nebulae and star clusters
15.7 Comets
15.8 Moon and planets (coming)
15.9 Questions and fixes

16 Index


1 Welcome to SubZeroAstro

1.1 What SubZeroAstro does

SubZeroAstro takes you **from a folder of raw sub-frames to a finished astrophoto** - with as little hassle as possible. It walks you through four pages, one after the other, like turning the pages of a book (each shows **Page 1 of 4**, **Page 2 of 4** … next to its title at the top, the same numbers this manual uses):

Page	What happens there
1. Astro Image Quality and Cull	Every sub-frame is measured (star size, roundness, signal, cloud). You keep the good ones and set aside the bad ones.
2. Calibrate and Stack	Your kept frames are calibrated with darks, flats and bias and combined into one clean **master** per filter.
3. Astro Image Processing	The masters are cropped, plate solved, cleared of gradients and (optionally) sharpened, de-noised and separated from their stars with the RC-Astro XTerminators.
4. Finishing Touches	A guided, pick-the-one-you-like workflow turns the masters into a finished colour picture you can save, sign and share.

At every page you can also **stop and continue in PixInsight** - SubZeroAstro saves exactly what you have so far, plus a note of what to do next there.



The SubZeroAstro start-up screen

1.2 Everything in one app

Planning a night, bringing the subs in, filing them, checking and culling, calibrating, stacking and processing usually take several programs - each to buy, learn and keep in step with the others. **SubZeroAstro does all of it in one app**, with one set of rigs and one way of working, and works hand in hand with the two programs most of us capture with, **N.I.N.A.** and the **ZWO ASIAIR**:

Feature	What it does for you	Where
Your weather, with a bottom line	The next nights at your site hour by hour - cloud, rain, seeing, transparency, wind, dew - and a verdict: a great night for imaging, a so-so one, or a night for processing.	6.5
Target planning	What to shoot tonight from your site and horizon - hours in the dark, peak altitude, Moon, size in your frame - sent straight into N.I.N.A.'s target list.	6.5
Rigs imported from N.I.N.A.	Your rigs read from N.I.N.A.'s profiles; its file name pattern checked for typos.	4.5
Same framing next session	A plate-solved master becomes a N.I.N.A. target with the same centre and camera angle.	4.5
Real-time ASIAIR import	Remote Copy for the ASIAIR: new subs from every ASIAIR come over Wi-Fi through the night, each under its rig, never twice, without the .jpgs.	13.3
Live grading with alerts	Each new sub measured as it lands; clouds, dew, focus, trailing or guiding trouble flagged after two poor frames.	6.2
Real-time guiding analysis	The guiding RMS N.I.N.A. recorded for every sub - shown, charted and used in culling.	6.2
Fast Track after the night	N.I.N.A. starts Fast Track when its sequence ends: a finished picture waiting in the morning.	4.5
Organize and re-organize your data	Every rig's subs filed by rig or target, night and filter - on a schedule, from a NAS; a library re-sorted in place; every run undoable.	13.3
Image QC and culling	Every sub measured and badged against its own filter, a session chart, three Auto-cull strengths.	Chapter 6
Filter names, FITS headers, viewer	Add or correct the filter of any subs; edit headers across many files with undo; a FITS and XISF viewer.	6.4
Calibration masters built for you	Bias, darks, flats and dark-flats turned into masters, no lights needed, then matched to each night automatically.	Chapter 7
Fast Track	Raw subs to finished picture in one press.	5.5
Processing by example	Each finishing step shows previews of your own picture to pick from, instead of sliders and numbers.	Chapter 9
Built-in partner tools	RC-Astro BlurXTerminator, NoiseXTerminator and StarXTerminator, GraXpert and ASTAP, run for you at the right step; PixInsight one click away at every page.	Chapter 8

1.3 Who this manual is for

This manual is written for **newcomers** to astrophotography processing. No knowledge of PixInsight or other processing software is needed. Experienced imagers will find the PixInsight equivalent of each step mentioned along the way.

1.4 Words you will meet

Word	What it means
Sub-frame (sub, light)	One single exposure of your target, e.g. 180 seconds.
Calibration frames	**Darks** (lens cap on, same exposure), **flats** (evenly lit, shows dust and vignetting), **bias** (shortest exposure) and **dark-flats**. They remove the camera's and telescope's own fingerprints.
Master	Many frames combined into one: a master light (your target) or a master dark / flat / bias.
Linear / stretched	Straight from the camera a picture is **linear** and looks almost black. **Stretching** (Brighten the Image) makes the faint detail visible.
OSC (colour camera)	One-shot-colour camera: records red, green and blue at once (e.g. ZWO ASI2600MC).
Mono camera	Records one filter at a time (L, R, G, B, Ha, OIII, SII); the colours are combined later.
Narrowband / dual-band	Filters that pass only the glow of hydrogen (Ha), oxygen (OIII) or sulphur (SII). A **dual-band** filter (e.g. Optolong L-Ultimate, Askar D1) passes two of them on a colour camera.
Plate solving	Working out exactly where in the sky the picture points, by matching its stars to a star catalogue.
FWHM	Star size (full width at half maximum). Smaller = sharper.
Eccentricity	How round stars are: 0 = round, 1 = a line. Above about 0.5 stars look elongated.
SNR	Signal-to-noise ratio: how clearly the stars rise above the sky. Drops with cloud, haze or moonlight.
Starless / stars-only	The picture split in two by StarXTerminator, so the nebula and the stars can be processed separately.

1.5 Your data, improved - never painted

SubZeroAstro brings out what your camera **recorded** - it does not invent detail or paint the target. Every step works from your own data:

- **Brightness and colour:** brightening, Curves, Saturation and the colour tools re-map the brightness and colour your camera measured. The colour-preserving stretch keeps each pixel's measured colour mix; palettes such as HOO and Foraxx assign your filters' real signal to colours.
- **Bright cores and rings:** Tame Bright Core and Tame the Ring re-make bright areas from your own unstretched (linear) data - detail they show was in your frames, hidden by the brightening.

- **AI, used the accepted way:** BlurXTerminator sharpens by deconvolution using the blur measured from your own stars; NoiseXTerminator removes noise; GraXpert models the light-pollution gradient so it can be subtracted. None of them adds structure that is not in the data.
- **Smoothing** (colour transitions, noise reduction) only averages what is there.

Where pixels are replaced - always to remove a flaw, never to add to the target:

- **Spot Fix** fills a blemish you circle (a hot pixel, a satellite remnant, a dust speck) from the sky around it - like PixInsight's CloneStamp, and only where you ask.
- **Star removal** (StarXTerminator) has to fill in the background behind each star it lifts out; *Put Stars Back* covers those places again with your real stars.
- **Mote Buster** and flats correct dust shadows and vignetting - artefacts of the optics, not of the sky.

2 What you need

2.1 Computer requirements

SubZeroAstro runs on **Windows** and on **Macs with Apple silicon**. Astro images are big (a 26-megapixel camera makes ~50 MB files; a night can easily be 20-50 GB), so more memory and a fast disk make everything quicker.

	Minimum	Recommended
Operating system	Windows 10 (64-bit) or a Mac with Apple silicon (M1 or newer) and a recent macOS	Windows 11, or macOS 14 (Sonoma) or newer
Processor	4 cores	8 cores or more
Memory (RAM)	16 GB	32 GB or more (64 GB for 60-megapixel cameras or very large stacks)
Free disk space	20 GB plus room for your images	An SSD with 100 GB or more free - stacking keeps temporary aligned frames on the local disk
Graphics card	Not required	An NVIDIA RTX card (Windows) or Apple silicon GPU makes the RC-Astro XTerminators many times faster
Screen	1600 × 900	1920 × 1080 or larger

> **Tip:** Images on a network drive (NAS) work fine. SubZeroAstro reads them carefully (3 files at a time) and remembers the measurements, so re-opening a session is quick.

2.2 Companion programs (optional but recommended)

SubZeroAstro works on its own, but it can call these free or commercial programs for the best results. Install them **before** the first setup (Chapter 4); SubZeroAstro finds them automatically in their usual places. Each time it starts, page 1 checks for them quietly in the background and shows an amber note if one is missing or not licensed (4.1).

Program	Used for	Where to get it	Without it
ASTAP + a star database (D50 suits most setups)	Plate solving (page 3)	hnsky.org/astap.htm (free)	Plate solving is skipped (PixInsight can do it later)
GraXpert	AI gradient removal (page 3)	graxpert.com (free)	A built-in gradient remover is used
RC-Astro CLI with your BlurXTerminator, NoiseXTerminator and StarXTerminator licences	Sharpening, noise reduction and star removal (pages 3 and 4)	Your RC-Astro account (rc-astro.com)	These steps are skipped; Take Stars Out is not available

Program	Used for	Where to get it	Without it
PixInsight (optional)	Further processing after any page	pixinsight.com	Not needed - SubZeroAstro can finish the picture

2.3 Your images

- SubZeroAstro reads **FITS** (`.fit`, `.fits`, `.fts`) and PixInsight **XISF** (`.xisf`) files on every page - light frames, calibration frames and masters - from capture programs such as N.I.N.A., ASIAIR, SharpCap and smart telescopes (ZWO Seestar, DWARF, Vaonis Vespera, Stellina, eVscope). XISF files can be uncompressed or compressed with any of PixInsight's options (zlib, LZ4, LZ4-HC, Zstandard, with or without byte shuffling).
- Keep each night's lights in their own folder, and your calibration frames in a **calibration library** folder with one subfolder per telescope (see 4.3).
- Your original files are **never changed or deleted**. Rejected frames are only moved into a `REJECTED` subfolder.

3 Installing SubZeroAstro

3.1 Windows

1. Open the SubZeroAstro releases page: **github.com/bapoteet/SubZeroAstro/releases**.
2. Under the newest release, click **SubZeroAstro-Windows.zip** to download it.
3. Right-click the downloaded zip › **Extract All…** and choose a permanent place, e.g. `C:\Astro\SubZeroAstro`.
4. Open the extracted folder and double-click **SubZeroAstro.exe**. (Right-click › *Pin to Start* or *Send to › Desktop* gives you a shortcut.)
5. If Windows shows **"Windows protected your PC"**, click **More info › Run anyway**. This appears because the app is new and not yet code-signed; it is safe to continue.

3.2 Mac (Apple silicon)

1. Open **github.com/bapoteet/SubZeroAstro/releases** and download **SubZeroAstro-macOS-AppleSilicon.zip** from the newest release.
2. Double-click the zip in your Downloads folder; **SubZeroAstro.app** appears.
3. Drag **SubZeroAstro.app** into your **Applications** folder.
4. The first time only: **right-click** (or Control-click) the app › **Open**, then **Open** again in the message. After that it opens normally.
5. If macOS says the app "is damaged" or "can't be opened", open **Terminal** (Applications › Utilities) and type: `xattr -dr com.apple.quarantine /Applications/SubZeroAstro.app` then press Return and open the app again.

> **Why the warnings?:** Both messages appear because SubZeroAstro is not yet signed by Microsoft or notarized by Apple. Signing is being set up for future versions.
>
> **Mac: window size:** SubZeroAstro opens filling the screen, with the menu bar and Dock still showing. Avoid the green button's full-screen mode on a Mac: it hides the menu bar (where **Stack › Build Calibration Masters…** and **Help** live). To fill the screen yourself, **Option-click** the green button, or double-click the window's title bar. If you make the window smaller, it opens at that size next time.

3.3 Updating to a new version

Download the newest zip from the releases page and replace the old app folder (Windows) or the app in Applications (Mac). **Your settings, tool locations, rig names, saved measurements and saved progress are kept** - they are stored separately from the app.

3.4 Removing SubZeroAstro

Delete the app folder (Windows) or drag SubZeroAstro from Applications to the Bin (Mac). Saved progress can be cleared first under **Settings › Saved Progress**. Your images are never touched.

4 First-time setup

Your setup checklist. SubZeroAstro works out of the box, but these few steps - once, about half an hour - switch on everything it can do:

1. **Install the helper programs** (all optional, all recommended): **ASTAP** *and a star database for it* (D50 for most telescopes, W08 too for wide lenses - ASTAP can't plate solve without one), **GraXpert**, and the **RC-Astro CLI** with your BlurXTerminator, NoiseXTerminator and StarXTerminator licences. **Settings › Your Tools…** shows what's found and has a Download Page button for each (4.1).
2. **Name your rigs**: **Settings › My Rigs…** (also in the File menu, and Your Rigs… in the Organize window) - one row per rig with its focal length; **From N.I.N.A.…** fills them in from N.I.N.A.'s profiles (4.5, 13.3). Organize, Calibrate and Stack and Fetch From My ASIAIRs all use these names.
3. **Tell it where you are**: press **Use My Location** in **Tonight's Target Picker** or **My Weather Forecast**. That turns on the weather light on page 1, the seven-night forecast and target planning for your sky (6.5).
4. **With N.I.N.A.**: **Settings › Work With N.I.N.A.…** - check its file name pattern, add your rigs, and, for Fast Track after the night, paste the External Script line into your sequence. Install N.I.N.A.'s free **Session Metadata** plugin to get each frame's guiding RMS (4.5, 6.2).
5. **With an ASIAIR**: set the telescope's focal length in each ASIAIR (it goes in every file's header), then **File › Fetch From My ASIAIRs…** - add each one's IP address and rig, and pick your incoming folder (13.3).
6. **Build your calibration library**: **Stack › Build Calibration Masters…** turns your darks, flats and bias into masters that are matched to every night automatically (chapter 7).
7. **Optional**: **Organize Automatically…** to file new frames on a schedule (13.3), and **Settings › Open FITS / XISF Files With SubZeroAstro…** so a double-click opens them in its viewer (6.4).

Where to get everything (all free except the RC-Astro tools; **Settings › Your Tools…** also has a Download Page button for the first three):


What	Download	Notes
ASTAP and its star databases	hnsky.org/astap.htm	Install ASTAP, then a database from the same page: D50 for most telescopes, W08 too for camera lenses
GraXpert	graxpert.com	Gradient removal
RC-Astro BlurXTerminator, NoiseXTerminator, StarXTerminator	rc-astro.com	Paid; install the RC-Astro CLI, then activate with the code from your rc-astro.com account (4.1)
N.I.N.A.	nighttime-imaging.eu	Windows capture program
Session Metadata plugin for N.I.N.A.	Inside N.I.N.A.: *Plugins › Available › Session Metadata* (about it)	Writes each frame's guiding RMS for SubZeroAstro

What	Download	Notes
ASIAIR app	Apple App Store or Google Play (search *ASIAIR*)	Shows each ASIAIR's IP address (Wi-Fi settings) and sets its focal length
PixInsight (optional)	pixinsight.com	Paid; only if you want to continue there
SubZeroAstro updates	**Help › Check for Updates…**	SubZeroAstro also offers each update itself (the blue bar on page 1)

4.1 Tell SubZeroAstro where your tools are


When SubZeroAstro starts, it checks for ASTAP, GraXpert and the RC-Astro CLI in the background. If one is missing - or RC-Astro is installed but a tool is not licensed, or ASTAP has no star database next to it (ASTAP can't plate solve without one; D50 is a separate download on the same page) - a slim **amber banner** appears at the top of page 1, saying what you would miss (for example *plate solving is skipped*). Nothing is wrong: you can still cull and stack. The banner has two buttons:

- **Set Up…** - opens the **Your Tools** window (also in **Settings › Your Tools (ASTAP, GraXpert, RC-Astro)…**).
- **Don't Remind Me** - hides the banner until something else changes. Use it if you have chosen not to use one of the programs.



The amber banner on page 1 when helper programs are missing (example)

The **Your Tools** window lists each program with its status, a **Download Page** button for anything missing, and **Browse…** to point at a program installed somewhere unusual. Click **Check Again** after installing something.



Settings › Your Tools: status, Browse… and Download Page for each helper program


The same programs are also shown in the **Your tools** box at the top of page 3 (**Astro Image Processing**), with a green ✔ **found** when detected. If one is missing, click **Browse…** next to it and pick the program:

Tool	Typical location on Windows	Typical location on a Mac
ASTAP	`C:\Program Files\astap\astap.exe`	`/Applications/ASTAP.app` (or `astap_cli`)
GraXpert	`C:\Users\<you>\AppData\Local\Programs\GraXpert\GraXpert.exe`	`/Applications/GraXpert.app`
RC-Astro CLI	`C:\Program Files\RC-Astro\CLI\rc-astro.exe`	where the RC-Astro installer put `rc-astro`

Activating RC-Astro licences. You do not need a terminal: click **RC-Astro Licences…** (next to the RC-Astro CLI row on page 3, or in the Your Tools window). The window shows which tools are licensed on this computer. To activate:


1. Click **Open My RC-Astro Account** and sign in on rc-astro.com.
2. Click **Get Activation Code** on the account page, then click it again to copy the code.
3. Paste the code into the box and click **Activate**. **One code activates every RC-Astro tool you own.**

The tools turn green and page 3 is updated straight away. If activation does not work, **Do It in a Terminal Window** runs RC-Astro's own `rc-astro license` command, where you paste the code and press Enter. **Check for Updates** and **Download & Install Update** keep the RC-Astro CLI itself up to date.



The RC-Astro Licences window (example: StarXTerminator not yet activated)

For the RC-Astro CLI the status line lists **BlurXTerminator ✓ · StarXTerminator ✓ · NoiseXTerminator ✓** for every product licensed on this computer. Below the XTerminator settings, **RC-Astro device** chooses the processor: pick your dedicated graphics card (e.g. *NVIDIA RTX…*) - it is much faster than integrated graphics.



Page 3 with the tools box at the top (example data)

4.2 Choose where results are saved

On page 2 (**Calibrate and Stack**) set two folders under **Save locations** once; they are remembered:

- **Calibration masters** - your calibration library (4.3). New master darks, flats and bias are saved there and found again automatically next time.
- **Master lights** - where your stacked masters go, one subfolder per target, e.g. `…\Master Lights\IC1805\IC1805_L-Ultimate_Master_2026-10-09_to_2026-10-11.fits`.

4.3 The calibration library

SubZeroAstro keeps calibration masters in a tidy structure inside the calibration folder:

`<calibration folder>\<telescope rig>\Masters\<camera>\Bias | Darks | Flats\ <filter>\…`

- **Rig names**: the first time, pick a rig name for each camera + focal length (e.g. *265mm scope* or *SQA55*). This matters for ASIAIR, which records the mount, not the telescope.
- **Even out the sky between frames** (on by default; PixInsight calls it LocalNormalization): light pollution, haze and moonlight change through the night, so each frame's sky is brighter in a different corner. Before combining, every frame's sky is matched to the best frame's, so satellites, planes and noise are rejected properly and the background comes out even. The target and its glow are left out of that sky estimate, so a bright target (a planetary nebula, a galaxy) gets no box-shaped border around it - also with drizzle and with the camera turned between nights.
- **Double the resolution (drizzle 2x)** (off by default; PixInsight: DrizzleIntegration): if you dither (the scope moves a few pixels between frames) and your stars are small and blocky, the frames' slightly different positions are combined on a grid twice as fine - a master twice the size with finer stars. It uses the regular stack to leave out satellites and planes. Slower, the

masters are 4x larger, and without dithering it adds nothing. After stacking, SubZeroAstro tells you when your frames are dithered and the stars small enough (under about 2.2 px) for drizzle to help (and when it was on but the frames were hardly dithered).

- **Darks** are matched by exposure, gain, offset and temperature (±3 °C). **Flats** are matched by camera, filter and rig, nearest in date. If you take flats every session (e.g. NINA's flat-panel sequence after imaging), a group of lights from several nights uses **each night's own flat** for that night's lights - dust that moved between nights leaves no shadows (the Flats cell and the stack log list them). **Bias** or **dark-flats** are needed to calibrate flats properly.
- You can add a folder of raw calibration sub-frames; SubZeroAstro builds the masters and saves them into the library.

4.4 Settings worth knowing

- **Settings › Star measurement** - *Fast* (default, about 3-4× quicker on a network drive), *Full frame* or *Off*.
- **Settings › Your Tools (ASTAP, GraXpert, RC-Astro)…** - see, locate and download the helper programs, and activate RC-Astro licences (4.1).
- **Settings › Saved Progress…** - where crash-recovery copies are kept, how much space they use and how long they are kept (30 days by default).
- **Settings › Show Intro Animation at Startup** - turn the start-up animation on or off. *Help › Play the Intro Animation* plays it any time.

4.5 Working with N.I.N.A.

Settings › Work With N.I.N.A.… brings together everything SubZeroAstro does with N.I.N.A.:

- **Your Rigs & File Names** - every N.I.N.A. profile on this computer is listed with its telescope name and focal length (N.I.N.A.: *Options › Equipment › Telescope*), camera and filters. If N.I.N.A. runs on each rig's own computer, copy that computer's profile files (the *.profile* files in *%LOCALAPPDATA%\NINA\Profiles*) over and press **Add Profile Files…** (they are remembered). Tick the rigs and press **Add Ticked to Your Rigs…** - Your Rigs opens with them added (a rig with the same name gets the focal length added, e.g. with and without a reducer); check the names, then **Save My Rigs**. *Your Rigs* has the same as a **From N.I.N.A. …** button.
- **File name pattern check** - SubZeroAstro reads what it needs from each file's header, so any pattern works, but a token N.I.N.A. doesn't know ends up in your file names as typed, or as a bare *$$*. The *File name pattern* column flags it; fix it in N.I.N.A. under *Options › Imaging › Image File Pattern*. **Copy Suggested Pattern** gives a clear one.
- **After the Night** - let N.I.N.A. start **Fast Track** when the imaging is done: in the Advanced Sequencer, at the end of the sequence (after warming the camera and parking), add *Utility › External Script* and paste the line from **Copy for N.I.N.A.**, e.g. `"C:\…\SubZeroAstro.exe" --fast-track "D:\NINA\Images" --hours 18`. SubZeroAstro starts (minimised), takes the frames changed in the last 18 hours, runs Fast Track on the suggested settings for the target with the most frames (`--target "M 31"` to choose), saves the picture as JPEG and TIFF in the usual *Finished* folder (`--out "D:\Pictures"` to choose) and closes. Any message on the way is answered with its default and noted in the log. It runs on the computer N.I.N.A. runs on, so SubZeroAstro must be installed there.
- **Targets** - *Tonight's Target Picker* reads your site and horizon from a N.I.N.A. profile and sends the targets you pick straight to N.I.N.A. (6.5).
- **Same Framing Next Session** (also *Stack › Same Framing Next Session (N.I.N.A.)…*) - pick a plate-solved master (Astro Image Processing solves masters when ASTAP is installed) or any solved picture of the target. SubZeroAstro works out the centre of the picture and the camera's

position angle exactly the way N.I.N.A. measures them, and **Send to N.I.N.A.** puts a target with both into N.I.N.A.'s target list (*Sequencer › Advanced › Targets › SubZeroAstro*, built from your Target Picker template if you chose one). Next session use it with *Slew, center and rotate* (with a rotator, or N.I.N.A.'s manual rotator telling you how far to turn the camera) or *Slew and center* without one, and the new frames line up with the old ones. A picture that isn't solved yet is solved by ASTAP first, from a copy - your file is not changed. **Copy Centre & Angle** copies them as text.

- **Guiding RMS and pier side** - with N.I.N.A.'s Session Metadata plugin, each frame's guiding is shown, charted and used in culling on Quality and Cull (6.2).

5 Finding your way around

5.1 The banner and page buttons

Every page has the same banner at the top: **SubZeroAstro**, the author and the **version** in small print (e.g. *v0.9.10 beta*), the **page title**, and beside it the **target** you are working on (e.g. *Target: M28*; with several targets loaded, *Targets: M27, M28*). On the right is a blue **Continue to … ➜** button that turns to the next page; on the left a grey ◀️ **previous page** button goes back. Going back keeps your work: press Continue again and the page you left comes back exactly as it was.

5.2 The log and the status bar

The text area at the bottom of each page is the **log**: it tells you what was done, what was found and any warnings, in plain language. The orange bar shows progress and an estimate of the time left.

When a page has finished its job, its green run button turns **amber** - ✔ **Stacked – Run Again?** on page 2, ✔ **Done – Run Again?** on page 3 - so you can see at a glance that the page is done. Pressing it again asks first, so nothing is redone by accident. Add new images and it turns green again.

5.3 Saved progress and undo

- **Page 1**: your folders and flags are saved as you go. **Ctrl+Z** undoes rejects, flags and auto-cull.
- **Pick up where you left off**: when you start SubZeroAstro again - after quitting normally or after a crash - it offers **Pick Up Where I Left Off**: your frames and flags come back and it goes straight to the page you were on (Calibrate and Stack, Image Processing with the same masters, or Finishing Touches, where your steps resume). **Start Fresh** begins a new project; after *End this Project and Start New Project* nothing is offered.
- **Page 2**: each master is noted as soon as it is saved; an interrupted run offers **Continue With the Rest**.
- **Page 3**: the image is saved after every step; **Go Back & Redo This Step** and **Start Fresh** are under the preview.
- **Page 4**: every step is saved: **Undo** (Ctrl+Z), **Go Back to Here**, **Back to Start**, and reopening the same masters later resumes the project.
- **Clear everything and start from scratch**: **File › Clear Everything – Start From Scratch…** forgets the saved quality measurements (page 1 measures every frame again), deletes all saved progress (stacking resume points, page 3 and page 4 step histories, the last session) can move your existing master lights aside into an *Old masters <date>* folder, so a new stack starts truly from nothing, and can reset all settings to factory defaults (your folders, tool locations, rig names and signature are kept) - like PixInsight's *Reset Engine*. Your images, calibration library and masters are never deleted. Then load your light frames again.

5.4 Stop Here – Continue in PixInsight

The purple **Stop Here – Continue in PixInsight** button (pages 2, 3 and 4) saves the image exactly as it is right now as PixInsight-ready XISF, writes a short note listing the PixInsight processes to use next, and opens the folder with the files selected.

5.5 ⚡ Fast Track: the whole way in one go


⚡ **Fast Track** takes your data to a finished picture on SubZeroAstro's suggested settings for your kind of target - the same steps and the same versions the cards mark as *suggested* when you go step by step - and shows every step as it happens, like a short film.

1. Open your light frames on page 1 (calibration frames can be in the same folder; your calibration library is used too) and press ⚡ **Fast Track** at the top right. On page 3 or page 4 the same button starts from the masters there (on page 4 it carries on from the picture as it is).
2. Fast Track asks one thing: **what the target is** (galaxy, nebula, planetary nebula, star cluster, comet). It recognises most catalogue names; change it if it is wrong - the steps and their settings follow the kind of object. With narrowband data it also asks for the **colour palette** (Hubble SHO, HSO, HOO + SII, HOO, Foraxx): the suggestion is the palette most people show that target in when it is a well-known one (the Pacman Nebula in SHO, the Crescent in HOO), else SHO for nebulae and HOO + SII for planetary nebulae.
3. Watch: page 1 measures the frames and leaves out the clearly bad ones (the gentlest cull, **Less aggressive** - nothing is moved or deleted), page 2 calibrates and stacks, page 3 runs its steps, page 4 does each recommended step. Each result fades in on the big picture with its name, and lands in the **film strip** underneath - click a frame to look at it again.
4. At the end the picture starts a slow flight: ✈️ **Fly Into It** glides in towards your target while turning gently, then back out, over and over (press it again to stop). Then: **Save the Picture…**, **Save Project…**, **Share to AstroBin…**, ▶️ **Play the Film Again**, 🔧 **Fine-Tune on Page 4** (every Fast Track step is in page 4's list: click one and use *Go Back to Here* to try another version), or ↻ **Reprocess Step by Step** (page 4 back at the masters as loaded - you pick each version yourself).

Fast Track also does two steps that are only optional when you go step by step, because they finish the picture: **Darken the Sky Background** and **Final Noise Reduction** (a last NoiseXTerminator pass, when the RC-Astro tools are installed). It leaves the steps that need your eye or your name for you: **Final Crop**, **Flip or Rotate**, **Spot Fix** and **Sign Your Picture**. **Stop** halts it after the current step; everything done so far stays on its page. All four pages are there afterwards with ◀️ Back, exactly as if you had clicked through them.

> **Tip:** Fast Track is also the quickest way to compare: run it, look at the result, then **Reprocess Step by Step** and pick other versions where you like.


6 Page 1 – Astro Image Quality and Cull



Page 1: frame list (left), the selected frame, the session chart and the measurements (example data)

6.1 Loading your sub-frames

1. Click **Load Light Frame Data** (Ctrl+O), then **Add Folders…**. You can pick **several folders at once**: click one, then **Shift**-click to add a range, or **Ctrl**-click (**Cmd**-click on a Mac) to add others one by one. Click **Add Folders…** again for folders in other places (other nights, other drives), or **Add Files…** for individual files.
2. **Include subfolders** is ticked by default, so nights kept in subfolders are found too (FLAT, DARK, BIAS, CALIB and OFFSET folders are skipped). Untick it to load only the files directly in each folder; your choice is remembered.
3. If your capture software does not record the filter (e.g. ASIAIR with a manual filter drawer), choose it under **Filter used**.
4. Press **Start Processing**. Frames appear at once and are measured in the background.



The Load Light Frame Data window

> **Calibration frames?:** Load Light Frame Data is for **light frames only**. To turn bias, darks and flats into masters, use **Stack › Build Calibration Masters…** instead (7.6) - no light frames needed.
>
> **Tip:** If the file names mention the filter (e.g. `…_SQA55Lult_0001.fit`), SubZeroAstro notices after the first few frames and offers to use it for the whole set. Duplicate files are skipped and reported.

6.2 Reading the measurements

Each frame gets a coloured **badge** (green = good, amber = check it, red = probably reject) and a **score** where 100 = a typical frame for that filter. Frames are only ever compared with frames from the **same camera and filter**.

Measurement	What it tells you	Bad sign
FWHM	Star size in pixels (and arcseconds)	Much larger than the median: poor focus or seeing
Eccentricity	Star roundness (0 = round)	Above ~0.5: tracking, guiding or wind
SNR	How clearly stars stand out	A drop: cloud, haze, dew, moonlight
Stars	Number of stars detected	A sudden drop: cloud or trees
Background	Sky brightness	A rise: moon, twilight, light pollution
Guiding	Guiding RMS during the exposure (″), from N.I.N.A.'s Session Metadata plugin	Much higher than the median: wind, clouds over the guide star, cable snag

Guiding RMS and pier side from N.I.N.A. A frame can't tell afterwards how well the guiding went, but N.I.N.A. knows: install the free **Session Metadata** plugin (N.I.N.A.: *Plugins › Available*) and it writes an *ImageMetaData.csv* next to your frames, one line per frame. SubZeroAstro finds it (in the frames' folder or up to two folders above) and shows each frame's **Guiding** RMS (with RA and Dec) and **Pier side**; *Guiding RMS (″)* can be charted and sorted, a frame with clearly rougher guiding than the night's median gets an amber or red badge, and the Auto-cull buttons and Auto-Flag also cull on it. Unguided rigs (a mount with a pointing model, such as a 10Micron or an Astro-Physics mount)


record no guiding, and nothing changes for them - their stars' roundness (eccentricity) already shows any tracking trouble. The pier side shows whenever the file records it (N.I.N.A. writes *PIERSIDE* in every header). **Organize My Astro Files** takes the file along: a copy goes into every folder its frames are filed into (after a Move the original goes once its folder has no frames left; Undo puts it back).

Watch for New Frames (File menu) grades the night while it is still going. Open the folder N.I.N.A. saves into (or the folder the frames are copied to) and tick it: every 20 seconds SubZeroAstro looks for new frames, measures each one as soon as it has finished writing, and compares it with the frames of the same camera and filter before it. **Two poor frames in a row** raise an alert - *Clouds?*, *Dew or haze?*, *Bright sky*, *Soft stars* (focus or seeing), *Trailed stars* or *Guiding trouble* - as a notification on the screen, a beep and a line in the status bar; **two good frames in a row** say it has cleared. The status bar shows ● *LIVE* with a count while it watches. Untick it to stop (opening another folder keeps watching the new one; Start Over stops it).

The **session chart** below the image shows one dot per frame in capture order. Choose what to plot, **click** a dot to jump to that frame, or **drag** across the chart to select a range. The **Kept frames** box on the right shows the averages of what you are keeping.

6.3 Choosing which frames to keep

1. Click an **Auto-cull** button - **Aggressive**, **Semi-aggressive** or **Less aggressive**. It only **flags** frames (yellow ring); hover over a button first to see how many it would flag.
2. Review the flagged frames (switch the list to *Flagged*); the measurements panel says why each was picked. Press **F** to un-flag one you want to keep.
3. Press **Reject Flagged** (Shift+X). Rejected frames are moved into a `REJECTED` subfolder - nothing is deleted, and **Ctrl+Z** brings them back.



After Semi-aggressive: suspect frames are flagged for review (example data)

Auto-Flag (Ctrl+F) lets you set your own limits. **X** rejects or restores the selected frame(s), **F** flags them, **D** clears all flags.

6.4 Filters, FITS headers and the viewer

- **Frame › Set Filter Name…** changes the filter for the selected frames (your files are not changed). Use it when the filter is missing or wrong - flats are matched by filter.
- **Frame › Edit FITS Headers…** (Ctrl+Shift+H) changes keywords **in the files themselves**, for the selected frames or all of them: OBJECT, FILTER (a filter typed *S11* instead of *SII*), IMAGETYP, EXPTIME, telescope, camera, focal length, pixel size, gain, offset, temperature, or any other keyword. The image data is not touched. The old values are kept in a small undo file in each folder: **Frame › Undo Last Header Change** puts them back. Only FITS files are edited; XISF files are left as they are.
- **Ctrl+H** opens the full **FITS header** of the selected file, with search and Copy All.
- **File › Open FITS / XISF Viewer…** (Ctrl+Shift+V, also in the View menu) looks at **any** FITS or XISF file without loading it into a session: the picture (auto-stretched, in colour for colour data - raw colour-camera frames too), zoom with the wheel, the pixel values under the mouse, size

and levels, the main capture facts and the whole header with search. *Previous* / *Next* (Page Up / Page Down) step through the other files in the folder; you can also drop a file on the window.

- **A NAS or network folder:** SubZeroAstro's own folder window (the one that picks several folders at once) has a **Network / NAS Folder…** button - it opens the system's folder window, which can browse the network. Or type the address into the folder box, e.g. *\\DS1522\Astro*. Shares you used are kept in the sidebar. Mapping the share to a drive letter (File Explorer › This PC › Map network drive) works everywhere too.
- **Make it your FITS / XISF viewer: Settings › Open FITS / XISF Files With SubZeroAstro…**. On Windows this adds SubZeroAstro to *Open with*; then right-click a .fits file › Open with › Choose another app › SubZeroAstro, tick *Always*. On a Mac: select a .fits file in Finder, ⌘I, *Open with* › SubZeroAstro › *Change All*. Do the same once for .xisf. A double-click then opens just the viewer - quickly, without the intro.
- **Ctrl+I** hides or shows the image - useful on a slow network drive.

6.5 Tonight's Target Picker

File › Tonight's Target Picker… (Ctrl+Shift+T) answers *what can I shoot tonight from here?* Everything is worked out on your computer - no account, no AI - from the position of the Sun, Moon and each object through the night (the internet is used only if you ask Use My Location for an approximate position).

- **Where and when**: your rig's latitude and longitude (west is negative). Pick one of your **N.I.N.A. profiles** - it also brings your focal length, pixel size and horizon file - or **Fill In From One of My Pictures…** to read them from a FITS/XISF header, or press **Use My Location**: on Windows it asks the computer's own location service (Wi-Fi/GPS - turn on *Settings › Privacy & security › Location* and *Let desktop apps access your location*); otherwise it asks an online service for an approximate position from your internet connection (city level - plenty for planning, since a target's altitude hardly changes over a few tens of km). Choose the night (tonight by default); the times shown are always this computer's clock and time zone.
- **Your sky**: click the compass to mark what you can't see - each click cycles *open → low trees (20°) → tall trees (35°) → blocked*. Or type it: *open sky from NNW to SSW* (the shorter way round), *trees to the east up to 30 degrees*, *house blocks N*, then **Use This Description**. A custom horizon file - N.I.N.A.'s *.hrz*, or the same list you made for Telescopius (one *azimuth altitude* pair per line, e.g. *205 10*) - loads with **Load a N.I.N.A. Horizon File…**; it's used in full detail, every degree, and loaded again next time (clicking the compass by hand sets it aside). **Lowest altitude** (30° by default) keeps you out of the thick, light-polluted air near the horizon.
- **Your rig**: focal length, pixel size and sensor size give the *In your frame* column - how much of your picture each target fills, or whether it needs a mosaic.
- **Work It Out** lists every target that is in the dark and above your horizon for at least the hours you ask: its window, how high it climbs and when, how far it is from the Moon, and a **Best** score (more hours, higher up, Moon out of the way - a bright Moon hurts galaxies far more than emission nebulae shot with a narrowband filter - and a good fit in your frame). Tick the types you want, filter by size, **group** by type, size or time of night, or type a name in **Find**. The chart below shows the selected target's altitude through the night with your horizon and the Moon.
- **Into N.I.N.A.**: select targets and **Send to N.I.N.A.** - they appear straight away in N.I.N.A.'s target list (Advanced Sequencer › Targets › *SubZeroAstro*), ready to drag into your sequence. Pick **N.I.N.A. Template…** once - one of your own saved targets - and every target you send gets its exposures, autofocus, dithering and checks, with only the name and coordinates changed. (Running N.I.N.A. on another computer? Copy the files from *Documents/N.I.N.A/Targets/SubZeroAstro* to the same folder there.) **Save List for N.I.N.A.…** writes a target list for the simple Sequencer's **Import Targets** (the CSV layout Telescopius exports), and **Copy Coordinates** puts RA/Dec (J2000) on the clipboard for the Framing

Assistant. **About This Target** shows the Wikipedia and SIMBAD notes; **Telescopius** copies the name and opens Telescopius.


- The objects are N.I.N.A.'s deep-sky database - read from N.I.N.A. itself when it is installed on this computer, otherwise SubZeroAstro's built-in copy of its 4 000+ imaging-worthy objects. Times are in your computer's time zone; positions are good to a fraction of a degree - plenty for planning.

My Weather Forecast (File menu, the toolbar, or the button in Tonight's Target Picker) shows the next **seven nights** at your site - **Use My Location** finds it. **The Week Ahead** lists them one per line: the bottom line, clear dark hours, best window, Moon and how sure the forecast is (high for the next two nights, fair for the two after, low beyond - seeing and transparency reach about three days ahead); double-click a night for its hours. **Tonight's weather light** sits at the top left of page 1, beside Zip My Logs: green for a good night, yellow for a so-so one, red for clouds - in words that change from night to night (*Tonight: clear skies - go go go!*, *Tonight: maybe - user discretion advised*, *Tonight: a no-go - maybe a movie instead* …) - hover over it for the reasons and the best window, click it for the whole week. It refreshes every two hours. Each night gets a **bottom line** in a coloured banner: *Looks like a great night for imaging!*, *Looks like a good but not perfect night - expect some clouds or so-so conditions*, or *Not a good night for imaging - but a great night for processing with SubZeroAstro* - with the reasons (clear hours, rain, gusty wind, damp air near the dew point, poor seeing, haze), the dark hours, the Moon, and the **best window** (the longest clear stretch). Below it, the dark hours hour by hour, coloured like a clear-sky chart (deep blue = good, white = bad): cloud (all, low, middle, high), rain chance, seeing, transparency, wind and gusts, temperature, and how far above the dew point it is (red = dew likely). The forecast comes from Open-Meteo (cloud, rain, wind, dew) and 7Timer! (seeing, transparency), free and with no account; the computer must be online.

6.6 On to stacking

When you are happy, click **Calibrate and Stack ➜** at the top right. Only your kept frames go to page 2.

7 Page 2 – Calibrate and Stack



Page 2 after stacking: one row per target and filter, with the calibration found for each (example data)

7.1 The light frame groups

Each target's rows come **broadband first** (L, R, G, B - tinted blue), then **narrowband** (Ha, OIII, SII and dual-band filters - tinted red). The **Stack: Broadband / Narrowband** tick boxes above the table include or leave out a whole kind at once - handy when one target has both, and you want, say, only the LRGB + Ha of a galaxy (untick a single row with its own box).

Your kept frames are grouped by **target + filter + camera + telescope** - one row each, with the number of frames, total exposure and nights. The **Filter** of a row can be changed from its drop-down (for example to match your flats).

7.2 Calibration: what the ✓ ⚠ ✗ mean

Mark	Meaning
✓ green	A matching calibration master was found (or will be built).
⚠ orange	Usable, with a note - e.g. darks scaled from another exposure, or flats taken long ago (*"dust may have moved"*). It **will** be used.
✗ red	Nothing suitable - e.g. *No flats for filter OIII*. You can still stack, without that correction.

Click a row to read the details below the table. Add calibration with **Add Calibration Folder…**, **Add Calibration Files…** or **Search Calibration Folder for Subframes**.

Where the calibration comes from, in order: frames you add here come first, then your calibration masters folder. Whatever a group still lacks - darks, bias, or flats from the lights' own nights - is looked for in your **organized library** (the one Organize files into): *Calibration Frames › <rig> › Flats / Dark flats / Bias / Masters*, and every rig folder's *Darks* of this camera at this exposure (darks belong to the camera, not the telescope). Flats only come from the lights' own rig and from within two months of the lights. The details below the table say *organized library* for what came from there, and the masters built from it are saved to your calibration folder, so next time they are found there first.

No flats at all? SkyFlats (Mote Buster). When a filter has no flats, SubZeroAstro can make a flat from your **light frames** (option *SkyFlats (Mote Buster) when flats are missing*, on by default; at least 12 frames). It uses every light with that filter, camera and rig - from all your targets and nights, because the stars land somewhere different in each. Each frame is scaled to the same brightness, its stars are hidden, and its own light-pollution tilt is taken out (that tilt changes from frame to frame, while the vignetting stays put). Of every pixel's values only the lower half is used - a nebula can only add light - and what remains is what your optics and dust do to an even sky: a flat. The Flats cell then shows ⚠️ *SkyFlat (Mote Buster) (made from N light frames)*. SkyFlats are never saved to your library. (For donuts that remain, *Mote Buster – Fix Dust Donuts* on Finishing Touches works on one picture.)

Ready-made data is recognised. Lights bought already calibrated - from Telescope Live and similar services, or calibrated earlier in other software - must not be calibrated again (the dark would be subtracted twice and the flat divided in twice). SubZeroAstro recognises them from their headers and names: Telescope Live's *PROC = True*, MaxIm DL's *CALSTAT*, PixInsight's and Siril's calibration notes, and names such as *_cal.fits* or PixInsight's *_c.xisf*. Such a set shows ✓ *not needed - the lights are already calibrated (…)* in the Bias, Darks and Flats cells, gets no SkyFlat, raises no missing-calibration warnings - and its frames are never used to build a SkyFlat for your own lights.

Every SkyFlat is checked before it is used. If it may not be good enough - too few usable frames, grainy, a brightness range no vignetting has (nebulosity or a light-pollution gradient got in), large areas filled in - or it cannot be made at all because the master dark or bias is as bright as the sky (a light leak, or the wrong exposure or gain), SubZeroAstro stops and asks: **Proceed Without Flats** (the default), **Use the SkyFlat Anyway**, or **Cancel Stacking**. The reasons are listed in the box and in the log. A poor flat adds blotches or rings instead of removing them; without flats you can still fix dust donuts afterwards with *Mote Buster – Fix Dust Donuts* on Finishing Touches.

Meridian flips are handled. When the camera turned 180° with the telescope halfway through the night, the nebula sits on different sensor pixels before and after the flip. SubZeroAstro finds the two sides from the frames themselves and takes each pixel of the SkyFlat from the side that shows plain sky there - otherwise a faint dark copy of the nebula, turned upside down, would be printed into the picture. The stacking log says when this was done.

> **SkyFlats:** A SkyFlat is best from several targets. From a single target whose nebula fills most of the picture, part of the nebula could be mistaken for vignetting - the Flats note warns you. Real flats are still the best: take some when you can.

Calibration check. Every stack checks its dark (or bias) against the lights and writes a *Calibration check* line in the log: light background - dark = sky left. If a master does not fit - **brighter than the lights**, **uneven like a picture** (light leaked in while the darks were taken: lens cap, filter wheel, focuser or room light) or **practically zero** (saved on another scale) - a window says so when stacking finishes. Such a frame makes bright bands, borders or blotches that no later step can fix: remove it from the *Calibration frames* list, or take new ones (scope fully covered, same gain, offset, temperature and exposure as the lights).

> **Important:** If the Flats cell says the flats have **no matching bias or dark-flats**, the correction will be too strong: bright corners and dark rings. Add a bias or dark-flats for that camera and gain.

7.3 Stacking options

- **Reject outliers beyond 3.0 σ** - removes satellite trails, planes and hot pixels. The default suits almost everything.
- **Weight frames by noise** - better frames count more.
- **Colour cameras: Full resolution** (default) or half resolution (faster, less noise per pixel).
- **Save as** FITS and/or XISF; **Save new calibration masters** into your library.
- **Line up all filters of a target** (on) - all masters of a target share one pixel grid, ready to combine (LRGB, SHO).

Sharp stars to the corners. Every telescope bends the field a little, mostly at the edges. After a **meridian flip** (or between nights with another setup) that bending is turned round with the camera, so a plain shift-and-rotate alignment lines up the centre but leaves stars a pixel or two apart near the edges - doubled or smeared corner stars. SubZeroAstro measures each frame's stars against the reference and, when the edges are off, lines that frame up with a smooth distortion model instead. The stack log says how many frames were corrected.

7.4 Running the stack

Press ▶️ **Check & Stack**. Anything missing is listed first, with **Stack Anyway** or **Add Calibration Frames First…**. The log shows each step. If a run is interrupted, the next run offers **Continue With the Rest**. When it finishes, the button turns amber: ✔ **Stacked – Run Again?**. Stacking again never overwrites a master - new versions are saved as `_2`, `_3`…

7.5 Results

Masters are saved in your master lights folder, one subfolder per target, with a `_stacklog.txt` listing every frame used. **Open Master Lights Folder** shows them. Click **Continue to Image Processing ➔** to carry on.

7.6 Build Calibration Masters (no lights needed)

Took a fresh set of darks, flats or bias? Turn them into masters right away - **no light frames needed**: on page 1 choose **Stack › Build Calibration Masters…** (or click **Build Calibration Masters…** in the *Calibration frames* box on page 2). Choose the folder with the subframes - bias, darks, flats and dark-flats can all be mixed together in one folder (for example *RedCat51Calis*), or sit in subfolders. SubZeroAstro reads each file's header (and, if the header doesn't say, the file or folder name: *Darks*, *Flats*, *Bias*…) and sorts them:

- **Bias** - one master per gain and offset.
- **Darks** - one master per exposure, gain, offset and temperature (180 s and 300 s darks make two master darks).
- **Flats** - one master per filter (and night). Each flat is calibrated with dark-flats or short darks of the same exposure, or else a bias - from the same folder or already in your library.
- **Dark-flats** - saved as masters too, for next time.


The telescope (rig) name is taken from the folder name (*RedCat51Calis → RedCat51*) or the headers - check it, because flats are only used for lights from the same rig. Untick any set you don't want, then click **Build Masters**. Each master is saved to your calibration library

(*<library>/<rig>/Masters/<camera>/…*) with its settings in the name, and is used automatically whenever you stack lights with matching settings.

Every master is checked as it is built. You are warned when a dark or bias is **uneven like a picture** (light leaked in), a dark is **far brighter than the bias** (light, or the camera not cooled), a bias is **practically zero** (saved on a 0..1 scale or with a pedestal taken off), or flats are **over-exposed** (clipped) or **very dim**. A warned master is still saved, so you can compare - but better to retake that set.

> **Taking good darks:** Darks: cap the telescope (or take the camera off) and cover it, at night or in a dark room, with the filter wheel on a filter - not an empty slot. Match the lights' exposure, gain, offset and temperature.

8 Page 3 – Astro Image Processing



Page 3 after processing: masters (left), preview with crop box, step history, and the step settings (right)

8.1 Masters and target sets

The masters from page 2 are loaded automatically (or use **Add Masters…** / **Add Folder…**; with **Add Folder…** only the newest restack of each master is taken). Masters of the **same target** form one row - e.g. *NGC281 [Ha, OIII, SII]*. If they were stacked in separate runs the row says **will be lined up**: they are matched star-to-star onto one grid before anything else, and edges not covered by every filter are trimmed.

8.2 Crop

The yellow box on the preview is the crop. **Auto-crop** trims the ragged stacking edges; drag the box or its sides to adjust, or **Full image** to keep everything. The same box is used for **every filter**, so they stay aligned.

8.3 Plate solve

ASTAP finds where the picture points in the sky, using the position and pixel scale recorded in the masters. If it fails, tick **Blind solve** (slower, searches the whole sky).

8.4 Remove gradients

Removes light-pollution glow and uneven backgrounds. **GraXpert (AI)** is recommended; **Smoothing** 0.1 is a good default. **Correction: Automatic** picks for each master: *Subtraction* when the lights were flat-calibrated (your flats, a SkyFlat, or ready-made data such as Telescope Live) - light pollution and moon glow add to the picture - and *Division* only for a master stacked without any flats, where vignetting is still in it. The log says which was used. Without GraXpert a built-in model is used.

8.5 The XTerminators

Tool	What it does	Good starting settings
BlurXTerminator	Sharpens stars and detail	Sharpen Stars 0.50, Adjust Star Halos 0.40, Sharpen Nonstellar 0.50, Automatic PSF on (ready-made data such as Telescope Live: Sharpen Stars 0.55, Adjust Star Halos 0.50 - its clean signal takes firmer sharpening; the log says so)
NoiseXTerminator	Reduces noise (a light pass on unstretched data)	Denoise 0.6
StarXTerminator	Separates a **starless** and a **stars-only** image	Generate Star Image on; **Unscreen Stars off**. When the picture is big (over about 40 megapixels, e.g. after drizzle) or the stars are large (about 5 px or more) it works on a half-size copy with the most tile overlap, so the glow of a bright star fits its tiles and leaves no squares; the starless picture keeps its full detail (the log says so)

Hover over any setting for a plain-language explanation. **Unscreen Stars** should stay **off** here: the stars image is then simply *original minus starless* and is added back later (what Finishing Touches expects). Turn it on only if you will recombine stretched images with a screen blend in PixInsight.

8.6 Saving the results


- The first time you run, SubZeroAstro asks **where the processed images should go**: *Next to the Masters* (a `Prepared` folder), *Folder Used Last Time*, or *Choose a Folder…*. Each target gets its own subfolder.
- **Linear masters** as XISF and/or FITS (these are what you process further), and a **stretched preview** as TIFF, JPG and/or PNG in the chosen **Preview palette**.

8.7 Running and the step history

Tick the steps you want and press ▶️ **Run Selected Steps**. As each step finishes, the preview shows its result. Under **Step history**:


- **Show** - look at the result after any step.
- **Hold for Before** - press and hold to compare with the step before.

- **Go Back & Redo This Step** - change that step's settings and run again; only that step and the ones after it are redone.
- **Start Fresh** - forget the saved steps and start from the original masters.



Step history under the preview (example data)


When it finishes, the bar at the bottom reads ✔ **Ready for Processing Finishing Touches**, the run button turns amber (✔ **Done – Run Again?**) and the **Astro Image Processing – Complete** window opens. It says what comes next and, for PixInsight users, lists a recommended order of PixInsight processes (also saved next to your files).



The Astro Image Processing – Complete window

Click **Continue to Finishing Touches ➜**, or **Stop Here – Continue in PixInsight**.

9 Page 4 – Finishing Touches




Finishing Touches: the workflow (left), the recommended next step and the picture (example data)

9.1 How it works

1. The **workflow list** on the left shows every step for your kind of data: ✓ done, ➜ next, ○ later, – not needed, ◇optional.
2. The card at the top says what is **Recommended next** and why. Click **Do It** (or click any step in the list).
3. Pick a version: each step shows 3-5 small pictures of **your** image - gentle to strong, or different colour mixes. ★ marks the suggestion. **Clicking only previews it big** - nothing changes yet.
4. Optional: tick **Fine-tune** and move the plain-language sliders; the preview follows. **Reset** returns to the version you picked. Under the sliders the app says how much of the picture the setting visibly changes - if it says *This barely changes your picture*, there is little for that step to do on this target (no green cast to remove, no burnt-out core to tame), so the sliders have almost nothing to work on.
5. Press the green **Apply** to keep it - or **Cancel** to leave the picture exactly as it was. When the step is done the panel says so in green (**✔ … applied**), Apply disappears and an amber **✔ Applied – Next Step ➜** button takes you straight to the next recommended step - so after a break you can always tell whether a step was applied. Steps that can be repeated also offer **Apply Again**. The picture goes back to the whole view after every step.
6. Not quite enough? Many steps can be run again on their own result: after one of them the card shows **↻ Do It Again** (and a ✓ step in the list can be clicked to run it again). That works for Balance Colours, Remove Green Cast, Tame Bright Core, Curves, Saturation, Bring Out

Hidden Structure, Shrink Stars, Star Colours, Mote Buster, Darken the Sky Background, Final Noise Reduction, Flip, Final Crop and Spot Fix. One-way steps - combining, brightening, taking the stars out or putting them back, signing - are not repeated; use **Go Back to Here** to redo those.



Picking a version: Brighten the Image (Stretch) offers five strengths (example data)

Several masters per filter, or masters from different setups. When you load more than one master of the same filter (other nights, other cameras or telescopes), all of them are used: they are brought to the same brightness and averaged, the less noisy ones counting more. This works the same for colour cameras (each colour separately). With a colour camera and a **dual-band filter** (L-Ultimate, L-eXtreme …), masters taken **without** the filter are left out of the picture - broadband starlight would bloat the stars and wash out the Ha / OIII colours - and the log says so. Every master is first matched star by star to one reference master. Masters from another camera or telescope are bent slightly differently by their optics - most at the edges, which would give coloured double stars in the corners - so SubZeroAstro measures that distortion from hundreds of stars and corrects it. When the masters carry a plate solution (data from remote observatories usually does, and page 3 adds one with ASTAP), it guides the match: the masters are lined up from where they point on the sky and the stars fine-tune it, so even masters with few stars in common line up. The deepest master (the most hours) is the reference everything is lined up to. Masters that page 3 already put on one grid are used as they are, and starless masters (StarXTerminator on page 3) are measured together with their stars-only images, so the stars are always there to line up by. After lining up, every master is checked: its four corners are compared with the reference's, and one still more than 1.5 px off is left out (when its filter has other masters) - the note says *alignment check: … within X px in every corner*. A master whose stars cannot be matched to the others is left out (when its filter has other masters), so it can't cause double stars, and the picture is cropped to the area all masters cover. The note under the title says how many masters were combined, corrected or left out.

Looking closely. Scroll on the picture to zoom in (past the preview's own pixels the full-resolution picture is drawn), drag to move around, double-click to fit it again. ⛶ **Full Window** (next to *Show:*)

hides the step list, the panels and the log so the picture fills the window - press it again or **Esc** to go back. Both work at every step, also while looking back through earlier steps.

Bringing out one colour. *Adjust Colours* strengthens or calms one colour range at a time: pick a version (Boost blues, Boost reds, Blues and reds, Boost magentas, Calm the greens), then fine-tune with one slider per colour (1 = unchanged), *Brighten boosted colours* and *Protect the sky*. It is best done after *Colour Intensity* and before *Final Noise Reduction* - boosting a colour also boosts its colour noise, which the noise step then cleans - but it can be opened at any time later too (and run again).

9.2 Going back

- **Undo** (Ctrl+Z) removes the last step.
- **Show:** pick any earlier step to look at it; **Hold for Before** compares; **Go Back to Here** continues from that step.
- **Back to Start** returns to the original masters.
- Every step is saved. Opening the same masters again offers to **carry on where you left off**.

9.3 The steps

Which steps appear depends on your data. In typical order:

Step	What it does	PixInsight equivalent
Add Hydrogen Glow	Adds Ha to the red of an RGB set, without its stars. For a nebula *Subtle* (half the Ha) is suggested - the full Ha on top of the red made a red emission nebula like IC 1396 over-red; *Natural* or *Strong* for more. For a galaxy (M31, M33, M101, NGC 891…) it adds only the compact HII regions - the red knots along the arms	Continuum subtraction + PixelMath / NBRGBCombination
Combine Colour Channels	Builds colour from separate filters: RGB, LRGB, Hubble (SHO), HSO, HOO, Foraxx… and **HOO + faint OIII**, which lifts faint OIII-only glow (the Squid in the Flying Bat) while OIII that follows the Ha is left alone (slider: Faint OIII boost)	ChannelCombination / LRGBCombination; OIII minus scaled Ha in PixelMath
Choose a Colour Palette	Dual-band colour cameras: separates Ha and OIII (or SII and OIII) and offers HOO, Gold & blue, Foraxx…	PixelMath palettes
Balance Colours	Neutral sky and natural star colour. For a nebula that fills the frame, the sky level is taken from the darkest part of the picture (not the whole picture, which is mostly nebula), so the dark sky between the clouds comes out neutral instead of cyan	BackgroundNeutralization / colour calibration

Step	What it does	PixInsight equivalent
Remove Green Cast	Removes the green tint (or turns Hubble colours gold and blue). On colour data it measures the green first: with no green cast it suggests None needed (removing green anyway turns the picture pink). With HSO the green is your SII (None needed); with HOO it is the OIII teal (a light 25%)	SCNR
Mote Buster ◇	Fix Dust Donuts: finds the round shadows of dust and divides them out with a synthetic flat - the detail underneath comes back	A new flat, or DBE with division
Take Stars Out	Hides the stars so the nebula can be brightened strongly (instant if page 3 already separated them). For a planetary nebula, small background galaxies on the sky around it go with the stars, so they keep star colours instead of the nebula's	StarXTerminator
Clean Bright-Star Leftovers	Recommended only when something is found. StarXTerminator paints a smooth, grain-free square over each big star; once the nebula and the stars are brightened differently those squares show, often with bright bars along their edges and a leftover dot where a close double star was. This finds the painted squares by their missing grain and patches each with the surroundings' own texture. The square glow and the bars around it (what you see once the picture is brightened) are taken away while the nebula's own detail is kept. Four versions are offered: Clean, no glow (suggested - the star's own glow comes back with the stars), Clean, faint glow, Clean, soft glow, and Don't clean. Squares inside bright, structured nebula (a reflection nebula hugging the star) are left alone - use Spot Fix on those if they show. Small leftover star cores (a dot, sometimes in one colour only) are removed too, also inside nebula. For a nebula it also takes away the round glows star removal left with no square to find them by (a very bright star's halo, with a coloured ring where the filters' halos differ - IC 1396's Garnet Star - and the teal or blue blobs some filters leave around bright stars across the sky), and small coloured rings left around a star in front of bright nebula (the tip of IC 1396's Elephant's Trunk). Glows around a star in the middle of the picture, where the target is, are kept	CloneStamp

Step	What it does	PixInsight equivalent
Brighten the Image (Stretch)	The stretch - five strengths, three methods	STF / HistogramTransformation / GHS
Bring Out the Tail ◇ (comets)	Takes away part of the round glow of the comet's head (the coma), measured all the way round the nucleus, so the tail and ion streamers stand out	1/rho or azimuthal-median coma model + PixelMath
Reveal Comet Jets ◇ (comets)	Brings out jets and shells near the nucleus by comparing the picture with copies of itself turned a little around the nucleus (Larson-Sekanina); *Jets map only* gives the grey study picture. Best with the stars out	LarsonSekanina
Adjust Colours ◇	Bring out (or calm) one colour at a time - reds, yellows, greens, cyans, blues, magentas; grey and white stay as they are	ColorSaturation
Resolve the Cluster Core	Star clusters only: lowers the blended glow of a globular's centre (measured between the stars) and keeps every star, so the core shows as stars instead of a bright haze. Nothing is smoothed (unlike Tame Bright Core)	star mask + HDRMultiscaleTransform
Tame Bright Core ◇	Recovers detail in a burnt-out galaxy core or bright nebula: lowers the core's glow towards its surroundings and brings its structure back from the linear data; a nucleus burnt out even in the masters is rounded off so no hard white dot is left, and the stronger versions take in more of the area around the core (works best right after Brighten the Image (Stretch)). Only offered for star clusters: a globular's centre is overlapping stars, and taming it leaves dark holes	HDRMultiscaleTransform with a mask
Adjust Brightness & Contrast	Curves presets, sliders and a curve you can drag	CurvesTransformation
Balance Colours (star clusters)	For a star cluster the suggestion is Cluster glow warm white: the cluster's own light is made the warm white of its old stars (balanced on its stars alone a globular can come out blue-violet)	ColorCalibration
Colour Intensity	Richer or calmer colour; dark sky protected. The suggested strength follows the target and the data: Vivid for galaxies and Rich for nebulae in colour (broadband), Calmer for star clusters (their star colours are already strong), Slight for narrowband, planetary nebulae, comets and any picture whose colours are already strong (more looks neon)	Saturation curve

Step	What it does	PixInsight equivalent
Bring Out Hidden Structure ◇	Local contrast for dust lanes and cores; the empty sky is protected (fine-tune *Protect the sky*)	LocalHistogramEqualization
Brighten Stars Separately	Gentle star stretch - small, colourful stars. The star steps show the stars on their own; tick *Show the nebula behind the stars* to see them over the nebula	Star stretch
Shrink Stars	Makes stars smaller. Stars only a pixel or two wide (a wide-field scope) are shrunk gently, by as much as their size allows - shrinking them fully would wipe out most of a crowded star field	Star reduction / MorphologicalTransformation
Star Colours	Natural star colours (estimated from your data) or clean white stars - recommended for narrowband	Star colour correction
Put Stars Back	Blends the stars back at the strength you pick	PixelMath screen blend
Darken the Sky Background ◇	Darker (or lighter) sky without dimming the nebula, faint dust or stars; also evens out a brighter corner or side. Much darker is suggested; Darker for planetary nebulae (keeps the faint outer halo); Darkest for star clusters, which have no faint nebulosity to keep	ABE/DBE model + PixelMath
Final Noise Reduction ◇	A last, light NoiseXTerminator pass on the finished picture (needs the RC-Astro CLI)	NoiseXTerminator
Flip or Rotate the Picture ◇	Flip Horizontally and/or Vertically (each press toggles), Rotate 90° Clockwise or Counter-clockwise (each press turns once more) - the saved pictures are turned too	FastRotation
Final Crop ◇	A last clean-up crop; finds ragged or off-colour edges for you	DynamicCrop
Spot Fix ◇	Click dust donuts, satellite remnants or hot pixels to patch them	CloneStamp
Sign Your Picture ◇	Your signature - and the target name above it - in a corner or wherever you drag it	Annotation

◇= optional: offered in the list but not pushed by *Recommended next*.

9.4 Mote Buster: dust donuts

Dust on a filter or on the camera window casts round shadows - **dust donuts** (rings with a reflector, discs with a refractor). A good flat removes them; when the flat is missing or no longer matches, **Mote Buster – Fix Dust Donuts** helps. A dust shadow does not wipe anything out: it lets through the same fraction of light everywhere inside it, nebula included. So SubZeroAstro measures each donut's shadow ring by ring - in 16 directions against the sky just outside it, levelled for any gradient

- builds a **synthetic flat** just for that donut and divides it out, the way a uniformity (flood-field) correction works. The detail underneath comes back instead of being painted over.

- Open **Mote Buster** while the picture is still unstretched (it comes before *Take Stars Out*). The donuts it finds in the sky are already circled in yellow.
- Donuts on bright nebulosity are not searched automatically (a gap between filaments could look like one) - **click** those yourself. Click to place a circle, then **turn the mouse wheel to size that circle** while you watch (just cover the donut). Click a circle to pick it again (it turns blue) and drag to move it; to remove it, **right-click** it, **Control-click** it on a Mac (Option- or Command-click also work), or pick it and press **Delete**. A dashed ring follows the mouse to show the size of the next circle. Clicks need not be exact: each circle is centred on its donut automatically.
- **Bright rings count too.** When the dust moved between the flats and the lights (or a filter was cleaned), the flat over-corrects: you get a *brighter* ring, often with a dark centre, and with mono filters it is usually in one filter only - a coloured (e.g. purple) halo. Mote Buster finds and fixes these as well, dimming the bright part and lifting the dark part. Every colour is centred and measured on its own (the same speck sits a little differently in each filter), and lopsided rings are followed too.
- Check the preview, then press the fix button. Mote Buster stays open on the **fixed picture**, so you can circle any donuts that are left and fix again - as many rounds as you like (each round is its own step; *Undo Last Step* takes back the last one). Press **✔ Applied – Next Step ➜** when you are happy. Spot Fix works the same way. For small specks (hot pixels, satellite remnants) use **Spot Fix** instead.

9.5 Stars: take out, brighten, colour, put back


Stars and nebula look best when processed separately. **Take Stars Out** hides the stars (the picture shows the nebula alone); the nebula steps follow; then **Brighten Stars Separately**, **Shrink Stars** and **Star Colours** work on the stars (their previews show the stars); **Put Stars Back** recombines them. If you **Skip** Take Stars Out, the stars simply stay in the picture.

9.6 Darker sky, Final Crop, Spot Fix and your signature

- **Darken the Sky Background** is for a sky that looks grey or washed out. Pick *Slightly darker*, *Darker*, *Much darker* or *Lighter* (each shows the sky's brightness before and after), then fine-tune with **Sky darkness**. It works like PixInsight's background extraction: SubZeroAstro maps the sky glow across the picture (a nebula cannot push that map up) and takes part of it away. Everything that shines above the sky - nebula, faint dust, stars - keeps exactly the brightness it had **above the sky**, so faint filaments stay visible and stars are not dimmed. A brighter corner or side loses more, so the sky also evens out. Darker skies show grain more: a lighter setting often looks more natural.
- **Final Noise Reduction** runs NoiseXTerminator once more on the finished picture - most useful right after a darker sky, which shows grain more. The choices (*Light*, *Medium*, *Strong*) are shown at full size on the busiest part of the picture so you can judge the grain; **Strength** fine-tunes it. (BlurXTerminator is not offered here on purpose: it is made for unstretched data and already runs on page 3. For more crispness at the end, use **Bring Out Hidden Structure**.)
- **Final Crop** shows a yellow box on the whole picture, already placed where it found ragged or off-colour edges. Drag it or its sides (**Found Edges** / **Whole Picture** reset it) and press **Crop to the Box**.
- **Spot Fix**: click the middle of a blemish - a circle appears - then **turn the mouse wheel to make that circle bigger or smaller** until it just covers the blemish. Click a circle to pick it again (it turns blue) and drag to move it; to remove it, **right-click** it, **Control-click** it on a Mac

(Option- or Command-click also work), or pick it and press **Delete**. A dashed ring follows the mouse to show the size of the next circle. Circles go from a hot pixel to a large satellite blob or halo (up to 700 pixels in radius, like Mote Buster's), and the patch blends in smoothly with the sky's own slope and grain even when it is big. **Stars inside the circle are kept**: they are lifted off, the sky under them is patched, and they are put back on top - as bright as they really are, since a dust donut dims its stars too. Only the thing at the middle of the circle (what you clicked on - a hot pixel, a satellite remnant, an unwanted star) is removed. Then **Fix the marked spots**.

- **Flip or Rotate the Picture** (optional): press **Flip Horizontally** (left ↔ right) and/or **Flip Vertically** (upside down) - each press flips the preview, pressing again flips it back (both together turn it 180°). **Rotate 90° Clockwise** and **Rotate 90° Counter-clockwise** turn it a quarter turn per press (a portrait picture becomes landscape). When it looks right, press **Keep This Orientation**. Useful to match how the object usually looks in charts and other pictures. If the picture is already signed, the preview turns the signature too, but when you keep it the signature is put back on top the right way round, in the same place (steps done after signing - crop, Spot Fix, colour - are done again underneath it).
- **Sign Your Picture**: type your name once (it is remembered) and, if you like, a **Target name** for a line above it - filled in for you (for example *NGC 281 "Pacman Nebula"*) and remembered for each target; empty it for none. Pick a font - *Elegant script*, *Handwritten* or *Classic* - a corner and a colour, and fine-tune size, opacity and distance from the edge. To put it anywhere else, **drag the dashed box** on the picture (or click where it should go); *Place* then says *Where I dragged it*. Do this last: the signature becomes part of the picture.



Sign Your Picture: signature text, corner, colour and three fonts (example data)

9.7 Saving and sharing

- **Save the Picture…** - TIFF (16-bit), JPG, PNG, XISF or FITS. All the files of one picture go into **their own folder inside the one you pick**, named after the target and telescope - for example *Final Astro Pics/M101_RedCat51/* holds M101_finished.tif, .jpg, .fits and the description. The folder you pick is remembered: each target keeps its own, and a new target starts in the folder you used last. Tick **Also save a short description of the target** to save *<target>_about.txt* next to the pictures: the opening paragraphs of its Wikipedia article plus **facts from SIMBAD**

(the professional astronomy database at CDS, Strasbourg) - the kind of object, its position (RA / Dec) and brightness. Faint objects without a Wikipedia article still get the SIMBAD facts. It is shown first so you can edit it (or type your own when there is no internet), and both sources are credited. **Add a small "Processed with SubZeroAstro" credit** (ticked at first) puts that line in small, light-grey, see-through letters in the bottom-left corner of the TIFF, JPG and PNG pictures - or the bottom-right corner if your signature is bottom-left. XISF and FITS files are never marked, and untick the box to leave the pictures clean (the choice is remembered; pictures shared to AstroBin follow it too).

- **Save Project As… / Open Project…** - keep every step in a folder of your choice and carry on later. A saved project can also be opened **right from the start**: the **Open a Saved Project…** button in the Load Light Frame Data window (or File › Open a Saved Project, Ctrl+Shift+O, on page 1) goes straight to Finishing Touches on its last step. Pick the project's folder or the folder you saved it into. **Keep the masters with the project?** (asked when you save; Yes by default) copies the masters the project uses - with their star images and stack logs - into a *Masters* folder inside the project, so one folder holds everything for the target and you can move or back it up as a whole; redoing page 3, adding nights and Share to AstroBin keep working. It also keeps the stacked master behind each page 3 (*_prepared*) master, so you can redo page 3 from scratch. Your original masters are copied, never moved or deleted - delete them yourself once the project reopens fine. A project folder with its masters inside can be copied between a Mac and a PC and still finds them. For a project saved before this option existed: open it, choose Save Project As… and pick the same folder.
- **Already stacked, no saved project?** Use **Process Existing Masters…** in the same window (or File › Process Existing Master Lights…, Ctrl+Shift+M): pick your master lights - e.g. the D1 and D2 masters of one target - and you go straight to Astro Image Processing (page 2) without restacking. Masters are saved next to your lights' folder, named like *IC1396_Askar D1_Master_2026-06-29_to_2026-07-03.fits*; each restack adds _2, _3, … - from a folder only the newest is used. WBPP masters from PixInsight open the same way.
- **A PixInsight project?** File › **Open a PixInsight Project…**: pick the project's *.pxiproject* folder (or the folder it is in). Each picture in it - as PixInsight left it, including changes kept inside the project - is saved as an XISF file in *<project>_SubZeroAstro* next to the project and opened on Astro Image Processing; masks are left out. If the project was moved, put the pictures' original files next to it so they can be found.
- **Share to AstroBin…** - saves an upload-ready JPG (and optional TIFF) plus an **acquisition CSV** with every night's subs, exposure, gain, temperature and FWHM, then opens AstroBin's upload page. Upload the picture, and on the *Acquisition* step choose **Import CSV**.
- **Stop Here – Continue in PixInsight** - see 5.4.

9.8 Starting your next target

When a picture is finished, click the teal ↻ **End this Project and Start New Project** button at the top right of Finishing Touches. SubZeroAstro asks first - and if you have not saved the picture yet, offers **Save the Picture First…**. Then every page and image closes, the helper programs are checked again, and you are back on **page 1 (Quality and Cull)** with the **Load Light Frame Data** window open, ready for the next target's light frames: cull, stack, process and finish, from the beginning.

> **Your work is safe:** Nothing on your disk is deleted. Your masters, finished pictures and every Finishing Touches step stay where they are: open the same masters on Finishing Touches later and the project carries on where you stopped.

10 Recipes for common setups

10.1 Colour camera (OSC), broadband

Cull › Stack (flats + darks or bias) › page 3: crop, plate solve, GraXpert, BlurX, StarX › page 4: Balance Colours, Remove Green Cast, Take Stars Out, Brighten, Curves, Colour Intensity, star steps, Put Stars Back, Final Crop, Sign.

10.2 Colour camera with a dual-band filter

Make sure the filter is set (page 1, *Filter used* or *Set Filter Name*) so the matching flats are found. On page 4 the first step is **Choose a Colour Palette** (HOO, Gold & blue, Foraxx…), and **Star Colours** is recommended so the stars are not all teal. Two dual-band filters of the same target - **L-Ultimate + L-Synergy** or **Askar D1 + D2** - are combined into a full **SHO** set automatically: the red pixels of the first give **Ha**, those of the second **SII**, and the green and blue pixels of both give **OIII**. Those pixels also catch a little of the red line, so each OIII estimate carries some Ha or SII; because both filters see the same OIII, SubZeroAstro measures that leakage from your data, for each filter (real OIII is never negative, so where the Ha or SII is brightest the lowest OIII-to-line ratio is the leak - typically 5-9 %, never more than 10 %), takes it out, and combines the two OIII estimates weighted by each filter's exposure time (never less than 20% for either, since both hold real OIII) (the page 4 log shows the numbers). *Combine Colour Channels* then offers the narrowband palettes - **Hubble (SHO)**, HSO, HOO + SII … - exactly as for a mono SHO set. Filter names such as *D1*, *Askar D2*, *Ha/OIII* or *SII-OIII* are all recognised.

10.3 Mono camera: LRGB

RGB (or LRGB) + Ha of a galaxy: SubZeroAstro recognises galaxies by name (M31, M33, M51, M81, M101, NGC 891, IC 342… or names like *Andromeda* or *Pinwheel*). **Add Hydrogen Glow** then recommends **HII regions**: the starlight - and the galaxy's own smooth light - is subtracted from the Ha, and only the compact hydrogen knots that clearly stand out are added to red. They stand out crisply against the blue arms without tinting the whole galaxy pink. Tick **Show the hydrogen regions** to see exactly what is added; *All hydrogen glow* adds everything, for galaxies set inside nebulosity.

Each filter is stacked separately on page 2 (one row each; keep *Line up all filters* on). Load all masters together on page 3 - they must appear as **one row**. Page 4 starts with **Combine Colour Channels** (RGB or LRGB).

10.4 Mono camera: narrowband (SHO)

As 10.3 with Ha, OIII and SII. Filter names from filter wheels such as *Ha 7nm*, *H-alpha*, *O*, *S* or *Antlia Ha 3nm Pro* are recognised. Page 4: **Combine Colour Channels** › Hubble (SHO), Foraxx or HOO; then Remove Green Cast - for Hubble (SHO) and Gold & blue it suggests **Remove only** for Hubble (SHO) - plain SCNR, the typical gold and blue - and also offers **Gold 50 / 75 / 100%**, which turn the green (your Ha, the strongest signal) gold instead of deleting it, so the bright structure keeps its brightness (suggested for Gold & blue) - and **Star Colours** before Put Stars Back.

10.5 Smart telescopes (Seestar, DWARF, Vespera)

Raw subs are recognised as lights automatically, with no calibration needed (the telescope calibrates on board). Alt-az field rotation is handled during alignment and the rotated edges are cropped. Because the frames turn against each other, the camera's own fixed pattern (warm pixels and colour blotches that stay put on the sensor) would stack into circular swirls; without darks the

stacker measures that pattern from the lights themselves and takes it out of every frame (it says so in the stack log). Dithering, if your telescope offers it, helps even more. Seestar *Stacked_…* files from several nights can be combined on page 2, or a single stack can go straight to page 3.

DWARF calibration frames: the DWARF keeps its own in a *CALI_FRAME* folder - bias and flats as *tele_0001.fits* with nothing in the header to say what they are, darks as masters named like *dark_exp_15.000000_gain_60_bin_1_37C_stack_20.fits*. Add that folder on page 2 (**Add Calibration Folder…**): the bias and flats are recognised from their folders (or, copied out, from their headers - not pointed at the sky, a near-zero exposure is a bias), the dark's exposure, gain, temperature and frame count from its name. The DWARF's flats record no filter; they are used for its lights. Page 2 also leaves out the DWARF's rejected frames (*failed_…*) and its own stacks (*stacked…*) when they sit among the subs.

10.6 Comets

A comet moves against the stars while you image it, so a normal stack (lined up on the stars) smears it, and a stack lined up on the comet trails the stars. SubZeroAstro does both and joins them. It recognises a comet by its name - or when you pick **Comet** as the type in Fast Track, e.g. for frames named *Snapshot* - (*C/2023 A3*, *12P/Pons-Brooks*, *161P Hartley-IRAS*, or any name containing *comet*) - page 2's plan shows ☄ for it. While stacking it finds the comet's head in every frame, works out its motion from the frames' times, makes a **second stack that follows the comet** (the stars are masked out of every frame first, so they leave no dotted trails across the tail; inside the comet's area they are put back from the star stack), and saves three masters: the main one with **sharp stars and a sharp comet**, plus **_Comet** (comet only) and **_Stars** (star-aligned) next to it. The log says how far the comet moved.

When the comet barely moved during the session (under 3 pixels - common with short sessions), or it is too faint or too uncertain to follow, only the ordinary stack is saved and the log says why. Long sessions of several frames per minute work best. On page 4 the main master goes through the usual steps; for a comet **Curves › Lift faint detail** and **Darken the Sky** are recommended (for a comet it takes one even sky level away, so the faint tail across the picture keeps its brightness), while star steps (*Take Stars Out*, *Shrink Stars*) are optional.

10.7 Target types

From the target's name SubZeroAstro works out what kind of object it is - **galaxy, nebula, planetary nebula, star cluster or comet** - and shows it in the title of page 4. The type only fine-tunes the recommendations; **no step is ever taken away**. Galaxies get *Tame Bright Core* (right after brightening - skip it if the core already shows its detail) and *Local Contrast* recommended, and HII regions in *Add Hydrogen Glow*; other targets get Tame Bright Core recommended only when a burnt-out core is found; star clusters make star removal and shrinking optional (the stars are the subject); comets get a comet stack on page 2. When the name gives nothing away, the usual workflow for your data applies. Tips for each kind of target are in chapter 15.

10.8 Step-by-step recipes: how to use them

The next sections walk through each kind of data from start to finish, with the choice to pick at every step. They are a **starting point**, not rules: every step shows its versions side by side, so trust your eyes when another one looks better. Pick the section for your data (what you captured with), then check **10.15** for what changes with your kind of target (galaxy, nebula, planetary nebula, cluster).

Pages 1-3: the same for every recipe

1. **Page 1 - Quality and Cull:** load the lights, press *Auto-Flag › Semi-aggressive* (or *Less aggressive* for a short session), look through the flagged frames and reject them. Set the filter name if the files don't carry it.

2. **Page 2 - Calibrate and Stack:** check every row has ✓ for darks (or bias) and flats - add them with *Add Calibration Folder…* or set your calibration masters folder. Keep **Line up all filters of a target** on, so every filter of one target lands on the same pixels. Press *Check & Stack*.
3. **Page 3 - Astro Image Processing:** all masters of one target must show as **one row**. Crop inside the area every frame covers (*Auto-crop* does it; a note in the log warns when a hand-drawn crop goes past it), keep plate solving and gradient removal on, **BlurXTerminator** *Sharpen Stars* 0.50 / *Adjust Star Halos* 0.40, **NoiseXTerminator** about 0.6, and **StarXTerminator** on (it makes *Take Stars Out* instant). Press *Run Selected Steps*, then *Continue to Finishing Touches*.

On page 4 the steps below are listed in order in *Your workflow*; ◇marks optional ones. Each recipe names the version to pick - the ★ the app suggests is usually the same.

10.9 Recipe: colour camera, broadband (RGB, no filter or UV/IR cut)

Best for galaxies, star clusters and reflection nebulae - all the starlight colours are kept.

1. **Balance Colours › Stars white** (neutral). *Stars white, warmer / cooler* only if you prefer that look.
2. **Remove Green Cast › 25-50 %** - a colour camera leaves a little green; real green almost never exists in space.
3. **Mote Buster** ◇if dust donuts show (check the circles, right-click or Control-click any that are not donuts).
4. **Take Stars Out**, then **Brighten the Image (Stretch) › Medium** (method *Automatic*; *Colour-preserving* keeps star and core colours better).
5. **Tame Bright Core** - galaxies: *Medium*; other targets only if the centre is burnt out.
6. **Curves › More contrast** or **Brighter highlights**. Use *Lift faint detail* only for deep data.
7. **Colour Intensity › Slight** or **Rich** (the sky is protected).
8. **Adjust Colours** ◇- a gentle *Boost blues* for galaxy arms or reflection nebulae; *Smooth colour transitions* 0.2-0.3 if the colour looks blotchy.
9. **Bring Out Hidden Structure › Subtle** or **Moderate** (keep *Protect the sky* about 0.85).
10. **Brighten Stars Separately › Medium** (*Keep bright stars small* stays on), **Shrink Stars › Moderate**, **Star Colours › Natural**, **Put Stars Back › 80-100 %**.
11. **Darken the Sky Background › Slightly darker** or **Darker**, then **Final Noise Reduction › Medium**.
12. **Final Crop**, **Spot Fix** for any specks, **Sign Your Picture**, *Save the Picture…*

10.10 Recipe: colour camera with one dual-band filter (HOO)

For emission nebulae with L-eXtreme, L-Ultimate, L-eNhance, Askar D1/ColourMagic and similar: red pixels record Ha, green and blue record OIII.

1. **Choose a Colour Palette › HOO** (natural red and teal). Alternatives: *HOO (vivid)*, *Gold & blue* (Hubble-like), *Foraxx (dynamic)*.
2. **Mote Buster** ◇if needed, then **Take Stars Out**.
3. **Brighten the Image (Stretch) › Medium** (stronger is fine with the stars out).
4. **Remove Green Cast** - *HOO* rarely needs much; *Gold & blue* offers **Gold 100 %**, which turns the green gold instead of deleting it.
5. **Tame Bright Core** ◇for a bright centre (Bubble, Orion, Lagoon).
6. **Curves › More contrast** or **Lift faint detail**.
7. **Colour Intensity › Rich**.

8. **Adjust Colours › Blues and reds** separates the teal OIII from the red Ha; *Calm the greens* for leftover green; *Smooth colour transitions* 0.3 if the colour is grainy.
9. **Bring Out Hidden Structure › Moderate**.
10. Stars: **Brighten Stars Separately › Medium**, **Shrink Stars › Moderate**, **Star Colours › Natural** (a dual-band filter makes all stars one colour - this gives them back their blue-to-orange range), **Put Stars Back › 80-100 %**.
11. **Darken the Sky**, **Final Noise Reduction**, crop, sign, save.

> **Tip:** A galaxy through a dual-band filter: pick **As captured** (or *HOO*), keep *Colour Intensity* at *Slight*, and expect strong red HII knots but little blue in the arms - the filter blocks most of the starlight that carries a galaxy's colour. Long integration helps; a few hours of broadband data give the full colour.

10.11 Recipe: colour camera with two dual-band filters (SHO)

Askar D1 + D2, or L-Ultimate + L-Synergy, of the same target: SubZeroAstro builds Ha, OIII and SII and the page 4 log shows the line leakage it took out and how the two OIII estimates were combined.

1. Stack each filter on page 2 (one row each); load both masters together on page 3 - **one row**.
2. **Combine Colour Channels › Hubble (SHO)** (or *Foraxx*, *HOO + SII*).
3. **Mote Buster** ◇, **Take Stars Out**, **Brighten the Image (Stretch) › Medium**.
4. **Remove Green Cast › Remove only** - plain SCNR, the typical Hubble-palette gold and blue; *Gold 100 %* turns the green (your Ha) gold instead of deleting it, for a brighter, warmer look.
5. **Tame Bright Core** ◇, **Curves › More contrast**.
6. **Colour Intensity › Slight** - the SII and OIII from a colour camera are weak, and stronger saturation turns their noise into speckle.
7. **Adjust Colours**: Blues about 1.2-1.3, *Smooth colour transitions* **0.4-0.6** (this is what keeps the background calm).
8. **Bring Out Hidden Structure › Subtle**, then the star steps (**Star Colours › Natural**), **Darken the Sky**, **Final Noise Reduction › Medium or Strong**.

10.12 Recipe: mono camera, RGB or LRGB

Galaxies, star clusters and reflection nebulae with separate R, G, B (and L) filters. L carries the detail, RGB the colour - so RGB can be shorter or binned.

1. **Combine Colour Channels › LRGB** (or *RGB* without L).
2. **Balance Colours › Stars white**, **Remove Green Cast › 25-50 %**.
3. **Mote Buster** ◇, **Take Stars Out**, **Brighten the Image (Stretch) › Medium** - for a galaxy *Gentle* (*Colour-preserving* keeps a galaxy's core colour; a stronger stretch turns its faint outer disk into fog).
4. **Tame Bright Core** - galaxies *Medium*; an L filter often needs it.
5. **Curves › Brighter highlights** or **More contrast** - for a galaxy *Punchy (S-curve + lift)*.
6. **Colour Intensity › Slight** or **Rich** - for a galaxy *Vivid*.
7. **Adjust Colours** ◇- *Boost blues* 1.2-1.4 for spiral arms, *Smooth colour transitions* about 0.3 (RGB is usually noisier than L).
8. **Bring Out Hidden Structure › Subtle** or **Moderate** (sky protected).
9. Star steps (**Star Colours › Natural** or *As they are*), **Darken the Sky › Slightly darker**, **Final Noise Reduction**, crop, sign.

10.13 Recipe: mono camera, LRGB + Ha (galaxies)

The classic galaxy set: broadband colour with the red hydrogen (HII) knots along the arms added from Ha.

1. **Add Hydrogen Glow › HII regions - natural** - the starlight is taken out of the Ha first, so only the compact pink knots are added to red, not a pink wash over the disc. *Strong* if the knots are the show-piece; tick *Show the hydrogen regions* to see what is added.
2. **Combine Colour Channels › LRGB**.
3. **Balance Colours › Stars white** (not warmer - neutral keeps the blue arms), **Remove Green Cast › 25-50 %**. When the field's stars would leave the galaxy's centre blue (few, faint stars - a field far from the Milky Way), **Galaxy centre warm white** is suggested instead: the centre's old stars are a warm white and the arms stay blue.
4. **Take Stars Out**, **Brighten the Image (Stretch) › Medium** or *Gentle*, method *Colour-preserving*.
5. **Tame Bright Core › Medium**.
6. **Curves › Brighter highlights** (avoid *Darker background* - it brings out faint background blotches).
7. **Colour Intensity › Slight** or **Rich**; **Adjust Colours › Boost blues** 1.2-1.4 with *Smooth colour transitions* 0.3.
8. **Bring Out Hidden Structure › Subtle** or **Moderate** (sky protected).
9. Star steps, **Darken the Sky › Slightly darker** (keep the faint outer arms), **Final Noise Reduction**, crop, sign.

> **Order matters:** **Add Hydrogen Glow comes before Combine Colour Channels** - it works on the separate R and Ha images. Combined without it? The step stays in the list marked ↷ (passed by): use **Back to Start** (or pick *Start (masters loaded)* under *Show* and press *Go Back to Here*), then Add Hydrogen Glow, then Combine. Also loaded OIII and SII masters of the galaxy? It is still processed as LRGB + Ha; the SHO and HOO palettes stay available under Combine Colour Channels.
>
> **Tip:** Look for: a yellow-white core, blue arms and pink-red knots. A pink galaxy means the Ha is too strong - go back to *HII regions - natural*. Typical time split: L 40-50 %, R, G and B equal, Ha a few hours.

10.14 Recipe: mono camera, narrowband (SHO or HOO)

1. **Combine Colour Channels › Hubble (SHO)** - or *HOO* with only Ha and OIII, *Foraxx (dynamic)*, *HOO + SII*, *HSO*.
2. **Mote Buster** ◇- with filters, each has its own dust: bright rings or coloured halos are fixed per colour.
3. **Take Stars Out**, **Brighten the Image (Stretch) › Medium**.
4. **Remove Green Cast › Remove only** for SHO (the typical gold and blue; *Gold* for a warmer look); plain removal for HOO.
5. **Tame Bright Core** ◇for a bright centre, **Curves › More contrast**.
6. **Colour Intensity › Rich**; **Adjust Colours › Blues and reds** to separate the gold and blue; *Smooth colour transitions* 0.2-0.3.
7. **Bring Out Hidden Structure › Moderate**.
8. Star steps - **Star Colours › Natural** is recommended (narrowband makes stars magenta or one colour), **Put Stars Back › 80-100 %**.
9. **Darken the Sky**, **Final Noise Reduction**, crop, sign.

10.15 Adjusting any recipe for your target

Target	What changes
Galaxy	*Tame Bright Core* (Medium) after brightening; *Colour-preserving* brightening; *Curves › Brighter highlights*; *Darken the Sky › Slightly darker* only (keep the halo and outer arms); a little *Boost blues*. See 15.2.
Emission nebula	Stars out before brightening, then brighten strongly; *Bring Out Hidden Structure › Moderate*; *Adjust Colours › Blues and reds*; *Tame Bright Core* only for a bright centre. See 15.3.
Planetary nebula	Small and bright: *HOO* (or SHO), *Brighten › Gentle* with *Colour-preserving*; *Tame Bright Core* comes after *Curves* and tames the bright ring to show the inner structure; skip *Remove Green Cast* if the OIII looks green-teal; *Smooth colour transitions* is on; crop tightly. See 15.4.
Dark nebula / faint dust	*Curves › Lift faint detail*, a light *Bring Out Hidden Structure (Subtle)*, no strong sky darkening - the dust *is* the faint part. See 15.5.
Star cluster / reflection nebula	Stars are the subject: *Take Stars Out* and *Shrink Stars* are optional, *Star Colours › Natural, vivid*, *Put Stars Back 100 %*; reflection nebulae: *Boost blues*. See 15.6.

11 Troubleshooting and questions

11.1 Common questions

Problem	What to do
Windows: "Windows protected your PC"	Click **More info › Run anyway** (3.1).
Mac: "can't be opened" or "is damaged"	Right-click › Open, or the Terminal command in 3.2.
Frames show **No filter**	Set the filter on page 1 (*Filter used* or *Frame › Set Filter Name…*). Needed to match flats and to offer the right palettes.
Flats column is ✗ red	No flats for that filter/rig. Change the row's Filter to match your flats, or add the flats folder.
Bright corners and dark rings	Flats calibrated without bias/dark-flats, or flats that don't match. Check the ⚠️ note on page 2 and add a bias or dark-flats (7.2).
Filters of one target in separate rows on page 3	Check that the target names match (OBJECT). Masters stacked in separate runs are lined up automatically.
No *Combine Colour Channels* on page 4	The masters were not loaded together, or a filter name was not recognised - the log lists the filters it found.
Plate solve failed	SubZeroAstro already retries with other field sizes (wrong binning or a reducer in the header are the usual cause; when the header has no focal length at all - Telescope Live files say 0 - typical fields from 0.25° to 4.5° are tried, and the one that works is reused for the other masters). If it still fails, read the log line: for small fields (under about 0.5°, e.g. galaxies with long focal lengths) ASTAP needs the **D50** or **D80** star database; with no pointing in the header tick **Search the whole sky**. A failed solve only means the picture has no sky coordinates - every other step works as usual.
Tools show *not found*	Click **Browse…** and point at the program, or use **Settings › Your Tools…** (4.1).
Amber banner on page 1	A helper program is missing or not licensed. **Set Up…** fixes it; **Don't Remind Me** if you don't use it (4.1).
An XTerminator says *not licensed*	Click **RC-Astro Licences…** on page 3 and activate with the code from your rc-astro.com account (4.1).
Frames skipped: *could not match the star field*	Usually clouds, trailing or a badly out-of-focus frame. Frames saved mirror-image (some capture programs do this) are recognised and lined up automatically.
XTerminators very slow	Choose your graphics card under **RC-Astro device** (4.1).
Slow on a network drive	Use *Star measurement: Fast*; hide the image (Ctrl+I); results are cached for next time.
Something went wrong mid-run	Restart: SubZeroAstro offers to resume from its saved progress.

Problem	What to do
Coloured specks (single red, green or blue pixels) all over the picture	Hot pixels that survived stacking - they do when the frames were not dithered (common with remote-observatory data), because they sit on the same pixel in every frame. Since 0.9.54 **Remove hot pixels** (page 2, on by default) replaces them in every frame before stacking; re-stack such data.
Doubled stars with frames from a remote observatory (or any camera with many hot pixels)	Fixed in 0.9.51. Calibrated frames that were not dithered can keep hundreds of hot pixels, and those sit in the same place on the sensor in every frame. Before 0.9.51 most of the "stars" found could be hot pixels, so frames from different nights could be lined up on the sensor instead of the sky - giving doubled stars. Now single-pixel spikes are ignored when stars are matched (a real star always spills light into its neighbours). Re-stack such data with 0.9.51 or later.
A frame shows *This file is damaged: its picture data was converted to text*	The file was downloaded or copied in a way that treated it as text: every byte the text conversion didn't understand was replaced, so the file is about twice its proper size (a 3056×3056 16-bit frame should be about 18.7 MB) and the picture is noise - while the header still reads fine. Such frames can never be aligned or stacked. Download them again (another browser, or as a zip) and check the file size.
Half the frames show *unreadable*, names starting with `._`	Those are hidden macOS copies (AppleDouble files) that a Mac writes next to every file on a NAS or external drive - not pictures. Version 0.9.31 and later ignore them; with an older version, delete the `._` files or turn off *Include subfolders*.

11.2 Getting help and reporting problems

Zip My Logs: the button at the top left of every page (also **Help › Zip My Logs**) puts the log of every open page, the stack logs of your masters, page 3's processing report and a short note about your computer (SubZeroAstro version, system, screen, which helper programs were found) into one zip on your Desktop and shows it - text only, no pictures. Attach that zip to your message: it is the quickest way to get help.

After a crash or a frozen computer: every session also writes its log to disk as it goes (Windows: *%LOCALAPPDATA%\SubZeroAstro\Logs*, Mac: *~/Library/Logs/SubZeroAstro*), with a note every 30 seconds of how much memory the app uses and how much the computer has left. Start SubZeroAstro again and press **Zip My Logs**: the zip includes the last sessions, and one that ended badly is marked *ENDED_BADLY*.

Updates: when a newer SubZeroAstro is published, a slim blue bar at the top of page 1 says so (checked quietly a few seconds after start-up). **What's New** shows what changed, **Update Now** downloads the new version, closes SubZeroAstro, puts the new files in place and starts it again - your settings and projects are kept - and **Skip This Version** hides the bar until the next one. Let any stacking or processing finish first. **Help › Check for Updates…** checks right away; untick **Help › Check for Updates at Startup** to stop the automatic check. If SubZeroAstro is in a folder it can't write to (or runs from Python), the button says **Download…** and opens the download page instead; hover over it to see why. On a Mac, keep SubZeroAstro.app in **Applications** (or another folder of yours) - an app opened straight from the Downloads folder runs from a hidden read-only copy and can't update itself. On Windows the update can only replace the program while no other SubZeroAstro is running - if an automatic organize run is working in the background (or a second

window is open), Update Now says so; let it finish, then update. If an update still can't replace a file, SubZeroAstro starts the version you had and tells you.

Note the version (in small print under the name at the top of every page, or **Help › About**) and take a screenshot of the page and its log. For problems and ideas, press **Zip My Logs** and send the zip with a short note. Advanced: `SubZeroAstro --selftest` runs the built-in self-test.

12 Keyboard shortcuts

12.1 Page 1 – Quality and Cull

Keys	Action
↑ ↓ ← →	Previous / next frame
Shift + arrows, Shift / Ctrl + click	Select several frames
X or Delete	Reject / restore the selected frame(s)
F	Flag / unflag
Shift+X	Reject all flagged frames
D	Clear all flags
Ctrl+F	Auto-Flag…
Ctrl+Z	Undo
Ctrl+0 / 1 / double-click	Fit to window / 100% / toggle
Mouse wheel, drag	Zoom, pan
Ctrl+O	Load Light Frame Data
Ctrl+Shift+O	Open one folder
Ctrl+N	Start over – load new data
Ctrl+H	FITS header window
Ctrl+I	Show / hide the image
Ctrl+E	Save a text list of kept frames
F5	Reload folder

12.2 Page 4 – Finishing Touches

Keys	Action
Ctrl+Z	Undo the last step
Mouse wheel (Spot Fix)	Spot size
Right-click (Spot Fix)	Remove the last spot

13 Files and folders SubZeroAstro creates

13.1 Next to your images

Where	What
`<lights folder>\REJECTED\`	Rejected sub-frames (moved, never deleted)
`<calibration folder>\<rig>\Masters\…`	Calibration masters (bias, darks, flats per filter)
`<master lights folder>\<target>\`	Master lights (`…_Master_<dates>.fits/.xisf`) and their `_stacklog.txt`
`Prepared\` (or your chosen folder)\ `<target>\`	Page 3 results: `…_prepared.xisf`, `…_prepared_stars.xisf`, quick-look JPG/TIFF, PixInsight next steps
`Finished\`, `PixInsight\`, `AstroBin\`	Page 4 saves, PixInsight hand-overs and AstroBin uploads

13.2 On your computer

What	Windows	Mac
Saved progress	`%LOCALAPPDATA%\SubZeroAstro\checkpoints`	`~/Library/Application Support/SubZeroAstro`
Measurement cache	`%LOCALAPPDATA%\FITSBlasterWin\cache`	`~/Library/Caches/SubZeroAstro`
Settings	Windows registry (SubZeroAstro settings)	`~/Library/Preferences`

13.3 Organize My Astro Files

The first time you open it, a note asks you to try it on one or two folders with **Copy** first, look at the result, then **Undo Last Run**, switch to **Move** and run it again - click it through (tick *Don't show this again* once you know the routine). The first Move asks once more.

File › Organize My Astro Files… (page 1) sorts a folder full of FITS and XISF files - subs and masters, lights, flats, dark flats, darks and bias, from any number of nights and targets - into one tidy library. It reads each file's own header (IMAGETYP, OBJECT, FILTER, DATE-OBS, camera, gain, temperature), so the file names and the current mess don't matter. Pick the **folder to organize** (a whole drive or a **NAS** share works too - on Windows a mapped drive or `\\nas\astro`, on a Mac the share as it appears under /Volumes) and where the organized files go (the same folder by default).

Everything the organizer makes goes into one folder, **Organized Astro Files**, inside the folder you choose under *Put the organized files in* - so you can always see where your sorted files are. Use the same one every time: organize one rig folder now and the whole drive later, and the files already sorted show as *already in the right place*. The undo logs are kept in it too.

Folders / files to organize: Browse… picks one or several folders at once (Shift-click a run, Ctrl/⌘-click separate ones), Add Files… picks single files. The buttons show where you are: a step you have done gets a ✓ and turns grey, the next one is highlighted ▶️, and the window says what you did

last time. Pick the **Layout** in the window (remembered). **By rig** (the default) starts with two big folders - **Light Frames** and **Calibration Frames** - and under each, one folder per rig (a telescope and the camera that lives on it). Calibration then goes by frame type, then camera:

Files	Go to (By rig)
Lights	`Light Frames/<rig>/<target>/<night>/<filter>/` (rejected ones keep their `REJECTED` folder)
Master lights, finished pictures	`Light Frames/<rig>/<target>/Masters/` with their star images and stack logs
Flats / dark flats	`Calibration Frames/<rig>/Flats/<camera>/<night>/<filter>/` and `Calibration Frames/<rig>/Dark flats/<camera>/<night>/<filter>/`
Darks	`Calibration Frames/<rig>/Darks/<camera>_G<gain>_O<offset>_<temp>C/<exposure>s/`
Bias	`Calibration Frames/<rig>/Bias/<camera>_G<gain>_O<offset>_<temp>C/`
Calibration masters	`Calibration Frames/<rig>/Masters/<camera settings>/` (master flats in `Flats <night>/<filter>`)
No header to go by	`Unsorted/`



Where each file goes (By rig): lights by rig, target and night (purple); each rig's own calibration (teal)

The organized library, by rig (example)

```
Your drive/
└── Organized Astro Files/                    ← everything the organizer makes
    ├── Light Frames/
    │   ├── SQA60/                            ← one folder per rig
    │   │   └── NGC6992/
    │   │       ├── 2026-10-01/
    │   │       │   ├── Ha/
    │   │       │   └── OIII/
    │   │       └── Masters/                  ← master lights, finals, stack logs
    │   └── RASA8/
    │       └── NGC6992/
    │           └── 2026-08-02/L/
    ├── Calibration Frames/
    │   ├── SQA60/                            ← the SQA60's own camera
    │   │   ├── Flats/ASI2600MM/2026-10-01/Ha/
    │   │   ├── Darks/ASI2600MM_G100_O50_-10C/
    │   │   │   ├── 180s/
    │   │   │   └── 300s/
    │   │   ├── Bias/ASI2600MM_G100_O50_-10C/
    │   │   └── Masters/                      ← calibration masters
    │   └── RASA8/                            ← same camera model, separate sensor
    │       └── …
    ├── Unsorted/                             ← headers that don't say what the file is
    └── _SubZeroAstro_organize/               ← the undo logs
```

An organized library, By rig (example: two telescopes with the same camera model)

By target puts all of one object's data together instead: `Targets/<target>/<night>_<rig>/LIGHT/<filter>/` and `…/FLAT/<filter>/`, `Targets/<target>/Masters/`, with darks and bias in `Darks library/<rig>/…` and `Bias library/<rig>/…`. Flats join the target shot that night with the same telescope - including targets organized in an earlier run, so a folder of calibration frames only can be sorted on its own; otherwise they go to `Flats/<scope>/<night>/<filter>/`.

- **Your Rigs… comes first** (once): one row per rig - its short name (*SQA60*, *RASA8* …), the focal length it writes in your FITS headers, and the camera only if two rigs have about the same focal length (written any way you like: *2600MMPro*, *ASI2600MM* and *ZWO ASI2600MM Pro* are the same camera, but MM and MC are not - a camera that doesn't match the files is named in the plan, so leave it blank when one scope has worn several cameras). Files are matched to a rig by focal length within ±3 % (adjustable in Your Rigs), because the header value drifts a little from night to night; when a reading is within reach of two rigs (a 506 mm and a 530 mm scope), the clearly nearer one wins and a reading right between them is asked about. A scope used with and without a reducer is one rig with two focal lengths (*360, 290*). **Find My Rigs in My Files** reads a sample of headers and adds a row for each focal length none of your rigs matches, with a name taken from your folders; **Add New Rig** when you get another one. Remembered, and Calibrate and Stack uses the same names. **Sort by** (bottom of the window) orders the rigs by name (A–Z) or by focal length - remembered. **Export…** saves your rigs (names, focal lengths, cameras, tolerance) to a small file; **Import…** on another computer loads it - a rig with the same name is updated, new ones are added, nothing is removed - then **Save My Rigs**.
- **Safe to Delete?…** answers the question before you clear out the old folders: it checks every file still in the folders you organized - is there a byte-for-byte identical copy in Organized Astro Files? The verdict is ✓ **Safe to delete** or ✕ **Not yet** (with the files that exist only there), plus PixInsight / Siril work copies, files in saved projects and non-astro files (JPG, notes, logs) listed for you to look at. It only reads; it never deletes anything.

- **What stays behind, and why**: after Step 3 the list shows every file left where it was, with the reason - it needs a rig (Your Rigs… / Which Rig?…), it is a duplicate of a file that was organized (Step 2 deletes it), it could not be read, or a file of that name with different contents is already in the organized folder. Folders not looked into on purpose (saved projects, PixInsight / Siril work folders such as *calibrated* or *registered*, hidden folders) are named too. Run Step 1 again after fixing the reason and those files go too.
- **Nothing is filed under a guess.** A file whose focal length matches none of your rigs stays where it is and the plan says so (add the rig in Your Rigs… and the plan updates at once). **A folder named after a rig** settles what the header can't: for example one USB stick filled from several ASIAIRs, each copied into its own folder named like the rig in Your Rigs (*SQA55*, *RASA 11* - capitals, spaces and dashes don't matter). Its files go to that rig when two rigs have the same scope and camera (identical headers), or when the header has no focal length; a header that belongs to another rig - or to none of your rigs - still decides. When a focal length fits two rigs - or the header has none - **Which Rig?…** asks you, folder by folder, and remembers your answer for that folder. **Rented telescopes** need no rig: frames from Telescope Live (file names like *CHI-1-CCD_…*, or its already-calibrated files) and iTelescope (*calibrated-T21-…*) are filed under the service's telescope - *Telescope Live CHI-1*, *iTelescope T21* - even when the focal length happens to match one of yours. Which Rig? also lists files whose focal length matches none of your rigs; for stray files you don't want, pick **✕ Delete these files** (you're asked to confirm, and each one deleted is named in the log).
- **The night** is the evening date at your site (from the header's longitude), so a session that runs past midnight stays together.
- **Step 1 – Look Through the Files** only reads - it shows how many files go where, and a list of each file, where it goes and why. Nothing changes until you press **Step 3 – Organize** (greyed out until Step 1 has run). Do **Step 2 – Duplicates…** in between when Step 1 finds any.
- **Copy** (the default) leaves the originals; **Move** moves them and removes the empty folders left behind. A copy is checked before a move removes the original.
- **Duplicates** (the same capture twice, e.g. *L_001 copy.fits*) are left where they are and flagged. Press **Step 2 – Duplicates…** (before Step 3 – Organize) to see each one next to the copy that is kept, tick the ones to deal with, then **Keep Them**, **Move to a Duplicates Folder** (set aside; Undo Last Run puts them back) or **Delete Ticked Duplicates…**. Delete compares every byte first and only deletes an exact copy - a file with the same capture time but different contents is kept for you to look at. Files that can't be read are left where they are and listed.
- **Saved projects** (page 4), files already in the right place, and the in-between folders other programs make (*calibrated*, *registered*, *debayered*, *process* … from PixInsight WBPP, Siril or APP) are left alone, so running it again on the same library only tidies what is new.
- **Move on the same drive is instant** - the files only get a new folder, nothing is copied - so organizing a big drive in place takes about as long as reading the headers. Copy, or moving to another drive, copies every byte.
- **Undo Last Run** puts every moved file back (or removes the copies). Each run's log is kept in `_SubZeroAstro_organize` inside the library.
- A big NAS takes a while - reading headers over the network is the slow part. Stop is safe: what was done is in the log and can be undone.
- **By target, then rig** is the third layout: `Light Frames/<target>/<rig>/<night>/<filter>/` (and `…/<rig>/Masters/`) - every rig's nights of one object together, then split by rig. Calibration frames stay in `Calibration Frames/<rig>/…`, because they belong to a rig, not to a target.
- **By date, then target, then rig** is the fourth: `Light Frames/<year>/<night>/<target>/<rig>/<filter>/` - everything every rig shot on one night, together. The night is read from each frame's own capture time (DATE-OBS in the header, recorded by the capture program) and is the evening's date, so frames taken after

midnight stay with the night they belong to. Master lights, which belong to no single night, go in `Light Frames/Masters/<target>/<rig>/`; calibration frames stay in `Calibration Frames/<rig>/…`.

- **Change My Library's Layout…** re-sorts a library you already organized into another layout (e.g. *By rig → By target, then rig*): pick the library folder and the new layout, check the plan, then Step 3. The files only move inside the library (a rename, not a copy), a re-sort never offers a duplicates step (the library was checked when its files came in; the frames you set aside earlier stay in the *Duplicates* folder and are not looked at again, and neither is a NAS's recycle bin (Synology *#recycle*, QNAP *@Recycle*), where files deleted on the NAS wait until it is emptied; two files headed for one name both stay, the second numbered), and SubZeroAstro remembers what every header said (in the library's *_SubZeroAstro_organize* folder), so after the first look a re-sort - or the next Organize - doesn't open the files again; it is quick even on a NAS, and **Undo Last Run** puts everything back.
- **Fetch From My ASIAIRs…** (also in the File menu) - no more USB sticks. Add each ASIAIR with a name, its **IP address** (in the ASIAIR app's Wi-Fi settings) and its **rig** from Your Rigs; pick your **incoming folder**. **Fetch Now** fetches from **all your ASIAIRs at the same time** (each has its own Wi-Fi radio, which is the slow part, so four come over in about the time of one) - so does the overnight fetch. It copies every sub that hasn't come over before - from all the ASIAIR's image folders (*EMMC Images*, *Udisk Images* …) - into *incoming*\<*rig*>*…*, so Organize files each one under its rig even when two rigs have the same scope and camera. The .jpg previews stay on the ASIAIR, each copy is checked before it counts, and SubZeroAstro remembers what it has fetched, so organizing (which empties the incoming folder) never brings a sub over twice. Subs written in the last two minutes wait for the next fetch. While it fetches you can **close the window and keep working** in SubZeroAstro - the fetch carries on, with its progress in the status bar - and **Pause** holds it between subs until you press **Resume**. **Test** shows what it finds on one ASIAIR. **Delete .jpgs on This ASIAIR…** (on demand only) lists the .jpg pictures on the selected ASIAIR - how many, how big, in which folders - and deletes them after you confirm; the FITS subs are never touched. Options: **Free space on the ASIAIR** deletes each sub - and its .jpg preview - from it once its copy is checked (off unless you tick it); **Keep fetching through the night, every N minutes** fetches while SubZeroAstro is open - over Wi-Fi this spreads the slow copying over the night, so the subs are already here in the morning (it carries on after a restart of SubZeroAstro); **Fetch first whenever Organize Automatically runs** fetches before each automatic run. On a Mac, connect the ASIAIR's share in Finder (⌘K, *smb://<IP>*) and use **Browse for Folder…**.
- **Organize Automatically…** files new frames with nobody at the computer. Choose the **incoming folder** (e.g. the NAS folder your rigs' frames are copied to), **your library**, the layout and how often - **every day**, **twice a week** (Monday and Thursday) or **once a week** (Sunday) - and a time, then **Save & Turn On**. SubZeroAstro sets up the computer's own scheduler (Windows Task Scheduler, or a macOS LaunchAgent), which starts it without a window at that time; it organizes (always a move, so the incoming folder empties out) and closes again. The computer must be on - and on Windows you logged in - at that time. On a Mac a NAS folder is under */Volumes/<share>* and exists only while the share is connected: SubZeroAstro remembers how each share was connected and reconnects it before a run (the password comes from your keychain - tick *Remember this password in my keychain* the first time you connect in Finder); adding the shares to *System Settings › General › Login Items* also connects them at login. Files that can't be filed (no rig matches, duplicates, or changed in the last hour, so perhaps still arriving) stay in the incoming folder; the last run's summary is shown in the Organize window and every run is listed in `_SubZeroAstro_organize/auto_organize_history.txt`. **Run Now** starts one run straight away, in the background like a scheduled run - it keeps going if you close SubZeroAstro, and the result shows in the window when it's done (while a run is going, `_SubZeroAstro_organize/auto_organize.lock` exists in the library). **Turn Off** removes the schedule; **Undo Last Run** undoes an automatic run too. **Delete the .jpg previews (ASIAIR)**

(next to Copy / Move, on by default) deletes the .jpg an ASIAIR saves next to every frame from the folders the frames came from - by hand and in automatic runs - plus any ASIAIR previews (*Light_…*, *…_thn.jpg*) left on their own anywhere in the incoming folder once their frames had been filed; never anything in your organized library, and never your own pictures; deleted previews can't be brought back with Undo. **Delete other files too (anything not FITS / XISF)**: after a Move, everything left in the incoming folders that isn't a frame - .jpg, .csv, .txt, Thumbs.db - is deleted, and folders left empty go too (never your library, nothing changed in the last few minutes, and never N.I.N.A.'s ImageMetaData file while its frames are still waiting). Unticked, Organize asks after each Move, and offers to delete the duplicate copies left there too (each checked byte for byte first). Windows' copies named *M31_0042 (1).fits* are recognised: the copy is the duplicate, the original is filed, and a lone *(1)* file is filed under its clean name. **Delete empty frames (all zeros)** (off unless you tick it) deletes frames that are all zeros or 0 bytes: the capture or a copy was cut short and the file never got its picture - there's nothing in it to rescue (check the imaging computer's own copy first if you can). Organize lists them as *all zeros* either way. A run cut short (the computer switched off) is safe: every file is either fully moved or still in the incoming folder, and the next run carries on.

14 Privacy, licence and credits

14.1 Privacy

SubZeroAstro does not send any information anywhere unless you ask it to. It reads and writes images only where you point it. **Share to AstroBin…** only opens AstroBin's page in your browser. Companion programs (ASTAP, GraXpert, RC-Astro) are separate programs with their own terms.

14.2 Licence and credits

SubZeroAstro is free software under the **MIT License**. Created by **Brian A. Poteet, DVM**, built with Claude (Anthropic). The culling view was inspired by FITS Blaster for macOS by Tom van Peer. PixInsight, BlurXTerminator, NoiseXTerminator, StarXTerminator, GraXpert, ASTAP, AstroBin and the telescope and filter names mentioned are trademarks of their respective owners. The deep-sky object list of Tonight's Target Picker comes from N.I.N.A. - Nighttime Imaging 'N' Astronomy (github.com/isbeorn/nina), used under the Mozilla Public License 2.0.

15 Processing Techniques and Tips

Every target type has its own small tricks. These are the ones that work best with SubZeroAstro - short points to try, gathered from real data (yours included). The names in *italics* are the versions and sliders on page 4. Nothing here is a rule: if a picture looks right to you, it is right.

15.1 Tips for every target

- **Follow the recommended order.** The card at the top of page 4 knows what your data needs; skipping ahead (Curves before Tame Bright Core, say) makes later steps work harder.
- **Colour needs room below white.** Anything brightened close to white cannot show colour - Saturation and Adjust Colours only tint its edges. Lower the brightness first (*Protect bright areas* in Brighten the Image (Stretch), or Tame Bright Core); the colour then comes back on its own.
- **Small steps, then Do It Again.** A gentle version run twice usually looks more natural than the strongest version once - and each round can be undone on its own.
- **Judge at full size.** *Full Window*, the mouse wheel to zoom, and *Hold for Before* show what a step really does. The little versions are for choosing a direction, not for judging detail.
- **Good data beats any processing.** Flats every night (a flat panel at the end of the session is ideal), a dark and bias library at one fixed camera temperature (0 °C works well for modern CMOS), and as many hours as you can: noise halves for every four times the exposure.

15.2 Galaxies

- **Tame Bright Core** is recommended for every galaxy, right after Brighten the Image (Stretch). Start with *Medium*; use *Strong* or *Maximum* for a very bright nucleus. Drag *Core size* to the left when the bright area is larger than the tint of *Show what will change*.
- **Bring Out Hidden Structure** (*Moderate* or *Strong*) after Curves shows the dust lanes and spiral arms.
- **HII regions:** with a mono RGB set plus Ha, *Add Hydrogen Glow* puts the red knots along the arms; with a colour camera, a few hours through a dual-band filter can be added the same way.
- **Filters:** broadband (or a mild light-pollution filter) gives the brightest arms and most natural colours. A dual-band filter (L-eNhance, L-Ultimate) lets through only a little of a galaxy's starlight, but with long integration it works well and makes the red HII regions stand out - M31 with a 55 mm refractor, an ASI2600MC and an L-Ultimate over about 20 hours shows the disc, the dust lanes and the HII regions clearly.
- **Small galaxies:** crop tightly at the end (*Final Crop*), keep the stars in check (*Shrink Stars Moderate*, *Put Stars Back 80-100%*) so the galaxy stays the subject.
- **Don't darken the sky too much** - *Slightly darker* keeps the faint outer arms and halo that make a galaxy look real.
- **Warm core, blue arms:** a spiral's bulge is old, yellowish starlight and its arms young, blue stars. If the disc looks grey, a gentle *Adjust Colours › Boost reds* (with *Protect the sky* up) warms the core, and *Boost blues* the arms.
- **The faint outer disc:** a gentle *Curves › Lift faint detail* before *Darken the Sky Background* shows more of the outer arms and halo, when the data is deep enough.

15.3 Emission nebulae

- **Palettes for a colour camera with a dual-band filter:** *HOO* (Ha red, OIII teal - natural), *HOO (vivid)*, *Gold & blue*, or *Foraxx (dynamic)*. With a mono camera, *Hubble (SHO)* or *HOO + SII*.
- **Take the stars out before brightening** - the nebula can then be brightened strongly without bloating the stars, and they go back at the end.
- **Separate Ha and OIII:** *Adjust Colours › Blues and reds* makes the blue OIII and red Ha stand apart; *Calm the greens* for leftover green.
- **Bright centres** (Bubble, Orion, Lagoon): *Tame Bright Core* right after Brighten the Image (Stretch).
- **Targets that fill the frame** (Veil, North America): a SkyFlat made from that target's own lights can leave faint dark copies of the nebula - use real flats, or untick *SkyFlats (Mote Buster)* and let gradient removal and Mote Buster deal with vignetting and dust.
- **Stars:** *Star Colours › Natural* (narrowband paints stars one colour) and *Put Stars Back 80-100%* keep the nebula the star of the picture.

15.4 Planetary nebulae

- **They are tiny and very bright.** Brighten the Image (Stretch) sets the brightness for the faint background, which pushes the bright ring or shell to nearly white - that is why it looks "hot". Use *Gentle*, and keep the *Method* on **Colour-preserving** (the default for planetary nebulae): the *Hyperbolic (GHS)* method brightens each colour separately and turns a bright planetary grey - no colour step can bring that back.
- **Tame the ring, not the centre.** A planetary's bright light is in its ring or shell; the middle is faint and see-through. For a planetary nebula *Tame Bright Core* (recommended, right **after Curves** - the workflow puts it there, because Curves' contrast would make the ring white again) works as *Tame the Ring*: inside the mask the nebula is brightened again, gently, from the linear data - the brightest part of the ring goes to the *Ring brightness* you pick (Gentle 85% … Maximum 55%), everything else follows the nebula's real brightness, so ring and inside separate again and both leave white behind. The outer halo is left as it is. Tick *Show what will change* to see the area - a light green wash with a yellow line at its edge, which should lie outside the ring; drag *Area* to the left if it doesn't. The result shows through the wash; untick the box for a clean look. *Medium* or *Strong* is a good start. Don't brighten or add contrast after it.
- **Star removal and small nebulae:** StarXTerminator can take a small, bright planetary for a star and put part of it in the stars image - where no nebula step reaches it, and *Put Stars Back* makes it white again. For a planetary nebula SubZeroAstro moves anything in the stars image that is much wider than a star, near the middle of the picture, back to the nebula when the stars are taken out.
- **Palette HOO:** Ha gives the red outer ring, OIII the teal-blue inside - the classic Ring Nebula look. *As captured* tends to look pale.
- **Colour:** *Saturation Vivid* or *Rich*, then *Adjust Colours › Blues and reds* (lower *Reds* a little for a bluer centre). If the colours change in hard bands around the ring, raise *Smooth colour transitions* - it blends the colours without softening the detail.
- **Faint outer halo:** after taming, *Curves › Lift faint detail* can show the dim shell around the bright ring (M57 has one).
- **Crop tightly:** at 900 mm M57 is only about 100 pixels across - *Final Crop* makes it fill the picture.
- **At the telescope:** shorter subs (60-120 s) keep the brightest part from burning out in the masters; collect plenty of them.

> **Worked example:** A recipe that works for M57 (colour camera + L-Ultimate, 3.6 h): *HOO* palette · *Take Stars Out* · *Brighten the Image (Stretch): Gentle* (Colour-preserving) · skip *Remove Green Cast* · *Curves: Lift faint detail* · *Tame Bright Core: Medium* · *Saturation: Vivid* · *Adjust Colours: Blues and reds* with Blues about 1.3, Reds 0.85 and *Smooth colour transitions* 0.6-1.0 · the star steps · *Put Stars Back* · a tight *Final Crop*. The result: a blue centre, a gold-to-red ring and the faint outer halo.

15.5 Dark nebulae and faint dust

- **The darkness is the subject.** Leave *Darken the Sky Background* off (or *Slightly darker*): darkening the sky erases the faint glow the dark clouds stand out against.
- **Broadband, dark skies and many hours** - dust shows up in broadband light only; dual-band filters hide it.
- **Gradients matter most here:** check the GraXpert result on page 3; a raised *GraXpert smoothing* keeps it from mistaking large faint dust for a gradient.
- **Lift, don't stretch:** *Curves › Lift faint detail* and a light *Bring Out Hidden Structure* (*Subtle*).
- **Tame the star field:** *Shrink Stars Strong* and *Put Stars Back 60-80%* so the dust shapes are not lost among thousands of stars.

15.6 Reflection nebulae and star clusters

- **Reflection nebulae** (Pleiades, Iris, M78) shine by reflected starlight: broadband only, no dual-band filter. *Balance Colours › Neutral sky only* keeps their blue.
- **Bright stars inside a nebula:** BlurXTerminator's *Adjust Star Halos* on page 3, and *Shrink Stars* with *Halo reduction*, calm the glow around them.
- **Star clusters:** the stars *are* the subject - taking them out is optional. *Star Colours › Natural, vivid* shows the mix of blue and orange stars.
- **Globular clusters** (M13, M92): *Brighten Gentle* keeps the core resolved; *Tame Bright Core* if the centre turns into a white disc.

15.7 Comets

SubZeroAstro recognises a comet by its name (*C/2023 A3*, *12P/Pons-Brooks*, or any name with *comet* in it) and handles it from stacking to the finished picture:

- **Capturing:** many short subs - the comet moves. With N.I.N.A.'s **Orbitals** plugin the mount follows the comet; a typical plan cycles the filters, e.g. 6 x 60 s each of R, G and B, then 6 x 30 s of L, again and again. Keep the target name the comet's name so SubZeroAstro knows it is a comet. Take flats for every filter as usual.
- **Page 2 (stacking):** each filter is stacked on the stars and then again following the comet (10.6). The main master joins the sharp stars and the sharp comet; *_Comet* and *_Stars* masters are saved next to it.
- **Page 3:** for a comet BlurXTerminator sharpens the coma and tail but not the stars (*Sharpen Stars* 0 - it would turn the star-like nucleus into a hard disc with a ring), and StarXTerminator is left out (it takes the inner coma for a star). The suggested crop leaves out the edge strip the comet stack could not fill. **Page 4:** an overexposed nucleus (one colour clipped, so the centre turns another colour - a purple dot in a cyan coma) gets the coma's own colour when the comet is loaded. *Brighten the Image* uses GHS for a comet (the colour-preserving stretch pushed the whole inner coma to the top - a flat disc; GHS keeps a bright nucleus fading into the coma) and *Colour Intensity* suggests *Rich*.
- **Page 4 (combining):** when the filters were shot one after another, the comet sits in a slightly different place in each filter's master. SubZeroAstro moves just the comet (head and tail) in

each filter onto the comet in the L (or first) master, so the comet's colours line up while the stars stay where they are. The load note says how far each filter's comet was moved.

- **Page 4 (steps):** after **Brighten the Image (Stretch)**, two comet steps are offered: **Bring Out the Tail** (take away part of the round coma so the tail and streamers show) and **Reveal Comet Jets** (Larson-Sekanina: jets and shells near the nucleus; *Jets map only* makes the grey study picture to save separately). **Darken the Sky Background** is recommended so the faint tail stands out; star removal and shrinking are optional.
- **Tips:** take the stars out before Reveal Comet Jets (stars turned around the nucleus leave little arcs). Use Go Back to Here to compare versions. A comet that barely moves during the session is simply stacked on the stars.

15.8 Moon and planets (coming)

A page for video of the Moon and planets (lucky imaging: grade thousands of frames, stack the best, sharpen) is on the way. For now: video (SER/AVI) with very short exposures for planets and Moon close-ups; single frames, stacked, for a full Moon; the best 10-25% of the frames usually give the sharpest result.

15.9 Questions and fixes

Problem	What to try
Bright stars turn into big soft discs	*Brighten Stars Separately* keeps bright stars their real size (fine-tune *Keep bright stars small*, about 0.85): one brightening curve for everything would lift a bright star's faint outer glow as much as a faint star's core. Turn it down toward 0 only if you want the big-glow look.
My stars look bloated and have fuzzy edges	Page 3: BlurXTerminator *Sharpen Stars* about 0.5 and *Adjust Star Halos* 0.3-0.5. Page 4: *Brighten Stars Separately › Subtle*, *Put Stars Back 80-100%* (not 120%), *Shrink Stars* with *Halo reduction* - and *Do It Again* if needed. If the stars are large on page 1 too (FWHM), it is focus or seeing.
The core of my galaxy or nebula is a white blob	*Tame Bright Core* right after *Brighten the Image (Stretch)* - *Strong* or *Maximum*, *Core size* to the left. Raise *Protect bright areas* in Brighten the Image (Stretch).
My colours look washed out, or the object stays white	Colour needs room below white: lower the brightness first (above), then *Saturation Vivid* and *Adjust Colours*. Saturation on a white area does nothing.
The background is green or magenta	*Remove Green Cast*; *Balance Colours › Neutral sky only*; *Adjust Colours › Calm the greens*.
The background is blotchy or noisy	More hours of data helps most. Then *Final Noise Reduction* (*Medium*), a gentler *Brighten*, and *Darken the Sky Background*.
Dark rings (dust donuts)	Flats taken the same night fix them at the source. Afterwards: *Mote Buster* (9.4) for donuts, *Spot Fix* for single blemishes.
A faint dark copy of the nebula, turned or shifted	A SkyFlat made from a target that fills the frame. Use real flats, or stack again with *SkyFlats (Mote Buster)* unticked (15.3).
Double stars, or coloured edges on stars near the corners	Masters from different nights or setups that did not line up - the page 4 log says which master was left out. Stack those nights together on page 2 if you can.

Problem	What to try
The faint outer parts disappeared	The sky was darkened too much, or noise reduction was too strong. Use *Slightly darker*, *Curves › Lift faint detail*, a lighter *Final Noise Reduction*.
Red, purple, blue or green blotches in the sky	Colour noise from the weaker colours or filters (OIII, SII; a short RGB set) showing in the sky. *Darken the Sky Background* has **Calm sky colours** (fine-tune; on by default, 0.6 for narrowband, 0.5 otherwise): across the whole sky - everything near the sky's own level - it smooths the colour much wider than the blotches and pulls it toward grey, without touching the brightness or the galaxy's / nebula's colours. Raise it toward 1.0 for a neutral grey sky. When the faint areas are faint nebula rather than empty sky (IC 1396, the Veil), use **Adjust Colours › Calm blues and purples** - it calms those hues everywhere, the gold and red untouched. Also: *Adjust Colours › Smooth colour transitions* 0.4-0.6, *Colour Intensity › Slight*, and more time on OIII and SII.
The background shows blotches or a moire-like pattern	Faint leftover noise at a large scale (often well under 1 % of the sky brightness), made visible by a strong stretch. *Bring Out Hidden Structure* protects the sky (keep *Protect the sky* about 0.85); also try *Curves* without *Darker background*, a stronger *Final Noise Reduction*, and dithering every 2-3 frames when you capture.
The picture looks over-sharpened or crunchy	Use a lower *Bring Out Hidden Structure* version (or skip it), and *Sharpen Nonstellar* about 0.3-0.5 on page 3.
Satellite trails	Many frames and sigma clipping on page 2 remove most of them; *Spot Fix* (with its stars kept) cleans up what is left.
Dew on the camera window	Put the imaging train together indoors, add a dew strip around the filter drawer or spacer, and keep a desiccant pack in the train; a fixed 0 °C camera temperature also helps.

16 Index

_

_Comet master....10.6
_Stars master....10.6

-

--fast-track....4.5

A

Add Folders....6.1
Add Hydrogen Glow....9.3
Add Masters....8.1
Adjust Colours....9.3
Aggressive....6.3
AI....1.5
Alt-az....10.5
Apply....9.1
ASIAIR integration....1.2
Askar D1....10.2
Askar D1 D2 recipe....10.11
Askar D2....10.2
ASTAP....2.2, 4.1
AstroBin....9.7
Auto-crop....8.2
Auto-cull....6.3
Auto-Flag....6.3
Automatic processing....5.5

B

Back button....5.1
Back to Start....9.2
Background....6.2
Badges....6.2
Balance Colours....9.3
Banner....5.1
Barnard....15.5
Bias....4.3
Blind solve....8.3
Bloated stars....15.9
BlurXTerminator....2.2, 8.5
Brighten Stars Separately....9.3
Brighten the Image (Stretch)....9.3
Bring Out Hidden Structure....9.3
Broadband and narrowband rows....7.1
Broadband recipe....10.9
Build Calibration Masters....7.6
Burnt-out core....15.9

C

Cache....13.2
Calibration....7.2
Calibration check....7.2
Calibration library....4.3, 7.6
Calibration masters folder....4.2
Cancel....9.1
Check & Stack....7.4
Check for Updates....11.2
Choose a Colour Palette....9.3
Cluster recipe....10.15
Colour cameras....7.3
Colour headroom....15.1
Combine Colour Channels....9.3
Comet LRGB....15.7
Comet processing....15.7
Comet stack....10.6
Comet tail....15.7
Comets....10.6
Continue button....5.1
Continue to Calibrate and Stack....6.6
Continue With the Rest....7.4
Crash recovery....5.3
Credits....14.2
Crop....8.2
Curves....9.3

D

D1 D2 step by step....10.11
Dark nebula processing....15.5
Dark nebulae....15.5
Dark-flats....4.3, 7.6
Darken the Sky Background....9.3, 9.6
Darks....4.3
Darks library....13.3
Default viewer....6.4
Defaults....5.5
Device (GPU)....4.1
Disk space....2.1
Do It....9.1
Do It Again....9.1
Double stars....9.1
Dual-band filter....1.4
Dual-band recipe....10.2
Dual-band step by step....10.10
Duplicates....13.3
Dust donuts....9.4
Dust motes....9.4
DWARF....10.5

E

Eccentricity....1.4, 6.2
Edit FITS Headers....6.4
Emission nebula processing....15.3
End this Project and Start New Project....9.8
External Script....4.5

F

FAQ....11.1, 15.9
Fast Track....5.5

Fast Track after the night....4.5
Fetch From My ASIAIRs....1.2
Field distortion....9.1
File formats....2.3
Film of the steps....5.5
Filter column....7.1
Filter used....6.1
Final Crop....9.3, 9.6
Final Noise Reduction....9.3
Fine-tune....9.1
Fine-Tune on Page 4....5.5
Finished folder....13.1
FITS....2.3
FITS header....6.4
FITS viewer....6.4
Fix Dust Donuts....9.3, 9.4
Flag....6.3
Flat warnings....7.2
Flats....4.3
Flip or Rotate the Picture....9.3
Folder organisation....2.3
Foraxx....15.3
Four pages....1.1
Full Window....9.1
Fuzzy stars....15.9
FWHM....1.4, 6.2

G

Galaxies....15.2
Galaxy....10.7
Galaxy processing....15.2
Galaxy recipe....10.15
Galaxy with Ha....10.13
Gatekeeper....3.2
Globular clusters....15.6
Glossary....1.4
Go Back & Redo This Step....8.7
Go Back to Here....9.2
Gradient removal....8.4
Graphics card (GPU)....2.1
GraXpert....2.2, 4.1, 8.4
Grey sky....9.6

H

Hardware requirements....2.1
Headroom....15.1
Hide image....6.4
HII regions....10.3
HII regions recipe....10.13
Hold for Before....8.7
Hold for Before (Finishing Touches)....9.2
Honest processing....1.5
HOO....15.3
HOO recipe....10.10
Horizon....6.5
Hubble palette....10.4

I

IFN....15.5
Image file pattern....4.5
Import Targets....6.5
Include subfolders....6.1
Install (Mac)....3.2
Install (Windows)....3.1
Intro animation....4.4

K

Keyboard shortcuts....12.1

L

L-eXtreme....10.2
L-eXtreme recipe....10.10
L-Synergy....10.2
L-Ultimate....10.2
L-Ultimate L-Synergy recipe....10.11
L-Ultimate recipe....10.10
Larson-Sekanina....15.7
Less aggressive....6.3
Library layout....13.3
Licence....14.2
Light groups....7.1
Light leak....7.2
Light pollution....8.4
Line up all filters....7.3
Linear....1.4
Live grading....1.2
Load Light Frame Data....6.1
Log....5.2
Logs....11.2
LRGB Ha step by step....10.13
LRGB recipe....10.3
LRGB recipe step by step....10.12
Lucky imaging....15.8

M

M13....15.6
M27....15.4
M45....15.6
M57....15.4
Master....1.4
Master bias....7.6
Master dark....7.6
Master flat....7.6
Master lights folder....4.2
Memory (RAM)....2.1
Missing calibration....7.2
MIT License....14.2
Mono....1.4
Mono HOO step by step....10.14
Mono LRGB step by step....10.12
Mono RGB recipe....10.12
Mono SHO step by step....10.14
Moon processing....15.8
Mote Buster....9.3, 9.4

N

N.I.N.A. 4.5
N.I.N.A. horizon file 6.5
N.I.N.A. integration 1.2
N.I.N.A. profiles 4.5
Narrowband 1.4
Narrowband recipe 10.4
Narrowband step by step 10.14
NAS 13.3
Nebula 10.7
Nebula recipe 10.15
Nebulae 15.3
Network drive (NAS) 6.1
New project 9.8
Next target 9.8
NINA 4.5
No flats 7.2
NoiseXTerminator 2.2, 8.5

O

Old flats 7.2
Open Master Lights Folder 7.5
Open Project 9.7
Orbitals 15.7
Organize 13.3
Organize My Astro Files 13.3
OSC 1.4
OSC broadband recipe 10.1
OSC recipe 10.9
Output files 13.1
Output folder 8.6

P

Page navigation 5.1
Painting 1.5
Pick the one you like 9.1
PixInsight 2.2
PixInsight hand-over 5.4
Planetary imaging 15.8
Planetary nebula 10.7
Planetary nebula processing 15.4
Planetary nebulae 15.4
Planetary recipe 10.15
Plate solve 8.3
Plate solving 1.4
Prepared folder 13.1
Preview palette 8.6
Privacy 14.1
Processing tips 15.1
Progress bar 5.2
Put Stars Back 9.3

Q

Quarantine 3.2
Quick-look image 8.6

R

RC-Astro CLI 2.2, 4.1
Real data 1.5
Recipe by target type 10.15
Recipes 10.8
Recommended next 9.1
Reflection nebula processing 15.6
Reject 6.3
Reject outliers 7.3
REJECTED folder 6.3, 13.1
Remove Green Cast 9.3
Reporting problems 11.2
Reprocess Step by Step 5.5
Resume 5.3
RGB + Ha galaxies 10.3
RGB colour camera 10.9
Rig names 4.3
Ring Nebula 15.4
Run Selected Steps 8.7

S

Same framing 1.2
Saturation 9.3
Save as FITS/XISF 7.3
Save final images 8.6
Save locations 4.2
Save Project As 9.7
Save the Picture 9.7
Saved progress 4.4
Saved progress location 13.2
Score 6.2
Search radius 8.3
Seestar 10.5
Self-test 11.2
Semi-aggressive 6.3
Session chart 6.2
Set Filter Name 6.4
Settings 4.4
Settings location 13.2
Several folders at once 6.1
Several masters per filter 9.1
Share to AstroBin 9.7
SHO recipe 10.4
Shortcuts 12.1
Shrink Stars 9.3
Sign Your Picture 9.3, 9.6
Signature fonts 9.6
Skip 9.1
Sky flat 7.2
SkyFlats (Mote Buster) 7.2
Smart telescopes 10.5
SmartScreen 3.1
SNR 1.4, 6.2
Spot Fix 9.3, 9.6
Stack log 7.5
Star cluster 10.7
Star cluster processing 15.6

Star Colours....9.3
Star count....6.2
Star measurement....4.4
Starless....9.5
Stars workflow....9.5
Start Fresh....8.7
StarXTerminator....2.2, 8.5
Status bar....5.2
Step history....8.7
Step-by-step recipes....10.8
Stop Here – Continue in PixInsight....5.4
Stretched....1.4
Sub-frame....1.4
Support....11.2
Synthetic flat....9.4
System requirements....2.1

T

Take Stars Out....9.3
Tame Bright Core....9.3
Target picker....6.5
Target sets....8.1
Target types....10.7
Telescope (rig)....7.1
Telescopius....6.5
Tonight's Target Picker....6.5
Tool locations....4.1
Troubleshooting....11.1

U

Undo....5.3, 9.2
Undo Last Header Change....6.4
Undo Last Run....13.3
Uninstall....3.4
Unique features....1.2
Unscreen Stars....8.5
Update Now....11.2
Updates....11.2
Updating....3.3

V

Vespera....10.5

W

Washed-out colours....15.9
Weight frames by noise....7.3
What to image tonight....6.5
Will be lined up....8.1
Work With N.I.N.A....4.5
Workflow by data type....10.8
Workflow list....9.1
Workflow overview....1.1

X

XISF....2.3
XISF viewer....6.4

Z

Zip My Logs....11.2
Zoom....9.1