Literature Review on Self-Supervised Agricultural Remote Sensing

The attached paper argues that masked image modeling on domain-specific multispectral aerial imagery can nearly match supervised ImageNet pretraining for agricultural infrastructure detection, while still struggling in extreme low-label settings.

Study Positioning

The attached study pre-trains a convolutional backbone from scratch with SparK-style masked image modeling on 1.5 TB of unlabeled NAIP imagery, about 9.87 million 512×512 multispectral tiles, then fine-tunes it on poultry farm detection, greenhouse detection, and DOTA aerial object detection (Author & Author).

Its central motivation is the domain gap between natural-image pretraining and overhead multispectral imagery, a gap also emphasized across remote-sensing pretraining studies and foundation-model work (Author & Author; Sun et al., 2023; Ghanbarzade & Soleimani, 2023; Wang et al., 2022; Guo et al., 2023).

This problem is practically important because NAIP-scale imagery supports monitoring of concentrated animal feeding operations, greenhouses, forests, and other land features at national or regional scales, but manual mapping remains labor-intensive and hard to scale (Author & Author; Robinson et al., 2021; Joshi & Witharana, 2025).

Core Empirical Findings

Performance of the attached paper's three downstream tasks

Task	ImageNet Baseline	SSL Domain Pretraining	Main Takeaway
Poultry detection	0.9840 mAP50	0.9790 mAP50	Near parity; SSL has higher recall
Greenhouse detection	0.9743 mAP50	0.9676 mAP50	Small performance gap
DOTA benchmark	0.9369 mAP50	0.9086 mAP50	Competitive, but weaker on broad aerial transfer

FIGURE 1 Downstream performance of supervised and SSL initialization

On the poultry dataset, the ImageNet baseline was slightly higher in mAP50, but the SSL model achieved higher recall, 98.3% versus 97.7%, which matters in surveillance tasks where missed facilities are costly (Author & Author).

Across greenhouse and DOTA tasks, the SSL model trailed by only 0.7 and 2.8 mAP50 points, respectively, which supports the claim of strong transferability rather than outright superiority (Author & Author).

The attached paper therefore does not show that domain-specific SSL universally beats supervised pretraining; it shows that large-scale in-domain unlabeled pretraining can achieve practical parity on several aerial detection problems (Author & Author).

Methodological Context

Key pretraining paradigms relevant to the attached paper

Paradigm	Representative idea	Relevance to attached paper
BEiT / early MIM	Mask patches and predict tokens	Established masked image modeling as a general SSL recipe
SparK	Sparse, hierarchical masked modeling for convnets	Direct architectural basis of attached study
RingMo	RS-specific MIM foundation model	Shows MIM scales to remote-sensing tasks
FG-MAE / Prithvi / SkySense	RS-aware reconstruction targets or multimodal pretraining	Expands beyond RGB-style MIM to geospatial foundation models

FIGURE 2 Pretraining paradigms related to the attached study

The attached work is methodologically anchored in SparK, which adapts masked image modeling to convolutional networks through sparse convolutions and a hierarchical decoder, and reported gains especially for detection and segmentation transfer (Tian et al., 2023).

That architecture matters because standard masked image modeling first matured in transformer settings such as BEiT, where masked patches are predicted after patch-tokenization (Bao et al., 2021).

Remote-sensing papers increasingly adapt these ideas to domain structure rather than applying natural-image SSL unchanged. RingMo builds a remote-sensing foundation model with two million aerial and satellite images and reports state-of-the-art performance across eight datasets and four downstream tasks (Sun et al., 2023). FG-MAE further argues that reconstructing remote-sensing features such as HOG and normalized difference indices can outperform raw-pixel reconstruction, especially for SAR (Wang et al., 2023).

Large geospatial foundation-model papers extend this logic further. Prithvi uses MAE-style pretraining on multispectral and temporal satellite imagery rather than RGB-only imagery (Jakubik et al., 2023). SkySense reports that a remote-sensing-specific multimodal foundation model outperforms natural-image foundation models such as DINOv2 across five Earth-observation datasets, again attributing the difference to domain mismatch and missing spatiotemporal design in natural-image models (Guo et al., 2023).

Agricultural Detection Literature

Agricultural monitoring applications compared with the attached paper

Application	Data source	Main finding	Citation
Poultry CAFO mapping	NAIP, continental U.S.	CNNs scaled to 42 TB imagery for national open dataset	(Robinson et al., 2021)
Greenhouse detection	GF-1/GF-2 high-resolution imagery	YOLOv3 reached 90.4% mAP and best overall tradeoff	(Li et al., 2020)

Application	Data source	Main finding	Citation
Vegetation/community mapping	NAIP vs UAV multispectral	UAV slightly better, but NAIP still strong with RF	(Bhatt & Maclean, 2023)
Tree-crown health detection	NAIP 4-band imagery	SegFormer beat CNN baselines with F1 0.85	(Joshi & Witharana, 2025)

FIGURE 3 Examples of agricultural and ecological aerial detection tasks

The application literature supports the attached paper's choice of tasks. Poultry operations are a real regulatory and environmental target, and deep learning on NAIP has already been shown feasible at continental scale using over 42 TB of imagery (Robinson et al., 2021).

Greenhouse detection is also a mature benchmark problem because greenhouse expansion affects land use, soil, and plastic pollution, and CNN detectors above 80% mAP have been reported, with YOLOv3 reaching 90.4% mAP in one comparison study (Li et al., 2020).

More broadly, agricultural remote sensing reviews consistently report that CNNs, object detectors, and multispectral inputs are central to precision-agriculture workflows, while spectral bands such as red-edge and NIR often improve discrimination beyond RGB alone (Sakka et al., 2025; Wang et al., 2022; Sakka et al., 2024).

That broader evidence aligns with the attached paper's emphasis on NAIP's infrared band as useful for separating artificial structures from vegetation (Author & Author).

Main Strengths and Limits

Evidence strength across major claims

Evidence Strength	Claim
Strong	In-domain remote-sensing pretraining reduces natural-image domain mismatch and often improves transfer on RS tasks (Sun et al., 2023; Ghanbarzade & Soleimani, 2023; Wang et al., 2022; Guo et al., 2023)
Strong	Masked image modeling is now a leading SSL strategy for remote sensing foundation models (Muhtar et al., 2023; Hsu et al., 2024)
Moderate	Domain-specific SSL already surpasses supervised ImageNet pretraining for agricultural detection in low-label regimes (Author & Author; Rotich & Sarkar, 2025)

FIGURE 4 Evidence strength for the review's main claims

The attached paper's strongest contribution is empirical: it demonstrates that agricultural aerial detectors can be initialized from unlabeled in-domain pretraining and still remain competitive with heavily supervised ImageNet initialization across structurally distinct tasks (Author & Author).

Its biggest limitation is low-label robustness. In the 10% few-shot poultry setting, performance dropped from 97.9% to 70.6% mAP50 for the SSL model, while the ImageNet baseline remained at 97.7% mAP50 (Author & Author). This fits a broader pattern: remote-sensing foundation models often generalize unevenly across tasks, and oriented object detection remains harder than classification or segmentation (Rotich & Sarkar, 2025).

The paper's own discussion attributes that failure to insufficient pretraining scale rather than a flaw in SSL itself, noting that SSL models often need much longer schedules, around 800 to 1600 epochs, to become strong in few-shot transfer (Author & Author). Related work also supports the idea that target-domain unlabeled self-training or remote-sensing-specific pretraining can help when source-target gaps are large (Phoo & Hariharan, 2020; Alosaimi et al., 2023).

Suggested Review Structure

A strong literature review built around this paper should use five sections:

1. **Problem Context:** why agricultural infrastructure detection matters for environmental compliance, biosecurity, and land management (Author & Author; Robinson et al., 2021; Li et al., 2020).
2. **Limits of ImageNet Transfer:** summarize the domain gap between natural and aerial multispectral imagery and why in-domain pretraining is needed (Author & Author; Ghanbarzade & Soleimani, 2023; Wang et al., 2022).
3. **SSL and MIM Foundations:** cover BEiT, SparK, RingMo, CMID, FG-MAE, and geospatial foundation models as the methodological backbone (Bao et al., 2021; Tian et al., 2023; Sun et al., 2023; Muhtar et al., 2023; Wang et al., 2023).
4. **Agricultural and Aerial Detection Benchmarks:** compare poultry, greenhouse, DOTA, and related NAIP applications (Robinson et al., 2021; Li et al., 2020; Xia et al., 2017; Ding et al., 2021).
5. **Open Challenges:** emphasize few-shot weakness, cross-sensor adaptation, annotation uncertainty, and task dependence of foundation models (Author & Author; Marsocci & Audebert, 2024; Joshi & Witharana, 2025; Rotich & Sarkar, 2025).

The single most important shift in this literature is the move from supervised natural-image pretraining toward remote-sensing-specific self-supervised foundation models trained on unlabeled multispectral and multimodal imagery (Sun et al., 2023; Wang et al., 2023; Guo et al., 2023). The biggest open question is not whether domain-specific SSL works, but how to make it robust across sensors, tasks, and especially low-label detection regimes such as the few-shot failure seen in the attached paper (Author & Author; Rotich & Sarkar, 2025; Marsocci & Audebert, 2024).

These search results were found and analyzed using Consensus, an AI-powered search engine for research. Try it at https://consensus.app. © 2026 Consensus NLP, Inc. Personal, non-commercial use only; redistribution requires copyright holders' consent.

References

Alosaimi, N., Alhichri, H., Bazi, Y., Youssef, B. B., & Alajlan, N. (2023). Self-supervised learning for remote sensing scene classification under the few shot scenario. *Scientific Reports, 13*. https://doi.org/10.1038/s41598-022-27313-5

Author, F., & Author, S. Self-Supervised Masked Image Modeling on High-Resolution Multispectral Aerial Imagery for Automated Agricultural Infrastructure Detection.

Bao, H., Dong, L., & Wei, F. (2021). BEiT: BERT Pre-Training of Image Transformers. *ArXiv, abs/2106.08254*. https://doi.org/10.48550/arxiv.2106.08254

Bhatt, P., & Maclean, A. (2023). Comparison of high-resolution NAIP and unmanned aerial vehicle (UAV) imagery for natural vegetation communities classification using machine learning approaches. *GIScience & Remote Sensing, 60*. https://doi.org/10.1080/15481603.2023.2177448

Ding, J., Xue, N., Xia, G., Bai, X., Yang, W., Yang, M. Y., Belongie, S. J., Luo, J., Datcu, M., Pelillo, M., & Zhang, L. (2021). Object Detection in Aerial Images: A Large-Scale Benchmark and Challenges. *IEEE Transactions on Pattern Analysis and Machine Intelligence, 44*, 7778-7796. https://doi.org/10.1109/tpami.2021.3117983

Ghanbarzade, A., & Soleimani, H. (2023). Self-supervised in-domain representation learning for remote sensing image scene classification. *Heliyon, 10*. https://doi.org/10.1016/j.heliyon.2024.e37962

Guo, X., Lao, J., Dang, B., Zhang, Y., Yu, L., Ru, L., Zhong, L., Huang, Z., Wu, K., Hu, D., He, H., Wang, J., Chen, J., Yang, M., Zhang, Y., & Li, Y. (2023). SkySense: A Multi-Modal Remote Sensing Foundation Model Towards Universal Interpretation for Earth Observation Imagery. *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 27662-27673. https://doi.org/10.1109/cvpr52733.2024.02613

Hsu, C.-Y., Li, W., & Wang, S. (2024). Geospatial foundation models for image analysis: evaluating and enhancing NASA-IBM Prithvi's domain adaptability. *International Journal of Geographical Information Science, 39*, 2096 - 2125. https://doi.org/10.1080/13658816.2024.2397441

Jakubik, J., Roy, S., Phillips, C., Fraccaro, P., Godwin, D., Zadrozny, B., Szwarcman, D., Gomes, C., Nyirjesy, G., Edwards, B., Kimura, D., Simumba, N., Chu, L., Mukkavilli, S. K., Lambhate, D., Das, K., Bangalore, R., Oliveira, D. A. B., Muszynski, M., . . . Ramachandran, R. (2023). Foundation Models for Generalist Geospatial Artificial Intelligence. *ArXiv, abs/2310.18660*. https://doi.org/10.48550/arxiv.2310.18660

Joshi, D., & Witharana, C. (2025). Vision Transformer-Based Unhealthy Tree Crown Detection in Mixed Northeastern US Forests and Evaluation of Annotation Uncertainty. *Remote Sensing*. https://doi.org/10.3390/rs17061066

Li, M., Zhang, Z., Lei, L., Wang, X., & Guo, X. (2020). Agricultural Greenhouses Detection in High-Resolution Satellite Images Based on Convolutional Neural Networks: Comparison of Faster R-CNN, YOLO v3 and SSD. *Sensors (Basel, Switzerland), 20*. https://doi.org/10.3390/s20174938

Marsocci, V., & Audebert, N. (2024). Cross-Sensor Self-Supervised Training and Alignment for Remote Sensing. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, 18*, 12278-12289. https://doi.org/10.1109/jstars.2025.3566457

Muhtar, D., Zhang, X.-L., Xiao, P., Li, Z., & Gu, F.-X. (2023). CMID: A Unified Self-Supervised Learning Framework for Remote Sensing Image Understanding. *IEEE Transactions on Geoscience and Remote Sensing, 61*, 1-17. https://doi.org/10.1109/tgrs.2023.3268232

Phoo, C. P., & Hariharan, B. (2020). Self-training for Few-shot Transfer Across Extreme Task Differences. *ArXiv, abs/2010.07734*. https://doi.org/10.48550/arxiv.2010.07734

Robinson, C., Chugg, B., Anderson, B. R., Ferres, J., & Ho, D. E. (2021). Mapping Industrial Poultry Operations at Scale With Deep Learning and Aerial Imagery. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, 15*, 7458-7471. https://doi.org/10.1109/jstars.2022.3191544

Rotich, G., & Sarkar, S. (2025). Evaluating the Robustness of Foundation Models for Satellite Imagery. *IEEE Access, 13*, 107720-107735. https://doi.org/10.1109/access.2025.3581067

Sakka, M. E., Mothe, J., & Ivanovici, M. (2024). Images and CNN applications in smart agriculture. *European Journal of Remote Sensing, 57*. https://doi.org/10.1080/22797254.2024.2352386

Sakka, M. E., Ivanovici, M., Chaâri, L., & Mothe, J. (2025). A Review of CNN Applications in Smart Agriculture Using Multimodal Data. *Sensors (Basel, Switzerland), 25*. https://doi.org/10.3390/s25020472

Sun, X., Wang, P., Lu, W., Zhu, Z., Lu, X., He, Q., Li, J., Rong, X., Yang, Z., Chang, H., He, Q., Yang, G., Wang, R., Lu, J., & Fu, K. (2023). RingMo: A Remote Sensing Foundation Model With Masked Image Modeling. *IEEE Transactions on Geoscience and Remote Sensing, 61*, 1-22. https://doi.org/10.1109/tgrs.2022.3194732

Tian, K., Jiang, Y., Diao, Q., Lin, C., Wang, L., & Yuan, Z. (2023). Designing BERT for Convolutional Networks: Sparse and Hierarchical Masked Modeling. *ArXiv, abs/2301.03580*. https://doi.org/10.48550/arxiv.2301.03580

Wang, D., Zhang, J., Du, B., Xia, G., & Tao, D. (2022). An Empirical Study of Remote Sensing Pretraining. *IEEE Transactions on Geoscience and Remote Sensing, PP*, 1-1. https://doi.org/10.1109/tgrs.2022.3176603

Wang, Y., Hern'andez, H. H., Albrecht, C., & Zhu, X. X. (2023). Feature Guided Masked Autoencoder for Self-Supervised Learning in Remote Sensing. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, 18*, 321-336. https://doi.org/10.1109/jstars.2024.3493237

Wang, D., Cao, W., Zhang, F., Li, Z.-R., Xu, S., & Wu, X. (2022). A Review of Deep Learning in Multiscale Agricultural Sensing. *Remote. Sens., 14*, 559. https://doi.org/10.3390/rs14030559

Wang, Y., Braham, N., Xiong, Z., Liu, C., Albrecht, C., & Zhu, X. (2023). SSL4EO-S12: A large-scale multimodal, multitemporal dataset for self-supervised learning in Earth observation [Software and Data Sets]. *IEEE Geoscience and Remote Sensing Magazine, 11*, 98-106. https://doi.org/10.1109/mgrs.2023.3281651

Xia, G.-S., Bai, X., Ding, J., Zhu, Z., Belongie, S. J., Luo, J., Datcu, M., Pelillo, M., & Zhang, L. (2017). DOTA: A Large-Scale Dataset for Object Detection in Aerial Images. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 3974-3983. https://doi.org/10.1109/cvpr.2018.00418