

5.18 Controller InventoryDataFileScans

The *InventoryDataFileScans* controller provides actions concerning *Inventory* objects with data of a file scan. This data is gathered in the bMS with a software scan.

To request *Inventory* objects with file scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the node *Inventoried Files* and the corresponding endpoint in the bMS. To delete *Inventory* objects the specified user needs read rights on the node *Inventoried Files* as well as read and modify rights on the endpoint. Inventory file scan data can be managed for endpoints of type *WindowsEndpoint* only.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryDataFileScans

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>Inventory</i> objects with the file scan data.	2015
GET	EndpointID=<endpoint id>	Returns the <i>Inventory</i> object with the file scan data of the endpoint with the specified ID.	2015
DELETE	EndpointID=<endpoint id>	Deletes all file scan data of the endpoint with the specified ID.	2015

[Properties of *Inventory*.](#)

[Properties of *DataFile*.](#)

5.19 Controller InventoryDataWMIScans

The *InventoryDataWMIScans* controller provides actions concerning *Inventory* objects with data of a WMI scan.

To request *Inventory* objects with WMI scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the corresponding endpoint. Inventory WMI scan data can be read for endpoints of type *WindowsEndpoint* only.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryDataWMIScans

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>Inventory</i> objects with WMI scan data.	2015
GET	TemplateName=<name of the WMI scan template>	Returns a list of all available <i>Inventory</i> objects with WMI scan data of scans executed with the specified inventory template.	2015
GET	TemplateName=<name of the WMI scan template> & Scan=<scan term>	Returns a list of all available <i>Inventory</i> objects with WMI scan data of the latest scan executed with the specified inventory template. As scan term only "Latest" is supported at the moment.	2015
GET	EndpointID=<endpoint id>	Returns an <i>Inventory</i> object with WMI scan data of the endpoint with the specified ID.	2015
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template>	Returns the <i>Inventory</i> object with WMI scan data, gathered with the specified inventory template only, of the endpoint of the specified ID.	2015
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template> & Scan=<scan term / time>	Returns the <i>Inventory</i> object with WMI scan data, gathered with the specified inventory template at the specified time or the latest scan only, of the endpoint of the specified ID. As scan term only "Latest" is supported at the moment. The scan time must be specified as UTC time in the format "yyyy-MM-ddThh:mm:ssZ" (y=year, M=month, d=day, h=hours, m=minutes, s=seconds). The scan time of the scans can be obtained over the InventoryOverviews controller.	2015

[Properties of Inventory.](#)

[Properties of DataWMI.](#)

5.20 Controller InventoryDataCustomScans

The *InventoryDataCustomScans* controller provides actions concerning *Inventory* objects with data of a Custom scan.

To request *Inventory* objects with custom scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the corresponding endpoint. Inventory Custom scan data can be read for endpoints of type *WindowsEndpoint* only.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryDataCustomScans

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>Inventory</i> objects with Custom scan data.	2015
GET	TemplateName=<name of the used scan template>	Returns a list of all available <i>Inventory</i> objects with Custom scan data of scans executed with the specified inventory template.	2015
GET	TemplateName=<name of the scan template> & Scan=<scan term>	Returns a list of all available <i>Inventory</i> objects with Custom scan data of the latest scan executed with the specified inventory template. As scan term only "Latest" is supported at the moment.	2015
GET	EndpointID=<endpoint id>	Returns an <i>Inventory</i> object with Custom scan data of the endpoint with the specified ID.	2015
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template>	Returns the <i>Inventory</i> object with Custom scan data, gathered with the specified inventory template only, of the endpoint of the specified ID.	2015
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template> & Scan=<scan term / time>	Returns the <i>Inventory</i> object with Custom scan data, gathered with the specified inventory template at the specified time or the latest scan only, of the endpoint of the specified ID. As scan term only "Latest" is supported at the moment. The scan time must be specified as UTC time in the format "yyyy-MM-ddThh:mm:ssZ" (y=year, M=month, d=day, h=hours, m=minutes, s=seconds). The scan time of the scans can be obtained over the InventoryOverviews controller.	2015

[Properties of Inventory.](#)

[Properties of DataCustom.](#)

5.21 Controller InventoryDataHardwareScans

The *InventoryDataHardwareScans* controller provides actions concerning *Inventory* objects with data of a hardware scan.

To request *Inventory* objects with hardware scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the corresponding endpoint. Inventory hardware scan data can be requested for the following types of endpoints (Windows, iOS, Android and Mac).

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryDataHardwareScans

Method	URL parameters	Description	Since bMS
GET	EndpointID=<endpoint id>	Returns an <i>Inventory</i> object with hardware scan data of the endpoint with the specified ID.	2017
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template>	Returns the <i>Inventory</i> object with hardware scan data, gathered with the specified inventory template only, of the endpoint of the specified ID. If endpoint is not of type <i>WindowsEndpoint</i> the parameter "TemplateName" is ignored.	2017
GET	EndpointID=<endpoint id> & TemplateName=<name of the scan template> & Scan=<scan term / time>	Returns the <i>Inventory</i> object with Custom scan data, gathered with the specified inventory template at the specified time or the latest scan only, of the endpoint of the specified ID. As scan term only "Latest" is supported at the moment. The scan time must be specified as UTC time in the format "yyyy-MM-ddThh:mm:ssZ" (y=year, M=month, d=day, h=hours, m=minutes, s=seconds). For endpoints of type <i>WindowsEndpoint</i> the scan time of the scans can be obtained over the InventoryOverviews controller. If endpoint is not of type <i>WindowsEndpoint</i> the parameter "TemplateName" and "Scan" are ignored.	2017

[Properties of Inventory.](#)

[Properties of DataHardware.](#)

5.22 Controller InventoryDataSnmpScans

The *InventoryDataSnmpScans* controller provides actions concerning *Inventory* objects with data of a SNMP scan. This data is gathered in the bMS with a SNMP job.

To request *Inventory* objects with SNMP scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the node *Inventoried Files* and the corresponding endpoint in the bMS.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryDataSnmpScans

Method	URL parameters	Description	Since bMS
GET	EndpointID=<endpoint id>	Returns the <i>Inventory</i> object with the SNMP scan data of the endpoint with the specified ID.	2017

[Properties of *Inventory*.](#)

[Properties of *DataSnmp*.](#)

5.23 Controller InventoryOverviews

The *InventoryOverviews* controller provides actions concerning *InventoryOverview* objects. It contains overview data of Custom, WMI and Hardware scans executed on a specific client.

To request *InventoryOverview* objects the URL must contain the bConnect version information. Only those *InventoryOverview* objects can be read, the specified user has at least configured read rights on the corresponding endpoint. *InventoryOverview* objects can be read for endpoints of type *WindowsEndpoint* only.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryOverviews

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>InventoryOverview</i> objects.	2015
GET	EndpointID=<endpoint id>	Returns the <i>InventoryOverview</i> object of the endpoint with the specified ID.	2015

[Properties of *InventoryOverview*](#)

5.24 Controller InventoryAppScans

The *InventoryAppScans* controller provides actions concerning *Inventory* objects with data of a mobile device app scan.

To request *Inventory* objects with app scan data the URL must contain the bConnect version information. Only those *Inventory* objects can be read, the specified user has at least configured read rights on the corresponding endpoints of type *Android* and *iOS* only.

URL: https://<bmsserver>:<port>/bConnect/v1.1/InventoryAppScans

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>Inventory</i> objects with app scan data.	2016R2
GET	EndpointID=<endpoint id>	Returns a list of all available <i>Inventory</i> objects with app scan data of scans executed on an endpoint specified by ID.	2016R2

[Properties of *Inventory*.](#)

[Properties of *InventoryApp*.](#)

5.25 Controller SoftwareScanRules

The *SoftwareScanRules* controller provides actions concerning the *SoftwareScanRule* objects that are created as result of the client software inventory, of the bMS. *SoftwareScanRule* objects are available for endpoints of type *WindowsEndpoint* only.

To request *SoftwareScanRule* object data the URL must contain the bConnect version information and the specified user needs at least configured read rights on the node "Software scan rules" in the module *Inventory*.

URL: https://<bmsserver>:<port>/bConnect/v1.1/SoftwareScanRules

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>SoftwareScanRule</i> objects.	2014

[Properties of SoftwareScanRule.](#)

Examples:

- GET-Request:
https://bmsserver.customer.net/bConnect/v1.1/softwarescanrules.xml

Result:

```
<ArrayOfSoftwareScanRule>
  <SoftwareScanRule>
    <Category>ManagedSoftware</Category>
    <Comment/>
    <Id>006548b4-d65b-4e6a-870e-a9f1eb8542f5</Id>
    <IsMswRule>true</IsMswRule>
    <Protected>true</Protected>
    <Rules>chlcdfkeanhekcakeigla...hlniifpakf</Rules>
    <SoftwareManufacturer>VideoLan</SoftwareManufacturer>
    <SoftwareName>VLC</SoftwareName>
    <SoftwareVersion>2.1.1-x64</SoftwareVersion>
  </SoftwareScanRule>
  <SoftwareScanRule>
    <Category/>
    <Comment/>
    ...
    <SoftwareVersion>5.0.0.16964</SoftwareVersion>
  </SoftwareScanRule>
  ...
  ...
</ArrayOfSoftwareScanRule>
```

5.26 Controller SoftwareScanRuleCounts

The *SoftwareScanRuleCounts* controller provides actions to get *SoftwareScanRuleCount* objects that provide the endpoints which match the software scan rule along with a count. *SoftwareScanRuleCount* objects are available for endpoints of type *WindowsEndpoint* only.

To request *SoftwareScanRuleCount* object data the URL must contain the bConnect version information and the specified user needs at least configured read rights on the node “*Licenses*” in the module *Licenses*.

URL: https://<bmsserver>:<port>/bConnect/v1.1/SoftwareScanRuleCounts

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>SoftwareScanRuleCount</i> objects.	2018 R2

[Properties of SoftwareScanRuleCount.](#)

Examples:

- GET-Request:
https://bmsserver.customer.net/bConnect/v1.1/softwarescanrulecounts.xml

Result:

```
<ArrayOfSoftwareScanRuleCount>
  <SoftwareScanRuleCount>
    <InstalledCount>50</InstalledCount>
    <InstalledEndpoints>
      <EndpointInfo>
        <Id>17B65E8A-DBF3-456C-B5A5-38E596F01C20</Id>
        <Name>WIN10-ENT</Name>
      </EndpointInfo>
    </InstalledEndpoints>
    <SoftwareScanRule>
      <Category>ManagedSoftware</Category>
      <Comment/>
      <Id>006548b4-d65b-4e6a-870e-a9f1eb8542f5</Id>
      <IsMswRule>true</IsMswRule>
      <Protected>false</Protected>
      <Rules>chlcdfkeanhekdakeigla...hlniifpakf</Rules>
      <SoftwareManufacturer>Oracle</SoftwareManufacturer>
      <SoftwareName>Java JRE</SoftwareName>
      <SoftwareVersion>8.0.111.14-x64</SoftwareVersion>
    </SoftwareScanRule>
  </SoftwareScanRuleCount>
</ArrayOfSoftwareScanRuleCount>
```


5.27 Controller EndpointInvSoftware

The *EndpointInvSoftware* controller provides actions concerning the *EndpointInvSoftware* objects, which contain the link between endpoints and inventoried software, of the bMS. *EndpointInvSoftware* objects are available for endpoints of type *WindowsEndpoint* only.

To request *EndpointInvSoftware* object data the URL must contain the bConnect version information and the specified user needs at least configured read rights for the corresponding *Endpoint* objects and the node "Software scan rules" in the module *Inventory*.

URL: https://<bmsserver>:<port>/bConnect/V1.1/EndpointInvSoftware

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all available <i>EndpointInvSoftware</i> objects.	2014

[Properties of *EndpointInvSoftware*.](#)

Examples:

- GET-Request:
https://bmsserver.customer.net/bConnect/v1.1/endpointinvsoftware.xml

Result:

```
<ArrayOfEndpointInvSoftware>
  <EndpointInvSoftware>
    <ConflictedRules>0</ConflictedRules>
    <GuidEndpoint>26c2712a-7f5e-4307-b675-8139accf4b4d</GuidEndpoint>
    <GuidRule>04b2928e-645b-4a99-8a2c-746fdc2c122d</GuidRule>
    <InventoryPath>$Registry$</InventoryPath>
    <InventoryVersion>8.8.9.237</InventoryVersion>
    <LastSeen>2013-05-22T09:30:56+02:00</LastSeen>
  </EndpointInvSoftware>
  <EndpointInvSoftware>
    <ConflictedRules>0</ConflictedRules>
    <GuidEndpoint>26c2712a-7f5e-4307-b675-8139accf4b4d</GuidEndpoint>
    <GuidRule>0574135c-901d-4b70-8f4c-f18d911068f5</GuidRule>
    <InventoryPath>$Registry$</InventoryPath>
    <InventoryVersion>6.2 SP0 x64-EN</InventoryVersion>
    <LastSeen>2013-05-22T09:30:56+02:00</LastSeen>
  </EndpointInvSoftware>
  ...
</ArrayOfEndpointInvSoftware>
```

5.28 Controller Images

The *Images* controller provides actions concerning the *Image* objects. Image objects are supported on [Jobs](#).

To request *Images* object data the URL must contain the bConnect version information.

URL: https://<bmsserver>:<port>/bConnect/V1.1/Images

Method	URL parameters	Description	Since bMS
GET	Id	Returns an Image .	2018 R2

[Properties of Image.](#)

Examples:

- GET-Request:
https://bmsserver.customer.net/bConnect/v1.1/images.xml?Id=B227BAACC41C9D51BD03B823E785A084

Result:

```
<Image>
  <Id>B227BAACC41C9D51BD03B823E785A084</Id>
  <MimeType>image/jpeg</MimeType>
  <Data>...</Data>
</Image>
```

5.29 Controller VariableDefinitions

The VariableDefinitions controller provides functionality to read, create, update and delete custom variables. These custom variables are available as [ObjectVariables](#) for the corresponding bMS objects, which do support variables.

Note: The deletion of a VariableDefinition object will also delete all its corresponding ObjectVariable instances.

To request *VariableDefinition* object data the URL must contain the bConnect version information.

URL: https://<bmsserver>:<port>/bConnect/V1.1/VariableDefinitions

Method	URL parameters	Description	Since bMS
GET	None	Returns all custom variables as a list of <i>VariableDefinition</i> objects. (Check properties of VariableDefinition for more information)	2019
GET	ID=<vardef id>	Returns a single <i>VariableDefinition</i> object with the specified ID	2019
GET	Scope=<vardef scope>	Returns custom variables with the given Scope as a list of <i>VariableDefinition</i> objects. Currently supported scopes are "Device", "MobileDevice" (DEPRECATED), "OrgUnit", "Job", "Software", "HardwareProfile", "AdObject", "Bulletin", "Component", "NetworkDevice", "ICDevice", "AndroidDevice" and "IOSDevice". The scopes "NetworkDevice", "ICDevice", "AndroidDevice" and "IOSDevice" can be combined as a comma separated list and are applicable for variable types "String", "Number", "Date" and "Password" only.	2019
GET	Scope=<vardef scope> & Category=<vardef category>	Returns custom variables with the given Scope and Category as a list of <i>VariableDefinition</i> objects	2019
GET	Scope=<vardef scope> & Category=<vardef category> & Name=<vardef name>	Returns a single <i>VariableDefinition</i> object with the given Scope, Category and Name	2019
POST	None (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Creates a new <i>VariableDefinition</i> object according to the specified mandatory and optional data. Mandatory properties: • Scope • Category • Name • Type	2019

PATCH	ID=<vardef id> (The properties that are to be updated must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Updates the specified properties of the <i>VariableDefinition</i> object by ID. Optional properties: • Category • Name • Value • Comments • Scope (only possible for scopes "NetworkDevice", "ICDevice", "AndroidDevice" and "IOSDevice")	2019
DELETE	ID=< vardef id >	Deletes a <i>VariableDefinition</i> object by ID.	2019

Examples:

- GET-Request:

<https://bmssserver.customer.net/bConnect/v1.1/variabledefinitions>

Result:

```
<ArrayOfVariableDefinition>
  <VariableDefinition>
    <Category>Location</Category>
    <Comments></Comments>
    <Id>07311C36-668C-4794-BD60-C79DD4A3D191</Id>
    <Name>Cost center</Name>
    <Scope>Device</Scope>
    <Type>Checkbox</Type>
    <Value>1</Value>
  </VariableDefinition>
  <VariableDefinition>
    <Category>Location</Category>
    <Comments/>
    <Id>292F4106-6CBD-410D-8527-FB2B979A828F</Id>
    <Name>Building</Name>
    <Scope>Device</Scope>
    <Type>String</Type>
    <Value></Value>
  </VariableDefinition>
  <VariableDefinition>
    <Category>Warranty data</Category>
    <Comments/>
    <Id>95371B4C-3F14-4ADA-9F8D-C13ED7F2878E</Id>
    <Name>Inventory id</Name>
    <Scope>Device</Scope>
    <Type>String</Type>
    <Value></Value>
  </VariableDefinition>
  ...

```

```
</ArrayOfVariableDefinition>
```

- PATCH-Request:

<https://localhost:443/bconnect/v1.1/variabledefinitions.xml?id=0E3D4C92-96F3-4260-BBFD-6D5218FDB087>

Body (xml format):

```
<VariableDefinition xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BC
onnect.DataModel">
  <Comments>default value updated</Comments>
  <Value>new default value</Value>
</VariableDefinition>
```

Result:

```
<VariableDefinition>
  <Category>Location</Category>
  <Comments>default value updated</Comments>
  <Id>0E3D4C92-96F3-4260-BBFD-6D5218FDB087</Id>
  <Name>Building</Name>
  <Scope>Device</Scope>
  <Type>String</Type>
  <Value>new default value</Value>
</VariableDefinition>
```

5.30 Controller KioskJobs

The KioskJobs controller provides functionality to read, create and delete job releases. They are available as [KioskJob](#) objects.

URL: `https://<bmsserver>:<port>/bConnect/V1.1/KioskJobs`

Method	URL parameters	Description	Since bMS
GET	User=<user_principal_name>	Returns a list of all released <i>KioskJob</i> objects for the specified user	2019
GET	EndpointId=<endpoint id>	Returns a list of all released <i>KioskJob</i> objects for the specified endpoint. Result also includes all inherited releases.	2019
GET	GroupId=<group id>	Returns a list of all released <i>KioskJob</i> objects for the specified group. Result also includes all inherited releases	2019
GET	JobDefinitionId =<job id>	Returns a list of all released <i>KioskJob</i> objects for the specified job definition.	2019
POST	JobDefinitionId=<job id> & TargetId=<endpoint id / group id / user id>	Release a job for endpoint, group or user.	2019
POST	JobDefinitionId=<job id> & User=<user_principal_name>	Release a job for user.	2019 R2
DELETE	KioskJobId=<kiosk job id>	Delete <i>KioskJob</i>	2019

Examples:

- GET-Request:

`https://bmsserver.customer.net/bConnect/v1.1/KioskJobs?endpointId=E4D6F70F-290C-4B0E-B9A9-D823171FF5E3`

Result:

```
[{
  "Id": "4",
  "AssignedObjectId": "E4D6F70F-290C-4B0E-B9A9-D823171FF5E3",
  "AssignedObjectName": "Windows PC",
  "AssignedObjectType": "WindowsEndpoint",
  "JobDefinitionId": "A57D8D92-D088-4FBF-BDE3-38FE3102297D",
  "JobDefinitionName": "Windows-Scan",
  "JobDefinitionDisplayName": "Windows-Scan",
  "JobDefinitionCategory": "",
  "JobDefinitionSupportedPlatforms": [
    "Windows"
  ]
}]
```

5.31 Controller EndpointSecrets

The EndpointSecrets controller provides functionality to read and update disk encryption information. They are available as [EndpointSecrets](#) objects.

URL: `https://<bmsserver>:<port>/bConnect/V1.1/EndpointSecrets`

Method	URL parameters	Description	Since bMS
GET	EndpointId=<endpoint id>	Returns the BitLocker unlock pin and volume secret information	2019 R2
PATCH	EndpointID=< endpoint id >	Optional properties: Pin	2019 R2

Examples:

- GET-Request:
`https://bmsserver.customer.net/bConnect/v1.1/EndpointSecrets?endpointId=E4D6F70F-290C-4B0E-B9A9-D823171FF5E3`

Result:

```
{
  "EndpointId": "E4D6F70F-290C-4B0E-B9A9-D823171FF5E3",
  "Pin": "123456",
  "VolumeSecretEntries": [
    {
      "VolumeId": "\\?\\Volume{1bc10a7f-b18c-3591-c322-075836942588}\\",
      "VolumeName": "System (C:)",
      "IsSystemVolume": true,
      "GeneratedRecoveryKey": "123456-789012-345678-901234-567890-123456-789012",
      "InventoryRecoveryKey": "123456-789012-345678-901234-567890-123456-789012",
      "InventoryTimestamp": "2019-10-10T09:14:33Z"
    }
  ]
}
```

5.32 Controller EndpointEnrollment

The EndpointEnrollment controller provides functionality to trigger enrollment state of a **Windows** endpoint. This means the endpoint will be set to Internet mode, the public key (if existing) is deleted and the enrollment data is generated / overwritten. By specifying an e-mail recipient, you can also have a corresponding e-mail with the enrollment information sent automatically.

URL: https://<bmsserver>:<port>/bConnect/V1.1/EndpointEnrollment

Method	URL parameters	Description	Since bMS
POST	sync=<true / false> (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Sets mode of the endpoint to <i>Internet</i>, deletes its stored public key (if existing) and generates / overwrites the enrollment data of this endpoint. By specifying an e-mail recipient, you can also have a corresponding e-mail with the enrollment information sent automatically. The optional EmailLanguageId parameter sets which e-mail template is used for the enrollment message. Default available mail templates are "de-DE" and "en-US". If the email language is not specified, the English template ("en-US") will be used. The optional URL parameter "sync" specifies whether to wait until the email has been successfully sent to the configured SMTP server (default: sync = false). Returns an EnrollmentData object. Mandatory Properties: - EndpointId Optional Properties: - EmailRecipient - EmailLanguageId	2020 R1

Example:

- POST-Request:
<https://bmsserver.customer.net/bConnect/v1.1/EndpointEnrollment.json>

Request body:

```
{
  "EndpointId" : " E4D6F70F-290C-4B0E-B9A9-D823171FF5E3",
  "EmailRecipient" : "user@customer.com",
  "EmailLanguageId": "de-DE"
}
```


Result:

```
{
  "EndpointId": " E4D6F70F-290C-4B0E-B9A9-D823171FF5E3",
  "InstallCommand":
    "ManagementAgent_setup.exe /Q OPTIONS=655667 INTERNET_MODE=1
    INTERNET_SERVER=172.16.5.55 INTERNET_SERVERPORT=443
    INTERNET_SERVERKEY=\"308201223...\" SERVERKEY=\"308201223...\"
    ENROLLMENT_TOKEN_DATA=\"ChF5dX...\",
  "ValidUntil": "\"2019-12-19T14:41:18.717792500Z\""
}
```

5.33 Controller ServerState

The ServerState controller provides functionality to read the current state of the baramundi server and its sub services.

URL: https://<bmsserver>:<port>/bConnect/V1.1/ServerState

Method	URL parameters	Description	Since bMS
GET	None	Returns a ServerState object, which represents the current state of the baramundi server and its sub services	2020 R1

Example:

- GET-Request:
<https://bmsserver.customer.net/bConnect/v1.1/ServerState.json>

Result:

```
{
  "Name": "bmsserver.customer.net ",
  "ExecutionState": "Running",
  "Services": [
    {
      "Name": "Active Directory Connector",
      "ExecutionState": "Running",
      "StateText": []
    },
    ...
    {
      "Name": "Windows Software Inventory",
      "ExecutionState": "Running",
      "StateText": [
        "Idle"
      ]
    }
  ]
}
```

5.34 Controller VPPUsers

The VPPUsers controller provides functionality to read, create and delete (retire) Apple VPP users.

Note: In order to use the VPPUsers controller a valid VPP token must be imported.

To request *VPPUser* object data the URL must contain the bConnect version information.

URL: https://<bmsserver>:<port>/bConnect/V1.1/VPPUsers

Method	URL parameters	Description	Since bMS
GET	None	Returns VPP users as a list of <i>VPPUser</i> objects. (Check properties of VPPUser for more information)	2020 R2
GET	ID=<vpp user id>	Returns a single <i>VPPUser</i> object by ID.	2020 R2
GET	Email=<VPP user email>	Returns the VPP users as a list of <i>VPPUser</i> objects, where the email address matches with the given parameter	2020 R2
GET	ManagedAppleId=<VPP user managed Apple Id>	Returns the VPP users as a list of <i>VPPUser</i> objects, where the managed Apple Id matches with the given parameter	2020 R2
GET	UserId=<VPP user UserId>	Returns the VPP users as a list of <i>VPPUser</i> objects, where the userId (assigned by Apple) matches with the given parameter	2020 R2
GET	ItunesStoreHash=<VPP user Itunes store hash>	Returns the VPP users as a list of <i>VPPUser</i> objects, where the Itunes store hash matches with the given parameter	2020 R2
POST	sendInvitationMail=<<i>True</i>, if an invitation mail should be sent to the given Email address, otherwise <i>False</i>> An email will only be sent in case of a non-managed Apple-Id. If the email language is not specified, the English template ("en-US") will be used. (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Creates a new <i>VPPUser</i> object according to the specified data. Mandatory properties: - IsManagedAppleId - Email (if 'IsManagedAppleId' is <i>False</i>) - ManagedAppleId (if 'IsManagedAppleId' is <i>True</i>) Optional properties: - EmailLanguageId (default available Values are "de-DE" and "en-US")	2020 R2
DELETE	ID=<vpp user id>	Deletes/retires a <i>VPPUser</i> object by ID.	2020 R2
PATCH	ID=<vpp user id>	Updates a set of properties of the <i>Job</i> with the specified ID.	2020R2

Examples:

- POST-Request:
`https://localhost:443/bconnect/v1.1/vppusers.json?sendInvitationMail=true`
 Body (json format):

```
{
  "Email": "Jones.Dow@myprivatemail.com",
  "IsManagedAppleId": false
}
```

 Result:

```
{
  "Id": "BF945C04-1A13-4F44-BCE6-FC998AE819FB",
  "Email": "Jones.Dow@myprivatemail.com ",
  "ManagedAppleId": null,
  "ItunesStoreHash": "",
  "InviteUrl":
    "https://buy.itunes.apple.com/WebObjects/MZFinance.woa/wa/associateVPPUserWith
    iTunesAccount?cc=de&l=en&inviteCode=fdbf5fb69b4feba7222edfb6&mt=8",
  "Status": "Registered",
  "UserId": "94675313",
  "IsManagedAppleId": false
}
```

5.35 Controller VPPLicenseAssociations

The VPPLicenseAssociations controller provides functionality to read, create and delete VPP license associations.

Note: In order to use the VPPLicenseAssociations controller a valid VPP token must be imported.

To request *VPPLicenseAssociation* object data the URL must contain the bConnect version information.

URL: `https://<bmsserver>:<port>/bConnect/V1.1/VPPLicenseAssociations`

Method	URL parameters	Description	Since bMS
GET	None	Returns VPP license associations as a list of <i>VPPLicenseAssociation</i> objects. (Check properties of VPPLicenseAssociation for more information)	2020 R2
GET	ID=<vpp license association id>	Returns a single <i>VPPLicenseAssociation</i> object by ID.	2020 R2
GET	EndpointId=<endpoint id>	Returns the VPP license associations as a list of <i>VPPLicenseAssociation</i> objects, where the endpoint id matches with the given parameter	2020 R2
GET	UserId=<VPP user UserId>	Returns the VPP license associations as a list of <i>VPPLicenseAssociation</i> objects, where the user id matches with the given parameter	2020 R2

POST	None (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Creates new <i>VPPLicenseAssociation</i> objects according to the specified data. Mandatory properties: - BundleId - ClientUserIdStr	2020 R2
DELETE	ID=<vpp license association id>	Deletes a <i>VPPLicenseAssociation</i> object by ID. This call will disassociate the VPP license of the given bundle identifier from the VPP user.	2020 R2
DELETE	UserId=<VPP user UserId>	Deletes all <i>VPPLicenseAssociation</i> objects of the given VPP user. This call will disassociate all VPP licenses of the VPP user.	2020 R2

Examples:

- POST-Request:

<https://localhost:443/bconnect/v1.1/vpplicenseassociations.xml>

Body (xml format):

```
<VPPLicenseAssociation xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BC
onnect.DataModel">
  <BundleId>com.baramundi.bmdenroll</BundleId>
  <ClientUserIdStr>2E97E7C1-CEF9-4611-A8BB-3E90ADFFE8A8</ClientUserIdStr>
</VPPLicenseAssociation>
```

Result:

```
<VPPLicenseAssociation xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BC
onnect.DataModel">
  <AdamId>593959012</AdamId>
  <BmsNetEndpoint i:nil="true" />
  <BundleId>com.baramundi.bmdenroll</BundleId>
  <ClientUserIdStr>2E97E7C1-CEF9-4611-A8BB-3E90ADFFE8A8</ClientUserIdStr>
  <Id>D04ABB35-16B2-499C-AF3B-440A1A07C3BE</Id>
  <LicenseIdStr>561967974</LicenseIdStr>
  <SerialNumber i:nil="true" />
  <ShouldBeDisassociated>false</ShouldBeDisassociated>
</VPPLicenseAssociation>
```

5.36 Controller MicrosoftUpdateInventories

The MicrosoftUpdateInventories controller provides the functionality to read the Microsoft Update Inventory data of the Windows endpoints. This includes the missing and installed updates found with the last Microsoft Update Inventory job.

To request *MicrosoftUpdateInventories* object data the URL must contain the bConnect version information.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftUpdateInventories>

Method	URL parameters	Description	Since bMS
GET	None	Returns installed and missing updates as a list of <i>MicrosoftUpdateInventories</i> objects for all Windows endpoints. (Check properties of MicrosoftUpdateInventories for more information).	2020 R2
GET	EndpointId=<endpoint id>	Returns installed and missing updates as a list of <i>MicrosoftUpdateInventories</i> objects for the specified Windows endpoint.	2020 R2
GET	GroupId=<group id>	Returns installed and missing updates as a list of <i>MicrosoftUpdateInventories</i> objects for all windows endpoints within the specified group. By default, only endpoints that are directly in this group are returned. For the inclusion of subgroup endpoints, see below.	2020 R2
	ExtendedInformation=<true/false>	Optional for all GET methods: If "true", the returned objects also contain the corresponding Description=<Description> and MoreInfoUrls=<MoreInfoUrls> properties.	2020 R2
	Recursive=<true/false>	Optional for GET method with GroupID parameter: If "true", installed and missing updates are returned as a list of <i>MicrosoftUpdateInventories</i> objects for all windows endpoints within the corresponding group and their subgroups. If not specified this parameter is taken as "false" by default.	2020 R2

Examples:

- GET-Request:

<https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftUpdateInventories?GroupID=036D9C03-4F3E-47E9-8123-2E8B0456C4C7&Recursive=true>

Result:

```
{
  "Endpoints": [
    {
      "EndpointID": "A61C9A21-DB8D-498C-9F9C-7B28E9DF9B9B",
      "UpdateInformation": [
        {
          "IsInstalled": False,
          "UpdateId": "C2A8FCE2-B93A-4FC0-95EA-16B783F341F4",
          "RevisionNumber": "200",
          "Classification": "Security Updates",
          "Products": [
            "Windows 10"
          ],
          "Title": "2020-02 Security Update for Adobe Flash Player for Windows 10 (KB4537759)",
          "Type": "Software",
          "SupportURL": "https://support.microsoft.com/help/4537759",
          "LastDeploymentChangeTime": "2019-01-15T00:00:00Z",
          "MsrcSeverity": "Critical",
          ...
        }
      ]
    }
  ]
}
```

5.37 Controller ComplianceViolations

The ComplianceViolations controller provides the functionality to read the compliance violations of all endpoint types.

To request *ComplianceViolations* object data the URL must contain the bConnect version information.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/ComplianceViolations>

Method	URL parameters	Description	Since bMS
GET	None	Returns compliance violations as a list of ComplianceViolations. (Check properties of ComplianceViolation for more information).	2020 R2
GET	EndpointId=<endpoint id>	Returns compliance violations of the specific endpoint	2020 R2

Examples:

- GET-Request:
<https://<bmsserver>:<port>/bConnect/V1.1/ComplianceViolations?EndpointId=036D9C03-4F3E-47E9-8123-2E8B0456C4C7>

Result:

```
{
  "CveId": "337B9D1A-744C-45FC-B670-8AAF50B80427"
  "EndpointId": "A61C9A21-DB8D-498C-9F9C-7B28E9DF9B9B",
  "Endpoint": "PC01 (domain.net)",
  "Name": "CVE-2015-0004"
  "Products": "Mozilla Firefox, Mozilla SeaMonkey",
  "CvssScore": 7.5,
  "Severity": "High",
  "Description": "...",
  "ComplianceType": "Windows",
  "State": "Active"
}
```

5.38 Controller VulnerabilityExclusions

The VulnerabilityExclusions controller provides the functionality to read the exclusions for vulnerabilities of industrial endpoints.

To request *VulnerabilityExclusions* object data the URL must contain the bConnect version information.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/VulnerabilityExclusions>

Method	URL parameters	Description	Since bMS
GET	None	Returns vulnerability exclusions as a list of VulnerabilityExclusions. (Check properties of VulnerabilityExclusion for more information).	2020 R2
GET	ObjectId=<object id>	Returns vulnerability exclusions of the specific <i>ObjectId</i> (logical group or endpoint). Sub units are not considered.	2020 R2
	includeSubfolders =<true/false>	Optional: If "true", the returned objects also contain vulnerability exclusions from sub units. If not specified, this parameter is taken as "false" by default.	2020 R2

Examples:

- GET-Request:
<https://<bmsserver>:<port>/bConnect/V1.1/VulnerabilityExclusions?objectId=A872D345-FE5F-4B0A-854C-6904B502E8DB&includeSubfolders=true>

Result:

```
{
  "CveName": "CVE-2016-8673",
  "CveId": "BE7DC137-A765-4F1D-8693-946D940CEF81",
  "OriginName": "Controlling Germany",
  "OriginId": "A872D345-FE5F-4B0A-854C-6904B502E8DB",
  "Initiator": "initiator@test.net",
  "Added": "2020-08-24T06:52:33.9423879Z",
  "Reason": "Update does not exist yet",
  "Status": "Exclusion"
}
```

5.39 Controller MicrosoftUpdateProfiles

The MicrosoftUpdateProfiles controller provides the functionality to read, create and modify Microsoft Update Profiles that provide an easy way to configure staging when deploying Microsoft updates.

To request *MicrosoftUpdateProfiles* object data the URL must contain the bConnect version information.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftUpdateProfiles>

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of existing Microsoft Update Profiles (Check properties of MicrosoftUpdateProfile for more information).	2021 R1
GET	Id=<id>	Returns the MicrosoftUpdateProfile that matches the provided ID.	2021 R1
GET	Name=<name>	Returns the MicrosoftUpdateProfile that matches the provided name.	2021 R1
POST	None (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Creates new MicrosoftUpdateProfile objects according to the specified data. Mandatory properties: - Name Optional properties: - Comment - UpdateDeferralPeriodInDays - BlockedUpdates - BlockedClassifications - BlockedProducts If no property named UpdateDeferralPeriodInDays is specified, then a 0 is stored as the default value. If the property BlockedClassifications is not specified explicitly, the values ["Upgrades", "Drivers"] (in JSON, similarly in XML) are used as default. If the property BlockedClassifications is specified, the value ["Upgrades"] must be included.	2021 R1
PUT	Id=<id>	Updates the MicrosoftUpdateProfile identified by the given ID with the properties provided in the body of the request. Omitted properties are considered null or default for the respective property. For default values see also property descriptions. If the property BlockedClassifications is specified, the value ["Upgrades"] must be included.	2021 R1
PATCH	Id=<id>	Updates the MicrosoftUpdateProfile identified by the given ID with the properties provided in the body of the request. Omitted properties will be considered unchanged.	2021 R1

		If the property BlockedClassifications is specified, the value ["Upgrades"] must be included.	
DELETE	Id=<id>	Deletes a MicrosoftUpdateProfile object by the given ID. The request will fail if the MicrosoftUpdateProfile is still assigned to at least one endpoint and the force parameter has not been set.	2021 R1
	Force=<true/false>	Optional for DELETE method with Id parameter: If "true", the MicrosoftUpdateProfile will be deleted even if it is still assigned to at least one endpoint. If not specified this parameter is taken as "false" by default.	2021 R1

Examples:

- GET-Request:
<https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftUpdateProfiles?ID=A330F59A-F756-4D30-87D5-34D54A45E0DC>

Result:

```
{
  "Id": "A330F59A-F756-4D30-87D5-34D54A45E0DC",
  "Name": "A meaningful name",
  "Comment": "This comment can help explain the reasoning behind the group's settings",
  "UpdateDeferralPeriodInDays": 13,
  "BlockedUpdates": [
    "17A8E018-C67E-4635-902E-B747CEC562D1",
    "CA3BB521-A8EA-4E26-A563-2AD6E3108B9A"
  ],
  "BlockedClassifications": [
    "Feature Packs",
    "Tools",
    "Upgrades",
  ],
  "BlockedProducts": [
    "Silverlight"
  ]
}
```

- DELETE-Request:
<https://<bmsserver>:<port>/v1.0/MicrosoftUpdateProfiles?id=CF0216FD-974B-4736-8413-3B5B1B229F68>

Result: No Content

5.40 Controller MicrosoftUpdateManagementSettings

The MicrosoftUpdateManagementSettings controller provides functionality to read and modify the Microsoft Update Management module settings.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftUpdateManagementSettings>

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of MicrosoftUpdateManagementSetting objects with the corresponding values	2021 R1
GET	Key=<key>	Returns the setting that matches the provided key	2021 R1
PUT	None	Modifies the setting, that was provided in body	2021 R1

Examples:

- PUT-Request:

<https://localhost:443/bconnect/v1.1/MicrosoftUpdateManagementSettings.xml>

Body (xml format):

```
<MicrosoftUpdateManagementSetting xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BConnect.DataModel">
  <Key>InventoryValidityPeriod</Key>
  <Value>90</Value>
</MicrosoftUpdateManagementSetting>
```

Result:

```
<MicrosoftUpdateManagementSetting xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
  xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BConnect.DataModel">
  <Key>InventoryValidityPeriod</Key>
  <Value>90</Value>
</MicrosoftUpdateManagementSetting>
```

5.41 Controller MicrosoftDefenderThreats

The MicrosoftDefenderThreats controller provides the functionality to read threats which were detected by Microsoft Defender Antivirus on Windows endpoints.

To request *MicrosoftDefenderThreats* object data the URL must contain the bConnect version information.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftDefenderThreats>

Method	URL parameters	Description	Since bMS
GET	None	Returns a list of all existing Microsoft Defender Threats (Check properties of MicrosoftDefenderThreats for more information).	2021 R1
GET	Id=<id>	Returns the Microsoft Defender Threat that matches the provided ID.	2021 R1
GET	EndpointId=<endpoint id>	Returns the Microsoft Defender Threats of the specific endpoint.	2021 R1
GET	GroupId=<group id>	Returns the Microsoft Defender Threats of the specific logical group.	2021 R1
	IncludeSubfolders=<true/false>	Optional for GET method with GroupId parameter: If "true", threats are returned for all windows devices within the corresponding group and their subgroups. If not specified this parameter is taken as "false" by default.	2021 R1

Examples:

- GET-Request:
<https://<bmsserver>:<port>/bConnect/V1.1/MicrosoftDefenderThreats?ID=AAFF8188-A10A-436C-9AEB-92D88BB31CCA>

Result:

```
{
  "Id": "2803FF79-48E4-4EE5-ADAB-A3630E242C36",
  "Name": "Virus:DOS/Test_File",
  "IsActive": false,
  "Severity": "Severe",
  "Category": "Virus",
  "ThreatType": "KnownGood",
  "DomainUser": "TESTDOMAIN\\user1",
  "ProcessName": "C:\\Windows\\System32\\test.exe",
  "FileNames": "file:_C:\\temp\\test.txt",
  "ActionSuccess": true,
  "ExecutionStatus": "AllowedExecutionStatus",
  "ThreatStatus": "Quarantined",
  "DetectionSource": "RealTime",
  "CleaningAction": "Quarantine",
  "AdditionalActions": "28",
  "DetectionTime": "2020-11-30T12:59:28.376Z",
```

```

"RemediationTime": "2020-11-30T12:59:36.294Z",
"LastStatusChangedTime": "2020-11-30T12:59:36.294Z",
"EndpointId": "F52D21F0-89F0-4295-B902-64230B593967",
"EndpointName": "DeviceName"
}

```

5.42 Controller ModernEnrollment

The ModernEnrollment controller provides the functionality to activate Mac endpoints for native enrollment. This can only be performed on Mac endpoints whose ManagementState is either 'unmanaged' or 'managed' with the MacEnrollmentType 'SSH'.

URL: https://<bmsserver>:<port>/bConnect/V1.1/ModernEnrollment

Method	URL parameters	Description	Since bMS
POST	None	Enables the endpoint (currently Mac endpoints only) with the given Id for native enrollment. Mandatory properties: - EndpointId Optional properties: - SendEnrollmentMail - EnrollmentMailAddress - EmailLanguageId If there is no email address given with the 'EnrollmentMailAddress' property and 'SendEnrollmentMail' is set to <i>true</i>, the email address of the linked ActiveDirectory user of the endpoint will be used. The EmailLanguageId holds the identifier of the email template, which will be used for the email enrollment message sent to the recipient. By default "de-DE" and "en-US" are available. If this property is not set, the Email template with the Id "en-US" will be used. Returns an ModernEnrollmentActivationResult object.	2021 R1

Examples:

- POST-Request:
https://localhost:443/bconnect/v1.1/ModernEnrollment.xml

Body (xml format):

```
<ModernEnrollmentSettings xmlns:i="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BC
onnect.DataModel">
  <EmailLanguageId>en-US</EmailLanguageId>
  <EnrollmentMailAddress>john.doe@bartoso.com</EnrollmentMailAddress>
  <EndpointId>499F69F4-11C8-49DB-91D8-F6148B70FE9C</EndpointId>
  <SendEnrollmentMail>true</SendEnrollmentMail>
</ModernEnrollmentSettings>
```

Result:

```
<ModernEnrollmentActivationResult xmlns:i="http://www.w3.org/2001/XMLSchema-
instance"
xmlns="http://schemas.datacontract.org/2004/07/Baramundi.Bms.Server.Connector.Rest.BC
onnect.DataModel">
  <EnrollmentTokenValidUntilUTC>31.01.2021 13:43:29</EnrollmentTokenValidUntilUTC>
  <EnrollmentUrl>https://localhost:443/ios-mdm/enroll/rfcdvkhikndbz</EnrollmentUrl>
  <ErrorSendingEmail>false</ErrorSendingEmail>
  <EndpointId>499F69F4-11C8-49DB-91D8-F6148B70FE9C</EndpointId>
</ModernEnrollmentActivationResult>
```

5.43 Controller IpNetworks

The IpNetworks controller provides the functionality to read, update and delete Ip Networks.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/IpNetworks>

Method	URL parameters	Description	Since bMS
GET	None	Returns all existing Ip Networks as a list of <i>IpNetwork</i> objects. (Check properties of IpNetworks for more information).	2021 R1
GET	Id=<id>	Returns the IpNetwork that matches the provided ID.	2021 R1
GET	Name=<name>	Returns the IpNetwork that matches the provided name.	2021 R1
POST	None (Mandatory and optional properties must be specified in the appropriate format in the HTTP body. In case of XML, the elements must be sorted alphabetically and the appropriate namespaces must be appended as attributes to the root element.)	Creates new IpNetwork objects according to the specified data. Mandatory properties: - Name - Scopes Optional properties: - BandwidthMode - Dips - WolRelay - MaxBandwidthKbits - DuplicateWolToThisNetwork - VLSM The parameter <i>BandWithMode</i> can be specified by a string value. Possible values are: "AllowAll" "BlockAll"	2021 R1

		• "UseBandwidth"	
PATCH	Id=<id>	Updates the IpNetwork identified by the given ID with the properties provided in the body of the request. Omitted properties will be considered unchanged.	2021 R1
DELTE	Id=<id>	Deletes an IpNetwork object by the given ID.	2021 R1

Examples:

- POST-Request:
https://localhost:443/bconnect/v1.0/IpNetworks.json

Body (json format):

```
{
  "Name": "name",
  "Dips": "dip",
  "DuplicateWolToThisNetwork": "False",
  "BandwidthMode": "AllowAll",
  "MaxBandwidthKbits": "100000000",
  "WolRelay": "wol",
  "Scopes": [
    {
      "NetworkAddress": "10.10.10.0",
      "SubnetMask": "255.255.255.0"
    }
  ]
}
```

Result:

```
{
  "Id": "FC092C22-02AD-493C-AECB-45BDBECA992B",
  "Name": "name",
  "Dips": "dip",
  "WolRelay": "wol",
  "MaxBandwidthKbits": 100000000,
  "BandwidthMode": "AllowAll",
  "DuplicateWolToThisNetwork": "False",
  "Scopes": [
    {
      "NetworkAddress": "10.10.10.0",
      "SubnetMask": "255.255.255.0"
    }
  ],
  "VLSM": "True"
}
```

5.44 Controller BfcxIntegrity

The BfcxIntegrity controller provides functions for reading, declaring, changing and deleting the checksum of a BFCRX installation service.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/BfcxIntegrity>

Method	URL parameters	Description	Since bMS
GET	None	Returns a SHA-256 checksum of a BFCRX installation service in the form of a lowercase hexadecimal string	2022 R1
PUT	None	Declares or changes the checksum of a BFCRX installation service, that was provided in body	2022 R1
DELETE	None	Deletes a declared checksum of a BFCRX installation service	2022 R1

Examples:

- PUT-Request:
<https://<bmsserver>:<port>/bConnect/V1.1/BfcrxIntegrity>
 Body (json format):

```
{
  "Hash": "8bbbcaff537e3a5e24fb0b2301c9bc600941492c6ff8b0d3e022231ef1be80c6"
}
```

Result:

```
{
  "Hash": "8bbbcaff537e3a5e24fb0b2301c9bc600941492c6ff8b0d3e022231ef1be80c6"
}
```

5.45 Controller ManagementAgentSetupIntegrity

The ManagementAgentSetupIntegrity Controller provides functions for reading, declaring, changing and deleting the checksums of bma installation sources.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/ManagementAgentSetupIntegrity>

Method	URL parameters	Description	Since bMS
GET	None	Returns PinnedBmaSetupFilesInformation with the corresponding values	2022 R1
PUT	None	Declares or changes PinnedBmaSetupFilesInformation with the corresponding values	2022 R1
DELETE	None	Deletes PinnedBmaSetupFilesInformation with the corresponding values	2022 R1

Examples:

- PUT-Request:
<https://<bmsserver>:<port>/bConnect/V1.0/ManagementAgentSetupIntegrity>
 Body (json format):


```
{
  "PinnedBmaSetupFiles":
  [
    {"RelativeFilePath":"ManagementAgent_setup.exe",
     "Hash":"8f7c95ccbd7fb1c70b0eef94ffe2669a8761d88d233961add81ad9baaeda6131"},
    {"RelativeFilePath":"Meine_Muster_Setup_Datei.dll",
     "Hash":"7fc7c94458c521607db3fdad420b63f4f2a468a80cc51ca76d288d9690c991e3"}
  ]
}
```

Result:

```
{
  "PinnedBmaSetupFiles":
  [
    {"RelativeFilePath":"ManagementAgent_setup.exe",
     "Hash":"8f7c95ccbd7fb1c70b0eef94ffe2669a8761d88d233961add81ad9baaeda6131"},
    {"RelativeFilePath":"Meine_Muster_Setup_Datei.dll",
     "Hash":"7fc7c94458c521607db3fdad420b63f4f2a468a80cc51ca76d288d9690c991e3"}
  ]
}
```

5.46 Controller EndpointSSHInfo

The EndpointSSHInfo controller provides functionality to read and update SSH information in the form of [EndpointSSHInfo](#) objects. Only Endpoints of type NetworkEndpoint are supported.

URL: <https://<bmsserver>:<port>/bConnect/V1.1/EndpointSSHInfo>

Method	URL parameters	Description	Since bMS
GET	EndpointId=<endpoint id>	Returns the SSH information corresponding to the Endpoint.	2022 R1
PATCH	EndpointId=<endpoint id>	Optional properties: - Port - HostKeys	2022 R1

Examples:

- GET-Request:
<https://bmsserver.customer.net/bConnect/v1.1/EndpointSSHInfo?EndpointId=DF59E6C5-7103-4DA8-ACBF-26D29D304301>

Result:

```
{
  "EndpointId": "DF59E6C5-7103-4DA8-ACBF-26D29D304301",
  "SshVersion": "SSH-2.0-OpenSSH_8.6",
  "Port": 22,
  "HostKeys": [
    {
      "KeyType": "ssh-rsa",
      "KeyData": "AAAAB3NzaC...."
    }
  ]
}
```

```
]
}
```

6 Simple integration samples

6.1 Windows PowerShell

Simple PowerShell script to request available bMS org units over bConnect.

For this sample the Windows PowerShell version 4.0 is required.

```
# Simple script to request available bMS org units over bConnect
# ! Windows PowerShell 4.0 required !

# credentials
$username = "<domain>\<user>"
$password = "<password>" | ConvertTo-SecureString -asPlainText -Force
$creds = New-Object System.Management.Automation.PSCredential($username,$password)

# configuration
$server      = "<baramundi server>" # baramundi Management Server as specified in the
bound certificate
$version     = "v1.1"              # current version of bConnect
$outputformat = "json"             # request the data in json format
$controller  = "orgunits"          # an existing controller
$attributes  = ""                  # starting with '?'

$url = "https://" + $server + "/bConnect/" + $version + "/" + $controller + "." +
$outputformat + $attributes

# request
$response = Invoke-WebRequest -Uri $url -Credential $creds

# HTTP status codes: 200=OK; 400=bad request; 403=unauthorized; 500=internal server error;
$stat = $response.statuscode;
write-host "Status:" $stat "$([char]10)"

# de-serialize response data and evaluate and output data
$jsonobjects = $response.Content | ConvertFrom-Json
foreach($line in $jsonobjects)
{
    write-host "Id:" $line.Id
    write-host "Name:" $line.Name
    write-host "GuidParent:" $line.GuidParent "$([char]10)"
}
```

6.2 Visual Basic Script (VBS)

Simple Visual Basic script to request available bMS org units over bConnect.

```
Dim httpObj
Set httpObj = CreateObject("MSXML2.ServerXMLHTTP")

'credentials
user      = "<user>"          'user authorized in baramundi Management Suite
password  = "<password>"      'password for the user above
'configuration
server    = "<baramundi server>" 'baramundi Management Server as specified in the bound
certificate
version   = "v1.1"            'current version of bConnect
outputformat = "xml"          'request the data in xml or json format
controller = "orgunits"       'an existing controller
attributes = ""               'starting with '?'

url = "https://" & server & "/bConnect/" & version & "/" & controller & "." & outputformat & attributes

'request
httpObj.Open "GET", url, False, user, password
httpObj.setOption 2, 13056 'suppress cert warning
httpObj.setRequestHeader "pragma", "no-cache" 'avoid caching
httpObj.setRequestHeader "Cache-Control", "no-cache, no-store" 'avoid caching
httpObj.send

'HTTP status codes: 200=OK; 400=bad request; 403=unauthorized; 500=internal server error;
plot = "HTTPS response status code: " & httpObj.Status & vbCrLf & vbCrLf

'check response data only if request was successful
If 200 = httpObj.Status then
    'de-serialize response data to xml object
    Dim objXML
    set objXML = CreateObject("Microsoft.XMLDOM")
    objXML.async = "false"
    objXML.loadXML(httpObj.responsetext)
    'evaluate and output data
    Dim nodes
    Set nodes = objXML.documentElement.selectNodes("//OrgUnit")
    For Each node In nodes
        plot = plot & "OrgUnit:" & vbCrLf
        plot = plot & "Id = " & node.SelectSingleNode("./Id").text & vbCrLf
        plot = plot & "Name = " & node.SelectSingleNode("./Name").text &
vbCrLf
        plot = plot & "GuidParent = " &
node.SelectSingleNode("./GuidParent").text & vbCrLf
        plot = plot & vbCrLf
    Next
End If

Set httpObj = Nothing
wscript.echo plot
```

6.3 C#

Simple sample in C# to request available bMS org units over bConnect. Used with .NET Framework 4.5.

```
namespace bConnectSample
{
    using System;
    using System.IO;
    using System.Net;
    using Newtonsoft.Json;

    internal class Program
    {
        public static bool AcceptAllCertifications(object sender,
            System.Security.Cryptography.X509Certificates.X509Certificate certification,
            System.Security.Cryptography.X509Certificates.X509Chain chain,
            System.Net.Security.SslPolicyErrors sslPolicyErrors)
        {
            return true;    // check here for valid server certificate
        }

        private static void Main(string[] args)
        {
            ICredentials creds = new NetworkCredential()    // credentials
            {
                UserName = "<user>",    // user authorized in baramundi Management Suite
                Password = "<password>"    // password for the user above
            };

            // configuration
            string server = "<baramundi server>";    // baramundi Management Server
            string version = "v1.1";    // current version of bConnect
            string outputformat = "json";    // request the data in xml format
            string controller = "orgunits";    // an existing controller
            string attribtues = "";    // starting with '?'

            string url = "https://" + server + "/bConnect/" + version + "/" + controller + "."
+ outputformat + attribtues;

            // Create a request for the URL.
            WebRequest request = WebRequest.Create(url);
            request.Method = "GET";
            request.Credentials = creds;
            ServicePointManager.ServerCertificateValidationCallback = new
System.Net.Security.RemoteCertificateValidationCallback(AcceptAllCertifications);

            try
            {
                HttpWebResponse response = (HttpWebResponse)request.GetResponse();
                StreamReader streamReader = new StreamReader(response.GetResponseStream());
                var results = JsonConvert.DeserializeObject<dynamic>(streamReader.ReadToEnd());
            }
        }
    }
}
```

```
        foreach (var orgUnit in results)
        {
            Console.WriteLine("Id:\t\t{0}", orgUnit.Id);
            Console.WriteLine("Name:\t\t{0}", orgUnit.Name);
            Console.WriteLine("GuidParent:\t{0}\n", orgUnit.GuidParent);
        }

        streamReader.Close();
        response.Close();
    }
    catch (WebException ex)
    {
        Console.WriteLine(ex.Message);
    }

    Console.Read();
}
}
```

7 Properties of object types

This chapter provides information about the properties of the objects used with bConnect. In the column Access of the specific object type for each property the access right for object creation=C, reading=R and updating=U is stated, depending on the actions the corresponding controller supports.

7.1 Version

Property	Data type	Access	Description
SupportedVersions	List of String (*)	R	List of supported versions
CurrentVersion	String (*)	R	Current version of bConnect

(*) must not be null for reading access

7.2 Info

Property	Data type	Access	Description
bConnectVersion	String (*)	R	Current version of bConnect
Description	String (*)	R	Simple description of bConnect
Company	String (*)	R	baramundi Software GmbH
Copyright	String (*)	R	Copyright ...
bMSVersion	String (*)	R	Current version of the bMS
UserContext	String (*)	R	Context this request is processed in

(*) must not be null for reading access

7.3 SearchResult

Property	Data type	Access	Description
Id	String (*)	R	Unique ID of a found object. Use this ID to load the whole object
Name	String (*)	R	Name of an object found
Type	Int (*)	R	Type of an object found (see coding below)
AdditionalInfo	String	R	Additional data of an object found
Deactivated	Bool (**)	R	For endpoints only: The endpoint is deactivated (Windows) or not managed (mobile endpoints, Macs).

(*) must not be null for reading access

(**) applies for endpoints only

Codings:

[Type]

0 Unknown	
1 WindowsEndpoint	endpoint of type WindowsEndpoint
2 AndroidEndpoint	BmsNetEndpoint
3 iOSEndpoint	BmsNetEndpoint
4 MacEndpoint	BmsNetEndpoint
6 WindowsJob	for endpoints of type WindowsEndpoint only
7 BmsNetJob	for endpoints of type BmsNetEndpoint only
8 OrgUnit	different nodes (including Logical Groups)
9 DynamicGroup	for endpoints of type WindowsEndpoint only
10 StaticGroup	for endpoints of all endpoint types
11 Application	for endpoints of type WindowsEndpoint only
12 App	for endpoints of type BmsNetEndpoint only
16 NetworkEndpoint	endpoint of type NetworkEndpoint
17 AD object	user or user group

7.4 OrgUnit

Property	Data type	Access	Description
Id	String	R	ID of an org unit
Comment	String	R/C/U	Freely editable text field
Extension	Extension (*)	R/C/U	Extended data for org units of node <i>Logical Groups</i>
GuidParent DEPRECATED (use ParentId instead)	String	R	ID of a superior org unit
HierarchyPath	String	R	Path of an org unit in the organizational hierarchy
Name	String	R/C/U	Name of an org unit
ParentId	String	R/C/U	ID of a superior org unit

(*) applies for org units of node *Logical Groups* only

7.4.1 Extension

Property	Data type	Access	Description
DIP	String	R/C/U	DIP list, separated by semi-colon
Domain	String	R/C/U	Windows domain name
LocalAdminPassword	String	R/C/U	Password for a local administrator (must be encrypted with baramundi Cryptor)
EnabledDHCP	Bool	R/C/U	If set the network settings will be provided by the dhcp server
SubnetMask	String	R/C/U	If not EnabledDHCP: Network mask
DefaultGateway	String	R/C/U	If not EnabledDHCP: Standard gateway
DnsServer	String	R/C/U	If not EnabledDHCP: DNS 1
DnsServer2	String	R/C/U	If not EnabledDHCP: DNS 2
DnsDomain	String	R/C/U	If not EnabledDHCP: DNS domain
WinsServer	String	R/C/U	If not EnabledDHCP: WINS 1
WinsServer2	String	R/C/U	If not EnabledDHCP: WINS 2
AutoInstallJobs	List of String	R/C/U	List of job IDs for auto installation (see object type Job)
HardwareProfiles	List of String	R/C/U	List of hardware profile IDs (see object type HardwareProfile)
InheritAutoInstallJobs	Bool	R/C/U	If set, the auto install jobs of parent org unit will be inherited (see object type Job)
RequestableJobs	List of String	R/C/U	List of job ids (for Kiosk; see object type Job)

7.5 DynamicGroup

Property	Data type	Access	Description
Id	String	R	ID of a dynamic group
Comment	String	R/C/U	Freely editable text field
HierarchyPath	String	R	Path of a dynamic group in the organizational hierarchy
Name	String	R/C/U	Name of a dynamic group
ParentId	String	R/C/U	ID of a superior org unit
Statement	String	R/C/U	SQL statement of a dynamic group (only WHERE clause can be defined; target is always the table "machine")

7.6 UniversalDynamicGroup

Property	Data type	Access	Description
Id	String	R	ID of a universal dynamic group
Comment	String	R	Freely editable text field
HierarchyPath	String	R	Path of a universal dynamic group in the organizational hierarchy
DisplayName	String	R	Display Name of a universal dynamic group
Name	String	R	Name of a universal dynamic group
ParentId	String	R	ID of a superior org unit
IsArgusSynced	Bool	R	If <i>true</i> , a universal dynamic group is synchronized to Argus Cockpit

7.7 StaticGroup

Property	Data type	Access	Description
Id	String	R	ID of a static group
Comment	String	R/C/U	Freely editable text field
EndpointIds	List of String	R/C/U	List of endpoint IDs linked to the static group
HierarchyPath	String	R	Path of a static group in the organizational hierarchy
Name	String	R/C/U	Name of a static group
ParentId	String	R/C/U	ID of a superior org unit

7.8 Endpoint

For bMS 2014 R2 the *Endpoint* object has been extended for mobile devices (Android, iOS) and Mac devices. Hence the property *Type* specifies if the endpoint is of type *WindowsEndpoint*, *AndroidEndpoint*, *iOSEndpoint*, *MacEndpoint* or *NetworkEndpoint*.

Property	Data type	Accesses	Description
Id	String (*)	R	ID of an endpoint.
Type	Int (*)	R/C	Type of an endpoint (see coding below)
GuidGroup DEPRECATED (use GuidOrgUnit instead)	String	R/C	ID of <i>Logical Group</i> , a client should be managed with
DisplayName	String (*)	R/C/U	Display name of an endpoint.
HostName	String	R/C/U	Host name of an endpoint.
Domain	String	R/C/U	LAN manager domain an endpoint should be in, after an operating system installation
PrimaryMAC	String	R/C/U	Primary MAC-address of an endpoint. Supported format: MM:MM:MM:MM:MM:MM Each «M» stands for one hexadecimal number (0 to F)
MACList	String (**)	R	List of all MAC-addresses of an endpoint
LogicalMAC	String (**)	R	Logical MAC-address of an endpoint
LAAList DEPRECATED	String (**)	R	List of locally administrated MAC-addresses
PrimaryIP	String (**)	R/C/U	Primary IP-address of an endpoint
PrimarySubnetMask	String (**)	R/C/U	Primary subnet mask of an endpoint
IPList	String (**)	R	List of all IP-addresses of an endpoint
GuidHardwareProfile	String (**)	R/C/U	Hardware profile's ID of an endpoint
OperatingSystem	String	R	Name of an installed OS
Options	UInt (**)	R/C/U	Options of an endpoint (see coding below)
Comments	String	R/C/U	Freely editable text field
PrimaryUser	String	R/C/U	Primary user of an endpoint
ClientAgentState	Int (**)	R	State of the agent on an endpoint (see coding below)
Activity	String	R	Current activity of the client agent
LastChange	DateTime (**)	R	Date and time of last change
LastSeen	DateTime	R	Date and time of last successful communication with the client agent
OSVersionString	String	R	Full name of the installed OS
OSVersionMajor	Int (**)	R	Major version of the installed OS
OSVersionMinor	Int (**)	R	Minor version of the installed OS
OSVersionBuild	Int (**)	R	Build number of the installed OS
LastUser	String	R	Last logged on user
IEVersionString	String (**)	R	Version of the installed Internet Explorer.
CPUDescription	String (**)	R	Description of the CPU.
CPUType	String (**)	R	Information about the CPU type.

CPUspeed	Int (**)	R	Information about the CPU speed in MHz.
TotalMemory	Int (**)	R	Information about the installed memory in MB
DriveCSize DEPRECATED	Int (**)	R	Size of C: drive
DriveCFree DEPRECATED	Int (**)	R	Free space on C: drive
DriveDSize DEPRECATED	Int (**)	R	Size of D: drive.
DriveDFree DEPRECATED	Int (**)	R	Free space on D: drive
DriveESize DEPRECATED	Int (**)	R	Size of E: drive
DriveEFree DEPRECATED	Int (**)	R	Free space on E: drive
GuidOrgUnit	String (*)	R/C/U	ID of a parent org unit
CustomStateType	Int (**)	R/U	Freely editable user defined state type
CustomStateTime	DateTime (**)	R	Time of the last change of a freely editable user defined state type
CustomStateText	String (**)	R/U	Freely editable user defined state type
BMSServer DEPRECATED	String (**)	R	Responsible baramundi Management Server
BootCounter DEPRECATED	Int (**)	R	Client reboot counter
ClientAgentVersion	String (**)	R	Client agent version
GuidJobPreinstallApp DEPRECATED	String (**)	R	ID of the configured pre-install application
GuidJobPostinstallApp DEPRECATED	String (**)	R	ID of the configured post-install application
Priority DEPRECATED	Int (**)	R	Used priority
GuidBootEnvironment	String (**)	R/C/U	If set, the giving boot environment will boot during the next start. For booting without PXE, this value must be left empty.
LocaleId	Int (**)	R	Localization ID of the client OS
Architecture	String (**)	R	Clients CPU architecture
CurrentUserSID	String	R	SID of the current user
WOLSent DEPRECATED	DateTime (**)	R	Date and time WOL signal was sent last time
LastBoot	DateTime (**)	R	Date and time of the clients last boot event
EnergyScheme	String (**)	R	Name of the active energy scheme
EnergySchemeId	String (**)	R	ID of the current energy scheme
OSVersionSPMajor DEPRECATED (use OSVersionString instead)	Int (**)	R	Service pack level of the installed OS
CPUCountPhysical	Int (**)	R	Number of physical CPUs
CPUCountLogical	Int (**)	R	Number of logical Cores
CPUCountTotalCores	Int (**)	R	Number of physical CPU cores
Manufacturer	String	R	Manufacturer of the device
ModelName	String	R	Model name of the device
ManagementState	Int (***)	R	Management state of the device (see coding below)
UniqueDeviceId	String (***)	R	Unique device ID
UserCategory	(***)	R/U	Free text category
Owner	Int (***)	R/C/U	Owner type of the device (see coding below)
ComplianceState	Int (***)	R	Compliance state of an endpoint (see coding below)

ComplianceCheckCategory	Int (***)	R/C/U	Compliance category of the device (see coding below)
ComplianceCheckDisabledFrom	DateTime (***)	R/U	Date and time the compliance check is disabled
ComplianceCheckDisabledUntil	DateTime (***)	R/U	Date and time the compliance check is re-enabled
SerialNumber	String	R/C	Serial number of the device
PublicKey	String (**)	R/U	Public key of the client certificate
ExtendedInternetMode	Bool (**)	R/C/U	If set Extended Internet Mode is enabled
LastChannel	String (**)	R	Type of the last channel used for communication (see coding below)
Mode	String (**)	R/C/U	Type of the currently configured mode (see coding below)
InstalledSoftware	List of < Software >	R	List of the software installed with the baramundi Management Suite on the client
OSVersionPatchLevel	String (**)	R	Patch level of the operating system (Revision ID) Applies for Windows 10 systems only
OSReleaseId	String (**)	R	Distinguishable ID for Windows 10 systems (e.g. "1507", "1511", ...) Applies for Windows 10 systems only
OSServiceBranch DEPRECATED	String (**)	R	The current branch the Windows 10 system is connected to (e.g. "LTSP", "CBB", "CB") Applies for Windows 10 systems only
SNMPData	SNMPDeviceData	R	SNMP data of the device
TPMData	TPMData (**)	R	TPM inventory data
IsSecureBootEnabled	Bool (**)	R	Secure boot enabled on this client
StorageMedia	List of < StorageMedium >	R	Inventoried Storages
IndustrialData	IndustrialData	R/C/U	Additional data for Industrial Endpoints
AndroidEnterpriseProfileType	Int (*****)	R/C	Type of android enterprise profile (see coding below)
VirusAndThreadProtectionStatus	String	R	The aggregation of all antivirus products for this computer (see coding below)
AutomaticUpdateStatus	String	R	The automatic update settings for this computer (see coding below)
FirewallAndNetworkProtectionStatus	String	R	The aggregation of all firewalls for this computer (see coding below)
AppAndBrowserControlStatus	String	R	The settings that restrict the access of web sites in each of the Internet zones for this computer (see coding below)
WindowsSecurityServiceStatus	String	R	The running state of the WSC service on this computer (see coding below)
UserAccountControlStatus	String	R	The User Account Control (UAC) settings for this computer (see coding below)

SecurityCenterUser	String	R	Last logged on user (except installation user) (see coding below)
AppleManagementMode	Int (****)	R/C	Type of iOS Management (see coding below)
ManagedAppId	String	R/C	The managed AppId
HasAppleAppUpdates	Bool (****)		Flag to check if the apple device has app updates which can be installed
LastUpdateInventoryDate	DateTime (**)	R	Date and time of the last executed update inventory
UpdateInventorySource	String (**)	R	Update metadata source of the last inventory (see coding below)
MissingCriticalUpdatesCount	Int (**)	R	Number of missing critical (defined by BMS) updates
MissingSecurityUpdatesCount	Int (**)	R	Number of missing security (defined by BMS) updates
MissingOtherUpdatesCount	Int (**)	R	Number of missing updates, which are neither critical nor security updates
DeferredUpdatesCount	Int (**)	R	Number of deferred updates
BlockedUpdatesCount	Int (**)	R	Number of blocked updates
FeatureUpdatesAvailable	Bool (**)	R	Indicates that some feature updates are available for installation
LastSuccessfulUpdateDate	DateTime (**)	R	Date and time of the last successfully executed update deploy job step (only applies to update job steps controlling the Windows Update Agent)
LastSuccessfulUpdateSource	String (**)	R	Update metadata source of the last successful update deploy job step (see coding below)
BitLockerNetworkUnlockStatus	String (**)	R	Status of Network Unlock Feature on Client. (see coding below)
DedicatedDeviceModeEnabled	Bool (***)	R	Enabled if the device is a Dedicated Device (Android Enterprise) or has Dedicated Device Mode enabled (iOS).
EmailRecipient	String (***)	C	The email address for the recipient of the enrollment email.
EmailLanguageId	String (***)	C	The Identifier of the email template, which will be used for the email enrollment message sent to the Recipient email. Default available templates are "de-DE" and "en-US".
TargetReleaseVersion	String	R	Version string of the targeted Feature Update version.
UpdateDownloadMode	String	R	Windows Update download mode (see coding below)
MicrosoftUpdateProfile	String (**)	R/C/U	Assigned Microsoft Update Profile name
GuidMicrosoftUpdateProfile	String (**)	R/C/U	Assigned Microsoft Update Profile id
UpdateState	String (**)	R	Update status of a client (see coding below). If an update inventory has not yet been performed on the client, this property is null

IsBitLockerStartupPinEnabled	Bool (**)	R	BitLocker Startup PIN enabled on this client
IsBitLockerStartupUsbKeyEnabled	Bool (**)	R	BitLocker Startup USB Key enabled on this client
MicrosoftDefenderData	MicrosoftDefenderData	R	Microsoft Defender Antivirus attributes
MacEnrollmentType	String	R	MacOS enrollment type, values are - Unenrolled - SSH - SSHAndNative - Native
DoNotDisturbUntil	DateTime (**)	R	Date and time (UTC) indicating the end of do not disturb
DoNotDisturbActive	Bool (**)	R	Do not disturb is currently active on this client
WindowsModernManagementData	WindowsModernManagementData	R	Data concerning the Modern Management of Windows endpoints
ForceMobileDataOnEnrollment	Bool (*****)	R/C	Forces the device to use mobile data connection during initial setup (QR-Code Setting)

(*) must not be null for reading access
(**) applies for WindowsEndpoint only
(***) applies for BmsNetEndpoint only
(****) applies for AppleEndpoint only
(*****) applies for AndroidEndpoint only

Codings:

[Mode]

LAN LAN only
Internet Internet only
Dynamic Device selects dynamically the appropriate channel

[LastChannel]

LAN LAN channel used by device in LAN mode
Internet Internet channel used by device in Internet mode
AutoLAN LAN channel selected automatically by device in Dynamic mode
AutoInternet Internet channel selected automatically by device in Dynamic mode

[VirusAndThreadProtectionStatus]

[AutomaticUpdateStatus]

[AppAndBrowserControlStatus]

[WindowsSecurityServiceStatus]

[UserAccountControlStatus]

[SecurityCenterUser]

Unknown The status of the security provider could not be determined.
Good The status of the security provider category is good and does not need user attention.
NotMonitored The status of the security provider category is not monitored by WSC.
Poor The status of the security provider category is poor and the computer may be at risk.
Snooze The security provider category is in snooze state. Snooze indicates that WSC is not actively protecting the computer.

[Type]

- 0 Unknown
- 1 WindowsEndpoint
- 2 AndroidEndpoint
- 3 iOSEndpoint
- 4 MacEndpoint
- 16 NetworkEndpoint
- 18 IndustrialEndpoint

[ClientAgentState]

- 1 Unchanged
- 0 Unknown
- 1 Not Installed
- 3 Running
- 4 Rebooting

[Options]

- 0x00000001 Admits an OS installation
- 0x00000002 Inherits auto installation
- Bit 3-4 *PrimaryUserUpdateOptions* (see below)
- Bit 5-6 *UserJobOptions* (see below)
- 0x00000100 Automatic Usage Tracking is active
- 0x00000200 Energy Management is active
- 0x80000000 Client is deactivated (read only flag)

[PrimaryUserUpdateOptions]

- 0x00000000 Primary user will be updated at the next announce (default).
- 0x00000004 Do not use the primary user.
- 0x00000008 Always update the primary user.
- 0x0000000C Never update the primary user.

[UserJobOptions]

- 0x00000000 Always execute user related jobs.
- 0x00000010 Never execute user related jobs.
- 0x00000030 Execute user related jobs if the primary user is logged in (default).

[ManagementState]

- 0 Unknown
- 1 Enrollable
- 2 Enrolling
- 3 Managed
- 4 Unmanaged

[Owner]

- 2 Unknown
- 0 Company
- 1 Private

[ComplianceState]

- 0 Unknown
- 1 Compliant
- 2 Not compliant, just a info
- 3 Not compliant, a warning
- 4 Not compliant, severe
- 5 Compliance inactive

[ComplianceCheckCategory]

- | | | |
|---|----------------------|--|
| 0 | active | Compliance is activated for the device |
| 1 | inactive | Compliance is deactivated for the device |
| 2 | temporarily inactive | Compliance is temporarily deactivated for the device |

[AndroidEnterpriseProfileType]

- 0 None (Android Legacy Device)
- 1 Fully managed device
- 2 Work Profile
- 4 Dedicated Device

[AppleManagementMode]

- 0 None (Will default to DeviceEnrollment for iOS Devices)
- 1 DeviceEnrollment
- 2 UserEnrollment

[BitLockerNetworkUnlockStatus]

- 0 Deactivated
BitLocker Network Unlock is not active, User needs to enter BitLocker PIN at startup.
- 1 OtherCertificate
BitLocker Network Unlock is active, but not configured for using with bMS. Installed BitLocker Network Unlock Certificate is unknown.
- 2 Activated
BitLocker Network Unlock is active, System boots without requesting PIN, if connected per LAN
- 3 NotSupported
BitLocker Network Unlock is not supported on device
- 4 Unknown
BitLockerNetworkUnlock status was not inventorised yet.

[LastSuccessfulUpdateSource, UpdateInventorySource]

WSUS
Windows Online
Microsoft Online

[UpdateState]

- 0 Out of date
The last inventory is further in the past than the configured tolerance value for update inventories
- 1 Noncompliant
The client has missing updates (which are neither blocked nor delayed) whose publication date is further in the past than the configured tolerance value for missing updates
- 2 Compliant
The last inventory is not as far in the past as the configured tolerance value for update inventories and/or all updates missing on the client are either blocked, delayed or their publication date is not as long ago as the configured tolerance value for missing updates

[UpdateDownloadMode]

NotSupported
 HttpOnly
 HttpBlendedWithPeeringAcrossPrivateGroup
 HttpBlendedWithPeeringBehindSameNat
 HttpBlendedWithInternetPeering
 SimpleDownloadModeNoPeering
 BypassMode
 Unknown

7.8.1 TPMData

Property	Data type	Access	Description
Version	String	R	TPM version
TPMStatus	Int	R	0 : Not available 1 : Deactivated 2 : Enabled 3 : Activated
IsOwned	Bool	R	Indicates whether the TPM has an owner

7.8.2 StorageMedium

Property	Data type	Access	Description
Index	Int	R	Disk index
Name	String	R	Disk name
ByteSize	ULong	R	Total size in bytes
BusType	Int	R	Bus type (see coding below)
PartitionStyle	Int	R	0 : Unknown 1 : MBR (Master boot record) 2 : GPT (GUID partition table)
StorageVolumes	List of < StorageVolumes >	R	Volumes on this disk

[BusType]

- 0 Unknown
- 1 SCSI
- 2 ATAPI
- 3 ATA
- 4 IEEE1394
- 5 SSA
- 6 FibreChannel
- 7 USB
- 8 RAID
- 9 iSCSI
- 10 SAS
- 11 SATA
- 12 SD
- 13 MMC
- 14 Virtual
- 15 FileBackedVirtual
- 16 StorageSpaces