HUNAN GREAT STEEL PIPE CO., LTD

ORIGINAL

STEEL INDUSTRIAL ZONE, TIANXIN DISTRICT NO 9 XIANGFU RD, CHNAGSHA HUNAN CHINA

MILL TEST CERTIFICATE(MTC) （EN 10204 3.1/ISO 10474 3.1B）

TO：PETROCON (PVT) LTD.

DESCRIPTION OF GOODS:FITTINGS

Date of issue: OCT.29.2020

Certificate No. 20404-CQ

ITEM	SPECIFICATION		QTY (PCS)	HEAT NO.	CHEMICAL COMPOSITION %											MECHANICAL PROPERTY			HARDNESS
					C	Mn	P	S	Si	Cr	Mo	V	Ni	Cu	CE	Y.S. Mpa	T.S. Mpa	EL. %	HB
5.1 i	Weld Neck Flanges, 150#, R.F as per ASME B 16.5, ASTM A-105.	Dia. 12" Sch-20	4	YF1601134	0.21	0.80	0.019	0.010	0.24	0.033	0.003	<0.01	0.009	0.07	0.28	295	555	25	/
5.1 ii		Dia. 12" Std. Wt.	42	YF1601134	0.21	0.80	0.019	0.010	0.24	0.033	0.002	<0.01	0.009	0.07	0.28	295	555	25	/
5.1 iii		Dia. 10" Sch-20	21	YF1601136	0.21	0.84	0.018	0.010	0.26	0.033	0.002	<0.01	0.008	0.08	0.28	290	525	25	/
5.1 iv		Dia. 10" Std. Wt.	20	YF1601136	0.21	0.84	0.018	0.010	0.26	0.033	0.002	<0.01	0.007	0.08	0.28	290	525	25	/
5.1 v		Dia. 8" Sch-20	19	YF1601136	0.21	0.84	0.018	0.010	0.26	0.033	0.003	<0.01	0.009	0.07	0.28	290	525	25	/
5.1 vi		Dia. 8" Std. Wt.	17	YF1601136	0.21	0.84	0.018	0.010	0.26	0.033	0.002	<0.01	0.009	0.07	0.28	290	525	25	/
5.1 vii		Dia. 6" Sch-40	209	YF1601241	0.20	0.84	0.020	0.011	0.25	0.033	0.002	<0.01	0.008	0.08	0.28	290	520	24	/
5.1 viii		Dia. 6" Std. Wt.	20	YF1601241	0.20	0.84	0.020	0.011	0.25	0.033	0.002	<0.01	0.007	0.08	0.28	290	520	24	/
5.1 x		Dia. 4"Sch-40	370	YF1601241	0.20	0.84	0.020	0.011	0.25	0.031	0.002	<0.01	0.009	0.07	0.28	290	520	24	/
5.1 xi		Dia. 4" Std. Wt.	30	YF1601241	0.20	0.84	0.020	0.011	0.25	0.031	0.002	<0.01	0.008	0.07	0.27	290	520	24	/
5.1 xii		Dia. 3" Sch-40	10	YF1601244	0.20	0.85	0.024	0.011	0.24	0.031	0.002	<0.01	0.008	0.07	0.27	290	520	25	/
5.1 xiii		Dia. 2" Sch-40	2	YF1601244	0.20	0.85	0.024	0.011	0.24	0.031	0.002	<0.01	0.008	0.08	0.27	290	520	25	/
5.2 i	Blind Flanges, 150#, R.F as per ASME B 16.5, ASTM A-105.	Dia. 12"	1	YF1601134	0.21	0.80	0.019	0.010	0.24	0.033	0.002	<0.01	0.007	0.08	0.28	295	555	25	/
5.2 iii		Dia. 8"	2	YF1601136	0.21	0.84	0.018	0.010	0.26	0.031	0.002	<0.01	0.009	0.07	0.28	290	525	25	/
5.2 iv		Dia. 6"	4	YF1601241	0.20	0.84	0.020	0.011	0.25	0.031	0.002	<0.01	0.008	0.07	0.27	290	520	24	/
5.2 v		Dia. 4" (ASTM A516-60)	31	18ND3776	0.19	0.89	0.016	0.010	0.30	0.031	0.002	<0.01	0.008	0.07	0.27	309	497	28	/
5.2 vi		Dia. 3" (ASTM A516-60)	1	18ND3776	0.19	0.89	0.016	0.010	0.30	0.031	0.002	<0.01	0.008	0.08	0.27	309	497	28	/

Surface & Marking	Dimensions	Heat Treatment	Nondestructive Test				
OK	OK	OK	RT ☐	UT ☐	MT ■	PT ☐	

WE HEREBY CERTIFY THE MATERIAL HERE IN DESCRIBED HAS BEEN MANUFACTURED, TESTED IN ACCORDANCE WITH ABOVE STANDARD AND SPECIFICATION SATISFIED THE REQUIREMENT.

SGS WITNESSED NOTED FOR INFORMATION ONLY SGS-CSTC STANDARDS TECHNICAL SERVICES (HK) LTD IND369

Stamp and signature

Q.A. Manager

DOCUMENTARY CREDIT NUMBER: TF20265194070001.APPLICANT NTN 0683878-2 AND H.S CODE NO. 7304.1900, 7307.9300 7307.9900, 7307.9200, 7307.9190, 8484.1010, 7318.1510